FoundationTTS: Text-to-Speech for ASR Customization with Generative Language Model

Ruiqing Xue*, Yanqing Liu*, Lei He, Xu Tan, Linquan Liu, Edward Lin, Sheng Zhao

Microsoft

Abstract

Neural text-to-speech (TTS) generally consists of cascaded architecture with separately optimized acoustic model and vocoder, or end-to-end architecture with continuous melspectrograms or self-extracted speech frames as the intermediate representations to bridge acoustic model and vocoder, which suffers from two limitations: 1) the continuous acoustic frames are hard to predict with phoneme only, and acoustic information like duration or pitch is also needed to solve the one-to-many problem, which is not easy to scale on large scale and noise datasets; 2) to achieve diverse speech output based on continuous speech features, complex VAE or flowbased models are usually required. In this paper, we propose FoundationTTS, a new speech synthesis system with a neural audio codec for discrete speech token extraction and waveform reconstruction and a large language model for discrete token generation from linguistic (phoneme) tokens. Specifically, 1) we propose a hierarchical codec network based on vectorquantized auto-encoders with adversarial training (VQ-GAN), which first extracts continuous frame-level speech representations with fine-grained codec, and extracts a discrete token from each continuous speech frame with coarse-grained codec; 2) we jointly optimize speech token, linguistic tokens, speaker token together with a large language model and predict the discrete speech tokens autoregressively. Experiments show that FoundationTTS achieves a MOS gain of +0.14 compared to the baseline system. In ASR customization tasks, our method achieves 7.09% and 10.35% WERR respectively over two strong customized ASR baselines.

Index Terms: Text to Speech, Large Language Model, VQ-GAN, Audio Codec

1. Introduction

Text-to-speech (TTS) can help reduce word error rate (WER) in the customization of automatic speech recognition (ASR) especially for low resource or out-of-vocabulary (OOV) scenarios by generating synthetic speech, and using the text and speech pairs to update the ASR models or using a spelling correction model with hypothesis decoded from TTS data [1, 2, 3, 4, 5, 6, 7, 8, 9]. However, compared to real speech in ASR training set, the adaptation performance with synthesized speech is inferior due to a lack of complex recording conditions, diverse and realistic speaker variance, and dynamic prosodic speech for different linguistic contexts, which reveals the drawback of neural TTS that is trained with relatively small and clean dataset compared to ASR applications that usually have 1000x more data. Thus, the closer the synthesized speech can simulate compared to real speech in the ASR training set, the better the customization performance. TTS models with a large-scale data set and diverse speech output are the key factors for better ASR customization with synthesized speech.

Neural text-to-speech synthesis [10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22] has shown close to human quality in terms of naturalness and audio fidelity in the past years, with cascaded or end-to-end Transformer or LSTM architectures. Cascaded models separately optimize acoustic model and vocoder with autoregressive [12] or non-autoregressive [16] Transformer layers, while end-to-end (E2E) TTS simplifies the model building by jointly training acoustic model and vocoder to improve the speech quality with traditional mel-spectrograms [15] or automatically learned speech representations [18]. The predicted frame-level features are transformed to raw waveform by the neural vocoders with adversarial training [23, 24, 25, 26]. DelightfulTTS 2 [18] proposes a new codec network based on vector-quantized auto-encoders with adversarial training to automatically learn frame-level speech representations. Instead of using mel-spectrograms or other pre-designed features, it uses the codec encoder to extract speech representations, quantize them with residual vector quantizers, and then uses the codec decoder to reconstruct waveform with adversarial training. Though the above works achieve high quality on a small and clean dataset, it is hard to scale with larger or noisy datasets with diversity control due to complex and continuous acoustic feature dependency between the acoustic model and vocoder.

TTS with continuous speech feature is hard to solve the one-to-many problem as output randomness is hard to implement on frame-level speech features to achieve observable diversity on prosody and speaker, and features like melspectrograms, linear-spectrograms or self-extracted speech features are highly correlated along time and frequency axes which leads to overfitting or over smoothing effects for the acoustic model to predict. Human speech naturally has a random sampling effect like white noise in source-filter vocoders [27, 28, 29, 30, 31] that linguistic or acoustic condition is not enough to simulate. Since diverse control is easier to achieve than language or image models do, some works leverage discrete speech tokens to explore different architectures to replace continuous feature-based models. [32] proposes an E2E TTS framework based on VO-VAE [33] and neural machine translation (NMT), where the VQ-VAE model learns a mapping from the speech waveform into a sequence of discrete tokens, and the Transformer-based NMT model is trained to estimate the discrete token sequence from a given input, due to the use of discrete speech tokens, it can do sampling at each step as in NMT and ASR and thus avoid the over smoothing problem. VOTTS [34] consists of an acoustic model (AM) called txt2vec and a vocoder called vec2way, which uses a selfsupervised vector-quantized (VQ) acoustic feature rather than mel-spectrograms, in which txt2vec is a classification model with cross-entropy loss rather than a regression model while vec2wav uses an additional feature encoder for smoothing the

^{*}These authors contributed equally to this work. Corresponding author: Ruiqing Xue, ruiqingxue@microsoft.com

discontinuous quantized feature. Instead of predicting the complicated mel-spectrograms, txt2vec only needs to consider the correlation along the time axis, which reduces the gap between ground truth speech frames and the predicted ones. Although diversity can be achieved by sampling in inference time, these discrete models typically use a very small amount and relatively clean dataset like popular JUST or LJ Speech [35, 36], but large-scale and nosier datasets are not yet systemically explored especially in diverse speech output for ASR customization.

Large language model (LLM) based acoustic model is making remarkable progress on large-scale speech dataset training. Speech recording typically contains acoustic or semantic abstractions like fine-grained phonetic-level or word-level prosody, syntax, grammar attributes, or coarse-grained attributes like speaker identification, style class, accent type, etc. Neural codec models have achieved close to recording quality by leveraging methods such as autoregressive waveform modeling [37, 38, 39] and adversarial training [40, 16, 41, 42]. Language models have also demonstrated their ability to model high-level, long-term sequences for different content types, as shown by the recent advances in text [43, 44, 45, 46, 47] and image [48, 49, 50, 51, 52, 53]. Audio generation [54, 55, 56, 57, 58, 59] has made progress towards a natural audio synthesis that remains natural and consistent over time. [54] shows that a Transformer [60] decoder trained on discretized speech units can generate coherent speech without relying on textual phonemes, by a continuing generation with a speech prompt or music prompt sequence with dynamic acoustic diversity, linguistic consistency, and high audio fidelity. However, the prompt is speech unit only and the speaker or text prompt is not yet explored.

In this work, we propose FoundationTTS, a framework that enables high-quality and diverse text-to-speech generation with long-term linguistic and acoustic dependency modeling on large-scale speech datasets. As demonstrated by our experiments, the speech output of FoundationTTS is more diverse than traditional models due to discrete sampling mechanisms in language models. We achieve this objective by combining recent advances in the adversarial neural audio codec, end-to-end neural text-to-speech [18], and large language modeling [43]. Specifically, starting from a raw audio waveform, we first reconstruct the waveform with a fine-grained audio codec, where the codec encoder extracts the frame-level speech representations from the waveform with a set of residual quantizers, which capture the acoustic details of the audio waveform and allow for high-quality reconstruction by the codec decoder. Then we construct another coarse speech codec to reconstruct the finegrained speech representations with few quantizers to get the acoustic/speech tokens. At last, we trained a decoder-only language model, which autoregressively predicts the acoustic tokens from the coarse-grained speech codec which captures both local dependencies (e.g., phonetics in speech) and global longterm structure (e.g., semantic content in speech). Modeling both linguistic and acoustic tokens lead to both high audio quality and long-term consistency. In summary, we make the following contributions:

- We propose FoundationTTS, a framework for text-to-speech generation, which combines discrete speech tokens in a hierarchical fashion with a large language model to achieve longterm consistency and diverse output on large-scale and complex speech datasets.
- We propose a hierarchical codec network with the finegrained codec reconstructing waveform with frame-level

speech representations and coarse-grained codec reconstructing the speech representations with fewer quantizers to convert continuous representations to discrete speech tokens for language modeling.

• We demonstrate the ability of FoundationTTS to generate linguistically consistent, prosody-diverse, and high-quality speech for ASR domain customization and general neural text-to-speech.

2. FoundationTTS

FoundationTTS is a two-stage TTS model, in the first stage, we introduce a hierarchical audio code that can encode and reconstruct waveform, more specifically, it consists of two components: 1) fine-grained audio codec for continuous speech frame extraction. 2) coarse-grained audio codec for discrete speech token extraction. In the second stage, a prefix language model is trained over the discrete speech token sequence generated by the audio codec in the first stage. We use the prefix language model instead of the encoder-decoder paradigm because it can simplify the model structure and has gained great success in GPT-like models.

2.1. Speech Tokenizer with Hierarchical Audio Codec

The neural audio codec uses more bitrate to reconstruct highquality waveform comparable to real speech with discrete tokenizers at the frame level, which will increase the discrete speech token number at each frame with multiple residual quantizers but directly using smaller quantizer is hard to reconstruct waveform because real audio samples are complex with noises, besides language model performs poor on too longrange context modeling and the tokenizer is based on character or word piece which is much shorter than speech frames. The fine-grained codec frame and coarse-grained LM model unit thus need a balance for audio codec reconstruction quality and LM performance. To solve this contradiction, as in Figure 2, we designed a hierarchical audio codec as a speech tokenizer: first, the fine-grained audio codec encodes waveform to continuous features with a convolutional encoder and reconstructs waveform with a mirror decoder from the bottleneck layer via residual quantizers; then the coarse-grained audio codec further compresses the continuous representation generated by the finegrained codec using fewer quantizers for shorter speech token sequence.

2.1.1. Fine-Grained Codec with VQGAN

Fine-grained codec is like the frame-level feature extraction network in DelightfulTTS 2 [18], which consists of a waveform down-sampling encoder, and another mirrored up-sampling decoder, and a residual vector quantizer acting as a feature bottleneck. The codec encoder receives 16kHZ waveform as input, and down-sampling it to frame-level representation by convolutional layers, resulting in a 600X compression ratio with downsampling layers. The frame-level speech representation is then quantized by a residual vector quantizer (RVQ) with multiple vector quantizers; thus, we can compress the 16kHz continuous waveform samples into 26.7 Hz discrete speech tokens with 3.4 kbps, with a frame length of 37.5ms, in this way we can tokenize each speech frame into multiple discrete tokens, but it's slow to predict multiple discrete tokens in one step like [54], which flattens multiple speech tokens at each step and predicts autoregressively from coarse quantizer layers.



Figure 1: Prefix language model of FoundationTTS. DelightfulTTS blocks act as the phoneme encoder with phoneme tokens and position embedding as input. A speaker token is also added to the prefix noted as SPK. A set of transformer decoders perform autoregressive decoding of speech tokens with full phoneme tokens and speaker tokens.

2.1.2. Coarse-Grained Codec for LM Token Extraction

A coarse-grained codec is designed to reconstruct the frame level feature from the fine-grained codec but with fewer quantizers, more quantizers will better reconstruct waveform in a fine-grained codec but it will also increase the speech token number for one speech frame and make it hard for language modeling with discrete tokens, the coarse-grained codec makes a balance on the token number and waveform reconstruction quality based on the pre-trained fine-grained codec. The framelevel acoustic feature from the fine-grained codec acts as the reconstruction target for the coarse-grained codec. The finegrained frame-level speech acoustic features are first fed into an improved conformer encoder [16], and the output is then quantized by a single-layer vector quantizer. Finally, the finegrained audio codec acoustic features are reconstructed by another conformer decoder. The purpose of reconstructing the fine-grained speech frames instead of the waveform is to simplify the predicting target and thus we can use fewer quantizers to approximate the speech by the fine-grained codec. To further improve reconstruction ability, we don't reconstruct features directly, instead, the decoder predicts the weight distribution of fine-grained RVQ, which we found will perform better tokenization in experiments and speed up training convergence.

We used the same discriminators described in Delightfultts 2 [18], which combine multi-scale and multi-period discriminators for both fine-grained audio codec and coarse-grained audio codec.

2.2. TTS Language Modeling

The acoustic model in traditional neural TTS is designed to predict continuous speech features, for example, mel-spectrograms used by TransformerTTS, FastSpeech, and DelightfulTTS [12, 13, 16] or self-learned acoustic features used by NaturalSpeech and DelightfulTTS 2 [22, 18] from linear spectrum or waveform directly. Although these models can synthesize high-quality

and natural speech, two drawbacks are still obvious: 1) hard to leverage complex real-world speech or large-scale speech datasets for acoustic modeling, such as noisier data in ASR corpus or audiobook instead of relatively clean recorded speech. 2) it is not straightforward to synthesize diverse speech output from continuous frame-level features to reduce the one-tomany mapping issue in TTS. Generally, optional approaches are needed to alleviate the diverse issue. The first class is to provide additional acoustic or linguistic conditions for the acoustic model except for the phoneme sequence input, such as pitch or phoneme embeddings [61, 62, 63], prosodies in different granularities have also been added to TTS in [64, 65]. The effectiveness of VQVAE is also explored in [66]. Another approach to address the problem is to exploit better training criteria except for the common L1 or L2 loss criterion for AM. However, the real acoustic distribution is much more complicated. Hence, some research uses normalizing flow [6, 67] for this problem. The normalizing flow transforms the data distribution into a known simple distribution and is optimized via maximum log-likelihood. However, both VAE and flow models should be carefully designed to ensure invertibility and stability, which restricts the scalability of such models.

As in Figure 1, to overcome these problems, we use discrete speech tokens as the modeling unit and designed a prefix language model to predict these discrete tokens. Specifically, the speech-language model consists of a DelightfulTTS encoder block and a decoder-only Transformer block. The DelightfulTTS encoder extracts linguistic representations from phoneme or text sequence, and the decoder-only transformer will autoregressively generate discrete acoustic tokens with linguistic representations as a prefix. The linguistic prefix and discrete speech tokens are fed into the same transformer decoder without a cross-attention layer. Different position embeddings and tokens are used to distinguish them from each other. We use bi-directional self-attention over linguistic prefixes and use monotonous self-attention on discrete speech tokens. Speaker



Figure 2: The structure of the hierarchical codec network consists of a fine-grained codec and a coarse-grained codec. The fine-grained codec is composed of a convolution down-sampling encoder that extracts frame-level speech representations from audio waveform, an RVQ block that discretizes the frame representation, and a convolution up-sampling decoder. The structure of coarse-grained codec is like fine-grained codec except that it uses DelightfulTTS block instead of convolution network and the number of RVQ layers is 1.

embeddings are also added as speaker prefixes in the Transformer decoder. It's observed that larger LM is more stable than smaller models in terms of naturalness or bad case ratio like skipping phone or repeat phone issues.

2.3. Training Objectives

Codec Loss Following DeflightufITTS 2, we train the hierarchical audio codec with adversarial objectives.

$$L_{\rm FCODEC} = L_{\rm adv} + L_{\rm rvq} + L_{\rm fm} + L_{\rm mrs} + L_{\rm msd} + L_{\rm mpd} \quad (1)$$

Fine-grained codec loss contains a multi-period discriminator loss $L_{\rm mpd}$, multi-scale discriminator loss $L_{\rm msd}$, together with an adversarial loss $L_{\rm adv}$, a multi-resolution spectrogram loss $L_{\rm mrs}$, a feature match loss $L_{\rm fm}$ and residual vector quantization loss $L_{\rm rvq}$ with random segmented waveform.

$$L_{\text{CCODEC}} = L_{\text{adv}} + L_{\text{vq}} + L_{\text{fm}} + L_{\text{mrs}} + L_{\text{msd}} + L_{\text{mpd}} \quad (2)$$

The coarse-grained codec uses the reconstructed finegrained frames, goes through the frozen fine-grained speech codec and generates a reconstructed waveform with the same multi-period discriminator loss $L_{\rm mpd}$, multi-scale discriminator loss $L_{\rm msd}$, together with an adversarial loss $L_{\rm adv}$, a multiresolution spectrogram loss $L_{\rm mrs}$, a feature match loss $L_{\rm fm}$ and vector quantization loss $L_{\rm vq}$.

Prefix Language Model Loss given an audio waveform $x = \{x_1, ..., x_{t_x}\}$, the hierarchical codec compresses it into discrete speech tokens as LM target, $c = \{c_1, ..., c_{t_c}\}$, and a DelightfulTTS block is used to map phoneme sequences into linguistic

representations $w = \{w_1, ..., w_{t_w}\}$, then the speech synthesis task can be viewed as a language model problem that trained with cross-entropy loss.

$$L_{LM} = -\mathbb{E}\sum_{t=1}^{T_c} \log p_{\theta} \left(c_t | c_1, ..., c_{t-1}, w_1, ..., w_{t_w} \right)$$
(3)

Where T_c is the frame number and t_w is the length of the phoneme sequence, θ is the trainable parameters of the language model.

2.4. Inference

During inference, as in Figure 3, the input phoneme sequence is first fed into a DelightfulTTS block in the prefix LM to extract the linguistic representation, and the decoder-only transformer autoregressively generates speech tokens conditioned on these linguistic features and speaker embedding. Another DelightfulTTS block in a coarse-grained codec decoder converts the discrete speech tokens into a frame-level weight distribution of RVQ tokens in the fine-grained codebook, and then the corresponding fine-grained speech tokens are generated based on the distribution. Finally, the fine-grained codec decoder reconstructs the waveform based on these fine-grained speech tokens. We apply top-p sampling to generate diverse speech.

3. Experiments

We explain the experiment dataset, training, and evaluation setting for the proposed FoundationTTS with TTS and ASR metrics in this section.



Figure 3: During inference, phoneme tokens are first fed into a DelightfulTTS encoder to extract the linguistic representation, and a decoder-only Transformer autoregressively generates speech tokens conditioned on these linguistic features and speaker token, we apply top-p sampling to generate diverse speech. Finally, the audio waveform will be reconstructed by hierarchical codec decoders based on the predicted speech tokens.

3.1. Experimental Setup

Datasets to evaluate the performance on ASR customization, we conduct experiments on both internal Chinese shanghai dialect datasets and English datasets. The internal Chinese shanghai dialect dataset contains 600 hours of the domain-specific corpus, the transcriptions are converted into phonemes by the rule-based grapheme-to-phoneme module, since the transcription contains polyphonic characters and the rule-based G2P module cannot accurately disambiguate, the polyphonic characters are reserved as extra tokens. The English datasets contain 900 hours corpus, which consists of LibriTTS, VCTK, and internal TTS data [68, 69], the text goes through the standard TTS front-end data processing process including rule-based text normalization and grapheme-to-phoneme conversion. The sample rate of the audio waveform is 16kHz.

Training Setting FoundationTTS consists of three components that are trained one by one, firstly, the fine-grained audio codec is trained with audio-only data. Secondly, the coarse-grained audio codec is trained with the pre-trained fine-grained audio codec. Finally, the prefix language model is trained with the speech token extracted with the coarse-grained audio codec. 8x 32GB V100 GPUs are used for both hierarchical codec and prefix language model training. During hierarchical codec training, we randomly segment the waveform into chunks of 24000 sample points to speed up model convergence. Adam optimizer is used for hierarchical codec and prefix language model training, with Radam and Lookahead optimization [70, 71]; for prefix language model training, we apply a learning rate of 0.001 with exponentially decaying to 0.00005 starting from 4,000 iterations. The fine-grained codec contains four convolutional layers in the encoder and decoder, and 16 residual quantizers are applied in between. The coarse-grained contains three improved conformer blocks in the encoder and decoder and one quantizer is applied after the codec encoder. The prefix LM contains 16 Transformer layers, and six improved conformer blocks as phoneme encoders, with a total parameter number of about 600M.

Evaluation Setting We evaluate the adaptation performance FoundationTTS on two independent ASR systems, Hybrid, and RNN-T [72, 73] on both Chinese shanghai dialect and English test set with word error rate (WER) metrics. We also evaluate the synthesized audio quality of FoundationTTS and reconstruct the quality of the hierarchical codec with both objective and subjective metrics, subjective metrics include the mean option score (MOS) of FoundationTTS and comparative mean option score (CMOS) of codec, ViSQOL [74] score of coarse-grained audio codec and fine-grained audio codec is reported as the objective metrics. The TTS and codec evaluation set used by subjective and objective metrics evaluation are randomly preserved from the training set, and the ASR adaptation evaluation set does not overlap with the training set.

3.2. Results

3.2.1. ASR Adaptation Performance

Hybrid ASR adaptation Table 1 shows the WER reduction on the hybrid ASR system with FoundationTTS domain-specific adaptation synthesized data, the baseline hybrid system is a pretrained Chinese shanghai dialect model, note that the baseline model is already adapted with domain-specific data, even so, our model still achieves a 7.09% WER reduction, the evaluation set contains 1000 sentences.

RNN-T adaptation We conduct another FoundationTTS adaptation experiment on the RNN-T ASR model, for comparison, we also list the WER of FastSpeech adaptation. FoundationTTS adaptation and FastSpeech adaptation are trained with the same domain-specific dataset. Table 2 shows that the FoundationTTS adaptation obtains 40.13% WER reduction when compared with the RNN-T baseline, and gets 10.35% WER reduction compared to FastSpeech adaptation, which indicates

	Female	Male	ALL
Hybrid Baseline	9.96%	10.63%	10.29%
+FoundationTTS adaptation	8.88%	10.26%	9.56%
WERR	10.84%	3.48%	7.09%

Table 1: WERR of ASR adaptation on Shanghai Dialect test set.

that FoundationTTS can synthesize more diverse and realistic audio than traditional non-autoregressive continuous acoustic frames based TTS model, the evaluation set contains 1032 sentences. The adaptation experiment on hybrid and RNN-T ASR models shows that the synthesized data is robust enough for different ASR models which consistently achieve WER reduction.

Method	WER
RNN-T Baseline	15.05%
+FastSpeech adaptation	10.05%
+FoundationTTS adaptation	9.01%

Table 2: WER Comparison of RNN-T, FastSpeech, and FoundationTTS on English adaptation test set.

System	MOS
FastSpeech	3.84 ± 0.09
FoundationTTS	3.98 ± 0.08
Recording	4.45 ± 0.10

Table 3: MOS Comparison of FoundationTTS vs FastSpeech trained on 900 hours diverse corpus.

3.2.2. TTS Quality Evaluation

Subjective metrics Table 3 shows the comparison between FoundationTTS and FastSpeech by the metrics of MOS. FoundationTTS and FastSpeech are trained with the same training data that consists of 900 hours of English corpus and more than 7000 speakers. The evaluation set contains 80 sentences, and each sample is rated by 10 judges, Results show that FoundationTTS outperforms FastSpeech in terms of naturalness.

Objective metrics of codec We report the ViSQOL score of fine-grained codec and coarse-grained codec in Table 4. The evaluation set contains 2939 sentences. The bitrates of finegrained codec and coarse-grained codec are 3.42 and 0.27 respectively. We can observe that ViSQOL score of fine-grained codec is +0.7 over coarse-grained codec, but coarse-grained codec using only 7.9% bitrates compared with fine-grained codec, higher bitrates of fine-grained codec lead to better audio reconstruct quality and lower bitrates of coarse-grained codec results in shorter discrete sequences, which is more suitable for large language modeling. The combination of fine-grained codec and coarse-grained codec balances the reconstruction quality and modeling efficiency. Note that we have tried to train the coarse-grained codec directly on the waveform, but the model fails to converge. This implies that the fine-grained codec simplifies the feature representation of the audio waveform and makes the coarse-grained codec easier to train.

Subjective metrics of codec We also report CMOS score between audio reconstructed by fine-grained codec and recording, as shown in table 5. The overall mean score of -0.06 indicates that the fine-grained codec can resynthesize high-fidelity speech waveform.

Codec	Bitrate (kbps)	ViSQOL
Coarse-grained Codec	0.27	3.07
Fine-grained Codec	3.42	3.77

Table 4: Comparison of ViSQOL for hierarchical audio codec.

System	CMOS
Codec Reconstruction vs Recording	-0.06

Table 5: CMOS for fine-grained codec reconstruction.

3.2.3. Ablation Analysis

Parameter number affects the stability and audio quality for the language model, we trained a series of speech token language models with different sizes ranging from 20M to 600M, which shows that the number of parameters significantly affects the end-to-end quality, the smallest 20M model cannot converge at all. Larger and more diverse training data requires a bigger model capacity, like what the GPT series model has shown in language.

The coarse-grained codec uses one quantizer in this work. We experiment with different quantizer numbers for the coarsegrained codec, which shows more quantizer has more audio reconstruction quality, but one speech frame will have more token id which is not suitable for language modeling, especially for the nosier dataset, less quantizer coarse codec is hard to better reconstruct the audio with high SNR or prosody varied corpus.

4. Conclusions

This paper describes FoundationTTS, a neural Text-to-Speech system that combines a hierarchical codec network with adversarial vector-quantized auto-encoders on continuous speech frames and a language model on discrete speech tokens, providing diverse speech output with large-scale and complex real speech dataset modeling ability without pre-designed acoustic features like mel or linear scale spectrograms. FoundationTTS achieves better quality than baseline systems on two ASR adaptation tasks. For future work, we plan to investigate a larger dataset with LM on more challenging datasets such as multispeaker or multilingual datasets to explore the challenges and the potential application for realistic speech syntheses scenarios and ASR adaptation.

FoundationTTS is capable of synthesizing high-quality speech that closely matches the naturalness and speaker similarity of human speech, with diverse and smooth prosody. However, this advanced capability also comes with potential risks, such as voice cloning of specific individuals, which could be misused. To address these risks, we are committed to implementing Microsoft AI Principles in the further development of these models for various scenarios.¹.

5. References

- [1] J. Li, R. Zhao, Z. Meng, Y. Liu, W. Wei, S. Parthasarathy, V. Mazalov, Z. Wang, L. He, S. Zhao *et al.*, "Developing rnnt models surpassing high-performance hybrid models with customization capability," *arXiv preprint arXiv:2007.15188*, 2020.
- [2] K. C. Sim, F. Beaufays, A. Benard, D. Guliani, A. Kabel, N. Khare, T. Lucassen, P. Zadrazil, H. Zhang, L. Johnson *et al.*, "Personalization of end-to-end speech recognition on mobile devices for named entities," in 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU). IEEE, 2019, pp. 23–30.
- [3] X. Wang, Y. Liu, S. Zhao, and J. Li, "A light-weight contextual spelling correction model for customizing transducer-based speech recognition systems," *arXiv preprint arXiv:2108.07493*, 2021.
- [4] X. Wang, Y. Liu, J. Li, V. Miljanic, S. Zhao, and H. Khalil, "Towards contextual spelling correction for customization of end-to-end speech recognition systems," *arXiv preprint arXiv:2203.00888*, 2022.
- [5] X. Wang, Y. Liu, J. Li, and S. Zhao, "Improving contextual spelling correction by external acoustics attention and semantic aware data augmentation," *arXiv preprint arXiv:2302.11192*, 2023.
- [6] G. Papamakarios, E. T. Nalisnick, D. J. Rezende, S. Mohamed, and B. Lakshminarayanan, "Normalizing flows for probabilistic modeling and inference." *J. Mach. Learn. Res.*, vol. 22, no. 57, pp. 1–64, 2021.
- [7] S. Ueno, M. Mimura, S. Sakai, and T. Kawahara, "Multi-speaker sequence-to-sequence speech synthesis for data augmentation in acoustic-to-word speech recognition," in *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2019, pp. 6161–6165.
- [8] A. Tjandra, S. Sakti, and S. Nakamura, "Machine speech chain with one-shot speaker adaptation," *arXiv preprint* arXiv:1803.10525, 2018.
- [9] M. Mimura, S. Ueno, H. Inaguma, S. Sakai, and T. Kawahara, "Leveraging sequence-to-sequence speech synthesis for enhancing acoustic-to-word speech recognition," in 2018 IEEE Spoken Language Technology Workshop (SLT). IEEE, 2018, pp. 477– 484.
- [10] Y. Wang, R. Skerry-Ryan, D. Stanton, Y. Wu, R. J. Weiss, N. Jaitly, Z. Yang, Y. Xiao, Z. Chen, S. Bengio *et al.*, "Tacotron: Towards end-to-end speech synthesis," *arXiv preprint arXiv:1703.10135*, 2017.
- [11] J. Shen, R. Pang, R. J. Weiss, M. Schuster, N. Jaitly, Z. Yang, Z. Chen, Y. Zhang, Y. Wang, R. Skerrv-Ryan *et al.*, "Natural TTS synthesis by conditioning wavenet on mel spectrogram predictions," in 2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2018, pp. 4779– 4783.
- [12] N. Li, S. Liu, Y. Liu, S. Zhao, and M. Liu, "Neural speech synthesis with transformer network," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 33, no. 01, 2019, pp. 6706– 6713.
- [13] Y. Ren, Y. Ruan, X. Tan, T. Qin, S. Zhao, Z. Zhao, and T.-Y. Liu, "Fastspeech: Fast, robust and controllable text to speech," *arXiv* preprint arXiv:1905.09263, 2019.
- [14] N. Li, Y. Liu, Y. Wu, S. Liu, S. Zhao, and M. Liu, "Robutrans: A robust transformer-based text-to-speech model," in *Proceedings* of the AAAI Conference on Artificial Intelligence, vol. 34, no. 05, 2020, pp. 8228–8235.

- [15] Y. Ren, C. Hu, X. Tan, T. Qin, S. Zhao, Z. Zhao, and T.-Y. Liu, "Fastspeech 2: Fast and high-quality end-to-end text to speech," in *International Conference on Learning Representations*, 2021. [Online]. Available: https://openreview. net/forum?id=piLPYqxtWuA
- [16] Y. Liu, Z. Xu, G. Wang, K. Chen, B. Li, X. Tan, J. Li, L. He, and S. Zhao, "Delightfultts: The Microsoft speech synthesis system for blizzard challenge 2021," arXiv preprint arXiv:2110.12612, 2021.
- [17] J. Donahue, S. Dieleman, M. Bińkowski, E. Elsen, and K. Simonyan, "End-to-end adversarial text-to-speech," *arXiv preprint* arXiv:2006.03575, 2020.
- [18] Y. Liu, R. Xue, L. He, X. Tan, and S. Zhao, "Delightfultts 2: Endto-end speech synthesis with adversarial vector-quantized autoencoders," arXiv preprint arXiv:2207.04646, 2022.
- [19] J. Kim, J. Kong, and J. Son, "Conditional variational autoencoder with adversarial learning for end-to-end text-to-speech," arXiv preprint arXiv:2106.06103, 2021.
- [20] R. J. Weiss, R. Skerry-Ryan, E. Battenberg, S. Mariooryad, and D. P. Kingma, "Wave-tacotron: Spectrogram-free end-to-end text-to-speech synthesis," in *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing* (*ICASSP*). IEEE, 2021, pp. 5679–5683.
- [21] X. Tan, T. Qin, F. Soong, and T.-Y. Liu, "A survey on neural speech synthesis," arXiv preprint arXiv:2106.15561, 2021.
- [22] X. Tan, J. Chen, H. Liu, J. Cong, C. Zhang, Y. Liu, X. Wang, Y. Leng, Y. Yi, L. He *et al.*, "Naturalspeech: End-to-end text to speech synthesis with human-level quality," *arXiv preprint arXiv:2205.04421*, 2022.
- [23] K. Kumar, R. Kumar, T. de Boissiere, L. Gestin, W. Z. Teoh, J. Sotelo, A. de Brébisson, Y. Bengio, and A. Courville, "Melgan: Generative adversarial networks for conditional waveform synthesis," arXiv preprint arXiv:1910.06711, 2019.
- [24] J. Kong, J. Kim, and J. Bae, "Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis," *Advances* in Neural Information Processing Systems, vol. 33, 2020.
- [25] J.-H. Kim, S.-H. Lee, J.-H. Lee, and S.-W. Lee, "Fre-gan: Adversarial frequency-consistent audio synthesis," *arXiv preprint* arXiv:2106.02297, 2021.
- [26] W. Jang, D. Lim, J. Yoon, B. Kim, and J. Kim, "Univnet: A neural vocoder with multi-resolution spectrogram discriminators for high-fidelity waveform generation," *arXiv preprint* arXiv:2106.07889, 2021.
- [27] Q. Hu, K. Richmond, J. Yamagishi, and J. Latorre, "An experimental comparison of multiple vocoder types," in *Eighth ISCA Workshop on Speech Synthesis*, 2013.
- [28] H. Zen, T. Nose, J. Yamagishi, S. Sako, T. Masuko, A. W. Black, and K. Tokuda, "The hmm-based speech synthesis system (hts) version 2.0." SSW, vol. 6, pp. 294–299, 2007.
- [29] H. Kawahara, I. Masuda-Katsuse, and A. De Cheveigne, "Restructuring speech representations using a pitch-adaptive time– frequency smoothing and an instantaneous-frequency-based f0 extraction: Possible role of a repetitive structure in sounds," *Speech communication*, vol. 27, no. 3-4, pp. 187–207, 1999.
- [30] T. Drugman and T. Dutoit, "The deterministic plus stochastic model of the residual signal and its applications," *IEEE Transactions on Audio, Speech, and Language Processing*, vol. 20, no. 3, pp. 968–981, 2011.
- [31] K. Tokuda, T. Kobayashi, T. Masuko, and S. Imai, "Melgeneralized cepstral analysis-a unified approach to speech spectral estimation." in *ICSLP*, vol. 94, 1994, pp. 18–22.
- [32] T. Hayashi and S. Watanabe, "Discretalk: Text-to-speech as a machine translation problem," arXiv preprint arXiv:2005.05525, 2020.
- [33] A. Razavi, A. Van den Oord, and O. Vinyals, "Generating diverse high-fidelity images with vq-vae-2," Advances in neural information processing systems, vol. 32, 2019.

¹https://www.microsoft.com/ai/responsible-ai

- [34] C. Du, Y. Guo, X. Chen, and K. Yu, "Vqtts: High-fidelity text-tospeech synthesis with self-supervised vq acoustic feature," *arXiv* preprint arXiv:2204.00768, 2022.
- [35] R. Sonobe, S. Takamichi, and H. Saruwatari, "Jsut corpus: free large-scale japanese speech corpus for end-to-end speech synthesis," arXiv preprint arXiv:1711.00354, 2017.
- [36] K. Ito and L. Johnson, "The lj speech dataset," https://keithito. com/LJ-Speech-Dataset/, 2017.
- [37] A. v. d. Oord, S. Dieleman, H. Zen, K. Simonyan, O. Vinyals, A. Graves, N. Kalchbrenner, A. Senior, and K. Kavukcuoglu, "Wavenet: A generative model for raw audio," *arXiv preprint* arXiv:1609.03499, 2016.
- [38] J.-M. Valin and J. Skoglund, "Lpcnet: Improving neural speech synthesis through linear prediction," in *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2019, pp. 5891–5895.
- [39] N. Kalchbrenner, E. Elsen, K. Simonyan, S. Noury, N. Casagrande, E. Lockhart, F. Stimberg, A. Oord, S. Dieleman, and K. Kavukcuoglu, "Efficient neural audio synthesis," in *International Conference on Machine Learning*. PMLR, 2018, pp. 2410–2419.
- [40] N. Zeghidour, A. Luebs, A. Omran, J. Skoglund, and M. Tagliasacchi, "Soundstream: An end-to-end neural audio codec," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2021.
- [41] M. Tagliasacchi, Y. Li, K. Misiunas, and D. Roblek, "Seanet: A multi-modal speech enhancement network," *arXiv preprint* arXiv:2009.02095, 2020.
- [42] A. Défossez, J. Copet, G. Synnaeve, and Y. Adi, "High fidelity neural audio compression," *arXiv preprint arXiv:2210.13438*, 2022.
- [43] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, "Language models are few-shot learners," *Advances in neural information processing systems*, vol. 33, pp. 1877–1901, 2020.
- [44] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever et al., "Language models are unsupervised multitask learners," *OpenAI blog*, vol. 1, no. 8, p. 9, 2019.
- [45] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. L. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray *et al.*, "Training language models to follow instructions with human feedback," *arXiv preprint arXiv:2203.02155*, 2022.
- [46] J. Wei, M. Bosma, V. Y. Zhao, K. Guu, A. W. Yu, B. Lester, N. Du, A. M. Dai, and Q. V. Le, "Finetuned language models are zeroshot learners," *arXiv preprint arXiv:2109.01652*, 2021.
- [47] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann *et al.*, "Palm: Scaling language modeling with pathways," *arXiv* preprint arXiv:2204.02311, 2022.
- [48] J. Yu, X. Li, J. Y. Koh, H. Zhang, R. Pang, J. Qin, A. Ku, Y. Xu, J. Baldridge, and Y. Wu, "Vector-quantized image modeling with improved vqgan," *arXiv preprint arXiv:2110.04627*, 2021.
- [49] A. Ramesh, P. Dhariwal, A. Nichol, C. Chu, and M. Chen, "Hierarchical text-conditional image generation with clip latents," arXiv preprint arXiv:2204.06125, 2022.
- [50] A. Ramesh, M. Pavlov, G. Goh, S. Gray, C. Voss, A. Radford, M. Chen, and I. Sutskever, "Zero-shot text-to-image generation," in *International Conference on Machine Learning*. PMLR, 2021, pp. 8821–8831.
- [51] K. He, X. Chen, S. Xie, Y. Li, P. Dollár, and R. Girshick, "Masked autoencoders are scalable vision learners," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 16 000–16 009.
- [52] H. Bao, L. Dong, and F. Wei, "Beit: Bert pre-training of image transformers," arXiv preprint arXiv:2106.08254, 2021.

- [53] D. Lee, C. Kim, S. Kim, M. Cho, and W.-S. Han, "Autoregressive image generation using residual quantization," in *Proceed*ings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 11 523–11 532.
- [54] Z. Borsos, R. Marinier, D. Vincent, E. Kharitonov, O. Pietquin, M. Sharifi, O. Teboul, D. Grangier, M. Tagliasacchi, and N. Zeghidour, "Audiolm: a language modeling approach to audio generation," arXiv preprint arXiv:2209.03143, 2022.
- [55] F. Kreuk, G. Synnaeve, A. Polyak, U. Singer, A. Défossez, J. Copet, D. Parikh, Y. Taigman, and Y. Adi, "Audiogen: Textually guided audio generation," *arXiv preprint arXiv:2209.15352*, 2022.
- [56] K. Lakhotia, E. Kharitonov, W.-N. Hsu, Y. Adi, A. Polyak, B. Bolte, T.-A. Nguyen, J. Copet, A. Baevski, A. Mohamed et al., "On generative spoken language modeling from raw audio," *Transactions of the Association for Computational Linguistics*, vol. 9, pp. 1336–1354, 2021.
- [57] F. Kreuk, Y. Taigman, A. Polyak, J. Copet, G. Synnaeve, A. Défossez, and Y. Adi, "Audio language modeling using perceptually-guided discrete representations," *arXiv preprint* arXiv:2211.01223, 2022.
- [58] S. Maiti, Y. Peng, T. Saeki, and S. Watanabe, "Speechlmscore: Evaluating speech generation using speech language model," arXiv preprint arXiv:2212.04559, 2022.
- [59] G. Maimon and Y. Adi, "Speaking style conversion with discrete self-supervised units," arXiv preprint arXiv:2212.09730, 2022.
- [60] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in Advances in neural information processing systems, 2017, pp. 5998–6008.
- [61] A. Łańcucki, "Fastpitch: Parallel text-to-speech with pitch prediction," in ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2021, pp. 6588–6592.
- [62] Y. Wang, D. Stanton, Y. Zhang, R.-S. Ryan, E. Battenberg, J. Shor, Y. Xiao, Y. Jia, F. Ren, and R. A. Saurous, "Style tokens: Unsupervised style modeling, control and transfer in end-to-end speech synthesis," in *International Conference on Machine Learning*. PMLR, 2018, pp. 5180–5189.
- [63] W.-N. Hsu, Y. Zhang, R. J. Weiss, H. Zen, Y. Wu, Y. Wang, Y. Cao, Y. Jia, Z. Chen, J. Shen *et al.*, "Hierarchical generative modeling for controllable speech synthesis," *arXiv preprint arXiv*:1810.07217, 2018.
- [64] G. Sun, Y. Zhang, R. J. Weiss, Y. Cao, H. Zen, and Y. Wu, "Fullyhierarchical fine-grained prosody modeling for interpretable speech synthesis," in *ICASSP 2020-2020 IEEE international conference on acoustics, speech and signal processing (ICASSP).* IEEE, 2020, pp. 6264–6268.
- [65] C.-M. Chien and H.-y. Lee, "Hierarchical prosody modeling for non-autoregressive speech synthesis," in 2021 IEEE Spoken Language Technology Workshop (SLT). IEEE, 2021, pp. 446–453.
- [66] X. Wang, S. Takaki, J. Yamagishi, S. King, and K. Tokuda, "A vector quantized variational autoencoder (vq-vae) autoregressive neural f_0 model for statistical parametric speech synthesis," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 28, pp. 157–170, 2019.
- [67] J. Kim, S. Kim, J. Kong, and S. Yoon, "Glow-tts: A generative flow for text-to-speech via monotonic alignment search," Advances in Neural Information Processing Systems, vol. 33, pp. 8067–8077, 2020.
- [68] H. Zen, V. Dang, R. Clark, Y. Zhang, R. J. Weiss, Y. Jia, Z. Chen, and Y. Wu, "Libritts: A corpus derived from librispeech for textto-speech," *arXiv preprint arXiv:1904.02882*, 2019.
- [69] C. Veaux, J. Yamagishi, K. MacDonald *et al.*, "Superseded-cstr vctk corpus: English multi-speaker corpus for cstr voice cloning toolkit," 2016.

- [70] L. Liu, H. Jiang, P. He, W. Chen, X. Liu, J. Gao, and J. Han, "On the variance of the adaptive learning rate and beyond," *arXiv* preprint arXiv:1908.03265, 2019.
- [71] M. Zhang, J. Lucas, J. Ba, and G. E. Hinton, "Lookahead optimizer: k steps forward, 1 step back," *Advances in neural information processing systems*, vol. 32, 2019.
- [72] A. Graves, "Sequence transduction with recurrent neural networks," arXiv preprint arXiv:1211.3711, 2012.
- [73] K. Rao, H. Sak, and R. Prabhavalkar, "Exploring architectures, data and units for streaming end-to-end speech recognition with rnn-transducer," in 2017 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU). IEEE, 2017, pp. 193–199.
- [74] A. Hines, J. Skoglund, A. C. Kokaram, and N. Harte, "Visqol: an objective speech quality model," *EURASIP Journal on Audio*, *Speech, and Music Processing*, vol. 2015, no. 1, pp. 1–18, 2015.