Perfe Mura *E *Corre

Performance study of Partitioned Caches in Asymmetric Multi-Core processors

Murali Dadi, Shubhang Pandey, Aparna Behera and T G Venkatesh

^{*}Electrical Engineering Department, Indian Institute of Technology Madras, Chennai, India.

*Corresponding author(s). E-mail(s): ee19s057@smail.iitm.ac.in; tgvenky@ee.iitm.ac.in; Contributing authors: muralidadi963@gmail.com;

ee16d038@smail.iitm.ac.in;

Abstract

The current workloads and applications are highly diversified, facing critical challenges such as the Power Wall and the Memory Wall Problem. Different strategies over the multiple levels of Caches have evolved to mitigate these problems. Also, to work with such diversified applications, the Asymmetric Multi-Core Processor (AMP) presents itself as a viable solution. In this paper, we study the performance of L2 and Last Level Cache for different cache partitions against various AMP configurations. In addition, this study investigates the optimal cache partitioning for a collection of Multi-threaded benchmarks from PARSEC and SPLASH2 benchmark suites under medium-sized inputs. We have studied the effect of block replacement strategies and their impact on the key metrics such as total on-chip power consumption and L2 & LLC Miss rates. Our study presents an intermediate cache design for AMPs between the two extremities of fully shared and fully private L2 & LLC level Cache, which helps achieve the desired power values and optimal cache miss penalties.

Keywords: Asymmetric Multi-Core Processors, L2 cache, Last Level Cache, Cache replacement policy, CPU power

2 Performance study of Partitioned Caches in Asymmetric Multi-Core processors

1 Introduction

The current workloads and applications are highly diversified, facing critical challenges such as the Power Wall and the Memory Wall Problem. Different strategies over the multiple levels of Caches have evolved to mitigate these problems. Also, to work with such diversified applications, the Asymmetric Multi-Core Processor (AMP) presents itself as a viable solution. In this paper, we study the performance of L2 and Last Level Cache for different cache partitions of various AMP configurations. In addition, this study investigates the optimal cache partitioning for a collection of Multi-threaded benchmarks from PARSEC and SPLASH2 benchmark suites under medium-sized inputs. We have studied the effect of block replacement strategies and their impact on the key metrics such as total on-chip power consumption and L2 & LLC Miss rates. Our study presents an intermediate cache design for AMPs between the two extremities of fully shared and fully private L2 & LLC level Cache, which helps achieve the desired power values and optimal cache miss penalties.

There has been immense progress in recent times in designing highperformance and energy-efficient asymmetric Multi-Core processors. However, the trade-off between performance and power plays a crucial role in the processor design. With the aggressive scaling in IC Technology, power density (W/cm^2) has increased due to an increase in the number of transistors per unit area [1]. In addition, the objective function (better performance or lower power consumption) may also change depending on the requirements and the operating conditions of a device. For example, in mobiles, energy needs to be optimized during idle periods for getting better battery life, while the performance needs to be prioritized during active times. LLCs are one of the processor's resources that significantly impact system performance and energy usage. So it becomes a significant challenge to handle LLCs efficiently [1],[2]. Motivated by this point we set the aim of our paper to carry out an extensive performance evaluation of the LLC of AMPs as detailed below. Note that in the context of this paper, we have three cache levels and the terms L3 and LLC have been used interchangeably.

In this paper, we have studied the performance aspects of LLC in Asymmetric Multi-Core architectures. The high level overview of the paper is as follows. In Multi-Core architecture, managing the shared LLCs is a critical task. Thus we have explored the effect of different configurations for L2 and LLCs which affects the critical system metrics such as L2 miss rate, L3 miss rate, and total power consumption of a Multi-Core architecture. Further in our study, we have investigated the impact on the power consumption of an Asymmetric Multi-Core processor due to different cores (with different operating frequencies) and also different order of execution (in-order or out-of-order). This forms the high level overview of our paper.

The remainder of this paper is organized as follows. Section 2 gives us a brief literature survey on the performance evaluation of the LLC. Then, section 3 presents the study related to the LLC and its corresponding simulation results.

Inferences drawn from these simulation results and the concluding remarks are presented in Section 4.

2 Literature Survey

This section reviews the existing literature works related to the study of performance and energy efficiency of the LLC. Cache memories are often employed in microprocessors to increase the system performance, and thus these caches have been the subject of numerous studies [2-6]. The replacement policies of LLC significantly affect the off-chip miss traffic and power consumption. Peneau et al. have studied how different LLC replacement strategies affect the system performance, and energy consumption [7]. The asymmetric Multi-Core architectures are in high demand, and the existing replacement policies have significant challenges when implemented in Asymmetric Multi-Core systems. Ramtake et al. have studied the effect of Associativity on L1, L2 caches in a Multi-Core system concerning the cache hit ratio and IPC (Instructions per Cycle) [8]. The modern VLSI chips integrate larger caches onto the processor, and managing such larger cache sizes has considerable overhead. Wu et al. have proposed a machine learning based management scheme for the shared LLC in chip multiprocessors [9]. Jang et al. [10] have suggested a cache design for larger LLCs, so that good performance is attained even with high granularity. Anandkumar et al. have proposed a new hybrid cache replacement strategy for heterogeneous Multi-Cores that combines LRU, and LFU replacement policies [11]. Heterogeneity in a Multi-Core system can be achieved by changing individual core frequencies, cache sizes, and other cache parameters. Silva et al. have investigated the benefits of having various cache sizes in HMPs (Heterogeneous Multi-Core Processors) and how a scheduling technique can explore such benefits to reduce the overall miss rate [12]. The LLC in a modern chipmultiprocessor (CMP) is typically shared by all the cores. Processors use the shared caches more frequently; therefore, eviction of the shared data causes more cache misses^[13]. Thus, to efficiently utilize the shared LLC on a CMP, Sato et al. have proposed cache partitioning to protect the shared data by reducing unnecessary evictions [14]. This approach separates shared and private data and uses cache partitioning to give each type of data its own cache space. Several research works have been done on the partitioning of the shared LLC to improve system performance. But they all miss the heterogeneity in the spatial locality of different applications. Gupta et al. [15] showed how leveraging spatial locality allows significantly more effective cache sharing. They have highlighted that when large block size is used, the cache capacity requirements of many memory-intensive applications can be dramatically lowered, allowing them to give more capacity to other workloads effectively. In CMPs (Chip Multi Processors), private LLC provides a better access latency than shared caches. But more private caches result in replication of shared data, leading to under-utilization of total net capacity of cache, thus decreasing the overall hit ratio. A part of the work performed by Chen et al. on private and shared

caches highlight the above mentioned issues both in terms of performance and energy [16]. To handle the problem mentioned above, Yuan et al. have proposed a new cache management technique that improves the performance of a CMP using the private LLC [17]. Sibai et al. have discussed issues related to sharing and privatizing second and third-level cache memories in homogeneous Multi-Core architectures [18].

Although caches can significantly boost system performance, they use a considerable amount of overall system power. Chakraborty et al. [19] have analyzed the effect of LLC on the chip temperature, and they have proposed a new policy that resizes on-chip LLC at run time so that the leakage power consumption is reduced.

From the above literature works, we observed that the performance of the LLC concerning the Multi-Core processors was investigated in-depth. However the combined effect of sharing/partitioning both the L2 and LLC along with the effect of replacement needs further study. Finally, the performance of the LLC in the context of asymmetric multi-core processors has not received much attention. To fill this gap, we have done an extensive performance study of the LLC, primarily concentrating on the heterogeneity of the processors.

The unique features of our paper are as follows.

- 1. While [18] evaluates the performance of shared/private LLC for homogeneous Multi-Core processors, we concentrate on the same problem but for the case of heterogeneous Multi-Core architectures.
- 2. In most of the papers such as [12], the heterogeneity of the Multi-Core processors is introduced either by varying cache size or by varying block size. A unique feature of our paper is that we have introduced the heterogeneity by varying the core frequency as well as by varying the order of execution (either in-order or out-of-order execution).
- 3. Another novel feature of our work is that we have extensively studied the performance of different configurations of AMPs that differ by the way the L2 and LLC are partitioned and arrive at the optimal configuration.

3 Performance trade-off in Asymmetric Multi-Core Architectures (AMPs)

In this section, we study the performance trade-off in Asymmetric Multi-Core architecture. Considering both performance and power as primary concerns, we have implemented nine different configurations. In configurations 1 to 5, all cores are powerful cores with Out-of-order execution and an operating frequency of 2.66GHz. But in the configurations 6 to 9, we have introduced Asymmetricity by changing the order of execution of cores (In-order or Out-of-order) and the frequency of operation of each core (1GHz or 2.66GHz). In these configurations, cores 0-7 are In-order cores running at 1GHz, whereas 8-15 are Out-of-order cores running at 2.66GHz. When Out-of-order and In-order cores share a cache memory, there is a chance that Out-of-order cores may

Con former time	Lo Casha Datalla	La Carla Datalla	Come England
Configuration	L2 Cache Details	L3 Cache Details	Core Frequencies
Index			
Configuration 1	All 16 cores sharing	All 16 cores sharing	All 16 cores are Out-
	2048KB of $L2$ cache	8192KB of L3 Cache	of-order, running at
			2.66GHz
Configuration 2	Two sets of 8 cores	all cores sharing	All cores are Out-
	and each set sharing	8192KB of L3 Cache	of-order, running at
	1024KB of $L2$ cache		2.66GHz
Configuration 3	Four sets of 4 cores, and	all cores sharing	All cores are Out-
	each set sharing $512KB$	8192KB of L3 Cache	of-order, running at
	of L2 cache		2.66GHz
Configuration 4	Eight sets of 2 cores, and	all cores sharing	All cores are Out-
	each set sharing $256KB$	8192KB of L3 Cache	of-order, running at
	of L2 cache		2.66GHz
Configuration 5	Each core with private	all cores sharing	All cores are Out-
	L2 cache of $128KB$	8192KB of L3 Cache	of-order, running at
			2.66GHz
Configuration 6	Each core with private	Two sets of 8 cores and	Core $0 - 7$, in-order,
	L2 Cache of size $128KB$	each set sharing cache of	speed $1GHz$. Cores 8 –
		size $4096KB$	15 out-of-order, speed
			2.66GHz
Configuration 7	Each core with private	Four sets of 4 cores, and	Cores $0 - 7$, in-order,
	L2 Cache of size $128KB$	each set sharing Cache of	speed $1GHz$. Cores 8 –
		size $2048KB$	15 out-of-order, speed
			2.66GHz
Configuration 8	Each core with private	Eight sets of 2 cores, and	Cores $0 - 7$ in-order,
	L2 Cache of size $128KB$	each set sharing Cache of	speed $1GHz$. Cores 8 –
		size $1024KB$	15 out-of-order, speed
			2.66GHz
Configuration 9	Each core with private	each core with private	Cores $0 - 7$ in-order,
	L2 Cache of size $128KB$	L3 Cache of size $512KB$	speed $1GHz$, Cores 8 –
			15 out-of-order, speed
			2.66GHz

 Table 1: L2 and L3 Cache details for different Configurations

occupy a large portion of the cache, which further degrades the performance of In-order cores running at a lower frequency. So we gradually partitioned the LLC among the cores from fully shared to fully private. The remaining details of all the nine configurations are given in Table 1. The architecture used for our study, along with the corresponding simulation setup, is as given below.

3.1 Architecture Studied

We have referred to the Nehalem architecture [20], one of the most successful processor architectures introduced by *Intel*. Nehalem has scalable performance for from 1 to 16 (or more) threads and from 1 to 8 (or more) cores. It contains scalable and configurable system interconnects and also contains an integrated memory controller. The three-level cache hierarchy of this microarchitecture which is shown in Fig 1 consists of 64KB of L1 cache with 32KB of data cache and 32KB of the instruction cache. Further, it has 256KB of L2 cache per core (private cache) for handling data and instructions. Finally, it has a fully inclusive and fully shared LLC of size 8MB where all applications can use the entire cache. Nehalem has a more out-of-order window and scheduler size, which helps it identify more independent operations that can run in parallel. It also has larger-sized buffers in the core to ensure that they do not limit the performance.



Fig. 1: Cache hierarchy of Nehalem architecture with 4 cores

3.2 Simulator and Workloads used

We have used *Sniper* v7.3 simulator for our study [21]. It is an accurate high-speed X86 based simulator suitable for exploring different heterogeneous Multi-Core architectures. This simulator also provides us high-speed timing simulations for the multi-threaded, multi-program workloads and sharedmemory applications. We have used five different workloads in this study from the PARSEC Benchmarks Suite [22] and SPLASH2 Benchmark Suite [23]. They are PARSEC-Bodytrack, PARSEC-frequine, SPLASH2-barnes, PARSEC-fluidanimate, and SPLASH2-radiosity. Further *McPAT* (Multicore Power, Area, and Timing) framework is integrated with Sniper for modeling the power and area aspects of many-core architectures. We have used McPAT v1.0 [24] in this study to get the different power consumption values of the processor.

3.3 Simulation Results

We have simulated all nine different configurations in the initial stage as mentioned in Table 1. We compared all these configurations using their L2 miss rate, L3 miss rate, and total power consumption as the metrics for comparison. The consolidated results are given in Tables 3,4 and presented separately in the sub-figures of Fig 2 (a), (b) and (c) for better understanding. Except for L2 and L3 Cache levels, all the remaining parameters are common in all the configurations, which are as mentioned in Table 2

From Fig. 2a, we observe that from configuration 1 to configuration 5, the L2 cache is changing from fully shared among all cores to fully private to each core. When we have more private caches, the chance of coherence misses is more, which increases the miss rate. Hence L2 Miss rate is increasing when

7

Number of Cores	16
Block Size	64 Bytes
Cache Coherence Protocol	MESI
Replacement Policy	LRU
L1 size	32KB(I), 32KB(D)
L1 shared cores	1 (private to each core)
L1 Associativity	8(D), 4(I)
L2 Size	2048KB (Total)
L2 Associativity	8
L3 Size	8192KB (Total)
L3 Associativity	16

 Table 2: Configuration details

moving from fully shared to fully private caches. But L2 cache is private to each core from configuration 5 to configuration 9, where the miss rate is almost the same.

Total L2 Misses / Total L2Miss Configuration L2Index Accesses rate Configuration 1 1,775,452/32,658,5145.43Configuration 2 2,414,712/23,034,264 10.48 $\overline{3.464,822/24,173,825}$ Configuration 3 14.33 Configuration 4 5,413,832/20,838,462 25.98Configuration 5 17,851,930/20,985,015 85.06Configuration 6 17,945,030/20,985,015 85.36Configuration 7 18, 105, 468/21, 045, 636 85.99 18,096,468/21,045,663 Configuration 8 85.99 Configuration 9 18,013,786/20,914,704 86.13

 Table 3: L2 cache Miss rate for all configurations

Table 4: L3 cache Miss rate and Power for all configurations

Configuration	Total $L3$ misses/Total $L3$	L3 Miss	Total
Index	Accesses	rate $(\%)$	Power (W)
Configuration 1	83, 872/1, 792, 716	4.67	275.238
Configuration 2	87, 401/2, 430, 864	3.59	275.449
Configuration 3	87, 561/3, 481, 529	2.51	274.293
Configuration 4	82,067/5,435,954	1.51	273.325
Configuration 5	85,948/17,871,357	0.48	273.718
Configuration 6	169, 125/17, 984, 595	0.94	263.471
Configuration 7	309, 358/18, 176, 373	1.7	265.63
Configuration 8	527,606/18,178,885	2.9	268.418
Configuration 9	1,033,091/18,161,730	5.688	270.978

From Fig. 2b, we can observe that when as we go from configuration 1 to 5, the L3 miss rate is decreasing even if the L3 cache is shared in all these cases. If we observe the number of total misses to the L3 cache in configurations 1 to 5 in the Table 4, they are almost the same. Due to the increasing miss rate of L2, the number of accesses to the L3 cache increases, reducing the overall L3 miss rate. L3 cache is changing from a fully shared cache to a fully private cache in configurations 5 to 9, increasing the miss rate due to increased data inconsistency (coherent misses). In addition, when the number of private



Fig. 2: Performance trade-off in Heterogeneous Multi-Core Architecture

caches is increased, there is a chance for replicating the same data, which also increases the total miss rate due to inefficient utilization of net cache capacity.

From Fig. 2c, we observe that in Configurations 1 to 5, all cores are running at 2.66GHz (Out-of-Order), so the total power consumed is almost the same in all the cases. But configurations 6 to 9 have eight cores running at 1GHz (Inorder), and the other eight cores are running at 2.66GHz (Out-of-order), which gives low power consumption. So the power consumption is reduced when we go for asymmetric Multi-Cores. However, as we go from configurations 5 to 9, the power consumption increases due to the increase in L3 miss rate, resulting in power-intensive off-chip main memory access.

3.3.1 Configurations 1, 6, 9 with different replacement policies and with different workloads

In section 3.3, we have encountered a trade-off between L3 miss rate and total power consumption of Asymmetric Multi-Core architecture. Using configuration 1, configuration 6, and configuration 9, we want to investigate this trade-off further with three different replacement policies (LRU, MRU, Round Robin) using five different workloads (PARSEC-bodytrack, PARSEC-frequine, SPLASH2-barnes, PARSEC-fluidanimate, SPLASH2-radiosity). We have examined the L2 miss rate, L3 miss rate, and total power consumption

in configurations 1,6,9 with the five different workloads mentioned above. Corresponding results for the above mentioned simulation using three different replacement policies are shown in Fig. 3 (LRU case), Fig. 4 (MRU case) and Fig. 5 (Round Robin case).



Fig. 3: Configurations 1, 6, 9 with LRU replacement policy

Configuration 6 is better for both in terms of L3 miss rate and power. We observe that a trade-off exists between the L3 miss rate and total power consumption from the above figure. Independent of the replacement policy and the workloads used when we go from configuration 1 to configuration 9, total power consumption decreases significantly in all the cases, but the L3 miss rate increases. The LRU and Round Robin replacement policies give a better L2 miss rate when compared to the MRU policy. But we need to consider the L3 misses over the L2 misses because the misses to the L3 cache go to the main memory, increasing the overall latency and energy consumption.

For the LRU replacement policy, when the configuration is changed from 1 to 6, the L3 miss rate and power consumption are reduced by 11.6% and 9.058%, respectively. Further, when the configuration changes from 6 to 9, both the L3 miss rate and power consumption increase by 27.25% and 3.06%, respectively. When the configuration is changed from 1 to 9, the L3 miss rate increases



10 Performance study of Partitioned Caches in Asymmetric Multi-Core processors

Fig. 4: Configurations 1, 6, 9 with MRU Replacement policy

by 13.25%, and power consumption reduces by 6.28%. In MRU replacement policy, from configuration 1 to configuration 6, L3 miss rate reduces by 14.2%, and power consumption reduces by 11.752%. Later from configuration 6 to configuration 9, both the L3 miss rate and power consumption increases by 32% and 2.75% respectively. From configuration 1 to configuration 9, the L3 miss rate is increased by 20.25%, and power consumption is reduced by 9.3%. In the Round Robin replacement policy, from configuration 1 to configuration 6, the L3 miss rate is reduced by 7.6%, and 10.81% reduction is observed for power consumption. From configuration 6 to configuration 9, the L3 miss rate increases by 28%, and power consumption increases by 3.668%. From configuration 1 to configuration 9, the L3 miss rate increases by 20.4%, and power consumption is reduced by 7.704%.

4 Inference and Conclusions

This paper has done a performance study of shared LLC exploiting the heterogeneity for the Asymmetric Multi-Core architecture. We started our investigation by understanding the metrics that significantly affect the L2 and LLCs by varying the parameters such as Cache size and associativity against different replacement strategies. We realized that replacement policy plays a



Fig. 5: Configuration 1, 6, 9 with Round Robin Replacement policies

significant impact on overall cache performance. From our first part of the study, we observe that an increase in cache size and degree of associativity improves the hit rate of a cache. But we see that the improvement in hit rate is not the same in all the cases. So we can say that cache hit rate not only depends on its parameters like cache size, associativity, block size, etc. But also depend upon the replacement policy that we are using and the different memory access patterns that the given workload follows. In the second part of our

Table 5: Comparision results for all configurations

Configuration	L3 miss rate	Power Consumption
Configuration 1 to 6	11.3% (Decrease)	10.54% (Decrease)
Configuration 6 to 9	29.08% (Increase)	3.154% (Increase)
Configuration 1 to 9	17.9% (Increase)	7.761% (Decrease)

work, we understand Cache Hierarchy and simulate the AMP Architecture. We inculcated the heterogeneity in our 16 core AMP by varying the individual core operating frequency and the method of execution, that is, whether the core is In-order or Out-of-order. It is crucial to mention beforehand that throughout our investigation of AMPs and their cache performance, the DVFS

(Dynamic Voltage and Frequency Scaling) is kept enabled. We observe that the power variations in our results must not be considered on absolute terms; instead, they should be regarded as relative to each architecture. We begin our simulations with all cores operating on the same frequency, with each core sharing both the L2 and LL caches also have Out-of-order execution. Then we gradually partition the caches such that they are private to each core and make some cores simpler, like lowering the frequency values and making them In-order to save on power. Our investigation showed that Configuration 6 is an optimal choice as it saves power compared to Configuration 1 and has the best LL miss rate. As we know that off-chip memory accesses usually consume more latency than on-chip memory accesses.

We tested our architectures on multi-threaded PARSEC and SPLASH2 benchmarks to have a real-world understanding. From Section 3.3.1, we have observed that on average, from configuration 1 to configuration 9, there is a 17.9% increase in L3 miss rate and 7.761% decrease in power consumption. We further observe from configuration 1 to configuration 6 that both the L3 miss rate and power consumption reduces by 11.14% and 10.54% respectively. In contrast, from configuration 6 to configuration 9, the L3 miss rate increases by 17.9%, and power consumption increases by 3.154%. So configuration 6 is giving a better performance as well as power. The above-mentioned comparison results for all the configurations are listed down in Table. 5.

An immediate next step to our work could be to increase the number of cores and bring more levels of heterogeneity in the system, such as flexible cache designs, varying the reorder buffer sizes, and propose many more optimizations.

Funding: This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

Informed Consent: Not Applicable to this article.

Conflict of Interest: On behalf of all authors, the corresponding author states that there is no conflict of interest.

Data Availability Statement: All data generated or analysed during the study are included in this article.

Author Contribution:

Murali Dadi: Conception and design of the study, Analysis and/or interpretation of data, Writing – original draft, Writing – review & editing.

Shubhang Pandey: Conception and design of study, Analysis and/or interpretation of data, Writing – original draft, Writing – review & editing.

Aparna Behera: Conception and design of study, Analysis and/or interpretation of data, Writing – original draft, Writing – review & editing.

TG Venkatesh: Conception and design of study, Analysis and/or interpretation of data, Writing – original draft, Writing – review & editing.

References

 Martin, C.: Multicore Processors: Challenges, Opportunities, Emerging Trends

- [2] Jamet, A.V., Alvarez, L., Jimenez, D.A., Casas, M.: Characterizing the impact of last-level cache replacement policies on big-data workloads. 2020 IEEE International Symposium on Workload Characterization (IISWC) (2020). https://doi.org/10.1109/iiswc50251.2020.00022
- Kharbutli, M., Solihin, Y.: Counter-based cache replacement and bypassing algorithms. IEEE Transactions on Computers 57(4), 433–447 (2008). https://doi.org/10.1109/tc.2007.70816
- [4] Lin, I.-C., Chiou, J.-N.: High-endurance hybrid cache design in cmp architecture with cache partitioning and access-aware policies. IEEE Transactions on Very Large Scale Integration (VLSI) Systems 23(10), 2149–2161 (2015). https://doi.org/10.1109/tvlsi.2014.2361150
- [5] Ferrerón, A., Alastruey-Benedé, J., Gracia, D.S., Arnal, T.M., Marín, P.I., Yúfera, V.V.: A fault-tolerant last level cache for cmps operating at ultralow voltage. Journal of Parallel and Distributed Computing 125, 31–44 (2019). https://doi.org/10.1016/j.jpdc.2018.10.010
- [6] Montaner, H., Silla, F., Fröning, H., Duato, J.: A new degree of freedom for memory allocation in clusters. Cluster Computing 15(2), 101–123 (2012)
- [7] Peneau, P.-Y., Novo, D., Bruguier, F., Sassatelli, G., Gamatie, A.: Performance and energy assessment of last-level cache replacement policies. 2017 First International Conference on Embedded & Distributed Systems (EDiS) (2017). https://doi.org/10.1109/edis.2017.8284032
- [8] Ramtake, D., Singh, N., Kumar, S., Patle, V.K.: Cache associativity analysis of multicore systems. 2020 International Conference on Computer Science, Engineering and Applications (ICCSEA) (2020). https: //doi.org/10.1109/iccsea49143.2020.9132884
- [9] Wu, Q., Ji, Z.: A Perceptron-based Replication Scheme for Managing the Shared Last Level Cache. Microprocessors and Microsystems, 104310 (2021). https://doi.org/10.1016/j.micpro.2021.104310
- [10] Jang, G., Gaudiot, J.-L.: Data shepherding: A last level cache design for large scale chips. 2019 IEEE 21st International Conference on High Performance Computing and Communications; IEEE 17th International Conference on Smart City; IEEE 5th International Conference on Data Science and Systems (HPCC/SmartCity/DSS) (2019). https://doi.org/ 10.1109/hpcc/smartcity/dss.2019.00265
- [11] Anandkumar, K.m., Akash, S., Ganesh, D., Christy, M.S.: A hybrid cache replacement policy for heterogeneous multi-cores. 2014 International Conference on Advances in Computing, Communications and Informatics (ICACCI) (2014). https://doi.org/10.1109/icacci.2014.6968209

- 14 Performance study of Partitioned Caches in Asymmetric Multi-Core processors
- [12] Silva, B.D.A., Cuminato, L.A., Bonato, V.: Reducing the overall cache miss rate using different cache sizes for heterogeneous multi-core processors. 2012 International Conference on Reconfigurable Computing and FPGAs (2012). https://doi.org/10.1109/reconfig.2012.6416783
- [13] Ling, M., Lu, X., Wang, G., Ge, J.: Analytical modeling the multi-core shared cache behavior with considerations of data-sharing and coherence. IEEE Access 9, 17728–17743 (2021). https://doi.org/10.1109/access.2021. 3053350
- [14] Sato, M., Nishimura, S., Egawa, R., Takizawa, H., Kobayashi, H.: A cache partitioning mechanism to protect shared data for cmps. 2016 IEEE Symposium in Low-Power and High-Speed Chips (COOL CHIPS XIX) (2016). https://doi.org/10.1109/coolchips.2016.7503674
- [15] Gupta, S., Zhou, H.: Spatial locality-aware cache partitioning for effective cache sharing. 2015 44th International Conference on Parallel Processing (2015). https://doi.org/10.1109/icpp.2015.24
- [16] Chen, C.-W., Hsia, A., Zhan, Y.-W., Liu, T.-J.: Energy-efficient hybrid coherence protocol for multicore processors. Cluster Computing 21(3), 1521–1541 (2018)
- [17] Yuan, F., Ji, Z.: Replication-aware cache management for cmps with private llcs. 2016 2nd IEEE International Conference on Computer and Communications (ICCC) (2016). https://doi.org/10.1109/compcomm. 2016.7925214
- [18] Sibai, F.: On the performance benefits of sharing and privatizing second and third-level cache memories in homogeneous multi-core architectures. Microprocessors and Microsystems **32**, 405–412 (2008). https://doi.org/ 10.1016/j.micpro.2008.06.002
- [19] Chakraborty, S., Kapoor, H.K.: Analysing the role of last level caches in controlling chip temperature. IEEE Transactions on Sustainable Computing 3(4), 289–305 (2018). https://doi.org/10.1109/tsusc.2018.2823542
- [20] Singhal, R.: Inside Intel® Core Microarchitecture (nehalem). IEEE
- [21] Carlson, T.E., Heirman, W., Eyerman, S., Hur, I., Eeckhout, L.: An evaluation of high-level mechanistic core models. ACM Transactions on Architecture and Code Optimization (TACO) (2014). https://doi.org/10. 1145/2629677
- [22] Bienia, C., et al.: The PARSEC Benchmark Suite: Characterization and Architectural Implications

- [23] Woo, S.C., et al.: The SPLASH-2 Programs: Characterization and Methodological Considerations
- [24] Li, S., Ahn, J.H., Strong, R.D., Brockman, J.B., Tullsen, D.M., Jouppi, N.P.: The McPAT Framework for Multicore and Manycore Architectures. ACM Transactions on Architecture and Code Optimization 10(1), 1–29 (2013). https://doi.org/10.1145/2445572.2445577