MParrotTTS: Multilingual Multi-speaker Text to Speech Synthesis in Low Resource Setting

Neil Shah^{1,2}, Vishal Tambrahalli¹, Saiteja Kosgi¹, Niranjan Pedanekar², Vineet Gandhi¹

¹Kohli Centre on Intelligent Systems, IIIT Hyderabad, India ²TCS Research, Pune, India

Abstract

We present MParrotTTS, a unified multilingual, multi-speaker text-to-speech (TTS) synthesis model that can produce highquality speech. Benefiting from a modularized training paradigm exploiting self-supervised speech representations, MParrotTTS adapts to a new language with minimal supervised data and generalizes to languages not seen while training the self-supervised backbone. Moreover, without training on any bilingual or parallel examples, MParrotTTS can transfer voices across languages while preserving the speaker-specific characteristics, e.g., synthesizing fluent Hindi speech using a French speaker's voice and accent. We present extensive results on six languages in terms of speech naturalness and speaker similarity in parallel and cross-lingual synthesis. The proposed model outperforms the state-of-the-art multilingual TTS models and baselines, using only a small fraction of supervised training data. Speech samples from our model can be found at https://paper2438.github.io/tts/

Index Terms: multilingual, multi-speaker, text-to-speech synthesis, self-supervised learning

1. Introduction

"With languages, you are at home anywhere."

- Edward De Waal

Our work focuses on a unified Text-to-Speech (TTS) system that can communicate using various languages (multilingual) and different voices (multispeaker), facilitating crosslanguage synthesis, i.e., allowing multiple languages to be spoken in each of the speaker's voices. We aim to accomplish this objective by utilizing limited supervised data, enabling adaptation to languages with limited resources. The most straightforward way to obtain such a TTS (text-to-speech) model is to train it with a multilingual speech dataset for every speaker involved. However, even with rich-resource languages (RRLs), such data is not available, as it is hard to find speakers with native proficiency in several languages. Training multilingual TTS faces various other challenges, such as the need for distinct input representations or pronunciations and uneven distribution of training data across languages.

Previous work has addressed these challenges in various ways. One of the primary ideas is to learn multilingual TTS by explicitly conditioning the decoder on learnable language and speaker embeddings [1, 2]. Speaker embeddings are sometimes obtained using a pre-trained speaker verification network. Additional embeddings capturing other properties like tone have also been utilized [1]. However, the quality remains below par if the text representation is entangled with speaker or the language information, specially when only a few speakers are



Figure 1: Illustration of MParrotTTS framework. (a) MParrotTTS architecture. The Speech Encoder is a pre-trained network, whereas Text encoder and Speech decoder are trainable networks. The speech decoder is trained from unpaired raw audio. (b) MParrotTTS uses a non-autoregressive text-encoder, shared across all languages.

used for each language. For this reason, several recent methods attempt to disentangle the text representation from language and speech information. Disentanglement is typically attained by back-propagating reverse gradients through an explicit language or speaker classification branch [2, 3, 4].

Nekvinda and Dušek [4] propose Meta-TTS, which uses a contextual parameter generation using language-specific convolutional text encoders. Cho *et al.* [3] build upon Meta-TTS by employing an additional speaker regularization loss. They also investigate the effect of using different formats for the textual input (phoneme, character, etc.). Some efforts have explored aspects of knowledge sharing [5] and knowledge distillation [6] for multilingual TTS. More recently, Wu *et al.* [7] uses a data augmentation technique based on a pre-trained voice conversion model to generate insufficient paired data for a pre-selected set of languages.

Despite the fact that the aforementioned endeavors have played a crucial role in expanding the realm of multilingual TTS, there are still certain limitations that persist. The majority of them [4, 8, 2, 9] rely on Tacotron [10] as their backbone, which is known to suffer from word alignment and word skipping/repetition errors. As pointed out by Nekvinda and Dušek [4], most prior multilingual TTS models limit to 2-3 languages simultaneously or require vast amounts of data to be trained. Furthermore, the training remains challenging in lowresource settings, especially in the absence of paired data from multiple speakers in each language.

In this work, we propose MParrotTTS, which exploits the recent success in self-supervised audio representations [11] to address the aforementioned limitations. MParrotTTSarchitecture is illustrated in Figure 1; in the first self-supervised phase

of training, a speech-encoder converts audio into discretized sound units, which are then reconstructed back to audio using a speech-decoder. In the second phase, a text encoder maps the input text sequence to a sequence of discrete sound units corresponding to the paired audio. We use HuBERT [12, 11] based embeddings as the self-supervised representation which has proven successful in Speech-to-Speech translation tasks [13, 14]. A significant advantage of using HuBERT-based embeddings is that they ignore speaker and acoustic information and encode only the speech content [13]. This characteristic is a boon in a low-resource setting, allowing the text-encoder to be trained on a small amount of paired data from a single speaker. Other benefits encompass the ability to handle audio noise during training and simplified training, eliminating the necessity for domain adversarial training [3, 15]. MParrotTTSalso employs knowledge sharing by training a unified text-encoder for multiple languages, where we explore character and phonemebased inputs.

MParrotTTSworks in extremely low resource regime [6] and we show that using 5 hours of single speaker paired data for each language is sufficient for training the unified model, capable of synthesizing high-quality speech corresponding to any unseen text on each of the seen language and the speaker. We show that MParrotTTScan generate high-fidelity speech for multiple voices from several European and Indic datasets, whose paired data is not used in training the model in any of the six languages explored in our study. Interestingly, MParrotTTSworks well even for languages unseen during the selfsupervised audio representation learning.

2. Method

The proposed MParrotTTSis shown in Figure 1. It consists of three modules, a speech-encoder, a text-encoder, and a speech-decoder. We adopt the speech-encoder and speech-decoder from [13]. The speech-encoder is mHuBERT [11], which maps the input speech signal to discrete sound units, and the speech-decoder is HiFiGAN [16], which converts the discrete sound units to audio signal. The text-encoder is a Non-autoregressive (NAR) encoder-decoder module that maps the input text representation to the sound units.

2.1. Text representation

Representing text from a set of various languages poses a challenge. Traditionally, end-to-end single language TTS models have used either characters [10] or phonemes [17, 18] as input text representation. In this paper, we separately evaluate the effects of using these representations to train the text encoder under a multilingual scenario. For a character representation, we extract the tokens using a dictionary created by iterating over the entire text corpus. In contrast, for phoneme representation, we utilize an off-the-shelf phonemizer [19] to extract phonemes belonging to the IPA vocabulary, which are common across languages. A benefit of this step is that the model is languageagnostic, as the model sees the common phonemes across the languages.

2.2. Speech-encoder

We use a pre-trained mHuBERT [11] as our speech-encoder \mathbf{E}_s , which is trained on speech-only data to generate discrete sound units. The model is trained using a Masked Language Model (MLM) loss similar to BERT [20] architecture. mHuBERT is pre-trained on multiple languages showing the model's capabil-

ity to capture sound units across the languages and generalize to new unseen languages. We also experimented with original Hu-BERT [12] embeddings and found that mHuBERT fares better in the studied multilingual scenario. For a given audio signal X, the speech embedding sequence h_s are computed with the speech-encoder as:

$$\mathbf{h}_s = (h_1, \dots, h_{\widehat{T}}) \coloneqq \mathbf{E}_s(X),\tag{1}$$

Where $X = (x_1, x_2, ..., x_T)$ is an input speech signal, $\hat{T} = T/320$ indicates down-sampling of the audio signal. The sound units $h_i \in \{1, ..., k\}$ where k = 1000 is the number of clusters in the mHuBERT's clustering step.

2.3. Text-encoder

Text-encoder \mathbf{E}_t is a NAR- based encoder-decoder architecture that maps text representations (character/phoneme tokens) $P = (p_1, p_2, .., p_N)$ to sound unit sequence \mathbf{h}_p , predicted as:

$$\mathbf{h}_p = (h_1, \dots, h_{\widehat{P}}) \coloneqq \mathbf{E}_t(P), \tag{2}$$

where \hat{P} is the number of sound units. The encoder and decoder are feed-forward transformer blocks with self-attention [21], and 1 dimensional convolutions similar to Fastspeech2 [17]. The encoder encodes the text representation P into a sequence of fixed dimensional token embeddings. These token embeddings are then passed to the duration predictor and length regulator to determine the output length \hat{P} . The decoder simultaneously predicts all \hat{P} units of \mathbf{h}_p . We note that our model's performance is not enhanced by conditioning the decoder with an additional language embedding, and as such, we choose to refrain from doing so. The text-encoder \mathbf{E}_t is trained to mimic its output \mathbf{h}_p to be similar to \mathbf{h}_s , sound units of corresponding audio signal extracted from a pre-trained \mathbf{E}_s speech-encoder. The text-encoder thus requires parallel data (P,X) to learn the mapping from text content to speech content.

2.4. Speech-decoder

We use a modified version of HiFiGAN [16] decoder to decode embeddings to speech. During training, we concatenate \mathbf{h}_s with a one-hot speaker vector \mathbf{h}_{spk} to generate $\mathbf{h} = (\mathbf{h}_s, \mathbf{h}_{spk})$. The speech-decoder has a generator G and a discriminator D. The generator G takes \mathbf{h} as an input and passes it through a series of transposed convolutions and residual blocks with dilation to generate a synthesized speech signal \hat{X} . The discriminator D has two sets of networks. The Multi-period discriminator handles the periodic portion of input audio, whereas the multi-scale discriminator captures long-term dependencies and patterns. Overall, the discriminator evaluates and distinguishes the synthesized \hat{X} from the original speech signal X.

3. Experiments

3.1. Dataset

We collate our multilingual dataset using various publicly available corpora containing samples from multiple speakers in six languages: (1) 80.76 hours of Hindi and Marathi [22] from 2 speakers, respectively; (2) 71.69 hours of German [23] from 3 speakers; (3) 83.01 hours of Spanish [23] from 3 speakers; (4) 10.70 hours of French [24] from 1 speaker; (5) 23.92 hours of English [25] from 1 speaker. Overall the dataset comprises of 354.12 hours of paired TTS data from 12 speakers. We resample all speech samples to $16 \ kHz$.

3.2. Speech-encoder training

We use a pretrained 12-layer transformer-based mHuBERT [11] architecture trained for 3 iterations on 13.5k hours of English, Spanish and French data from VoxPopuli unlabelled speech corpus [11, 26]. We extract a 768 dimensional continuous vector from the eleventh activation layer similar to [11]. These vectors are further discretized to \mathbf{h}_s units using a k-means clustering algorithm with k = 1000.

3.3. Text-encoder training

To demonstrate the efficacy of our model in a low-resource setting, we only use 5 hours of paired data for a single speaker in each language to train the text encoder (using mere 30 hours of paired data across all languages in total). We report the evaluation metrics for *seen speakers* where the model has seen the speaker paired data and *unseen speakers* whose paired data is not used to train the text-encoder.

To evaluate the performance of the TTS systems on various text representations, we train two variants of the text-encoder, the character text-encoder (CTE) and the phoneme text-encoder (PTE). The first variant uses character tokens across the languages to learn sound units, while the second uses phoneme tokens. Additionally, we employ Deep Forced Aligner [27] to align ground-truth speech and input text representations to train the duration predictor. We use cross-entropy loss with 1000 classes to predict h_p .

3.4. Speech-decoder training

We train a multi-speaker speech-decoder using speech-only data from all 12 speakers since training this model doesn't require any paired data. First, we extract the sound units \mathbf{h}_s from the source audio using the pre-trained speech-encoder \mathbf{E}_s . During decoder training, we concatenate the sound units \mathbf{h}_s with onehot speaker vector \mathbf{h}_{spk} . However, during inference, we pass the generated sound units \mathbf{h}_p from the text-encoder along with the target speaker's one-hot vector to synthesize speech.

3.5. Baseline models

We compare against the publicly available state-of-the-art multilingual TTS approaches. First, we train a fully supervised multi-lingual, multi-speaker FastSpeech2 (FS2) model [28]. We train the FastSpeech2 model on the entire dataset (approximately 12 times more paired data than MParrotTTS), seeing all the 12 speakers. Only 100 samples for each speaker are kept aside for validation of FastSpeech2 model.

We also compare against the Meta-TTS [4], a meta learning-based TTS model which uses language-specific contextual parameter generation. We use their released checkpoint and compare the naturalness of the synthesized speech on the shared set of languages. Specifically, we compare their model across the French, Spanish, and German languages.

Please note that both FS2 and Meta-TTS models are fully supervised; they use all the available paired text-speech pairs to train their end-to-end TTS. In contrast, MParrotTTS only uses a small portion of the paired data.

3.6. Evaluation metrics

We use the Mean Opinion Score (MOS) to evaluate the quality of synthesized speech, where the participants are asked to rate the samples based on their naturalness. The user is asked to rate the naturalness of the audio where 5 is "completely natural,"

 Table 1: Comparison of Naturalness MOS on seen speakers
 with FS2 model

Language	GT	СТЕ	PTE	FS2
Hindi	3.78 ± 0.14	$\textbf{3.33} \pm \textbf{0.19}$	3.22 ± 0.15	3.33 ± 0.12
Marathi	4.81 ± 0.07	$\textbf{3.78} \pm \textbf{0.12}$	3.04 ± 0.19	3.59 ± 0.15
German	3.54 ± 0.20	3.33 ± 0.19	$\textbf{3.58} \pm \textbf{0.12}$	3.21 ± 0.16
French	3.83 ± 0.19	2.23 ± 0.14	$\textbf{4.17} \pm \textbf{0.19}$	3.50 ± 0.16
English	4.20 ± 0.12	3.11 ± 0.11	$\textbf{3.50} \pm \textbf{0.10}$	2.50 ± 0.18
Spanish	3.67 ± 0.12	3.5 ± 0.21	$\textbf{3.67} \pm \textbf{0.20}$	2.50 ± 0.21

Table 2: Comparison of Naturalness MOS on unseen speakers with FS2 model

Language	GT	CTE	РТЕ	FS2
Hindi	4.22 ± 0.18	$\textbf{3.28} \pm \textbf{0.19}$	3.05 ± 0.20	3.22 ± 0.21
Marathi	4.48 ± 0.13	$\textbf{3.63} \pm \textbf{0.18}$	3.11 ± 0.18	3.15 ± 0.19
German	3.17 ± 0.22	2.72 ± 0.23	$\textbf{3.55} \pm \textbf{0.20}$	2.05 ± 0.22
Spanish	3.67 ± 0.19	3.17 ± 0.17	$\textbf{3.33} \pm \textbf{0.18}$	3.17 ± 0.19

and 1 is "completely unnatural". And to evaluate the model's ability to capture speaker information, we use speaker similarity MOS, where the participants rate the similarity of a synthesized sample with a ground truth sample from the same speaker. We also assess the model's performance in cross-lingual synthesis, where a speaker's voice in one language is used to synthesize content in a different language. In addition to evaluating the naturalness of the synthesized voice, participants were also requested to identify the native accent of the speaker. This experiment was conducted to assess the effectiveness of our proposed setup in preserving the nuances of the native speaker when speaking foreign content.

We conduct our evaluations using the Absolute category rating scale, in which the subjects are asked to provide ratings on a scale of 1 to 5, with a 1 point increment. We collect evaluations from five native speakers for each language across all the subjective listening tests. We randomly select five sentences from the test set, and each participant is asked to rate the samples synthesized using our model and the baseline model along with the ground truth audio. For English and French languages, we only use single speaker data; hence we exclude these two languages as part of *unseen speaker* evaluation.

4. Results and Discussion

Naturalness MOS Based on the results presented in Table 1 and Table 2, our model demonstrates significantly superior performance compared to a multilingual FS2 model. Notably, our model's success is even more impressive considering that it was trained on only a fraction, specifically 1/12th, of the paired data used to train the FS2 model. This indicates the viability of MParrotTTS in a low-resource scenario where collecting paired data is difficult and costly. We also observe that the naturalness in different languages varies with the input text representation. For Indic languages (Hindi and Marathi), representing the text in characters (CTE) performs better than phonemes (PTE). Whereas for English and the European Languages (German, French, and Spanish), phoneme representation PTE serves better. With the appropriate choice of tokenization scheme (CTE or PTE), our model consistently outperforms FS2 on both seen and unseen speakers, even though no paired data is used for unseen speakers. Another interesting observation is that for some of the European languages MParrotTTS fares better than the ground

 Table 3: Comparison of Naturalness MOS with Meta-TTS model

Language	Our model	Meta-TTS [4]
French Spanish German	$\begin{array}{c} \textbf{4.08} \pm \textbf{0.19} \\ \textbf{3.75} \pm \textbf{0.16} \\ \textbf{3.33} \pm \textbf{0.19} \end{array}$	$\begin{array}{c} 2.58 \pm 0.18 \\ 3.00 \pm 0.20 \\ \textbf{3.50} \pm \textbf{0.18} \end{array}$

Table 4: Comparison of speaker similarity MOS with FS2 model

Language	Our model	FS2
Hindi	4.29 ± 0.18	3.92 ± 0.21
Marathi	4.21 ± 0.16	3.83 ± 0.08
German	4.09 ± 0.11	3.25 ± 0.14
French	3.87 ± 0.20	3.50 ± 0.19
English	3.94 ± 0.18	3.00 ± 0.19
Spanish	4.33 ± 0.17	3.50 ± 0.19

truth. We believe the noise in the ground-truth data hampers its naturalness score. Since mHubert embeddings ignore/suppress the ambient information, it imparts noise robustness to MParrotTTS, improving the naturalness over the ground-truth audio in noisy scenarios.

Table 3 includes our findings on the naturalness of MParrotTTS as assessed by MOS scores, when compared against the Meta-TTS model on the shared set of languages (French, Spanish, and German). While our model gives comparable results for German, it significantly outperforms Meta-TTS in French and Spanish. The MOS scores for German remain low for MParrotTTS because of low-quality training data (even ground truth MOS scores are low in Table 1 and Table 2). Meta-TTS uses 20 hours of paired data from 40 German speakers for their training. They also perform extensive pre-processing, which includes careful data selection methods. As our model is intended to operate in a low-resource setting where gathering paired data poses a challenge, we refrain from applying any data-cleaning techniques and limit the text-encoder training to five hours of noisy data from a single speaker.

Speaker Similarity We conducted a comparative analysis of our model's ability to capture speaker identity as opposed to that of the FS2 model. Speaker similarity is reported on a scale of 1 to 5, where 1 corresponds to "Not at all similar," and 5 corresponds to "extremely similar". Our results, presented in Table 4, consistently demonstrate the superiority of our model over FS2, indicating its effectiveness in separating speaker and content information. This is attributed to the decoder being conditioned solely on speaker ID and the shared sound unit space, which is common across all languages.

Cross lingual synthesis We also assess the model's performance in synthesizing the samples of a speaker in a different language. Table 5 presents the results of a study that compares the naturalness of MOS in a cross-lingual setting. The first column shows the speaker-text pair, where the speaker of a native language attempts to speak a different non-native language. We report the MOS scores for a few speaker-text pairs.

Our model exhibits significantly higher ratings than FS2, demonstrating the flexibility of our model to generate sound units from any given text and synthesize speech for any target speaker of a different native language. In addition, more than 90 % of the participants were able to discern the nativity of the

 Table 5: Comparison of Naturalness MOS for cross-lingual speech synthesis

Speaker-Text	Our model	FS2
Hindi-Spanish	3.87 ± 0.22	3.25 ± 0.19
Marathi-English	3.63 ± 0.21	3.5 ± 0.22
French-Hindi	4.07 ± 0.12	2.71 ± 0.21
Spanish-German	4.14 ± 0.20	2.29 ± 0.21
English-German	3.57 ± 0.15	2.43 ± 0.18
English-Hindi	3.57 ± 0.19	2.57 ± 0.18
French-German	3.93 ± 0.17	2.71 ± 0.18
Spanish-French	3.71 ± 0.18	2.57 ± 0.17
Hindi-Marathi	4.13 ± 0.21	3.25 ± 0.19
Marathi-French	2.87 ± 0.19	2.75 ± 0.18

synthesized speech produced by both the models.

Collectively, our findings indicate that MParrotTTS possesses the ability to produce high-quality, multilingual, and multi-speaker speech that effectively captures the distinctive characteristics of individual speakers, even when synthesized for a different language.

5. Conclusion

In this paper, we present MParrotTTS, a unified multilingual self-supervised learning-based text-to-speech (TTS) synthesis framework that has the significant potential to enhance the TTS capability on low-resource languages. We demonstrate that high-fidelity speech can be obtained by utilizing a minimal amount of single-speaker training data per language. Our approach enables generalization to various voices within a particular language without requiring paired data for each voice. The experimental findings have shown that the quality of speech synthesis is significantly influenced by the text representations used, such as characters or phonemes, particularly in diverse linguistic contexts. Our experimental outcomes have revealed that our model outperformed the baseline FastSpeech2 and Meta-TTS models, in terms of naturalness and speaker similarity. In addition, our method has effectively showcased the ability for cross-language synthesis (to produce speech in a language that is not native) while maintaining the speaker-specific nuances and delivery style.

One limitation of our approach is that the duration predictor in the non-autoregressive model might lean towards the style of the single seen speaker. Future research will investigate methods to obtain speaker adaptive duration prediction or allow levers to control the duration prediction. Our current self-supervised backbone is trained on limited set of languages. A direction of future exploration would be to fine-tune selfsupervised HuBert-based embeddings using the raw audio from a diverse set of languages (South Asian, Latin, English, etc.) to have a more comprehensive quantized code set of sound units. Another area of future work will be releasing an open-source, multilingual TTS model, allowing the community to apply the investigated ideas to other resource-scarce, less studied, and less privileged languages.

6. References

 Z. Liu and B. Mak, "Cross-lingual multi-speaker text-to-speech synthesis for voice cloning without using parallel corpus for unseen speakers," *arXiv preprint arXiv:1911.11601*, 2019.

- [2] Y. Zhang, R. J. Weiss, H. Zen, Y. Wu, Z. Chen, R. Skerry-Ryan, Y. Jia, A. Rosenberg, and B. Ramabhadran, "Learning to Speak Fluently in a Foreign Language: Multilingual Speech Synthesis and Cross-Language Voice Cloning," in *Proc. Interspeech 2019*, 2019, pp. 2080–2084.
- [3] H. Cho, W. Jung, J. Lee, and S. H. Woo, "SANE-TTS: Stable And Natural End-to-End Multilingual Text-to-Speech," in *Proc. Interspeech* 2022, 2022, pp. 1–5.
- [4] T. Nekvinda and O. Dušek, "One Model, Many Languages: Meta-Learning for Multilingual Text-to-Speech," in *Proc. Interspeech* 2020, 2020, pp. 2972–2976.
- [5] A. Prakash, A. L. Thomas, S. Umesh, and H. A. Murthy, "Building multilingual end-to-end speech synthesisers for indian languages," in *Proc. of 10th ISCA Speech Synthesis Workshop* (SSW'10), 2019, pp. 194–199.
- [6] J. Xu, X. Tan, Y. Ren, T. Qin, J. Li, S. Zhao, and T.-Y. Liu, "Lrspeech: Extremely low-resource speech synthesis and recognition," in *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2020, pp. 2802–2812.
- [7] J. Wu, A. Polyak, Y. Taigman, J. Fong, P. Agrawal, and Q. He, "Multilingual text-to-speech training using cross language voice conversion and self-supervised learning of speech representations," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2022, pp. 8017–8021.
- [8] M. Chen, M. Chen, S. Liang, J. Ma, L. Chen, S. Wang, and J. Xiao, "Cross-lingual, multi-speaker text-to-speech synthesis using neural speaker embedding." in *Interspeech*, 2019, pp. 2105– 2109.
- [9] H. Zhang and Y. Lin, "Unsupervised Learning for Sequence-to-Sequence Text-to-Speech for Low-Resource Languages," in *Proc. Interspeech* 2020, 2020, pp. 3161–3165.
- [10] Y. Wang, R. Skerry-Ryan, D. Stanton, Y. Wu, R. J. Weiss, N. Jaitly, Z. Yang, Y. Xiao, Z. Chen, S. Bengio, Q. Le, Y. Agiomyrgiannakis, R. Clark, and R. A. Saurous, "Tacotron: Towards End-to-End Speech Synthesis," in *Proc. Interspeech* 2017, 2017, pp. 4006–4010.
- [11] A. Lee, H. Gong, P.-A. Duquenne, H. Schwenk, P.-J. Chen, C. Wang, S. Popuri, Y. Adi, J. Pino, J. Gu, and W.-N. Hsu, "Textless speech-to-speech translation on real data," in *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies.* Seattle, United States: Association for Computational Linguistics, Jul. 2022, pp. 860–872. [Online]. Available: https://aclanthology.org/2022. naacl-main.63
- [12] W.-N. Hsu, B. Bolte, Y.-H. H. Tsai, K. Lakhotia, R. Salakhutdinov, and A. Mohamed, "Hubert: Self-supervised speech representation learning by masked prediction of hidden units," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 29, pp. 3451–3460, 2021.
- [13] A. Polyak, Y. Adi, J. Copet, E. Kharitonov, K. Lakhotia, W.-N. Hsu, A. Mohamed, and E. Dupoux, "Speech Resynthesis from Discrete Disentangled Self-Supervised Representations," in *Proc. Interspeech 2021*, 2021, pp. 3615–3619.
- [14] Y. Jia, M. Tadmor Ramanovich, Q. Wang, and H. Zen, "CVSS corpus and massively multilingual speech-to-speech translation," in *Proceedings of the Thirteenth Language Resources and Evaluation Conference*. Marseille, France: European Language Resources Association, Jun. 2022, pp. 6691–6703. [Online]. Available: https://aclanthology.org/2022.lrec-1.720
- [15] Y. Ganin, E. Ustinova, H. Ajakan, P. Germain, H. Larochelle, F. Laviolette, M. Marchand, and V. Lempitsky, "Domainadversarial training of neural networks," *The journal of machine learning research*, vol. 17, no. 1, pp. 2096–2030, 2016.
- [16] J. Kong, J. Kim, and J. Bae, "Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis," *Advances in Neural Information Processing Systems*, vol. 33, pp. 17022– 17033, 2020.

- [17] Y. Ren, C. Hu, X. Tan, T. Qin, S. Zhao, Z. Zhao, and T.-Y. Liu, "Fastspeech 2: Fast and high-quality end-to-end text to speech," arXiv preprint arXiv:2006.04558, 2020.
- [18] I. Elias, H. Zen, J. Shen, Y. Zhang, Y. Jia, R. Skerry-Ryan, and Y. Wu, "Parallel Tacotron 2: A Non-Autoregressive Neural TTS Model with Differentiable Duration Modeling," in *Proc. Inter*speech 2021, 2021, pp. 141–145.
- [19] M. Bernard and H. Titeux, "Phonemizer: Text to phones transcription for multiple languages in python," *Journal of Open Source Software*, vol. 6, no. 68, p. 3958, 2021.
- [20] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of deep bidirectional transformers for language understanding," in *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Minneapolis, Minnesota: Association for Computational Linguistics, Jun. 2019, pp. 4171–4186. [Online]. Available: https://aclanthology.org/N19-1423
- [21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," *Advances in neural information processing systems*, vol. 30, 2017.
- [22] S. S. in INdian languages (SYSPIN), "Text-to-speech synthesizer in nine indian languages," https://syspin.iisc.ac.in/datasets, 2022.
- [23] M. A. I. L. GmbH., "The m-ailabs speech dataset," https://github. com/imdatsolak/m-ailabs-dataset, 2017.
- [24] P.-E. Honnet, A. Lazaridis, P. N. Garner, and J. Yamagishi, "The siwis french speech synthesis database? design and recording of a high quality french database for speech synthesis," Idiap, Tech. Rep., 2017.
- [25] K. Ito and L. Johnson, "The lj speech dataset," https://keithito. com/LJ-Speech-Dataset/, 2017.
- [26] C. Wang, M. Riviere, A. Lee, A. Wu, C. Talnikar, D. Haziza, M. Williamson, J. Pino, and E. Dupoux, "VoxPopuli: A largescale multilingual speech corpus for representation learning, semi-supervised learning and interpretation," in *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers).* Online: Association for Computational Linguistics, Aug. 2021, pp. 993–1003. [Online]. Available: https://aclanthology.org/2021. acl-long.80
- [27] S. S. in INdian languages (SYSPIN), "Deep forced alligner," https://github.com/bloodraven66/DeepForcedAligner, 2017.
- [28] C.-M. Chien, J.-H. Lin, C.-y. Huang, P.-c. Hsu, and H.-y. Lee, "Investigating on incorporating pretrained and learnable speaker representations for multi-speaker multi-style text-to-speech," in *ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2021, pp. 8588– 8592.