

DIAS: A Comprehensive Dataset and Benchmark for Intracranial Artery Segmentation in DSA sequences

Wentao Liu¹, Tong Tian³, Lemeng Wang¹, Weijin Xu¹, Haoyuan Li¹, Wenyi Zhao¹, Siyu Tian⁴, Xipeng Pan⁵, Huihua Yang^{1,5,*}, Feng Gaog^{2,*}, Yiming Deng², Ruisheng Su⁶

¹*School of Artificial Intelligence, Beijing University of Posts and Telecommunications, Beijing, China*

²*Department of Interventional Neuroradiology, Beijing Tiantan Hospital, Capital Medical University, Beijing, China*

³*State Key Laboratory of Structural Analysis, Optimization and CAE Software for Industrial Equipment, School of Aeronautics and Astronautics, Dalian University of Technology, Dalian, China*

⁴*Ultrasonic Department, The Fourth Hospital of Hebei Medical University and Hebei Tumor Hospital, Shijiazhuang, China*

⁵*School of Computer Science and Information Security, Guilin University of Electronic Technology, Guilin, China*

⁶*Department of Radiology & Nuclear Medicine, Erasmus MC, University Medical Center Rotterdam, The Netherlands*

liuwentao@bupt.edu.cn

Abstract—Digital subtraction angiography (DSA) is universally acknowledged as the gold standard for examining lesion angioarchitecture, elucidating arterial blood supply dynamics, and guiding endovascular interventions. The automatic segmentation of intracranial arteries (IA) in DSA, which is pivotal for quantifying vascular morphology, plays an essential role in computer-assisted stroke research and clinical practices. Nevertheless, research in this specific domain remains constrained, primarily owing to the unavailability of publicly datasets for IA segmentation within the research community. Currently, the predominant focus of methodologies lies in the segmentation of single-frame DSA using in-house datasets. These methods, limited by the partial inclusion of contrast in single-frame DSA, encounters challenges in rendering a precise representation of vascular structures. In this paper, we introduces DIAS, a dataset specifically developed for IA segmentation in DSA sequences. A comprehensive benchmark has been established for evaluating DIAS, covering fully, weakly, and semi-supervised segmentation methods. Specifically, we propose a vessel sequence segmentation network that captures the spatiotemporal representation of intravascular contrast for segmenting vessels in DSA sequences. For weakly-supervised learning, we propose a novel scribble learning-based image segmentation framework, incorporating both scribble supervision and consistency regularization. Furthermore, we introduce a random patch-based self-training framework that harnesses unlabeled DSA sequences to improve segmentation performance. Our extensive experiments on the DIAS dataset demonstrate the effectiveness of these methods as potential baselines for future research and clinical applications. The dataset and code will be publicly available at <https://github.com/lseventeen/DIAS>.

Index Terms—digital subtraction angiography, intracranial artery segmentation, dataset, semi-supervision learning, weakly supervision learning

This work was supported in part by the National Natural Science Foundation of China under Grant 62376038 and in part by the National Key Research and Development Program of China under Grant 2018AAA0102600.

I. INTRODUCTION

Cerebrovascular diseases significantly contribute to global mortality and long-term disability [1]. In recent decades, there has been a notable decline in the mortality rate associated with intracranial artery (IA) diseases, such as intracranial arterial stenosis (ICAS), middle cerebral artery occlusion (MCAO), and intracranial aneurysm, largely attributed to rapid advancements in medical and imaging technology [2]. Digital Subtraction Angiography (DSA), an imaging modality, visualizes the flow of a contrast agent through vessels by capturing a sequence of images over a duration typically spanning 3 to 15 seconds, with a sampling rate between 3 to 5 frames per second [3]. It removes bony structures by subtracting the pre-contrast image, thus preserving the vessels filled with contrast agent. Owing to its inherently superior spatial and temporal resolution, DSA can accurately elucidate lesion details in instances where computed tomography angiography (CTA) and magnetic resonance angiography (MRA) may not offer a definitive diagnosis [2]. Thus, DSA is widely recognized as the gold standard for investigating lesion angioarchitecture, deciphering the dynamics of arterial blood supply, and guiding endovascular intervention [4].

Conventionally, neuroradiologists undertake the visual analysis of DSA for diagnostic purposes, clinical decision-making, and postoperative assessment, which is inherently time-consuming, labor-intensive, and subjective. Automated segmentation of vessels DSA harbors the potential to mitigate this challenge by delineating vascular morphology. Currently, DSA-based cerebrovascular image segmentation finds utility in various downstream clinical applications, including automated thrombolysis in cerebral infarction scoring [5], 3D recon-




Fig. 1. A representative sample of intracranial vessels in sagittal view from DSA, where t to $t+5$ are consecutive frames of the arterial phase.

struction of vessel [6], and image guidance of interventional surgery [7]. Despite the undeniable significance of cerebrovascular segmentation in DSA, it remains an under-researched area. One possible reason is the current absence of a DSA dataset tailored specifically for the formulation and evaluation of cerebrovascular segmentation techniques in the medical imaging community. However, given the intrinsic attributes of its imaging modality, the task of creating a brain DSA vascular segmentation dataset is immensely challenging. Primarily, the DSA sequence presents a projection of intravascular contrast media from a consistent viewing angle, thereby visualizing only a fraction of the IA within the contrast agent in any given image, as illustrated in Fig. 1. In the process of annotating vessels within DSA, neuroradiologists are required to conduct a detailed examination of each image frame, which is both laborious and expensive [8]. Moreover, the intricate nature of cerebral vessels, characterized by overlapping structures in imagery, diminished contrast, and multifaceted background disturbances, accentuates the difficulties associated with annotation.

Currently, several segmentation approaches for DSA cerebral vessels have emerged [8]–[10]. Yet, all these efforts are anchored to proprietary datasets, absent a consistent evaluation benchmark. Furthermore, most of these methods [9], [10] are limited to single-frame image segmentation, overlooking the rich temporal characteristics inherent in DSA sequences. Segmentation methods based on single-frame DSA may not comprehensively capture the vascular intricacies of IA, potentially limiting their efficacy in diagnosing and treating cerebrovascular diseases [8]. In DSA sequences, vascular segmentation is characterized as a dimensionality-reduction task, taking a 2D+time image input to yield a 2D mask output. This task deviates from traditional 2D and 3D vascular segmentation methods [11]–[13]. The pivotal challenge lies in accurately capturing the spatiotemporal information present within the angiography for precise vessel segmentation.

In this work, we construct the DSA-sequence Intracranial Artery Segmentation dataset (DIAS), meticulously annotated at the pixel level by neurosurgeons. Given the intricate and labor-intensive nature of vessel annotation within DSA

sequences, we’ve provided two types of weak annotations for training samples, aiming to facilitate studies on weakly-supervised IA segmentation. For the DIAS, we have devised three benchmarks tailored for fully-supervised segmentation (FSS), weakly-supervised segmentation (WSS), and semi-supervised segmentation (SSS): the vessel sequence segmentation network, the scribble learning-based segmentation framework and the random patch-based self-training framework. We have carried out comprehensive experiments using the DIAS, establishing robust baselines that will serve as a foundation for future algorithmic comparisons on the DIAS dataset. We hope that the DIAS dataset could facilitate open research in cerebral vessel segmentation.

II. RELATED WORK

A. Vessel Segmentation Datasets

Vessel segmentation is a popular area of research within computer-aided medicine, which has witnessed remarkable progress in recent years, owing to technological advancements and the availability of high-quality annotated datasets. We have summarized the several publicly available vessel segmentation datasets in Table I. A representative example is retinal vessel segmentation, which has many publicly available datasets due to its easy availability, such as colour fundus datasets (DRIVE [14], CHASE_DB1 [15], STARE [16], HRF [17]) and OCTA datasets (ROSE1 and ROSE2 [18]). These datasets consist of 20–117 2D images with spatial resolution ranging from 304×304 to 3504×2336 . However, other vessel segmentation datasets are relatively scarce [8]. CHUAC [19] and DCA1 [20] are coronary angiography datasets with resolutions of 189×189 and 300×300 , respectively. ASOCA [21] and VESSEL12 [22] are the 3D vessel segmentation datasets of coronary artery CTA and lung CT from the challenges, in which only training set data is available.

The availability of such datasets has led to a surge of outstanding works in the field of segmentation, with researchers striving to develop algorithms that outperform existing methods. So far, there have been no publicly available DSA datasets with vessel annotation in the medical imaging community, and only a few studies conducted with in-house datasets. DCVessel [9] comprises 30 DSA arterial-phase images at a resolution of 700×700 , while HEART [23] comprises 1092 DSA coronary images at 256×256 resolution. Su *et al.* [8] manually segmented arteries and veins on 97 DSA series, covering both anterior-posterior and lateral views, each with a resolution of 1024×1024 pixels. In this work, we have released DIAS, an IA segmentation dataset derived from DSA sequences. It comprises 120 sequences (753 frames), each with a resolution of 800×800 pixels, and the lengths of these sequences range from 4 to 14. The DIAS can serve as a reliable benchmark for the development of algorithms on IA segmentation from DSA sequences. We hope that this dataset will intrigue researchers to explore this field further.

B. Vessel Segmentation Methods

In the past few years, deep learning has demonstrated great potential in vessel segmentation, surpassing traditional

TABLE I
SUMMARY OF SEVERAL PUBLIC VESSEL SEGMENTATION DATASETS. † REPRESENTS ONLY TRAINING SET DATA IS AVAILABLE.

Dataset	Year	Target	Modality	Dimension	Numbers	Resolution
DRIVE [14]	2004	retinal vessels	color fundus	2D	40	565×584
CHASE_DB1 [15]	2012	retinal vessels	color fundus	2D	28	999×960
STARE [16]	2000	retinal vessels	color fundus	2D	20	700×605
HRF [17]	2013	retinal vessels	color fundus	2D	45	3504×2336
ROSE1 [18]	2020	retinal vessels	OCTA	2D	117	304×304
ROSE2 [18]	2020	retinal vessels	OCTA	2D	112	512×512
CHUAC [19]	2018	coronary artery	angiography	2D	30	189×189
DCA1 [20]	2019	coronary artery	angiography	2D	134	300×300
ASOCA† [21]	2022	coronary artery	CTA	3D	40	512×512×200
VESSEL12† [22]	2014	lung vessel	CT	3D	20	-
DIAS	2023	intracranial artery	DSA	2D+Time	120 (753)	800×800×4-14

methods, such as hand-crafted features [24], filtering-based models [25], and statistical models [26]. Deep learning-based methods have become primary approaches for vessel segmentation, with UNet [27] serving a crucial role as a milestone network architecture, giving rise to numerous variant networks. These networks utilize an encoder-decoder architecture with popular components, such as multi-scale design [9], [13], [28], deep supervision [9], [12], [29], attention mechanisms [13], [30], [31], atrous convolution [9], [12], [29], [32], and improved skip connections [9], [12]. Moreover, several novel neural networks [33], [34] have also succeeded in vessel segmentation by leveraging generative adversarial networks (GAN) or graph neural networks (GNN). Some studies focused on vessel segmentation beyond network architecture, such as optimized training strategies [35], [36] and modifying loss functions [37].

However, there have been few studies on DSA vessel segmentation. Meng *et al.* [9] proposed a CNN-based multiscale dense CNN segmentation framework, which includes a multiscale atrous convolution module, an improved dense block, and redesigned skip connections, for IA segmentation in single frame DSA. Zhang *et al.* [23] proposed a boundary enhancement and feature denoising module to improve the extraction of boundary information in DSA coronary segmentation. These two approaches are tailored for vessel segmentation in individual DSA frames. For vessel sequence, Hao *et al.* proposed the sequential vessel segmentation network (SVS-Net) for vessel segmentation in X-ray coronary angiography, which incorporates 3D convolutional layers to extract rich temporal-spatial features and employs channel attention blocks to learn discriminative features [38]. Su *et al.* proposed a spatio-temporal U-Net (ST U-Net) architecture which integrates convolutional gated recurrent units in the contracting branch of U-Net for cerebral artery and vein segmentation in DSA sequences [8]. While both methods achieve vessel segmentation within sequences, the former is not adaptable to variable sequences, and the latter is challenging to extend to other models.

Fully annotating vessel datasets is both time-consuming and costly. Consequently, annotation-efficient segmentation methods based on weakly-supervised and semi-supervised




Fig. 2. Full annotated process of DIAS.

have attracted significant attention from researchers. WSL trains models with sparse annotations instead of full ones. The common methods involves online labeling [39] via consistency checks with the mean teacher or using pseudo-labels supervision [40] derived from model predictions. SSS aims to explore tremendous unlabeled data with supervision from limited labeled data. Recently, self-training methods [41], [42] have dominated this field. Furthermore, methods employing consistency regularization strategies [41], [43], [44] improve the generalization ability by encouraging high similarity in predictions from two perturbed networks for the same input image. To our knowledge, there is no existing literature on semi-supervised or weakly-supervised vessel segmentation in DSA sequences. In this regard, we propose a comprehensive benchmark involving FSS, WSS, and SSS for IA segmentation based on the constructed DSA-sequences dataset.

III. DIAS DATASET

A. Dataset Description

The DIAS dataset was derived from intraoperative DSA images obtained during ischemic stroke treatments, including ICAS and MCAO, at Beijing Tiantan Hospital. The ethical committee at Beijing Tiantan Hospital authorized the use of all the data presented in this study. All images were retrospectively collected between January 2019 and December 2021 and then anonymized to protect the patients' privacy by removing all identifiable clinical treatment details. The original DSA sequences were captured by the angiography machine




Fig. 3. Full annotated representative samples of DIAS at coronal view and sagittal view.




Fig. 4. Examples of two forms scribble annotations: the scribbles annotation with little clinical experience (SALE) and Random Drawing based the Full Annotation (RDFA). Red represents annotated vessel pixels, blue represents annotated background pixels.

during the actual endovascular therapy process and stored as DICOM files. It contains 1027 2D-DSA sequences from 416 patients in anteroposterior view, lateral view or both. In this study, we retained 120 sequences after excluding those with significant motion artifacts or incomplete arterial phase, or any duplicates. The number of frames varies between sequences (6–46 frames), but the frame rate is fixed (4 FPS). The sequences were then extracted into individual images with a resolution of 800×800 pixels using RadiAnt. We retained all the arterial-phase frames and removed the pre-contrast, capillary-phase, and venous-phase frames under the guidance of a neurosurgeon. As a result, the length of DSA sequences in the DIAS dataset ranges from 4 to 14 frames.

B. Reference Annotation Protocol

1) *Full Annotation*: Manual annotation of IA in DSA sequences requires taking into account all the image information in the sequence. Fig. 1 shows an example of intracranial

vessels in five consecutive frames of the arterial phase in the sagittal view. During this period, the contrast agent is gradually dispersed from the internal carotid artery (ICA) to cerebral vessels such as the anterior cerebral artery (ACA), middle cerebral artery (MCA), and posterior cerebral artery (PCA) with blood flow. For a single image, the contrast agent is visible only in a portion of the IA. For instance, the contrast agent at t filled the C1-C3 segment of the ICA, while at $t+4$, it filled the ACA, MCA, and PCA. Annotating the IA of each image in the sequence and then merging the annotation mask can maximize the utilization of the sequence’s vessel information to obtain accurate annotations. The thinness of vessels, particularly in later-stage arterial images, renders the commonly used strategy of outlining their borders in medical image annotation unfeasible. Thus, we have to annotate each vessel pixel by pixel, which is a labor-intensive and time-consuming procedure. Fig. 3 shows that our proposal for a compromise solution, which reduces workload while maintaining annotation accuracy:

- The arterial-phase DSA sequences were divided into two phases from the middle: the anterior phase and the later phase. The contrast agent during the anterior phase predominantly fills the ICA as opposed to the smaller vessels such as the ACA, MCA, and PCA arteries, which are filled by the contrast agent in the later phase.
- The last image of each phase is annotated pixel-wise, followed by a meticulous review of other same-phase images to finalize the annotation. Thick vessels are the focus of annotation in the anterior phase, while thin vessels are prioritized in the later phase.
- The annotations of thick and thin vessels are merged using a pixel-level OR operation (1 for vessel pixel and 0 for background) to create the ultimate vessel mask.

We randomly selected 60 sequences from DIAS for the purpose of annotating blood vessels, using the patient ID as the criterion for selection. The remaining 60 sequences were used for research on IA semi-supervised segmentation. The DSA sequence was initially annotated by two MD students of surgery, followed by corrections from an associate physician with 10 years of experience, and finally confirmed and double-checked by a chief physician with 15 years of experience.

2) *Scribble Annotation*: Scribble-based image segmentation has proven to be an efficacious and sought-after method for WSS [45]. This approach to weak annotation allows annotators to easily mark object centers without the challenging task of delineating class boundaries. To explore the potential of scribble supervision for IA segmentation in DSA sequences, we generated two forms of scribble annotations for the training set of DIAS: the Scribbles Annotation with Little Clinical Experience (SALE) and Random Drawing based the Full Annotation (RDFA). SALE simulates vessel annotation with little expert experience, wherein the thick vessels highlighted by the contrast agent are annotated, as illustrated by the red marker in Fig. 4 (a). Despite receiving clinicians’ basic training, accurately distinguishing the thin vessels and edges of thick blood vessels with low contrast remains challenging. Consequently, pixels in these regions were annotated during




Fig. 5. Illustration of the proposed pipeline for DSA-sequence intracranial artery segmentation. (a) Vessel sequence segmentation network with (b) sequence feature extraction module; (c) WSL: scribble learning-based segmentation composed of scribble supervision and consistency regularization; (d) SSL: random patch-based self-training framework. (WSC: Weight Sharing Convolution, SF: Sequence Fusion, GMP: Global Max Pooling, WSD: Weight Sharing Downsampling, DA: Data augmentation, WA: Weak Augmentation, SA: Strong Augmentation)

annotation. Moreover, scribble segmentation relies on supervised information for every category. Apart from annotating the vessels, we conducted extensive scribble annotations for the background wherever possible, as illustrated by the blue marker in Fig. 4 (a). Follow [46], we generate RDFA by skeletonizing and randomly pruning each category of the full annotation, as shown in Fig. 4 (b). RDFA simulates random scribble annotations, diverging from SALE, which focuses on easier annotations. In SALE and RDFA, we set the pixel values of the background and vessel annotations to 0 and 1, respectively, while pixels without annotations are assigned a value of 255.

IV. METHODS

Automatic IA segmentation in DSA sequences is an under-explored and challenging task. To fully explore potential research topics, three elaborately designed benchmarks for IA segmentation were proposed, aiming to provide comprehensive benchmarks for FSS, WSS, and SSS, which are increasingly drawing attention in the medical image analysis community.

A. Fully-supervised Segmentation

Segmenting IA in DSA sequence can be considered as a dimensionality reduction (DR) task. Given an image $I \in \mathbb{R}^{\prod_{d=1}^N n_d}$, where N represents the number of dimensions and n_d is the size of the image in the corresponding dimension d , DR segmentation can be defined as finding a function f such that $f : I \rightarrow O$, where $O \in \mathbb{R}^{\prod_{d=1}^M n_d}$ represents segmentation output and $M (< N)$ is its dimensionality [47]. For IA segmentation in DSA sequence, $N = 3$, $M = 2$.

Contrary to traditional medical image segmentation models that solely focus on spatial features, our proposed vessel sequence segmentation network (VSS-Net) efficiently captures spatio-temporal representation of vessels from various scales to achieve precise IA segmentation in DSA. Figure 5 (a,b) illustrates an overview of the proposed network architecture. VSS-Net is composed of multi-scale sequence feature extraction modules (SFEM). These modules handle the 2D+T input sequences and incorporate feature maps from the preceding stage, resulting in 2D feature maps that capture both spatial and temporal representations. Subsequently, these feature maps can be fed into any 2D model following the encoder-decoder framework, enabling vessel segmentation in the sequence.

In the encoder, the input feature map from each stage is integrated with the raw sequence, serving to supplement fine-grained semantic information, except for the initial stage. Specifically, the raw sequence has been resized to be consistent with the corresponding feature maps by bilinear interpolation. Each image of sequence are concatenated with feature maps from the same temporal sequence, and then they are fused using a 1×1 convolution with shared weights (WSC), leading to a reduction by half in the number of channels. This process is formulated as:

$$Q = \sum_{i=1}^N W * (x_i \oplus f_i) \quad (1)$$

where, x represents the input frame, f is the feature map, N denotes the length of the sequence. W are 1×1 convolutional kernels. $*$ denotes the convolution operation. \oplus denotes the concatenation operation.

Subsequently, we employ a bidirectional ConvGRU to construct the spatiotemporal connection between the feature maps of sequence. ConvGRU [48] is an extension of the traditional GRU that integrates convolutional operations, making it more suitable for spatial data like images. Consider x_t as the input to the ConvGRU, with corresponding hidden states denoted by h_t , we can delineate the updating process of ConvGRU unrolled by time as follows:

$$z_t = \sigma(W_z * x_t + U_z * h_{t-1}) \quad (2)$$

$$r_t = \sigma(W_r * x_t + U_r * h_{t-1}) \quad (3)$$

$$\tilde{h}_t = \tanh(W_h * x_t + U_h * (r_t \odot h_{t-1})) \quad (4)$$

$$h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t \quad (5)$$

where, σ represents the sigmoid function. \tanh represents the hyperbolic tangent function. \odot denotes the Hadamard product, i.e., element-wise multiplication. W_r, W_z, W_h and U_r, U_z, U_h are 2D-convolutional kernels.

We simultaneously capture the spatiotemporal dynamics of vascular flow in both forward and backward directions. Subsequently, the outputs of the bidirectional ConvGRU are fused into a single sequence [49]. The resulting integrated features encompass angiographic representations of both macrovascular and microvascular structures, spanning the early to late arterial stages. The process can be formulated as follows:

$$h_t^f = \text{ConvGRU}(h_{t-1}, x_t) \quad (6)$$

$$h_t^b = \text{ConvGRU}(h_{t+1}, x_t) \quad (7)$$

$$h_t = \tanh(W_f * h_t^f + W_b * h_t^b) \quad (8)$$

where, h_t^f and h_t^b denote the hidden states from the forward and backward ConvGRU units, respectively. x_t is the t^{th} output feature from WSC.

The output feature maps are spatially downsampled using stride convolution with weight sharing to serve as inputs for the next stage encoder. Simultaneously, we employ global max pooling along the sequence dimension of the feature maps for dimensionality reduction. The generated multi-scale feature maps are compatible with any U-shaped segmentation architecture. In particular, we integrate it with FR-UNet, where the outputs of the multi-scale SFEM are fed into each stage of FR-UNet. The resultant VSS-Net effectively harnesses the strengths of both components, extracting spatiotemporal representations to realize precise vessel segmentation within sequences.

B. Weakly-supervised Segmentation

A common strategy for scribble-supervised semantic segmentation is to handle the problem as a fully supervised task, using a loss function \mathcal{L} on the available labeled points. However, this baseline approach does not utilize the unlabeled points that contain critical semantic information. The performance degradation is unavoidable due to the lack of labeled data points. To enhance the segmentation performance of scribble, the key lies in extending the supervision of labeled pixels to unlabeled pixels. To overcome these issues, we

propose SSCR, a novel framework for learning-based scribble image segmentation composed of scribble supervision and consistency regularization (CR). Fig. 5 (b) presents the implementation framework for SSCR. SSCR generates pseudo-annotations for the unlabeled pixels with guidance provided by scribble supervision, utilizing partial cross-entropy to extend supervised information, and maximizes the performance of scribble segmentation by regularizing segmentation network using mutual consistency and cross pseudo supervision (CPS).

We define P as the set of image pixels and $S \subseteq P$ as the set of annotated pixels. The proposed approach feeds P into two segmentation networks with different augmentation strategies. The outputs of each network are supervised by applying the cross-entropy function solely to the annotated pixels on the scribble labels. The function, namely partial cross entropy (pCE), can be formulated as:

$$\mathcal{L}_{pce}(y, \hat{y}) = - \sum_{i=1}^M \sum_{j=1}^N \mathbb{1}(p_{i,j} \in S) (y_{i,j} \log(\hat{y}_{i,j|\theta})) \quad (9)$$

where, M and N represent the width and height of the image, respectively. $\hat{y}_{i,j|\theta}$ is the predict for the pixel $p_{i,j} \in S$ given the network parameters θ , and $y_{i,j}$ denotes the ground truth label.

To generate pseudo labels, we first calculate the class distribution of the one-hot prediction map using limited softmax, which exclusively calculates the channel corresponding to the annotated class. Then, we apply scribble annotations to correct the pseudo labels in order to improve their confidence. The formula for creating the pseudo label is as follows:

$$PL_i = \begin{cases} s_{i,j}, & \text{if } p_{i,j} \in S \\ \text{argmax}(\text{softmax}(\mathcal{H}(p_{i,j}; \theta)[C])), & \text{otherwise} \end{cases} \quad (10)$$

where, $s_{i,j} \in S$ defines annotated pixels, and $\mathcal{H}(p_{i,j}; \theta)$ defines the predicted output of $p_{i,j}$. C is the channel of annotated class, i.e., 0 and 1.

We enforce network consistency by utilizing cross pseudo supervision, which employs pseudo labels from one network to supervise the other network [43]. Additionally, these pseudo labels are imposed a consistency loss to penalize inconsistent segmentation. The training objective contains three losses: scribble supervision loss \mathcal{L}_{scr} , cross pseudo supervision loss \mathcal{L}_{cps} , and consistency loss \mathcal{L}_{con} :

$$\mathcal{L}_{scr} = \frac{1}{2} (\mathcal{L}_{pce}(P_A, SL) + \mathcal{L}_{pce}(P_B, SL)) \quad (11)$$

$$\mathcal{L}_{cps} = \frac{1}{2} (\mathcal{L}_{ce}(P_A, PL_B) + \mathcal{L}_{ce}(P_B, PL_A)) \quad (12)$$

$$\mathcal{L}_{con} = \mathcal{L}_{mse}(PL_A, PL_B) \quad (13)$$

where, \mathcal{L}_{ce} denotes the cross-entropy loss function and \mathcal{L}_{mse} denotes the mean square error loss function. P_A and P_B are the outputs of two models. PL_A and PL_B are the pseudo labels. SL is the scribble label.

Finally, the training objective \mathcal{L} is formulated as

$$\mathcal{L} = \mathcal{L}_{scr} + \lambda_1 \mathcal{L}_{cps} + \lambda_2 \mathcal{L}_{con} \quad (14)$$

where, λ_1 and λ_2 are the weight of loss components \mathcal{L}_{cps} and \mathcal{L}_{con} .

C. Semi-supervised Segmentation

Annotation of cerebral vessels manually from DSA image sequences is a laborious and time-consuming task. Semi-supervised learning has shown the potential to alleviate this problem by learning from a large set of unlabeled images and limited labeled samples [42]. The primary challenge in semi-supervised setting lies in how to effectively utilize the unlabeled images. Self-training [50] via pseudo labeling is a conventional, simple, and popular pipeline to leverage unlabeled data, where the retrained student is supervised with hard labels produced by the teacher trained on labeled data, which is commonly regarded as a form of entropy minimization in semi-supervised learning. For semi-supervised segmentation problem, let $\mathcal{D}^l = \{(x_i, y_i)\}_{i=1}^M$ be pixel-wise labeled images and $\mathcal{D}^u = \{u_i\}_{i=1}^N$ be unlabeled images, where in most cases $N \gg M$. Self-training can be simplified into the following steps: leftmargin=*,itemsep=-5pt

- 1) Train a teacher model T on labeled data \mathcal{D}^l ;
- 2) Predict hard pseudo labels on unlabeled data \mathcal{D}^u with T to obtain $\hat{\mathcal{D}}^u = \{(u_i, T(u_i))\}_{i=1}^N$;
- 3) Re-train a student model S on the label data and pseudo-label data $\mathcal{D}^l \cup \hat{\mathcal{D}}^u$ for final evaluation.

We follow the plainest self-training strategy to provide a SSS benchmark for DIAS. The injection of strong data augmentations on unlabeled images is highly advantageous as it decouples the predictions as well as alleviates overfitting on noisy pseudo-labels. Despite its simplicity, self-training with strong data augmentations surpasses existing methods without any bells and whistles [41]. We performed two types of data augmentations in our implementation: weak and strong, denoted by A^s and A^w respectively. Weak data augmentations (WDA) consist of horizontal flipping, vertical flipping, and [90, 180, 270] degree rotation. Strong data augmentations (SDA) include Cutout, adding white Gaussian noise, Gaussian blurring, and elastic deformation. We randomly adjust the contrast of each image in the DSA sequence to simulate angiography with intensity differences. We randomly extract patches from the DSA sequence to train the teacher and student models. Notably, the patches in each mini-batch were randomly extracted from \mathcal{D}^l and $\hat{\mathcal{D}}^u$ with a probability P when retraining the student model. Additionally, the final performance can be further improved by switching the teacher-student role and relabeling unlabeled images for iterative training. The pseudocode of the random patch-based self-training framework, referred to as RPST, is provided in Algorithm 1.

V. EXPERIMENTS

A. Implementation Details and Evaluation Metrics

The DIAS dataset was divided into 30 training samples, 10 validation samples, and 20 testing samples on the patient level. To facilitate input into the model, all DSA sequences were resampled to a length of 8. All DSA sequences were z-score normalized. Patches of size 64×64 were randomly cropped for training, with a batch size of 64. The model parameters were optimized using AdamW [51] with an initial learning rate of $5e-4$. The learning rate is gradually reduced by the cosine annealing algorithm over 100 epochs. The parameter

Algorithm 1: RPST

Input: Labeled training set $\mathcal{D}^l = \{(x_i, y_i)\}_{i=1}^M$,
 Unlabeled training set $\mathcal{D}^u = \{u_i\}_{i=1}^N$,
 Weak/strong augmentation $\mathcal{A}^w/\mathcal{A}^s$,
 Teacher/student model T/S ,
 Execution probability $P \in (0, 1)$

Output: Trained student model S

Train T on \mathcal{D}^l with loss \mathcal{L}

Obtain pseudo labeled $\hat{\mathcal{D}}^u = \{(u_i, T(u_i))\}_{i=1}^N$

for Iterative training N **do**

for Minibatch with the size of B **do**

for $k \in \{1, \dots, B\}$ **do**

if Random number $r > P$ **then**

Randomly extract patch (x_k^p, y_k^p) from \mathcal{D}^l

$x_k^p, y_k^p \leftarrow (\mathcal{A}^s \& \mathcal{A}^w)(x_k^p, y_k^p)$

else

Randomly extract patch (x_k^p, y_k^p) from $\hat{\mathcal{D}}^u$

$x_k^p, y_k^p \leftarrow \mathcal{A}^w(x_k^p, y_k^p)$

end

$\hat{y}_k^p = S(x_k^p)$

Update S to minimize \mathcal{L} of $\{(\hat{y}_i^p, y_k^p)\}_{i=1}^B$

end

if Not the last iterative **then**

Obtain new pseudo labeled $\hat{\mathcal{D}}^u = \{(u_i, S(u_i))\}_{i=1}^N$

end

P was set to 0.5, i.e., half of the patches in each batch were extracted from labeled data, while the rest came from unlabeled data in SSS experiment. For SSCR, the weights of loss components λ_1 and λ_2 were empirically set to 1 and 0.5. We only use one network to generate the results for evaluation. All experiments used PyTorch with constant hyperparameters and were conducted on a single GeForce RTX 3090 GPU. We calculated the dice similarity coefficient (DSC), the area under the receiver operating characteristic curve (AUC), accuracy (Acc), sensitivity (Sen), specificity (Spe), and intersection over union (IOU) to evaluate the performance of DSA sequence segmentation. Moreover, we introduced the vascular connectivity (VC) [12] metric, which calculates the ratio of connected components in the segmentation image to those in the ground truth, as a means of measuring the connectivity of vessels.

B. Fully-supervised Segmentation

We conducted comparative experiments on DIAS using several state-of-the-art segmentation networks, which included traditional 2D/3D networks such as UNet [27], Attention-UNet [52], UNet++ [53], Res-UNet [54], MAA-Net [13], CS²-Net [30], FR-UNet [12] and 3D→2D networks like IPN [55], PSC [47], SVS-Net [38], ST U-Net [8]. To order to achieve DR segmentation for these 2D/3D models, we propose a straightforward yet efficient DR operation that can convert them into DR models without altering their design. The DR operation is readily integrated into the input of a 2D model

or the output of a 3D model as a plug-and-play module. Specifically, given a DSA sequence $x \in \mathbb{R}^{C \times F \times H \times W}$, where C , F , H and W denote the number of channels, frame, height, and width, respectively. The initial number of channels is 1, which is squeezed by DR operation. The compressed input is then fed to the 2D model, where F replaces C as the input channel:

$$y = \mathcal{H}_{2d}(Squ(x)) \quad (15)$$

where, Squ is dimensionality squeeze operation and \mathcal{H}_{2d} is a 2D model.

For a 3D model \mathcal{H}_{3d} , the DSA sequence is fed directly into the model, where it is treated as volume data. The dimension, C , of the model output is squeezed by DR operation. Finally, 1×1 convolution reduces F to the number of classes:

$$y = Conv_{1 \times 1}(Squ(\mathcal{H}_{3d}(x))) \quad (16)$$

Table II demonstrates that the comprehensive performance of VSS-Net surpasses other networks, achieving the best DSC, Sen, IOU, AUC and VC, among all the evaluated methods. Using FR-UNet as a baseline, VSS-Net shows improvements in numerous metrics except for Spe. Specifically, Sen has increased by 1.3%. ST U-Net, also employing ConvGRU, shows performance very close to VSS-Net, achieving the best results in Acc and Spe. However, the number of model parameters is approximately 5.58 times that of VSS-Net. The VC score that is 19.57 higher than VSS-Net indicates poorer vascular connectivity. Both IPN and SVS-Net employ 3D convolutions in the encoder and 2D convolutions in the decoder, incorporating dimensionality reduction in the intermediate stages. PSC’s segmentation results are similar to those of 3D models, but IPN shows poorer performance, possibly due to the absence of skip connections, which are significantly important for enhancing the detailing in vascular structures. Upon overall comparison of the DSC scores for all ‘DR+2D model’ and ‘DR+3D model’, 2D models slightly outperform 3D models with fewer parameters. Although in terms of data format, 2D+time DSA sequences are equivalent to 3D data, they do not have a one-to-one spatial relationship with the ground truth. More importantly, 3D convolutions can only model local temporal representations. The ‘DR+2D model’ benefits from treating ‘sequences’ as ‘channels’, which enables it to learn global representations along the sequence dimension while performing 2D convolutions, which aggregates contrast agent responses that reflect vascular morphological information in the sequence direction. However, the approach of setting fixed channel numbers is not applicable to variable image sequences. We have visualized the segmentation results of the methods that exhibited outstanding performance, as showed in Figure 6. In the figure, the red and blue colors represent pixels that are false negatives and false positives, respectively, indicative of segmentation errors. It can be observed that a prevalent issue shared by all methods is the abundant incorrect segmentation of thin vessels. Specifically, we enlarged representative details in the images, as illustrated by the yellow and blue boxes in Figure 6. In comparison with other methods, VSS-Net has the

highest number of white pixels in the fine vessels, indicating the best segmentation results.

C. Weakly-supervised Segmentation

We compared our method with five scribble-supervised segmentation methods: partial Cross Entropy (pCE) [57], Entropy Minimization (EM) [56], Regularized Loss (RLoss) [45], Intra-class Intensity Variance Minimization (IVM) [46] and Dynamically Mixed Pseudo Labels Supervision (DMPLS) [40]. To ensure a fair comparison, all experimental networks employed the UNet [27], consistent with the approach in DMPLS. Table III presents the results of scribble-supervised segmentation of the DIAS dataset. Fig. 7 showcases the visual results of all methods. Thanks to pseudo supervision and consistency regularization for scribble supervision, SSCR achieved significantly better performance in RDFA and SALE by obtaining the highest scores in most metrics among all methods. It is noteworthy that in the segmentation results of IVM, the Sen on RDFA is 4.67% higher compared to SSCR, and it is 4.12% higher on SALE. Sen is used to measure the proportion of correctly identified positive classes (i.e., vessels) out of all actual positive classes, independent of the background. The visualization results from IVM indicate that achieving high Sen comes at the cost of introducing numerous incorrectly segmented vessel pixels. Consequently, this leads to lower scores in other evaluation metrics such as the DSC and AUC. Regarding SALE, the vessels segmented by the same method are thicker than the ones trained with RDFA annotation, leading to a larger number of false positive pixels at the vessel’s edge. This outcome may have been caused by the SALE focusing on the annotation of thick vessels. Similarly, due to the lack of supervision for small vessels, where vascular connectivity issues are more prevalent, SALE struggles to extract fine vessels, resulting in a VC score significantly better than RDFA. From the last column of the figure, it is evident that SSCR’s segmentation results have the least number of blue pixels, corroborating the best quantitative results presented in the Table III.

We conducted ablation studies to investigate the impact of various components in our proposed pipeline for weakly-supervised IA segmentation. As illustrated in Table IV, with pCE serving as the baseline, we incrementally added components for comparative analysis. Initially, the introduction of pseudo-label supervision resulted in a slight decline in metrics such as DSC and AUC. Based on this, we utilized a dual-model framework to establish cross pseudo-supervision, leading to a 1.08% enhancement in DSC. Compared to a single-model approach, a dual-model setup, receiving the same scribble supervision, generates pseudo-labels for mutual supervision. This avoids the scenario of a model being self-supervised by its own predictions, thereby enhancing the model’s generalizability. We employ consistency regularization on the pseudo-labels generated by dual models to penalize inconsistent segmentation without CPS. Compared to ‘pCE+PS’, ‘pCE+PS+CR’ exhibits a 1.2% improvement in DSC. Additionally, it has attained the highest Sen. We implement a combined strategy of cross pseudo-supervision

TABLE II
RESULTS OF FULLY-SUPERVISED SEGMENTATION WITH STATE-OF-THE-ART MODELS.

Methods		Params / M	Metrics						
Type	Networks		DSC	Acc	Sen	Spe	IOU	AUC	VC↓
2D	UNet [27]	31.04	0.7677	0.9647	0.757	0.9829	0.6258	0.9811	68.29
	Res-UNet [54]	9.37	0.7656	0.9655	0.7425	0.985	0.6235	0.9816	60.56
	UNet++ [53]	9.05	0.7768	0.9659	0.7726	0.983	0.6374	0.983	54.65
	Att-UNet [52]	8.73	0.7760	0.9660	0.7686	0.9835	0.6258	0.9811	59.37
	CS ² -Net [30]	8.93	0.7747	0.9664	0.7524	0.9855	0.6344	0.9833	64.87
	MAA-Net [13]	5.80	0.7693	0.9661	0.7423	0.9855	0.6361	0.9818	68.18
	FR-UNet [12]	7.37	0.7779	0.9665	0.7646	0.9841	0.6376	0.9827	53.92
3D	UNet [27]	90.27	0.7691	0.9648	0.769	0.9824	0.6275	0.9819	62.92
	Res-UNet [54]	26.38	0.7701	0.9653	0.7597	0.9835	0.6284	0.9817	73.05
	UNet++ [53]	26.17	0.7649	0.9639	0.7711	0.9811	0.6214	0.9811	67.02
	Att-UNet [52]	23.6	0.7677	0.9647	0.757	0.9829	0.6258	0.9811	68.29
	CS ² -Net [30]	23.83	0.7687	0.9645	0.7712	0.9816	0.6267	0.9808	67.91
	FR-UNet [12]	20.57	0.7635	0.9646	0.7518	0.983	0.621	0.9815	65.67
3D→2D	IPN [55]	6.36	0.7587	0.9643	0.7392	0.9837	0.6138	0.9715	61.85
	PSC [47]	6.43	0.7649	0.9646	0.7552	0.9832	0.6223	0.9814	76.04
	SVS-Net [38]	8.48	0.7698	0.9659	0.7474	0.9853	0.6277	0.9803	97.28
	ST-UNet [8]	104.37	0.7818	0.9675	0.7533	0.9864	0.6436	0.9843	62.59
	VSS-Net	18.69	0.7822	0.9668	0.777	0.9838	0.6442	0.9857	43.02




Fig. 6. Visualization of segmentation results of state-of-the-art models. The first row is coronal view, and the second row is sagittal view. The red pixel indicates false negatives, and the green pixel indicates false positives.

TABLE III
RESULTS OF SCRIBBLE-SUPERVISED IA SEQUENCE SEGMENTATION.

Methods	RDFA							SALE						
	DSC	Acc	Sen	Spe	IOU	AUC	VC↓	DSC	Acc	Sen	Spe	IOU	AUC	VC↓
pCE [47]	0.7455	0.9586	0.7845	0.9735	0.5966	0.9379	60.11	0.6396	0.9246	0.8462	0.9308	0.4738	0.9560	10.02
EM [56]	0.7458	0.9575	0.8029	0.9707	0.5970	0.9725	41.18	0.6356	0.9226	0.8508	0.9281	0.4699	0.9618	9.05
RLoss [45]	0.7146	0.9600	0.6539	0.9867	0.5581	0.9367	46.30	0.5916	0.9147	0.7812	0.9257	0.4232	0.9475	5.17
IVM [46]	0.6606	0.9299	0.8546	0.9360	0.4971	0.9455	71.58	0.6322	0.9198	0.8760	0.9232	0.4662	0.9628	14.78
DMPLS [40]	0.7471	0.9581	0.7963	0.9717	0.5995	0.9708	37.56	0.6327	0.9208	0.8508	0.9259	0.4668	0.9643	9.86
SSCR	0.7589	0.9603	0.8079	0.9732	0.6141	0.9761	36.52	0.6722	0.9343	0.8348	0.9421	0.5115	0.9658	10.30




Fig. 7. Visualization of the segmentation results of scribble supervised segmentation methods trained on RDFA and SALE annotations.

TABLE IV
ABLATION STUDIES RESULTS OF SSCR FOR IA SEQUENCE SEGMENTATION WITH SALE ANNOTATION. (PCE: PARTIAL CROSS ENTROPY, PS: PSEUDO-LABELING SUPERVISION, CPS: CROSS PSEUDO SUPERVISION, CR: CONSISTENCY REGULARIZATION)

Methods				Metrics						
pCE	PS	CPS	CR	DSC	Acc	Sen	Spe	IOU	AUC	VC↓
✓				0.6396	0.9246	0.8462	0.9308	0.4738	0.9560	10.02
✓	✓			0.6364	0.9244	0.8346	0.9316	0.4706	0.9479	6.57
✓	✓	✓		0.6472	0.9275	0.8385	0.9346	0.4827	0.9445	7.29
✓	✓		✓	0.6484	0.9276	0.8536	0.9334	0.4827	0.9639	8.28
✓	✓	✓	✓	0.6722	0.9343	0.8348	0.9421	0.5115	0.9658	10.30

and consistency regularization on the pseudo-labels produced by dual models. The integrated approach, termed as SSCR and denoted as ‘pCE+PS+CPS+CR’, has achieved notable improvements, surpassing ‘pCE+PS+CPS’ and ‘pCE+PS+CR’

by 2.5% and 2.38%, respectively.

D. Semi-supervised Segmentation

The number of labeled and unlabeled samples and strong data augmentation (SDA) affect the performance of RPST. In this section, we randomly select 1, 3, and 10 labeled DSA sequences from the DIAS training set for SSS experiments. We leverage 30 and 60 DSA unlabeled sequences to generate pseudo labels and participate in training student. Table V shows that pseudo-labeled data generated by the trained teacher significantly improves the performance of the model, especially when there are fewer labeled data available. For example, the DSC of the student is improved by 2.2% with one labeled data and 30 unlabeled data compared to the teacher. This performance gain is positively correlated with the amount of unlabeled data. Ablation studies on SDA demonstrate the effectiveness of enforcing consistency through the application

TABLE V
ABLATION RESEARCH RESULTS OF RPST FOR SEMI-SUPERVISED IA SEQUENCE SEGMENTATION.

Methods	Data		Metrics						
	Labels	Unlabels	DSC	Acc	Sen	Spe	IOU	AUC	VC↓
Teacher	1	0	0.6266	0.9259	0.6853	0.9451	0.4693	0.8538	385.62
Student	1	30	0.6486	0.9294	0.7085	0.9464	0.4941	0.9505	107.35
Student w/o SDA	1	60	0.6394	0.9296	0.6922	0.9483	0.4832	0.9352	108.96
Student	1	60	0.6502	0.9305	0.7177	0.9482	0.4958	0.9433	103.09
Teacher	3	0	0.6919	0.949	0.7358	0.9673	0.5336	0.9182	320.02
Student	3	30	0.7265	0.9555	0.7478	0.9721	0.5745	0.9591	121.84
Student w/o SDA	3	60	0.7228	0.9555	0.7456	0.9734	0.57	0.9578	125.83
Student	3	60	0.7275	0.9549	0.7595	0.9778	0.5893	0.9616	125.78
Teacher	10	0	0.7402	0.9596	0.7477	0.9779	0.591	0.9694	148.89
Student	10	30	0.7544	0.9618	0.766	0.9786	0.6087	0.9769	93.31
Student w/o SDA	10	60	0.7556	0.9625	0.7552	0.9805	0.6096	0.9737	93.92
Student	10	60	0.7579	0.9625	0.7662	0.9795	0.613	0.9786	87.72




Fig. 8. Result of iterative training with different amounts of labeled data.

of both strong and weak data augmentation. While the pseudo-labeled data used to train the student model contains noisy labels, they can still enhance the model’s generalization capability, albeit with the supervision of incorrect pixel labels of vessel. The results of DIAS show that the benefits brought by the pseudo-labeled data outweigh the drawbacks of noisy labels in IA sequence segmentation. As the number of labeled data increases, this beneficial effect gradually diminishes.

All the unlabeled images can be labeled with a new teacher, i.e., the student from the previous stage, and re-trained in the iterative training stage. Fig. 8 presents our examination of the effectiveness of iterative training in RPST. In the extremely scarce-label regime with only one labeled sequence (#1), performance is improved from 65.02% to 66.85% with the extra two-iteration training. The performance of #10 improved from 75.79% to 76.39%. Each iteration enables the model to further learn and adjust based on the foundation established by previous iterations, increasing its confidence in its own predictions and resulting in the generation of more reliable pseudo-labels, thereby enhancing segmentation accuracy. With an increasing number of training iterations, the marginal improvement in performance diminishes.

VI. DISCUSSION

A. Impact of Sequences as Inputs

The DSA sequence is a 2D temporal image sequence that represents the contrast agent’s response at different times while flowing through the blood. Theoretically, accurate delineation of vessels requires the aggregation of contrast agent responses from all images in the sequence. In clinical practice, neurosurgeons commonly utilize Minimum Intensity Projection (MIP) to process target sequences in DSA for the visualization of vascular structures [58]. MIP is a straightforward and effective method for aggregating significant vascular information from target sequences. To evaluate the impact of various input modalities on segmentation performance, we conduct comparative experiments that include subsets of the image sequence (First, Last, and First+Last), MIP and average intensity projection (AIP) image as input to the VSS-Net. As shown in Table VI, In ‘First’, where the contrast agent is exclusively displayed in the ICA, the segmentation results are inferior, the DSC is only 62.32%. In comparison, the ‘Last’ as input to the model obtained better results, thanks to the more angiographic information in thin vessel, the DSC is 76.04%. The quantitative results are consistent with those portrayed in Fig. 9 (e) and (f). When using only the first image as the model input, the large vessels are accurately segmented. However, due to the absence of angiographic information for fine vessels in the first image frame, the thin vessel at the arterial termini within the middle cerebral artery (MCA) remain incomplete. Conversely, using only the last image as input enables the accurate segmentation of most small vessels, yet it falls short in precisely delineating the larger vessels in proximity to the ICA.

The combination of early and late arterial angiography, known as ‘First+Last’, yielded favorable results, surpassing those of both inputs used independently. As shown in Fig. 9 (a) and (b), although the combination of the ‘First’ and ‘Last’ images from the arterial phase can display the majority of the vascular structures filled with contrast agent, we can still utilize the intermediate images to supplement details. The experimental findings indicate that employing the complete




Fig. 9. The first row is the visualization of various inputs, and the second row is the corresponding segmentation result.

TABLE VI
RESULTS OF FULLY-SUPERVISED SEGMENTATION WITH VARIOUS INPUT

Input	Metrics						
	DSC	Acc	Sen	Spe	IOU	AUC	VC↓
First image	0.6232	0.9515	0.5388	0.9864	0.4601	0.9049	12.05
Last image	0.7604	0.9647	0.7394	0.9842	0.6146	0.9813	51.89
First + Last image	0.7777	0.9668	0.7589	0.9850	0.6373	0.9846	44.22
Mean	0.7790	0.9663	0.7695	0.9834	0.6398	0.9809	39.25
Min	0.7812	0.9673	0.7631	0.9854	0.6418	0.9842	40.02
Full	0.7822	0.9668	0.7770	0.9838	0.6442	0.9857	43.02

DSA sequence as input is imperative for achieving optimal performance. The segmentation results of MIP and AIP are quite close to those obtained using the method that utilizes the full DSA sequence as input. Density projection methods such as MIP and AIP convert arterial phase sequences into 2D images along the temporal dimension, which necessitates the pre-selection of target sequences to avoid the influence of capillary and venous phase angiography. Using DSA sequences as the network’s input holds potential in addressing this challenge, as VSS-Net can selectively extract target sequence angiographic information from the entire series, including the capillary and venous phases, for the segmentation of IA.

B. Potential Clinical Applications and Limitations

Segmentation of vessels in DSA for quantifying their morphology has already found application in clinical research, particularly for planning interventional surgeries [7] and diagnosing strokes [5]. However, as discussed in Section VI-A, the segmentation of a single DSA frame is inadequate for fully delineating the vascular structure. We believe that the application of our proposed method for segmenting DSA vessel sequences in the aforementioned higher-level tasks will yield more accurate vascular structures. This advancement is expected to drive forward the progress of these higher-level tasks. In this work, we propose a comprehensive benchmark based on our created dataset for intracranial arterial

segmentation in DSA sequences. Importantly, the proposed approach is not confined to intracranial arteries. With the availability of relevant annotated data, it can be extended to other segmentation tasks in DSA sequences, such as venous segmentation [8], as well as for the diagnosis of stroke-related conditions like aneurysms [3], ICAS, and MCAO [59].

Currently, the DIAS dataset is relatively small, primarily due to the substantial effort expended on one-to-one pixel annotations of DSA sequences. In future work, we plan to leverage RPST to generate pseudo-labels for DSA sequences pending annotation. Annotation experts will then meticulously revise these pseudo-labels to obtain precise annotations, rather than starting the annotation process from the beginning. This strategy aims to increase annotation efficiency, thereby facilitating the further expansion of DIAS. On the other hand, in the DIAS dataset, intracranial arterial sequences are selected by neurosurgeons from DSA sequences that may include stages such as the capillary or venous phase. Given the nature of 3D spatial projection, angiography from other phases in DSA may impact arterial segmentation, as the same pixel can represent an artery or a vein at different times. In our next phase of work, we plan to segment intracranial arteries from DSA sequences that include the venous phase and other stages, without relying on the neurosurgeons’ prior knowledge to pre-select arterial phase sequences.

VII. CONCLUSION

In this paper, we present the DSA-sequence IA segmentation dataset, DIAS, which provides pixel-level annotations along with two forms of weakly supervised annotations. We establish a benchmark for evaluating IA sequence segmentation on DIAS, comprising (1) the Vessel Sequence Segmentation Network, VSS-Net; (2) the Scribble Learning-based Segmentation Framework, SSCR; and (3) the Random Patch-based Self-Training Framework, RPST. Leveraging the DIAS dataset, we have conducted comprehensive experiments to validate the effectiveness of our proposed methodologies, facilitating a deeper understanding of their performance characteristics and offering valuable insights for future research endeavors.

Looking ahead, our research will persist, including the expansion of segmentation targets to venous and the segmentation of arteries from complete angiographic sequences. We emphasize that the DIAS dataset and benchmark have been made publicly available, enabling researchers to replicate our work and explore novel algorithms in this domain.

ACKNOWLEDGMENTS

This work was supported in part by the National Natural Science Foundation of China (No.62376038) and National Key R&D Program of China (No.2018AAA0102600).

REFERENCES

- [1] M. Vaduganathan, G. A. Mensah, J. V. Turco, V. Fuster, and G. A. Roth, "The global burden of cardiovascular diseases and risk: a compass for future health," pp. 2361–2371, 2022.
- [2] C. P. Hess, "Imaging in cerebrovascular disease," *Molecular, Genetic, and Cellular Advances in Cerebrovascular Diseases*, pp. 1–23, 2018.
- [3] H. Jin, J. Geng, Y. Yin, M. Hu, G. Yang, S. Xiang, X. Zhai, Z. Ji, X. Fan, P. Hu *et al.*, "Fully automated intracranial aneurysm detection and segmentation from digital subtraction angiography series using an end-to-end spatiotemporal deep neural network," *Journal of NeuroInterventional Surgery*, vol. 12, no. 10, pp. 1023–1027, 2020.
- [4] S. Shaban, B. Huasen, A. Haridas, M. Killingsworth, J. Worthington, P. Jabbour, and S. M. M. Bhaskar, "Digital subtraction angiography in cerebrovascular disease: current practice and perspectives on diagnosis, acute treatment and prognosis," *Acta Neurologica Belgica*, vol. 122, no. 3, pp. 763–780, 2022.
- [5] R. Su, S. A. Cornelissen, M. Van Der Sluijs, A. C. Van Es, W. H. Van Zwam, D. W. Dippel, G. Lycklama, P. J. Van Doormaal, W. J. Niessen, A. Van Der Lugt *et al.*, "autotici: Automatic brain tissue reperfusion scoring on 2d dsa images of acute ischemic stroke patients," *IEEE Transactions on Medical Imaging*, vol. 40, no. 9, pp. 2380–2391, 2021.
- [6] M. Groher, F. Bender, R.-T. Hoffmann, and N. Navab, "Segmentation-driven 2d-3d registration for abdominal catheter interventions," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2007, pp. 527–535.
- [7] M. Spiegel, T. Redel, T. Struffert, J. Hornegger, and A. Doerfler, "A 2d driven 3d vessel segmentation algorithm for 3d digital subtraction angiography data," *Physics in Medicine & Biology*, vol. 56, no. 19, p. 6401, 2011.
- [8] R. Su, M. van der Sluijs, S. Cornelissen, P. J. van Doormaal, R. v. d. Broek, W. van Zwam, J. Hofmeijer, D. Ruijters, W. Niessen, A. van der Lugt *et al.*, "Spatio-temporal u-net for cerebral artery and vein segmentation in digital subtraction angiography," *arXiv preprint arXiv:2208.02355*, 2022.
- [9] C. Meng, K. Sun, S. Guan, Q. Wang, R. Zong, and L. Liu, "Multiscale dense convolutional neural network for dsa cerebrovascular segmentation," *Neurocomputing*, vol. 373, pp. 123–134, 2020.
- [10] R.-Q. Li, G.-B. Bian, X.-H. Zhou, X. Xie, Z.-L. Ni, and Z. Hou, "Cau-net: A novel convolutional neural network for coronary artery segmentation in digital subtraction angiography," in *International Conference on Neural Information Processing*. Springer, 2020, pp. 185–196.
- [11] W. Liu, T. Tian, W. Xu, H. Yang, X. Pan, S. Yan, and L. Wang, "Phtrans: Parallely aggregating global and local representations for medical image segmentation," in *Medical Image Computing and Computer Assisted Intervention—MICCAI 2022: 25th International Conference, Singapore, September 18–22, 2022, Proceedings, Part V*. Springer, 2022, pp. 235–244.
- [12] W. Liu, H. Yang, T. Tian, Z. Cao, X. Pan, W. Xu, Y. Jin, and F. Gao, "Full-resolution network and dual-threshold iteration for retinal vessel and coronary angiograph segmentation," *IEEE Journal of Biomedical and Health Informatics*, vol. 26, no. 9, pp. 4623–4634, 2022.
- [13] W. Liu, H. Yang, T. Tian, X. Pan, and W. Xu, "Multiscale attention aggregation network for 2d vessel segmentation," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2022, pp. 1436–1440.
- [14] J. Staal, M. D. Abramoff, M. Niemeijer, M. A. Viergever, and B. van Ginneken, "Ridge-based vessel segmentation in color images of the retina," *IEEE Trans. Medical Imaging*, vol. 23, no. 4, pp. 501–509, 2004. [Online]. Available: <https://doi.org/10.1109/TMI.2004.825627>
- [15] M. M. Fraz, P. Remagnino, A. Hoppe, B. Uyyanonvara, A. R. Rudnicka, C. G. Owen, and S. A. Barman, "An ensemble classification-based approach applied to retinal blood vessel segmentation," *IEEE Transactions on Biomedical Engineering*, vol. 59, no. 9, pp. 2538–2548, Sep. 2012.
- [16] A. Hoover, V. Kouznetsova, and M. Goldbaum, "Locating blood vessels in retinal images by piecewise threshold probing of a matched filter response," *IEEE Transactions on Medical Imaging*, vol. 19, no. 3, pp. 203–210, 2000.
- [17] J. Odstrcilik, R. Kolar, A. Budai, J. Hornegger, J. Jan, J. Gazarek, T. Kubena, P. Cernosek, O. Svoboda, and E. Angelopoulou, "Retinal vessel segmentation by improved-matched filtering: evaluation on a new high-resolution fundus image database," *IET Image Processing*, vol. 7, no. 4, pp. 373–383, 2013.
- [18] Y. Ma, H. Hao, J. Xie, H. Fu, J. Zhang, J. Yang, Z. Wang, J. Liu, Y. Zheng, and Y. Zhao, "Rose: a retinal oct-angiography vessel segmentation dataset and new model," *IEEE transactions on medical imaging*, vol. 40, no. 3, pp. 928–939, 2020.
- [19] A. Carballal, F. J. Nóvoa, C. Fernandez-Lozano, M. García-Guimaraes, G. López-Campos, R. Calviño-Santos, J. M. Vázquez-Naya, and A. Pazos, "Automatic multiscale vascular image segmentation algorithm for coronary angiography," *Biomed. Signal Process. Control*, vol. 46, pp. 1–9, 2018. [Online]. Available: <https://doi.org/10.1016/j.bspc.2018.06.007>
- [20] F. Cervantes-Sanchez, I. Cruz-Aceves, A. Hernandez-Aguirre, M. A. Hernandez-Gonzalez, and S. E. Solorio-Meza, "Automatic Segmentation of Coronary Arteries in X-ray Angiograms using Multiscale Analysis and Artificial Neural Networks," *Applied Sciences*, vol. 9, no. 24, 2019. [Online]. Available: <https://www.mdpi.com/2076-3417/9/24/5507>
- [21] R. Gharleghi, D. Adikari, K. Ellenberger, S.-Y. Ooi, C. Ellis, C.-M. Chen, R. Gao, Y. He, R. Hussain, C.-Y. Lee *et al.*, "Automated segmentation of normal and diseased coronary arteries—the asoca challenge," *Computerized Medical Imaging and Graphics*, vol. 97, p. 102049, 2022.
- [22] R. D. Rudyanto, S. Kerkstra, E. M. Van Rikxoort, C. Fetita, P.-Y. Brillet, C. Lefevre, W. Xue, X. Zhu, J. Liang, I. Öksüz *et al.*, "Comparing algorithms for automated vessel segmentation in computed tomography scans of the lung: the vessel12 study," *Medical image analysis*, vol. 18, no. 7, pp. 1217–1232, 2014.
- [23] M. Zhang, F. Yu, J. Zhao, L. Zhang, and Q. Li, "Befd: boundary enhancement and feature denoising for vessel segmentation," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2020, pp. 775–785.
- [24] J. Zhang, G. Wang, H. Xie, S. Zhang, Z. Shi, and L. Gu, "Vesselness-constrained robust pca for vessel enhancement in x-ray coronary angiograms," *Physics in Medicine & Biology*, vol. 63, no. 15, p. 155019, 2018.
- [25] N. Sang, H. Li, W. Peng, and T. Zhang, "Knowledge-based adaptive thresholding segmentation of digital subtraction angiography images," *Image and Vision Computing*, vol. 25, no. 8, pp. 1263–1270, 2007.
- [26] B. Liu, Q. Jiang, W. Liu, M. Wang, S. Zhang, X. Zhang, B. Zhang, and Z. Yue, "A vessel segmentation method for serialized cerebralvascular dsa images based on spatial feature point set of rotating coordinate system," *Computer Methods and Programs in Biomedicine*, vol. 161, pp. 55–72, 2018.
- [27] O. Ronneberger, P. Fischer, and T. Brox, "U-net: Convolutional networks for biomedical image segmentation," in *International Conference on Medical image computing and computer-assisted intervention*. Springer, 2015, pp. 234–241.
- [28] H. Wu, W. Wang, J. Zhong, B. Lei, Z. Wen, and J. Qin, "Scs-net: A scale and context sensitive network for retinal vessel segmentation," *Medical Image Analysis*, vol. 70, p. 102025, 2021.
- [29] Y. Wu, Y. Xia, Y. Song, D. Zhang, D. Liu, C. Zhang, and W. Cai, "Vessel-net: Retinal vessel segmentation under multi-path supervision," in *International conference on medical image computing and computer-assisted intervention*. Springer, 2019, pp. 264–272.
- [30] L. Mou, Y. Zhao, H. Fu, Y. Liu, J. Cheng, Y. Zheng, P. Su, J. Yang, L. Chen, A. F. Frangi *et al.*, "Cs2-net: Deep learning segmentation of curvilinear structures in medical imaging," *Medical image analysis*, vol. 67, p. 101874, 2021.
- [31] S. Zhang, H. Fu, Y. Yan, Y. Zhang, Q. Wu, M. Yang, M. Tan, and Y. Xu, "Attention guided network for retinal image segmentation," in *International conference on medical image computing and computer-assisted intervention*. Springer, 2019, pp. 797–805.
- [32] W. Wang, J. Zhong, H. Wu, Z. Wen, and J. Qin, "Rvseg-net: An efficient feature pyramid cascade network for retinal vessel segmentation," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2020, pp. 796–805.

- [33] S. A. Kamran, K. F. Hossain, A. Tavakkoli, S. L. Zuckerbrod, K. M. Sanders, and S. A. Baker, "Rv-gan: segmenting retinal vascular structure in fundus photographs using a novel multi-scale generative adversarial network," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2021, pp. 34–44.
- [34] S. Y. Shin, S. Lee, I. D. Yun, and K. M. Lee, "Deep vessel segmentation by learning graphical connectivity," *Medical image analysis*, vol. 58, p. 101556, 2019.
- [35] Y. Zhou, H. Yu, and H. Shi, "Study group learning: Improving retinal vessel segmentation trained with noisy labels," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2021, pp. 57–67.
- [36] R. Xu, T. Liu, X. Ye, L. Lin, and Y.-W. Chen, "Boosting connectivity in retinal vessel segmentation via a recursive semantics-guided network," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2020, pp. 786–795.
- [37] H. Zhao, H. Li, and L. Cheng, "Improving retinal vessel segmentation with joint local loss by matting," *Pattern Recognition*, vol. 98, p. 107068, 2020.
- [38] D. Hao, S. Ding, L. Qiu, Y. Lv, B. Fei, Y. Zhu, and B. Qin, "Sequential vessel segmentation via deep channel attention network," *Neural Networks*, vol. 128, pp. 172–187, 2020.
- [39] H. Chen, J. Wang, H. C. Chen, X. Zhen, F. Zheng, R. Ji, and L. Shao, "Seminar learning for click-level weakly supervised semantic segmentation," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 6920–6929.
- [40] X. Luo, M. Hu, W. Liao, S. Zhai, T. Song, G. Wang, and S. Zhang, "Scribble-supervised medical image segmentation via dual-branch network and dynamically mixed pseudo labels supervision," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2022, pp. 528–538.
- [41] L. Yang, W. Zhuo, L. Qi, Y. Shi, and Y. Gao, "St++: Make self-training work better for semi-supervised semantic segmentation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 4268–4277.
- [42] W. Liu, W. Xu, S. Yan, L. Wang, H. Li, and H. Yang, "Combining self-training and hybrid architecture for semi-supervised abdominal organ segmentation," in *Fast and Low-Resource Semi-supervised Abdominal Organ Segmentation: MICCAI 2022 Challenge, FLARE 2022, Held in Conjunction with MICCAI 2022, Singapore, September 22, 2022, Proceedings*. Springer, 2023, pp. 281–292.
- [43] X. Chen, Y. Yuan, G. Zeng, and J. Wang, "Semi-supervised semantic segmentation with cross pseudo supervision," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021, pp. 2613–2622.
- [44] Y. Ouali, C. Hudelot, and M. Tami, "Semi-supervised semantic segmentation with cross-consistency training," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020, pp. 12 674–12 684.
- [45] M. Tang, F. Perazzi, A. Djelouah, I. Ben Ayed, C. Schroers, and Y. Boykov, "On regularized losses for weakly-supervised cnn segmentation," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018, pp. 507–522.
- [46] X. Luo, W. Liao, J. Xiao, J. Chen, T. Song, X. Zhang, K. Li, D. N. Metaxas, G. Wang, and S. Zhang, "Word: A large scale dataset, benchmark and clinical applicable study for abdominal organ segmentation from ct image," *Medical Image Analysis*, vol. 82, p. 102642, 2022.
- [47] D. Lachinov, P. Seeböck, J. Mai, F. Goldbach, U. Schmidt-Erfurth, and H. Bogunovic, "Projective skip-connections for segmentation along a subset of dimensions in retinal oct," in *International Conference on Medical Image Computing and Computer-Assisted Intervention*. Springer, 2021, pp. 431–441.
- [48] N. Ballas, L. Yao, C. Pal, and A. C. Courville, "Delving deeper into convolutional networks for learning video representations," in *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, Y. Bengio and Y. LeCun, Eds., 2016. [Online]. Available: <http://arxiv.org/abs/1511.06432>
- [49] P. Yan, G. Li, Y. Xie, Z. Li, C. Wang, T. Chen, and L. Lin, "Semi-supervised video salient object detection using pseudo-labels," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2019, pp. 7284–7293.
- [50] D.-H. Lee *et al.*, "Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks," in *Workshop on challenges in representation learning, ICML*, vol. 3, no. 2, 2013, p. 896.
- [51] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," *arXiv preprint arXiv:1711.05101*, 2017.
- [52] J. Schlemper, O. Oktay, M. Schaap, M. Heinrich, B. Kainz, B. Glocker, and D. Rueckert, "Attention gated networks: Learning to leverage salient regions in medical images," *Medical image analysis*, vol. 53, pp. 197–207, 2019.
- [53] Z. Zhou, M. M. Rahman Siddiquee, N. Tajbakhsh, and J. Liang, "Unet++: A nested u-net architecture for medical image segmentation," in *Deep learning in medical image analysis and multimodal learning for clinical decision support*. Springer, 2018, pp. 3–11.
- [54] X. Xiao, S. Lian, Z. Luo, and S. Li, "Weighted res-unet for high-quality retina vessel segmentation," in *2018 9th international conference on information technology in medicine and education (ITME)*. IEEE, 2018, pp. 327–331.
- [55] M. Li, Y. Chen, Z. Ji, K. Xie, S. Yuan, Q. Chen, and S. Li, "Image projection network: 3d to 2d image segmentation in octa images," *IEEE Transactions on Medical Imaging*, vol. 39, no. 11, pp. 3343–3354, 2020.
- [56] Y. Grandvalet and Y. Bengio, "Semi-supervised learning by entropy minimization," *Advances in neural information processing systems*, vol. 17, 2004.
- [57] M. Tang, A. Djelouah, F. Perazzi, Y. Boykov, and C. Schroers, "Normalized cut loss for weakly-supervised cnn segmentation," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 1818–1827.
- [58] Y. Wu, F. Li, Y. Wang, T. Hu, and L. Xiao, "Utility of minimum intensity projection images based on three-dimensional cube t 1 weighted imaging for evaluating middle cerebral artery stenosis," *The British Journal of Radiology*, vol. 94, no. 1121, p. 20210145, 2021.
- [59] J. Khankari, Y. Yu, J. Ouyang, R. Hussein, H. M. Do, J. J. Heit, and G. Zaharchuk, "Automated detection of arterial landmarks and vascular occlusions in patients with acute stroke receiving digital subtraction angiography using deep learning," *Journal of NeuroInterventional Surgery*, vol. 15, no. 6, pp. 521–525, 2023.