Causal Structure Learning by Using Intersection of Markov Blankets

Yiran Dong 12235035@zju.edu.cn

School of Mathematical Sciences Zhejiang University Hangzhou 310027, China.

Chuanhou Gao Gaochou@zju.edu.cn

School of Mathematical Sciences Zhejiang University Hangzhou 310027, China.

Editor: My editor

Abstract

In this paper, we introduce a novel causal structure learning algorithm called Endogenous and Exogenous Markov Blankets Intersection (EEMBI), which combines the properties of Bayesian networks and Structural Causal Models (SCM). Exogenous variables are special variables that are applied in SCM. We find that exogenous variables have some special characteristics and these characteristics are still useful under the property of the Bayesian network. EEMBI intersects the Markov blankets of exogenous variables and Markov blankets of endogenous variables, i.e. the original variables, to remove the irrelevant connections and find the true causal structure theoretically. Furthermore, we propose an extended version of EEMBI, namely EEMBI-PC, which integrates the last step of the PC algorithm into EEMBI. This modification enhances the algorithm's performance by leveraging the strengths of both approaches. Plenty of experiments are provided to prove that EEMBI and EEMBI-PC have state-of-the-art performance on both discrete and continuous datasets.

Keywords: Structure learning, Bayesian network, Structure causal model, Exogenous variables, Markov blanket

1 Introduction

Causal structure learning, or causal discovery [\(Glymour et al.](#page-38-0) [\(2016\)](#page-38-0)), aims to find the causal relation of features in datasets and generate a graph based on causal relations. Knowing the causal relation can increase the interpretability of data and contribute to the feature selection [\(Li et al.](#page-39-0) [\(2017\)](#page-39-0)) or feature intersection process [\(Luo et al.](#page-39-1) [\(2019\)](#page-39-1)). More and more graphical models are proposed in all kinds of areas. In picture generating, Variational AutoEncoder (VAE) [\(Kingma](#page-39-2) [and Welling](#page-39-2) [\(2013\)](#page-39-2); [Kingma et al.](#page-39-3) [\(2019\)](#page-39-3)) and diffusion model [\(Sohl-Dickstein et al.](#page-40-1) [\(2015\)](#page-40-1); [Ho](#page-38-1) [et al.](#page-38-1) [\(2020\)](#page-38-1)) use probability graphical model [\(Koller and Friedman](#page-39-4) [\(2009\)](#page-39-4)) to approximate the joint distribution of data and they can generate new pictures from the joint distribution. In natural language processing, Latent Dirichlet Allocation (LDA) [\(Blei et al.](#page-38-2) [\(2003\)](#page-38-2)) and stochastic variational inference (Hoff[man et al.](#page-38-3) [\(2013\)](#page-38-3)) are topic models based on the Bayesian network to gather the topic information from massive document collections. Furthermore, Graph Neural Network (GNN) [\(Scarselli et al.](#page-40-2) [\(2008\)](#page-40-2); [Zhou et al.](#page-40-3) [\(2020\)](#page-40-3)) uses the graph structure of the dataset as prior knowledge to construct different kinds of neural networks. With the development of graphical model, causal

[©]2023 Yiran Dong and Chuanhou Gao.

structure learning becomes an important question since a good graph structure can dramatically improve the generative and predictive ability of graphical models.

There are three basic types of causal structure learning algorithms at the beginning [\(Scutari](#page-40-4) [et al.](#page-40-4) [\(2018\)](#page-40-4)). Constraint-based methods, like the PC algorithm [\(Spirtes et al.](#page-40-5) [\(1999\)](#page-40-5); [Colombo](#page-38-4) [et al.](#page-38-4) [\(2014\)](#page-38-4)), build the graph structure based on conditional independence in the dataset. Scorebased methods, like the Greedy Equivalence Search (GES) [\(Chickering](#page-38-5) [\(2002\)](#page-38-5)), aim to maximize the corresponding score to find the optimal graph structure. And hybrid methods mix the property of both methods. Max-Min Hill Climbing (MMHC) [\(Tsamardinos et al.](#page-40-6) [\(2006\)](#page-40-6)) is a typical hybrid causal discovery algorithm, it uses the constraint-based method to find the skeleton of the graph and uses GES to orient every edge. Recently, more and more different types of causal learning methods are proposed, like constraint functional causal models, permutation-based methods, etc.

Linear Non-Gaussian Acyclic Model (LiNGAM) [\(Shimizu et al.](#page-40-7) [\(2006\)](#page-40-7)) is one of the constraint functional causal models. It uses Independent Component Analysis (ICA) (Hyvärinen and [Oja](#page-38-6) [\(2000\)](#page-38-6)) to identify the exogenous variables among the original features. However, in SCM [\(Bollen](#page-38-7) [\(1989\)](#page-38-7)), observed variables are called endogenous variables. Exogenous variables, as latent variables, have no parent and contain all the randomicity of endogenous variables. Therefore, it is inappropriate for LiNGAM and its variants to find exogenous variables from endogenous variables. Moreover, LiNGAM and its variants can only find part of the exogenous variables. If we can find all the exogenous variables for every endogenous variable, learning the connections in endogenous variables will be much easier and more accurate by using the properties of exogenous variables.

Inspired by LiNGAM and SCM, we propose EEMBI and EEMBI-PC algorithms which are the mixtures of constraint-based and constraint functional causal models. EEMBI wants to find exogenous variables and uses them to remove the redundant edges. Different from LiNGAM and its variants, EEMBI uses ICA to generate all the exogenous variables directly under the causal sufficiency assumption. In the Markov blanket of node *T*, there is not only children and parents of *T* but also some extra spouses nodes of *T*. It is easy to identify these spouse nodes by using the exogenous variable of *T*. Therefore, EEMBI has four phases

- (1) Find the Markov blanket for every endogenous variable;
- (2) Generate all exogenous variables and match them with endogenous variables;
- (3) Find the parents for every endogenous variable using the Markov blanket of exogenous variables and build a Bayesian network;
- (4) Turn the Bayesian network to a Completed Partially Directed Acyclic Graph (CPDAG).

If we turn the Bayesian network in (3) as the skeleton the of graph and use the PC algorithm to orient the edges, we have EEMBI-PC algorithms.

The rest of the paper is organized as follows: Section 2 gives some background knowledge including properties of the Bayesian network, SCM, and ICA. In Section 3, we give our improved IAMB algorithms to find Markov blankets for endogenous variables. In Section 4, we give the main body of EEMBI and EEMBI-PC, i.e. algorithms that generate corresponding exogenous variables and find the parent nodes for endogenous variables. We also provide plenty of theorems to guarantee their efficiency. In Section 5, we compare EEMBI and EEMBI-PC with a number of baselines on discrete and continuous datasets. We conclude the paper in Section 6.

Notation: We use italicized lowercase letters and lowercase Greek, like x, y, α, β to represent single nodes or scalars. Column vectors are set as bold lowercase letters. Decorative uppercase letters represent sets, such as X, Y . Italicized uppercase letters, like A, B, E , can either be sets or scalars, depending on the context. Matrices are denoted by bold uppercase letters.

2 Preliminaries

In this section, we give some basic information about Bayesian networks, causal structure learning, and structural causal models. Then we simply introduce the principle of Independent Component Analysis (ICA).

2.1 Foundation of Bayesian Network

A graph structure, represented as $G = (X, \mathcal{E})$ [\(Koller and Friedman](#page-39-4) [\(2009\)](#page-39-4)), consists of the nodes X and the edges $\mathcal E$ between nodes. If a graph structure $\mathcal G$ whose nodes are also the features of the dataset X, and every edge is directed i.e. it has one source and one target, we call this graph a Bayesian network. For any edges $x \to y \in \mathcal{E}$, we call x the parent of y, and y is the child of x. We denote the parents of *x* as Pa_x and children of *x* as Ch_x . If $x \to z \leftarrow y \in \mathcal{E}$, then we call *y* a spouse of *x*. The union of *Chx*, *Pax*, and all spouses of *x* is defined as Markov blanket of *x*, denoted as *MBx*. Now we give some basic definitions about the Bayesian network.

Definition 1 *For a subset of nodes x*0, *^x*1, ..., *^xⁿ in the Bayesian network, if there are directed edges between these nodes such that* $x_0 \rightarrow x_1 \rightarrow x_2 \rightarrow ... \rightarrow x_n$ *, we say that* $x_0, x_1, ..., x_n$ *form a path. Moreover, If there is a path such that* $x_0 \to x_1 \to \dots \to x_n$ *where* $x_n = x_0$ *, we call this path a cycle.*

If there is no cycle in the Bayesian network G , we define G as a Directed Acyclic Graph (DAG). In this and the latter section, we mainly discuss the Bayesian network in condition of DAG. Normally, we use DAG G to represent the joint distribution P of the dataset **X**, whose nodes X are random variables in P . According to the edges in \mathcal{E} , we can decompose the joint distribution by using a conditional probability distribution,

$$
P = \prod_{x \in X} P(x \mid Pa_x) \tag{1}
$$

DAG is composed of three basic structures: (1) chain: $x_i \rightarrow x_j \rightarrow x_k$; (2) fork: $x_i \leftarrow x_j \rightarrow x_k$; (3) V-structure: $x_i \rightarrow x_j \leftarrow x_k$. Specifically, x_j in V-structure is called a collider.

Now, consider a chain $x_i \rightarrow x_j \rightarrow x_k$ as a whole DAG, we can decompose the chain according to equation [\(1\)](#page-2-0),

$$
P(x_i, x_j, x_k) = P(x_k | x_j)P(x_j | x_i)P(x_i)
$$

$$
P(x_i, x_j, x_k)/P(x_j) = P(x_k | x_j)P(x_j, x_i)/P(x_j)
$$

$$
P(x_i, x_k | x_j) = P(x_k | x_j)P(x_i | x_j)
$$

Therefore, we get x_i and x_k are conditional independent given x_j , denoted as $x_i \perp x_k | x_j$. Following the similar procedure, we have $x_i \perp x_k | x_j$ in fork and $x_i \perp x_k | \emptyset$ in V-structure where \emptyset is empty set.

Each of these basic structures contains a single conditional independency, large DAG may contain numerous conditional independencies. Thus the Bayesian network is one of the structural representations of joint distribution *P*. By learning the true structure of the Bayesian network in X, we can accurately capture the true conditional independency relationships between random variables, thus approaching the true joint distribution *P* more closely. This is one of the motivations that we need to learn the structure of the Bayesian network from the dataset. To establish a direct connection between conditional independency and graphical structure, we introduce d-separation.

Definition 2 *We say* $x_0, x_1, ..., x_n$ ∈ *X form a trail if* x_0 $\rightleftharpoons x_1$ $\rightleftharpoons ...$ $\rightleftharpoons x_n$ *where* " \rightleftharpoons " *stands for "* \rightarrow " *or "* \leftarrow ". Moreover, for a subset $Z \subset X$, if the trail satisfies (1) For any V-structure $x_i \to x_{i+1} \leftarrow x_{i+2}$ *in the trail, the collider* $x_{i+1} \in Z$; (2) There is no other node in the trail belongs *to Z. Then we call that the trail is active given Z.*

Definition 3 Let A, B, and C be three disjoint subset nodes in DAG G. If for any node $x \in A$ and *any node y* ∈ *B, there is no active trail given C, we call A and B are d-separated given C, denoted* $as A \perp^d B \mid C.$

Observing the d-separation in three basic structures, we can find that basic structures have exactly the same d-separated relationship and conditional independencies. Expanding from the basic structures to the larger DAG, we have the following theorem.

Theorem 4 *Let A, B, and C be three disjoint subset nodes in DAG* G*. A and B are d-separated given C if and only if A and B are independent given C. i.e.* $A \perp B \mid C \Longleftrightarrow A \perp B \mid C$ *.*

The detailed proof of **Theorem [4](#page-3-0)** can be found in [Pearl](#page-39-5) [\(1988\)](#page-39-5). **Theorem 4** gives us a theoretical basis that we can construct the graph by using conditional independencies. Therefore, the key to learn the structure of DAG is to find all the conditional independencies in random variables of the dataset. However, the chain and fork structures have the same conditional independency with different structures. That is to say, different DAGs may contain exactly the same conditional independencies.

Definition 5 *Let* G *and* H *be two DAGs, we denote the set of all conditional independencies in* G as $I(G)$ and the set of all conditional independencies in distribution P as $I(P)$ *.* If $I(G) = I(H)$ *, we say* G *and* H *are I-equivalent.*

The aim of structure learning is not only to find one DAG that $I(G) = I(P)$, but to find all the DAGs which are I-equivalent to G [\(Koller and Friedman](#page-39-4) [\(2009\)](#page-39-4)).

Theorem 6 *Let* G *and* H *be two DAGs, we define the skeleton of* G *to be a graph structure that replaces the directed edges in* G *as undirected edges.* G *and* H *are I-equivalent if and only if* G *and* H *have the same skeleton and same V-structures.*

Having the method to find all the I-equivalent DAGs, we still need some methods to represent the I-equivalent class.

Definition 7 *A Partially Directed Acyclic Graph (PDAG) is an acyclic graph which contains both directed edges and undirected edges. We say a PDAG* H *is Completed Partially Directed Acyclic Graph (CPDAG) of* G*, if* H *satisfies*

(1) H *and* G *have the same skeletons;*

(2) H contains the directed edge $x_i \rightarrow x_k$ *if and only if all the I-equivalent graphs of* G *contain this edge.*

Figure 1: (a), (b) and (c) are examples of Bayesian networks, PDAG, and CPDAG. (a) is also a DAG since it has no cycle. (b) has both directed and undirected edges, but it is not CPDAG since it changes the V-structure of (a). (c) is the CPDAG of (a), it keeps the V-structure $x_4 \to x_2 \leftarrow x_3$. (c) also keeps $x_2 \rightarrow x_5$, since if we reverse the direction of this edge, it will form a new V-structure and the new graphs will not be I-equivalent to (a) anymore.

The differences between DAG, PDAG and CPDAG are shown in Figure [1.](#page-4-0) Almost all the structure learning algorithms return a CPDAG, and many algorithms learn the structure based on Theorem [6](#page-3-1), i.e. they learn the skeleton of CPDAG, and then based on this skeleton to find all the V-structures.

In addition to the theoretical basics, many of the causal structure learning algorithms, like PC, MMHC, or Structural Agnostic Modeling (SAM) [\(Kalainathan et al.](#page-38-8) [\(2022\)](#page-38-8)), require the causal sufficiency assumption of the dataset [\(Eberhardt and Scheines](#page-38-9) [\(2007\)](#page-38-9)). This assumption posits that there is no latent variable that is a common cause of any pair of nodes. By assuming causal sufficiency, these algorithms aim to discover the causal relationships among observed variables without considering hidden confounding factors, which simplifies the tasks and identifies the direct causal relationships.

We take the PC algorithm as an example. The PC algorithm is one of the most commonly used constraint-based methods. We show the process of it in Figure [2.](#page-5-0) PC algorithm starts at a fully connected undirected graph, and for every pair of nodes $x, y \in X$, PC algorithm violently traverses all the subset $Z \subset X\backslash \{x, y\}$. Then it uses the conditional independence test in statistics, like Randomized Conditional Independence Test (RCIT), Hilbert-Schmidt Independence Test (HSIT), Gaussian conditional independence test (G-test), to test whether $x \perp y \mid Z$. If the PC algorithm finds a *Z* such that $x \perp y \mid Z$, then it makes *x*, *y* disconnected. This procedure or similar methods are contained in many constraint-based structure learning algorithms. It based on the theorem that two nodes *x*, *y* are connected if and only if there is no subset $Z \subset X\{x, y\}$ such that *x*, *y* are d-separated given *Z*. After this procedure, we have the skeleton of the graph (the first arrow in Figure [2\)](#page-5-0). For V-structure, PC algorithm traverses all triples x_i , x_j , x_k , if for any $Z \subset X\setminus \{x_i, x_k\}$ which satisfies $x_i \perp x_j \perp Z$ and $x_i \notin Z$ then x_i , x_j form a M structure i.e. $x_i \rightarrow x_j \notin Z$ (the second arrow in $x_i \perp x_k$ | Z and $x_j \notin Z$, then x_i, x_j, x_k form a V-structure, i.e. $x_i \to x_j \leftarrow x_k$ (the second arrow in
Figure 2). Finally, we give directions on other undirected edges as much as we can by following Figure [2\)](#page-5-0). Finally, we give directions on other undirected edges as much as we can by following Meek's rules [\(Meek](#page-39-6) [\(2013\)](#page-39-6)).

Figure 2: The process of the PC algorithm.

Definition 8 *Let* G *be a PDAG.*

- *(1) If* x_i → x_j ∈ $\&$ *and* x_j − x_k ∈ $\&$, *then orient* x_j − x_k *into* x_j → x_k *;*
- *(2) If* x_i → x_j → x_k ∈ $\&$ *and* x_i − x_k ∈ $\&$, *then orient* x_i − x_k *into* x_i ← x_k *;*
- (3) If $x_i x_j \to x_k \in \mathcal{E}$, $x_i x_l \to x_k \in \mathcal{E}$, $x_i x_k \in \mathcal{E}$, and x_j , x_l are disconnected, then orient $x_i - x_k$ *into* $x_i \rightarrow x_k$ *.*

We define these three rules as Meek's rules.

Meek's rules prevent the DAG which can be represented by the CPDAG from having a cycle or forming a new V-structure (the third arrow in Figure [2\)](#page-5-0). After these three steps, the PC algorithm returns a CPDAG.

Different methods in causal discovery exhibit distinct principles. GES transforms the structure learning problem into an optimization task, where it seeks to learn the CPDAG by optimizing the Bayesian Information Criterion (BIC) score. But all the causal discovery algorithms are still rely on fundamental principles Theorem [4](#page-3-0) and Theorem [6](#page-3-1).

2.2 Structural Causal Model

Structural Causal Model (SCM) or Structural Equation Model (SEM) [\(Bollen](#page-38-7) [\(1989\)](#page-38-7)) is one of the important tools in causal structure learning. It provides another way to study the Bayesian network.

Definition 9 *We define the structural causal model as* $M = (X, Y, D_X, D_Y, \mathcal{F}, P_Y)$ *and define*

- *(1)* X *is the set of endogenous variables and* Y *is the set of exogenous variables.*
- *(2)* D_X = $\prod_{x \in X} D_x$ *and* D_y = $\prod_{e \in Y} D_e$ *where* D_x *and* D_e *are the codomains of endogenous variable x and exogenous variable e.*
- *(3)* $\mathcal{F} = \{f_x, x \in \mathcal{X}\}\$ is the set of measurable functions f_x which maps the codomain of $\mathcal{X} \cup \mathcal{Y}\setminus\{x\}$ *to the codomain of* $x \in X$.
- (4) $P_y = \prod$ *e*∈Y *P^e is the joint distribution function of exogenous variables* Y*.*

Comparing the definition of Bayesian network and SCM, we find that SCM has two sets of nodes, endogenous and exogenous nodes. Endogenous variables are the observed variables in the

dataset, and exogenous variables are hidden variables. Although the nodes in the Bayesian network are the same as endogenous variables in SCM, SCM does not treat variables in the dataset as random variables, it puts the randomicity of features into exogenous variables and assumes the independence of exogenous variables. This is why SCM only has the distribution functions for exogenous variables $P_y = \prod P_e$ and does not have distribution functions of endogenous variables. *e*∈Y SCM assumes that as long as we know all the randomicity, the endogenous variable can be determined by the randomicity and other endogenous variables. Therefore, instead of putting the edges E into M, SCM defines a set of maps $\mathcal{F}: D_X \times D_Y \to D_X$. SCM not only puts the structure into \mathcal{F} but also puts the models and parameters into \mathcal{F} .

Definition 10 *Let* $M = (X, Y, D_X, D_Y, \mathcal{F}, P_Y)$ *be a SCM. For any endogenous* $x \in X$ *and variables z* ∈ $X \cup Y$ *, let* $\tilde{X} = X \setminus \{z\}$ *and* $\tilde{Y} = Y \setminus \{z\}$ *, z is a parent of x if and only if there is no* $\tilde{f}_x : D_{\tilde{X} \setminus \{x\}} \times D_{\tilde{Y}}$ → *D^x such that*

$$
x = f_x(X \setminus \{x\}, \mathcal{Y}) \Longleftrightarrow x = \tilde{f}_x(\tilde{X} \setminus \{x\}, \tilde{\mathcal{Y}}).
$$

Different from the nodes in CPDAG, *x* and *y* can not be the parent of each other, since they both have their corresponding exogenous variables as parents and the functional relationship can not be reversed. Thus $z \in X \cup Y$ is a parent of $x \in X$ if and only if x is not deterministic by any transformation of f_x without knowing *z* [\(Olkope and Mooij](#page-39-7) [\(2016\)](#page-39-7)). And exogenous variables are not deterministic, so they do not have any parents.

We give a simple example of SCM. Let us consider the influencing factors of a student's final test grade. Let *s* be the score of his final test grade, *t* be the time this student spends on this course, *d* be the difficulty of the final test. For simplicity, we assume the values of these three variables have no boundary. We put randomicity of s, t, d into e_s , e_t , e_d . For example, e_s can be the health condition of the student on the day of the final test e_s can be the family influence on student e_t can condition of the student on the day of the final test, e_t can be the family influence on student, e_d can be the mood of the teacher when he writes the questions. Thus *^s*, *^t*, *^d* are the endogenous variables, e_s , e_t , e_d are the exogenous variables. If we know the set of functions $\mathcal{F} = \{f_d, f_t, f_s\}$,

$$
d = f_d(e_d) = 3e_d + 1
$$

\n
$$
t = f_t(e_t) = e_t^2
$$

\n
$$
s = f_s(d, t, e_s) = 10t - 2d + 3e_s + 5.
$$

and by **Definition [10](#page-6-0)**, we have the structure of SCM in Figure [3.](#page-7-0) If e_s , e_t , e_d follow standard Gaus-
sign distribution i.i.d. we have the SCM in this example $M - \left(\int_S t \, dV \right) e^{-\rho} e^{-\rho} dV \mathbb{R}^3 \mathbb{R}^3 \nsubseteq (\Phi(r))^3$ sian distribution i.i.d, we have the SCM in this example $M = (\{s, t, d\}, \{e_s, e_t, e_d\}, \mathbb{R}^3, \mathbb{R}^3, \mathbb{F}, (\Phi(x))^3)$
where \mathbb{R} is the set of all real numbers and $\Phi(x)$ is the distribution function of standard Gaussian d where $\mathbb R$ is the set of all real numbers and $\Phi(x)$ is the distribution function of standard Gaussian distribution.

2.3 Independent Component Analysis

Independent Component Analysis (ICA) (Hyvärinen and Oja [\(2000\)](#page-38-6)) aims to find the source messages from given mixed messages. Let $\mathbf{x} = (x_1, x_2)$ be two messages which are mixed of two independent source messages $\mathbf{s} = (s_1, s_2)$. Then ICA wants to construct the functions F_1, F_2 such that

$$
s_1 = F_1(x_1, x_2),
$$

$$
s_2 = F_2(x_1, x_2).
$$

Figure 3: The structure of SCM in the final test example.

To achieve the independence of s_1 and s_2 , ICA minimizes the mutual information of s_1 and s_2 , $I(s_1, s_2)$. But the actual value of mutual information is hard to compute, especially when the dimension of source messages is more than 2, i.e. $I(s_1, s_2, ..., s_n)$ where $n > 2$.

FastICA is the most commonly used method in ICA problems [\(Hyvarinen](#page-38-10) [\(1999\)](#page-38-10)), it assumes F_1 and F_2 to be linear functions. With this assumption, it defines the negentropy of *x* as $J(x)$ = $H(x_{gauss}) - H(x)$ where x_{gauss} is a random variable that follows standard Gaussian distribution, then minimization of mutual information $I(s_1, s_2, ..., s_n)$ is equivalent to maximize $\sum_i J(s_i)$. Furthermore, *i*

we can make the loss function easier by making approximation on negentropy

$$
J(x) \approx \left[E(G(x)) - E(G(x_{gauss})) \right]^2, \tag{2}
$$

where *G* is chosen as $G(x) = \frac{1}{a} \log \cosh(ax)$ or $G(x) = -\exp(-\frac{1}{2})$ $\frac{1}{2}x^2$). We use *g* to denote the derivation of *G*. The whole FastICA algorithm is shown in Algorithm 1.

Algorithm 1 FastICA

Input: x, *n* 1: Centering $\mathbf{x}: \mathbf{x} = \mathbf{x} - E(\mathbf{x});$ 2: $C = E(xx^{\top})$; 3: **U**, **S**, **V** = *S VD*(**C**); 4: ${\bf x} = {\bf U} {\bf S}^{-\frac{1}{2}} {\bf U} {\bf x};$ 5: for *i* from 1 to *n* do 6: Initialize w_i ; 7: $\beta = E \left[\mathbf{w}_i^\top \right]$ \int_i^{\top} **x***g*(**w**_{*i*}^{\top}) $\left[\begin{matrix} \nabla \mathbf{x} \end{matrix}\right]$; 8: $\mathbf{w}_i^+ = \mathbf{w}_i - \mu \left\{ E \left[\mathbf{x} g(\mathbf{w}_i^- \right] \right\}$ \int_{i}^{\top} **x**)] $-\beta \mathbf{w}_{i}$ $\Big\}$ $\Big\{ E\Big[g'(\mathbf{w}_{i}^{\top})\Big]$ $\begin{bmatrix} \nabla \mathbf{x} \end{bmatrix} - \beta;$ 9: $\mathbf{w}_i = \mathbf{w}_i^+ / || \mathbf{w}_i^+ ||;$ 10: **if** $i > 0$ then 11: $\mathbf{w}_i = \mathbf{w}_i - \sum_{i=1}^{i-1}$ *j*=1 $\mathbf{w}_i^{\top} \mathbf{w}_j \mathbf{w}_j$; 12: $\mathbf{w}_i = \mathbf{w}_i / || \mathbf{w}_i ||;$ 13: end if 14: end for **Output:** $W = [w_1, ..., w_n]$

In the input of **Algorithm 1, x** is the vector of observed variables. FastICA needs the sample of **x** to compute the mean and covariance of **x**. *n* is the dimension of source messages **s**. Commonly, $n =$ $\dim s = \dim x$. Line 2 to line 4 is called the whitening step. $SVD(C)$ stands for the singular value decomposition of the positive definite matrix C . Whitening can make the covariance matrix of x become an identity matrix, i.e. $E(\mathbf{x}\mathbf{x}^{\top}) = \mathbf{I}$. It helps reduce the dimension of parameters, reduce the noise, and prevent overfitting. Line 7 to line 9 are using Newton's method to maximize equation [\(2\)](#page-7-1) under the constraint $E((\mathbf{w}_i^{\top})$ $\binom{1}{i}$ x)²) = 1 where β is the Lagrange multiplier of this constraint. To prevent
ing to the same vector, line 10 to line 12 decorrelate **w**, from **w**, different w_i from converging to the same vector, line 10 to line 12 decorrelate w_i from $w_1, ..., w_{i-1}$ based on Gram-Schmidt-like method [\(Kantorovich and Akilov](#page-39-8) [\(2016\)](#page-39-8)). FastICA algorithm returns the *n* × *n* coefficient matrix, then $\mathbf{s} = \mathbf{W}^\top \mathbf{x}$.

3 Improved Incremental Association Markov Blanket

The Incremental Association Markov Blanket (IAMB) algorithm [\(Tsamardinos et al.](#page-40-8) [\(2003\)](#page-40-8)) was proposed to find the Markov blanket of nodes. In this section, we improve the IAMB algorithm and give theoretical analyses of it.

We give our improved IAMB in **Algorithm 2.**

```
Algorithm 2 Improved IAMB
```

```
Input: data set X, number of nodes n, α
 1: Initialize all the Markov Blanket of nodes {CMB1, ...,CMBn} as empty set ∅;
 2: for i from 1 to n do
 3: S = \{x_1, x_2, ..., x_n\};<br>4: while CMB<sub>i</sub> is cha
 4: while CMB_i is changed do
 5: Find the node x_j \in S j \neq i that maximizes I(x_i; x_j | CMB_i);
 6: if I(x_i; x_j | CMB_i) > \alpha then<br>7. Add x, in CMB.
 7: Add x_j in CMB<sup>i</sup>;
 8: Remove x_j from S;
 9: end if
10: end while
11: for node x_k in CMB_i do
12: if I(x_i; x_k | CMB_i \setminus \{x_k\}) < \alpha then<br>
Bemove x<sub>1</sub> from CMB_i<sup>x</sup>
13: Remove x_k from CMB_i;
14: end if
15: end for
16: end for
17: for i from 1 to n do
18: for node x_j in CMB_i do
19: if x_i \notin CMB_j then
20: Remove x_j from CMB_i;
21: end if
22: end for
23: end for
Output: {CMB1,CMB2, ...,CMBn}
```
Improved IAMB uses Conditional Mutual Information (CMI) to find all the conditional independencies. In the beginning, we use *CMBⁱ* to represent the candidate of the true Markov blanket *MB*^{*i*} and initialize *CMB*^{*i*} as an empty set for $i = 1, 2, ..., n$. Line 2 to line 10 is the forward phase, it is mainly based on the total conditioning property of Markov blankets [\(Pellet and Elissee](#page-39-9)ff [\(2008\)](#page-39-9)).

Theorem 11 (Total Conditioning) Let x and y be random variables in data set **X**, then $y \in MB_x$ if *and only if* $x \not\perp y \mid X \setminus \{x, y\}$ *.*

Theorem [11](#page-9-0) establishes that two nodes exhibit a strong dependent relationship if one node is part of the other node's Markov blanket. Therefore if a node has the highest CMI with the target node, then it is likely to be a member of the target node's Markov blanket. In the forward phase, we iterate through every node x_i , and find the node x_j that maximizes the value of CMI given current CMB_i . If the CMI is big enough, i.e. it exceeds a predefined threshold α , we will add the node into the *CMBⁱ* . We continue the forward phase until *CMBⁱ* remains unchanged. Ultimately, *CMBⁱ* contains *MB*^{*i*} after the forward phase for $i = 1, 2, ..., n$.

For the each node x_i that after the forward phase, it follows the backward phase. the backward phase is based on the theorem below,

Theorem 12 Let x and y be two random variables. If $y \notin MB_x$, then $x \perp\!\!\!\perp y \mid MB_x$ and $x \perp\!\!\!\perp y \mid MB_y$. *Moreover, for any subsets of nodes* $Z \subset X$ *that* $x, y \notin Z$ *and* $MB_x \cap Z = \emptyset$ *, then* $x \perp y \mid MB_x \cup Z$.

Proof The detailed proof can be found in Appendix A.

If x_j is not in MB_i , then $MB_i \subset CMB_i\setminus\{x_j\}$. We can divide $CMB_i\setminus\{x_j\}$ into two parts $CMB_i\setminus\{x_j\}$ *MB*^{*i*} ∪ *Z*. Then by the **Theorem [12](#page-9-1)**, we have $x_i \perp x_j \mid CMB_i \setminus \{x_j\}$. Thus in the backward phase, we pick every node in CMB_i to compute the CMI $I(x_i; x_j | CMB_i \setminus \{x_j\})$. If the CMI is smaller than the threshold, we see x_i and x_j are conditional independence and remove x_j from CMB_i .

Different from the original IAMB, the improved IAMB has the checking phase after doing the forward phase and backward phase on every node in X . The checking phase is based on the simple fact that

$$
y\in MB_x\Longleftrightarrow x\in MB_y,
$$

i.e. the symmetry of Markov blankets. For node x_i , we check every node x_j in the CMB_i of x_i that whether x_i also belongs to the CMB_j . If not, we exclude x_j from CMB_i .

CMI is a powerful measure to estimate conditional independencies. However, the computation of CMI is much more complex than the computation of mutual information. In the original IAMB algorithm, CMI is computed based on the definition, which requires a large amount of data to obtain accurate estimates. Additionally, we need to do discretization before applying the original IAMB on continuous datasets. However, continuous data may lose its information after discretization, resulting in CMI estimates that may deviate significantly from the true values.

In improved IAMB, we apply *k*th nearest neighbour conditional mutual information (kNN-CMI) which is proposed in [Mesner and Shalizi](#page-39-10) [\(2020\)](#page-39-10). Let *X*, *Y*, *Z* \subset *X* be three disjoint sets of random variables. To compute $I(X; Y | Z)$, kNN-CMI computes the l_{∞} distance $\rho_{k,i}$ of $(\mathbf{x}_i, \mathbf{y}_i, \mathbf{z}_i)$ to the *k*th nearest neighbor (kNN) with hyperparameter *k* in the dataset where $\mathbf{x}_i \cdot \mathbf{y}_i \cdot \mathbf{z}_i$ is nearest neighbor (kNN) with hyperparameter *k* in the dataset where $\mathbf{x}_i, \mathbf{y}_i, \mathbf{z}_i$ is the value of *X*, *Y*, *Z* on the *i*th instance. Then define N_{max} as on the *ⁱ*th instance. Then define *^NXY*,*ⁱ* as

$$
N_{XZ,i} = \left| \left\{ (\mathbf{x}_j, \mathbf{z}_j); || (\mathbf{x}_i, \mathbf{z}_i) - (\mathbf{x}_j, \mathbf{z}_j) || \le \rho_{k,i}, 1 \le j \le N \right\} \right|
$$

 \blacksquare

where ∥ · ∥ is the *l*[∞] norm and *N* is the total number of instances in the dataset. We can also define $N_{YZ,i}$ and $N_{Z,i}$ in a similar way. Then we define \tilde{k}_i as the number of instances whose distance to \tilde{k}_i as \tilde{k}_i as the number of instances whose distance to \tilde{k}_i as \tilde{k}_i as the two also count the h $(\mathbf{x}_i, \mathbf{y}_i, \mathbf{z}_i)$ is less or equal to $\rho_{k,i}$. The difference between \tilde{k}_i and k_i is that we also count the boundary
points into \tilde{k}_i . Apparently, \tilde{k}_i is equal to k_i on continuous data, since the points into \tilde{k}_i . Apparently, \tilde{k}_i is equal to k_i on continuous data, since the number of boundary points in the continuous condition is zero with probability one. Then we have the approximation of CMI on the *i*th instance:

$$
\xi_i = \psi(\tilde{k}_i) - \psi(N_{XZ,i}) - \psi(N_{YZ,i}) + \psi(N_{Z,i}),
$$

where ψ is derivation of logarithm gamma function $\psi(x) = \frac{d}{dx} \log \Gamma(x)$.

Then kNN-CMI uses $\frac{1}{N} \sum_{n=1}^{N}$ $\sum_{i=1}^{n} \xi_i$ to approximate *I*(*X*, *Y* | *Z*). Author in [Mesner and Shalizi](#page-39-10) [\(2020\)](#page-39-10) also proves that

$$
\lim_{N \to \infty} E\left(\frac{1}{N} \sum_{i=1}^{N} \xi_i\right) = I(X; Y | Z).
$$

kNN-CMI uses kNN to obtain the distance $\rho_{k,i}$, it does not depend on the type of data. There-
kNN CMI can directly compute the estimation of CMI for discrete, continuous, or even mixed fore kNN-CMI can directly compute the estimation of CMI for discrete, continuous, or even mixed datasets without losing any information. Moreover, kNN-CMI is one of the most accurate estimations of the true CMI under any size of sample size. Thus based on these properties of kNN-CMI, improved IAMB can return the candidate Markov blankets, which are close to true Markov blankets on any type of dataset.

Combing Theorem [11](#page-9-0), Theorem [12](#page-9-1), and the analyses above, we can guarantee the effectiveness of improved IAMB.

Corollary 13 If the conditional mutual information we compute satisfies $I(X; Y | Z) = 0$ if and only *if* $X \perp Y \mid Z$, then the improved IAMB returns the true Markov blankets for any small enough α *.*

4 Endogenous and Exogenous Markov Blankets Intersection

In this section, we introduce the main algorithms in this paper: endogenous and exogenous Markov blankets intersection (EEMBI) algorithm and EEMBI-PC. They use improved IAMB to obtain the Markov blankets of endogenous variables for the first step. Now we introduce the rest of the steps.

4.1 Generating and Matching of Exogenous Variables

The nodes in SCM are composed of endogenous variables X and exogenous variables Y . Every endogenous variable at least needs one endogenous variable to contain its randomicity. We can simplify this definition by letting $|X| = |Y|$ under the causal sufficiency assumption. We can put the randomicity of x_i into one exogenous variable e_i , and the randomicity of x_i has no influence on other endogenous variables because of the causal sufficiency assumption. Then every endogenous variable has only one parent in Y.

By **Definition [10](#page-6-0)**, we know that every endogenous node $x \in \mathcal{X}$ can be determined by its parents in X and *Y*. Therefore we can transform $f_i \in \mathcal{F}$ as

$$
x_i = f_i(Pa_i, e_i)
$$

where Pa_i is the parents of x_i in X . If we want to treat all the DAG as a SCM, we need to find the exogenous variables.

Let $X = \{x_1, ..., x_n\}$ and $\mathcal{Y} = \{e_1, ..., e_n\}$ where e_i is the exogenous variable corresponding to x_i . Using the acyclic characteristics of DAG, we can find an endogenous node x_j which has no parent in X and is only determined by its exogenous variable e_j , i.e. $x_j = f_j(e_j)$. Then we replace x_j with $f_j(e_j)$ in the function of its children. For example, if $x_i = f_i(x_j, x_k, e_i)$ is a child of x_i , we replace x_j
with f_i to obtain $x_i = f_i(f_i(e_i), x_i, e_i)$. After the replacement for all the children of x_j , we can still with f_j to obtain $x_i = f_i(f_j(e_j), x_k, e_i)$. After the replacement for all the children of x_j , we can still find another node *x*, which is only determined by the exogenous variables according to the acyclic find another node x_l which is only determined by the exogenous variables according to the acyclic characteristics of DAG, and continue the replacement for its children. At last, we can use exogenous variables to represent all the endogenous variables $x_i = g_i(e)$ where $e = (e_1, e_2, ..., e_n)^\top$ is the vector of all expressions variables, and *a*, is the combination of f_i , $i \in Pa_i$, and f_j . Then we have of all exogenous variables. and g_i is the combination of f_j , $j \in Pa_i$, and f_i . Then we have

$$
\mathbf{x} = \mathbf{g}(\mathbf{e}),\tag{3}
$$

where $\mathbf{x} = (x_1, x_2, ..., x_n)^\top$ is the vector of all endogenous and $\mathbf{g} = (g_1, g_2, ..., g_n)^\top$. Equation [\(3\)](#page-11-0) gives us a way to generate e. If we want to treat e as source messages, we need to state that e are independent with each other.

Firstly, If we see X and Y as a whole graph, it still satisfies the **Theorem [4](#page-3-0).** Although $x_i \in X$ is not a random variable and is determined by its parents, we can see the conditional distribution $P(x_i | Pa_i, e_i)$ as a Dirac distribution whose probability is one when $x_i = f_i(Pa_i, e_i)$ is zero otherwise. Thus the conditional independencies in basic structure achieve, and d-separation is equivalent to conditional independencies.

If all the path between two exogenous variables e_i , e_j contains at least one V-structure, then e_i
 e_j will be conditionally independent given the empty set i.e., they are independent. Let us and e_i will be conditionally independent given the empty set, i.e. they are independent. Let us assume there is a trail $e_i \rightarrow x_i \rightleftharpoons y_1 \rightleftharpoons y_2, ..., y_m \rightleftharpoons x_j \leftarrow e_j$ where $y_1, y_2, ..., y_m \in \mathcal{X}$ which has no V-structure. Then we can verify the first and the last \rightleftharpoons as \rightarrow and \leftarrow , and the trail become $e_i \rightarrow x_i \rightarrow y_1 \rightleftharpoons y_2, ..., y_m \leftarrow x_j \leftarrow e_j$. We can find that there are two reverse paths on this trail if we continue this process. Then there must be a V-structure in the cross of these two paths which is contradictory to our assumption. Thus we can have the conclusion that all the trails between e_i, e_j
are not active and all the exogenous variables are independent with each other are not active and all the exogenous variables are independent with each other.

With the independencies of exogenous variables, we can see **e** as source messages and endogenous variables x as the mixture of e in the ICA problem. Then we can use the method in ICA to recover or generate the exogenous variables. In this paper, we only use FastICA in **Section 2.3** to generate exogenous variables.

We still face a matching problem after generating e' , since the criteria in ICA are independencies and information. ICA does not have interpretability on source messages it generates. But to construct SCM, we need to find the corresponding exogenous variable for every endogenous variable and match them up. To avoid confusion, we denote the vector of the generated exogenous variables after matching as $\mathbf{e}' = (e'_1)$ $'_{1}, e'_{2}$ e'_{i} , ..., e'_{n}) where e'_{i} *i* is the generated exogenous variable corresponding to *xi* .

The only message about matching is that e_i is the only exogenous variable that directly connects with x_i . According to this property, we can use mutual information to make an assessment of their relationship.

Theorem 14 Let graph G be a trail $x \leq x_1 \leq ... \leq x_n$. Then we have

$$
I(x \, ; x_1) > I(x \, ; x_2) > \ldots > I(x \, ; x_n).
$$

For more general DAG G, if this trail is the only trail x can reach $x_1, x_2, ..., x_n$ *in* G *, the formula above also achieves.*

Proof The detailed proof can be found in Appendix A.

In the condition of **Theorem [14](#page-11-1)**, it is easy to obtain $I(x_i; e_i) > I(x_j; e_i)$, $i \neq j$. Furthermore, we extend this idea to more complex situations. Using **Theorem 14**, we have an important theorem can extend this idea to more complex situations. Using Theorem [14](#page-11-1), we have an important theorem for the matching process.

Theorem 15 *Let* $\mathbf{x} = (x_1, x_2, ..., x_n)^\top$ *be the vector of endogenous variables in graph* G *, and* $\mathbf{e} = (e_1, e_2, ..., e_n)^\top$ *be the vector of exogenous variables under some unknown arrangement (<i>i, i, j)* $(e_{i_1}, e_{i_2}, ..., e_{i_n})^{\top}$ *be the vector of exogenous variables under some unknown arrangement* $(i_1, i_2, ..., i_n)$ *.* Then $e_{i_m} = e_m$ for all $m = 1, 2, ..., n$ if and only the arrangement $(i_1, i_2, ..., i_n)$ maximizes $\sum_{m=1}^{n} I(x_m; e_{i_m})$ *under the constraints* $I(x_m : e_{i_m}) \neq 0$, *i.e.*

$$
(j_1, j_2, ..., j_n) = \underset{(i_1, i_2, ..., i_n)}{\arg \max} \sum_{m=1}^n I(x_m; e_{i_m})
$$
\n(4)

with
$$
I(x_m; e_{i_m}) \neq 0, \quad m = 1, 2, ..., n
$$
 (5)

where $j_i = i$.

Proof The detailed proof can be found in Appendix A

Theorem [15](#page-12-0) presents a method for matching, it turns the matching problem as an optimization problem. Although for a single pair x_i and e_i , $I(x_i; e_i) > I(x_j; e_i)$, $i \neq j$ may not achieve in complex situations the sum of the mutual information can reach the maximization under the right complex situations, the sum of the mutual information can reach the maximization under the right permutation of e. Combing Theorem [15](#page-12-0) and the generating process, we propose the generating and matching algorithm in Algorithm 3.

In Algorithm 3, the data set X is still the instances set of endogenous vector x . We only consider discrete and continuous data set. We use FastICA on X to obtain the instances of exogenous variables E in line 1. The E computed by FastICA is continuous. To compute the mutual information for endogenous and exogenous variables, we need to discretize E for the condition that X is discrete. In line 2 to line 6, we use sigmoid function on every element of E, and change the value of elements to 0 or 1 depends on the threshold 0.5. Then we have e' as binary variables. So far, we complete the connecting process generating process.

In line 13, Modified Jonker-Volgenant [\(Crouse](#page-38-11) [\(2016\)](#page-38-11)) aims to find the solution for minimizing the assignment cost:

$$
\min \sum_{i=1}^n \sum_{j=1}^n C_{ij} M_{ij},
$$

where C is the cost matrix, C_{ij} represents the cost if we assign *j* to *i*, and $M_{ij} = 1$ if we assign *j* to *i* otherwise $M_{ij} = 0$. Modified Jonker-Volgenant algorithm find the M to minimize the cost, and outputs the indices $(j_1, j_2, ..., j_n)$ which $M_{i,j_i} = 1$. In matching process, we set the element in cost matrix C_{ij} as the minus mutual information of x_i and e_j , and we set C_{ij} as infinite if mutual information is zero. Then minimizing the assignment cost is equivalent to maximize the equation

 \blacksquare

Algorithm 3 Generating and Matching

```
Input: data set X, number of nodes n
 1: Apply ICA method on X to obtain E;
 2: if X is discrete then
 3: for every element E_{ij} in E do
 4: E_{ij} = 1 if sigmoid(E_{ij}) > 0.5, otherwise E_{ij} = 0;<br>5: end for
      5: end for
 6: end if
 7: Initialize n \times n matrix C as zero matrix;
 8: for i from 1 to n do
 9: for j from 1 to n do
10: C_{ij} = -I(x_i; e'_j)j
);
11: if I(x_i; e'_i)'_{j}) = 0 then
12: C_{ij} = +\infty;13: end if
14: end for
15: end for
16: Use modified Jonker-Volgenant algorithm on C to obtain a permutation (j_1, j_2, ..., j_n);
17: Rearrange columns of E according to (j_1, j_2, ..., j_n);
Output: E
```
[\(4\)](#page-12-1) under constraints [\(5\)](#page-12-2). After rearranging columns of \mathbf{E}, e'_i i is the exogenous variable correspond to x_i for $i = 1, 2, ..., n$.

Although we use FastICA, which use linear function to separate observed messages, to generate exogenous variables, we do not have to assume the mixed function to be linear function. Then we have

$$
e' = PW^\top x = PW^\top g(e),
$$

where W is the output of FastICA in Algorithm [3](#page-13-0), line 1, and P is the permutation matrix which is constructed according to the permutation in line 13. Thus e' can be determined by e which illustrates that the exogenous vector we generated in **Algorithm 3** only contains part of the information of true exogenous vector. Apparently, the exogenous vector e' we generate is equal to true exogenous vector e' if and only if $g(e)$ is a linear functions. In other cases, e and e' are very different. However, we only prove Theorem [15](#page-12-0) on e and we apply Theorem 15 on e'. Therefore, we still need to fill this gap.

Theorem 16 *Let* e *be the true exogenous vector of CPDAG* G*, and* e ′ *be an another exogenous vector that can be determined by* e*. i.e. e*′ *i is the exogenous variable of xⁱ and there is a* h *such that*

$$
e'=h(e).
$$

Then for element of **h** h_i , there is a function \tilde{h}_i such that $e'_i = h_i(\mathbf{e}) = \tilde{h}_i(e_i)$. Moreover, if **h** in *equation* [\(3\)](#page-11-0) *is invertible, then* $I(x_i; e'_i)$ I'_i) = *I*(*x_i* ; *e_i*) *and I*(*x_j* ; *e_i*) = *I*(*x_j* ; *e_i*) i_i) *achieve for any* $j \neq i$.

Proof The detailed proof can be found in **Appendix A**.

The dimension of **e** and **x** are the same according to the assumption we made at the beginning, therefore invertibility of g is easy to achieve. If e' is generated from **Algorithm [3](#page-13-0)**, the assumption of **Theorem [16](#page-13-1)** achieves. Then $I(x_j; e_i) = I(x_j; e'_i)$ i' for any *i*, *j*. Therefore the $(1, 2, ..., n)$ is also the permutation that can maximize

$$
\sum_{i=1}^n I(x_i \; ; e_{i_m}')
$$

under the same constraints in **Theorem [15](#page-12-0). Theorem [16](#page-13-1)** guarantees the effectiveness of **Algorithm** [3](#page-13-0). Although we can not generate the true exogenous vector, depending on the similarity between e' and e, we can still learn the true graph structure without knowing the true exogenous vector in next subsection.

4.2 Markov Blankets Intersection

Figure 4: (a) is CPDAG G with exogenous variables. (b) and (c) are augmented graphs G_1^a and G_2^a . Although G_1 and G_2 are I-equivalent, their augmented graphs G_1^a , G_2^a are no longer I-equivalent. Since they have different conditional independencies between endogenous and exogenous variables, and only one of them is correct.

First of all, we give the definition of endogenous Markov blanket and exogenous Markov blanket.

Definition 17 *Let* X *be the set of endogenous variables and* Y *be the set of exogenous variables. Let xⁱ* ∈ X, *^eⁱ* ∈ Y*. We define the endogenous Markov blanket of xⁱ as the Markov blanket in* ^X*, and the exogenous Markov blanket of eⁱ as the Markov blanket in* X*. We denote the exogenous Markov blanket of* e_i *as* MB_i^e *.*

The endogenous Markov blankets are the normal Markov blankets in Section 2.1. The exogenous Markov blankets are the Markov blanket of exogenous variables. They are both a subset of X , since we only care about the structure of endogenous variables.

Although we know the true exogenous variables are the parents of endogenous variables, there are still some differences between e' and e as we analyze in the last subsection. To find the exogenous Markov blankets, we need to make sure that the exogenous variables we generate also satisfy this relation.

Theorem 18 Let $e' = (e'_1$ $\frac{1}{1}, e_2'$ $\mathbf{z}'_2, ..., \mathbf{e}'_n$ ^T is the exogenous vector we generate in **Algorithm 3***. If* \mathbf{z}'_1 with each other than \mathbf{z}'_1 is a parent of x, and \mathbf{z}'_1 has no parent. (*e* ′ $'_{1}, e'_{2}$ $(e_1, \ldots, e_n')^{\top}$ are independent with each other, then e'_i is a parent of x_i and e'_i has no parent.

Figure 5: An example of Markov blankets intersection on a augmented graph. The intersection of Markov blanket of x_1 and e_1 is the parents of x_1 .

Proof The detailed proof can be found in Appendix A.

It seems to be contradictory to the analyses in the last subsection that e'_{i} *i* can be determined only by e_i and $e'_i \leftarrow e_i \rightarrow x_i$ forms a fork structure. Actually, e_i , as a hidden variable, is a variable we may never know. Without giving e_i , this trail $e'_i \leftarrow e_i \rightarrow x_i$ is always active. If we omit the e_i the edge between *e* ′ α_i' and x_i can be any direction. But **Theorem [18](#page-14-0)** states that only $e'_i \rightarrow x_i$ achieves.

Theorem [18](#page-14-0) indicates that *e* ′ \mathbf{F}_i and \mathbf{e}_i have the same exogenous Markov blanket MB_i^e . We need to combine exogenous variables and endogenous variables into one graph according to Theorem [18](#page-14-0).

Definition 19 *Let* $G = (X, \mathcal{E})$ *be a DAG, we define the augmented graph* $G^a = (X \cup \mathcal{Y}, \mathcal{E} \cup \mathcal{E}')$
where $M = \{g_1, g_2, \ldots, g_n\}$ is the set of exagenous variables and $\mathcal{E}' = \cup \{g_1 \rightarrow x\}$ *where* $\mathcal{Y} = \{e_1, e_2, ..., e_n\}$ *is the set of exogenous variables and* $\mathcal{E}' = \bigcup \{e_i \to x_i\}$ *.*

After the generating and matching process, we add the exogenous variables and obtain the augmented graph \mathcal{G}^a of DAG \mathcal{G} . Different from SCM, augmented graphs do not define the functional relationship or prior distributions, and keep the set of edges \mathcal{E}' , since we only care about the structure of the graph.

After knowing the relation between endogenous variables and exogenous variables, we can study the exogenous Markov blankets on the augmented graph. Since e'_{i} α ^{*i*} is only connected with x_i , the relation between e'_{i} α_i' and x_j depends on the relation between x_i and x_j .

The child of x_i is not in MB_i^e since $e_i \rightarrow x_i \rightarrow x_j$ forms a chain structure. If x_j is a parent of $x_i, e'_i \rightarrow x_i \leftarrow x_j$ forms a V-structure, then $x_j \in MB_i^e$. However, there are some undirected edges in CPDAG. As we discussed in Section 2.1, if CPDAG G contains the undirected edges $x_i - x_j$, then there must be two I-equivalents DAG $G_1 = (X_1, E_1)$ and $G_2 = (X_2, E_2)$, such that $x_i \to x_j \in E_1$ and $x_i \leftarrow x_j \in \mathcal{E}_2$. But after adding the exogenous variables, \mathcal{G}_1^a , \mathcal{G}_2^a may have different V-structures. It seems to be contradictory to the I-equivalence since the augmented graph is only a definition, it can not change the conditional independencies in the graph. G_1 and G_2 are equivalent under the property of conditional independence, but they are not equivalent in augment graphs.

For example, let e_1, e_2 be two exogenous variables that follow the standard Gaussian distributions, $x_1 = 2e_1$ and $x_2 = x_1 + e_2^2$ (Figure [4\)](#page-14-1). Using the definition of I-equivalence, x_1, x_2 has no
conditional independency therefore $x_1 \to x_2$ and $x_2 \gets x_1$ are I equivalent. If given $x_1 = c_1$ as a conditional independency, therefore $x_1 \rightarrow x_2$ and $x_1 \leftarrow x_2$ are I-equivalent. If given $x_1 = c$ as a constant, $x_2 = e_2^2 + c$ is independent with e_1 . If given an empty set, $x_2 = x_1 + e_2^2 = 2e_1 + e_2^2$ is not independent with e_1 . Therefore we have the facts that $x_2 \perp x_1 \mid x_1$ and $x_2 \not\perp x_1 \mid \emptyset$. For e_2 , we can also infer $x_1 \perp \!\!\!\perp e_2 \mid \emptyset$ and $x_1 \not\!\!\!\perp e_2 \mid x_2$ in a similar way. Thus $e_1 \rightarrow x_1 \rightarrow x_2$ forms a chain and

 $x_1 \rightarrow x_2 \leftarrow e_2$ form a V-structure which is exactly the G_1^a (Figure [4](#page-14-1) (b)), and G_1^a is not I-equivalent with \mathcal{G}_2^a .

The reason for this paradox is that under the SCM, only $x_1 \rightarrow x_2$ is correct, and $x_1 \leftarrow x_2$ can not be achieved under **Definition [10](#page-6-0)** since x_1 is not determined by x_2 . Using the conclusion of **Theorem [18](#page-14-0)**, we may add the x_2 into the exogenous Markov blanket of e_1 because x_2 is spouse node of e_1 in other I-equivalence DAG, but $x_2 \notin MB_1^e$ since it does not satisfy **Theorem [11](#page-9-0)**, i.e. $x_2 \perp z_1 \perp x_1$. Thus we have the following theorem:

Theorem 20 *Let eⁱ be the exogenous variables with respect to the endogenous variables xⁱ . Then* $x_j \in MB_i^e$ if and only if x_j is a parent of x_i *under Definition [10](#page-6-0).*

Proof The detailed proof can be found in Appendix A.

 \blacksquare

Combing Theorem [18](#page-14-0), we can conclude that the theorem above also achieves for e' .

These analyses also indicate that we can not find the undirected edges of CPDAG by finding the exogenous Markov blankets, but we can learn a DAG by intersecting endogenous Markov blankets and exogenous Markov blankets (Figure [5\)](#page-15-0). We give the intersection algorithm in Algorithm 4.

Algorithm 4 Intersection Algorithm

```
Input: \mathcal{MB} = \{MB_1, ..., MB_n\}, X, E, n, \beta1: for i from 1 to n do
  2: Initialize MB_i^e = \emptyset;
  3: S = MB_i;4: while MB_i^e is changed do
  5: Find the node x_j \in S that maximizes I(e_i; x_j | MB_i^e);
  6: if I(e_i; x_j | MB_i^e) > \beta then<br>
\alpha, \beta dd r, in MR^e.
  7: Add x_j in MB_i^e;
 8: Remove x_j from S;
 9: end if
10: end while
11: for node x_k in MB_i^e do
12: if x_k \neq x_i and I(e_i; x_k | MB_i^e \setminus \{x_k\}) < \beta then<br>
13: Remove x from MB<sup>e</sup>
13: Remove x_k from MB_i^e;
14: end if
15: end for
16: for node x_l, l \neq i, in MB_i^e do
17: Add the edge x_l \rightarrow x_i in G;
18: end for
19: end for
Output: DAG G.
```
The Intersection algorithm starts at an augmented graph constructed by the Markov blankets. We assume that we already know the Markov blankets of all nodes $M\mathcal{B}$, and use $M\mathcal{B}$ as one of the inputs. X , and E are the instances of endogenous variables and exogenous variables, they have the same dimension *n* and the same number of instances. β is a threshold similar to α in **Algorithm [2](#page-8-0).**

Line 1 to line 15 is the modification of the forward phase and backward phase in improved IAMB. By **Theorem [20](#page-16-0)**, we have $MB_i^e \subset MB_i$, therefore we can totally shrink the searching area

Figure 6: (a) is original DAG. EEMBI and EEMBI-PC aim to find the CPDAG of (a). $(a) \rightarrow (b) \rightarrow (c) \rightarrow (d) \rightarrow (e)$ is the process of EEMBI and $(a) \rightarrow (b) \rightarrow (c) \rightarrow (f) \rightarrow (g) \rightarrow (h)$ is the process of EEMBI-PC. After learning the Markov blankets, we can connect the node to all the nodes in its Markov blanket to obtain (b). Then generating and matching algorithm assigns the exogenous variable for every x_i to obtain the augmented graph (c). After finding the exogenous Markov blankets for e_i , we can exclude the edges between nodes and their spouses $x_1 - x_2$, $x_3 - x_4$, and return the DAG (d). Finally, we turn the DAG into the CPDAG (e). EEMBI-PC turns the DAG into a skeleton (f) and uses the PC algorithm to find all the V-structures $x_3 \rightarrow x_6 \leftarrow x_4, x_1 \rightarrow x_4 \leftarrow x_2$ in (g). Applying Meek's rules, we have the CPDAG of (h).

from all the nodes $S = \{1, 2, ..., n\}$ to the endogenous Markov blanket MB_i . In the forward and hackward phase we also use kNN CMI to estimate the CMI. We can find the parents of x efficiently backward phase, we also use kNN-CMI to estimate the CMI. We can find the parents of x_i efficiently by assessing every conditional independency of e_i and x_j given MB_i^e in the forward phase. Although some children or spouses of x_i may be added in MB_i^e accidentally, they can be removed in the backward phase according to **Theorem [12](#page-9-1)**. After the forward and backward phases, we connect the nodes in MB_i^e with x_i in line 17. For node x_i , we only connect x_i with its parents and leave its children behind. However, when we consider $x_j \in Ch_i$, x_i , as a parent of x_j , can be connected under the same process. In this way, the connection of the x_i with its spouses is excluded from the Markov blanket. Therefore, according to Theorem [13](#page-10-0) and Theorem [18](#page-14-0), Algorithm [4](#page-16-1) returns the DAG whose connections follow Definition [10](#page-6-0).

Combing all the algorithms above, we can give the main algorithms in this paper in Algorithm [5](#page-18-0) and Algorithm [6](#page-18-1).

Algorithm 5 EEMBI

Input: X, α, β

- 1: Use **improved IAMB** on **X** based on the threshold α to obtain Markov blankets set MB;
- 2: Compute the instances of exogenous variables E by using Generating and Matching Algorithm and construct the augmented graph;
- 3: Build the DAG G using Intersection Algorithm;
- 4: Turn the DAG into the CPDAG by Meek's rules;

Output: CPDAG G .

Algorithm 6 EEMBI-PC

Input: X, α, β

- 1: Use **improved IAMB** on **X** based on the threshold α to obtain Markov blankets set \mathcal{MB} ;
- 2: Compute the instances of exogenous variables E by using Generating and Matching Algorithm and construct the augmented graph;
- 3: Learn the DAG from Intersection Algorithm and turn all the directed edges into undirected edges to obtain the skeleton of graph;
- 4: Find all the V-structure by PC algorithm based on the skeleton of graph;
- 5: Orient the rest of the edges using Meek's rules;

Output: CPDAG G .

In the last step of the EEMBI, we keep the skeleton and V-structure of the DAG and turn other edges into undirected edges. Then we apply Meek's rules to it. In this way, we successively turn a DAG into a CPDAG.

EEMBI-PC follows the standard steps of constraint-based methods: Learn the skeleton; Find the V-structures; Orient the rest of the edges. The difference of EEMBI-PC starts at line 3. EEMBI-PC uses Algorithm [4](#page-16-1) to learn the skeleton and uses the PC algorithm to learn V-structures. Having the skeleton of the graph as prior knowledge, the PC algorithm does not need to traverse all the subsets of X to find V-structure. For any possible V-structure $x_i - x_j - x_k$, PC algorithm only traverses all the subsets of $Pa_i \cup Ch_i \cup Pa_k \cup Ch_k$, which is more efficient than original PC algorithm. The visualization of the EEMBI and EEMBI-PC is shown in Figure [6.](#page-17-0) It is easy to conclude that

Corollary 21 *EEMBI and EEMBI-PC return the CPDAG of the data set* X*.*

Finally, we discuss the complexity of EEMBI and EEMBI-PC.

In the forward and backward phases of improved IAMB, we need to compute the CMI for n^2 times for one node x_i in the worst case. Thus finishing the first two phases for all nodes needs $O(n^3)$ operations. And the checking phase only needs $O(n^2)$ operations, and the computational complexity of improved IAMB is $O(n^3)$. In Algorithm [3](#page-13-0), it needs $O(n^2)$ time to compute the cost matrix C and $O(n^3)$ to apply the Jonker-Volgenant algorithm to solve equation [\(4\)](#page-12-1). Thus Algorithm [3](#page-13-0) costs $O(n^3)$ operations. In the intersection algorithm, since we shrink the area to Markov blanket, finding the parents and children for x_i only needs $O(|MB|^2)$ operations where $|MB| = max_i(|MB_i|)$, and complexity of the **Algorithm [4](#page-16-1)** is $O(n \times |MB|^2)$. Therefore the computational complexity of EEMBI is $O(n^3) + O(n^3) + O(n \times |MB|^2) = O(n^3)$.

For EEMBI-PC, it has the same complexity as EEMBI in the first three steps. The PC algorithm needs to test every subset of $Pa_i \cup Ch_i \cup Pa_k \cup Ch_k$ for every possible V-structure $x_i - x_j - x_k$, finding V-structure process needs $O(c \times 2^{2|Pa \cup Ch|})$ time where *c* is the number of $x_i - x_j - x_k$ in skeleton, and $|Pa \cup Ch| = max_i(|Pa_i \cup Ch_i|)$. In conclusion, the computation complexity of the whole EEMBI-PC algorithm is $O(n^3 + c \times 2^{2|Pa \cup Ch|}).$

5 Experiment

In this section, we provide several experiments to state the effectiveness of our proposed algorithms. Firstly, we introduce the setup of experiments. Then we evaluate the EEMBI and EEMBI-PC on discrete and continuous datasets. Finally, we study the influence of hyperparameters and give the results of ablation studies. We do all the experiments on CPU i7-12700H with 24G RAM. The code of the proposed algorithms can be found in https://[github.com](https://github.com/ronedong/EEMBI)/ronedong/EEMBI

Data set	Sample	Number of		Data set	Sample	Number of	
	Size	Nodes			Size	Nodes	β
ALARM	3000	37	0.01	BARLEY	3000	48	0.01
CHILD	3000	20	0.01	INSURANCE	3000	27	0.01
MILDEW	3000	35	0.01	HailFinder	3000	56	0.01
SACHS	7466	11	0.05	DREAM3-Ecoli 1.2	483	50	0.05
DREAM3-Yeast 1.2.3	483	50	0.05	Education $1,2,3,4,5$	1000	50	0.05

Table 1: Basic information about datasets

5.1 Experimental Setup

We evaluate the performance of EEMBI and EEMBI-PC on six discrete datasets: ALARM, BAR-LEY, CHILD, INSURANCE, MILDEW, and HailFinder [\(Scutari](#page-40-9) [\(2023\)](#page-40-9)); Additionally, we conduct experiments on eleven continuous datasets: SACHS [\(Sachs et al.](#page-39-11) [\(2005\)](#page-39-11)), five dream3 datasets (Dream3-Ecoli 1, Dream3-Ecoli2, Dream3-Yeats 1, Dream3-Yeast 2, Dream3-Yeast 3) [\(Marbach](#page-39-12) [\(2008\)](#page-39-12)), as well as five education datasets (Education Net 1,2,3,4,5). An overview of the basic information for these seventeen datasets is provided in Table [1.](#page-19-0) We compare EEMBI and EEMBI-PC against seven baselines on the discrete datasets:

• PC, Fast Causal Inference (FCI) [\(Spirtes et al.](#page-40-10) [\(1995\)](#page-40-10)), Grow-Shrink (GS) [\(Margaritis](#page-39-13) [\(2003\)](#page-39-13)), and Constraint-based causal Discovery from NOnstationary Data (CDNOD) [\(Huang et al.](#page-38-12)

[\(2020\)](#page-38-12)): they are all constraint-based models. PC algorithm uses G-test as the conditional independent test score;

- Greedy Interventional Equivalence Search (GIES) (Hauser and Bühlmann [\(2012\)](#page-38-13)): it is a score-based methods, and is the modification of GES;
- MMHC [\(Tsamardinos et al.](#page-40-6) [\(2006\)](#page-40-6)): mixture methods mentioned in Section 1;
- Greedy Relaxation of the Sparsest Permutation (GRaSP) [\(Lam et al.](#page-39-14) [\(2022\)](#page-39-14)): a permutationbased method.

In addition to the seven baseline methods used on discrete datasets, we include three additional algorithms that are specifically designed for continuous data as baselines for the proposed methods:

- Direct Linear Non-Gaussian Acyclic Model (DirectLiNGAM) [\(Shimizu et al.](#page-40-11) [\(2011\)](#page-40-11)) and Causal Additive models (CAM) (Bühlmann et al. (2014)): they are constraint functional causal models, and DirectLiNGAM is the improvement of LiNGAM;
- Non-combinatorial Optimization via Trace Exponential and Augmented lagRangian for Structure learning (NOTEARS) [\(Zheng et al.](#page-40-12) [\(2018\)](#page-40-12)): NOTEARS is a score-based method, and it is also one of the state-of-the-art causal structure learning algorithms.

PC, GIES, and GS are achieved by the Python package causal discovery box [\(Kalainathan](#page-38-15) [\(2018\)](#page-38-15)). FCI, GRaSP, and CDNOD are achieved by the package causal-learn [\(Zheng](#page-40-13) [\(2021\)](#page-40-13)). DirectLiNGAM is achieved with the package LiNGAM [\(T.Ikeuchi](#page-40-14) [\(2023\)](#page-40-14)). We implement MMHC and NOTEARS by using the code provided in their original papers.

We use the adjacency matrix \bf{A} to represent the CPDAG of dataset \bf{X} . The adjacency matrix is constructed as follows:

- If $x_i \rightarrow x_j \in \mathcal{E}$, then $A_{ij} = 1$ and $A_{ji} = 0$;
- If $x_i x_j \in \mathcal{E}$, then $A_{ij} = A_{ji} = 1$;
- If x_i and x_j are not connected, $A_{ij} = A_{ji} = 0$.

All these causal structure learning algorithms return the adjacency matrices of the dataset. We use Structural Hamming Distance (SHD) and Area Under the Precision Recall curve (AUPR) to measure the difference between predicted and true adjacency matrices. They are widely used metrics in causal structure learning. SHD counts the number of different edges between predicted and true adjacency matrices,

$$
SHD(\mathbf{A}, \mathbf{B}) = \sum_{i} \sum_{j} |A_{ij} - B_{ij}|,
$$

where A and B are two adjacency matrices. AUPR computes the area under the curve which is constructed by precision: $\frac{TP}{TP+FP}$ and recall: $\frac{TP}{TP+FN}$ with different causation thresholds where *T P*, *FP*, *FN* are short for True Positive, False Positive, and False Negative. All the causal structure learning algorithms aim to learn adjacency matrices that have lower SHDs and higher AUPRs with true adjacency matrix.

Data processing: For discrete datasets, we encode the categorical values to integer values based on their orders. For continuous datasets, we apply min-max normalization and turn all the values of features in [0,1]. Since we only compare CPDAG in all experiments, we turn the true adjacency matrices of DAG into CPDAG using the function dag2cpdag in pcalg package.

Hyperparameters: EEMBI and EEMBI-PC have only two hyperparameters: α in Algorithm [2](#page-8-0) and β in Algorithm [4](#page-16-1). We fix the $\alpha = 0.01$, and we set $\beta = 0.01$ on discrete datasets and $\beta = 0.05$ on continuous datasets. We use all the instances of SACHS and dream3 datasets. However, restricted by the computational complexity and memory of CPU, we only sample part of instances to do the causal structure learning in all discrete datasets and Education datasets. The numbers of instances we sample are shown in Sample Size of Table [1.](#page-19-0)

For every structure learning algorithm, we sample from each dataset three times and feed the instances to algorithms to obtain an adjacency matrix for every sampling. After computing the SHD and AUPR metrics for every sampling, we combine all the results and compute the mean and standard deviation for every algorithm on every dataset. We show the SHD results in Table [2,](#page-21-0) Table [3](#page-24-0) and Table [4](#page-26-0) in the form of *mean* (*standard deviation*). However, we use all the instances in SAHCS and Dream3 datasets, there is no randomicity in these experiments. Therefore, we only run methods once on SACHS and Dream3 and show the results without standard deviations. We highlight the lowest SHD result in each dataset for emphasis. The AUPR results are shown in bar graphs in Figure [6,](#page-36-0) Figure [7,](#page-36-1) and Figure [8.](#page-37-0) The detailed mean and standard deviation values of AUPR can be found in Appendix B.

5.2 Discrete datasets

Table 2: SHD on discrete datasets

Figure 7: AUPR results of causal structure learning methods on discrete datasets

On outcomes of discrete datasets in Table [2](#page-21-0) and Figure [6,](#page-36-0) except for the MILDEW and Hail-Finder datasets, EEMBI-PC has the best performance on the other four datasets, i.e. it has the lowest SHD and highest AUPR. Although EEMBI has the lowest SHD on HailFinder and GS has the highest AUPR on MILDEW, EEMBI-PC shows very close outcomes to them and has the lowest SHD on MILDEW and highest AUPR on HailFinder. Therefore, EEMBI-PC has the best performance of all causal structure learning algorithms on discrete datasets. EEMBI also has SHDs which are close to EEMBI-PC on ALARM, CHILD, MILDEW, and HailFinder datasets. For instance, the SHD of EEMBI (29.3) is only 0.3 higher than the SHD of EEMBI-PC (29.0). But EEMBI has ordinary results on AUPR, it exceeds the baseline algorithms only on CHILD and INSURANCE datasets, and has much lower AUPRs than most of the baselines on BARLEY and MILDEW. Furthermore, the proposed methods outperform the baselines dramatically on some datasets. For example, on HailFinder EEMBI and EEMBI-PC are the only two algorithms that have SHDs lower than 100, 92.3 and 93.0. The best baseline, MMHC, only has 115.3 SHD, and the worst baseline, FCI, has 205.3 SHD which is more than twice of SHD of EEMBI and EEMBI-PC.

In addition to these numerical results, we also present selected parts of the CPDAG structure learned from different methods in Figure [8](#page-23-0) and Figure [9.](#page-23-1) We pick eight features from the nodes and include all the edges connecting these eight nodes from the original CPDAG. The direction of the edges remains unchanged. Then these eight nodes and edges form a subgraph. We label the name of the features on the nodes.

In Figure [8,](#page-23-0) CPDAGs (b) (c) learned from PC and CDNOD both fail to capture the connection between *HypoxianlnO*2 and *LungParench*, as well as the connection between *Disease* and *LungParench*. (b) incorrectly connects *Disease* and *HypoxianlnO*2. (c) mistakenly adds 3 edges: *Disease* → *HypoxianlnO*2, *RUQO*2 → *LowerBodyO*2 and *CO*2*Report* → *LungParench*. Furthermore, (c) incorrectly determines the directions of 4 edges among these right connections like $RUQO2 \rightarrow HypoxianlnO2$ and $CO2 \rightarrow LungParent$. (d) learned from EEMBI-PC only misses

Figure 8: Parts of the CPDAG structure of CHILD dataset. (a) is the true CPDAG of CHILD dataset. (b) (c) (d) are the CPDAGs learned from PC, CDNOD, and EEMBI-PC algorithms.

one connection between *HypoxianlnO*2 and *LungParench*, and it only has two connections with wrong directions.

Figure 9: Parts of the CPDAG structure of INSURANCE dataset. (a) is the true CPDAG of CHILD dataset. (b) (c) (d) are the CPDAGs learned from PC, CDNOD, and EEMBI-PC algorithms

In Figure [9,](#page-23-1) (b) additionally connects 5 edges, like *S eniorTrain* → *GoodS tudent*, misses 6 edges, such as *GoodS tudent* − *S ocioEcon*, and have the wrong directions on all the edges. (c) connects 6 edges and omits 4 edges mistakenly. And it only has the right direction on *RiskAversion*− *AntiThe ft.* (d) does not have any additional edge and only miss two edges *Age* − *S ocioEcon* and *GoodS tudent*−*S ocioEcon*. More surprisingly, (d) learn the right direction of all connections except for *Age* → *RsikAversion*.

5.3 Continuous datasets

Table [3,](#page-24-0) [4,](#page-26-0) and Figure [7,](#page-36-1) [8](#page-37-0) shows the comparison results on continuous datasets. On SACHS, EEMBI-PC has the lowest SHD and reaches the top on AUPR. Although EEMBI and NOTEARS are close to EEMBI-PC on SHD, they are exceeded by many baselines like PC, FCI, and GIES on AUPR.

Algorithms	SACHS	Education 1	Education 2	Education 3	Education 4	Education 5
PC	32.0	636.0(5.72)	660.0(11.58)	628.3(14.06)	621.0(2.83)	633.0(9.42)
FCI	43.0	650.3(7.13)	671.3(10.40)	632.0(3.74)	641.3(3.68)	669.7(3.68)
GIES	38.0	692.3(31.86)	700.7(35.37)	665.3(23.16)	677.7(9.29)	685.7(32.74)
MMHC	37.0	662.3(7.72)	689.7(5.56)	639.7(4.19)	650.0(2.94)	671.7(7.41)
GS	35.0	649.3(9.39)	667.3(3.40)	608.7(4.78)	636.7(15.43)	646.3(9.46)
GRaSP	36.0	686.3(3.09)	677.3(9.46)	646.7(13.60)	646.3(8.34)	672.0(18.06)
CDNOD	37.0	650.7(8.34)	664.7(4.03)	617.0(2.94)	619.0(5.89)	649.3(6.02)
DirectLiNGAM	51.0	658.7(7.54)	629.7(11.73)	742.7(91.00)	781.7(114.44)	757.3(93.83)
CAM	37.0	659.3(6.55)	679.0(10.42)	643.3(9.74)	671.0(15.77)	672.7(33.32)
NOTEARS	28.0	628.0(4.08)	644.7(5.44)	593.3(5.31)	612.3(2.49)	630.3(3.30)
EEMBI	30.0	618.0(5.10)	627.0(2.16)	582.3(6.13)	580.3(2.49)	610.0(5.10)
EEMBI-PC	27.0	644.7(6.94)	654.0(4.32)	608.0(1.41)	619.0(5.72)	634.7(6.65)

Table 3: SHD on SAHCS and Education datasets

On Education datasets, EEMBI shows its dominance. It reaches the lowest SHDs and the highest AUPRs of these five datasets. EEMBI is the only method whose SHD is lower than 600 on Edu-Net 4, and it is one of the two methods whose SHD is lower than 600 on Edu-Net 3, together with NOTEARS. Moreover, EEMBI has very small standard deviations. It has the smallest deviations on Edu-Net 2 (2.16) and Education 4 (2.39) and has the third smallest deviations on Edu-Net 1 (5.10) and Education 5 (5.10). Small standard deviations indicate that EEMBI is much more robust to

Figure 10: AUPR on SACHS and Education datasets

Figure 11: AUPR on Dream3 datasets

noisy and randomicity of data. EEMBI-PC has poor performance on these five datasets. Although EEMBI-PC outperforms baselines except for the PC algorithm and NOTEARS on SHD, it still has big gaps with EEMBI. For AUPR, EEMBI-PC is exceeded by CDNOD and NOTEARS on Edu-Net 1, 2, 3 and basically reaches the bottom on Edu-Net 1. NOTEATRS has better performance than other baseline algorithms and EEMBI-PC on SHD, but is still beaten by EEMBI on every Education dataset.

Algorithms	Ecoli 1	Ecoli 2	Yeast 1	Yeast 2	Yeast 3
PC.	212.0	216.0	216.0	257.0	293.0
FCI	289.0	290.0	286.0	350.0	361.0
GIES	262.0	280.0	261.0	296.0	298.0
MMHC	205.0	227.0	281.0	281.0	301.0
GS	164.0	192.0	192.0	213.0	233.0
GRaSP	204.0	426.0	200.0	298.0	234.0
CDNOD	230.0	249.0	236.0	315.0	313.0
DirectLiNGAM	219.0	247.0	219.0	289.0	289.0
CAM	360.0	346.0	354.0	390.0	392.0
NOTEARS	157.0	181.0	195.0	230.0	253.0
EEMBI	124.0	164.0	143.0	215.0	226.0
EEMBI-PC	144.0	158.0	158.0	220.0	236.0

Table 4: SHD on Dream3 datasets

For Dream3 datasets, EEMBI achieves the lowest SHD among all methods, except for the Ecoli 2 dataset where it is close to the best-performing method, EEMBI-PC. but it only has the highest AUPR on Yeast 1. On the other hand, EEMBI-PC performs exceptionally well on the Ecoli 1 and Ecoli 2 datasets, achieving the highest AUPR. Similar to discrete datasets, EEMBI and EEMBI-PC have the lowest two SHDs on every dream dataset. However, they both show poorer performance in terms of AUPR on Yeast 2, 3. In contrast, NOTEARS and CAM achieve the tops on them, and NOTEARS has the closest SHD to proposed methods among the baseline algorithms.

EEMBI outperforms baselines and EEMBI-PC on continuous datasets overall.

5.4 Sensitiveness and Ablation Study

In Figure [12,](#page-27-0) we show the performance of baselines and proposed methods with respect to the sample size on Edu-Net 3, 4 datasets. We consider the performance of causal learning algorithms on 400, 600, 800, 1000, 1200, 1400, and 1600 sample sizes. Similarly, we apply every algorithm three times with different instances on every sample size and show the mean values on graphs. We remove the DirectLiNGAM since its poor results affect the presentation of other algorithms. In (a) (b), The SHDs have decreasing tendency with the increase of sample size. EEMBI has the smallest SHD on any sample size, it only decreases at the beginning in (a) and is stable after 600 sample size. In (b), EEMBI begins to decrease at the 600 sample size and gradually becomes steady. EEMBI-PC fluctuates intensely in (a) (b). And NOTEARS has the second lowest SHDs except on small sample sizes. Most of the methods, including EEMBI and NOTEARS, decrease slightly with respect to sample size. However, GIES in (a) and CAM in (b) decrease dramatically, which indicates that GIES and CAM are sensitive to sample size. For (c) (d), all methods have increasing tendencies.

Figure 12: The change of SHD and AUPR of causal structure learning algorithms with respect to sample size on Education 3, 4. (a) (b) show the SHD with respect to sample size and (c) (d) show the AUPR with respect to sample size.

EEMBI reaches the top of the graph all the time, and it has a completely opposite behavior compared to its performance in (a) (b). EEMBI-PC still has fluctuation corresponding to EEMBI-PC in (a) (b). Surprisingly, MMHC has the lowest AUPR on most of the sample sizes and has big gaps to other baselines.

Figure 13: The SHD and AUPR of EEMBI and EEMBI-PC with respect to β on ALARM ((a),(e)), BARLEY $((b), (f))$, CHILD $((c), (g))$, and INSURANCE $((d), (h))$

Since we fix the hyperparameter α and use different β on discrete and continuous datasets. We are only interested in the influence of β . We study the performances of proposed methods, EEMBI and EEMBI-PC, with respect to β on four discrete datasets in Figure [13.](#page-28-0) EEMBI-PC outperforms EEMBI on every dataset except for a few points. EEMBI-PC with $\beta = 0.01$ shows the lowest SHDs on CHILD and INSURANCE, and the highest AUPR on all four datasets. However, the regularity of EEMBI is much more complicated. EEMBI has its best performance under $\beta = 0.01$ on CHILD but with $\beta = 0.05$ on INSURANCE. Moreover, it reaches its minimum SHD under $\beta = 0.1$ but reaches its maximum AUPR under $\beta = 0.01$ on ALARM. In conclusion, EEMBI-PC with $\beta = 0.05$ is the best method for discrete datasets.

To prove every step in EEMBI and EEMBI-PC is useful, an ablation study is needed. After getting the Markov blankets from improved IAMB, we link every node with the nodes in its Markov blanket using undirected edges, and the undirected graph is represented by an adjacency matrix and is compared with the true CPDAG of datasets. Then we get the SHD and AUPR of improved IAMB on datasets. We also remove the matching phase in EEMBI and EEMBI-PC, i.e. delete the line 7 to line 14 in Algorithm [3](#page-13-0) and directly use the exogenous variables generated by FastICA as the input of Algorithm [4](#page-16-1). We denote the EEMBI and EEMBI-PC without matching phase as EEMBI (WM) and EEMBI-PC (WM) where WM is short for "Without Matching". We run improved IAMB, EEMBI (WM), and EEMBI-PC (WM) three times, and compare them with original EEMBI and EEMBI-PC in Table [5.](#page-29-0) The results of AUPR are shown in Appendix B. We may compare improved IAMB with EEMBI and EEBI-PC to demonstrate the effectiveness of the combination of Algorithm [3](#page-13-0) and Algorithm [4](#page-16-1). We also may compare EEMBI with EEMBI (WM), or compare EEMBI-PC with EEMBI-PC (WM) to state the effectiveness of Algorithm [3](#page-13-0) solo. We can find that EEMBI or EEMBI-PC has a much smaller SHD than EEMBI (WM) or EEMBI-PC (WM), and improved

IAMB. For example, on Edu-Net 1, the SHD of EEMBI (618.0) is smaller than the SHD of EEMBI (WM) (647.3) and the SHD of improved IAMB (676.0). Although EEMBI (WM) has lower SHD than EEMBI-PC on Edu-Net 3 and Edu-Net 4, this comparison is meaningless since they have different steps besides the matching phases.

Algorithms	Education 1	Education 2	Education 3	Education 4	Education 5
Improved IAMB	676.0(7.48)	682.7(6.18)	639.7(2.49)	651.7(4.99)	679.7(5.25)
EEMBI (WM)	647.3(3.68)	660.0(2.16)	603.7(3.40)	613.0(12.75)	641.3(6.94)
EEMBI-PC (WM)	665.3(12.26)	670.0(1.41)	630.0(0.82)	636.3(4.19)	657.0(6.38)
EEMBI	618.0(5.10)	627.0(2.16)	582.3(6.13)	580.3(2.49)	610.0(5.10)
EEMBI-PC	644.7(6.94)	654.0(4.32)	608.0(1.41)	619.0(5.72)	634.7(6.65)

Table 5: SHD on Dream3 datasets

6 Conclusion

This paper proposes a pair of new causal structure learning algorithms: EEMBI and EEMBI-PC. They use improved IAMB to learn the Markov blankets for all nodes. Different from original IAMB, improved IAMB has an extra phase to guarantee its accuracy, and it uses kNN-CMI as estimation of CMI so that it can have more accurate conditional independencies and can work on both discrete and continuous datasets directly. FastICA is implemented to generate exogenous variables. To match every exogenous variable with its endogenous variable, we turn the problem into an optimization problem in equation [\(4\)](#page-12-1) and propose generating and matching algorithm in Algorithm [3](#page-13-0). Using the properties of exogenous variables, we prove that the parents of endogenous variables belong to the Markov blankets of the corresponding exogenous variables. So we intersect endogenous Markov blankets and exogenous Markov blankets to find the parents of nodes in Algorithm [4](#page-16-1). We have different algorithms by using different strategies to orient the edges in the final phases. For EEMBI, we directly orient the edges from the parents node found in **Algorithm [4](#page-16-1)** to the target node and obtain a DAG. And we turn the DAG into CPDAG by using Meek's rules. For EEMBI-PC, we use undirected edges to link the parents with the target node to obtain the skeleton of the DAG. And we use the PC algorithm and Meek's rules to obtain the CPDAG. The experiments give empirical evidence that EEMBI-PC has the best performance on discrete datasets and EEMBI is the state-ofthe-art method on continuous datasets.

Although EEMBI only needs polynomial complexity $O(n^3)$, the proposed methods still require much more computational time compare to baseline algorithms in experiments, especially under large sample sizes. This is primarily due to the complex computation of kNN-CMI and improved IAMB costs most of the time. In our future studies, we aim to explore a more efficient estimation for CMI to enhance the efficiency of improved IAMB. Furthermore, we are interested in finding an ICA method that can accurately recover the exogenous variables from observed data so that EEMBI and EEMBI-PC can be much more accurate.

Acknowledgments and Disclosure of Funding

This work was funded by the National Nature Science Foundation of China under Grant 12071428 and 11671418, and Zhejiang Provincial Natural Science Foundation of China under Grant No. LZ20A010002.

Appendix A. Proof

We give proofs of theorems in this appendix.

Proof of Theorem [12](#page-9-1)

Let $x, y \in X$ be two endogenous variables, and x, y are connected by some trails. Since any trails that connect *x* and *y* must go through the Markov blanket of *x*, we have three conditions.

condition 1

If trail $x \rightleftharpoons x_1 \rightleftharpoons x_2... \rightleftharpoons y$ goes through one of the parents of *x*, i.e. $x \leftarrow x_1$. Since $x \leftarrow x_1 \rightleftharpoons x_1$ forms either a fork structure or a chain structure. Therefore given $x_1 \in MB_x$ can make this trail not active.

If trail $x \rightleftharpoons x_1 \rightleftharpoons x_2 \rightleftharpoons x_3... \rightleftharpoons y$ goes through one of the children of $x x_1$. Since $x_1 \in Ch_x$, we have $x \to x_1$. Then the other two conditions follow.

condition 2

If $x \to x_1 \to x_2$ forms a chain structure, then given $x_1 \in MB_x$ unactive this trail.

condition 3

If $x \to x_1 \leftarrow x_2$ forms a V-structure, so x_2 is one of the spouses of x. Then $x_1 \leftarrow x_2 \rightleftarrows x_3$ forms a fork structure or chain structure, and given $x_2 \in MB_x$ can make this trail not active.

Combing these three conditions, we know any trails between *x* and *y* are not active given MB_x , thus $x \perp y \mid MB_x$. The proof for $x \perp y \mid MB_y$ can be achieved in a similar way.

Let *Z* ⊂ *X*, *y* ∉ *Z* and *Z* ∩ *MB*_{*x*} = \emptyset .

$$
P(x \mid Z, MB_x) = \sum_{y} P(x \mid y, Z, MB_x) P(y \mid Z, MB_x)
$$

$$
= \sum_{y} P(x \mid MB_x) P(y \mid Z, MB_x)
$$

$$
= P(x \mid MB_x)
$$

Since $x \perp z$, $y \mid MB_x$, we have

$$
P(x | y, Z, MB_x) = P(x | MB_x) = P(x | Z, MB_x).
$$

 \mathcal{L}

Therefore $x \perp\!\!\!\perp y \mid Z \cup MB_x$,

Proof of Theorem [14](#page-11-1)

Consider a chain structure $x \to y \to z$. By the definition of mutual information $I(x; y) =$ $H(x) - H(x | y)$ and conditional mutual information $I(x; y | z) = H(x | z) - H(x | y, z)$, we have

$$
I(x ; y) + I(x ; z | y) = H(x) - H(x | y) + H(x | y) - H(x | y, z)
$$

= $H(x) - H(x | y, z)$
= $I(x ; y, z)$

According to the symmetry, we have

$$
I(x ; y, z) = I(x ; y) + I(x ; z | y)
$$

= $I(x ; z) + I(x ; y | z)$

By the property of chain structure, $I(x; z | y) = 0$. Since *x* is not independent with *y* given *z*, i.e. $I(x; y \mid z) > 0$, we have $I(x; y) > I(x; z)$. We have the same conclusion for the fork structure $x \leftarrow y \rightarrow z$ since it has the same conditional independency as the chain structure. For V-structure $x \rightarrow y \leftarrow z$, it is easy to see $I(x; y) > I(x; z) = 0$.

Now we expand the structure from the basic structure to a trail $x \rightleftharpoons x_1 \rightleftharpoons x_2... \rightleftharpoons x_n$. We can assume there is no V-structure in this trail. Otherwise, we can find the first collider node x_m in this trail $x \rightleftharpoons x_1 \rightleftharpoons x_2... \rightarrow x_m \leftarrow x_{m+1}... \rightleftharpoons x_n$. Then for any $j > m$, this trail is not active between *x* and *x^j* , and

$$
I(x \ ; x_{m+1}) = I(x \ ; x_{m+2}) = \ldots = I(x \ ; x_n) = 0
$$

by the d-separation theorem. We can cut this trail from x_m and reconsider this new trail $x \rightleftharpoons x_1 \rightleftharpoons x_2$ $x_2... \rightleftharpoons x_m.$

Since $x \rightleftharpoons x_1 \rightleftharpoons x_2... \rightleftharpoons x_n$ has no V-structure, we have $x \perp x_n | x_{n-1}$. Similar to the analyses at first, we have

$$
I(x \; ; \; x_{n-1}, x_n) = I(x \; ; \; x_{n-1}) + I(x \; ; \; x_n \; | \; x_{n-1})
$$
\n
$$
= I(x \; ; \; x_n) + I(x \; ; \; x_{n-1} \; | \; x_n).
$$

Thus we also can provide $I(x; x_{n-1}) > I(x; x_n)$. Similarly, we also have $x \perp x_{n-2} | x_{n-1}$ and $I(x; x_{n-2}) > I(x; x_{n-1})$. Continuing this process, we have the conclusion that for any trail $x \rightleftharpoons$ $x_1 \rightleftharpoons x_2... \rightleftharpoons x_n$

$$
I(x \, ; x_1) > I(x \, ; x_2) > \ldots > I(x \, ; x_n).
$$

If the graph is not a trail, but $x \rightleftharpoons x_1 \rightleftharpoons x_2... \rightleftharpoons x_n$ is the only trail by which *x* can reach x_1, x_2 , $...,$ and x_n . Then the conditional independencies are the same as the analyses we discussed above. Therefore the conclusion

$$
I(x \, ; x_1) > I(x \, ; x_2) > \ldots > I(x \, ; x_n).
$$

can be achieved in this situation.

Proof of Theorem [15](#page-12-0)

In the Second

Since e_i is only connected with x_i , for $x_j \notin MB_i^e$, the trail that connects x_j and e_i must go through x_i . This trail must contain at least one of the spouses e_i or children of x_i because e_i has no parent.

If $x_j \notin MB_i^e$ is not descendent of x_i , i.e. there is no path connecting e_i and x_j . Then all the trails that connect x_j and e_j must go through one of the parents of x_i . For any one of these trails, it must contain a V-structure $e_i \rightarrow x_i \leftarrow x_k \rightleftharpoons ...$ and x_i is a collider where x_k is the parent of x_i that this trail contains. Therefore all these trails are unactive given the empty set, and $I(x, a) = 0$ trail contains. Therefore all these trails are unactive given the empty set, and $I(x_j; e_i) = 0$.

Thus for any node $x_j \notin MB_i^e$, $I(x_j; e_i) \neq 0$ if and only if x_j is one of the descendent of x_i .

Let e_1, e_2, \ldots, e_n be the exogenous variables that correspond to endogenous variables x_1, x_2, \ldots, x_n . We need to prove

$$
\sum_{m=1}^{n} I(x_m; e_m) = \max_{j_1, j_2, \dots, j_n} \sum_{m=1}^{n} I(x_m; e_{j_m})
$$
 (6)

with
$$
I(x_m; e_{j_m}) \neq 0, \quad m = 1, 2, ..., n.
$$
 (7)

Since e_i and x_i are connected, $I(x_i; e_i) > 0$. For node x_j is not the descendent of e_i , e_i is not not interval that x_i as we discussed before. Then $I(x_i; e_i) > I(x_i; e_i) = 0$. Otherwise, there is a independent with x_j as we discussed before. Then $I(x_i; e_i) \geq I(x_j; e_i) = 0$. Otherwise, there is a path $e_i \rightarrow x_i \rightarrow ... \rightarrow x_j$ which starts from e_i and reaches x_j . If this path satisfies the assumption in
Theorem 14 i.e. it is the only trail that connect *x*, and *x*, we also have $I(x, i.e.) > I(x, i.e.)$ **Theorem [14](#page-11-1),** i.e. it is the only trail that connect x_i and x_j , we also have $I(x_i; e_i) > I(x_j; e_i)$.
However, if there are more than one trails that connect e_i and x_j , since e_j has no parent, t

However, if there are more than one trails that connect e_i and x_j , since e_i has no parent, the trail is active given the empty set if and only if this trail is a path from e_i to $x_j e_i \rightarrow x_i \rightarrow ... x_k \rightarrow x_j$. If we add the expression variable *e*^{*i*} to x_i </sup> e_i with this trail forms a M structure $x_i \rightarrow x_i \leftarrow e_i$. So this trail add the exogenous variable e_j to x_j , e_j with this trail forms a V-structure $x_k \to x_j \leftarrow e_j$. So this trail is unactive between x_i and e_j and $I(x_i : e_j) = 0$. Although we can not guarantee $I(x_i : e_i) \ge I(x_j : e_i)$ achieves in this condition, but if we assign e_i to x_j and assign e_j to x_i , we break the constraint $I(x_m : e_{j_m}) \neq 0$ in equation [\(6\)](#page-32-0)

Therefore, for given node x_i and any other node $x_j \in \mathcal{X}$, we have $I(x_i : e_i) \geq I(x_j : e_i)$ or $I(x_i; e_j) = 0$. If we change the exogenous variables correspond to them, we either can not reach the maximum of $\sum_{m=1}^{n} I(x_m; e_{j_m})$ or break the constraints.

For any three nodes $x_i, x_j, x_k \in X$, if we assign e_k, e_i, e_j to x_i, x_j, x_k and $I(x_i : e_k) \neq 0$, $I(x_j : e_i) \neq 0$.
 $(x_i : e_i) \neq 0$. By the analyses x_i, x_j and x_j are the descendants of x_i, x_j, x_k . There are three 0, $I(x_k; e_j) \neq 0$. By the analyses, x_i, x_j , and x_k are the descendants of x_k, x_i, x_j . There are three
paths \mathcal{P}_k , which starts from x_i to x_j , \mathcal{P}_k , which starts from x_k to x_j , and \mathcal{P}_k , which sta paths P_1 , which starts from x_k to x_i , P_2 , which starts from x_i to x_j , and P_3 , which starts from x_j to x_k . Then $\mathcal{P}_1, \mathcal{P}_2$ and \mathcal{P}_3 form a cycle that is contradictory to the assumption that \mathcal{G} is DAG. Therefore, (k, i, j) is not in the solution of equation [\(6\)](#page-32-0) and equation [\(7\)](#page-32-1). More complex situations can be proved in a similar way. So $(1, 2, ..., n)$ is the solution of equation [\(6\)](#page-32-0) under the constraints [\(7\)](#page-32-1)

On the other hand, if we have the solution of equation [\(6\)](#page-32-0) under the constraints [\(7\)](#page-32-1) as $(i_1, i_2, ..., i_n)$. We need to state that $(i_1, i_2, ..., i_n)$ exists and is unique. We know $I(x_m; e_m) \neq 0$ for all $m = 1, 2, ..., n$, so there exist permutations that satisfy all the constraints in equation [\(7\)](#page-32-1). Since the number of arrangements $\mathcal A$ for finite number $(1, 2, ..., n)$ is also finite. We can pick permutations that follow the constraints, and denote them as \mathcal{A}' . Since \mathcal{A}' is finite, we can find a unique permutation r that maximizes $\sum_{m=1}^{n} I(x_m; e_{j_m})$. Then this **r** is the solution of equation [\(6\)](#page-32-0) under constraints [\(7\)](#page-32-1).

Now let this solution $\mathbf{r} = (i_1, i_2, ..., i_n)$ and $(i_1, i_2, ..., i_n) \neq (1, 2, ..., n)$. Without loss of generality, we assume $i_m \neq m$ for some $m \leq l$ and $i_m = m$ otherwise. Since $I(x_m : e_{i_m}) \geq 0$, x_m is the descendent of x_{i_m} , $m = 1, 2, ..., l$. Because $i_m = m$ for $m \ge l$, $1 \le i_m \le l$ for $m \le l$. Then the paths from x_{i_m} to x_m
 $m = 1, 2, ..., l$ forms a cycle, which is contradictory to the property of DAG. *^m* ⁼ ¹, ², ..., *^l* forms a cycle, which is contradictory to the property of DAG.

Combing all the analyses, we have that $(e_i, ..., e_i)$ are the exogenous variables which correspond
r. r. r. r. if and only if $(i, i_0, ..., i_n)$ is the solution of equation (6) under the constraints (7) to $(x_1, x_2, ..., x_n)$ if and only if $(i_1, i_2, ..., i_n)$ is the solution of equation [\(6\)](#page-32-0) under the constraints [\(7\)](#page-32-1).

Proof of Theorem [16](#page-13-1)

Since e' is another exogenous vector that determined by e , i.e.

$$
e^{\prime }=h(e),
$$

for every element of **h** h_i , e'_i \mathbf{r}'_i and \mathbf{e}_i are both exogenous variables of x_i , then \mathbf{e}_i must be one of the inputs of the determined function *hⁱ* .

But (*e* ′ $\mathbf{e}_1^{\prime}, \dots, \mathbf{e}_n^{\prime}$) are independent with each other and $(\mathbf{e}_1, \mathbf{e}_2, \dots, \mathbf{e}_n)$ are independent with each be determined function \mathbf{e}_k best more than one input, we assume \mathbf{e}_k and \mathbf{e}_k are bot other. If the determined function h_i has more than one input, we assume e_i and e_j are both in its inputs. And for any transformation of the determined function \tilde{h}_i , we can not remove e_j from its input. By the definition of parents in SCM, we e_j is a parent of e'_i \int_{i} and e'_{j} *f*_{*i*}. Then $e'_i \leftarrow e_j \rightarrow e'_j$ *j* forms a fork structure and is active given the empty set. So $I(e_i)$ $'_{i}$; e'_{j} f_j > 0 which is contradictory to the independence assumption. Therefore every determined function h_i has an equivalent transformation \tilde{h}_i such that e'_i $\tilde{h}_i = \tilde{h}_i(e_i)$ for $i = 1, 2, ..., n$.
 $(\tilde{h}_i, \tilde{h}_i, \tilde{h}_i)$ According

Let $\tilde{\mathbf{h}} = (\tilde{h}_1, \tilde{h}_2, ..., \tilde{h}_n)$. According to the analyses above, we have $\mathbf{e}' = \tilde{\mathbf{h}}(\mathbf{e})$. Since $\tilde{\mathbf{h}}$ is the stormation of **h** and **h** is invertible, we can conclude that $\tilde{\mathbf{h}}$ is invertibl transformation of **h** and **h** is invertible, we can conclude that $\tilde{\bf{h}}$ is invertible and every element \tilde{h}_i is invertible.

Since e'_{i} e_i ^{*i*} is determined by e_i , $x_i \leftarrow e_i \rightarrow e'_i$ *i* forms a fork structure, and

$$
I(x_i; e_i, e'_i) = I(x; e_i) + I(x_i; e'_i | e_i)
$$

= $I(x_i; e'_i) + I(x_i; e_i | e'_i)$.

In **Theorem [14](#page-11-1)**, we have $I(x; x_{n-1} | x_n) > 0$ because x_{n-1}, x_n have other parents e_{n-1}, e_n and are not only determined by each other. Different from **Theorem [14](#page-11-1)**, we only have $I(x_i; e_i | e'_i)$ $'_{i}$) ≥ 0 in this condition. We have $I(x_i; e_i) \geq I(x_i; e'_i)$ \sum_{i}^{i}) because of $I(x_i; e'_i)$ I_i | *e_i* | *e*_{*i*} | *e*_{*i*} | *e*_{*i*} | *e*_{*i*} $'_{i}$) ≥ 0 . Therefore for any function \tilde{h}_i , $I(x_i; e_i) \geq I(x_i; \tilde{h}_i(e'_i))$ $'_{i}$)). Since \tilde{h}_{i} is invertible, we can get

$$
I(x_i; e'_i) \ge I(x_i; (\tilde{h}_i)^{-1}(e_i)) = I(x_i; e_i).
$$

Therefore $I(x_i; e_i) = I(x_i; e'_i)$ *i*²). For any other node *x*_{*j*}, we can find a set of nodes *Z* such that *x*^{*j*} ⊥∟ $e_i \mid Z$. We can simply write the structure as $x_j \Leftrightarrow Z \leftarrow e_i \rightarrow e'_i$ I_i' , and we also have $I(x_j; e'_i)$ $'_{i} | e_{i} = 0$ and $I(x_j; e_i | e'_i)$ I'_i \geq 0. Therefore we have $I(x_j; e_i) = I(x_j; e'_i)$ $'_{i}$) in a similar way.

L.

Proof of Theorem [18](#page-14-0)

Firstly, we state that e'_{i} \mathbf{r}'_i has no exogenous parent and endogenous parent except for x_i . If e'_i *i* has a parent, its parent can not belong to exogenous variables because e' are independent with each other and do not have a connection with each other. Let us assume x_j is the parent of e'_i *i* . The trail $e'_{i} \leftarrow x_{j} \leftrightharpoons e'_{j}$ \mathbf{z}'_j is always active no matter the direction of \leftrightharpoons , and \mathbf{e}'_i \int_i and e'_j *j* are not independent given the empty set which is contradictory to the independence assumption. Therefore, all the exogenous variables we generate do not have a parent as $e_j \in Y$ or $x_j \in X$ $j \neq i$.

Now we need to prove x_i is not the parent of e'_i i_i . We discuss the relation between e'_{i} $'$ ^{*i*} and x_i in two conditions.

condition 1

Let us assume x_i has at least one endogenous parent $x_j \in Pa_i$. If e'_i i ^{*i*} is not a parent of x_i , then $e'_i \leftarrow x_i$. The trail $e'_j \leftarrow x_j \rightarrow x_j \rightarrow e'_i$ i is active given the empty set regardless of the relation between x_j and e'_j \int_j . We have $I(e'_j)$ *j* ; *e* ′ i' > 0 which is contradictory to the independence assumption.

condition 2

If x_i has no endogenous parent and we assume x_i is a parent of e_i' e'_i ← *x_i*. Since e'_i *i* does not have other parents, x_i is the only parent of e'_i $'_{i}$, and e'_{i} i is determined by x_i . By **Algorithm 3**, we have

$$
\mathbf{e}' = \mathbf{P}\mathbf{W}^\top \mathbf{x},
$$

where W is the matrix trained by FastICA algorithm and P is the permutation matrix that rearranges e' according to the **Theorem [15](#page-12-0)**. If x_i is the only parent of e'_i i_i , there exits a constant *c* such that *e* ′ $\alpha_i' = cx_i$. Therefore $x_i = \frac{1}{c}e_i'$ $'_{i}$, and e'_{i} *i*_i is also a parent of x_i , i.e. $x_i \rightarrow e'_i$ \mathbf{z}'_i and $\mathbf{x}_i \leftarrow \mathbf{e}'_i$ *i* are equivalent. Without loss of generality, we treat *e*['] \mathbf{r}'_i as a parent of x_i in this special condition.

Combing the analyses at the beginning, we can conclude that $e' = (e'_1)$ e'_n have no parent, and *e* ′ i ^{*i*} is a parent of x_i .

Proof of Theorem [20](#page-16-0)

Let us assume x_j is a node in exogenous Markov blanket of e_i , $x_j \in MB_i^e$ where $i \neq j$. By the definition of Markov blanket, x_j must be a parent of x_i because e_i only has one child and has no parent. But x_j can be a child of x_i in other I-equivalence DAG.

Let us assume x_j is a parent of x_i in some I-equivalence DAG but does not satisfy **Definition** [10](#page-6-0). Since x_i and x_j must be connected no matter what conditions, then the determined function f_j takes x_i as an input, we can write the determined function as:

$$
x_j = f_j(Pa_j, e_j),
$$

where $x_i \in Pa_j$. For any spouses of e_i , e_i is not conditionally independent with spouses given *Z* as long as $x_i \in Z$ according to **Theorem [4](#page-3-0).** Let $Z = Pa_i$ which satisfies $x_i \in Z$. We want to prove $e_i \perp v_j \mid Pa_j$, we state it in three conditions:

condition 1

If there is no trail from x_j to x_k where $x_k \in Pa_i$. Then all the trails from e_i to x_j have same structure

$$
e_i \to x_i \to x_{i_1} \Leftrightarrow \dots \Leftrightarrow x_{i_l} \Leftrightarrow x_j. \tag{8}
$$

 x_{i_1} can not be a parent of x_i by the assumption of **condition 1**. Therefore $e_i \rightarrow x_i \rightarrow x_{i_1}$ forms a chain structure, and $e_i \perp e_j | x_i$ which indicates $e_i \perp e_j | Z$.

condition 2

If there are some trails that connect x_j and any parent of x_i x_k through the child of x_j , and they can be all represented as:

$$
e_i \to x_i \leftarrow x_k \Leftrightarrow x_{i_1} \dots \leftrightharpoons x_{i_l} \leftarrow x_j. \tag{9}
$$

If this trail x_k and x_j is a path, $x_k \leftarrow x_{i_1} \leftarrow ... \leftarrow x_{i_l} \leftarrow x_j$, but $x_i \in Pa_j$. Then $x_i \rightarrow x_j$ and $x_i \leftarrow x_i \leftarrow x_i \leftarrow x_i$ form a cycle which is contradictory to the property of undirected $x_i \leftarrow x_k \leftarrow x_{i_1} \leftarrow \dots \leftarrow x_{i_l} \leftarrow x_j$ form a cycle, which is contradictory to the property of undirected edge $x_i - x_j$ in CPDAG. Thus $x_k \Leftrightarrow x_{i_1} \ldots \Leftrightarrow x_{i_l} \leftarrow x_j$ can not be a path.

Then $x_k \Leftrightarrow x_{i_1} \ldots \Leftrightarrow x_{i_l} \leftarrow x_j$ must contain at least one V-structure and at least one collider is not belong to *Pa_j*. Otherwise, if all the colliders $x_k \Leftarrow x_{i_1} \dots \Leftarrow x_{i_l} \leftarrow x_j$ are parents of x_j , let assume the first collider is x_i , where $1 \le a \le l$ and $x_i \in Pa_i$. Then $x_i \leftarrow x_i \in x_i$ is a path. Since $x_i \rightarrow x_i$ first collider is x_{i_a} where $1 \le a \le l$, and $x_{i_a} \in Pa_j$. Then $x_{i_a} \leftarrow ... x_{i_l} \leftarrow x_j$ is a path. Since $x_{i_a} \rightarrow x_j$, there two paths form a cycle these two paths form a cycle.

Therefore the trail [\(9\)](#page-34-0) either is not active given *Pa^j* or contains a collider not belongs to *Pa^j* and is not active given the empty set.

condition 3

If there are some trails that connect x_j and any parent of x_i x_k through the parent of x_j , we have the representation of these trails as

$$
e_i \to x_i \leftarrow x_k \Leftrightarrow x_{i_1} \dots \leftrightharpoons x_{i_l} \to x_j. \tag{10}
$$

Then we notice $x_{i_l} \in Pa_j$ and trails like [\(10\)](#page-35-0) are not active given x_{i_l} or given Pa_j .

Combing these three conditions, we have $e_i \perp e_j | Pa_j$. Since x_j is only determined by e_j given $Pa_j = c$, and $x_j = f_j(c, e_j)$, we obtain $e_i \perp x_j \mid Pa_j$ which is contradictory to the character of space of x. Therefore x is not in the expression Markov blanket of e. And if $x_i \in MR^e$, x must spouses of x_i . Therefore x_j is not in the exogenous Markov blanket of e_i . And if $x_j \in MB_i^e$, x_j must be a parent of x_i in **Definition [10](#page-6-0)**.

On the other hand, let x_j is a parent of x_i in **Definition [10](#page-6-0)**, i.e.

$$
x_i = f_i(Pa_i, e_i),
$$

where $x_j \in Pa_i$. It is easy to notice the fact that structure $x - y - z$ is a V-structure if and only if for any subset of nodes $y \in Z \subset X$, *x* are *z* are not conditionally independent given *Z*, *x* $\perp \!\!\!\perp y \mid Z$. Notice that trail $e_i \to x_i \leftarrow x_j \leftarrow e_j$ is active if given x_i , then for any $Z \in \mathcal{X}$, as long as $x_i \in Z$, e_i and x_j are not conditionally independent given *Z* because $e_i \not\perp e_j | x_i \rightarrow e_i \not\perp e_j | Z$ and the determined function f_j takes e_j as input. Therefore x_j is a spouse of x_i and $x_j \in MB_i^e$.

Appendix B. AUPR results

We show the AUPR of proposed methods and baselines on all the datasets in Table [6,](#page-36-0) [7,](#page-36-1) and [8,](#page-37-0) including the mean and standard deviation of every algorithm. The mean values of these algorithms are the same as the values in bar graphs. Similar to the SHD in Section 5, we thicken the highest AUPR of causal discovery algorithms on every dataset.

Table shows the AUPR results on the ablation study corresponding to the SHD results in Table [9.](#page-37-1) The outcomes are very similar to the outcomes in Table. The improved IAMB has the smallest AUPR on every Education dataset. The AUPR of EEMBI or EEMBI-PC is always higher than EEMBI (WM) or EEMBI-PC (WM).

Algorithms	ALARM	BARLEY	CHILD	INSURANCE	MILDEW	HailFinder
PC	0.602(0.01)	0.191(0.02)	0.539(0.04)	0.350(0.02)	0.516(0.03)	0.356(0.01)
FCI	0.551(0.02)	0.366(0.01)	0.482(0.02)	0.401(0.03)	0.327(0.03)	0.362(0.01)
GIES	0.592(0.05)	0.298(0.03)	0.509(0.01)	0.381(0.02)	0.456(0.01)	0.386(0.01)
MMHC	0.568(0.02)	0.367(0.02)	0.449(0.01)	0.387(0.03)	0.538(0.03)	0.357(0.02)
GS	0.570(0.01)	0.332(0.01)	0.499(0.04)	0.373(0.03)	0.594(0.01)	0.311(0.01)
GRaSP	0.567(0.01)	0.281(0.07)	0.509(0.01)	0.412(0.07)	0.417(0.09)	0.357(0.04)
CDNOD	0.551(0.03)	0.233(0.02)	0.457(0.02)	0.336(0.02)	0.493(0.01)	0.206(0.02)
EEMBI	0.571(0.02)	0.263(0.02)	0.573(0.01)	0.433(0.03)	0.408(0.06)	0.334(0.01)
EEMBI-PC	0.620(0.01)	0.456(0.04)	0.610(0.01)	0.547(0.03)	0.570(0.04)	0.397(0.01)

Table 6: AUPR on discrete datasets

Table 7: AUPR on SACHS and Education datasets

Algorithms	SACHS	Education 1	Education 2	Education 3	Education 4	Education 5
PC.	0.399	0.366(0.01)	0.325(0.03)	0.298(0.04)	0.336(0.01)	0.390(0.03)
FCI	0.407	0.367(0.02)	0.299(0.05)	0.314(0.01)	0.300(0.01)	0.295(0.02)
GIES	0.417	0.324(0.05)	0.325(0.05)	0.310(0.04)	0.307(0.02)	0.317(0.06)
MMHC	0.319	0.286(0.02)	0.238(0.02)	0.270(0.02)	0.255(0.01)	0.272(0.02)
GS	0.407	0.346(0.02)	0.330(0.01)	0.377(0.01)	0.321(0.04)	0.367(0.02)
GRaSP	0.405	0.313(0.01)	0.322(0.01)	0.320(0.03)	0.337(0.01)	0.297(0.04)
CDNOD	0.371	0.354(0.02)	0.350(0.01)	0.369(0.01)	0.377(0.01)	0.335(0.05)
DirectLiNGAM	0.349	0.403(0.01)	0.440(0.01)	0.254(0.13)	0.253(0.14)	0.267(0.13)
CAM	0.371	0.382(0.01)	0.368(0.01)	0.363(0.01)	0.333(0.02)	0.369(0.05)
NOTEARS	0.333	0.369(0.02)	0.374(0.02)	0.407(0.02)	0.357(0.01)	0.390(0.01)
EEMBI	0.366	0.418(0.02)	0.443(0.01)	0.448(0.02)	0.464(0.01)	0.462(0.02)
EEMBI-PC	0.422	0.325(0.03)	0.332(0.02)	0.363(0.01)	0.336(0.02)	0.383(0.02)

Algorithms	Ecoli 1	Ecoli 2	Yeast 1	Yeast 2	Yeast 3
PC.	0.036	0.113	0.120	0.116	0.119
FCI	0.057	0.134	0.155	0.134	0.151
GIES	0.049	0.078	0.081	0.090	0.099
MMHC	0.055	0.104	0.134	0.112	0.111
GS	0.040	0.082	0.123	0.138	0.117
GRaSP	0.048	0.102	0.083	0.078	0.089
CDNOD	0.044	0.068	0.121	0.092	0.126
DirectLiNGAM	0.017	0.076	0.141	0.137	0.146
CAM	0.049	0.123	0.112	0.149	0.175
NOTEARS	0.029	0.086	0.052	0.155	0.096
EEMBI	0.051	0.075	0.163	0.085	0.140
EEMBI-PC	0.059	0.134	0.076	0.092	0.093

Table 8: AUPR on Dream3 datasets

Table 9: AUPR on Dream3 datasets

Algorithms	Education 1	Education 2	Education 3	Education 4	Education 5
Improved IAMB	0.317(0.02)	0.324(0.01)	0.348(0.01)	0.325(0.01)	0.334(0.01)
EEMBI (WM)	0.338(0.02)	0.356(0.01)	0.409(0.01)	0.372(0.04)	0.377(0.02)
EEMBI-PC (WM)	0.252(0.05)	0.309(0.01)	0.327(0.01)	0.300(0.02)	0.337(0.02)
EEMBI	0.418(0.02)	0.443(0.01)	0.448(0.02)	0.464(0.01)	0.462(0.02)
EEMBI-PC	0.325(0.03)	0.332(0.02)	0.363(0.01)	0.336(0.02)	0.383(0.02)

References

- David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *Journal of Machine Learning Research*, 3(1):993–1022, 2003.
- Kenneth A Bollen. *Structural equations with latent variables*, volume 210. John Wiley & Sons, 1989.
- Peter Bühlmann, Jonas Peters, and Jan Ernest. Cam: Causal additive models, high-dimensional order search and penalized regression. *The Annals of Statistics*, pages 2526–2556, 2014.
- David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of Machine Learning Research*, 3(11):507–554, 2002.
- Diego Colombo, Marloes H Maathuis, et al. Order-independent constraint-based causal structure learning. *Journal of Machine Learning Research*, 15(1):3741–3782, 2014.
- David F Crouse. On implementing 2d rectangular assignment algorithms. *IEEE Transactions on Aerospace and Electronic Systems*, 52(4):1679–1696, 2016.
- Frederick Eberhardt and Richard Scheines. Interventions and causal inference. *Philosophy of Science*, 74(5):981–995, 2007.
- Madelyn Glymour, Judea Pearl, and Nicholas P Jewell. *Causal inference in statistics: A primer*. John Wiley & Sons, 2016.
- Alain Hauser and Peter Buhlmann. Characterization and greedy learning of interventional markov ¨ equivalence classes of directed acyclic graphs. *Journal of Machine Learning Research*, 13(1): 2409–2464, 2012.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.
- Matthew D Hoffman, David M Blei, Chong Wang, and John Paisley. Stochastic variational inference. *Journal of Machine Learning Research*, 2013.
- Biwei Huang, Kun Zhang, Jiji Zhang, Joseph Ramsey, Ruben Sanchez-Romero, Clark Glymour, and Bernhard Schölkopf. Causal discovery from heterogeneous/nonstationary data. *Journal of Machine Learning Research*, 21(1):3482–3534, 2020.
- Aapo Hyvarinen. Fast and robust fixed-point algorithms for independent component analysis. *IEEE Transactions on Neural Networks*, 10(3):626–634, 1999.
- Aapo Hyvärinen and Erkki Oja. Independent component analysis: algorithms and applications. *Neural Networks*, 13(4-5):411–430, 2000.
- Diviyan Kalainathan. causal discovery box, 2018. URL [https://fentechsolutions.github.](https://fentechsolutions.github.io/CausalDiscoveryToolbox/html/index.html) [io/CausalDiscoveryToolbox/html/index.html](https://fentechsolutions.github.io/CausalDiscoveryToolbox/html/index.html).
- Diviyan Kalainathan, Olivier Goudet, Isabelle Guyon, David Lopez-Paz, and Michele Sebag. Struc- ` tural agnostic modeling: Adversarial learning of causal graphs. *Journal of Machine Learning Research*, 23(219):1–62, 2022.

Leonid Vitalevich Kantorovich and Gleb Pavlovich Akilov. *Functional analysis*. Elsevier, 2016.

- Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *International Conference on Learning Representations*, 2013.
- Diederik P Kingma, Max Welling, et al. An introduction to variational autoencoders. *Foundations and Trends*® *in Machine Learning*, 12(4):307–392, 2019.
- Daphne Koller and Nir Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.
- Wai-Yin Lam, Bryan Andrews, and Joseph Ramsey. Greedy relaxations of the sparsest permutation algorithm. In *Uncertainty in Artificial Intelligence*, pages 1052–1062, 2022.
- Jundong Li, Kewei Cheng, Suhang Wang, Fred Morstatter, Robert P Trevino, Jiliang Tang, and Huan Liu. Feature selection: A data perspective. *ACM computing surveys (CSUR)*, 50(6):1–45, 2017.
- Yuanfei Luo, Mengshuo Wang, Hao Zhou, Quanming Yao, Wei-Wei Tu, Yuqiang Chen, Wenyuan Dai, and Qiang Yang. Autocross: Automatic feature crossing for tabular data in real-world applications. page 1936–1945. Association for Computing Machinery, 2019. ISBN 9781450362016. doi: 10.1145/3292500.3330679.
- Daniel Marbach. Dream 3, 2008. URL [https://www.synapse.org/#!Synapse:syn2853594/](https://www.synapse.org/#!Synapse:syn2853594/wiki/71567) [wiki/71567](https://www.synapse.org/#!Synapse:syn2853594/wiki/71567).
- Dimitris Margaritis. Learning bayesian network model structure from data. Technical report, Carnegie-Mellon Univ Pittsburgh Pa School of Computer Science, 2003.
- Christopher Meek. Causal inference and causal explanation with background knowledge. *arXiv preprint arXiv:1302.4972*, 2013.
- Octavio Cesar Mesner and Cosma Rohilla Shalizi. Conditional mutual information estimation for ´ mixed, discrete and continuous data. *IEEE Transactions on Information Theory*, 67(1):464–484, 2020.
- Sch Olkope and Joris M Mooij. Foundations of structural causal models with cycles and latent variables by stephan bongers, patrick forre, jonas peters 2, bernhard. *arXiv preprint arXiv:1611.06221*, 2016.
- Judea Pearl. *Probabilistic reasoning in intelligent systems: networks of plausible inference*. Morgan kaufmann, 1988.
- Jean-Philippe Pellet and André Elisseeff. Using markov blankets for causal structure learning. *Journal of Machine Learning Research*, 9(7), 2008.
- Karen Sachs, Omar Perez, Dana Pe'er, Douglas A Lauffenburger, and Garry P Nolan. Causal protein-signaling networks derived from multiparameter single-cell data. *Science*, 308(5721): 523–529, 2005.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2008.

Marco Scutari. bnlearn, 2023. URL <https://www.bnlearn.com/>.

- Marco Scutari, Catharina Elisabeth Graafland, and José Manuel Gutiérrez. Who learns better bayesian network structures: Constraint-based, score-based or hybrid algorithms? In *International Conference on Probabilistic Graphical Models*, pages 416–427. Proceedings of Machine Learning Research, 2018.
- Shohei Shimizu, Patrik O Hoyer, Aapo Hyvärinen, Antti Kerminen, and Michael Jordan. A linear non-gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7(10), 2006.
- Shohei Shimizu, Takanori Inazumi, Yasuhiro Sogawa, Aapo Hyvarinen, Yoshinobu Kawahara, Takashi Washio, Patrik O Hoyer, Kenneth Bollen, and Patrik Hoyer. Directlingam: A direct method for learning a linear non-gaussian structural equation model. *Journal of Machine Learning Research*, 12(4):1225–1248, 2011.
- Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pages 2256–2265. Proceedings of Machine Learning Research, 2015.
- Peter Spirtes, Christopher Meek, and Thomas Richardson. Causal inference in the presence of latent variables and selection bias. UAI'95, page 499–506, San Francisco, CA, USA, 1995. Morgan Kaufmann Publishers Inc. ISBN 1558603859.
- Peter Spirtes, C Meek, and T Richardson. An algorithm for causal inference in the presence of latent variables and selection bias in computation, causation and discovery, 1999.
- M.Ide T.Ikeuchi, G.Haraoka. Lingam, 2023. URL [https://lingam.readthedocs.io/en/](https://lingam.readthedocs.io/en/latest/index.html) [latest/index.html](https://lingam.readthedocs.io/en/latest/index.html).
- Ioannis Tsamardinos, Constantin F Aliferis, Alexander R Statnikov, and Er Statnikov. Algorithms for large scale markov blanket discovery. In *FLAIRS conference*, volume 2, pages 376–380. St. Augustine, FL, 2003.
- Ioannis Tsamardinos, Laura E Brown, and Constantin F Aliferis. The max-min hill-climbing bayesian network structure learning algorithm. *Machine Learning*, 65:31–78, 2006.
- Xun Zheng, Bryon Aragam, Pradeep K Ravikumar, and Eric P Xing. Dags with no tears: Continuous optimization for structure learning. *Advances in Neural Information Processing Systems*, 31, 2018.
- Yujia Zheng. causal-learn, 2021. URL [https://causal-learn.readthedocs.io/en/latest/](https://causal-learn.readthedocs.io/en/latest/index.html) [index.html](https://causal-learn.readthedocs.io/en/latest/index.html).
- Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. *AI open*, 1:57–81, 2020.