# Highlights

A Robust and Efficient Optimization Model for Electric Vehicle Charging Stations in Developing Countries under Electricity Uncertainty

Mansur M. Arief, Yan Akhra, Iwan Vanany

- Proposed a simulation-based optimization model to design optimal EV charging station infrastructure that can withstand uncertain power supply in developing countries.
- Used control variates (CV) variance reduction technique to enhance simulation efficiency and provide a highly robust solution that buffers against uncertain electricity disruptions.
- Numerical experiment using data from Surabaya, Indonesia showed the proposed model achieved 13% higher average objective value compared to the non-robust solution.
- The enhanced simulation efficiency through CV reduces the required sample size by a factor of 10 compared to Monte Carlo simulations
- The proposed model showcases a potential to provide a robust solution to the challenges associated with EV charging infrastructure under random electricity disruptions in developing countries.

# A Robust and Efficient Optimization Model for Electric Vehicle Charging Stations in Developing Countries under Electricity Uncertainty

Mansur M. Arief<sup>a,\*</sup>, Yan Akhra<sup>b</sup>, Iwan Vanany<sup>b</sup>

 <sup>a</sup>Department of Aeronautics and Astronautics Engineering, Stanford University, 450 Serra Mall, Stanford, 94305, CA, USA
 <sup>b</sup>Department of Industrial and Systems Engineering, Institut Teknologi Sepuluh Nopember, Sukolilo, Surabaya, 60111, East Java, Indonesia

# Abstract

The rising demand for electric vehicles (EVs) worldwide necessitates the development of robust and accessible charging infrastructure, particularly in developing countries where electricity disruptions pose a significant challenge. Earlier charging infrastructure optimization studies do not rigorously address such service disruption characteristics, resulting in suboptimal infrastructure designs. To address this issue, we propose an efficient simulation-based optimization model that estimates candidate stations' service reliability and incorporates it into the objective function and constraints. We employ the control variates (CV) variance reduction technique to enhance simulation efficiency. Our model provides a highly robust solution that buffers against uncertain electricity disruptions, even when candidate station service reliability is subject to underestimation or overestimation. Using a dataset from Surabaya, Indonesia, our numerical experiment demonstrates that the pro-

<sup>\*</sup>Corresponding Author

Email address: mansur.arief@stanford.edu (Mansur M. Arief )

posed model achieves a 13% higher average objective value compared to the non-robust solution. Furthermore, the CV technique successfully reduces the simulation sample size up to 10 times compared to Monte Carlo, allowing the model to solve efficiently using a standard MIP solver. Our study provides a robust and efficient solution for designing EV charging infrastructure that can thrive even in developing countries with uncertain electricity disruptions. *Keywords:* electric vehicle, charging station, developing country, uncertainty, variance reduction

# 1. Introduction

The growing global demand for electric vehicles (EVs) has brought to the forefront the need for reliable and easily accessible EV charging infrastructure. According to a report by the International Energy Agency, as numerous governments set ambitious goals for electrifying their transportation systems, the worldwide EV demand has exponentiated in recent years. In 2010, there were only approximately 17,000 EVs on the world's roads. In 2019, for instance, China led the global EV market, with more than 1 million EVs cars sold that year (more than 50% of global EV demand), followed by the whole of Europe with 561,000 cars sold and the USA with 327,000 cars sold. This trend is projected to persist in the upcoming years (IEA, 2021).

Developing countries are also striving to promote EV adoption, coupled with greener electricity (Lai et al., 2022) to expedite the achievement of their sustainability goals. For example, Indonesia has set an ambitious target of having 20% of all automobile sales be electric by 2025, with a long-term goal of achieving fully electrified transportation by 2050 (Simanjutak, 2022). However, developing countries like Indonesia face significant infrastructure constraints that must be addressed to achieve these goals. The availability of EV charging infrastructure is a crucial issue that must be addressed to support the widespread adoption of EVs. In Indonesia, there were only 240 public EV charging points across the country as of 2021 (Purnama et al., 2021). However, an estimated 31,000 EV charging stations are required throughout the country to support sustainable electrification of vehicles in the country (Harsono, 2020).

This lacking infrastructure issue is not unique to Indonesia and is faced by many other developing countries to support the growth of EV adoption. Tackling this challenge by designing a convenient and reliable EV charging network is, however, a very complex task. To ensure a convenient location, it is essential to consider factors such as population density or potential EV demand distribution (Khalid et al., 2019). However, in major cities in developing countries, finding suitable land for charging stations may be challenging due to limited space availability. Furthermore, in developing countries, service uncertainty, including electricity, is one of the most significant issues. Implementing smart charging strategies (Fachrizal et al., 2020) becomes hardly feasible due to electricity supply uncertainty. Outages and other electricity disruptions often occur, posing a significant problem for users who demand reliable service.

To address this challenge, our study proposes a robust solution for designing EV charging infrastructure that accounts for the challenge of electricity disruptions in developing countries. We introduce a simulation-based optimization model that estimates the service reliability of candidate charging stations and incorporates this information into the objective function and constraints. This approach offers a versatile solution by utilizing simulation approaches compared to previous works that assume available disruption probability models. Additionally, we employ a variance reduction technique called control variates (CV) to enhance simulation efficiency, reducing the required sample size by up to 10 times compared to naive Monte Carlo (MC) simulations. This results in an efficient mixed-integer programming (MIP) model that solves for optimal solutions that strike the balanced objective between minimizing the total cost of operating and investing in the charging infrastructure and providing high-quality service to the public. Fig. 1 illustrates the comparison between the traditional modeling approach without variance reduction vs. the proposed framework that utilizes the variance reduction technique to achieve a tighter confidence interval (hence much more precise output) with less computational burden.

Our work contributes in three key ways. Firstly, we propose a model that specifically addresses the critical issue of electricity disruption in EV charging station planning, particularly in developing countries. Secondly, we integrate the estimation of disruption probabilities into our model, providing a more data-driven approach compared to previous works that assumed available disruption probability models apriori. Finally, our study demonstrates the robustness of the proposed model in solving EV charging infrastructure problems by comparing its performance to a non-robust model, even when disruption probabilities are slightly under or over-estimated. Our numerical experiment, based on an EV dataset from Surabaya, Indonesia, shows that our model achieves a 13% higher average objective value compared to the

#### Without Variance Reduction



Figure 1: Illustration of the proposed framework. The incorporation of partial knowledge about real-world uncertainty in the modeling allows us to reduce the variance of the simulation outputs, hence reducing the required sample size to achieve a tighter confidence

interval (i.e., higher confidence results).

non-robust solution, highlighting its superior performance to help build sustainable and thriving ecosystems for EVs, both in developed and developing countries in the years to come.

The rest of this paper is structured as follows. In Section 2, we provide a concise overview of the literature related to the optimization of EV charging infrastructureWe then present the proposed model formulations in Section 3 and approach incorporating the CV technique to estimate the service reliability (i.e. the complement of disruption probability). In Section 4, we describe the experiment settings and discuss the main findings in Section 5. Finally, we conclude our work in Section 6.

# 2. Literature review

In this section, we briefly review earlier works directly related to the planning of EV charging infrastructure and relevant case studies that motivate our approach. Examining these earlier works offers insight into the evolution of methodologies, leading to the proposed work, which uniquely introduces a combination of stochastic modeling and variance reduction techniques. The summary is provided in Table 1.

The planning of EV charging infrastructure can be viewed as a facility location problem, which aims to minimize an objective function subject to constraints related to the desired performance of the network facilities. Early studies, including those by He et al. (2016) and Albana et al. (2022), adopted deterministic models focusing on minimizing charging stations and development costs, respectively. Ko et al. (2017) sought to maximize service demand, whereas Jegham and Layeb (2020) aimed to minimize infrastructure and ac-

Authors	Authors Objectives		$\mathbf{V}\mathbf{R}^{\dagger}$
He et al. (2016)	Minimize station count	D	-
Albana et al. (2022)	Minimize development and transport costs	D	-
Ko et al. (2017)	Maximize service demand	D	-
Jegham and Layeb (2020)	Minimize infrastructure and access costs	D	-
Asamer et al. (2016)	Maximize covered taxi trips	D	-
Frade et al. $(2011)$	Maximize demand covered	D	-
Kunith et al. (2017)	Minimize battery and infrastructure costs	D	-
Spieker et al. (2017)	Maximize POI and traffic coverage	D	-
Fekete et al. (2016)	Maximize covered demand volume	D	-
Yuan et al. (2015)	Minimize station count	D	-
Hua and Xu (2019)	Maximize service performance	D	-
Fredriksson et al. (2021)	Minimize station count	D	-
Miljanic et al. (2018)	Minimize path length	D	-
Bouguerra and Layeb (2019)	Minimize station count	D	-
Lo Franco et al. (2020)	Minimize station count	D	-
Sun et al. (2020)	Maximize total EV flow	D	-
Huang and Sun (2023)	Minimize station, construction, and travel costs	D	-
Hamed et al. (2023)	Maximize EV coverage in day and night	D	-
Zhang et al. (2022)	Minimize operating costs	D	-
Amilia et al. (2022)	Minimize total cost	D	-
Hosseini and MirHassani (2015)	Minimize station, recharging, and travel costs	S	-
Yıldız et al. (2019)	Minimize infrastructure costs	S	-
Alhazmi et al. (2017)	Maximize station coverage	S	-
Li et al. (2016)	Minimize total cost	S	-
Ren et al. (2019)	Maximize EV coverage by stations	S	-
Vazifeh et al. (2019)	Minimize station count	S	-
Speth et al. (2022)	Maximize traffic volume and vehicles served	S	-
This study	Maximize service-penalized profit	$\mathbf{S}$	$\mathbf{C}\mathbf{V}^{\ddagger}$

 Table 1: Summary of EV Charging Infrastructure Optimization Model

\*Modeling: D (Deterministic), S (Stochastic)

 $^\dagger \textit{VR:}$  Variance Reduction

 $^{\ddagger}CV: Control Variates$ 

cess costs. Similar objectives were pursued by Asamer et al. (2016), Frade et al. (2011), and Kunith et al. (2017), with deterministic models being the common methodology.

Several other studies, like those conducted by Spieker et al. (2017), Fekete et al. (2016), Yuan et al. (2015), Hua and Xu (2019), Fredriksson et al. (2021), and Miljanic et al. (2018), continued the trend of deterministic models, exploring various aspects of EV charging station optimization. Other researchers, including Bouguerra and Layeb (2019), Lo Franco et al. (2020), Sun et al. (2020), Huang and Sun (2023), Hamed et al. (2023), Zhang et al. (2022), and Amilia et al. (2022), focused on minimizing the number of charging stations or the operating cost, or maximizing the EV flow coverage.

Another line of work integrates charging infrastructure into the smart-grid design (Chen and Tong, 2012; Lam et al., 2012a,b) or other renewable energy sources such as solar cells (Guo et al., 2012). While this approach provides an integrated solution to renewable energy issues and amplifies the positive impact of EVs on the environment, it may not be practical for urban areas in developing countries. A comprehensive review of charging infrastructure designs is presented by Unterluggauer et al. (2022), emphasizing the need for increasingly detailed modeling that accounts for randomness and variability. However, there is a lack of rigorous real-world case studies that emphasize uncertainty quantification in the modeling framework.

Several case studies have been conducted in both developed and developing countries. For example, Frade et al. (2011) studied the problem of slowcharging technology in Lisbon, where vehicles are often parked overnight. In contrast, Huang et al. (2016) considered both fast- and slow-charging technologies, focusing on robustly covering all demands and avoiding partial fulfillment in the city of Toronto. Another case study was conducted by Erbaş et al. (2018) using a GIS-based model in Ankara and adopting a fuzzy approach. A city-scale simulation was developed for Singapore by Bi et al. (2017), focusing on the trade-off between cost minimization and customer accessibility maximization. Lastly, Amilia et al. (2022) proposed a set covering model for EV charging stations in Surabaya but ignored electricity disruption and only provided redundant demand coverage to provide a buffer against uncertainty, resulting in an overly simplified model and sub-optimal solutions.

In light of these studies, it is clear that the EV facility location problem is a complex and multifaceted issue that requires a tailored approach for different regions and contexts. Developing countries, in particular, may face unique challenges, such as power electricity disruptions, that must be considered in the planning and design of EV facilities. Such disruptions and uncertainty are addressed only in a handful of studies. For instance, Zhang et al. (2023) uses a multi-criteria decision-making approach aiming to strike a balanced solution against flooding disruption that maximizes the charging convenience, minimizes the impact of flood hazards, and minimizes the impact of existing charging stations using TOPSIS. Liu et al. (2022) integrates the electric bus charging stations with photovoltaic and energy storage systems using a two-stage stochastic programming model, enabling them to incorporate the uncertainty of PV power outputs. Hussain et al. (2020) optimizes the size of the energy storage system considering the annualized cost, penalty cost for buying power during peak hours, and penalty cost for resilience violations. Other works that consider stochastic modeling include (Hosseini and MirHassani, 2015; Yıldız et al., 2019; Alhazmi et al., 2017; Li et al., 2016; Ren et al., 2019; Vazifeh et al., 2019; Speth et al., 2022), which directly use either structure of the stochastic models or simulations to represent elements of uncertainty into their optimization models. The caveat is that the resulting model can be extremely hard to solve, especially when a solution with high confidence is desired.

The proposed work extends the use of stochastic modeling and introduces control variates (Hesterberg and Nelson, 1998), a variance reduction technique that can speed up a simulation-based optimization model, to the field. We propose an approach that addresses the challenges of the need to account for electricity disruptions via simulation and controlling the resulting objective value uncertainties by adjusting the simulation sample size. Simulation modeling enables the modeler to adjust the degree of modeling fidelity, depending on the prior knowledge available, and can be easily verified by estimating the probability of electricity disruptions and comparing it with available historical data. The resulting simulation-based robust model can be accelerated using variance reduction techniques (i.e., control variates), and it offers a more accurate and practical approach for planning and designing EV charging infrastructure that considers uncertainty and disruptions. The integration of stochastic modeling and control variates sets this work apart from previous research, potentially paving the way for more efficient and effective EV charging station location optimization solutions.



Figure 2: The distribution of EV charging demands across the city of Surabaya (blue nodes) and the charging station candidates (red nodes).

# 3. Model formulation

In this section, we describe our modeling components, including the decision variables, objective function, constraint set, model benchmarks (robust and non-robust model), and the CV method we employ to improve simulation efficiency.

#### 3.1. Decision Variables

We consider a set of demand nodes I and supply nodes J, representing sub-district centers and charging station candidate locations in the region under study. We also consider K vehicle types, representing different vehicle modalities that the residents use for commuting (here, we consider two modalities: electric motorcycles and electric cars). The average time to travel from node  $i \in I$  to node  $j \in J$  is denoted by  $d_{ij}$ . A threshold parameter  $d_{max}$ is introduced as an upper bound for this travel time as a proxy to study the robustness of the solution w.r.t. consumer time-to-travel for charging. The decision variables include binary variables  $x_j$  indicating whether the charging station candidate j is selected or not and  $y_{ij}$  indicating whether demand node i is to be assigned to be served by charging station j. In addition, we also use integer decision variables  $v_{ij}^k$  and  $u_j$ , denoting the number of electric vehicles of type k from node i charged at node j and the number of units of charging connectors installed at node j, respectively.

$$x_j = \begin{cases} 1, & \text{if station } j \in J \text{ is selected} \\ 0, & \text{otherwise} \end{cases}$$
(1)

$$y_{ij} = \begin{cases} 1, & \text{if node } i \in I \text{ is assigned to node } j \in J \\ 0, & \text{otherwise,} \end{cases}$$
(2)

$$v_{ij}^k \in \{0, 1, \cdots\}, \forall i \in I, j \in J, k \in K$$
 (3)

$$u_j \in \{0, 1, \cdots\}, \forall j \in J \tag{4}$$

Each opened station j incurs a daily cost  $h_j$  and can only accommodate  $q_j$  charging connectors due to limited space. Each charging connector incurs g daily operational cost and has a limited daily charging throughput of  $c_j$  kWh. A vehicle type k takes  $e_k$  kWh energy and  $t_k$  time to charge using fast-charging technology. We use the electricity price denoted by r to convert the energy used to monetary value.

#### 3.2. Objective Function

The objective is to maximize daily profits under random disruption events at each station, i.e., the revenue from all undisrupted stations minus operational and investment costs. We add a penalty term for any unmet customer demands due to the disruptions to study proper incentivizing mechanisms to achieve further robust models in the ablation study.

To this end, we consider each charging station  $j \in J$  to have a reliability

$$p_j = \mathbb{P}(Z_j \le z_j) = \mathbb{E}[\mathbb{I}(Z_j) \le z_j].$$
(5)

The disruption events are simulated utilizing random variable  $Z = [Z_j]_{\forall j \in J} \sim q. Z_j$  represents the underlying state triggering electricity disruption at station j whenever it exceeds some threshold  $z_j$ . In practice, electricity disruption events may occur due to extreme weather, spiking demand, or fallen trees (Sowden, 2022) (in which  $Z_j$  might represent wind speed, cumulative region-wide demand, or fallen tree branch weights, respectively, that hits electrical equipment and  $z_j$  is the equipment threshold to deal with the corresponding random  $Z_j$  realization). Khalid et al. (2019) presents a review of how EV charging infrastructures strain the electricity grids, which, in turn, exacerbate the likelihood of electricity outages, especially in developing countries.

With this consideration, the objective function can be formulated as follows: we have prior information about  $p_j, \forall j \in J$ .

$$\max \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} \underbrace{re_k p_j v_{ij}^k}_{\text{revenue}} - \underbrace{sd_{ij}(1-p_j)v_{ij}^k}_{\text{penalty}} - \sum_{j \in J} \underbrace{(gu_j + h_j x_j)}_{\text{total cost}}.$$
(6)

On the other hand, if  $p_j$  is not available, then we can use simulation to

estimate the following objective:

$$\max \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} \underbrace{re_k v_{ij}^k \mathbb{E} \left[ \mathbb{I}(Z_j \le z_j) \right]}_{\text{revenue}} - \underbrace{sd_{ij} v_{ij}^k \mathbb{E} \left[ \mathbb{I}(Z_j > z_j) \right]}_{\text{penalty}} - \sum_{j \in J} \underbrace{(gu_j + h_j x_j)}_{\text{total cost}}, \tag{7}$$

where  $\mathbb{I}(Z_{jl} \leq z_j)$  is binary variables indicating whether the disruption occurs or not.

$$\mathbb{I}(Z_{jl} \le z_j) = \begin{cases} 1, & \text{if } Z_{jl} \le z_j \\ 0, & \text{otherwise} \end{cases}$$
(8)

Monte Carlo (MC) simulation is one of the most practical methods to achieve this. MC uses n i.i.d. copies of the random variable to estimate the expectation. For each  $j \in J$ , we first generate  $Z_{j1}, Z_{j2}, \dots Z_{jn}$ . We then check if the disruption event is triggered or not at the *l*-th sample and output the binary indicators  $I_{jl} = \mathbb{I}(Z_{jl} \leq z_j)$ . Then, we use the binary indicators in our final (robust) objective function:

$$\max \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} \sum_{l=1}^{n} \frac{1}{n} \left( \underbrace{(re_k v_{ij}^k I_{jl}}_{\text{revenue}} - \underbrace{sd_{ij} v_{ij}^k (1 - I_{jl})}_{\text{penalty}} \right) - \underbrace{\sum_{j \in J} (gu_j + h_j x_j)}_{\text{total cost}}.$$
(9)

We call our model the *Robust Model* in the experiment, to contrast with the original (*Non-Robust*) model proposed by Amilia et al. (2022), which is attained when setting  $I_{jl} = 1$  for all  $j \in J, l \in \{1, 2, \dots n\}$  in (9) during optimization. The solutions of both models are evaluated under random disruption events generated using a different random seed.

# 3.3. Constraints

The maximization of the objective function in (9) is subject to a set of constraints:

s.t. 
$$\sum_{k \in k} v_{ij}^k \le y_{ij} M, \qquad \forall i \in I, j \in J, \qquad (10)$$

$$d_{ij}y_{ij} \le d_{max}, \qquad \forall i \in I, j \in J, \qquad (11)$$

$$\sum_{j \in J} v_{ij}^k = w_i^k, \qquad \forall i \in I, k \in K, \tag{12}$$

$$\sum_{i \in I} \sum_{k \in K} t_k v_{ij}^k \le c_j u_j, \qquad \forall j \in J, \qquad (13)$$

$$u_j \le x_j q_j, \qquad \forall j \in J, \qquad (14)$$

$$\sum_{i \in I} y_{ij} \le x_j M, \qquad \forall j \in J, \qquad (15)$$

$$\sum_{j \in J} y_{ij} \ge 1, \qquad \forall i \in I, \qquad (16)$$

$$\sum_{j \in J} x_j \le N \tag{17}$$

$$\sum_{j\in J}\sum_{l=1}^{n}\frac{1}{n}y_{ij}I_{jl} \ge \bar{p}, \qquad \forall i \in I \qquad (18)$$

$$\sum_{j\in J}\sum_{l=1}^{n}\frac{1}{n}v_{ij}^{k}I_{jl} \ge \sum_{j\in J}v_{ij}^{k}\bar{p},\qquad\qquad\forall i\in I, k\in K\qquad(19)$$

In the above formulation, constraint (10) ensures that charging stations can only charge vehicles if assigned. Constraint (11) ensures the maximum time-to-charge for consumers does not exceed the set threshold  $d_{max}$ . Constraint (12) ensures all charging demands are fulfilled, where  $w_i^k$  denotes the number of vehicles of type k to charge at demand point i. Constraint (13) ensures that the required charging capacity to fulfill each station's assigned demand does not exceed the installed capacity. Constraint (14) restricts the number of charging connectors installed in each station. Constraint (15) ensures that demands are assigned only to opened stations. Constraint (16) guarantees that at least one stations cover each demand. Constraint (17) limits the maximum number of stations to open. Finally, constraint (18-19) ensures that the probability that at least one of the assigned charging stations serving a given demand is not under an electricity outage is greater than or equal to  $\bar{p}$ , assuming that outages between stations are independent.

#### 3.4. Robust vs. Non-Robust Model

The consideration of  $p_j$  in our formulation is part of our attempt to boost the robustness of the original model and address the unique challenges and characteristics of urban areas in developing countries. The Non-Robust Model ignores disruption probability, resulting in a more simplified model. Our formulation is general, in the sense that we can attain the earlier model by setting  $I_{jl} = 1$  for all  $j \in J, l \in \{1, 2, \dots, n\}$ . This earlier model ignores disruption uncertainty and often results in an overly cost-optimized solution that can have serious performance degradation when disruption occurs. Fig 6 (left) shows a non-robust solution where only two stations are selected to cover 30+ demand nodes in the city of Surabaya. In this solution, many demand nodes are only covered by one station (no redundancy), and thus, when an electricity disruption hits the charging station, the charging demands will not be met and the residents are served very poorly. Our proposed robust model aims to incorporate the disruption uncertainty and optimizes the location and capacity of EV charging stations while balancing the trade-offs between consumer service level and economic profits. This incorporation maintains a linear objective function and linearized constraints, which still yields an MIP model that can solve efficiently using standard solvers.

# 3.5. Improving the Efficiency of Disruption Probability Estimation

While the proposed objective function in (9) is still linear, the sample size n required to achieve high statistical confidence might blow up as the disruption probabilities  $1 - p_j, \forall j \in J$  become lower (e.g., as the utilities in developing countries mature). Note that our objective essentially estimates  $p_j$  by generating enough values  $Z_{j1}, Z_{j2}, \dots, Z_{jn}$ , and compute

$$\hat{p}_{j} = \frac{1}{n} \sum_{l=1}^{n} \mathbb{I}(Z_{jl} \le z_{j})$$
(20)

which can be shown to be unbiased and converges to  $p_j$ .

Remark 1 (Unbiased and Convergence). Under the assumption that  $Z = [Z_j]_{\forall j \in J} \sim q$  are independently and identically distributed, and  $z_j, \forall j \in J$  are fixed threshold values, estimator  $\hat{p}_j$  is an unbiased and consistent estimator of  $p_j$ .

*Proof.* The proof is straightforward but is provided here for completeness. Unbiasedness:

$$\mathbb{E}[\hat{p}_j] = \mathbb{E}\left[\frac{1}{n}\sum_{l=1}^n \mathbb{I}(Z_{jl} \le z_j)\right]$$
(21)

$$= \frac{1}{n} \sum_{l=1}^{n} \mathbb{E} \left[ \mathbb{I}(Z_{jl} \le z_j) \right]$$
(22)

$$=\frac{1}{n}\sum_{l=1}^{n}p_{j}$$
(23)

$$= p_j \tag{24}$$

where the first equality follows from the definition of  $\hat{p}_j$ , the second equality follows from the linearity of the expectation operator to the sum of indicator functions, and the third line follows from the fact that  $Z_{jl}$  are independently and identically distributed, and the third equality follows from the definition of  $p_j$ .

Consistency: We know that by the law of large numbers, for any  $\epsilon > 0$ ,

$$\lim_{n \to \infty} \mathbb{P}\left( \left| \hat{p}_j - p_j \right| \ge \epsilon \right) = 0.$$
(25)

Hence,  $\hat{p}_j$  converges in probability to  $p_j$ , and thus it is a consistent estimator of  $p_j$ .

Supposed that we already have an estimate  $\hat{p}_j, \forall j \in J$ . We can now plug the estimate into our optimization problem, giving

$$\max \sum_{i \in I} \sum_{j \in J} \sum_{k \in K} \underbrace{re_k \hat{p}_j v_{ij}^k}_{\text{revenue}} - \underbrace{sd_{ij}(1 - \hat{p}_j) v_{ij}^k}_{\text{penalty}} - \sum_{j \in J} \underbrace{(gu_j + h_j x_j)}_{\text{total cost}}$$
(26)

s.t. Constraint (10) - (17)

$$\sum_{j \in J} y_{ij} \hat{p}_j \ge \bar{p}, \qquad \forall i \in I \qquad (27)$$

$$\sum_{j \in J} v_{ij}^k \hat{p}_j \ge \sum_{j \in J} v_{ij}^k \bar{p}, \qquad \forall i \in I, k \in K.$$
(28)

Note that this formulation using  $\hat{p}_j, \forall j \in J$  is equivalent to the robust model using indicator variables  $I_{jl}, \forall j \in J, l \in \{1, 2, \dots, n\}$  earlier that uses the objective function (9).

# 3.5.1. Estimating $\hat{p}_j$ to Sufficient Accuracy

While  $\hat{p}_j$  is unbiased and consistent, the sample size to ensure a precise estimate can be arbitrarily large, especially when we want a higher accuracy (e.g. when the disruption rate  $1 - p_j$  is tiny, such as in developed countries where utility service has high reliability). Suppose we want an  $\delta$ -accuracy and  $1 - \alpha$  confidence level to estimate  $p_j = 0.9999$ . Then, we can use Hoeffding's inequality to determine the sample size. According to Hoeffding's inequality, for any  $\delta > 0$ , the probability that the estimate deviates from the true value by more than  $\delta$  is bounded by

$$\mathbb{P}(|\hat{p}_j - p_j| > \delta) \le 2e^{-2n\delta^2},\tag{29}$$

where n is the sample size. Hence, if we want to ensure  $1 - \alpha$  confidence level, we set  $2e^{-2n\delta^2} = \alpha$ , and solve for n

$$n = \frac{1}{2\delta^2} \ln\left(\frac{2}{\alpha}\right). \tag{30}$$

For instance, if we want an accuracy of  $\delta = 0.0001$  and a confidence level of  $1 - \alpha = 0.95$ , then the required sample size is

$$n = \frac{1}{2(0.0001)^2} \ln\left(\frac{2}{0.05}\right) \approx 114,763,\tag{31}$$

which is quite huge. Figure 3 shows the sample size (in a  $\log_{10}$  scale) for various  $\alpha$  and  $\delta$  values. Note, however, that this is an upper bound and in practice, this sample size is not always necessary.

If we have N := |J| stations and each  $p_j$  has to be estimated using  $n \approx 114,763$  samples, then we will need  $N \times 114,763$  samples to estimate the samples prior to solving the optimization problem, which can be overly burdensome if each simulation runs considers complex systems. Thus, we seek ways to improve efficiency and reduce the variance of the estimator.



Figure 3: Sample size required to achieve  $\delta$ -accuracy and  $1 - \alpha$  confidence.

# 3.5.2. Improving Efficiency via Control Variates

One way to improve the estimation efficiency and thus reduce the sample size is through the use of control variates (CV) (Hesterberg and Nelson, 1998). CV involves introducing a new variable that is correlated with the random variable of interest and can be easily estimated. The CV is then used to adjust the estimate of the random variable to improve its efficiency by reducing the variance of the estimator using the cheaper-to-compute random variable. In our case, we can use CV to estimate  $p_j = \mathbb{P}(Z_j \leq z_j)$ . Let  $g(Z_j)$  be a function of  $Z_j$  that is easy to compute. Specifically, if we consider Gaussian  $q = N(\mu, \sigma)$  and  $Z_j \sim q$ , we can use

$$g(z) = \Phi(z) \tag{32}$$

the CDF of the standard normal distribution as the CV to compute  $g(Z_j)$ . The CV estimator for  $p_j$  is computed as

$$\hat{p}_{j} = \frac{1}{n} \sum_{l=1}^{n} \mathbb{I}(Z_{jl} \le z_{j}) + \pi_{j} \left( \mathbb{I}(X_{jl} \le \bar{z}_{j}) - g(\bar{z}_{j}) \right)$$
(33)

where  $Z_{jl}$  is the *l*-th sample from the distribution q,  $X_{jl}$ 's are standard normal random variables correlated with  $Z_{jl}$ , and  $\bar{z}_j$  are the scaled version of  $z_j$ chosen to threshold  $X_{jl}$ . Finally,  $\pi_j$  is chosen to minimize the variance

$$\pi_j = -\frac{\operatorname{Cov}\left(\sum_{l=1}^n \mathbb{I}(Z_{jl} \le z_j), \sum_{l=1}^n \mathbb{I}(X_{jl} \le \bar{z}_j)\right)}{\operatorname{Var}\left(\sum_{l=1}^n \mathbb{I}(X_{jl} \le \bar{z}_j)\right)}.$$
(34)

We can show that the CV estimator is unbiased and achieves variance reductions in the following remarks. The reduction in variance, subsequently, allows us to reduce the sample size to achieve the same level of  $\delta$  and  $\alpha$ .

Remark 2 (Unbiasedness of CV estimator). The CV estimator (33) is unbiased for  $p_j$ .

*Proof.* The proof is straightforward, showing  $\mathbb{E}[\hat{p}_j] = p_j$ .

$$\mathbb{E}[\hat{p}_j] = \frac{1}{n} \sum_{l=1}^n \mathbb{E}[\mathbb{I}(Z_{jl} \le z_j)] + \pi_j \left(\frac{1}{n} \sum_{l=1}^n \mathbb{E}[\mathbb{I}(X_{jl} \le \bar{z}_j)] - g(\bar{z}_j)\right)$$
(35)

$$= \frac{1}{n} \sum_{l=1}^{n} p_j + \pi_j \left( \frac{1}{n} \sum_{l=1}^{n} g(\bar{z}_j) \right) - \pi_j g(\bar{z}_j)$$
(36)

$$=p_j.$$
(37)

Remark 3 (Variance Reduction of CV Estimator). Assuming we can generate highly correlated random variables  $Z_{jl}$  and  $X_{jl}$  simultaneously and choose the optimal  $\pi_j$  (34), the CV estimator (33) attains a variance reduction.

*Proof.* Note that the variance without using CV is

$$\operatorname{Var}(\hat{p}_j) = \frac{1}{n^2} \operatorname{Var}\left(\sum_{l=1}^n \mathbb{I}(Z_{jl} \le z_j)\right).$$
(38)

With CV, the variance of the estimator is

$$\operatorname{Var}(\hat{p}_{j}) = \frac{1}{n^{2}} \left( \operatorname{Var}\left( \sum_{l=1}^{n} \mathbb{I}(Z_{jl} \leq z_{j}) \right) + 2\pi_{j} \operatorname{Cov}\left( \sum_{l=1}^{n} \mathbb{I}(Z_{jl} \leq z_{j}), \sum_{l=1}^{n} \mathbb{I}(X_{jl} \leq \bar{z}_{j}) \right) + \pi_{j}^{2} \operatorname{Var}\left( \sum_{l=1}^{n} \mathbb{I}(X_{jl} \leq \bar{z}_{j}) \right) \right).$$

$$(39)$$

Plugging in the optimal  $\pi_j$  for our problem and simplifying, we have

$$\operatorname{Var}(\hat{p}_{j}) = \frac{1}{n^{2}} \operatorname{Var}\left(\sum_{l=1}^{n} \mathbb{I}(Z_{jl} \leq z_{j})\right)$$

$$- \frac{\operatorname{Cov}^{2}\left(\sum_{l=1}^{n} \mathbb{I}(Z_{jl} \leq z_{j}), \sum_{l=1}^{n} \mathbb{I}(X_{jl} \leq \bar{z}_{j})\right)}{n^{2} \operatorname{Var}\left(\sum_{l=1}^{n} \mathbb{I}(X_{jl} \leq \bar{z}_{j})\right)}.$$

$$(40)$$

We can see that the second term in RHS is non-positive, which means that the variance is reduced the most if  $\mathbb{I}(Z_{jl} \leq z_j)$  and  $\mathbb{I}(X_{jl} \leq \overline{z}_j)$  are highly correlated (either positively or negatively), which intuitively means  $X_{jl}$  provides some information about  $Z_{jl}$ . It is important to note, however, that in practice, we often use sample covariances and sample variances to compute  $\pi_j$ , so the CV estimator might not achieve this theoretical variance reduction.  $\Box$ 

#### 4. Numerical experiments

In this study, we examine the EV and electricity data obtained from Surabaya, Indonesia. The EV dataset includes 11 candidate charging stations, 31 sub-regions of the city representing demand nodes, and two vehicle types, namely motorcycles (k = 1) and cars (k = 2). Figure 2 illustrates the locations of the candidate charging stations (red nodes) and demand nodes (blue nodes), where the size of the blue nodes denotes the size of the demand at each location. This charging demand, i.e. the number of EVs of type kat each demand node i, is represented by  $w_i^k$ . The average travel time from demand node i to charging station j using vehicle  $k, d_{ij}^k$ , is amassed from Google Maps. The full capacity for each charging connector is considered as  $c_j = 1440$  minutes/day for all  $j \in J$  with 24/7 operational hours and the number of connectors installed in station  $j \in J$  is limited to  $q_j = 8$  for all  $j \in J$ , due to land availability in the candidate locations.

We estimate the disruption probability by simulating random electricity demands  $Z = [Z_j]_{\forall j \in J}$  where  $Z_j \sim q_j$ . We obtain this masked data from the local electricity company, which performed data masking and rescaling for privacy and security reasons. The masked mean and standard deviation of  $q_j$ along with demand threshold  $z_j$  are summarized in Table 2. The simulation uses this probability model to generate random demands and an electricity disruption event is triggered for the whole day at station j when  $Z_j \geq z_j$ . Hence, we have station reliability  $p_j = \mathbb{P}(Z_j \leq z_j), \forall j \in J$ . The other experiment parameters are summarized in Table 3.

We then build our model by running n simulation replications and computing the mean of the objective function values. The result is summarized

Station $\#(j)$	Mean $(\mu_j)$	Standard Deviation $(\sigma_j)$	Threshold $(z_j)$
1	28979	3622	36 224
2	11590	1440	14490
3	5795	722	7250
4	5789	715	7245
5	17387	2180	21750
6	17385	2169	21730
7	11590	1442	14475
8	11595	1435	14 481
9	5797	720	7246
10	5785	731	7241
11	11600	1450	14500

Table 2: The mean and standard deviation of the masked cumulative electricity demand probability  $q_j = N(\mu_j, \sigma_j^2)$  and its threshold  $z_j, \forall j \in J$ 

No	Parameter name	Symbo	ol Value	Unit
1	Station $#1$ operational + investment cost	$h_1$	4 602 739	IDR
	Station $#2$ operational + investment cost	$h_2$	1586301	IDR
	Station $#3$ operational + investment cost	$h_3$	1068493	IDR
	Station $#4$ operational + investment cost	$h_4$	1150684	IDR
	Station $#5$ operational + investment cost	$h_5$	1068493	IDR
	Station $#6$ operational + investment cost	$h_6$	1586301	IDR
	Station $#7$ operational + investment cost	$h_7$	2794520	IDR
	Station $#8$ operational + investment cost	$h_8$	1972602	IDR
	Station $#9$ operational + investment cost	$h_9$	2054794	IDR
	Station $#10$ operational + investment cost	$h_{10}$	1643835	IDR
	Station #11 operational $+$ investment cost	$h_{11}$	1643835	IDR
2	Electricity pricing rate	r	2467	IDR/kWh
3	Penalty rate for unmet demand	s	50000	IDR/minute/vehicle
4	Full-charging power need for motorcycle	$e_1$	90	kWh
	Full-charging power need for car	$e_2$	133	kWh
5	Full-charging time for motorcycle	$t_1$	20	minute
	Full-charging time for car	$t_2$	39	minute
6	Charging connector operational cost	g	479285	IDR/unit
7	Max number of alternative candidates	N	11	station
8	Max travel time threshold	$d_{max}$	35	minutes
9	Min service level threshold	$\bar{p}$	0.9	95 n/a
10	Big-M	M  99  999  999		n/a

 Table 3: Additional Model Parameters

in Fig. 4 and Fig. 5 for n up to 10,000. The selected stations and demand assignments for each model solution are shown in Fig. 6 (left: Non-Robust Model, right: Robust Model) and Fig. 7 (left: Misspecified Model #1, right: Misspecified Model #2). The Misspecified Model #1 is built assuming  $0.95p_j$ while the Misspecified Model #2 assumes  $1.05p_j$  for all  $j \in J$ , highlighting underestimation and overestimation of service reliability respectively.

The CV estimator is constructed using standard normal random variables  $X_{jl}$  with  $\bar{z}_j$  properly scaled. This gives a highly correlated random variables  $\mathbb{I}(X_{jl} \leq \bar{z}_j)$  to  $\mathbb{I}(Z_{jl} \leq z_j)$ . We show the estimated station reliability  $(p_j)$  using MC and CV in Fig. 8 and its standard error in Fig. 9 to highlight the superior estimation efficiency using the CV estimator.

#### 5. Discussion and Findings

In this section, we discuss our findings regarding the robustness of the optimal solutions against disruptions even when the probability is misspecified and the enhanced disruption simulation efficiency that allows robust decision-making for our problem against disruption uncertainties. We also highlight the limitation of the model and our outlook for future research.

#### 5.1. Robustness of the Optimal Solutions

Figure 4 summarizes the objective function values obtained by benchmarking the Robust Model, Non-Robust Model, Misspecified Model #1 (underestimated station reliability), and Misspecified Model #2 (overestimated station reliability). The optimal solution of the Robust Model (represented by orange and brown lines) outperforms the other models. Conversely, the solution of the Non-Robust Model (represented by blue and purple lines) yields



Figure 4: The summary of simulated objective function values. The thick line denotes the mean given the sample size n and the shaded area denotes the 95% confidence interval. The efficiency-enhanced simulation using CV clearly provides a much tighter confidence interval compared to MC for any sample size n.



Figure 5: The standard error of simulated objective function values over sample size n. The standard error of the CV estimates is about  $10 \times$  smaller than MC estimates, suggesting the CV's superior efficiency.



Figure 6: The optimal solutions of the Non-Robust Model (left figure) and Robust Model (right figure).



Figure 7: The optimal solutions of the Misspecified Model #1 (left figure) and Misspecified Model #2 (right figure).

the lowest objective value. The Non-Robust Model prioritizes minimizing operational and investment costs, resulting in only two charging stations being opened. This leads to lower revenue and higher penalties, particularly during disruptions. In contrast, the Robust Model balances operational and investment costs with potential revenue losses and penalties incurred during disruptions. As a result, the Robust Model opens three charging stations, distributing the large charging stations across the geography of the city, resulting in an 18% higher total cost than the Non-Robust Model solution. However, it provides better protection against revenue loss and penalties incurred during disruptions. We also suggest that these charging stations implement a smart energy management policy (Li et al., 2020) for added robustness. This added robustness leads to a 10% higher revenue and 60%lower penalty when disruptions occur, yielding an approximately 13% higher overall objective. Figure 6 shows that the Robust Model's balanced solution covers more demand points with two charging stations, resulting in a better revenue and penalty trade-off than the Non-Robust Model.



Figure 8: The estimated reliability for each of the 11 candidate charging stations using MC estimator (orange line) and CV estimator (blue line). The shaded region represents the 95% confidence interval of the estimator given sample size n. Again, clearly, CV estimates produce tighter confidence intervals, highlighting its effectiveness in enhancing the simulation efficiency, allowing terminating with fewer sample size n while achieving the same (or even better) confidence level vs MC.



Figure 9: The standard error of the estimated station reliability in Fig. 8 from MC (orange line) and CV (blue line). Overall, CV produces an estimate with  $10 \times$  higher precision, compared to MC, allowing our proposed method to handle cases when disruptions occur more rarely (e.g., in cities in a developed country).

The Robust Model with misspecified station reliability still provides some level of robustness, as evidenced by the objective values of both the underestimation and overestimation scenarios. These models' solutions have objective values lower than the Robust Model solution but higher than the Non-Robust Model solution. Thus, while accurately estimating station reliability is beneficial, the model can still tolerate imperfections. When utilizing the Robust Model with underestimated station reliability, the solution tends to be more conservative and provides a higher level of buffer against disruptions. This results in a solution with four charging stations, with over 90% of demand points covered by two or more charging stations. On the other hand, overestimating station reliability leads to a solution with only three charging stations, resulting in a lower cost and an objective value very close to the Robust Model. Figure 7 illustrates the charging station placement for both the underestimated and overestimated scenarios.

#### 5.2. Improved Simulation Efficiency using CV Estimator

We now discuss how we incorporate the simulation into our robust model. The main challenges center around incorporating electricity station reliability  $p_j, \forall j \in J$  (and thus corresponding disruption probability  $1 - p_j, \forall j \in J$ ), which might require a huge sample size to achieve desired precision level (thus increasing the computational burden of computing the objective function (either (9) or (26)) and the reliability constraints (either (18)-(19) or (27)-(28)).

While both MC and CV estimators of the objective values are unbiased and converge to the same value for each model, the proposed CV estimation approach appears to effectively reduce the estimation variance, thus yielding tighter confidence intervals in Fig. 4 (brown, silver, pink, and purple lines vs. orange, red, green, and blue lines). Furthermore, Fig. 5 highlight that all CV estimators attain about  $10 \times$  smaller standard errors compared to their MC counterparts. This means that CV improves the simulation efficiency and reduces the sample size required to attain the same precision up to a factor of 10 vs. naive MC simulation approach, without accuracy loss.

The dominant efficiency performance of the CV-based estimation technique that reduces the sample size requirement while maintaining accuracy allows us to incorporate the estimated station reliability into the objective function and reliability constraints. This results in the proposed Robust Model that can be solved without increasing the computational cost significantly. The high efficiency of the CV over MC in estimating the reliability probabilities (even to values close to 1.00) is emphasized in Fig. 8, in which all CV estimates attain much tighter confidence intervals regardless of the target probability. In this estimation, again, CV estimators attain  $10 \times$  smaller standard error for the same sample size used by MC estimators. This highlights the applicability of our robust modeling method to deal with problems where electricity disruptions are extremely rare and need to be estimated to an ultra-level precision.

#### 5.3. Limitation of the Current Work

Although our CV-assisted robust model provides optimal solutions that strike a balance between minimal cost and buffering against electricity disruptions, we acknowledge that scaling it to larger problems, such as a larger charging station candidate set and more fine-grained demand points, heavily relies on the efficiency of the MIP solver. Moreover, we acknowledge that the electricity pricing rate used in this study is simplified, whereas more recent dynamic electricity pricing schemes are available and more realistic, though highly nonlinear. Incorporating such schemes could improve the accuracy of our revenue model, but it may not be feasible with our current solver. Additionally, the CV estimation approach used in this study is based on some prior knowledge about the probability model of the random variable triggering the disruption events. In practice, such knowledge may not be easy to obtain. However, we recognize that machine learning models can be leveraged to extract features from historical datasets and estimate disruption events. We can also leverage machine learning techniques to estimate the battery capacity of the EVs (Zhao et al., 2023) to better predict the charging time for each arriving demand to extend our model to incorporate nonlinear dynamics and more realistic operations in our future work.

# 6. Conclusion

In this study, we propose a simulation-based optimization model to address the critical issue of designing robust planning for EV charging stations in developing countries, where electricity disruptions may frequently occur and impact customer satisfaction. Our model considers service reliability as a key factor and incorporates it into the objective function and constraints using the control variates (CV) variance reduction technique to improve simulation efficiency. Our numerical experiment, based on a dataset from Surabaya, Indonesia, demonstrates the superior performance of our robust model solution compared to its non-robust counterpart, even in cases of underestimated or overestimated service reliability. While our proposed model shows promise, we acknowledge its reliance on an efficient MIP solver and its use of a simplified electricity pricing rate. Furthermore, our CV estimator is based on prior knowledge of the probability model, which may not be available in practice. As such, we seek to extend our model to cover nonlinear MIP and learning-based disruption estimation in future work. Nonetheless, our model's ability to reduce the required sample size by up to  $10 \times$  compared to Monte Carlo simulations highlights its potential to provide a robust solution to the challenges associated with EV charging infrastructure under random electricity disruptions.

#### References

- Albana, A.S., Muzakki, A.R., Fauzi, M.D., 2022. The optimal location of ev charging stations at surabaya using the location set covering problem, in: 2022 International Conference on Technology and Policy in Energy and Electric Power (ICT-PEP), IEEE. pp. 95–99.
- Alhazmi, Y.A., Mostafa, H.A., Salama, M.M., 2017. Optimal allocation for electric vehicle charging stations using trip success ratio. International Journal of Electrical Power & Energy Systems 91, 101–116.
- Amilia, N., Palinrungi, Z., Vanany, I., Arief, M., 2022. Designing an optimized electric vehicle charging station infrastructure for urban area: A case study from indonesia, in: 2022 IEEE 25th International Conference on Intelligent Transportation Systems (ITSC), IEEE. pp. 2812–2817.
- Asamer, J., Reinthaler, M., Ruthmair, M., Straub, M., Puchinger, J., 2016.

Optimizing charging station locations for urban taxi providers. Transportation Research Part A: Policy and Practice 85, 233–246.

- Bi, R., Xiao, J., Pelzer, D., Ciechanowicz, D., Eckhoff, D., Knoll, A., 2017. A simulation-based heuristic for city-scale electric vehicle charging station placement, in: 2017 IEEE 20th International Conference on Intelligent Transportation Systems (ITSC), IEEE. pp. 1–7.
- Bouguerra, S., Layeb, S.B., 2019. Determining optimal deployment of electric vehicles charging stations: Case of tunis city, tunisia. Case Studies on Transport Policy 7, 628–642.
- Chen, S., Tong, L., 2012. iems for large scale charging of electric vehicles: Architecture and optimal online scheduling, in: 2012 IEEE Third International Conference on Smart Grid Communications (SmartGridComm), IEEE. pp. 629–634.
- Erbaş, M., Kabak, M., Özceylan, E., Çetinkaya, C., 2018. Optimal siting of electric vehicle charging stations: A gis-based fuzzy multi-criteria decision analysis. Energy 163, 1017–1031.
- Fachrizal, R., Shepero, M., van der Meer, D., Munkhammar, J., Widén, J., 2020. Smart charging of electric vehicles considering photovoltaic power production and electricity consumption: A review. ETransportation 4, 100056.
- Fekete, P., Lim, S., Martin, S., Kuhn, K., Wright, N., 2016. Improved energy supply for non-road electric vehicles by occasional charging station location modelling. Energy 114, 1033–1040.

- Frade, I., Ribeiro, A., Gonçalves, G., Antunes, A.P., 2011. Optimal location of charging stations for electric vehicles in a neighborhood in lisbon, portugal. Transportation Research Record 2252, 91–98.
- Fredriksson, H., Dahl, M., Holmgren, J., 2021. Optimal allocation of charging stations for electric vehicles using probabilistic route selection. Computing and informatics 40, 408–427.
- Guo, F., Inoa, E., Choi, W., Wang, J., 2012. Study on global optimization and control strategy development for a phev charging facility. IEEE transactions on vehicular technology 61, 2431–2441.
- Hamed, M.M., Kabtawi, D.M., Al-Assaf, A., Albatayneh, O., Gharaibeh, E.S., 2023. Random parameters modeling of charging-power demand for the optimal location of electric vehicle charge facilities. Journal of Cleaner Production 388, 136022.
- Harsono, N., 2020. Indonesia needs 31,000 charging stations to reach electric vehicle goals. URL: https://www.thejakartapost.com/news/2020/09/04/i ndonesia-needs-31000-charging-stations-to-reach-electric-vehicle-goals.h tml.
- He, F., Yin, Y., Wang, J., Yang, Y., 2016. Sustainability si: Optimal prices of electricity at public charging stations for plug-in electric vehicles. Networks and Spatial Economics 16, 131–154.
- Hesterberg, T.C., Nelson, B.L., 1998. Control variates for probability and quantile estimation. Management Science 44, 1295–1312.

- Hosseini, M., MirHassani, S.A., 2015. Refueling-station location problem under uncertainty. Transportation Research Part E: Logistics and Transportation Review 84, 101–116.
- Hua, G., Xu, Y., 2019. Optimal deployment of charging stations and movable charging vehicles for electric vehicles. Journal of System and Management Sciences 9, 105–116.
- Huang, K., Kanaroglou, P., Zhang, X., 2016. The design of electric vehicle charging network. Transportation Research Part D: Transport and Environment 49, 1–17.
- Huang, P., Sun, Y., 2023. Geographic information system-assisted optimal design of renewable-powered electric vehicle charging stations in highdensity cities, in: Future Urban Energy System for Buildings: The Pathway Towards Flexibility, Resilience and Optimization. Springer, pp. 383– 403.
- Hussain, A., Bui, V.H., Kim, H.M., 2020. Optimal sizing of battery energy storage system in a fast ev charging station considering power outages. IEEE Transactions on Transportation Electrification 6, 453–463.
- IEA, 2021. Global EV Outlook 2020. URL: https://www.iea.org/reports/gl obal-ev-outlook-2020.
- Jegham, M.A., Layeb, S.B., 2020. Locating and sizing electric vehicles charging stations in new markets. International Journal of Applied Decision Sciences 13, 153–182.

- Khalid, M.R., Alam, M.S., Sarwar, A., Asghar, M.J., 2019. A comprehensive review on electric vehicles charging infrastructures and their impacts on power-quality of the utility grid. ETransportation 1, 100006.
- Ko, J., Kim, D., Nam, D., Lee, T., 2017. Determining locations of charging stations for electric taxis using taxi operation data. Transportation Planning and Technology 40, 420–433.
- Kunith, A., Mendelevitch, R., Goehlich, D., 2017. Electrification of a city bus network—an optimization model for cost-effective placing of charging infrastructure and battery sizing of fast-charging electric bus systems. International Journal of Sustainable Transportation 11, 707–720.
- Lai, X., Chen, Q., Tang, X., Zhou, Y., Gao, F., Guo, Y., Bhagat, R., Zheng, Y., 2022. Critical review of life cycle assessment of lithium-ion batteries for electric vehicles: A lifespan perspective. Etransportation 12, 100169.
- Lam, A.Y., Huang, L., Silva, A., Saad, W., 2012a. A multi-layer market for vehicle-to-grid energy trading in the smart grid, in: 2012 Proceedings IEEE INFOCOM Workshops, IEEE. pp. 85–90.
- Lam, A.Y., Leung, K.C., Li, V.O., 2012b. Capacity management of vehicleto-grid system for power regulation services, in: 2012 IEEE Third International Conference on Smart Grid Communications (SmartGridComm), IEEE. pp. 442–447.
- Li, D., Zouma, A., Liao, J.T., Yang, H.T., 2020. An energy management strategy with renewable energy and energy storage system for a large electric vehicle charging station. Etransportation 6, 100076.

- Li, S., Huang, Y., Mason, S.J., 2016. A multi-period optimization model for the deployment of public electric vehicle charging stations on network. Transportation Research Part C: Emerging Technologies 65, 128–143.
- Liu, X., Liu, X., Zhang, X., Zhou, Y., Chen, J., Ma, X., 2022. Optimal location planning of electric bus charging stations with integrated photovoltaic and energy storage system. Computer-Aided Civil and Infrastructure Engineering.
- Lo Franco, F., Ricco, M., Mandrioli, R., Grandi, G., 2020. Electric vehicle aggregate power flow prediction and smart charging system for distributed renewable energy self-consumption optimization. Energies 13, 5003.
- Miljanic, Z., Radulovic, V., Lutovac, B., 2018. Efficient placement of electric vehicles charging stations using integer linear programming. Advances in Electrical & Computer Engineering 18.
- Purnama, S., Liman, U., Assegaf, F., 2021. Number of electric vehicle charging stations reaches 240. URL: https://en.antaranews.com/news/188389/ number-of-electric-vehicle-charging-stations-reaches-240.
- Ren, X., Zhang, H., Hu, R., Qiu, Y., 2019. Location of electric vehicle charging stations: A perspective using the grey decision-making model. Energy 173, 548–553.
- Simanjutak, M., 2022. Indonesia Energy. URL: https://www.trade.gov/co untry-commercial-guides/indonesia-energy.
- Sowden, H., 2022. 10 Common Causes of Power Outages (and 2 Unusual

Ones). URL: https://blog.ecoflow.com/us/common-causes-of-power-out ages/.

- Speth, D., Plötz, P., Funke, S., Vallarella, E., 2022. Public fast charging infrastructure for battery electric trucks—a model-based network for germany. Environmental Research: Infrastructure and Sustainability 2, 025004.
- Spieker, H., Hagg, A., Gaier, A., Meilinger, S., Asteroth, A., 2017. Multistage evolution of single-and multi-objective mclp: Successive placement of charging stations. Soft Computing 21, 4859–4872.
- Sun, Z., Gao, W., Li, B., Wang, L., 2020. Locating charging stations for electric vehicles. Transport Policy 98, 48–54.
- Unterluggauer, T., Rich, J., Andersen, P.B., Hashemi, S., 2022. Electric vehicle charging infrastructure planning for integrated transportation and power distribution networks: A review. ETransportation, 100163.
- Vazifeh, M.M., Zhang, H., Santi, P., Ratti, C., 2019. Optimizing the deployment of electric vehicle charging stations using pervasive mobility data. Transportation Research Part A: Policy and Practice 121, 75–91.
- Yıldız, B., Olcaytu, E., Şen, A., 2019. The urban recharging infrastructure design problem with stochastic demands and capacitated charging stations. Transportation Research Part B: Methodological 119, 22–44.
- Yuan, W., Huang, J., Zhang, Y.J.A., 2015. Competitive charging station pricing for plug-in electric vehicles. IEEE Transactions on Smart Grid 8, 627–639.

- Zhang, L., Zeng, Z., Gao, K., 2022. A bi-level optimization framework for charging station design problem considering heterogeneous charging modes. Journal of Intelligent and Connected Vehicles 5, 8–16.
- Zhang, Q., Yu, H., Zhang, G., Ma, T., 2023. Optimal planning of floodresilient electric vehicle charging stations. Computer-Aided Civil and Infrastructure Engineering 38, 489–507.
- Zhao, J., Ling, H., Liu, J., Wang, J., Burke, A.F., Lian, Y., 2023. Machine learning for predicting battery capacity for electric vehicles. ETransportation 15, 100214.