Old and New Benchmarks for Relative Termination of String Rewrite Systems

Dieter Hofbauer ⊠ ASW Saarland

Johannes Waldmann \square HTWK Leipzig

— Abstract

We provide a critical assessment of the current set of benchmarks for relative SRS termination in the Termination Problems Database (TPDB): most of the benchmarks in Waldmann_19 and ICFP_10_relative are, in fact, strictly terminating (i. e., terminating when non-strict rules are considered strict), so these benchmarks should be removed, or relabelled. To fill this gap, we enumerate small relative string rewrite systems. At present, we have complete enumerations for a 2-letter alphabet up to size 11, and for a 3-letter alphabet up to size 8. For some selected benchmarks, old and new, we discuss how to prove termination, automated or not.

2012 ACM Subject Classification Theory of computation \rightarrow Equational logic and rewriting; Theory of computation \rightarrow Rewrite systems

Keywords and phrases termination, relative termination, string rewriting

1 Introduction

A rewrite system R is terminating relative to a system S if any (infinite) rewrite sequence modulo $R \cup S$ contains only finitely many R-steps. This property is denoted by SN(R/S). The term was coined by Klop [7]. Relative termination as a generalization of standard termination is a basis for modular termination proofs due to the fact that $SN(R \cup S)$ holds if and only if both SN(R/S) and SN(S) hold. It is a research topic on its own, cf. [1, 11], and is widely used by current termination provers.

The Termination Problems Database (TPDB, see https://termination-portal.org/ wiki/TPDB) contains relative termination benchmarks since version 2.0. For string rewriting, the directory SRS_Relative of the current TPDB (versions 11.*) consists of five subdirectories:

- **ICFP_2010_relative:** 160 benchmarks, cf. [10] [VBS TC22: 132].
- Mixed_relative_SRS: 20 benchmarks [VBS TC22: 20].
- Waldmann_06_relative: 11 benchmarks [VBS TC22: 11].
- Waldmann_19: 100 benchmarks, length-preserving (alphabet size 3, left- and right-hand sides of length 3, 2 to 7 rules), randomly chosen [VBS TC22: 91].
- Zantema_06_relative: 14 benchmarks, hand-crafted [VBS TC22: 9].

The number of benchmarks solved by the *Virtual Best Solver (VBS)* in the Termination Competition 2022 (TC22) are given in square brackets, see https://termcomp.github. io/Y2022/SRS_Relative.html. "The VBS records the best (consistent) score for each claim collected at least since 2018", according to https://termination-portal.org/wiki/ Termination_Competition_2022.

The category SRS_Relative is missing an enumeration of small systems. We are starting this, and report some results and observations. The first enumeration of (strict) SRS was given by Kurth [9], and was later extended by Geser [2] and others [4]. Our ultimate goal is to cover all small relative SRSs (up to a certain size) for which termination cannot be decided

Old and New Benchmarks for Relative Termination of String Rewrite Systems

by current provers. The naive approach is to enumerate them all, and call the provers for each one. The challenge is to achieve the same result with fewer prover calls, by short-cutting the enumeration and omitting redundant cases.

There is no new theorem or method in this paper. It's just that no one has done the work before. Source code and data for the experiments reported here are available at https://gitlab.imn.htwk-leipzig.de/waldmann/pure-matchbox/-/issues/472.

2 How to win SRS_Relative, without proving Relative Termination

The approach is strikingly simple: prove (standard) termination instead for the *strictified* system, where all non-strict rules are replaced by their strict counterparts (replacing $\ell \rightarrow^{=} r$ by $\ell \rightarrow r$). This is based on the trivial observation that $SN(R \cup S)$ implies SN(R/S). Surprisingly, this works for at least 210 (out of 305) benchmarks in SRS_Relative, in comparison to the winner of TC22, MultumNonMulta (MnM), with 203 YES and 8 NO answers.

What if the answer to the question about termination of the strictified system $R \cup S$ is NO? In this case we can infer $\neg SN(R/S)$, provided we have a proof of SN(S). This is in fact the method we recommend for proving SN(R/S): if SN(S), then prove $SN(R \cup S)$ using any of the methods for standard termination that are not available for relative termination (a DP transformation followed by weakly monotone matrix interpretations, or RFC-matchbounds). Only if $\neg SN(S)$, check SN(R/S) with special methods (e. g., strictly monotone matrix interpretations).

The point is that methods for standard termination are more powerful (due to reduced monotonicity requirements, for example), and that checking SN(S) is straightforward (at least for the set of current benchmarks). A potential drawback is that we cannot re-use information from the proof, or disproof, of SN(S), to investigate $SN(R \cup S)$ or SN(R/S).

3 Relative Non-Termination via Loops

One way of proving the statement $\neg SN(R/S)$ is to exhibit a mixed looping derivation $v \rightarrow^+_{R\cup S} uvw$ that contains at least one strict *R*-step. In fact, all known non-terminating problems in SRS_Relative have been shown to be looping.

As shown by Geser and Zantema [5], loops for standard SRS can be characterized by looping forward closures. However, the corresponding statement does not hold for relative SRS: Consider the example $\{ab \rightarrow a, c \rightarrow^{=} bc\}$ from [3], which has a loop $(abc \rightarrow ac \rightarrow^{=} abc)$, but no looping forward closure. In this example, a looping forward closure can be found after reversing the system, but for the system $\{bab \rightarrow a, c \rightarrow^{=} cb, d \rightarrow^{=} bd\}$ neither the system nor its reversal has a looping forward closure, although a loop exists $(cad \rightarrow^{=2} cbabd \rightarrow cad)$.

We could use overlap closures instead, but this changes the nature of the enumeration since there is one case where we need to overlap two closures with a rule. If we want to limit ourselves to overlaps between one closure and one rule, then we can consider backward overlaps. A characterizing theorem for looping relative SRS is missing, to the best of our knowledge.

A special method for proving $\neg SN(R/S)$ is this: exhibit a derivation $v \rightarrow_S^+ uvw$ such that u or w contains an R-redex. As an example consider $R = \{a \rightarrow b\}$ and $S = \{c \rightarrow^= ac\}$, where $c \rightarrow_S^+ ac$ and a is an R-redex. This corresponds to the so-called R-emitting loops for term rewriting, used by AProVE twice in TC22.

D. Hofbauer and J. Waldmann

4 Experiments and Results

We did an optimized enumeration and called the prover matchbox on each relative SRS that was produced, using a simple strategy that contains weights (from GLPK), matrix interpretations of dimension 2 to 9 (with binary bitblasting for bit widths from 4 down to 1), full tiling for width 2, 3, 4 (possibly repeated), and closure enumeration, using parallel computation on up to 8 cores. Some unsolved problems will be submitted to TPDB.

4.1 Results for 2-letter alphabets

All SRS up to size 9 could be solved. Here, the size of a system is the sum of the sizes of its rules, and the size of a rule is the sum of the lengths of its left- and right hand sides. The empty string is denoted by ϵ . Unsolved for size 10 are

 $= \{aa \to \epsilon, abb \to = abbba\} \qquad = \{aabba \to baab, \epsilon \to = a\}$

4.2 Results for 3-letter alphabets

All SRS up to size 6 could be solved. Unsolved for size 7:

{ac → c, ε →⁼ ab, ab →⁼ ε} = {ac → c, ε →⁼ ab, ba →⁼ ε}
Unsolved for size 8: 24 systems, some of them looking vaguely similar, e. g.,
{ac → c, ε →⁼ ab, aab →⁼ ε},
but also some that don't, like

 $= \{ab \to \epsilon, \epsilon \to acb, acb \to \epsilon\}.$

5 Two Examples from the Enumeration

In this section, we give hand-crafted termination proofs for two samples from the enumeration.

5.1 Example $\{ac \rightarrow c, \epsilon \rightarrow^{=} ab, ab \rightarrow^{=} \epsilon\}$

The following interpretation M is a model for this system:

 $\epsilon_M = 0$ $a_M(y) = \max(0, y - 1)$ $b_M(y) = y + 1$ $c_M(y) = 0$

Here, a string $w \in \{a, b\}^*$ gets value 0 iff $w \to^* a^n$ via the relative rules alone; the number n in that normal form gives the number of rewrite steps starting from wc. We compute n as the first component of the monotone interpretation I on domain \mathbb{N}^2 (the second component being M), ordered by $(x_1, y_1) > (x_2, y_2)$ iff $x_1 > x_2 \land y_1 = y_2$:

 $\epsilon_I = (0,0)$ $a_I(x,y) = \text{if } y > 0 \text{ then } (x,y-1) \text{ else } (x+1,0)$ $b_I(x,y) = (x,y+1)$ $c_I(x,y) = (x,0)$

Old and New Benchmarks for Relative Termination of String Rewrite Systems

Proof of Monotonicity, for $(x_1, y) > (x_2, y)$:

4

$$\begin{aligned} a_I(x_1, y) &= & \text{if } y > 0 \text{ then } (x_1, y - 1) \text{ else } (x_1 + 1, 0) \\ &> & \text{if } y > 0 \text{ then } (x_2, y - 1) \text{ else } (x_2 + 1, 0) \\ &= & a_I(x_2, y) \end{aligned}$$

Proof of Compatibility, again for $(x_1, y) > (x_2, y)$:

$$ac_I(x,y) = a_I(x,0) = (x+1,0) > (x,0) = c_I(x,y)$$

 $ab_I(x,y) = a_I(x,y+1) = (x,y)$

5.2 Example $\{ac \rightarrow c, \epsilon \rightarrow = ab, ba \rightarrow = \epsilon\}$

We want to use the same interpretation as in previous example, but its second component is no longer a model, since $ba_I(x,0) = b_I(x+1,0) = (x+1,1) \neq (x,0) = \epsilon_I(x,0)$. The proof succeeds by keeping the interpretation and using different orders:

$$(x_1, y_1) > (x_2, y_2) \quad \text{iff} \quad (x_1 > x_2) \land (y_1 \ge y_2) \land (x_1 - y_1 > x_2 - y_2) \\ (x_1, y_1) \ge (x_2, y_2) \quad \text{iff} \quad (x_1 \ge x_2) \land (y_1 \ge y_2) \land (x_1 - y_1 \ge x_2 - y_2)$$

6 Some SRS from Zantema_06_relative

We assume that these 13 systems were hand-crafted to be "obviously terminating", but outside of the range of (then) current methods of automation. Four of these benchmarks remain unsolved in the termination competition so far: rel03, rel07, rel11, and rel12. Meanwhile, we have automated proofs for rel11 and rel12, obtained by brute-forced matrix interpretations [6, 8]. The following remain open:

$$\{ac \to cca, c \to^{=} baab, baab \to^{=} c\} (relO3)$$
$$\{ad \to db, a \to bbb, d \to \epsilon, a \to \epsilon, bc \to cdd, ac \to bbcd, bdb \to^{=} ad, ad \to^{=} bdb\} (relO7).$$

6.1 rel11: $\{bpb \rightarrow bapb, p \rightarrow^{=} apa, apaa \rightarrow^{=} p\}$

The following arctic-below-zero matrix interpretation of dimension 4 proves termination. Here, - stands for $-\infty$:

$$a \mapsto \begin{pmatrix} 0 & - & - & - \\ - & -1 & - & - \\ - & - & 1 & - \\ - & - & - & 0 \end{pmatrix} \qquad b \mapsto \begin{pmatrix} 0 & 0 & - & - \\ 1 & 1 & - & 1 \\ 0 & 1 & - & 1 \\ - & 0 & - & 0 \end{pmatrix} \qquad p \mapsto \begin{pmatrix} 0 & - & - & 0 \\ - & - & 1 & - \\ - & - & - & - \\ - & - & - & 0 \end{pmatrix}$$

6.2 rel12: $\{bpb \rightarrow abapba, p \rightarrow^{=} apa, apa \rightarrow^{=} p\}$

A termination proof can be obtained by a natural matrix interpretation of dimension 5:

$$a \mapsto \begin{pmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{pmatrix} \qquad b \mapsto \begin{pmatrix} 1 & 1 & 0 & 0 & 0 \\ 0 & 1 & 4 & 0 & 1 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{pmatrix} \qquad p \mapsto \begin{pmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{pmatrix}$$

D. Hofbauer and J. Waldmann

7 Conclusion

With this contribution, we provide some small hard benchmarks for relative termination of string rewriting, to encourage the search for more powerful proof methods and their automation.

— References -

- 1 Alfons Geser. *Relative Termination*. Dissertation, Universität Passau, Germany, 1990. URL: http://vts.uni-ulm.de/docs/2012/8146/vts_8146_11884.pdf.
- 2 Alfons Geser. Is Termination Decidable for String Rewriting With only One Rule. Habilitationsschrift, Universität Tübingen, 2001.
- 3 Alfons Geser, Dieter Hofbauer, and Johannes Waldmann. Sparse tiling through overlap closures for termination of string rewriting. In Herman Geuvers, editor, 4th Intl. Conference on Formal Structures for Computation and Deduction, FSCD 2019, June 24-30, 2019, Dortmund, Germany, volume 131 of LIPIcs, pages 21:1–21:21. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2019. doi:10.4230/LIPIcs.FSCD.2019.21.
- 4 Alfons Geser, Johannes Waldmann, and Mario Wenzel. Symbolic enumeration of one-rule string rewriting systems. In A. Middeldorp and R. Thiemann, editors, *Proc. 15th Intl. Workshop on Termination, WST-16*, pages 8:1–8:5, Obergurgl, Austria, 2016.
- 5 Alfons Geser and Hans Zantema. Non-looping string rewriting. ITA, 33(3):279–302, 1999. doi:10.1051/ita:1999118.
- 6 Dieter Hofbauer and Johannes Waldmann. Termination of string rewriting with matrix interpretations. In F. Pfenning, editor, Term Rewriting and Applications, 17th Intl. Conference, RTA 2006, Seattle, WA, USA, August 12-14, 2006, Proceedings, volume 4098 of Lecture Notes in Computer Science, pages 328–342. Springer, 2006. doi:10.1007/11805618_25.
- 7 Jan Willem Klop. Term rewriting systems: A tutorial. *Bull. EATCS*, 32:143–183, 1987.
- 8 Adam Koprowski and Johannes Waldmann. Arctic termination ... below zero. In A. Voronkov, editor, Rewriting Techniques and Applications, 19th Intl. Conference, RTA 2008, Hagenberg, Austria, July 15-17, 2008, Proceedings, volume 5117 of Lecture Notes in Computer Science, pages 202–216. Springer, 2008. doi:10.1007/978-3-540-70590-1_14.
- 9 Winfried Kurth. Termination und Konfluenz von Semi-Thue-Systemen mit nur einer Regel. Dissertation, Technische Universität Clausthal, 1990.
- 10 Johannes Waldmann and Bertram Felgenhauer. ICFP Programming Contest 2010 International Cars and Fuels Production. Talk at Intl. Conf. Functional Programming, Baltimore, Maryland, USA, 2010. https://www.imn.htwk-leipzig.de/~waldmann/talk/10/ icfp/slides.pdf.
- 11 Hans Zantema. Relative termination in term rewriting. In M. Codish and A. Middeldorp, editors, Proc. 7th Intl. Workshop on Termination, WST 2004, Aachen, Germany, 2004, Aachener Informatik Berichte AIB-2004-07, pages 51–54, 2004.