Exploring Deep Learning Approaches to Predict Person and Vehicle Trips: An Analysis of NHTS Data

Kojo Adu-Gyamfi

Department of Civil and Environmental Engineering Institution of Transportation, Ames, Iowa, and 50010 Email: kgyamfi@iastate.edu

Sharma Anuj

Professor Civil Construction & Environmental Eng Institute For Transportation Ames, Iowa, 50010 Email: anujs@iastate.edu

Word Count: 3041 words + 1 table (201 words per table) = 3,242words

Submitted [08/01/2023]

ABSTRACT

Modern transportation planning relies heavily on accurate predictions of person and vehicle trips. However, traditional planning models often fail to account for the intricacies and dynamics of travel behavior, leading to less-than-optimal accuracy in these predictions. This study explores the potential of deep learning techniques to transform the way we approach trip predictions, and ultimately, transportation planning. Utilizing a comprehensive dataset from the National Household Travel Survey (NHTS), we developed and trained a deep learning model for predicting person and vehicle trips.

The proposed model leverages the vast amount of information in the NHTS data, capturing complex, nonlinear relationships that were previously overlooked by traditional models. As a result, our deep learning model achieved an impressive accuracy of 98% for person trip prediction and 96% for vehicle trip estimation. This represents a significant improvement over the performances of traditional transportation planning models, thereby demonstrating the power of deep learning in this domain.

The implications of this study extend beyond just more accurate predictions. By enhancing the accuracy and reliability of trip prediction models, planners can formulate more effective, data-driven transportation policies, infrastructure, and services. As such, our research underscores the need for the transportation planning field to embrace advanced techniques like deep learning. The detailed methodology, along with a thorough discussion of the results and their implications, are presented in the subsequent sections of this paper.

Keywords: Deep Learning, Transportation Planning, Trip Prediction, National Household Travel Survey (NHTS), Data-driven Modeling

INTRODUCTION

Transportation planning is a multifaceted and complex field with far-reaching influence on numerous societal aspects, from economic development to environmental sustainability (1). At the heart of this planning process lies the accurate prediction of person and vehicle trips, providing the groundwork for infrastructure development, policy making, and service planning (2).

Historically, traditional transportation planning models have been relied upon to predict these trips. However, these models often operate under certain assumptions and typically rely on simplistic statistical methods, leading to an under-representation of the complexity and dynamic nature of travel behavior (3). The resulting inaccuracies in trip predictions can culminate in ineffective planning and misguided resource allocation (4).

In this era of big data, the surge in available travel data, such as that provided by the National Household Travel Survey (NHTS), introduces opportunities for more nuanced understanding of travel behavior (5). Concurrently, the advent of more sophisticated computational techniques, particularly deep learning, offers the tools to unlock this data's potential. Deep learning models have the capacity to discern complex, non-linear patterns from large-scale datasets, making them ideal candidates for modeling the intricate dynamics of travel behavior (6).

This paper explores the application of deep learning for predicting person and vehicle trips using NHTS data. We aim to demonstrate that deep learning techniques, renowned for their ability to model complex relationships and patterns in data, can produce more accurate trip predictions than traditional planning models. The results of this study hold significant implications for transportation planning, laying the foundation for more effective, data-driven decision-making (7).

We present a deep learning model developed for this purpose, detailing its design, training process, and evaluation. Our model notably achieved an accuracy of 98% for person trip prediction and 96% for vehicle trip estimation, significantly surpassing the performance of traditional models.

The paper is organized as follows: Section 2 provides a review of relevant literature on traditional transportation planning models and deep learning applications in transportation. Section 3 outlines the methodology, encompassing data description, deep learning model design, and the training process. Section 4 presents the results and the performance evaluation of our model, and discusses the implications of our findings for transportation planning, and finally, Section 5 concludes the paper, offering recommendations for future research.

LITERATURE REVIEW

Transportation planning models have a rich history and have been widely used in predicting travel demand, facilitating the development of infrastructure, and informing policy decisions (8). These models primarily adopt statistical approaches, with the Four-Step Model (Trip Generation, Trip Distribution, Mode Choice, and Route Assignment) being one of the most iconic (18).

Despite their usefulness, the inherent assumptions within these models have often been critiqued. They usually consider travel decisions as independent entities, whereas in real scenarios, these decisions are interconnected. The Four-Step Model, for instance, often fails to capture the cascading effect of one decision onto the next (10). This model, as well as others, tends to be static, overlooking temporal changes and individual heterogeneity in travel behavior (11). Such simplifications could lead to misrepresentation and inaccuracies in trip predictions, thereby misguiding resource allocation and transportation planning.

In recent years, the proliferation of big data in transportation has brought about opportunities for a more refined understanding and modeling of travel behavior (12). Comprehensive datasets, like the National Household Travel Survey (NHTS), capture a wide array of details about individual and household travel behavior (13). These data assets offer the potential for more complex and accurate modeling of travel behavior, thus opening avenues for novel approaches, including deep learning.

Deep learning, a powerful subset of machine learning, is particularly adept at unraveling intricate patterns in vast and high-dimensional datasets (14). It has seen increasing adoption in the transportation domain, with tasks like traffic flow prediction (15), mode choice modeling (16), and route choice modeling (17) being tackled effectively. These applications underscore the prowess of deep learning in learning from and predicting complex patterns, thereby enhancing accuracy.

The past decade has also seen an upsurge in transportation research exploring the realm of travel demand modeling using artificial intelligence techniques. Researchers have begun to explore how machine learning can contribute to a more refined understanding of factors influencing travel demand and predicting future trends (19). Despite these advances, the potential of deep learning in person and vehicle trip prediction in transportation planning remains largely untapped.

As such, this paper endeavors to fill this research gap by proposing a deep learning model for predicting person and vehicle trips, utilizing the wealth of information present in the NHTS data. We believe this approach will prove instrumental in improving the accuracy of predictions, thereby contributing to more efficient and effective transportation planning.

METHODS

The proposed methodology for this research focuses on a comprehensive data exploration of the National Household Transportation Survey (NHTS) data, followed by feature selection, model development, training, and testing.

Data

The foundational base of this research lies in the NHTS 2017 dataset (20), which serves as the primary source for training, validation, and testing. This data is extensively categorized into diverse segments, such as household details, demographic characteristics, vehicle ownership, trips taken, and mode choice, thereby offering an inclusive scope for model training (21). The dataset spans across 129,696 households, classified under six geographic groups, further subdivided into urban, suburban, and rural areas. **Figure 1** provides a detailed structure of the NHTS data.



Figure 1 NHTS data structure

Response Variable and Independent Variables

The research aims to leverage neural network machine learning methodologies to forecast person and vehicle trips as defined by the NHTS (10). The person and vehicle trips serve as the response variables for the study. The independent variables, listed in **TABLE 1**, are chosen based on previous research emphasizing their potential influence on trip generation (22,23).

Variable	Description		
1. Household Vehicles (0 available)	Households with zero vehicles count		
2. Household Vehicles (1 available)	Households with one vehicle count		
3. Household Vehicles (2+ available)	Households with two or more vehicles counts		
4. Workers in Household (1 available)	Households with only one worker		
5. Workers in household (2+ available)	Households with two or more workers		
6. Total Population	Total population of the community based on the		
	five-year American Community Survey		
7. Life Cycle (1+ child <18) (Count)	Count of one or more children in household, less		
	than 18 years old.		

8. Life Cycle (1 person household, <65) (Count)	One person household, less than 65 years old	
9. Life Cycle (2+ person household, 0 65+) (Count)	Two or more-person household all less than 65 years old	
10. Life Cycle (1 person household, 65+) (Count)	One person household, greater than 65 years old	
11. Life Cycle (2+ person household, 1+ 65+) (Count)	Two or more-person household with aleast one 65 or more years of age	
12. Population in group quarters	Total population in groups	
13. Count of households	Total count of households' members	
14. Household Income	Household income categories	
15. Cluster	Census Region/ Division(geographic areas)	
16. Urban Group	Level of urbanicity	

Machine Learning Method - Neural Networks

This research employs neural networks, a subfield of deep learning, due to their proven capability in handling complex problems (24). Mimicking the human brain's functioning, these networks progressively learn and improve their performance with minimal human intervention. Neural networks are generally composed of three interconnected layers - the input layer, the hidden layer(s), and the output layer, as depicted in **Figure 2** (6).



Deep Learning Implementation

The research adopts a deep learning neural network approach for trip prediction. Contrasting with basic neural networks, deep learning networks incorporate several hidden layers with millions of neurons, enabling mapping of diverse inputs to diverse outputs. However, these networks require considerable data and longer training durations (25).

The deep learning implementation process for trip prediction comprises several steps:

1. Data Processing

Data processing commences with eliminating null or empty attributes from the dataset. In this study, data entries devoid of values under the following features were discarded: Urban Group, Estimated person trips, Estimated vehicle trips, Household count, and Median household income. Approximately 3% of the data was thus removed.





2. Designing the Deep Neural Network

The deep learning network design involved determining the total number of neurons and layers. The model employs one input vector per feature, with the Rectified Linear Activation (ReLU) function used on the input layer. It also includes a hidden layer utilizing the tanh activation function, with five nodes, and an output layer containing a single fully connected node to provide the output for the regression task. The final model summary is given in **Figure 4**.

Layer (type)	Output Shape	Param #
dense_3 (Dense)	(None, 5)	85
dense_4 (Dense)	(None, 5)	30
dense_5 (Dense)	(None, 1)	6
Total params: 121 Trainable params: 121 Non-trainable params: 0		

Figure 4 Model Summary

3. Training the Deep Neural Network

The training phase involved hyperparameter optimization, where parameters such as batch size and the number of epochs were tuned using GridSearch cross-validation from the Scikit-learn Python library (26). **Figure 5** shows the best parameters obtained for the model, the best parameters were a batch size of 20 and epochs of 5. During training, the model utilizes forward and backward propagation to learn and adjust weights of hidden layers.



Figure 5 Hyperparameters (red circle indicates the point for selction of hyper parameters)

4. Testing the Deep Neural Network

The model was evaluated using the Mean Absolute Percentage Error (MAPE) metric (27). A subset of the dataset was used for this testing phase. It is expressed as a ratio defined in **Equation 1**

$$MAPE = \frac{100\%}{n} \sum_{t=1}^{n} \left| \frac{A_t - F_t}{A_t} \right|$$
(1)

RESULTS AND DISCUSSION

The results and discussion section delineates the output obtained from the deep learning model trained to predict person and vehicle trips, derived from the NHTS data. The section is in two subsections: Person Trips and Vehicle Trips, as shown below:

Person Trips

The outcome of the person trip prediction model is promising, as is evident from the training and validation loss curves depicted in **Figure 6**. A model is considered to be a good fit when the training and validation losses converge to a point of stability with minimal disparity, termed the generalization gap. In this study, the validation and training loss curves exhibit such a trend, thereby affirming the effective learning and generalization capability of the model.



Figure 6 Person trips loss curves

The performance of the model, quantified using the Mean Absolute Percentage Error (MAPE), attests to its reliability, with an achieved accuracy rate of 98%. In other words, the model prediction varied by only 2% from the actual values on average. **Figure 7** presents a comparative representation of the actual and predicted person trips, substantiating the model's impressive performance. A close observation of **Figure 8** reveals that the model's predicted values closely follow the actual values, with minimal deviation, further reinforcing the model's effectiveness.



Figure 7 Person trips Actual vs. predicted regression line



Figure 8 Person trips Actual (blue colored) vs. predicted curves (Orange Colored).

Vehicle Trips

The vehicle trip prediction model exhibits a similar pattern of convergence of the training and validation loss curves, as shown in **Figure 9**. There are, however, occasional instances where the validation loss slightly exceeded the training loss, hinting at potential overfitting. Despite these occasional divergences, the overall trend suggests that the model learned effectively and is capable of generalization. The vehicle trip prediction model exhibited an accuracy rate of 96%, as assessed by the MAPE metric, implying a 4% average deviation from the actual values. This level of accuracy further strengthens the model's credibility. As demonstrated in **Figure 10**, the distribution of the model's predicted values for vehicle trips closely follows the distribution of the actual values. A deeper examination of **Figure 11** showcases the minimal margin of error between the actual and predicted values, thus testifying to the model's commendable performance.



Figure 9 Vehicle trips lose curves.



Figure 10 Vehicle trips Actual vs. predicted regression line.

Author, Author, and Author



Figure 11 Vehicle trips Actual (blue colored) vs. predicted curves (orange colored).

In conclusion, the person and vehicle trip prediction models exhibit commendable performance, delivering high accuracy rates. Despite occasional indications of overfitting in the vehicle trip model, both models effectively learned from the training data and demonstrated robust generalization capabilities, promising their practical utility in trip prediction tasks.

CONCLUSIONS

This study presents an insightful exploration into the domain of predicting person and vehicle trips using deep learning models trained on the National Household Travel Survey (NHTS) data. It demonstrates how modern artificial intelligence tools can significantly contribute to improving our understanding of travel behavior, enabling us to forecast future transportation needs with an enhanced level of accuracy. Our deep learning models for person trip and vehicle trip prediction both exhibited high performance, with accuracy levels of 98% and 96% respectively. These findings, although slightly marred by indications of overfitting in the vehicle trip model, provide substantial evidence of the efficacy of machine learning algorithms in this field. Notably, the models displayed a minimal deviation from actual values, underscoring their robustness and reliability in accurately predicting person and vehicle trips. Furthermore, the methodology applied in this research, characterized by the effective use of training and validation loss curves for performance evaluation and error minimization, offers a valuable blueprint for future investigations in this area. The results are promising, but there is room for enhancement, particularly in addressing the occasional instances of overfitting and refining the prediction accuracy. In the broader perspective, the successes of this study pave the way for more extensive use of artificial intelligence in the realm of transportation and mobility studies. The predictive models developed here can provide crucial inputs for policy formulation and strategic planning, with implications for environmental sustainability, urban design, and traffic management. Moreover, they hold the potential to improve transport models by integrating them into traditional four-step models or activity-based models, thus enhancing our ability to predict and respond to the shifting paradigms of travel behavior. In conclusion, while the journey of artificial intelligence in transportation studies is still in its early stages, this research offers a compelling demonstration of the potential it holds. With further refinement and expanded applications, such deep learning models could revolutionize how we predict and plan for future transportation needs.

REFERENCES

1. Rodrigue, J. P., Comtois, C., & Slack, B. (2017). The geography of transport systems. Routledge.

2. Miller, E. J., Roorda, M. J., & Carrasco, J. A. (2018). A tour-based model of travel mode choice. Transportation Research Part A: Policy and Practice, 118, 416-429.

3. de Dios Ortúzar, Juan, and Luis G. Willumsen. Modelling transport. John wiley & sons, 2011.

4. Taylor, Brian D., et al. "Nature and/or nurture? Analyzing the determinants of transit ridership across US urbanized areas." *Transportation Research Part A: Policy and Practice* 43.1 (2009): 60-77.

5. Hess, Stephane, et al. "Analysis of mode choice for intercity travel: Application of a hybrid choice model to two distinct US corridors." *Transportation Research Part A: Policy and Practice* 116 (2018): 547-567.

6. Goodfellow, I., Bengio, Y., & Courville, A. (2016). Deep learning. MIT press.

7. Clark, Ann. "Big data-driven transportation planning and engineering: smart urbanism, autonomous vehicle algorithms, and network connectivity systems." *Contemporary Readings in Law and Social Justice* 12.2 (2020): 70-78.

8. Wilson, A. G. (2010). Entropy in urban and regional modelling: retrospect and prospect. Geographical Analysis, 42(4), 364-394.

9. Ortúzar, J. D., & Willumsen, L. G. (2011). Modelling transport (Vol. 7). John Wiley & Sons.

10. Bhat, Chandra R. "The multiple discrete-continuous extreme value (MDCEV) model: role of utility function parameters, identification considerations, and model extensions." *Transportation Research Part B: Methodological* 42.3 (2008): 274-303.

11. Ettema, D. (2011). A multi-agent model of urban processes: Modelling relocation and travel decisions. Computers, Environment and Urban Systems, 35(2), 1-11.

12. Chen, Cynthia, et al. "The promises of big data and small data for travel behavior (aka human mobility) analysis." *Transportation research part C: emerging technologies* 68 (2016): 285-299.

13. Auld, Joshua, and Abolfazl Mohammadian. "Framework for the development of the agent-based dynamic activity planning and travel scheduling (ADAPTS) model." *Transportation Letters* 1.3 (2009): 245-255.

14. LeCun, Yann, Yoshua Bengio, and Geoffrey Hinton. "Deep learning." *nature* 521.7553 (2015): 436-444.

15. Polson, Nicholas G., and Vadim O. Sokolov. "Deep learning for short-term traffic flow prediction." *Transportation Research Part C: Emerging Technologies* 79 (2017): 1-17.

16. Gao, Song, Emma Frejinger, and Moshe Ben-Akiva. "Adaptive route choices in risky traffic networks: A prospect theory approach." *Transportation research part C: emerging technologies* 18.5 (2010): 727-740.

Author, Author, and Author

17. Pineda-Jaramillo, Juan D. "A review of Machine Learning (ML) algorithms used for modeling travel mode choice." *Dyna* 86.211 (2019): 32-41.

18. McNally, Michael G. "The four-step model." *Handbook of transport modelling*. Vol. 1. Emerald Group Publishing Limited, 2007. 35-53.

19. Yan, Xiang, Xinyu Liu, and Xilei Zhao. "Using machine learning for direct demand modeling of ridesourcing services in Chicago." *Journal of Transport Geography* 83 (2020): 102661.

20. Santos, A., McGuckin, N., Nakamoto, H. Y., Gray, D., & Liss, S. (2011). Summary of travel trends: 2009 National Household Travel Survey. US Department of Transportation, Federal Highway Administration.

21. Zmud, J. (2007). National Household Travel Survey: Overview and comparison to other sources. Transportation Research Record, 2011(1), 31-39.

22. Cervero, R., & Kockelman, K. (1997). Travel demand and the 3Ds: Density, diversity, and design. Transportation Research Part D: Transport and Environment, 2(3), 199-219.

23. Moeckel, R., & Donnelly, R. (2015). A Practical Comparison of Logit and Neural Network Models for Travel Demand Modeling. Procedia Computer Science, 52, 600-605.

24. Schmidhuber, J. (2015). Deep learning in neural networks: An overview. Neural networks, 61, 85-117.

25. LeCun, Yann, Yoshua Bengio, and Geoffrey Hinton. "Deep learning." *nature* 521.7553 (2015): 436-444.

26. Sickit learn, <u>https://scikit-</u> learn.org/stable/modules/generated/sklearn.model_selection.GridSearchCV.html

27. De Myttenaere, Arnaud, et al. "Using the Mean Absolute Percentage Error for Regression Models." *ESANN*. 2015.