Video Captioning with Aggregated Features Based on Dual Graphs and Gated Fusion

Yutao Jin, Bin Liu* and Jing Wang

Nanjing Tech University, Nanjing, China

ARTICLE INFO

Keywords: video captioning graph neural network gated fusion

ABSTRACT

The application of video captioning models aims at translating the content of videos by using accurate natural language. Due to the complex nature inbetween object interaction in the video, the comprehensive understanding of spatio-temporal relations of objects remains a challenging task. Existing methods often fail in generating sufficient feature representations of video content. In this paper, we propose a video captioning model based on dual graphs and gated fusion: we adapt two types of graphs to generate feature representations of video content and utilize gated fusion to further understand these different levels of information. Using a dual-graphs model to generate appearance features and motion features respectively can utilize the content correlation in frames to generate various features from multiple perspectives. Among them, dual-graphs reasoning can enhance the content correlation in frame sequences to generate advanced semantic features; The gated fusion, on the other hand, aggregates the information in multiple feature representations for comprehensive video content understanding. The experiments conducted on worldly used datasets MSVD and MSR-VTT demonstrate state-of-the-art performance of our proposed approach.

1. Introduction

With the continuous development of network communication technology and wide-spread application of intelligent mobile devices, a large amount of video data has been generated, which poses great challenges to video content understanding. Therefore, how to use deep learning technology to generate accurate descriptions for videos has become a hot topic. The video captioning model can convert videos into accurate natural language descriptions to reflect the content of videos as truly as possible. The video captioning model enables computers to have visual perception and semantic understanding capabilities, involving computer vision and natural language processing.

The current mainstream method for video captioning is the encoder-decoder architecture based on deep learning. Venugopalan et al. [1] use convolutional neural network to extract features from each sampled frame and use the average pooling strategy to generate an average frame feature vector representing the entire video content, which is input into LSTM (Long Short-Term Memory) to generate captions. Venugopalan et al. [2] proposed S2VT model, which utilizes LSTM to encode frame feature sequences to mine temporal information. The above methods utilize the frame level global information of videos but ignore the fine information of local object regions. In addition, simple encoding for features obtained by extractors can not explore the deeper semantic information of videos. Zhang et al. [3] consider the interaction between objects in each frame and construct an object relational graph to enhance object feature representations. The enhanced object features are combined with frame level appearance and motion features to represent

video content. Xue and Zhou [4] calculate the cosine similarity between frame features and use frame features as nodes to construct a frame similarity graph (FSG) to generate high-level frame features. At the same time, the spatiotemporal relationships between objects are calculated and object features are as nodes to construct a Spatio-Temporal Aware Graph (STAG) to generate high-level object features. The methods elaborated above extract the features of each video from multiple perspectives but these features are only directly input into the Recurrent Neural Network for the generation of captions after simple unified processing, which fails to make full use of the information of each perspective of the feature, resulting in low utilization efficiency.

This paper proposes a video captioning method based on dual graphs and gated fusion, which fully utilizes the correlation in frame-frame and frame-object to generate features with richer semantic information and aggregates different features for better understanding of the video content. Specifically, 2D CNN, 3D CNN, and Faster-RCNN are used to extract appearance features, motion features, and object features respectively. In addition, two independent BiLSTMs are used to preprocess the appearance features and motion features respectively. Then, a Graph Attention Network (GAT) is constructed based on the preprocessed frame features for the interaction information between frames and a Frame Object Relational Graph (FORG) is constructed based on the preprocessed frame features and the extracted object features for the correlation between frames and objects. Dual-graphs reasoning can generate four feature sequences with deeper semantic information. Finally, we use multiple independent attention networks to obtain enhanced features and utilize the gated fusion method to fuse these various features as the input to the language LSTM to generate captions. Our method achieved great results on two benchmarks: MSVD and MSR-VTT.

^{*}Corresponding author

[👤] nj_liubin@163.com (B. Liu)

The main contributions of this paper are as follows: (1) Separating appearance features and motion features can generate more types of feature representations in subsequent stages, which helps to understand the content of videos from multiple perspectives. (2) GAT and FORG are constructed to generate frame features with higher level semantic information, which fully explores the correlations in frame-frame and frame-object. (3) Feature representations are fused based on multi-attention and gated fusion, which integrates information from multiple perspectives. The fused feature has a more comprehensive and accurate understanding of video content, enabling the generation of high quality captions.

2. Related work

2.1. Video Captioning

In the early stage of video captioning task development, fixed templates are used to generate captions. With the development of deep learning, especially the successful application of the deep network with encoder-decoder framework in tasks such as machine translation and image captioning, the video captioning model with encoder-decoder framework based on deep learning has become the current mainstream framework [5–16].

Yao et al. [5] utilize 3D CNN to extract temporal and spatial feature information from videos and use a temporal attention mechanism to assign corresponding attention weight to each 3D CNN frame feature to generate global context feature, which is input into the decoder LSTM to generate captions. Pei et al. [6] proposed MARN model, which stores and uses the memory visual context information of each word for multiple video scenes to provide important reference for the generation of captions. Zeng et al. [7] proposed VCRN model, which clusters the visual features of all videos in the dataset. Clustering centers implicitly represent visual commonsense concept or knowledge and combine with the visual features of the source videos to generate captions. Babariya and Tamaki [8] use YOLOv3 to extract several object regions in each frame and use the object region with the highest score to generate the object feature of that frame, which is encoded together with the frame feature to obtain richer visual feature representation. Zhang and Peng [9] proposed the OA-BTG model, which encodes object regions belonging to the same object entity to extract VLAD representations in forward and backward time order. A hierarchical attention mechanism is then used to generate the spatio-temporal features that integrate all object information, which is input into the decoder to generate captions. Tan et al. [10] proposed RMN model, designing three reasoning modules: locate module, relate module, and func module, as well as a module selector, to simulate human-level reasoning.

For the different types of features obtained, most of the existing methods choose to simply fuse them, which may not make full use of the semantic information in those features. This paper uses multi-attention and gated fusion to integrate the extracted features from multiple perspectives to help generate more detailed captions.

2.2. Graph convolution neural network

Graph convolution neural network is characterized by using the correlation between node features to obtain new features with rich interaction information. In recent years, graph convolutional neural network has been successfully applied in computer vision and natural language processing tasks such as image captioning [17–19], video captioning [3, 20–24], video question answering [25, 26].

Yao et al. [19] design 11 spatial relationships between objects and construct the spatial object relational graph. Hua et al. [20] use a semantic segmentation tool to separate objects and surrounding scenes and extract relationship information between objects and surrounding scenes. An object scene relational graph is then constructed based on the extracted object-scene information and the semantic relationship between objects. Yan et al. [21] construct two kinds of object relational graphs by calculating the relative spatiotemporal position and similarity relationships between objects, as well as using object features as nodes. Xue and Zhou [22] calculate the cosine similarity between each frame feature and other frame features as edges and construct a frame similarity graph with frame features as nodes. Xiao et al. [23] use frame features as nodes and adopt a nodereduce strategy to update the graph, fusing information from multiple sequential frames into one node. Zhang et al. [3] respectively construct the partial object relational graph and the complete object relational graph based on the extracted object features. The above graphs determine the relationships between nodes in a self-defined way. Inspired by the self-attention mechanism in [27], Veličković et al. [28] utilize this technique to determine the relationship between nodes and construct a new graph convolutional neural network called graph attention network. Li et al. [29] refer to graphs that use self-attention mechanism to calculate relationship between objects as implicit object relational graphs and also refer to graphs that extract relationship between objects by customized methods as explicit object relational graphs. Li et al. [26] use graph attention network with multihead attention mechanism to obtain semantic relationships between objects and generate high-level object features.

Intuitively, visual features with deeper semantic information can be generated by combining the local information of objects with the global information of frames, which can represent the video content better. However, the above methods only focus on the interactions in object-object and frame-frame, which ignore the correlation between frames and objects. In this paper, we use FORG [24] and GAT to obtain different types of features to represent video content from multiple perspectives: FORG can obtain the correlation between frame features and object features to generate enhanced frame features containing object information; GAT is used to extract the correlation between frames to generate enhanced frame features containing the frame-frame interaction information.



Fig. 1. The overview of our proposed video captioning model with aggregated features based on dual graphs and gated fusion.

3. Methodology

The overall framework of our proposed video captioning model is shown in Fig. 1, which is divided into three parts: Input encoder, Feature enhancement based on dual graphs and Decoder.

In the input encoder, the feature extractors are used to obtain corresponding appearance features V_a , motion features V_m and object features V_o for a video frame sequence respectively. Then, two independent BiLSTMs are used to mine temporal information in appearance features and motion features. In the feature enhancement stage, four types of frame features with high-level semantic information are generated by GAT and FORG based on the correlations in frame-frame and frame-object; In the decoder, we use multi-attention and gated fusion for four types of frame features to generate the fused feature with global semantic information, which is input into the language LSTM to generate captions.

3.1. Input encoder

3.1.1. Feature extraction

For a video frame sequence $X = \{x_1, x_2, ..., x_L\}$, 2D CNN and 3D CNN are respectively used to extract appearance features $V_a = \{v_{a,1}, v_{a,2}, ..., v_{a,L}\}$ and motion features $V_m = \{v_{m,1}, v_{m,2}, ..., v_{m,L}\}$. Faster-RCNN is used to extract object features $V_o = \{v_{o,1}^1, ..., v_{o,1}^N, ..., v_{o,L}^1, ..., v_{o,L}^N\}$, where *N* denotes the number of object features in each frame. *R* object features are extracted for a video in total, where $R = L \times N$.

3.1.2. Preprocessing based on BiLSTM

Two independent BiLSTMs are used to mine temporal information in appearance and motion features to generate frame feature sequences F_a and F_m , as shown in Eq. (1) and Eq. (2).

$$F_a = BiLSTM_a(V_a) \tag{1}$$

$$F_m = BiLSTM_m(V_m) \tag{2}$$

3.2. Feature enhancement based on Dual-Graphs Reasoning

When people watch videos, they often intend to gain an overall understanding of videos, instead of a separate understanding of each frame. Therefore, it is necessary to consider the content correlation between frames for generating captions. We use dual-graphs reasoning to obtain the content correlations between frames from four perspectives: two independent GATs are respectively constructed for the appearance feature sequence and motion feature sequence to extract two types of correlations between frames; Combined with the object information in each frame, two independent FORGs are respectively constructed for the appearance feature sequence and motion feature sequence to extract two types of correlations between frames and objects. The structure of dual-graphs reasoning is shown in Fig. 2.

3.2.1. Feature enhancement based on frame-frame interaction

Most existing methods use relatively simple frame features processing methods, such as the average pooling and the temporal attention mechanism. In this paper, we use GAT to extract frame-frame correlation to construct a complete graph of frame features. The implicit relationship between frames is automatically learned and high-level frame feature sequences with rich frame-frame interaction information are generated based on GAT: Firstly, the weight $\alpha_{i,j}$ between the i_{th} frame node and the j_{th} neighbor node is calculated, as shown in Eq. (3); Then, the feature representation f_i^g of the i_{th} frame node enhanced by GAT is calculated, as shown in Eq. (4).

$$\alpha_{i,j} = \frac{\exp\left(LeakyReLU\left(a^{T}\left[W_{g}f_{i};W_{g}f_{j}\right]\right)\right)}{\sum_{k=1}^{L}\exp\left(LeakyReLU\left(a^{T}\left[W_{g}f_{i};W_{g}f_{k}\right]\right)\right)}$$
(3)



Fig. 2. Diagram for Dual-Graphs Reasoning.

$$f_i^g = \sigma\left(\sum_{j=1}^L \alpha_{i,j} W_g f_j\right) \tag{4}$$

Where $a^T \in \mathbb{R}^{2D'_v}, W_g \in \mathbb{R}^{D'_v \times D_v}$ denote learnable parameters and f_i, f_j denotes the feature representation of the i_{th} frame and the j_{th} frame. [;] represents the concatenation operation for features. F_a and F_m are enhanced by GAT to obtain new appearance feature $F_a^g = \{f_{a,i}^g\}$ and motion feature $F_m^g = \{f_{m,i}^g\}$:

$$F_a^g = GAT(F_a) \tag{5}$$

$$F_m^g = GAT\left(F_m\right) \tag{6}$$

3.2.2. Feature enhancement combined with object information

Most of the existing methods only use object features to construct a relational graph to utilize the interaction information between objects. While it is conducive to make full use of the relationship between frame features and object features for the generation of more accurate captions. Combining the local information of objects with the global information of frames can obtain more comprehensive video information. Therefore, we use FORG to mine the correlation between frames and objects. Each frame feature and the object features of the entire video are used to construct a FORG and the correlation between each frame and all objects is used to enhance the frame features, which generate high-level semantic representations of the video: the kernel function is used to calculate the correlation between a frame feature and each object feature, as shown in Eq. (7); Then the

. . .

correlation is used to calculate each enhanced frame feature f_i^f , as shown in Eq. (8).

$$F_{kernel}\left(f_{i}, v_{o}^{j}\right) = \psi\left(f_{i}\right)\phi\left(v_{o}^{j}\right)^{T}$$

$$\tag{7}$$

$$f_{i}^{f} = f_{i} + \sum_{j=1}^{R} F_{kernel}(f_{i}, v_{o}^{j}) W_{f} v_{o}^{j}$$
(8)

where ψ and ϕ both are linear layers followed by Tanh activation function. $W_f \in \mathbb{R}^{D_p \times D_o}$ denotes learnable parameters. $v_o^j \in \mathbb{R}^{D_o}$ denotes the j_{th} object feature in the video and f_i denotes the feature representation of the i_{th} frame. Combined with object features, F_a and F_m are enhanced by FORGs to obtain new appearance features F_a^f and motion feature F_m^f :

$$F_a^f = FORG(F_a, V_o) \tag{9}$$

$$F_m^f = FORG(F_m, V_o) \tag{10}$$

Where V_o represents the object features of the entire video.

3.3. Decoder

We follow the existing methods adopting the hierarchical LSTMs [3, 7, 24] as the decoder. The first level is the attention LSTM (denoted as $LSTM_A$ in Eq. (12)) and its hidden state is regarded as the primary vocabulary representation. We also introduce a multi-attention module and a gated fusion module at this level: the multi-attention module can help to generate context features and the gated fusion

module can help to aggregate context features. The second level is the language LSTM (denoted as LSTM_L in Eq. (23)), which receives the comprehensive feature with rich spatio-temporal information and the hidden state of LSTM_A . The output of LSTM_L is used to generate fine vocabulary representation.

3.3.1. Attention LSTM

The last time step hidden state h_{t-1}^L of LSTM_L, global average feature \overline{F} (Eq. (11)) and the last time step word embedding w_{t-1} are concatenated as the input of LSTM_A. The output of LSTM_A is the primary semantic information h_t^A (Eq. (12)) at the current time step.

$$\overline{F} = \frac{1}{L} \sum \left(\left[F_a; F_m \right] \right) \tag{11}$$

$$h_t^A = LSTM_A\left(\left[h_{t-1}^L; \overline{F}; w_{t-1}\right], h_{t-1}^A\right)$$
(12)

Where h_{t-1}^A denotes the last time step hidden state of LSTM_A.

3.3.2. Multi-attention module

We generate context features by using a mechanism similar to the self-attention model [24, 27], as shown in Eq. (13). The hidden state of $LSTM_A$ is expanded as the query matrix Q and the frame feature sequence is packaged as matrix K and matrix V. Then we use four independent attention networks to generate four types of context features, as shown in Eq. (14–17).

$$A(Q, K, V) = softmax\left(\frac{QK^{T}}{\sqrt{d_{k}}}\right)V$$
(13)

$$CG_t^a = A_a^g \left(H_t^A, F_a^g, F_a^g \right)$$

$$CF_a^a = A^f \left(H^A, F^f, F^f \right)$$
(14)
(14)
(15)

$$CG_t = A_m^g \left(H_t^A, F_m^g, F_m^g\right) \tag{15}$$

$$CF_t^m = A_m^f \left(H_t^A, F_m^f, F_m^f \right)$$
(17)

Where H_t^A denotes the matrix expanded by the hidden state h_t^A . CG_t^a and CG_t^m denote the context features generated by the appearance feature sequence and motion feature sequence enhanced by GAT, respectively. CF_t^a and CF_t^m denote the context features generated by the appearance feature sequence and motion feature sequence enhanced by FORG, respectively.

3.3.3. Gated fusion module

We adapt a gated fusion module [7] to hierarchically fuse the context features, which was generated by the multiattention module. Different types of context features are fused based on the hidden state of LSTM_A , as shown in Eq. (18) and Eq. (19). Two types of appearance context features and two types of motion context features respectively perform the first level fusion, as shown in Eq. (20) and Eq. (21). Then, we use the second level fusion for the generated high-level appearance context feature C_t^a and motion context feature C_t^m to generate the final context feature C_t^e , as shown in Eq. (22).

$$\lambda = \sigma \left(W_{\lambda} \left[X; Y; h_t^A \right] \right) \tag{18}$$

$$G(X,Y) = \lambda \odot f(X) + (1-\lambda) \odot f(Y)$$
(19)

$$C^a_t = G_a \left(CG^a_t, CF^a_t \right) \tag{20}$$

$$C_t^m = G_m \left(CG_t^m, CF_t^m \right) \tag{21}$$

$$C_t^e = G_e \left(C_t^a, C_t^m \right) \tag{22}$$

3.3.4. Language LSTM

The final context feature C_t^e and the hidden state of LSTM_A are concatenated as the input of LSTM_L , as shown in Eq. (23). Then the hidden state of LSTM_L is used to generate the word probability distribution p_t , as shown in Eq. (24).

$$h_t^L = LSTM_L(\left[C_t^e; h_t^A\right], h_{t-1}^L)$$
(23)

$$p_t = softmax \left(MLP(h_t^L) \right) \tag{24}$$

Where *MLP* is a two-layers perceptron with Tanh as activation function.

3.3.5. Loss function

We use cross-entropy loss to train the model:

$$L_{CE} = -\sum_{t=1}^{T} \log P_t(g_t^*)$$
⁽²⁵⁾

Where g_t^* is the ground-truth caption for a video and *T* is the length of the caption.

4. Experiments

We conduct experiments on MSVD and MSR-VTT and use BLEU-4 [30], METEOR [31], ROUGE-L [32], and CIDEr [33] as evaluation metrics.

4.1. Datasets

MSVD contains 1970 YouTube video clips. Each video clip is annotated with multiple languages. We use English annotations and each video clip has approximately 40 annotations. Following the previous work, we take 1200 video clips for training, 100 video clips for validation and 670 video clips for testing.

MSR-VTT contains 10000 video clips, divided into 20 categories. Each video clip has 20 English annotations. We split the dataset to 6513 video clips for training, 497 video clips for validation and 2990 video clips for testing.

4.2. Data Preprocessing

We follow the strategy illustrated in [10] to preprocess corpus and extract features: All captions are converted to lower case and punctuations are removed. Then, the length of each caption is fixed as 26, that is, the captions with more than 26 words are truncated and the captions with less than 26 words are padded with zeros. For MSVD, words that appear less than twice are removed and the vocabulary

Table 1

Result comparisons on MSVD and MSR-VTT. B@4 M, R, and C respectively represent BLEU-4, METROR, ROUGE-L, and CIDEr. T	The
bold numbers represent the highest value of the metrics among all methods.	

Models		M	SVD		MSRVTT					
	B@4	М	R	С	B@4	М	R	С		
OA-BTG [9]	56.9	36.2	_	90.6	41.4	28.2	_	46.9		
RMN [10]	54.6	36.5	73.4	94.4	42.5	28.4	61.6	49.6		
ORG-TRL [3]	54.3	36.4	73.9	95.2	43.6	28.8	62.1	50.9		
TGN-RGN [23]	52.6	36.3	72.7	89.6	41.1	28.6	60.8	48.8		
STAG-FSG [22]	58.6	37.1	73.0	91.5	43.3	29.0	63.5	49.5		
D-LSG [24]	60.9	37.6	75.2	100.8	44.6	28.8	62.3	51.2		
MFF-GATE [21]	56.4	37.6	73.4	93.1	43.9	30.2	62.6	50.8		
Ours	59.1	38.1	75.6	102.7	44.9	29.0	62.4	51.9		

size is set to 7351; For MSR-VTT, words that appear less than 5 times are removed and the vocabulary size is set to 9732. 26 equally-spaced frames are obtained for each video. Inception ResNetV2 (IRV2) [34] is used as 2D CNN to extract appearance features and I3D [35] is used as 3D CNN to extract motion features. Faster-RCNN [36] is used to extract 36 object features in each frame.

4.3. Training details

We use the Adam optimizer to optimize the model. The initial learning rate is set to 0.0008. The batch size and the word embedding size are set to 128 and 300 for both datasets. The size of the hidden state of $LSTM_L$ is set to 1024 and 1536 for MSVD and MSR-VTT, respectively. The feature sizes in GAT and FORG are set to 1024 for both datasets. We use layer normalization in our model to accelerate convergence. We use beam search with size 5 to generate captions during inference.

4.4. Comparison with State-of-the-Art

We compare some State-of-the-Art (SOTA) models with our proposed model. The SOTA models are divided into two categories: models that use object features but do not use graph neural network (GNN) and models that use both object features and GNN.

4.4.1. Models that use object features but do not use GNN

OA-BTG [9] uses a bidirectional temporal graph to process object features, which can well capture the spatiotemporal dynamic information of the same object entity. The model uses the object attention mechanism to aggregate the features of different object entities, which may ignore the interaction information between objects. In addition, the model also uses a bidirectional temporal graph and a temporal attention mechanism to process frame feature sequences, which takes the temporal information between frame features into account but ignore the interaction information. Object features in RMN [10] are fused with appearance features and motion features respectively, which consider the correlation between frames and objects but ignore the hidden correlation between frames.

4.4.2. Models that use both object features and GNN

ORG-TRL [3] constructs the object relational graph with GCN reasoning, which takes into account the interaction between object features but ignores the correlation between frame features; TGN-RGN [23] uses TGN to mine the interaction information between frame features and uses RGN to mine the interaction information between object features. STAG-FSG [22] uses FSG to mine the interaction information between frame features and uses STAG to mine the interaction information between object features. TGN-RGN and STAG-FSG do not consider the correlation between frame features and object features. D-LSG [24] uses latent proposal aggregation to aggregate the frame feature sequence fused with object information into several high-level feature representations. D-LSG considers the correlation between frame features and object features but ignores the correlation between frame features. MFF-GATE [21] uses a gate method to fuse appearance features and motion features and constructs Object Similarity Graph and Object G-IOU Graph to mine the interaction information between objects. The generated high-level object features and frame features are also fused based on the gate method.

The result comparisons are shown in Table 1. For MSVD, our model achieves the best performance on ME-TEOR, ROUGE-L, and CIDEr and the result on BLEU-4 is second only to D-LSG. For MSR-VTT, our model outperforms the SOTA models on BLEU-4 and CIDEr and the rest metrics also achieved comparable performance. It is crucial to have a comprehensive understanding of video content from multiple perspectives. Compared with the SOTA models, the reasons why our model achieves higher performance can be attributed to: (1) we simultaneously pay attention to the correlation in frame-frame and frame-object and extract multiple types of feature representations of video content; (2) The use of multi-attention and gated fusion can effectively utilize feature information from various perspectives.

4.5. Ablation Study

To validate the effectiveness of our model (AMS-DG-GATE), ablation studies were conducted on MSVD and

Models	Settings				MS	SVD		MSRVTT			
	AMC	AMS	DG-GATE	B@4	М	R	С	B@4	М	R	С
Baseline1	1			54.8	36.3	73.5	95.1	43.8	28.3	61.8	49.7
Baseline2		1		56.4	36.7	74.1	98.1	44.3	28.3	61.9	50.3
AMC-DG-GATE	1		1	58.0	37.6	74.2	99.9	44.8	28.8	62.1	50.1
AMS-DG-GATE		1	1	59.1	38.1	75.6	102.7	44.9	29.0	62.4	51.9

Table 2Ablation study on multiple feature representations.

Table 3

Ablation study on feature enhancement based on dual graphs.

Models	Settings			MSVD				MSRVTT			
	GAT	FORG	GATE	B@4	М	R	С	B@4	М	R	С
AMS-GAT-GATE	1		1	58.0	36.9	74.1	97.8	44.1	28.5	61.9	50.4
AMS-FORG-GATE		1	✓	58.8	37.7	74.6	100.5	44.3	28.8	62.1	50.3
AMS-DG-GATE	1	✓	\checkmark	59.1	38.1	75.6	102.7	44.9	29.0	62.4	51.9

MSR-VTT to evaluate the effect on multiple feature representations, feature enhancement based on dual graphs and gated fusion, as shown in Table 2, Table 3 and Table 4, respectively.

Each ablation model is with various settings: (1) AMC denotes the concatenation of appearance features and motion features; (2) AMS denotes the separation of appearance features and motion features; (3) DG denotes the use of both GAT and FORG for feature enhancement; (4) GAT denotes the use of only GAT for feature enhancement; (5) FORG denotes the use of only FORG for feature enhancement; (6) GATE denotes the use of the gated fusion module.

4.5.1. The effect of multiple feature representations

The result comparisons are shown in Table 2, where the Baseline1 model concatenates appearance features and motion features, while Baseline2 model separates appearance features and motion features. Baseline2 model achieves improvements on almost all of metrics for two datasets, which indicates that the separation of appearance features and motion features can achieve better results. This is because the information contained in appearance features and motion features has their own emphasis and separating them can help to fully utilize the unique semantic information in two types of frame features. AMC-DG-GATE model concatenates appearance features and motion features and then uses dual-graphs reasoning to obtain two types of feature representations. AMS-DG-GATE model separates appearance features and motion features and then obtains four types of feature representations by dual-graphs reasoning. AMS-DG-GATE model outperforms AMC-DG-GATE model on all evaluation metrics for both datasets, indicating that more types of feature representations are beneficial for mining the content information of videos and help to generate higher quality captions. The above two sets of comparisons both prove the effectiveness of multiple feature representations.

4.5.2. The effect of feature enhancement based on dual graphs

The result comparisons are shown in Table 3, where AMS-GAT-GATE model only uses GAT reasoning on frame feature and AMS-FORG-GATE model introduces object feature for FORG reasoning. With the help of local fine information of the objects, AMS-FORG-GATE model performs better than AMS-GAT-GATE model. Compared with AMS-GAT-GATE model and AMS-FORG-GATE model, AMS-DG-GATE model has significant improvement on metrics for both datasets because dual-graphs reasoning can simultaneously focus on the correlations in frame-frame and frameobject and more sufficiently represent video content than single-graph reasoning. The above comparisons indicate that the effect of feature enhancement based on dual graphs is significantly better than that based on single graph, which proves the effectiveness of the dual-graphs method.

Table 4

Ablation study on gated fusion.

Models	Settings			MSVD				MSRVTT			
	GAT	FORG	GATE	B@4	М	R	С	B@4	М	R	С
AMS-DG	1	1		59.4	37.3	74.8	97.0	44.1	28.3	62.3	48.9
AMS-DG-GATE	1	✓	✓	59.1	38.1	75.6	102.7	44.9	29.0	62.4	51.9



Baseline2: a woman is cooking AMS-DG-GATE: a person is mixing some food in a bowl GT: a person mixing food in a bowl

⁽a)



Baseline2: a person is folding a piece of paper AMS-DG-GATE: a person is folding a paper airplane GT: a person is folding a paper airplane

(c)



Baseline2: a person is making a dish AMS-DG-GATE: a person is cutting vegetables in a kitchen GT: a man cutting vegetables in kitchen





Baseline2: a man is making a dish AMS-DG-GATE: a man is cutting a piece of meat GT: a man is cutting meat

(d)

Fig. 3. The ground-truth captions and the captions generated by Baseline2 model and AMS-DG-GATE model.

4.5.3. The effect of gated fusion

The result comparison is shown in Table 4. AMS-DG model inputs the concatenation of multiple context features into LSTM_L instead of using the gated fusion module. AMS-DG-GATE model inputs the aggregated feature generated by gated fusion into LSTM_L. Compared with AMS-DG model, our AMS-DG-GATE model improves on almost all metrics for both two datasets, especially CIDEr increasing by 5.7% and 3% on MSVD and MSR-VTT respectively. This is also because the gated fusion module can make full use of context features from multiple perspectives. The above comparison indicates that the use of gated fusion has great improvement on model performance, which proves the effectiveness of gated fusion.

4.6. Qualitative Analysis

We compare the captions generated by our proposed AMS-DG-GATE model and baseline2 model with the groundtruth captions (GT), as shown in Fig. 3. It can be found that AMS-DG-GATE model can generate more accurate and detailed captions. 'a paper airplane' in example (c) and 'vegetables' in example (b) indicate that AMS-DG-GATE model can accurately recognize more detailed local object information due to the use of object feature. 'mixing some food' in example (a) and 'cutting a piece of meat' in example (d) reflect that AMS-DG-GATE model generates not only accurate words but also more detailed descriptions. 'mixing', 'cutting' and 'in a kitchen' indicate that AMS-DG-GATE model accurately focuses on motion and background information due to the interaction information captured by GAT and FORG and the comprehensive understanding of the feature representations from multiple perspectives generated by gated fusion.

5. Conclusion

This paper proposes a video captioning model based on dual graphs and gated fusion, which uses dual-graphs reasoning to generate multiple types of feature representations of video content and uses gated fusion to deeply understand these information from different perspectives. Firstly, the appearance features and motion features are respectively modeled by adopting dual-graphs reasoning to mine the correlations in frame-frame and frame-object to generate multiple types of feature representations. Then, the multiattention mechanism are utilized to generate corresponding context features and then a gated fusion mechanism is used to fuse the multiple context features hierarchically. The generated fusion feature can more comprehensively and accurately represent video content, helping to generate higher quality captions. Our proposed model has achieved state-ofthe-art performance on MSVD and MSR-VTT, proving the effectiveness of our model.

In future work, we will attempt to use different graph neural networks to handle the relationships between frame features and object features to the generate more types of feature representations. Futhermore, we will explore more efficient strategies in utilizing the miscellaneous feature representations.

CRediT authorship contribution statement

Yutao Jin: Conceptualization, Methodology, Writing – original draft. **Bin Liu:** Supervision, Conceptualization, Methodology. **Jing Wang:** Validation, Writing – review & editing.

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgement

This work was supported by National Natural Science Foundation of China under Grant 61672279.

References

- S. Venugopalan, H. Xu, J. Donahue, M. Rohrbach, R. Mooney, K. Saenko, Translating videos to natural language using deep recurrent neural networks, arXiv preprint arXiv:1412.4729 (2014).
- [2] S. Venugopalan, M. Rohrbach, J. Donahue, R. Mooney, T. Darrell, K. Saenko, Sequence to sequence-video to text, in: Proceedings of the IEEE international conference on computer vision, 2015, pp. 4534–4542.
- [3] Z. Zhang, Y. Shi, C. Yuan, B. Li, P. Wang, W. Hu, Z.-J. Zha, Object relational graph with teacher-recommended learning for video captioning, in: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, 2020, pp. 13278–13288.
- [4] P. Xue, B. Zhou, Exploring the spatio-temporal aware graph for video captioning, IET Computer Vision 16 (2022) 456–467.
- [5] L. Yao, A. Torabi, K. Cho, N. Ballas, C. Pal, H. Larochelle, A. Courville, Describing videos by exploiting temporal structure, in: Proceedings of the IEEE international conference on computer vision, 2015, pp. 4507–4515.
- [6] W. Pei, J. Zhang, X. Wang, L. Ke, X. Shen, Y.-W. Tai, Memoryattended recurrent network for video captioning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2019, pp. 8347–8356.
- [7] P. Zeng, H. Zhang, L. Gao, X. Li, J. Qian, H. T. Shen, Visual commonsense-aware representation network for video captioning, arXiv preprint arXiv:2211.09469 (2022).
- [8] R. J. Babariya, T. Tamaki, Meaning guided video captioning, in: Pattern Recognition: 5th Asian Conference, ACPR 2019, Auckland, New Zealand, November 26–29, 2019, Revised Selected Papers, Part II 5, Springer, 2020, pp. 478–488.
- [9] J. Zhang, Y. Peng, Object-aware aggregation with bidirectional temporal graph for video captioning, in: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, 2019, pp. 8327–8336.
- [10] G. Tan, D. Liu, M. Wang, Z.-J. Zha, Learning to discretely compose reasoning module networks for video captioning, arXiv preprint arXiv:2007.09049 (2020).
- [11] H. Ryu, S. Kang, H. Kang, C. D. Yoo, Semantic grouping network for video captioning, in: proceedings of the AAAI Conference on Artificial Intelligence, volume 35, 2021, pp. 2514–2522.
- [12] H. Chen, K. Lin, A. Maye, J. Li, X. Hu, A semantics-assisted video captioning model trained with scheduled sampling, Frontiers in Robotics and AI 7 (2020) 475767.
- [13] B. Wang, L. Ma, W. Zhang, W. Jiang, J. Wang, W. Liu, Controllable video captioning with pos sequence guidance based on gated fusion network, in: Proceedings of the IEEE/CVF international conference on computer vision, 2019, pp. 2641–2650.
- [14] B. Wang, L. Ma, W. Zhang, W. Liu, Reconstruction network for video captioning, in: Proceedings of the IEEE conference on computer vision and pattern recognition, 2018, pp. 7622–7631.
- [15] M. M. Rahman, T. Abedin, K. S. Prottoy, A. Moshruba, F. H. Siddiqui, Video captioning with stacked attention and semantic hard pull, PeerJ Computer Science 7 (2021) e664.
- [16] Y. Hu, Z. Chen, Z.-J. Zha, F. Wu, Hierarchical global-local temporal modeling for video captioning, in: Proceedings of the 27th ACM International Conference on Multimedia, 2019, pp. 774–783.

- [17] V. Milewski, M.-F. Moens, I. Calixto, Are scene graphs good enough to improve image captioning?, arXiv preprint arXiv:2009.12313 (2020).
- [18] Y. Zhong, L. Wang, J. Chen, D. Yu, Y. Li, Comprehensive image captioning via scene graph decomposition, in: Computer Vision– ECCV 2020: 16th European Conference, Glasgow, UK, August 23– 28, 2020, Proceedings, Part XIV 16, Springer, 2020, pp. 211–229.
- [19] T. Yao, Y. Pan, Y. Li, T. Mei, Exploring visual relationship for image captioning, in: Proceedings of the European conference on computer vision (ECCV), 2018, pp. 684–699.
- [20] X. Hua, X. Wang, T. Rui, F. Shao, D. Wang, Adversarial reinforcement learning with object-scene relational graph for video captioning, IEEE Transactions on Image Processing 31 (2022) 2004–2016.
- [21] Z. Yan, Y. Chen, J. Song, J. Zhu, Multimodal feature fusion based on object relation for video captioning, CAAI Transactions on Intelligence Technology 8 (2023) 247–259.
- [22] P. Xue, B. Zhou, Exploring the spatio-temporal aware graph for video captioning, IET Computer Vision 16 (2022) 456–467.
- [23] X. Xiao, Y. Zhang, R. Feng, T. Zhang, S. Gao, W. Fan, Video captioning with temporal and region graph convolution network, in: 2020 IEEE International Conference on Multimedia and Expo (ICME), IEEE, 2020, pp. 1–6.
- [24] Y. Bai, J. Wang, Y. Long, B. Hu, Y. Song, M. Pagnucco, Y. Guan, Discriminative latent semantic graph for video captioning, in: Proceedings of the 29th ACM International Conference on Multimedia, 2021, pp. 3556–3564.
- [25] J. Jiang, Z. Liu, N. Zheng, Livlr: A lightweight visual-linguistic reasoning framework for video question answering, IEEE Transactions on Multimedia (2022).
- [26] F. Li, T. Bai, C. Cao, Z. Liu, C. Yan, B. Wu, Relation-aware hierarchical attention framework for video question answering, in: Proceedings of the 2021 International Conference on Multimedia Retrieval, 2021, pp. 164–172.
- [27] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, I. Polosukhin, Attention is all you need, Advances in neural information processing systems 30 (2017).
- [28] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Lio, Y. Bengio, Graph attention networks, arXiv preprint arXiv:1710.10903 (2017).
- [29] L. Li, Z. Gan, Y. Cheng, J. Liu, Relation-aware graph attention network for visual question answering, in: Proceedings of the IEEE/CVF international conference on computer vision, 2019, pp. 10313–10322.
- [30] K. Papineni, S. Roukos, T. Ward, W.-J. Zhu, Bleu: a method for automatic evaluation of machine translation, in: Proceedings of the 40th annual meeting of the Association for Computational Linguistics, 2002, pp. 311–318.
- [31] S. Banerjee, A. Lavie, Meteor: An automatic metric for mt evaluation with improved correlation with human judgments, in: Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization, 2005, pp. 65–72.
- [32] C.-Y. Lin, Rouge: A package for automatic evaluation of summaries, in: Text summarization branches out, 2004, pp. 74–81.
- [33] R. Vedantam, C. Lawrence Zitnick, D. Parikh, Cider: Consensusbased image description evaluation, in: Proceedings of the IEEE conference on computer vision and pattern recognition, 2015, pp. 4566–4575.
- [34] C. Szegedy, S. Ioffe, V. Vanhoucke, A. Alemi, Inception-v4, inception-resnet and the impact of residual connections on learning, in: Proceedings of the AAAI conference on artificial intelligence, volume 31, 2017.
- [35] J. Carreira, A. Zisserman, Quo vadis, action recognition? a new model and the kinetics dataset, in: proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2017, pp. 6299–6308.
- [36] S. Ren, K. He, R. Girshick, J. Sun, Faster r-cnn: Towards real-time object detection with region proposal networks, Advances in neural information processing systems 28 (2015).



Yutao Jin is now a post-graduate student in computer science at Nanjing Tech University. His research interests include deep learning, computer vision and natural language processing.



Bin Liu received the Ph.D. degree in management science and engineering from Southeast University, Nanjing, China. He is currently an Associate Professor with the School of Computer Science and Technology, Nanjing Tech University, Nanjing. His current research interests include deep learning and computer vision.



Jing Wang received her B.S. and M.S. degrees in electrical engineering from Nanjing Tech University, Nanjing, China, in 2007, and the Ph.D. degree in in electrical engineering from the Catholic University of America, Washington, DC, USA, in 2011. From 2007 to 2011, she was a Research Assistant with the Department of Electrical Engineering and Computer Science, the Catholic University of America. She is currently a Research Associate Professor at the Department of Electrical Engineering and Control Science, Nanjing Tech University. Her research interests include optimization theory, signal processing and communication theory in general, and wireless sensor localization in particular.