# PycWB: A User-friendly, Modular, and Python-based Framework for Gravitational Wave Unmodelled Search

Yumeng Xu<sup>a</sup>, Shubhanshu Tiwari<sup>a</sup>, Marco Drago<sup>b,c</sup>

<sup>a</sup>Physik-Institut, University of Zurich, Winterthurerstrasse 190, 8057, Zurich, Switzerland <sup>b</sup>Dipartimento di Fisica Universit di Roma "La Sapienza" Piazzale Aldo Moro 2 I-00185 Roma Italy <sup>c</sup>INFN Sezione di Roma Piazzale Aldo Moro 2 I-00185 Roma Italy

#### Abstract

Unmodelled searches and reconstruction is a critical aspect of gravitational wave data analysis, requiring sophisticated software tools for robust data analysis. This paper introduces PycWB, a user-friendly and modular Python-based framework developed to enhance such analyses based on the widely used unmodelled search and reconstruction algorithm Coherent Wave Burst (cWB). The main features include a transition from C++ scripts to YAML format for user-defined parameters, improved modularity, and a shift from complex class-encapsulated algorithms to compartmentalized modules. The PycWB architecture facilitates efficient dependency management, better error-checking, and the use of parallel computation for performance enhancement. Moreover, the use of Python harnesses its rich library of packages, facilitating post-production analysis and visualization. The PycWB framework is designed to improve the user experience and accelerate the development of unmodelled gravitational wave analysis.

# Metadata

Current code version	0.17.1
Permanent link to code / repository	git.ligo.org/yumeng.xu/pycwb
Legal Code License	GNU General Public License
Code versioning system used	git
Software languages, tools, and services used	Python, C++, Javascript, HTML
Compilation requirements and dependencies	gcc, ROOT, wheel, setuptools
Link to developer documentation / manual	<pre>yumeng.xu.docs.ligo.org/pycwb</pre>
Support email for questions	yumeng.xu@ligo.org

Table 1: Code metadata

Preprint submitted to Elsevier

August 21, 2023

#### 1. Motivation and Significance

The choice of programming language significantly influences the design and usage of scientific software. The benefits of having a Python-based software or Python interface for critical software in gravitational waves (GW) data analysis are outlined in [1, 2]. Python, as of now, is on its way to becoming the default programming language in GW data analysis. This statement can be corroborated by the emergence of Python-based gravitational waveform models like pySEOBNR[2], gwsurrogate[3], inference software like BILBY[4], PyCBC-inference[5]. And the success and wide usage of GW data analysis algorithms like PyCBC [6].

Despite these advancements, there remain several opportunities where Python-based software can accelerate the usage and development of GW data analysis algorithms. One specific example is the so-called unmodelled search and waveform reconstruction algorithms in GW data analysis. The lack of readily available Python-based open-source software restricts the development and usage of un-modelled algorithms, limiting it primarily to researchers proficient in languages like C/C++ which is a low-level programming language. Creating Python-based solutions and interfaces will enhance participation and development in the field.

The Coherent Wave Burst (cWB) algorithm has been at the forefront of advancements in GW astrophysics [7]. The range of applicability of cWB for GW transient data analysis is very wide as it is an all-sky morphology-independent algorithm i.e. it does not rely on the waveform models or the sky direction of the source. Instead cWB relies on the coherent energy produced by the GW signal in the network of detectors. cWB has played a major role in the discovery of the first detection of GW signal GW150914 [8] and more recently it has proved itself to be a crucial method to detect interesting transient GW signals that are not well modelled like GW190521 [9, 10]. cWB is routinely used in a variety of GW transient searches for the LIGO-Virgo-KAGRA collaborations like IMBH searches [11], eBBH searches [12] and generic searches for transients with short [13] and long duration [14].

While cWB offers an extensive array of functionalities and scripts, however, it falls short in facilitating user-specific modifications not inherently supported by the framework. Although cWB does provide plugin support, these plugins are required to access and manipulate global variables at the specific point of invocation. This approach demands a comprehensive understanding of the underlying code and risks unintentional disruptions or alterations to the variables. Moreover, the lack of clear dependencies between the modules further complicates the task for developers aiming to make modifications as the understanding of the interaction between different components becomes challenging. The PycWB framework addresses these issues and offers a more straightforward and stable environment for customization and code alteration.

This paper introduces PycWB, a modularized Python package for the cWB algorithm. This package will enable the easier integration of the future machine learning algorithm and new Python-based waveform models. The remainder of this paper is structured as follows: Section 2 provides an introduction to the structure and features of PycWB. Then, in Section 3, we present several use cases that demonstrate the user-friendliness and efficiency of PycWB, comparing its application with the traditional cWB. Finally, we share our conclusions and insights on the impact and potential of our new framework in the concluding section.

#### 2. Software Description

The software framework in focus is implemented in Python and leverages the coherent Wave Burst (cWB) software originally developed on ROOT [15]. The description of the core cWB algorithm and the code can be found here [16, 17]. The native pyROOT interface of ROOT has immensely facilitated this Python implementation, saving the need for rewriting the entire suite of algorithms used for cWB. Instead, the core cWB code is integrated, specifically the WAT module, which is included in the package and automatically compiled upon installation using pip. The installation process is streamlined to avoid the usually intricate cWB setup.

To install the PycWB, we provide the easiest way which is to use conda due to its dependencies on ROOT and HEALPix[18] for cWB core code

In its design, the software takes a modular approach. This way, the core cWB code is divided into different modules, providing a roadmap for future transitions, where the existing C++ codes can be replaced seamlessly with Python modules.



Figure 1: This figure shows the structure of the PycWB. The blue blocks represent the Python modules and the orange blocks represent the Python class. The green blocks show the external C/C++ code embedded in PycWB, while the yellow blocks highlight the key variables.

#### 2.1. User Configurations

The PycWB framework makes it simpler for users to set their own parameters. Instead of using C++ scripts like before, PycWB uses YAML format, a more user-friendly way that doesn't need C++ knowledge. Users or developers can easily set their own parameters using a Python dictionary. This dictionary is set up like a JSON schema, allowing flexibility in defining parameters. This system makes sure the user inputs are correct, checks them against the types and ranges that are already set, and provides default values when needed. Additionally it can automatically generate guides or instructions from this schema, keeping users updated with the software's requirements. This new approach makes it simpler for users to work with the software, manage their settings, and helps in faster development.



1	<pre>strcpy(analysis,"2G");</pre>
2	
3	nIFO = 3;
4	cfg_search = 'r';
<b>5</b>	optim=false;
6	
7	<pre>strcpy(ifo[0],"L1");</pre>
8	<pre>strcpy(ifo[1],"H1");</pre>
9	<pre>strcpy(ifo[2],"V1");</pre>
10	<pre>strcpy(refIF0,"L1");</pre>
11	
12	<pre>strcpy(channelNamesRaw[0],"L1:</pre>
	GWOSC-4KHZ_R1_STRAIN");
13	<pre>strcpy(channelNamesRaw[1],"H1:</pre>
	GWOSC-4KHZ_R1_STRAIN");
14	<pre>strcpy(channelNamesRaw[2],"V1:</pre>
	GWOSC-4KHZ_R1_STRAIN");
15	
16	<pre>strcpy(frFiles[0],"input/</pre>
	L1_frames.in");
17	<pre>strcpy(frFiles[1],"input/</pre>
	H1_frames.in");
18	<pre>strcpy(frFiles[2],"input/</pre>
	V1_frames.in");



	0 0 1
19	analysis: "2G"
20	cfg_search: "r"
$^{21}$	
$^{22}$	optim: False
23	
$^{24}$	ifo: ["L1","H1","V1"]
25	refIFO: "L1"
26	
27	channelNamesRaw: ['L1:GWOSC-4
	KHZ_R1_STRAIN', 'H1:GWOSC-4
	KHZ_R1_STRAIN', 'V1:GWOSC-4
	KHZ_R1_STRAIN']
28	<pre>frFiles: ["input/L1_frames.in",</pre>
	"input/H1_frames.in", "input
	/V1_frames.in"]

#### 2.2. Modular and Classes

The original cWB framework presented a challenging structure where class-based constructions excessively encapsulated numerous methods and key algorithms. This approach led to dense coding, which was difficult to comprehend and modify due to its high interdependencies and complexity. However, in the PycWB framework, a fundamental shift towards modularity and clarity is adopted. Essential functions are transferred to Python classes, serving as standard data formats or interfaces between different modules. Meanwhile, key algorithms have been detached from their original class environments and restructured into independent modules. This revamped architecture facilitates efficient dependency management. The necessary variables are initialized before each function call, and functions are called as pure procedures, thereby significantly enhancing the software's comprehensibility, usability, and adaptability.



Figure 2: This figure shows the modular design of PycWB. On the left, the workflow appears streamlined, but the updates on shared variables are scattered within the modules making it resemble a black box. On the right, we demonstrate our approach to modularization in PycWB. We have isolated each module to ensure it only depends on the input and subsequently delivers the output to the next steps. This architecture enhances the transparency and flexibility of the process, allowing for easier comprehension and customization.

# 2.3. Parallelization

The modularization in Python facilitates easy parallelization of various processes in PycWB, using Python's multiprocessing library. As a result, computations across layers are expedited, bringing about a speedup of 4 to 6 times in the pixel finding and clustering stage. Reading data and data conditioning also enjoy speed improvements, leading to an overall speedup of 2 to 3 times.

A further enhancement of performance by PycWB can be envisaged by the integration of GPU acceleration. With the increase in the number of GW events and data the integration of GPU acceleration will become essential for cWB algorithm. To this end PycWB interface provides a much more straightforward solution with Numba[19].

#### 2.4. Post production processing

With Python's wealth of packages for data processing, visualization, and machine learning, post-production data processing is seamless. The modular framework lets users easily select and implement the post-processing modules they need without requiring code modifications or recompilation. For instance, integrating the autoencoder neural network for glitch detection [20] into PycWB is as simple as interfacing a few lines of

TensorFlow[21] code with the framework. This ensures that advanced techniques such as machine learning can be employed efficiently and effectively without the need for extensive code modifications.



Figure 3: A selection of python packages that can be seamlessly integrated for post-production in PycWB

#### 2.5. Web interface

Similar to cWB, PycWB also provides a web interface. But the web interface in PycWB is structured as a separate module. This module contains HTML, CSS and Javascript frameworks as a web app, along with simple Python functions to copy the static webpage files to the designated output directory. As a result, there's no need for HTML webpage generation. This separation of the web interface and the Python code contributes to the modularity and usability of PycWB.

# 3. Illustrative Examples

# 3.1. Real data analysis

To validate the performance of PycWB, we conducted identical analyses on real LIGO-Virgo events GW150914[8], GW170809[22], and GW190521 [9] using both cWB and PycWB. For the cWB analysis, we used the cwb\_gwosc command to download data from GWOSC [23, 24] and process them.

```
cwb_gwosc GW=EVENT_ID IF0=V1 TAG=TSTXY all
```

For PycWB, we utilized the same user configuration file and data, executing the analysis via a simple command.

pycwb\_search user\_parameters.yaml

Table 3 outlines the events analyzed and the speed factors for both cWB and PycWB. The speed factor, calculated as the ratio of computation time to the length of the data, indicates a 2-3 times overall performance boost with PycWB. This notable increase in speed is primarily attributed to effective parallelization made very simple to implement due to the Python interface.

In addition, we highlight key parameters of the recovered events to showcase the consistency in accuracy between cWB and PycWB. Given that both platforms use the same algorithms and setups, similar accuracy levels are to be expected. Any minor deviations

Event name	cWB speed factor	PycWB speed fac- tor	relative im- provement
GW150914	10X	20.1X	2 times
GW170809	4.76X	12.8X	2.7  times
GW190521	8.5X	24.5X	2.9  times

Table 2: Performance comparison: PycWB shows 2-3 times of performance improvement due to the parallelization compared to cWB on the selected events.

could potentially be attributed to differences in data types between Python and C++. These results affirm PycWB's capabilities in maintaining the robustness of the algorithm while enhancing performance.

Event name	Software	rho[0]	likelihood	start time
GW150914	cWB PycWB	$\frac{16.70109}{16.76488}$	$634.7065 \\ 641.5996$	$\frac{1126259462.125}{1126259462.125}$
GW170809	cWB PycWB	6.045537 6.045362	$\frac{117.5504}{117.5518}$	$\frac{1186302519.6875}{1186302519.6875}$
GW190521	cWB PycWB	$\begin{array}{c} 10.13721 \\ 10.64826 \end{array}$	$215.8701 \\ 236.0143$	$\begin{array}{c} 1242442967.125\\ 1242442967.125\end{array}$

Table 3: The results obtained from the PycWB analysis are consistent with those obtained from cWB, accommodating only the differences inherent in the data types between Python and C++.

Figure 4 presents an example of an analysis conducted on GW150914 using PycWB. The left panel displays the time-frequency map of the likelihood of selected pixels, providing a visual representation of how the event's signal changes over time and frequency. The right panel illustrates the reconstructed waveform of the event.

# 3.2. Batch Injection with Python script

The PycWB framework simplifies the handling of batch injections involving large parameter sets. In cWB, injecting complex GW signals (like binary black holes populations) is achieved with cumbersome scripts which create XML files, in particular the LIGO Light-Weight (LIGOLW) XML format [25] for parameters. Moreover, one needs to modify the XML table manually when dealing with keys not predefined in the LIGOLW XML table. On the other hand, PycWB provides the option to generate an array of parameters directly through a Python function. This function returns a list of parameters, offering significant flexibility and efficiency. Recently search algorithms like PyCBC etc provide HDF5 injection file support to mitigate the issues with LIGO-LW XML file formats, these injection files can be seemlessly integrated in PycWB to have consistent injections between pipelines.



Figure 4: A selection of the plots from the PycWB analysis on GW150914, the first detected GW event. These plots were created using Matplotlib, a popular data visualization library in Python, which takes the output from the likelihood module. In comparison with C++, Python's Matplotlib requires significantly less code for plotting, demonstrating the efficiency and ease of use provided by PycWB in visualizing analysis results.

The parameters are passed directly to the waveform generator, thus allowing users to employ their own waveform generators with additional parameters, circumventing the need for any code modification within PycWB. The Python function can be constructed as demonstrated in the code snippet 3.

Listing 3: generate\_parameters.py: A simple example for batch injection script

1	<pre>def get_injection_parameters():</pre>
2	return [{
3	'mass1': 20,
4	'mass2': 20,
5	'spin1z': spin1z,
6	'spin2z': 0,
7	'distance': 200,
8	'inclination': 0,
9	'polarization': 0,
0	'gps_time': 1126259462.4,
1	'coa_phase': 0,
2	'ra': 0,
3	'dec': 0
4	} for spin1z in [0, 0.3, 0.6]]

To implement this, the parameters\_from\_python keyword can be used in place of the parameters keyword in the YAML file containing user parameters. The example shows in code snippet 4.

Listing 4: Example user parameter file for generating injection parameters from script

```
injection:
1
     segment: # ....
2
     parameters_from_python:
3
       file : "generate_parameters.py"
4
       function: "get_injection_parameters"
5
                                       8
```

```
approximant: #...
generator: #...
```

#### 3.3. Injection with third-party Python waveform models

While PycWB uses PyCBC as the default for waveform generation during injection, users may wish to utilize their own models or adopt new ones that have yet to be implemented in PyCBC. To accommodate this, PycWB features an option within its read\_data module that allows for the integration of any waveform generator. The only requirement is for the user to write a wrapper function that accepts input from their injection parameters and returns the '+' (plus) and '×' (cross) polarization. This flexible approach enables seamless integration of a diverse array of waveform models, thereby expanding the analytical capabilities of the PycWB framework.

We demonstrated this ability by running a data injection with the cutting-edge waveform model, pyseobnr. This model, only implemented in Python, utilizes the effectiveone-body method and numerical relativity (NR) calibration, serving as a testament to the framework's compatibility and flexibility.

Listing 5: Example code using the pySEOBNR waveform model for injection

```
from pyseobnr.generate_waveform import GenerateWaveform
1
2
    def waveform_generator(mass1, mass2, spin1x, spin1y, spin1z, spin2x,
3
        spin2y, spin2z, distance, inclination, polarization, coa_phase,
        f_lower, delta_t, **kwargs):
        parameters = {
4
           'mass1': mass1,
\mathbf{5}
            'mass2': mass2,
6
            'spin1x': spin1x,
7
            'spin1y': spin1y,
8
            'spin1z': spin1z,
9
            'spin2x': spin2x,
10
            'spin2y': spin2y,
11
            'spin2z': spin2z,
12
            'distance': distance,
13
            'inclination': inclination,
14
            'polarization': polarization,
15
            'coa_phase': coa_phase,
16
            'f_ref': f_lower,
17
            'f22_start': f_lower,
18
            'deltaT': delta_t,
19
            "approximant": "SEOBNRv5HM",
20
        }
21
       wfm_gen = GenerateWaveform(parameters)
^{22}
       hp, hc = wfm_gen.generate_td_polarizations_conditioned_2()
23
^{24}
       return hp, hc
25
```

To integrate a third-party waveform model that's not natively supported in PycWB, the user only needs to write a wrapper function, as demonstrated in code snippet 5.

Then, to incorporate this into a run, the user simply adds a **generator** key to the user parameter file, specifying the location and function name, as shown in code snippet 6.

Listing 6: Example for using the waveform model wrapper in user parameter file

```
    injection:
    segment: # ...
    parameters_from_python: # ...
    approximant: "SEOBNRv5HM"
    generator:
    module: "PATH_TO_THE_CODES"
    function: waveform_generator
```

# 4. Conclusions

The Coherent WaveBurst (cWB) is playing a key role in the discovery and analysis of gravitational waves. Despite its importance, the accessibility and user-friendliness of its interface have been a challenge, primarily due to the complex and highly technical nature of the C++ language it was originally written in.

In addressing this challenge, we present PycWB, a Python-based modular adaptation of the cWB. This transformation not only makes cWB more accessible to the scientific community but also unlocks the potential for numerous innovations in the field. By leveraging the power and simplicity of Python, PycWB makes complex analyses in gravitational wave research more manageable and user-friendly. The capability to use PycWB within interactive Jupyter Notebooks simplifies the learning process for new users, making it significantly more approachable. Moreover, the seamless compatibility with PyCBC and other Python-based waveform models such as pyseobnr and gwsurrogate greatly simplifies injection studies. Data post-processing is much easier. Its Python-based data output from each module makes data manipulation more intuitive. Additionally, users have the flexibility to choose the specific data they wish to save at each stage of the process.

Furthermore, the PycWB framework allows seamless integration with machine learning libraries in Python, paving the way for more sophisticated and automated analyses. This adaptability extends to developers, who can easily design new modules or add GPU-accelerated capabilities with Python packages like numba, without an in-depth understanding of the entire PycWB structure.

In conclusion, PycWB provides user-friendly, flexible, and powerful architecture, which opens new avenues for research and discovery in the realm of gravitational waves. The ease of use and adaptability of PycWB empowers both experienced researchers and new-comers alike to contribute to this exciting field of research.

# 5. Conflict of Interest

We wish to confirm that there are no known conflicts of interest associated with this publication and there has been no significant financial support for this work that could have influenced its outcome.

# Acknowledgements

We are grateful to Giovanni Andrea Prodi, Francesco Salemi, Sophie Bini, Dixeena Lopez, Michael Ebersold, Edoardo Milotti and Gabriele Vedovato for their helpful comments and encouragement throughout this project. Y. Xu is supported by China Scholarship Council. S. Tiwari is supported by the Swiss National Science Foundation (SNSF) Ambizione Grant Number: PZ00P2-202204. M. Drago acknowledges the support from the Amaldi Research Center funded by the MIUR program 'Dipartimento di Eccellenza' (CUP:B81I18001170001) and the Sapienza School for Advanced Studies (SSAS). The authors are grateful for computational resources provided by the LIGO Laboratory and supported by National Science Foundation Grants PHY-0757058 and PHY-0823459. This paper has document number LIGO-P2300267.

This research has made use of data or software obtained from the Gravitational Wave Open Science Center (gwosc.org), a service of the LIGO Scientific Collaboration, the Virgo Collaboration, and KAGRA. This material is based upon work supported by NSF's LIGO Laboratory which is a major facility fully funded by the National Science Foundation, as well as the Science and Technology Facilities Council (STFC) of the United Kingdom, the Max-Planck-Society (MPS), and the State of Niedersachsen/Germany for support of the construction of Advanced LIGO and construction and operation of the GEO600 detector. Additional support for Advanced LIGO was provided by the Australian Research Council. Virgo is funded, through the European Gravitational Observatory (EGO), by the French Centre National de Recherche Scientifique (CNRS), the Italian Istituto Nazionale di Fisica Nucleare (INFN) and the Dutch Nikhef, with contributions by institutions from Belgium, Germany, Greece, Hungary, Ireland, Japan, Monaco, Poland, Portugal, Spain. KAGRA is supported by Ministry of Education, Culture, Sports, Science and Technology (MEXT), Japan Society for the Promotion of Science (JSPS) in Japan; National Research Foundation (NRF) and Ministry of Science and ICT (MSIT) in Korea; Academia Sinica (AS) and National Science and Technology Council (NSTC) in Taiwan.

# Appendix A. Full user parameter file example

Listing 7: Run the search with python

```
###### project ######
 1
2
    outputDir: "output"
3
    nproc: 6
 4
    ###### search ######
5
 6
    analysis: "2G"
\overline{7}
    cfg_search: "r"
8
9
    optim: False
10
11
    ###### network configuration ######
12
    ifo: ["L1","H1"]
13
    refIFO: "L1"
14
^{15}
    # lags
16
    lagSize: 1
17
    lagStep: 1.
18
    lagOff: 0
19
    lagMax: 0
20
21
    # superlags
22
    slagSize: 1 # number of super lags (simulation=1) - if slagSize=0 -
^{23}
        > Standard Segments
    slagMin: 0
^{24}
    slagMax: 0
^{25}
    slagOff: 0
^{26}
27
    # job
28
    segLen: 1200
^{29}
    segMLS: 600
30
    segTHR: 200
^{31}
    segEdge: 10
^{32}
33
    # frequency
^{34}
    fLow: 16.
35
    fHigh: 1024.
36
37
38
    levelR: 3
39
    l_low: 4 # low frequency resolution level // std (sthr = 2)
40
    l_high: 10 # high frequency resolution level // std (sthr = 8)
^{41}
42
```

```
wdmXTalk: "wdmXTalk/OverlapCatalog16-1024.bin"
^{43}
44
   healpix: 7
45
46
   ###### cWB production thresholds & regulators ######
\mathbf{47}
48
   bpp: 0.001
49
   subnet: 0.5
50
   subcut: -1.0
51
   netRHO: 5.0
52
   cedRHO: 5.0
53
   netCC: 0.5
54
   Acore: 1.7
55
   Tgap: 0.2
56
   Fgap: 128.0
57
   delta: 0.5
58
   cfg_gamma: -1.0
59
   LOUD: 300
60
61
   pattern: 10
62
63
   iwindow: 100
64
65
   # simulation
66
   simulation: "all_inject_in_one_segment"
67
   nfactor: 1
68
69
    injection:
70
      segment:
71
        start: 1126258862.4
72
        end: 1126260062.4
73
        noise:
74
          seeds: [0, 1]
75
      parameters:
76
        mass1: 20
77
        mass2: 20
78
        spin1z: 0
79
        spin2z: 0
80
        distance: 500
81
        inclination: 0
82
        polarization: 0
83
        gps_time: 1126259462.4
84
        coa_phase: 0
85
        ra: 0
86
        dec: 0
87
      approximant: "IMRPhenomXHM"
88
```

# Appendix B. Example Python codes for PycWB

Listing 8: Run the search with python

```
1 from pycwb.search import search
2
3 search('./user_parameters.yaml')
```

Listing 9: Run the search with python step by step

```
1
    import os
 \mathbf{2}
    import pycwb
 3
   from pycwb.config import Config
 ^{4}
   from pycwb.modules.logger import logger_init
 \mathbf{5}
 6
    if not os.environ.get('HOME_WAT_FILTERS'):
 7
       pyburst_path = os.path.dirname(os.path.abspath(pycwb.__file__))
 8
        os.environ['HOME_WAT_FILTERS'] = f"{os.path.abspath(pyburst_path)}/
 9
            vendor"
10
    logger_init()
11
12
    config = Config('./user_parameters_injection.yaml')
13
14
    from pycwb.modules.read_data import generate_injection
15
    from pycwb.modules.job_segment import create_job_segment_from_injection
16
17
    # generate injected data for each detector with given parameters in
18
        config
19
    job_segments = create_job_segment_from_injection(config.ifo, config.
20
        simulation, config.injection)
^{21}
    data = generate_injection(config, job_segments[0])
^{22}
23
    # apply data conditioning to the data
^{24}
    from pycwb.modules.data_conditioning import data_conditioning
25
    from pycwb.modules.plot import plot_spectrogram
26
27
    strains, nRMS = data_conditioning(config, data)
^{28}
29
    # calculate coherence
30
    from pycwb.modules.coherence import coherence
31
32
   fragment_clusters = coherence(config, strains, nRMS)
33
34
    # supercluster
35
    from pycwb.modules.super_cluster import supercluster
36
   from pycwb.types.network import Network
37
38
```

```
network = Network(config, strains, nRMS)
39
    pwc_list = supercluster(config, network, fragment_clusters, strains)
40
41
    # likelihood
42
    from pycwb.modules.likelihood import likelihood
^{43}
44
    events, clusters = likelihood(config, network, pwc_list)
45
    from pycwb.modules.plot import plot_event_on_spectrogram
46
47
    # plot statistics
^{48}
49
    from gwpy.spectrogram import Spectrogram
50
51
    for cluster in clusters:
       merged_map, start, dt, df = cluster.get_sparse_map("likelihood")
52
       plt = Spectrogram(merged_map, t0=start, dt=dt, f0=0, df=df).plot()
53
       plt.colorbar()
54
55
    from gwpy.spectrogram import Spectrogram
56
57
   for cluster in clusters:
58
       merged_map, start, dt, df = cluster.get_sparse_map("null")
59
       plt = Spectrogram(merged_map, t0=start, dt=dt, f0=0, df=df).plot()
60
       plt.colorbar()
61
```

#### References

- [1] K. Wette, SoftwareX 12, 100634 (2020), arXiv:2012.09552 [astro-ph.IM] .
- [2] D. P. Mihaylov, S. Ossokine, A. Buonanno, H. Estelles, L. Pompili, M. Pürrer, and A. Ramos-Buades, (2023), arXiv:2303.18203 [gr-qc].
- [3] S. Field, C. Galley, and J. Blackman, in APS April Meeting Abstracts, APS Meeting Abstracts, Vol. 2018 (2018) p. G14.005.
- [4] G. Ashton et al., Astrophys. J. Suppl. 241, 27 (2019), arXiv:1811.02042 [astro-ph.IM].
- [5] C. M. Biwer, C. D. Capano, S. De, M. Cabero, D. A. Brown, A. H. Nitz, and V. Raymond, Publ. Astron. Soc. Pac. 131, 024503 (2019), arXiv:1807.10312 [astro-ph.IM].
- [6] S. A. Usman et al., Class. Quant. Grav. 33, 215004 (2016), arXiv:1508.02357 [gr-qc].
- [7] S. Klimenko et al., Phys. Rev. D 93, 042004 (2016), arXiv:1511.05999 [gr-qc].
- [8] B. P. Abbott et al. (LIGO Scientific, Virgo), Phys. Rev. D 93, 122003 (2016), arXiv:1602.03839 [gr-qc].
- [9] R. Abbott et al. (LIGO Scientific, Virgo), Phys. Rev. Lett. 125, 101102 (2020), arXiv:2009.01075
   [gr-qc].
- [10] M. Szczepańczyk et al., Phys. Rev. D 103, 082002 (2021), arXiv:2009.11336 [astro-ph.HE] .
- R. Abbott et al. (LIGO Scientific, VIRGO, KAGRA), Astron. Astrophys. 659, A84 (2022), arXiv:2105.15120 [astro-ph.HE].
- [12] B. P. Abbott *et al.* (LIGO Scientific, Virgo), Astrophys. J. 883, 149 (2019), arXiv:1907.09384 [astro-ph.HE].
- [13] R. Abbott et al. (KAGRA, VIRGO, LIGO Scientific), Phys. Rev. D 104, 122004 (2021), arXiv:2107.03701 [gr-qc].
- [14] R. Abbott *et al.* (KAGRA, VIRGO, LIGO Scientific), Phys. Rev. D 104, 102001 (2021), arXiv:2107.13796 [gr-qc].
- [15] R. Brun and F. Rademakers, Nucl. Instrum. Meth. A **389**, 81 (1997).
- [16] M. Drago, S. Klimenko, C. Lazzaro, E. Milotti, G. Mitselmakher, V. Necula, B. O'Brian, G. A. Prodi, F. Salemi, M. Szczepanczyk, S. Tiwari, V. Tiwari, G. V, G. Vedovato, and I. Yakushin, SoftwareX 14, 100678 (2021).

- [17] S. Klimenko, G. Vedovato, V. Necula, F. Salemi, M. Drago, R. Poulton, E. Chassande-Mottin, V. Tiwari, C. Lazzaro, B. O'Brian, M. Szczepanczyk, S. Tiwari, and V. Gayathri, "cwb pipeline library: 6.4.1," (2021).
- [18] K. M. Górski, E. Hivon, A. J. Banday, B. D. Wandelt, F. K. Hansen, M. Reinecke, and M. Bartelmann, The Astrophysical Journal 622, 759 (2005).
- [19] S. K. Lam, A. Pitrou, and S. Seibert (2015).
- [20] S. Bini, G. Vedovato, M. Drago, F. Salemi, and G. A. Prodi, Class. Quant. Grav. 40, 135008 (2023), arXiv:2303.05986 [gr-qc].
- [21] M. Abadi et al., (2016), arXiv:1603.04467 [cs.DC] .
- [22] B. P. Abbott *et al.* (LIGO Scientific, Virgo), Phys. Rev. X 9, 031040 (2019), arXiv:1811.12907 [astro-ph.HE].
- [23] R. Abbott et al. (LIGO Scientific, Virgo), SoftwareX 13, 100658 (2021), arXiv:1912.11716 [gr-qc] .
- [24] R. Abbott *et al.* (KAGRA, VIRGO, LIGO Scientific), Astrophys. J. Suppl. 267, 29 (2023), arXiv:2302.03676 [gr-qc].
- [25] The LIGO Scientific Collaboration, "LIGO Light-Weight XML I/O library for Python," (2022).