An algorithm to approximate the real trilogarithm for a real argument

Alexander Voigt

Flensburg University of Applied Sciences, Kanzleistraße 91–93, 24943 Flensburg, Germany

August 28, 2023

Abstract

We present an algorithm to approximate the real trilogarithm for a real argument with IEEE 754-1985 double precision accuracy. The approximation is structured such that it can make use of instruction-level parallelism when executed on appropriate CPUs.

1 Introduction

The trilogarithm Li₃ is a special function that appears in the calculation of loop integrals in high-energy physics, for example in two-loop self-energy integrals in the calculation of the Higgs boson pole mass or in twoloop three-point integrals in the calculation of Higgs boson decays. For this reason the trilogarithm is implemented in Feynman integral libraries such as TSIL [1] and 3vil [2] or in the CHAPLIN [3], HPOLY.f [4] and handyG [5] libraries as one basis function to numerically evaluate harmonic or generalized polylogarithms, respectively, in terms of which certain classes of Feynman integrals can be expressed. Since such loop integrals must be numerically evaluated many times in parameter studies of models beyond the Standard Model of particle physics, a time-efficient implementation of the trilogarithm is advantageous.

An often used strategy to implement a special function is to map its argument to one or more small regions on which a suitable approximant for the function can be given. This strategy is, for example, usually used to implement the real dilogarithm of a real argument: Using the known functional relations for the real dilogarithm, it is possible to map its argument to the interval [0, 1/2], where an expansion in terms of Chebyshev polynomials [6] or a rational minimax approximant [7, 8] can be used for the numerical evaluation. For a particularly time-efficient evaluation of a special function on some interval one should try to minimize the number of costly arithmetic floating-point operations, such

as division or multiplication. In addition one can try to make use of so-called instruction-level parallelism (ILP), which is the ability of modern CPUs to execute multiple independent operations at the same time. The combination of all these strategies was for example used in Ref. [8] to obtain a time-efficient implementation of the real dilogarithm for a real argument with IEEE 754-1985 double precision accuracy. In this publication we will use the strategy from Ref. [8] to construct a time-efficient algorithm for the numerical evaluation of the real trilogarithm for a real argument with IEEE 754-1985 double precision accuracy.

2 The trilogarithm

For all $z \in \mathbb{C}$ the trilogarithm Li₃ : $\mathbb{C} \to \mathbb{C}$ is defined as (see e.g. [9])

$$\operatorname{Li}_{3}(z) = \int_{0}^{z} \frac{\operatorname{Li}_{2}(t)}{t} dt, \tag{1}$$

where $\text{Li}_2:\mathbb{C}\to\mathbb{C}$ is the dilogarithm, defined as

$$\operatorname{Li}_{2}(z) = -\int_{0}^{z} \frac{\ln(1-t)}{t} dt. \tag{2}$$

For |z| < 1 the trilogarithm has the series expansion

$$\operatorname{Li}_{3}(z) = \sum_{k=1}^{\infty} \frac{z^{k}}{k^{3}}.$$
(3)

For $z \neq 0$ the following relations hold:

$$\text{Li}_3(z) = \text{Li}_3(1/z) - \ln(-z)\zeta(2) - \frac{1}{6}\ln^3(-z),$$
 (4)

$$\text{Li}_3(z) = -\text{Li}_3(1 - 1/z) - \text{Li}_3(1 - z) + \zeta(3)$$

$$+\ln(z)\zeta(2) - \frac{1}{2}\ln^2(z)\ln(1-z) + \frac{1}{6}\ln^3(z), (5)$$

where ζ is the Riemann zeta function with $\zeta(2) = \pi^2/6$. For the following considerations we define the real trilogarithm for a real argument, $\text{li}_3 : \mathbb{R} \to \mathbb{R}$, as

$$li_3(x) = \Re[Li_3(x)]. \tag{6}$$

3 Algorithm to approximate the real trilogarithm

To obtain a time-efficient approximation of the real trilogarithm we proceed similarly to Ref. [5]: We use Eqs. (4)–(5) to transform the argument of the trilogarithm to the intervals [-1,0] and/or [0,1/2]. On each of these intervals Ref. [5] approximates li₃ in terms of Chebyshev polynomials, which are evaluated using Clenshaw's algorithm [10]. Clenshaw's algorithm, however, is purely sequential and thus cannot make use of ILP. For this reason we use a different technique to approximate li₃ on these intervals to allow for ILP: We use a rational minimax approximant of the form

$$li_3(x) = x \sum_{k=0}^{\infty} \frac{x^k}{(k+1)^3} \approx x \frac{\sum_{k=0}^5 p_k x^k}{\sum_{k=0}^6 q_k x^k},$$
(7)

where we evaluate the numerator and denominator polynomials using Estrin's scheme [11]. The coefficients p_k and q_k in Eq. (7) are calculated using the MiniMaxApproximation function from Wolfram/Mathematica [12] and are listed in Table 1 and 2. For arguments $x \in [-1,0]$ the error of the approximant in Eq. (7) is less than $2.050 \cdot 10^{-17}$, while for $x \in [0,1/2]$ it is less than $1.066 \cdot 10^{-17}$. These maximum errors are small enough to achieve IEEE 754-1985 double precision accuracy in the numeric evaluation of li₃.

In detail, our algorithm to numerically evaluate li₃ is as follows: We split the domain of li₃ into the sub-domains $\mathbb{R} = (-\infty, -1) \cup \{-1\} \cup (-1, 0) \cup \{0\} \cup (0, 1/2) \cup (0, 1/$ $\{1/2\} \cup (1/2,1) \cup \{1\} \cup (1,2) \cup \{2\} \cup (2,\infty)$. For arguments $x \in (-\infty, -1)$ we use Eq. (4) to transform the argument to the interval (-1,0), where we use the rational minimax approximant from Eq. (7) with the coefficients listed in Table 1. For x = -1 we implement the known value $li_3(-1) = -3\zeta(3)/4$. For $x \in (-1,0)$ we directly use the appropriate approximant from Eq. (7). For x=0 we use the known value $li_3(0) = 0$. For $x \in (0, 1/2)$ we directly use the approximant in Eq. (7) with the coefficients listed in Table 2. For x = 1/2 we use the known value $li_3(1/2) =$ $[21\zeta(3) + 4\ln^3(2) - 2\pi^2\ln(2)]/24$. For $x \in (1/2, 1)$ we use Eq. (5) to transform the argument to the intervals (-1,0) and (0,1/2), where we use the appropriate approximant from Eq. (7) on each interval. For x = 1 we use the known value $li_3(1) = \zeta(3)$. For $x \in (1,2)$ we use Eq. (5) to transform the argument to the intervals (-1,0) and (0,1/2), where we use the appropriate approximant from Eq. (7) on each interval. For $x \geq 2$ we use Eq. (4) to transform the argument to the interval (0, 1/2], where we use the appropriate approximant from Eq. (7).

An implementation of the described algorithm in C is given in Appendix A. This C implementation is also provided in an ancillary file in the arXiv submission of this publication under the CC-BY-4.0 license.

Table 1: Coefficients of the numerator and denominator polynomials for the minimax approximant in Eq. (7) for $x \in [-1, 0]$.

p_0	$0.99999999999999995 \cdot 10^{+0}$
p_1	$-2.0281801754117129576 \cdot 10^{+0}$
p_2	$1.4364029887561718540 \cdot 10^{+0}$
p_3	$-4.2240680435713030268 \cdot 10^{-1}$
p_4	$4.7296746450884096877 \cdot 10^{-2}$
p_5	$-1.3453536579918419568 \cdot 10^{-3}$
q_0	$1.00000000000000000000 \cdot 10^{+0}$
q_1	$-2.1531801754117049035 \cdot 10^{+0}$
q_2	$1.6685134736461140517 \cdot 10^{+0}$
q_3	$-5.6684857464584544310 \cdot 10^{-1}$
q_4	$8.1999463370623961084 \cdot 10^{-2}$
q_5	$-4.0756048502924149389 \cdot 10^{-3}$
q_6	$3.4316398489103212699 \cdot 10^{-5}$

Table 2: Coefficients of the numerator and denominator polynomials for the minimax approximant in Eq. (7) for $x \in [0, 1/2]$.

p_0	0.999999999999999999999999999999999999
p_1	$-2.5224717303769789628 \cdot 10^{+0}$
p_2	$2.3204919140887894133 \cdot 10^{+0}$
p_3	$-9.3980973288965037869 \cdot 10^{-1}$
p_4	$1.5728950200990509052 \cdot 10^{-1}$
p_5	$-7.5485193983677071129 \cdot 10^{-3}$
q_0	$1.00000000000000000000 \cdot 10^{+0}$
q_1	$-2.6474717303769836244 \cdot 10^{+0}$
q_2	$2.6143888433492184741 \cdot 10^{+0}$
q_3	$-1.1841788297857667038 \cdot 10^{+0}$
q_4	$2.4184938524793651120 \cdot 10^{-1}$
q_5	$-1.8220900115898156346 \cdot 10^{-2}$
q_6	$2.4927971540017376759 \cdot 10^{-4}$

4 Benchmark

In the following we investigate the run-time of the C implementation given in Appendix A. Table 3 shows the average run-time of a single call of li_3 in nano seconds for arguments on different intervals and on different 64-bit CPU architectures (compiled with gcc 10.2.1 with -02 optimization level). The run-times shown in the table have been obtained by measuring the average run-time of li_3 on 10^6 random values on each interval using the Google benchmark library version 1.5.2 [13]. For comparison we also show in Table 3 the average run-time for the real natural logarithm ln, the real cosine function cos and the real identity function id(x) = x.

We find that the run-time of li_3 is similar to the runtime of ln for arguments on the intervals [-1,0] and [0,1/2], where no transformation is performed and the rational minimax approximants from Eq. (7) are used directly. For arguments $x \in [-2,-1]$ or $x \in [2,3]$ the transformation onto [-1,0] and [0,1/2], respectively,

Table 3: Average run-time in nano seconds for one invocation of li₃, ln, cos and id for arguments on different intervals on different CPU architectures (compiled with gcc 10.2.1 with -02 optimization level).

			/
Function	Interval	$i5\text{-}8265\mathrm{U}$	i7-5600U
li_3	[-2, -1]	16.7	20.3
li_3	[-1, 0]	4.31	5.81
li_3	[0, 1/2]	5.09	6.42
li_3	[1/2, 1]	24.3	29.4
li_3	[1, 2]	24.2	31.0
li_3	[2, 3]	13.2	15.9
\ln	[1, 2]	5.20	6.34
cos	$[0, \pi/2]$	11.0	13.3
id	[-2, 2]	0.259	0.315

involves extra arithmetic floating-point operations and one additional call of ln, which leads to an increased run-time of li₃ by approximately a factor 3 in total. For arguments $x \in [1/2,1]$ or $x \in [1,2]$ a transformation onto both [-1,0] and [0,1/2] intervals is performed, where the corresponding approximants from Eq. (7) are used, respectively. This transformation, which requires extra arithmetic floating-point operations and two additional calls of ln, and the necessity to use two approximants leads to an increased run-time of li₃ by approximately a factor 5 on these intervals.¹

5 Summary

We have presented an algorithm to approximate the real trilogarithm of a real argument with IEEE 754-1985 double precision. The approximation is structured to allow for the use of instruction-level parallelism on appropriate CPUs. A C implementation of the real trilogarithm, using the algorithm presented in this publication, can be found in the appendix as well as in an ancillary file in the arXiv submission of this publication under the CC-BY-4.0 license. Implementations in C, C++, Fortran, Julia and Rust can be found in Refs. [14–16].

A Implementation of the real trilogarithm

```
#include <math.h>
// Re[Li 3(x)] for x in [-1, 0]
static double li3_neg(double x)
   const double P[] = {
      0.99999999999999795e+0,
     -2.0281801754117129576 e+0,
      1.4364029887561718540e+0,
      -4.2240680435713030268e-1,
      4.7296746450884096877e-2,
     -1.3453536579918419568e-3
   }:
   const double Q[] = {
      1.00000000000000000000e+0,
     -2.1531801754117049035e+0,
      1.6685134736461140517e+0,
     -5.6684857464584544310e-1,
      8.1999463370623961084e-2.
     -4.0756048502924149389e-3,
      3.4316398489103212699e-5
   };
   const double x2 = x*x;
   const double x4 = x2*x2;
   const double p = P[0] + x*P[1]
      + x2*(P[2] + x*P[3])
      + x4*(P[4] + x*P[5]);
   const double q = Q[0] + x*Q[1]
      + x2*(Q[2] + x*Q[3])
      + x4*(Q[4] + x*Q[5] + x2*Q[6]);
   return x*p/q;
// Re[Li_3(x)] for x in [0, 1/2]
static double li3_pos(double x)
   const double P[] = {
      0.999999999999999893e+0,
     -2.5224717303769789628e+0,
      2.3204919140887894133e+0.
     -9.3980973288965037869e-1,
      1.5728950200990509052e-1.
     -7.5485193983677071129e-3
   };
   const double Q[] = {
      1.0000000000000000000000e+0,
     -2.6474717303769836244 e+0,
      2.6143888433492184741e+0.
     -1.1841788297857667038 e+0.
      2.4184938524793651120e-1.
     -1.8220900115898156346e-2,
      2.4927971540017376759e-4
   const double x2 = x*x;
   const double x4 = x2*x2;
   const double p = P[0] + x*P[1]
      + x2*(P[2] + x*P[3])
      + x4*(P[4] + x*P[5]);
   const double q = Q[0] + x*Q[1]
      + x2*(Q[2] + x*Q[3])
      + x4*(Q[4] + x*Q[5] + x2*Q[6]);
   return x*p/q;
```

¹A potential performance optimization for arguments $x \in [1/2, 1]$ or $x \in [1, 2]$ could be to not perform a transformation onto other intervals, but instead directly use dedicated rational minimax approximants on these intervals, at the cost of an increased number of coefficients to be stored in the source code.

```
// Re[Li_3(x)] for x in (-inf, +inf)
double li3(double x)
   const double zeta2 = 1.6449340668482264;
   const double zeta3 = 1.2020569031595943;
   if (x < -1) {
      const double 1 = log(-x);
      return li3_neg(1/x)
         -1*(zeta2 + 1.0/6*1*1);
   } else if (x == -1) {
      return -0.75*zeta3;
    else if (x < 0) {
      return li3_neg(x);
   } else if (x == 0) {
      return 0;
   } else if (x < 0.5) {
      return li3_pos(x);
   } else if (x == 0.5) {
      return 0.53721319360804020;
   } else if (x < 1) {
      const double 1 = log(x);
      return -li3_neg(1 - 1/x)
         - li3_pos(1 - x) + zeta3
         + 1*(zeta2
              + 1*(-0.5*log(1 - x)
                   + 1.0/6*1));
   } else if (x == 1) {
      return zeta3;
   } else if (x < 2)
      const double 1 = log(x);
      return -li3_neg(1 - x)
         - li3_pos(1 - 1/x) + zeta3
         + 1*(zeta2
              + 1*(-0.5*log(x - 1)
                   + 1.0/6*1));
   } else {
      const double 1 = log(x);
      return li3_pos(1/x)
         + 1*(2*zeta2 - 1.0/6*1*1);
   }
```

References

- [1] Stephen P. Martin and David G. Robertson. "TSIL: A Program for the calculation of two-loop self-energy integrals". In: *Comput. Phys. Commun.* 174 (2006), pp. 133–151. DOI: 10.1016/j.cpc.2005.08.005.
- [2] Stephen P. Martin and David G. Robertson.
 "Evaluation of the general 3-loop vacuum Feynman integral". In: *Phys. Rev. D* 95.1 (2017),
 p. 016008. DOI: 10.1103/PhysRevD.95.016008.
- [3] Stephan Buehler and Claude Duhr. "CHAP-LIN Complex Harmonic Polylogarithms in Fortran". In: *Comput. Phys. Commun.* 185 (2014), pp. 2703–2713. DOI: 10.1016/j.cpc.2014.05.022.
- [4] J. Ablinger et al. "Numerical Implementation of Harmonic Polylogarithms to Weight w = 8". In: Comput. Phys. Commun. 240 (2019), pp. 189–201. DOI: 10.1016/j.cpc.2019.02.005.

- [5] L. Naterop, A. Signer, and Y. Ulrich. "handyG Rapid numerical evaluation of generalised polylogarithms in Fortran". In: Comput. Phys. Commun. 253 (2020), p. 107165. DOI: 10.1016/j.cpc.2020.107165.
- [6] Yudell L. Luke. Mathematical Functions and their Approximations. Academic Press Inc., 1975. DOI: 10.1016/C2013-0-11106-3.
- [7] Robert A. Morris. "The dilogarithm function of a real argument". In: *Mathematics of Computation* 33 (1979), pp. 778–787.
- [8] Alexander Voigt. "Comparison of methods for the calculation of the real dilogarithm regarding instruction-level parallelism". In: arXiv (Jan. 2022). DOI: 10.48550/arXiv.2201.01678.
- [9] Leonard Lewin. *Polylogarithms and Associated Functions*. Elsevier Norh Holland, Inc., 1981.
- [10] C. W. Clenshaw. "A note on the summation of Chebyshev series". In: *Mathematics of Computation* 9 (1955), pp. 118–120.
- [11] Gerald Estrin. "Organization of Computer Systems: The Fixed plus Variable Structure Computer". In: Papers Presented at the May 3-5, 1960, Western Joint IRE-AIEE-ACM Computer Conference. IRE-AIEE-ACM '60 (Western). San Francisco, California: Association for Computing Machinery, 1960, pp. 33–40. DOI: 10.1145/1460361.1460365.
- [12] Wolfram Research, Inc. *Mathematica*. Version 13.0.0. Champaign, IL. 2021.
- [13] Google LLC. Benchmark. Version 1.5.2. [License: Apache-2.0]. 2020. URL: https://github.com/google/benchmark.
- [14] Alexander Voigt. *Polylogarithm*. Version 6.14.0. [License: MIT]. 2023. URL: https://github.com/Expander/polylogarithm.
- 15] Alexander Voigt. *PolyLog.jl.* Version 2.3.1. [License: MIT]. 2023. URL: https://github.com/Expander/PolyLog.jl.
- [16] Alexander Voigt. polylog.rs. Version 2.5.1. [License: LGPL-3.0]. 2023. URL: https://github.com/Expander/polylog.rs.