A search for a muon to electron conversion in COMET

Yuki Fujii on behalf of the COMET collaboration

Monash University, Clayton, Victoria, Australia

E-mail: yuki.fujii@monash.edu

ABSTRACT: The COMET experiment at J-PARC, Japan, aims to search for muon to electron conversion with aluminium nuclei, achieving a sensitivity four orders of magnitude higher than the current upper limit at a 90% confidence level. The proton beam line has recently been completed, and muons have been successfully transported through the curved solenoid in the Phase-alpha of the experiment. In this paper, we will present preliminary results from the Phase-alpha beam measurement, the status of the intermediate sensitivity experiment (COMET Phase-I), and the ultimate goal of COMET Phase-II.

KEYWORDS: Particle detectors; Spectrometers

Contents

1	Introduction	1
2	Signal and Backgrounds in COMET	2
3	Apparatus	2
4	Physics Sensitivity	5
5	Status	6
6	Summary and Prospects	6

1 Introduction

The COMET experiment searches for a transition of a muon to an electron without emission of neutrinos, also known as a μ -e conversion. This process violates the conservation law of lepton flavour and is strictly forbidden in the standard model of particle physics (SM). Even when considering the minimum SM model extension with neutrino oscillations, the conversion rate $(CR(\mu^-N \rightarrow e^-N))$ is strongly suppressed to approximately 10^{-54} , which is completely undetectable. On the other hand, a large enhancement of the $CR(\mu^-N \rightarrow e^-N)$, up to 10^{-15} , is predicted in many BSM models, e.g., Leptoquark models [1]. The signal electron is essentially monochromatic with an energy $E_{\mu e} = M_{\mu} - B_{\mu} - E_{recoil} \approx 105$ MeV in case of muonic aluminium. This peculiar feature together with the low background level make the μ -e conversion an ideal tool to investigate the BSM physics. The current upper limit on $CR(\mu^-N \rightarrow e^-N)$ is 7×10^{-13} at 90% confidence level set by the SINDRUM II experiment [3].

In COMET, our primary target is to achieve 100 times better single event sensitivity, 10^{-15} , which is called COMET Phase-I [2], followed by another two orders of magnitude improved sensitivity in Phase-II. This allows us to indirectly explore the new physics energy scale up to 100–1000 TeV. Furthermore, the complementary searches with other muon CLFV modes ($\mu \rightarrow e\gamma$ and $\mu \rightarrow eee$) will provide more detailed new physics investigation by looking at slightly different parameter space. In addition to those two stages, we recently performed the first muon beam delivery to the COMET experimental area with a set of detectors, which is called COMET Phase-alpha. In this paper, we first introduce the event feature of the signal and backgrounds, then we report details of the experimental apparatus used in Phase-I and Phase-II, and the current preparation status. Also, the preliminary results from the first muon beam delivery and profile measurement in COMET Phase-alpha, are briefly presented.

2 Signal and Backgrounds in COMET

In the SM, a muon decays into an electron and two neutrinos to conserve the lepton flavour; $\mu^- \rightarrow e^- v_{\mu} \overline{v_e}$. If this happens while the muon is bounded to an atom, this is known as muon decay in orbit (DIO). Due to the presence of a nucleus, DIO electrons receive the recoil energy and they can have a broad energy spectrum with an endpoint of ≈ 105 MeV, hence, the DIO is an intrinsic background for the signal event. Alternatively, a muon is captured by a nucleus and emits a neutrino and neutrons/protons/alpha particles. The capture process also includes a radiative process called radiative muon capture; RMC. This process produces a photon or a pair of e^+e^- in the final state. However, the maximum energy of gamma-rays is sufficiently lower than the of the conversion electron energy to make this background negligible. The DIO events can only be discriminated by their energy, therefore the precise momentum measurement is a key design factor. According to our studies based on simulations, a momentum resolution of 200 keV/c is required to achieve a single event sensitivity of 10^{-15} . To lower the sensitivity by a factor of 100, this resolution has to be improved further down to 150 keV/c. In the case of the signal event, a muon stops inside the target and forms a muonic atom at 1s ground state. The electron emitted from the muonic aluminium has a monochromatic energy of 105 MeV as already explained with a decay time of $\tau_{\mu} = 864$ ns.

Other sources of background are the electrons produced by the in flight decays of muons or pions. In this case, the time delay due to the muonic atom lifetime is not present so this prompt background can be suppressed by a timing cut. We therefore adopt a pulsed beam structure with a separation of ~1.2 μ s between the pulses and use a delayed measurement window between 700 ns and 1170 ns from the bunch arrival on the target to avoid those prompt backgrounds in COMET. In this scheme, it is also important to maintain a highly pulsed structure, since any leakage protons appearing inter-bunches can create a signal-like secondary particle in this time window. We call this an "Extinction" factor defined as; $R_{\text{ext}} = (\text{#of protons between bunches})/(\text{#of protons in a main bunch})$, and this R_{ext} should be less than $10^{-10} (10^{-11})$ to accomplish the Phase-I (Phase-II) sensitivity.

The last background is a cosmic-ray induced background randomly produced inside the detector with an energy close to 105 MeV. The cosmic-ray background will be suppressed by covering the entire detector with a cosmic-ray-veto detector.

3 Apparatus

Muon beam To produce the world's most intense muon beam, we use the proton beam accelerated up to 8 GeV in the main ring (MR) of the proton synchrotron at J-PARC (Japan Proton Accelerator Research Complex), Japan. To realise an ideal bunch separation timing, only one of two buckets is filled with protons at the rapid cycling synchrotron which accelerates the proton beam from 400 MeV to 3 GeV before the MR. This corresponds to 4 out of 9 total buckets in the main ring with a bunch separation of 1.17 μ s. After the acceleration, protons are slowly extracted towards the J-PARC Hadron experimental facility by using one or two electrostatic septa (ESS) and multiple magnetic septa (SMS) while keeping the bunched structure (BSX: Bunched Slow Extraction) [4]. The protons are delivered to the COMET beam area and impinged into the pion production target which is surrounded by the 5 T pion capture solenoid. Through the hadronic interaction, pions are produced, and low momentum back scattered pions are efficiently transferred towards the 3 T



Figure 1: Overview of the COMET Phase-I and Phase-II conceptual design.

muon transportation solenoid (MTS). Most of pions decay into muons before reaching the exit of the MTS. Due to the curved structure of the MTS, charged particles vertically drift depending on their charge and transverse momentum while travelling inside, with an additional dipole field used to adjust compensate the drifting of low momentum negative muons to keep them around the centre at the end of the MTS.

Phase-I In Phase-I, we will conduct the physics measurement using a Cylindrical Detector (CyDet) system placed at the end of the first 90 degrees of the MTS (see Figure 1) inside the 1 T solenoidal magnetic field (Detector Solenoid: DS). The muon stopping target, a series of 200 μ m thick aluminium disks, is located inside the CyDet. The cylindrical shape helps to avoid the remaining beam particles such as pions and their secondaries that concentrate on the beam axis with small transverse momentum, as well as filtering the most of DIO electrons whose momentum is below 70 MeV/c. The CyDet system consists of a Cylindrical Drift Chamber (CDC) and a set of Cylindrical Trigger Hodoscope (CTH) detectors as shown in Figure 2(a). The CDC, filled with a He: iC_5H_{10} (90:10) gas mixture, contains almost 5,000 all stereo anode wires, and is used to reconstruct the momentum of charged particles [5]. The wires are read out by 105 RECBE boards ¹ with minor adaptations. The expected momentum resolution is about 200 keV/c, which is good enough to achieve the Phase-I physics sensitivity. The CTH detectors are located at both ends of CDC and consist of two layers of concentric rings containing 64 counters each [7]. Each counter is a plastic scintillator (BC-408) with height×width×length of $5 \times 88 \times 360$ ($10 \times 88 \times 340$) mm³ for the inner (outer) layer. All scintillators are connected to fibre bundles to readout the scintillation photons outside of the detector solenoid for using silicon photo-multipliers (SiPM) which are relatively weak against radiation damage and have to be placed outside of the detector solenoid where the neutron level is an order lower, inside the cooling box. Due to an extremely high hit rate environment, the fake trigger could be an issue especially in Phase-I physics measurement. To suppress the trigger

¹Readout Electronics for CDC in BElle (RECBE) [6]

rate caused by non signal-like fake events as low as possible, an online trigger system is introduced by utilising machine learning based algorithms inside field programmable gate arrays (FPGAs) in the CyDet system, which is called COTTRI (COmeT TRIgger) [11]. This will realise the trigger rate of less than 13 kHz, which is within the maximum available rate for our data acquisition (DAQ) system.

We will also perform a direct beam measurement by replacing the CyDet with a set of planar shaped detectors called StrECAL (Straw+ECAL, see Figure 2(b)). The beam measurement detector consists of a series of straw tube tracker (StrawTrk) stations and a full absorption type electron calorimeter (ECAL). The StrawTrk has five stations and each one consists of one vertical layer and the other horizontal layer. Each layer has staggered straw tubes in order to minimise gaps to reduce inefficiency. A straw is made of 20 μ m thick aluminised Mylar with a 10 mm diameter, filled with Ar:CO₂=50:50. The ECAL is composed of arrays of LYSO (Lu_{2(1-x)}Y_{2x}SiO₅) crystals with dimensions 2 × 2 × 12 cm³ [9]. This length corresponds to 10.5 radiation lengths to contain the signal like electrons with minimum leakage. In each crystal, scintillation photons will be read by an avalanche photodiode (APD, Hamamatsu S8664-1010, 10 × 10 mm²). Both StrawTrk and ECAL signals are read by specially designed waveform digitisers [10] based on domino ring sampler chips (DRS4). The beam measurement detectors are also regarded as detector prototypes for Phase-II physics measurement. The DS will be covered by the iron yoke and cosmic ray veto counters made



Figure 2: Two detector systems used in COMET Phase-I.

of plastic scintillator. Also, there is a possibility to introduce resistive plate chambers (RPC) around the MTS to DS bridging solenoid where plastic scintillators cannot work properly due to higher neutron levels expected.

Phase-II To achieve another 100 times better sensitivity than in Phase-I, the production target will be replaced from graphite to tungsten to increase the pion yield, and shielding materials will be reinforced. The MTS will be extended by another 90 degrees to further reduce pions, and there will be an additional electron spectrometer after the muon stopping target to filter most DIO electrons. This electron spectrometer enables using the detector system that covers almost fully 2π forward direction, increasing the signal acceptance. In COMET Phase-II, it is crucial to improve the momentum resolution which is dominated by the multiple scattering effects. Therefore, all straw tubes will be replaced by thinner ones, 12 μ m wall thickness with twice smaller diameter of 5 mm to reduce the material budget inside the tracking volume. The ECAL will cover the 50 cm radius to increase the acceptance with 1,920 crystals.

4 Physics Sensitivity

In Table 1, we summarise the breakdown of the expected signal acceptance in each phase together with the expected number of background events. The efficiencies have been obtained from a

Table 1: Signal efficiency and expected number of background events for the COMET Phase-I [2]

 / Phase-II [12, 13].

Items	Phase-I	Phase-II
Signal acceptance	0.2	0.18
Trigger + DAQ efficiency	0.8	0.87
Track finding efficiency	0.99	0.77
Track selection	0.9	0.94
Momentum window	0.93	0.62
Timing window	0.3	0.49
Total	0.04	0.034
Sources of background		
Muon decay in orbit	0.01	0.068
Radiative muon capture	0.0019	Negligible
Neutron emission after muon capture	<0.001	Negligible
Charged particle emission after muon capture	<0.001	Negligible
Prompt beam induced electrons	<0.0038	0.002
Radiative pion capture	0.0028	0.001
Delayed beam induced ²	Negligible	0.001
Antiproton induced	0.0012	0.30
Cosmic ray induced	<0.01	0.29
Total	< 0.032	0.662

detailed simulation using the results of the tests on the prototypes. The estimate of the number of events assumes 150 (230) days of data acquisition with 3.2 kW (56 kW) beam power in Phase-I (Phase-II) and 4.7×10^{-4} (1.6×10^{-3}) stopped muons per proton on target. The single event sensitivity is defined as:

$$SES(\mu^- N \to e^- N) = \frac{1}{N_\mu \cdot f_{cap} \cdot f_{gnd} \cdot A_{sig}},\tag{4.1}$$

where N_{μ} is the total number of stopped muons, $f_{cap} = 0.61$ is the fraction of nuclear muon captures, $f_{gnd} = 0.9$ is the model dependent fraction of muons to be the ground state. Given the signal efficiencies reported in Table 1, the expected S.E.S. for Phase-I (Phase-II) is 3×10^{-15} (1.4×10^{-17}) , which is 100 (10,000) times better than the one achieved by SINDRUM II.

²Assuming R_{ext} is 10⁻¹⁰ and 10⁻¹¹ for Phase-I and Phase-II, respectively

5 Status

The tests of the 8 GeV BSX proton beam have shown that the extinction factor is enough to keep the out of pulse background at a negligible level [14]. The C-line construction was recently completed up to the COMET beam area and is ready to provide the beam. The coils for the proton capture solenoid are all winded and the cryostat cold bore part has been constructed [15]. The first 90 degrees of the muon transport solenoid, that is the full TS for Phase-I, has been constructed and tested up to 1.5 T. The coil winding for the detector solenoid has been completed and the cryostat will be made soon this year. The CDC has already been constructed, and its performance has been evaluated with cosmic rays. It meets the performance requirement, a spatial resolution of 170 μ m [5]. We have almost completed the R&D for the CTH and the design has been fixed. The support structure has been partially purchased and the detector construction is underway. A trigger system for COMET Phase-I is being prepared and we have recently performed a successful test of a small trigger electronics chain.

The first station of the straw tube tracker has been completed [16] and commissioned in Phasealpha beam measurement very recently. The LYSO crystals are almost fully purchased, and the ECAL support structure has been manufactured.

The CRV design is almost finalised and the first module has recently been been produced.

For Phase-II, the thinner straw tube will be used with $12 \,\mu$ m with a twice smaller diameter. The test production of thin straw tubes was done in success, and they are under the long term stability test [17].

In February and March 2023, the proton beam has been successfully delivered to the COMET beam area as COMET Phase-alpha. In this measurement, pions produced in a thin graphite target have been transported through the MTS and the muons coming from their decays have been successfully observed by a set of dedicated detectors. Preliminary results can be found in [18] while the final ones will be published soon.

6 Summary and Prospects

The COMET experiment aims to search for the μ -*e* conversion with 100 and 10,000 better sensitivities than the present upper limit. The COMET beam line has been completed in 2022. More recently the proton beam has successfully beam delivered to COMET Phase-alpha and the first muons have been observed. Phase-I preparation is well on track and first physics measurements are expected for 2024-2025.

Acknowledgments

This was written on behalf of, and the author acknowledges strong support from, the COMET collaboration. We acknowledge support from JSPS, Japan; ARC, Australia; Belarus; NSFC, China; IHEP, China; IN2P3-CNRS, France; CC-IN2P3, France; SRNSF, Georgia; DFG, Germany; JINR; IBS, Korea; RFBR, Russia; STFC, United Kingdom; and the Royal Society, United Kingdom. The views expressed herein are those of the author and are not necessarily those of the Australian Government or Australian Research Council.

References

- I. Bigaran, J. Gargalionis, and R.R. Volkas, A near-minimal leptoquark model for reconciling flavour anomalies and generating radiative neutrino masses, J. High Energ. Phys., 2019, 106 (2019). https://doi.org/10.1007/JHEP10(2019)106
- G. Adamov, et.al. (COMET Collaboration), COMET Phase-I technical design report, Progress of Theoretical and Experimental Physics, vol.2020, 033C01 (2020).
- [3] W. Bertl, et.al., A search for μ-e conversion in muonic gold, Eur. Phys. J. C Vol 47, 337–346 (2006).
- [4] M. Tomizawa, et.al., Slow extraction from the J-PARC main ring using a dynamic bump, Nucl. Instrum. Methods A, Vol 902, pp51–61 (2018).
- [5] M. Moritsu, et.al., Construction and performance tests of the COMET CDC, Proceedings of Science, Vol 340, p538 (2019).
- [6] T. Uchida, et.al., 2011 IEEE Nuclear Science Symp. Conf. Record, p. 694 (2011).
- [7] Y. Fujii, et.al., Studies of optical fibre and SiPM readout system for the Cylindrical Trigger Hodoscope in COMET Phase-I, The 30th International Symposium on Lepton Photon Interactions at High Energies (Lepton Photon 2021), Zenodo, https://doi.org/10.5281/zenodo.7542297 (2022).
- [8] H. Nishiguchi, et.al., Construction on vacuum-compatible straw tracker for COMET Phase-I, Nucl. Instrum. Methods A, Vol 958, 162800 (2020).
- K. Oishi, Development of Electromagnetic Calorimeter Using LYSO Crystals for the COMET Experiment at J-PARC, in Proceedings of the Eur. Phys. Soc. Conf. on High Ene. Phys, EPS-HEP, 5-12 July 2017, Venice, Italy (2018)
- [10] K. Ueno, et.al., Design of Radiation Tolerant Electronics for StrECal System in COMET Experiment, in Proceedings of the Eur. Phys. Soc. Conf. on High Ene. Phys, EPS-HEP, 1-17 July 2019, Ghent, Belgium (2019)
- [11] Y. Fujii, et.al., Online Machine-Learning-Based Event Selection for COMET Phase-I, Phys. Sci. Forum 2023, 8, 32. https://doi.org/10.3390/psf2023008032
- [12] K. Oishi Study of Sensitivity to Search for a Charged Lepton Flavor Violating Process, Kyushu University, PhD thesis, 2021, http://epp.phys.kyushu-u.ac.jp/thesis/2021DoctorOishi.pdf
- [13] B. Krikler Sensitivity and background estimates for phase-II of the COMET experiment, Imperial College London, PhD thesis, 2016, https://doi.org/10.25560/45365
- [14] K. Noguchi, et al., Extinction Measurement at J-PARC MR with Slow-Extracted Pulsed Proton Beam for COMET Experiment, Proceedings of Science vol. 402, p104 (2022).
- [15] M. Yoshida et al., *Status of Superconducting Solenoid System for COMET Phase-I Experiment at J-PARC*, in *IEEE Transactions on Applied Superconductivity*, vol. 25, no. 3, pp. 1–4, June (2015).
- [16] H. Nishiguchi, et.al., Vacuum-Compatible, Ultra-Thin-Wall Straw Tracker; Detector construction, Thinner straw R&D, and the brand-new graphite-straw development, Nucl. Instrum. Methods A, Vol 1042, 167373 (2022).
- [17] N. Tsverava, et.al., Development of Ultrathin 12 μm Thick Straw Tubes for the Tracking Detector of COMET Experiment, 2019 IEEE NSS/MIC, Manchester, UK, 2019, pp. 1-4, doi: 10.1109/NSS/MIC42101.2019.9060032.

[18] K. Oishi, COMET Phase-Alpha Experiment to Investigate COMET's New Muon Beamline at J-PARC The 31st International Symposium on Lepton Photon Interactions at High Energies (Lepton Photon 2023), Melbourne, Australia (2023).