# **Ensuring User-side Fairness in Dynamic Recommender Systems**

Hyunsik Yoo University of Illinois Urbana-Champaign hy40@illinois.edu

Zhining Liu University of Illinois Urbana-Champaign liu326@illinois.edu

Zhichen Zeng University of Illinois Urbana-Champaign zhichenz@illinois.edu

Fei Wang Amazon feiww@amazon.com

## ABSTRACT

User-side group fairness is crucial for modern recommender systems, as it aims to alleviate performance disparity between groups of users defined by sensitive attributes such as gender, race, or age. We find that the disparity tends to persist or even increase over time. This calls for effective ways to address user-side fairness in a dynamic environment, which has been infrequently explored in the literature. However, fairness-constrained re-ranking, a typical method to ensure user-side fairness (i.e., reducing performance disparity), faces two fundamental challenges in the dynamic setting: (1) non-differentiability of the ranking-based fairness constraint, which hinders the end-to-end training paradigm, and (2) time-inefficiency, which impedes quick adaptation to changes in user preferences. In this paper, we propose FAir Dynamic rEcommender (FADE), an end-to-end framework with fine-tuning strategy to dynamically alleviate performance disparity. To tackle the above challenges, FADE uses a novel fairness loss designed to be differentiable and lightweight to fine-tune model parameters to ensure both user-side fairness and high-quality recommendations. Via extensive experiments on the real-world dataset, we empirically demonstrate that FADE effectively and efficiently reduces performance disparity, and furthermore, FADE improves overall recommendation quality over time compared to not using any new data.

#### **CCS CONCEPTS**

• Information systems → Data mining; • Computing method**ologies**  $\rightarrow$  *Machine learning*.

#### **KEYWORDS**

recommender systems, user-side fairness, dynamic updates

#### **ACM Reference Format:**

Hyunsik Yoo, Zhichen Zeng, Jian Kang, David Zhou, Zhining Liu, Fei Wang, Eunice Chan, and Hanghang Tong. 2023. Ensuring User-side Fairness in Dynamic Recommender Systems. In Woodstock '23: ACM Symposium on Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org. Conference acronym 'XX, June 03-05, 2023, Woodstock, NY

© 2023 Association for Computing Machinery.

ACM ISBN 978-1-4503-XXXX-X/18/06...\$15.00

https://doi.org/XXXXXXXXXXXXXXX

Jian Kang University of Illinois Urbana-Champaign jiank2@illinois.edu

Eunice Chan University of Illinois Urbana-Champaign ecchan2@illinois.edu

David Zhou University of Illinois Urbana-Champaign david23@illinois.edu

Hanghang Tong University of Illinois Urbana-Champaign htong@illinois.edu



Figure 1: The changes in overall recommendation performance and performance disparity between two user groups over time in the dynamic recommendation system. (a) The performance gain of the models using new data compared to the one NOT using new data tends to increase over time, indicating the importance of incremental adaptation to new data for improving the recommendation quality. (b) The performance disparity tends to remain relatively high over time when the model uses new data without fairness regularization, indicating the importance of the problem of dynamic user-side fairness.

Neural Gaze Detection, June 03-05, 2023, Woodstock, NY. ACM, New York, 

#### INTRODUCTION 1

Recommender systems are essential for delivering high-quality personalized recommendations in a two-sided market; i.e., userside and item-side [29, 32, 37]. In this market, users provide feedback on recommended items, refining the recommendations to better reflect their preferences. However, these recommender systems can perform poorly for users from certain demographic groups even while delivering high-quality recommendations on average [3, 27]. For example, a job recommender system might recommend more irrelevant job opportunities to female engineers in STEM, which can significantly impact their career growth [10, 17]. <sup>1</sup> Thus, it is important to alleviate the performance disparity between different user groups in recommender systems [19].

As the real-world user-item interaction network continues to evolve, it is crucial for recommender systems to dynamically learn from newly observed data in order to capture the most up-to-date

<sup>1</sup>STEM is an acronym representing the four fields of Science, Technology, Engineering, and Mathematics.

user preferences and continually improve recommendation quality [13, 34]. As shown in Figure 1-(a), based on a real-world movie recommendation dataset comprising male and female users, recommendation performance tends to increase as more recent data is included to train the recommendation model. However, as indicated in Figure 1-(b), the performance disparity between the two user groups tends to remain relatively high over time. This highlights the importance of considering user-side fairness in the dynamic setting, which has been largely ignored in existing literature [13, 34].

Ensuring dynamic user-side fairness is challenging. One common approach involves using a fairness-constrained re-ranking strategy [5, 19], where a quality-oriented base recommender generates initial ranking lists and a fairness-aware re-ranking module is applied to produce new fair ranking lists by re-ranking them under the fairness constraint. However, this approach presents two key challenges in dynamic settings.

(C1) Non-differentiable. In a dynamic environment, the endto-end training paradigm is crucial for fair recommender systems to continuously update their parameters (e.g., user/item representations) according to fairness constraints to ensure fairness, since those parameters play a vital role as input features in various realworld applications. Re-ranking optimizes a non-differentiable fairness measure, which makes it impossible to jointly optimize the fairness measure and the general recommendation loss using a gradient descent algorithm. This decoupling of the two optimization processes precludes *end-to-end* training, and as a result, their model parameters remain unaffected by the fairness constraint in all future time periods.

**(C2) Time-inefficient.** The dynamic setting necessitates quick responses to changes in user preferences and behavior. Re-ranking has a high time complexity that often grows exponentially with the length of the base ranking lists (e.g., when re-ranking as a 0-1 integer programming problem). Furthermore, re-ranking needs to be performed from scratch during each online inference phase over time, further exacerbating the computational burden.

To address these challenges, we study the problem of dynamic user-side fairness and propose <u>FAir Dynamic rEcommender</u> (FADE), an *end-to-end* framework with *fine-tuning* strategy to dynamically alleviate performance disparity. The key idea of FADE is to leverage a carefully designed fairness loss, which is differentiable and lightweight, to address the two challenges as it is **(C1)** based on the differentiable Hit function and **(C2)** able to be efficiently computed via negative item sampling strategy. With the proposed loss, FADE aims to enhance the quality of recommendations while simultaneously imposing fairness regularization. By employing *fine-tuning*, FADE updates the model parameters *using only new data* at each time period, which **(C2)** ensures fast execution time and enables effective adaptation to changes in the data distribution.

FADE opts for fine-tuning instead of full retraining, which is to train the model using the entire dataset from scratch whenever new data becomes available. This decision stems from not only the significantly improved time-efficiency of fine-tuning, but also its ability to improve overall performance by emphasizing recent data. To validate the advantages of FADE, we conduct comparisons against the full-retraining variant and other fairness-aware baselines on the real-world dynamic dataset.

Table 1: Symbols used in this paper.

Symbol	Description			
$\mathcal{D}_t$	Dataset collected at time period $t$			
$\mathcal{U}_t, \mathcal{I}_t, \mathcal{E}_t$	Sets of users, items, and their interactions at time period $t$			
Y <sub>t</sub>	User-item interaction matrix at the time period $t$			
$\widehat{\mathbf{Y}}_t$	User-item predicted score matrix at time period $t$			
$W_t$	Set of model parameters at time period $t$			
а	Binary sensitive attribute of a user			
$\mathcal{L}_{ m rec}, \mathcal{L}_{ m fair}$	Recommendation loss and fairness loss, respectively			
$C_u, N$	Set of candidate items for a user $u$ and its size			
$\mathcal{G}_u$	Set of ground-truth items in $C_u$			
s <sub>u</sub>	Unsorted list of recommendation scores of items in $C_u$			
$\mathbf{r}_u$ List of items in $C_u$ ranked by their scores in $\mathbf{s}_u$				
$\mathbf{P}_u, \widehat{\mathbf{P}}_u$	Permutation matrix and relaxed permutation matrix for $s_u$			
λ	Scaling parameter for $\mathcal{L}_{\mathrm{fair}}$			
τ	Temperature parameter for $\widehat{\mathbf{P}}_{\mathbf{s}_u}$			
μ	The number of negative items in $C_u$			

To summarize, the main contributions of the paper are as follows:

- Problem. We observe that the user-side performance disparity tends to persist or even worsen over time, even though the overall performance increases. To our best knowledge, we are the first to study dynamic user-side fairness in recommender systems.
- Algorithm. We propose FADE, a novel fine-tuning-based recommender system equipped with a lightweight and differentiable fairness loss to effectively and efficiently alleviate performance disparity over time.
- Experiments. Empirical experiments on the real-world dataset demonstrate that FADE effectively and efficiently reduces the performance disparity. Meanwhile, FADE improves overall recommendation quality over time by using fine-tuning compared to not using any new data.

#### **2 PROBLEM DEFINITION**

In this section, we first present the key notations in the paper. Then we provide preliminaries on the settings of dynamic recommendation and user-side fairness. Finally, we formally define the problem of dynamic user-side fairness in recommender systems.

**Notations.** Table 1 provides a list of symbols used in this paper. Throughout the paper, we use bold upper-case letters for matrices (e.g., Y), bold lower-case letters for vectors (e.g., r) and calligraphic letters for sets (e.g.,  $\mathcal{U}$ ). We use conventions similar to NumPy [14] in Python for indexing. For example, Y[*i*, *j*] is the entry at the *i*-th row and the *j*-th column in matrix Y.

We use  $\mathcal{D}_t = {\mathcal{U}_t, \mathcal{I}_t, \mathcal{E}_t, \mathbf{Y}_t}$  to denote the dataset collected at time period  $t \ \forall t \in \{1, ..., T\},^2$  where the subscript  $_t$  indicates the time period  $t, \mathcal{U}_t$  is the user set,  $\mathcal{I}_t$  is the item set,  $\mathcal{E}_t$  is the useritem interaction set, and  $\mathbf{Y}_t$  is the user-item interaction matrix. We consider binary user-item interaction in this work, i.e.,  $\mathbf{Y}_t[u, i] = 1$ if user u has interacted with item i within the t-th time period, and 0 otherwise. The initial user set, item set, user-item interaction set, and the user-item interaction matrix before the first time period (i.e., t = 1) is denoted as  $\mathcal{U}_0, \mathcal{I}_0, \mathcal{E}_0$ , and  $\mathbf{Y}_0$ , respectively. Lastly, we denote the subscript : $_t$  as the time period from the beginning up to

<sup>&</sup>lt;sup>2</sup>Depending on the needs of the system or implementation, the time period could be either a specific time frame (e.g., daily, weekly, monthly) or until a specific number of interactions has been collected.

*t*. For example,  $\mathcal{U}_{t}$  denotes a set of items accumulated up to time period *t* from the beginning (i.e., a set of entire users in the system). **Dynamic recommendation**. We assume that an initial recommendation model has been pre-trained with  $\mathcal{D}_0 = \{\mathcal{U}_0, I_0, \mathcal{E}_0, Y_0\}$  in an offline manner, and then the model is trained solely with the newly collected data  $\mathcal{D}_t$  at the current time period *t*,  $\forall t \in \{1, ..., T\}$ . Once the model has been trained/fine-tuned on  $\mathcal{D}_t$ , a top-*K* recommendation list  $[i_1, ..., i_K]$  for each user *u*, ranked by the predicted scores  $\widehat{Y}_t[u, i], \forall i$ , is generated.

**User-side fairness.** Given a binary sensitive attribute  $a \in \{0, 1\}$  (e.g., gender), we focus on ensuring user-side group fairness, i.e., mitigate the recommendation performance disparity between the advantaged user group (a = 0) and the disadvantaged user group (a = 1) [19]. More specifically, the user-side performance disparity at any time period t is defined as follows.

DEFINITION 1. User-side Performance Disparity [19]. For any time period t, given a user set  $\mathcal{U}_{:t}$  with sensitive attribute a, an item set  $I_{:t}$ , the ground-truth test interaction set  $\mathcal{D}_{t}^{\text{test}}$  and a recommendation model with parameters  $\mathcal{W}_{t}$ , the user-side performance disparity is

$$PD_{t} = \mathbb{E}_{\mathcal{U}_{t}}[Perf(\mathcal{D}_{t}^{test}|a=0;\mathcal{W}_{t})] - \mathbb{E}_{\mathcal{U}_{t}}[Perf(\mathcal{D}_{t}^{test}|a=1;\mathcal{W}_{t})]$$
(1)

where  $Perf(\cdot)$  could be measured by any top-K recommendation evaluation metrics such as Recall@K or F1@K.

**Problem definition.** We formally define the problem of dynamic user-side fairness in recommender systems as follows.

PROBLEM 1. Dynamic user-side fairness in recommender systems.

**Input:** (1) a pre-trained recommendation model with parameters  $\mathcal{W}_0$ ; (2) a continually collected dataset  $\mathcal{D}_t = \{\mathcal{U}_t, \mathcal{I}_t, \mathcal{E}_t, \mathbf{Y}_t\}, \forall t \in \{1, ..., T\}$ ; (3) a binary sensitive attribute  $a \in \{0, 1\}$ ; (4) a specific performance evaluation metric  $\text{Perf}(\cdot)$  to calculate  $\text{PD}_t$  (see Eq. (1)).

**Output:** For any time period t, a fairness-regularized model with the parameters  $W_t$  that (1) optimizes the PD<sub>t</sub> to be close to zero and (2) achieves high-quality recommendations.

#### **3 FADE: A FAIR DYNAMIC RECOMMENDER**

In this section, we propose FADE, a novel dynamic fair recommender system that effectively and efficiently reduces performance disparity over time. We first introduce differentiable Hit operator in Section 3.1 to address the *non-differentiability* of commonly used ranking/sorting-based recommendation metrics. To ensure the *high efficiency* in dynamic settings, the negative sampling strategy is introduced in Section 3.2, based on which, a differentiable and lightweight fairness loss is proposed in Section 3.3 to fit in the (mini-batch) gradient-based optimization. The overall loss function is presented in Section 3.4, and the complexity analysis is further carried out in Section 3.5.

#### 3.1 Differentiable Hit

Most evaluation metrics for top-*K* recommendations, such as Recall@*K* and NDCG@*K*, are fundamentally based on Hit@*k*,  $\forall k \in \{1, ..., K\}$ , which is a binary function that outputs 1 if the *k*-th ranked item is relevant to the user and 0 otherwise. In this sense, we can optimize the quality of recommendations by optimizing the Hit function. However, the Hit function is not differentiable due to its reliance

on the ranking/sorting of the items. To address this challenge, we propose a differentiable version of the Hit function.

First, let us define a standard Hit function. Suppose a score vector  $\mathbf{s}_u = [s_{u1}, s_{u2}, \dots, s_{uN}]^{\mathsf{T}}$  for a user *u* represents the "unsorted" list of recommendation scores (i.e.,  $s_{ui} = \hat{\mathbf{Y}}_t[u, i]$ ) of *N* candidate items in a set  $C_u$  (i.e.,  $|C_u| = N$ ), a vector  $\mathbf{r}_u$  represents the "sorted" list of items ranked in descending order by their scores in  $\mathbf{s}_u$ , and  $\mathbf{r}_u[k]$  represents the *k*-th ranked item. Lastly, let  $\mathcal{G}_u$  denote the set of ground-truth items for user *u*; it is important to note that in the context of dynamic learning, we consider only the items that users have interacted with at the current time period *t* (i.e.,  $\mathcal{G}_u \subset I_t$ ) for FADE, as it specifically utilizes the current data for training, adapting to the dynamic nature of the system.

With the above definitions, we can define the Hit function, Hit<sub>u</sub>(k), which determines whether the k-th ranked item  $\mathbf{r}_u[k]$  is in  $\mathcal{G}_u$ , as follows:

$$\operatorname{Hit}_{u}(k) = \begin{cases} 1 & \text{if } Y_{t}[u, \mathbf{r}_{u}[k]] = 1\\ 0 & \text{if } Y_{t}[u, \mathbf{r}_{u}[k]] = 0 \end{cases}$$
(2)

Here, the *sorting operation* used to produce the  $\mathbf{r}_u$ , which also can be represented as *a permutation matrix*, renders the  $\operatorname{Hit}_u(k)$  nondifferentiable. However, we can overcome this limitation by using the continuous relaxation for permutation matrices to approximate the deterministic sorting operation with a differentiable continuous sorting [7]. First, for the deterministic sorting, the permutation matrix  $\mathbf{P}_u \in \mathbb{R}^{N \times N}$  is given by [7]:

$$\mathbf{P}_{u}[k,j] = \begin{cases} 1 & \text{if } j = \arg\max[(N+1-2k)\mathbf{s}_{u} - \mathbf{A}_{u}\mathbf{1}] \\ 0 & \text{otherwise} \end{cases}, \quad (3)$$

where 1 is the column vector of all ones and  $A_u$  is the absolute distance matrix of  $s_u$  with  $A_u[k, j] = |s_{uk} - s_{uj}|$ . For instance, if we set  $k = \lfloor (N + 1)/2 \rfloor$ , then the non-zero entry in the *k*-th row,  $P_u[k,:]$ , corresponds to the element with the minimum sum of absolute distances to the other elements, and this corresponds to the median element, as desired.

Then, the argmax operator is replaced by Gumbel-softmax [11] to obtain a continuous relaxation of the permutation matrix. Specifically, the k-th row of the permutation matrix is relaxed as follows [7]:

$$\widehat{\mathbf{P}}_{u}[k,:] = \operatorname{softmax}\left[\left(\left(N+1-2k\right)\mathbf{s}_{u}-\mathbf{A}_{u}\mathbf{1}\right)/\tau\right], \quad (4)$$

where  $\tau$  is the temperature parameter, and  $\hat{\mathbf{P}}_u$  approaches a permutation matrix (i.e., Eq. (3)) when  $\tau \to 0^+$ . Intuitively,  $\hat{\mathbf{P}}_u[k,:]$ corresponds to a soft ranking of the items, and each entry of  $\hat{\mathbf{P}}_u[k,:]$ indicates the probability that the corresponding item will be the *k*-th ranked item. Since  $\hat{\mathbf{P}}_u$  is continuous everywhere and differentiable almost everywhere w.r.t. the elements of  $\mathbf{s}_u$ , we can define a differentiable Hit, as we elaborate below.

First, note that the *k*-th row of the deterministic permutation matrix  $P_u[k, :]$  (i.e., Eq. (3)) is equal to the one-hot vector of the *k*-th ranked item. Thus, we can reformulate the Hit function (i.e., Eq. (2)) as follows:

$$\operatorname{Hit}_{u}(k) = \mathbf{P}_{u}[k,:] \cdot \mathbf{Y}_{t}[u,:]^{\mathsf{T}},$$
(5)

where  $Y_t[u, i] = 1$  if the item *i* is a ground-truth item, and 0 otherwise. Finally, by replacing  $P_u[k, :]$  (Eq. (3)) with  $\widehat{P}_u[k, :]$  (Eq. (4)), we formally define a differentiable Hit@k (DH) as follows:

$$DH(\mathcal{W}_t, C_u; k) = \widehat{P}_u[k, :] \cdot Y_t[u, :]^{\mathsf{T}},$$
(6)

where  $W_t$  is the latest model parameters and  $C_u$  is the candidate items set for user u. Note that by using the differentiable Hit as a building block, an approximation of various top-k recommendation metrics can be formulated as follows:

Recommendation Metric = 
$$\sum_{k=1}^{K} w \operatorname{DH}(\mathcal{W}_t, \mathcal{C}_u; k),$$
 (7)

where *w* varies depending on the specific recommendation metric, e.g.,  $w = 1/|\mathcal{G}_u|$  for Recall@*K* and w = 1/K for Precision@*K*.

For the sake of model simplicity and efficient training, we set w = K = 1 in FADE, which can be viewed as using a differentiable Hit@1, i.e., DH( $W_t$ ,  $C_u$ ; 1) (see Eq. (6)), as a surrogate of the measure of recommendation quality for a user. While this differentiable Hit@1 used for training encourages the top-1 recommendation, it could potentially benefit more relaxed Hit@k-based metrics in the evaluation stage. We will empirically demonstrate that these settings consistently yield effective results across various recommendation metrics that rely on the Hit function, including Recall, F1, and NDCG. Lastly, we will denote DH( $W_t$ ,  $C_u$ ; 1) as DH( $W_t$ ,  $C_u$ ) in the subsequent parts of this paper for simplicity.

*Remarks.* Note that existing learning-to-rank methods, such as pairwise [24] or listwise objectives [2, 9], might also be able to solve the problem of non-differentiability of ranking-based metrics. However, they have major drawbacks compared with our proposed differentiable Hit: (1) pairwise methods are insufficient for capturing top-k recommendations, while (2) listwise methods, though better at modeling ranking, suffer from high computational complexity [18] as they usually consider the entire item list or permutation of items (e.g., modeling permutations with Plackett-Luce distribution [31]).

#### 3.2 Negative Sampling

Constructing the relaxed permutation matrix  $\widehat{\mathbf{P}}_u$  in Eq. (4) incurs a quadratic time-complexity with respect to the size of the candidate item set, i.e.,  $O(N^2)$ , caused by computing  $\mathbf{A}_u \in \mathbb{R}^{N \times N}$ . This becomes intractable when considering the whole item set  $\mathcal{I}_{:t}$ . To address the time-efficiency challenge, we utilize negative sampling to reduce the computational cost of computing DH.

We construct a much smaller subset of items via negative sampling. Specifically, for each interaction from user u to item i in a mini-batch of  $\mathcal{E}_t$ , we sample  $\mu$  negative items, which have never been interacted with user u, and construct a candidate item set  $C_u$ with  $\mu$  sampled negative items and the *single* ground-truth item i. With  $\mu \ll |\mathcal{I}_t|$ , where  $\mu$  is a small constant, the computational complexity of computing DH for  $\mathcal{D}_t$  shrinks from  $O(|\mathcal{U}_t||\mathcal{I}_t|^2)$  to  $O(|\mathcal{E}_t|\mu^2)$ .

#### 3.3 Fairness Loss

We design our fairness loss for reducing performance disparity between the advantaged (a = 0) and disadvantaged (a = 1) user groups. Based on DH and the candidate item set,  $C_u$ , sampled for each user interaction in  $\mathcal{E}_t$ , the differentiable performance disparity

Alg	orithm I FADE: Fair Dynamic Recommender					
1:	Training procedure at time period <i>t</i> ;					
2:	<b>Input:</b> Model parameters $\hat{W}_{t-1}$ , hyperparameters $\lambda$ , $\tau$ , $\mu$ , sen					
	sitive attribute <i>a</i> , incoming dataset $\mathcal{D}_t = {\mathcal{U}_t, \mathcal{I}_t, \mathcal{E}_t, \mathbf{Y}_t}$					
3:	<b>Output:</b> Updated model parameters $W_t$					
4:	$\mathcal{W}_t \leftarrow \mathcal{W}_{t-1};$					
5:	for epoch do					
6:	for mini-batch $\mathcal{B}_l$ obtained from $\mathcal{E}_t$ do					
7:	$\mathcal{L}_{\text{rec}} \leftarrow 0;  \mathcal{L}_{\text{fair}} \leftarrow 0;$					
8:	<b>for</b> user-item interaction $(u, i) \in \mathcal{B}_l$ <b>do</b>					
9:	$\mathcal{L}_{\text{rec}} \leftarrow \mathcal{L}_{\text{rec}} + \mathcal{L}_{\text{rec}}((u, i));$					
10:	$C_u \leftarrow \text{single positive item } i \text{ and sampled } \mu \text{ number}$					
	of negative items;					
11:	Compute $DH(C_u; W_t)$ based on Eq. (7);					
12:	if $a = 0$ then					
13:	$DH_0 \leftarrow DH_0 + DH(C_u; \mathcal{W}_t);$					
14:	else if $a = 1$ then					
15:	$DH_1 \leftarrow DH_1 + DH(C_u; W_t);$					
16:	end if					
17:	end for					
18:	$PD^{diff} \leftarrow \frac{DH_0}{ \{\mathcal{B}_l a=0\} } - \frac{DH_1}{ \{\mathcal{B}_l a=1\} }$ based on Eq. (8);					
19:	Compute $\mathcal{L}_{\text{fair}}$ based on Eq. (9);					
20:	$\mathcal{L} = \mathcal{L}_{rec} + \mathcal{L}_{fair};$					
21:	Update $\mathcal{W}_t$ based on $\mathcal{L}$ via gradient-descent;					
22:	end for					
23:	end for					

24: return  $W_t$ 

PD<sup>diff</sup> is defined as follows.

$$PD^{diff}(\mathcal{D}_{t}) = \frac{1}{|\{\mathcal{E}_{t}|a=0\}|} \sum_{e_{u,i} \in \{\mathcal{E}_{t}|a=0\}} DH(C_{u}; \mathcal{W}_{t}) - \frac{1}{|\{\mathcal{E}_{t}|a=1\}|} \sum_{e_{u,i} \in \{\mathcal{E}_{t}|a=1\}} DH(C_{u}; \mathcal{W}_{t}),$$
(8)

which is an approximation of  $PD_t$  in Eq. (1) on the sampled item set. Then, based on the  $PD^{diff}$ , we propose the following fairness loss:

$$\mathcal{L}_{\text{fair}}(\mathcal{D}_t) = -\log\left(\sigma\left(-\operatorname{PD}^{\text{diff}}(\mathcal{D}_t)\right)\right),\tag{9}$$

where  $\sigma(\cdot)$  is the sigmoid function. Intuitively, this loss aims to benefit the disadvantaged user group (*a*=1) over the advantaged user group (*a*=0) by explicitly minimizing the value of PD<sup>diff</sup>. By doing so, the goal is to reduce the PD, which tends to be positive due to underlying biases present in real-world user-item interaction networks, such as imbalanced numbers of entities or training data, as well as biases introduced by training algorithms.

### 3.4 Overall Loss with Fine-Tuning Strategy

With the proposed fairness loss, FADE fine-tunes the model parameters incrementally over time only with the new data  $\mathcal{D}_t$  collected at time period *t*, for the sake of time efficiency, by optimizing the following loss functions:

$$\mathcal{L}(\mathcal{D}_t) = \mathcal{L}_{\text{rec}}(\mathcal{D}_t) + \lambda \mathcal{L}_{\text{fair}}(\mathcal{D}_t), \tag{10}$$

where  $\mathcal{L}_{\text{rec}}$  is for improving the overall recommendation performance,  $\mathcal{L}_{\text{fair}}$  (i.e., Eq. (9)) is for regularizing the performance disparity between the disadvantaged and advantaged groups, and  $\lambda$ 

is the scaling parameter for controlling the trade-off between the overall performance and the fairness. Although in this paper, we use the popular Bayesian personalized ranking (BPR) loss as  $\mathcal{L}_{rec}$ , this loss can be any differentiable recommendation loss that can be optimized by a gradient descent algorithm.

Finally, by jointly optimizing  $\mathcal{L}_{rec}$  and  $\mathcal{L}_{fair}$  in an end-to-end fashion to fine-tune the model parameters for each time period, we can dynamically reduce the performance disparity, which may otherwise worsen as the optimization continues, while simultaneously enhancing the overall recommendation performance over time.

It should be noted that the value of PD varies depending on the specific performance metric used. Thus, it is necessary to train FADE to adapt to different metrics accordingly. We will empirically show that despite being based on the same differentiable Hit, FADE can effectively adapt to each metric by optimizing the scaling parameter  $\lambda$  in Eq. (10).

#### 3.5 Complexity Analysis

We argue that our fairness loss adds only a constant amount of complexity to most existing recommendation models. Assuming we employ MF-BPR [24] as the base recommendation model with user/item embeddings of dimensionality *d*, the time complexity of  $\mathcal{L}_{rec}(\mathcal{D}_t)$  is  $O(|\mathcal{E}_t|nd)$ , where *n* represents the number of negative items.

Regarding our fairness loss, for each user interaction, computing the score vector  $\mathbf{s}_u$  has a time complexity of  $O(\mu d)$ , and computing DH incurs  $O(\mu^2)$  as discussed in Section 3.2. As a result, the time complexity of  $\mathcal{L}_{\text{fair}}(\mathcal{D}_t)$  becomes  $O(|\mathcal{E}_t|(\mu^2 + \mu d))$ , which can be approximated as  $O(|\mathcal{E}_t|\mu d)$  since  $\mu \ll d$ . Therefore, the time complexity of the recommendation loss,  $\mathcal{L}_{\text{rec}}(\mathcal{D}_t)$ , and the fairness loss,  $\mathcal{L}_{\text{fair}}(\mathcal{D}_t)$ , are comparable.

The aforementioned considerations can be extended to other (embedding-based) recommendation models, including neural-netbased models. Additionally, it is worth noting that several existing fairness-aware methods [1, 28, 30] rely on adversarial learning techniques, which can lead to higher time-complexity compared to our fairness loss; we empirically observed that FADE runs about 10x faster than one of the adversarial-based approaches.

### 4 EXPERIMENT

We design experiments to answer the following key research questions (RQs):

- **RQ1.** How effective is FADE in balancing overall performance and user-side fairness in dynamic a setting?
- **RQ2.** How time-efficient is FADE?
- RQ3. How sensitive is FADE to its hyperparameters?

#### 4.1 Experimental Settings

**A** – **Dataset.** For experiments, we use the Movielens-1M dataset containing 1 million ratings on 3, 883 movies by 6, 040 users at different timestamps.<sup>3</sup> The sensitive attribute *a* is determined by the gender of each user, with male assigned as a = 0 (i.e., advantaged) and female as a = 1 (i.e., disadvantaged) due to the following observation: In this dataset, the population is predominantly male, with 4,328 male users and 1,708 female users [21]. Furthermore,

<sup>3</sup>https://grouplens.org/datasets/movielens/1m/

there are 616,003 and 202,941 training instances (i.e., items) for male and female users, respectively. Following previous works in recommender systems [12, 35], we binarize the 5-star ratings by assigning Y[u, i] = 1 if user *u* gives movie *i* a rating greater than 2, and Y[u, i] = 0 otherwise.<sup>4</sup>

To simulate the dynamic settings defined in Section 2, we first sort the interactions in the dataset  $\mathcal{D}$  in chronological order and then divide them into pre-training and dynamic-update data in a ratio of 6:4. We then split the dynamic-update data into 10 periods, each containing an equal number of interactions. This process yields { $\mathcal{D}_0, \mathcal{D}_1, \ldots, \mathcal{D}_T$ }, where T = 10 and  $\mathcal{D}_0$  corresponds to the pre-training data.

**B** – **Compared methods.** To ensure that the effectiveness of FADE is independent of the base recommender system used, we use two base system including Matrix Factorization (MF) and Neural Collaborative Filtering (NCF), both with the Bayesian Personalized Ranking (BPR) loss [24]. In this setup, we aim to validate the effectiveness of our *fine-tuning strategy* and the *fairness loss* used in FADE in ensuring high overall performance and user-side fairness over time. To establish a benchmark, we compare FADE with the following combinations:

- RETRAIN: Fully retraining the model using the accumulated data  $\mathcal{D}_{:t}$  at each time period *t*, without the fairness loss. Fully retraining refers to training the model with the entire dataset from scratch when new data is collected.
- FADE-RETRAIN: Fully retraining the model with the fairness loss in Eq.(9) (i.e., FADE utilizing full-retraining instead of fine-tuning).
- FINETUNE: Fine-tuning the model based on the current data  $\mathcal{D}_t$  at each time period *t*, without the fairness loss (i.e., FADE without the fairness loss).
- PRE-TRAIN: The static model pre-trained on  $\mathcal{D}_0$  without the fairness loss

In addition, we also compare FADE with the other fairness-aware competitors. For a fair comparison, we implemented these methods using a fine-tuning strategy. The competitors we consider are:

- REC: This method involves using a predicted recommendation score as a surrogate measure of recommendation quality in the fairness loss (i.e., Eq. (9)) of FADE, instead of the differentiable Hit. It can be considered as a variant of [33] that is implemented with a fine-tuning strategy.
- ADVER: This method is based on adversarial learning technique proposed in [20]. It is originally designed to filter out sensitive attributes from user embeddings, but its primary focus is not on reducing the performance disparity among different user groups.

**C** – **Evaluation tasks.** To evaluate the overall recommendation performance and the disparity, we design the dynamic recommendation task. Specifically, given the model trained up until time period *t*, the model is tested by recommending items for the remaining time periods with the test set  $\mathcal{D}_t^{\text{test}} = \mathcal{D}_{t+1} \cup \cdots \cup \mathcal{D}_T$ . Note that the data at the last time period,  $\mathcal{D}_T$ , is only used for testing and not for the training purpose.

<sup>&</sup>lt;sup>4</sup>This allows us to treat the ratings as implicit feedback, which is an actively studied and practically relevant research topic, given its abundance and ease of collection in real-world scenarios. Note that our models can be easily adjusted to handle explicit feedback data by replacing the recommendation loss with a suitable loss function, such as the mean squared error loss.



Figure 2: The trade-off between overall recommendation performance (indicated on the x-axis) and performance disparity (PD) (indicated on the y-axis) of six compared methods and FADE. Using our fairness loss results in the significant reduction of PD in all cases, while not harming overall performance considerably. Additionally, our fairness loss are consistently more effective in mitigating PD than the other fairness-aware losses.



Figure 3: The trend of the performance disparity (PD). Without the fairness loss, the PD is relatively high and often increase, while with the fairness loss, particularly in FADE, the PD tends to remain relatively low.

We adopt a similar approach as previous studies [13, 19], where we randomly sample 100 items that the user has not interacted with as negative samples. These negative samples, along with the ground-truth items, are used for evaluation.

**D** – **Implementation details.** For each user-item pair in the training dataset, we randomly sample four items that the user has never interacted with as negative samples for BPR loss, for all compared methods. The learning rate is set to 0.001. We apply the Adam optimization algorithm [15] to update the model parameters.

The hyperparameters of each method have been carefully tuned. Here are the specific settings for ADVER: The adversarial coefficient  $\gamma$  is selected from the suggested range [1, 10, 20, 50], as mentioned in their paper [20]. The filter modules are two-layer neural networks with the LeakyReLU activation. The discriminators are multi-layer perceptrons with 7 layers, LeakyReLU activation function, and a dropout rate of 0.3. The discriminators are trained for 10 steps.

For FADE and FADE-RETRAIN based on both MF and NCF, we set  $\tau = 8$  and  $\mu = 4$ , which consistently show excellent tradeoff between performance and disparity across all metrics and base recommendation models. The parameter  $\lambda$  is selected within a range of 0 to 3 for FADE, FADE-RETRAIN, and REC based on MF, while it is chosen within a range of 0 to 14 for those based on NCF. We use a random seed to control the randomness for better reproducibility. **E** – **Software and Hardware configuration.** All codes are programmed in Python 3.6.9 and PyTorch 1.4.0. All experiments are performed on a Linux server with 2 Intel Xeon Gold 6240R CPUs and 4 Nvidia Tesla V100 SXM2 GPUs with 32 GB memory.

#### 4.2 Effectiveness Results (RQ1)

**A** – **Effectiveness in Overall Performance.** To evaluate the recommendation quality, we compare the overall performance, averaged across each dynamic update data, of the following five methods: PRE-TRAIN, RETRAIN, FADE-RETRAIN, FINETUNE, and FADE. The results are shown in Figure 2.

First, compared to PRE-TRAIN, the four other methods, including FADE, yield increased overall performance for all metrics in both base recommendation models, indicating that the new data is indeed useful for improving overall performance of the models over time. Ensuring User-side Fairness in Dynamic Recommender Systems

Table 2: Efficiency comparison on the running time (seconds).

Madala	Full-retrain-based		Fine-tune-based		
Models	Retrain	FADE-RETRAIN	Adver	Finetune	FADE (Ours)
MF	1575.63	1698.27	50.82	1.91	4.84
NCF	1793.53	2273.25	53.74	5.20	8.88

Second, there are only marginal performance gaps between FINE-TUNE (fine-tuning without fairness consideration) and FADE (finetuning with fairness consideration) in all cases, and similar results are observed for RETRAIN and FADE-RETRAIN. Specifically, on average across all cases, FADE exhibits a modest decrease of 1.42% compared to FINETUNE; FADE-RETRAIN even exhibits a slight increase of 0.40% compared to RETRAIN. The results suggest that incorporating our fairness loss does not significantly compromise the overall performance of the recommendation methods, including FADE. This decrease in overall performance can be because FADE improves the performance of the disadvantaged group while reducing the performance of the advantaged group, in all cases. For example, when using FADE in NCF, the NDCG@20 for the advantaged group decreases from 0.720 to 0.710, while for the disadvantaged group, it increases from 0.687 to 0.709, reducing PD from 0.033 to 0.001, compared to FINETUNE (i.e., FADE without the fairness loss).

Third, FINETUNE and FADE outperform RETRAIN and FADE-RETRAIN, respectively, in most cases, since fine-tuning can enable the models to focus more on the current data at each time period and to adapt to the latest user interests, leading to an improved recommendation quality in the dynamic setting.

**B** – Effectiveness in Ensuring User-side Fairness. First, to verify that FADE effectively alleviates the performance disparity (PD), we compare the PDs of the aforementioned five methods, including FADE. As shown in Figure 2, the PDs of RETRAIN and FINETUNE are higher than that of PRE-TRAIN across all metrics in MF, meaning that learning with new data introduces a disadvantage for the disadvantaged group compared to the advantaged group. However, in NCF, the PDs of RETRAIN and FINETUNE are comparable to that of PRE-TRAIN across all metrics. We suspect this may be because the PD of NCF-based PRE-TRAIN is already significantly high, which means that its model parameters already capture the underlying bias in the dataset.

However, FADE-RETRAIN and FADE yield significantly lower PDs compared to RETRAIN and FINETUNE, respectively, consistently in *all* cases. Specifically, *on average across all cases*, FADE-RETRAIN and FADE yield 95.07% and 94.59% lower PDs than those of RETRAIN and FINETUNE, respectively. The results indicate that our fairness loss indeed helps reduce the performance disparity created by capturing both historical data and newly collected data over time.

Furthermore, we examine how the disparities change over time with FADE and the three methods, RETRAIN, FADE-RETRAIN, FINE-TUNE, as shown in Figure 3. We can see that without the fairness loss (RETRAIN/FINETUNE), the PDs tend to persist relatively high over time in all cases. Also, they might even increase over time w.r.t. Recall and F1. However, when augmented with the fairness loss (FADE-RETRAIN/FADE), the PDs tend to remain relatively low and stable over time.

**C** – **Comparison with Fairness-Aware Competitors.** We further compare FADE with the two fairness-aware competitors, REC and

Conference acronym 'XX, June 03-05, 2023, Woodstock, NY

ADVER, to validate FADE's superiority in balancing recommendation quality and performance disparity, in Figure 2. Note that all of those methods are implemented based on fine-tuning strategy for fair comparison. First, compared to the method without fairness regularization (i.e., FINETUNE), all methods show a sacrifice in overall performance due to fairness considerations across all metrics in both base recommendation models. However, regarding the performance disparity, FADE consistently outperforms the competitors in *all* cases, yielding PDs that are closest to zero.

The superiority of FADE over REC, in terms of PD, indicates that the predicted recommendation scores of both MF and NCF are less effective as proxies for measuring recommendation quality when compared to the differential Hit (i.e., Eq. (7)) used in our fairness loss. This shows that our fairness loss is well-designed to address disparity. Also, ADVER leads to a significant decrease in performance without significantly reducing the performance disparity. This is because ADVER is not designed to reduce the difference in performance between user groups; instead, its focus is on removing information related to sensitive attributes from user representations.

#### 4.3 Efficiency Results (RQ2)

To verify that FADE is highly time-efficient, we compare them with full-retraining based methods (i.e., RETRAIN and FADE-RETRAIN) as well as fine-tuning based methods (i.e., FINETUNE and ADVER), in both MF and NCF base models, and the corresponding results are shown in Table 2. Note that each result represents the average running time of a model across nine dynamic update data at each time period (i.e.,  $\{\mathcal{D}_1, \ldots, \mathcal{D}_9\}$ ), excluding the pretraining data  $\mathcal{D}_0$ .

Regarding the MF-based methods, we have three observations. Firstly, FINETUNE/FADE achieve approximately 824/350 times faster running time compared to RETRAIN/FADE-RETRAIN, indicating that the fine-tuning strategy employed in FADE enables the models to achieve high time efficiency, making them ideal for dynamic settings. Secondly, FADE-RETRAIN/FADE exhibit approximately 1.08/2.53 times slower running time in comparison to RETRAIN/FINETUNE. This suggests that the additional computational cost introduced by our fairness loss is not significant. Lastly, FADE demonstrates a time efficiency around 10.5 times faster than ADVER, highlighting the lightweight design of our fairness loss compared to the existing fairness-aware loss based on adversarial learning techniques. Regarding the NCF-based models, the results are similar.

#### 4.4 Hyperparameter Analysis (RQ3)

We investigate the sensitivity of FADE to four hyperparameters: (1) the scaling parameter for the fairness loss  $\lambda$ , (2) the number of epochs of dynamic updates, (3) the temperature parameter  $\tau$ , and (4) the number of negative candidate items  $\mu$ . All of the corresponding figures illustrate the performance of the advantaged and disadvantaged user groups for different values of these hyperparameters. Due to space limitation, we omit the results of NCF-based methods, which demonstrate a similar trend to those of the MF-based methods.

**A** – **Effect of**  $\lambda$  (Scaling Parameter for the Fairness Loss). Figure 4 shows that, for all metrics, the performance of the advantaged group tend to decrease while that of the disadvantaged group tend

Conference acronym 'XX, June 03-05, 2023, Woodstock, NY



Figure 4: The effect of the scaling parameter  $\lambda$  on the performance of the advantaged and disadvantaged groups. As  $\lambda$  increases, the performance of the advantaged group tend to decrease while that of the disadvantaged group tend to increase, indicating that  $\lambda$  effectively regulates the trade-off between the overall recommendation quality and the disparity in quality between two user groups.



Figure 5: The effect of the three hyperparameters, namely (a) the number of epochs of dynamic updates, (b) the temperature parameter  $\tau$ , and (c) the number of negative candidate items  $\mu$ , on the performance of the advantaged and disadvantaged user groups.

to increase as  $\lambda$  increases. We can see that the decrease for the advantaged group is slightly faster than the increase for the disadvantaged group, leading to an overall performance reduction. Additionally, the performance disparity between the two user groups steadily reduces until  $\lambda$  reaches an optimal value, which varies depending on the specific metric used. Note that a  $\lambda$  value of zero corresponds to no fairness regularization (i.e., FINETUNE). The results indicate that  $\lambda$  effectively controls the trade-off between overall performance and performance disparity, allowing for a customizable balance.

**B** – Effect of the Number of Epochs of Dynamic Updates. Recall that in our dynamic learning scenario, given the model pretrained with historical data in an offline manner, FADE incrementally fine-tunes the model parameters with new data at each time period. In this context, we study the impact of the training epoch at each dynamic update phase on the model's performance. Figure 5-(a) shows that the performance of both user groups increases as the number of epochs increases until reaching a peak around epoch 10. Subsequently, the performance gradually declines with further increases in the number of epochs. Notably, this pattern is consistent across different models with or without fairness regularization, such as FINETUNE and FADE.

We suspect that setting the number of epochs too low may result in the model not learning enough from the current data. Conversely, when the number of epochs is set too high, the model is prone to overfitting on the current data and potentially losing the knowledge acquired from historical data. We argue that this phenomenon is well-suited for the dynamic environment, as setting a low value for the number of epochs results in high time efficiency. Also, the similar trend has been observed in the previous works on dynamic/online recommender systems [8].

**C** – **Effect of**  $\tau$  (**Temperature Parameter in the Fairness Loss**). As described in Section 3.1,  $\tau$  represents the temperature parameter

of Gumbel-Softmax used to generate the relaxed permutation matrix  $\widehat{\mathbf{P}}_u$  for each user u. Higher values of  $\tau(> 0)$  result in smoother rows in the relaxed permutation matrix,  $\widehat{\mathbf{P}}_u[i,:]$ .

Figure 5-(b) shows that the performance of both user groups increases until  $\tau = 3$ , and then stabilizes. These findings indicate that FADE is not highly sensitive to  $\tau$ , consistently delivering excellent performance for both user groups as long as  $\tau$  is not too small. Notably, when  $\tau$  is set below 2, the performance of the advantaged group significantly decreases, which is due to the excessive penalization by the fairness regularization.

This phenomenon can be explained as follows: When  $\tau$  is set too low, the Gumbel-Softmax distribution becomes sharp, resulting in a overly deterministic decision-making process for the model, i.e.,  $\hat{\mathbf{P}}_u[i,:]$  will be close to the one-hot vector of the *i*-th ranked item. As a result, the entry corresponding to the positive item in that vector is likely to have an extremely small value, from the initial phase of training, potentially hindering the effectiveness of the fairness regularization. However, as  $\tau$  gradually increases, the distribution becomes smoother, enabling the model to explore a wider range of options and potentially discover better solutions, i.e., each element of  $\hat{\mathbf{P}}_u[i,:]$  will represent well the probability that the corresponding item will be the *i*-th ranked item.

**D** – **Effect of**  $\mu$  (the Number of Negative Candidate Items).  $\mu$  represents the number of negative items in the candidate set  $C_u$  for each user interaction when computing the differentiable Hit, which is then used to quantify the differentiable performance disparity used as fairness regularization during the optimization process.

Figure 5-(c) shows that the performance of both user groups tend to slightly decrease as  $\mu$  increases. The possible explanation for this phenomenon is that when the number of negative items is low, the model focuses more on the positive items, which are likely to be more relevant and lead to higher accuracy. Also, as the number of Ensuring User-side Fairness in Dynamic Recommender Systems



Figure 6: The effect of retraining at a certain time period on the overall performance and performance disparity (PD). Conducting retraining at a certain point may effectively prevent FADE from accumulating errors caused by excessive focus on the latest data; furthermore, it has minimal influence on the PD of FADE.

negative items increases, there is a higher chance of including less suitable items for negative samples, which can slightly degrade the overall accuracy.

Regardless, the results suggest that setting a low value for  $\mu$  is beneficial in terms of both recommendation performance and time-efficiency, making it advantageous in dynamic environments.

#### 4.5 Discussion: Potential Needs for Retraining

We further investigate the performance and disparity of full-retraining and fine-tuning based fairness-aware models over time, as well as the potential need for retraining at a certain point. To conduct this analysis, we compare the performance of FADE-RETRAIN, FADE, and FADE that undergoes retraining at time period 5 and continues with fine-tuning, denoted by FADE-5. They are all based on MF.

Figure 6 illustrates that the overall performance of FADE remains consistently higher than that of FADE-RETRAIN until time period 5. However, beyond that point, the performance of FADE starts to decline. On the other hand, when retraining is performed at time period 5 followed by fine-tuning (i.e., FADE-5), the performance either matches or exceeds that of FADE-RETRAIN. One possible explanation for this observation is as follows: When the model undergoes prolonged fine-tuning without retraining, errors, caused by forgetting historical knowledge, can accumulate and become more significant compared to the model that undergoes retraining. This accumulation of errors may lead to a decrease in performance over time.

Regarding the performance disparity, Figure 6 reveals that the PDs of FADE and FADE-RETRAIN tend to align until time period 7. However, beyond that point, FADE exhibits significantly lower PD values compared to FADE-RETRAIN. Interestingly, when retraining is performed at time period 5 (i.e., FADE-5), the resulting PD aligns with that of FADE and does not increase as observed with FADE-RETRAIN, meaning that the retraining has minimal influence on the PD of FADE.

It is worth noting that we utilize FADE with an epoch of dynamic update set to 20 for this study. This differs from the FADE used in the main experiments, which has an epoch set to 10. We exclude the latter in this case study because it consistently achieves higher overall performance than FADE-RETRAIN, making it unsuitable for this specific investigation.

### **5 RELATED WORK**

Fair recommender system. As recommender systems typically involve at least two stakeholders (e.g., user and items), there exist different fairness demands (e.g., user-side, item-side, or multi-side fairness). Usually, user-side fairness refers to ensuring fairness w.r.t. the recommendation quality for different users, and item-side fairness focuses on the exposure opportunity of items in recommendations; two-side fairness is about how to balance these two fairnesses. In this work, we focus on user-side group-fairness. As described in Section 1, the existing re-ranking methods [5, 19] face challenges in the dynamic setting: (1) non-differentiable fairness-constraint, and (2) high time-complexity. Specifically, they use a general recommender to generate base ranking lists, and then re-rank them under the fairness constraint to generate new fair ranking lists. However, it is time-inefficient as the optimization problem corresponds to a 0-1 integer programming problem. Moreover, their non-differentiable fairness constraint hinders gradient-based optimization. Another line of research [1, 28, 30] adopts adversarial functions to learn fair representations of users that are independent of sensitive attributes of users. However, their formulations do not explicitly address reducing performance disparity, which is the main focus our work.

Dynamic recommender systems. In practice, it is essential to periodically retrain the recommender systems with new data to capture the current interests of users. While fully retraining the model with the entire dataset when new data is collected is a natural solution, this approach can be time-inefficient. An alternative solution is to fine-tune the model parameters over time using only the new data, which is referred to as dynamic/online recommender systems in the literature [4, 8, 13, 22, 25, 34]. To efficiently/effectively learn from relatively sparse new data, several methods have been proposed based on reweighting either (1) the impact of each user-item interaction [8, 25] or (2) that of each model parameter [4, 22, 34]. The formal approach involves adjusting the importance of each new user-item interaction when using it to fine-tune the model parameters, while the latter approach controls how much each model parameter should be fine-tuned based on new data. [13] utilizes both approaches. One unique advantage of the fairness loss in FADE is that it can be easily applied to any existing dynamic recommender systems optimized by the gradient-based algorithms.

Dynamic fairness in recommender system. There are a number of works on dynamic fairness in several applications of graph mining, including individual fairness in dynamic financial networks [26] and dynamic fairness in node representation learning [16]. However, recommender systems differ from these typical graph mining applications in that they involve multiple stakeholders within the system. Despite this difference, most existing works on fairness in dynamic/online recommender systems primarily focus on item-side fairness [6, 23, 36]. These approaches typically aim to address exposure fairness among items in the recommendations. For example, [36] investigates popularity bias in dynamic recommender systems, and [6] focuses on ensuring exposure fairness between popular and unpopular item groups in dynamic scenarios where the popularity of items can change over time. However, most of these existing works are not designed to tackle dynamic user-side fairness, particularly in terms of ensuring disparity in recommendation quality for different user groups separated by the sensitive

attributes such as gender or race. In this paper, our objective is to address this gap by focusing on dynamic user-side fairness.

### 6 CONCLUSION

In this paper, we study user-side fairness in the dynamic recommendation scenario. We point out two key challenges of the existing fairness-ensuring re-ranking method in the dynamic setting: (1) *non-differentiability* of the fairness measure and (2) *time-inefficiency* of the algorithm, both of which hinder dynamic learning and inference. To tackle these challenges, we propose FADE, an end-to-end framework based on our differentiable and lightweight fairness loss to dynamically reduce the performance disparity. With fine-tuning strategy, FADE incrementally updates the model parameters using only the new data collected at each time period. Through extensive experiments, we verify that FADE effectively and efficiently alleviates the performance disparity, while simultaneously improves the overall recommendation quality over time.

To our best knowledge, we are the first to study the problem of *dynamic user-side fairness* in recommender systems. Our discovery could encourage follow-up studies on utilizing other factors, such as temporal information, to further enhance fairness in dynamic settings, or on generalizing our proposed algorithm to address itemside or multi-sided fairness problems in recommender systems.

#### REFERENCES

- [1] Ghazaleh Beigi, Ahmadreza Mosallanezhad, Ruocheng Guo, Hamidreza Alvari, Alexander Nou, and Huan Liu. 2020. Privacy-aware recommendation with privateattribute protection using adversarial learning. In *Proceedings of the 13th International Conference on Web Search and Data Mining*. 34–42.
- [2] Zhe Cao, Tao Qin, Tie-Yan Liu, Ming-Feng Tsai, and Hang Li. 2007. Learning to rank: from pairwise approach to listwise approach. In Proceedings of the 24th international conference on Machine learning. 129–136.
- [3] Jiawei Chen, Hande Dong, Xiang Wang, Fuli Feng, Meng Wang, and Xiangnan He. 2020. Bias and debias in recommender system: A survey and future directions. ACM Transactions on Information Systems (2020).
- [4] Zhengxiao Du, Xiaowei Wang, Hongxia Yang, Jingren Zhou, and Jie Tang. 2019. Sequential scenario-specific meta learner for online recommendation. In Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. 2895–2904.
- [5] Zuohui Fu, Yikun Xian, Ruoyuan Gao, Jieyu Zhao, Qiaoying Huang, Yingqiang Ge, Shuyuan Xu, Shijie Geng, Chirag Shah, Yongfeng Zhang, et al. 2020. Fairnessaware explainable recommendation over knowledge graphs. In Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval. 69–78.
- [6] Yingqiang Ge, Shuchang Liu, Ruoyuan Gao, Yikun Xian, Yunqi Li, Xiangyu Zhao, Changhua Pei, Fei Sun, Junfeng Ge, Wenwu Ou, et al. 2021. Towards longterm fairness in recommendation. In Proceedings of the 14th ACM international conference on web search and data mining. 445–453.
- [7] Aditya Grover, Eric Wang, Aaron Zweig, and Stefano Ermon. 2019. Stochastic Optimization of Sorting Networks via Continuous Relaxations. In Proceedings of the International Conference on Learning Representations.
- [8] Xiangnan He, Hanwang Zhang, Min-Yen Kan, and Tat-Seng Chua. 2016. Fast matrix factorization for online recommendation with implicit feedback. In Proceedings of the 39th International ACM SIGIR conference on Research and Development in Information Retrieval. 549–558.
- [9] Shanshan Huang, Shuaiqiang Wang, Tie-Yan Liu, Jun Ma, Zhumin Chen, and Jari Veijalainen. 2015. Listwise collaborative filtering. In Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval. 343–352.
- [10] Rashidul Islam, Kamrun Naher Keya, Ziqian Zeng, Shimei Pan, and James Foulds. 2021. Debiasing career recommendations with neural fair collaborative filtering. In Proceedings of the Web Conference 2021. 3779–3790.
- [11] Eric Jang, Shixiang Gu, and Ben Poole. 2016. Categorical reparameterization with gumbel-softmax. arXiv preprint arXiv:1611.01144 (2016).
- [12] Piyush Kansal, Nitish Kumar, Sangam Verma, Karamjit Singh, and Pranav Pouduval. 2022. FLiB: Fair Link Prediction in Bipartite Network. In Advances in Knowledge Discovery and Data Mining: 26th Pacific-Asia Conference, PAKDD 2022, Chengdu, China, May 16–19, 2022, Proceedings, Part II. Springer, 485–498.

- [13] Minseok Kim, Hwanjun Song, Yooju Shin, Dongmin Park, Kijung Shin, and Jae-Gil Lee. 2022. Meta-Learning for Online Update of Recommender Systems. In Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 36. 4065–4074.
- [14] Diederik P Kingma and Jimmy Ba. 2011. Adam: A method for stochastic optimization. Computing in science & engineering 13 (2011), 22–30.
- [15] Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014).
- [16] Oyku Deniz Kose and Yanning Shen. 2023. Dynamic Fair Node Representation Learning. In ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 1–5.
- [17] Preethi Lahoti, Krishna P Gummadi, and Gerhard Weikum. 2019. ifair: Learning individually fair data representations for algorithmic decision making. In 2019 ieee 35th international conference on data engineering (icde). IEEE, 1334–1345.
- [18] Hyunsung Lee, Sangwoo Cho, Yeongjae Jang, Jaekwang Kim, and Honguk Woo. 2021. Differentiable ranking metric using relaxed sorting for top-k recommendation. IEEE Access 9 (2021), 114649–114658.
- [19] Yunqi Li, Hanxiong Chen, Zuohui Fu, Yingqiang Ge, and Yongfeng Zhang. 2021. User-oriented fairness in recommendation. In Proceedings of the Web Conference 2021. 624–632.
- [20] Yunqi Li, Hanxiong Chen, Shuyuan Xu, Yingqiang Ge, and Yongfeng Zhang. 2021. Towards personalized fairness based on causal notion. In Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval. 1054–1063.
- [21] Yanying Li, Xiuling Wang, Yue Ning, and Hui Wang. 2022. Fairlp: Towards fair link prediction on social network graphs. In Proceedings of the International AAAI Conference on Web and Social Media, Vol. 16. 628–639.
- [22] Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. 2017. Meta-sgd: Learning to learn quickly for few-shot learning. arXiv preprint arXiv:1707.09835 (2017).
- [23] Marco Morik, Ashudeep Singh, Jessica Hong, and Thorsten Joachims. 2020. Controlling fairness and bias in dynamic learning-to-rank. In Proceedings of the 43rd international ACM SIGIR conference on research and development in information retrieval. 429-438.
- [24] Steffen Rendle, Christoph Freudenthaler, Zeno Gantner, and Lars Schmidt-Thieme. 2012. BPR: Bayesian personalized ranking from implicit feedback. arXiv preprint arXiv:1205.2618 (2012).
- [25] Jun Shu, Qi Xie, Lixuan Yi, Qian Zhao, Sanping Zhou, Zongben Xu, and Deyu Meng. 2019. Meta-weight-net: Learning an explicit mapping for sample weighting. Advances in neural information processing systems 32 (2019).
- [26] Zixing Song, Yueen Ma, and Irwin King. 2022. Individual Fairness in Dynamic Financial Networks. In NeurIPS 2022 Workshop New Frontiers in Graph Learning.
- [27] Yifan Wang, Weizhi Ma, Min Zhang, Yiqun Liu, and Shaoping Ma. 2023. A survey on the fairness of recommender systems. ACM Transactions on Information Systems 41, 3 (2023), 1-43.
- [28] Chuhan Wu, Fangzhao Wu, Xiting Wang, Yongfeng Huang, and Xing Xie. 2021. Fairness-aware news recommendation with decomposed adversarial learning. In Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 35. 4462–4469.
- [29] Haolun Wu, Bhaskar Mitra, Chen Ma, Fernando Diaz, and Xue Liu. 2022. Joint multisided exposure fairness for recommendation. In Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval. 703–714.
- [30] Le Wu, Lei Chen, Pengyang Shao, Richang Hong, Xiting Wang, and Meng Wang. 2021. Learning fair representations for recommendation: A graph-based perspective. In *Proceedings of the Web Conference 2021*. 2198–2208.
- [31] Liwei Wu, Cho-Jui Hsieh, and James Sharpnack. 2018. Sql-rank: A listwise approach to collaborative ranking. In *International Conference on Machine Learning*. PMLR, 5315–5324.
- [32] Shiwen Wu, Fei Sun, Wentao Zhang, Xu Xie, and Bin Cui. 2022. Graph neural networks in recommender systems: a survey. *Comput. Surveys* 55, 5 (2022), 1–37.
- [33] Sirui Yao and Bert Huang. 2017. Beyond parity: Fairness objectives for collaborative filtering. Advances in neural information processing systems 30 (2017).
- [34] Yang Zhang, Fuli Feng, Chenxu Wang, Xiangnan He, Meng Wang, Yan Li, and Yongdong Zhang. 2020. How to retrain recommender system? A sequential metalearning method. In Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval. 1479–1488.
- [35] Yu Zheng, Chen Gao, Xiang Li, Xiangnan He, Yong Li, and Depeng Jin. 2021. Disentangling user interest and conformity for recommendation with causal embedding. In *Proceedings of the Web Conference 2021*. 2980–2991.
- [36] Ziwei Zhu, Yun He, Xing Zhao, and James Caverlee. 2021. Popularity bias in dynamic recommendation. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining. 2439–2449.
- [37] Lixin Zou, Long Xia, Zhuoye Ding, Jiaxing Song, Weidong Liu, and Dawei Yin. 2019. Reinforcement learning to optimize long-term user engagement in recommender systems. In Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. 2810–2818.