Understanding ProbLog as Probabilistic Argumentation

Francesca Toni Nico Potyka

Department of Computing Imperial College London, UK {ft, n.potyka}@ic.ac.uk Markus Ulbricht Department of Computer Science

Leipzig University, Germany mulbricht@informatik.uni-leipzig.de

Pietro Totis

Department of Computer Science KU Leuven, Belgium pietro.totis@kuleuven.be

ProbLog is a popular probabilistic logic programming language/tool, widely used for applications requiring to deal with inherent uncertainties in structured domains. In this paper we study connections between ProbLog and a variant of another well-known formalism combining symbolic reasoning and reasoning under uncertainty, i.e. probabilistic argumentation. Specifically, we show that ProbLog is an instance of a form of Probabilistic Abstract Argumentation (PAA) that builds upon Assumption-Based Argumentation (ABA). The connections pave the way towards equipping ProbLog with alternative semantics, inherited from PAA/PABA, as well as obtaining novel argumentation semantics for PAA/PABA, leveraging on prior connections between ProbLog and argumentation. Further, the connections pave the way towards novel forms of argumentative explanations for ProbLog's outputs.

1 Introduction

ProbLog [10, 20] is a popular probabilistic logic programming formalism, equipped with efficient tools in support of applications¹ In a nutshell, ProbLog programs amount to logic programs where facts may be equipped with probabilities. Thus, ProbLog can be naturally used for applications requiring to deal with inherent uncertainties, e.g. in neuro-symbolic settings to learn how to operate on images [18], object tracking [1], modelling metabolic networks[16], or synthesising inductive data models [7].

As a knowledge representation and reasoning (KRR) formalism, ProbLog can be seen as bringing together symbolic reasoning and reasoning under uncertainty. Thus, it makes sense to wonder how it relates to the family of KRR formalisms broadly referred to as *Probabilistic Argumentation* (PA) [14], which also bring together these two types of reasoning. Indeed, some existing works already study the connections between the two, in particular in the presence of inherent uncertainties, e.g. in neuro-symbolic settings with images [18]. Also, SMProbLog [23] extends ProbLog beyond the standard well-founded model semantics [11] towards the stable model semantics [12] so as to capture a form of PA. Further, [19] shows how the form of PA in [17] can be implemented in ProbLog. These existing works thus focus on showing how (variants of) Problog can obtain (forms of) PA. In this paper, instead, we focus on the opposite direction, specifically on whether (some forms of) PA can be used to obtain (variants of) ProbLog. In summary, our contribution is two-fold:

- We define a new instance of the well-known Assumption-based Argumentation (ABA) [3, 4] and use it to instantiate Probabilistic Abstract Argumentation (PAA) [9] (Section 3);
- We formally relate ProbLog and the proposed instance of PAA (Section 4).

This reinterpretation of ProbLog in argumentation terms opens new avenues (as discussed in Section 5).

R. Calegari, A. D'Avila Garcez, C. Dodaro, F. Fabiano, S. Gaggl, A. Mileo, (Eds.): ICLP 2023

EPTCS 385, 2023, pp. 183–189, doi:10.4204/EPTCS.385.18

© Toni, Potyka, Ulbricht & Totis This work is licensed under the Creative Commons Attribution License.

¹See https://dtai.cs.kuleuven.be/problog/.

S. Costantini, E. Pontelli, A. Russo, F. Toni,

2 Background

Logic Programs. A *logic program* (LP) is a set of (implicitly universally quantified) rules of the form $l_0 \leftarrow l_1, \ldots, l_m$, with $m \ge 0$, l_0 an atom (called the *head* of the rule) and each l_i (for $1 \le i \le m$) an atom or the *negation-as-failure not* a_i of an atom a_i . If m = 0 then the rule is called a *fact*. The *Herbrand base* of an LP is the set of all ground atoms obtained from the predicate, function/constant symbols in the LP.

ProbLog. The material in this section is adapted from [10, 20]. A *ProbLog program* is a set *R* of rules as in an LP together with a set *F* of *probabilistic facts* of the form $p :: l_0 \leftarrow$, where $p \in [0, 1]$ and l_0 is an atom that is not the head of any rule in *R*. The semantics of a ProbLog program is based on distribution semantics [21]: a ProbLog program $T = F \cup R$ defines a probability distribution over LPs $L = F' \cup R, F' \subseteq \{l \leftarrow | p :: l \leftarrow \in F\}$:

$$P(L|T) = \prod_{l \leftarrow \in F', p:: l \leftarrow \in F} p \cdot \prod_{l \leftarrow \notin F', p:: l \leftarrow \in F} (1-p)$$

Then, for a query q, the success probability for q, given T, is²

$$P_{s}(q|T) = \sum_{L=F'\cup R, F'\subseteq \{l\leftarrow |p::l\leftarrow \in F\}, \exists \theta: L\models q\theta} P(L|T)$$

for \models the chosen logic programming semantics: if *L* is a *positive LP* (without negation as failure), as in [21], then this is the least Herbrand model; otherwise, let it be the well-founded model [11].

Example 1. Consider the (propositional) LP amounting to the following rules:

 $a \leftarrow b, not c; \quad b \leftarrow; \quad d \leftarrow not d$

(referred to in short as ρ_1, ρ_2, ρ_3 , respectively). Then, for $R = \{\rho_1, \rho_3\}$ and $F = \{0.3 :: b \leftarrow\}$, $T = F \cup R$ is a ProbLog program. Given that $R \not\models a$ (as the well-founded model of R deems a, b, c false and dundecided) and $R \cup \{\rho_2\} \models a$ (as the well-founded model of $R \cup \{\rho_2\}$ deems a, b true, c false and dundecided), $P_s(a|T) = P(R \cup \{\rho_2\}|T) = 0.3$.

ProbLog typically assumes that the well-founded model of every LP $L \subseteq F' \cup R, F' \subseteq \{l \leftarrow | p :: l \leftarrow \in F\}$ is two-valued [10, 23], but the well-founded model may be three-valued [13], as in the example.

Abstract Argumentation. An Abstract Argumentation (AA) framework [8] is a pair (*Args*, *Att*) with *Args* the *arguments* and *Att* \subseteq *Args* \times *Args* the *attack* relation. AA frameworks can be equipped with various argumentative semantics [8], e.g. the *grounded* or *stable extensions* semantics [8], identifying sets of "acceptable arguments". For illustration, given AAF = (Args, Att) with $Args = \{\alpha, \beta\}$ and $Att = \{(\beta, \beta)\}$, the grounded extension of *AAF* is $\{\alpha\}$ and there is no stable extension of *AAF*.

Assumption-based argumentation (ABA). An *ABA framework* (as originally proposed in [3], but presented here following more recent accounts by [22, 4]) is a tuple $\langle \mathcal{L}, \mathcal{R}, \mathcal{A}, - \rangle$ where

- $\langle \mathcal{L}, \mathcal{R} \rangle$ is a deductive system, where \mathcal{L} is a *language* and \mathcal{R} is a set of *(inference)* rules of the form $s_0 \leftarrow s_1, \ldots, s_m$ $(m \ge 0, s_i \in \mathcal{L}, \text{ for } 1 \le i \le m)$;
- $\mathscr{A} \subseteq \mathscr{L}$ is a (non-empty) set of *assumptions*;
- is a total mapping from \mathscr{A} into \mathscr{L} , where \overline{a} is the *contrary* of *a*, for $a \in \mathscr{A}$.

²A query q is a possibly non-ground atom from the Herbrand base of T and θ denotes a possibly empty variable substitution.

Given a rule $s_0 \leftarrow s_1, \ldots, s_m$, s_0 is referred to as the *head* and s_1, \ldots, s_m as the *body*; if m = 0 then the body is said to be *empty*. *Flat ABA frameworks* are restricted so that assumptions are not heads of rules.

Differently from AA, where arguments and attacks are given, in flat ABA they are derived from the building blocks of ABA frameworks. Specifically, *arguments* are deductions of claims using rules and supported by assumptions, and *attacks* are directed at the assumptions in the support of arguments:

- an argument for (the claim) $s \in \mathcal{L}$ supported by $A \subseteq \mathcal{A}$ and $\mathcal{S} \subseteq \mathcal{R}$ (denoted $A \vdash_{\mathcal{S}} s$) is a finite tree with nodes labelled by sentences in \mathcal{L} or by $true^3$, the root labelled by *s*, leaves either *true* or assumptions in *A*, and non-leaves *s'* with, as children, the elements of the body of one rule in \mathcal{S} with head *s'* (*true* in the case of a rule with an empty body), and \mathcal{S} the set of all these rules;
- an argument $A_1 \vdash_{\mathscr{S}_1} s_1$ attacks an argument $A_2 \vdash_{\mathscr{S}_2} s_2$ iff $s_1 = \overline{a}$ for some $a \in A_2$.

Given an ABA framework $\langle \mathcal{L}, \mathcal{R}, \mathcal{A}, \overline{} \rangle$, let *Args* be the set of all arguments and *Att* be defined as above. Then (*Args*, *Att*) is an AA framework (that we refer to as *the AA framework for* $\langle \mathcal{L}, \mathcal{R}, \mathcal{A}, \overline{} \rangle$) and standard argumentative semantics for the latter can be used to determine, e.g., grounded extensions.⁴

LPs as Flat ABA Frameworks. Flat ABA can be instantiated to capture logic programming under several semantics [3], including the well-founded model [11] and the stable model semantics [12].

Example 2. The semantics of the LP $\{\rho_1, \rho_2, \rho_3\}$ from Example 1 can be captured by understanding it as a flat ABA framework $\langle \mathcal{L}, \mathcal{R}, \mathcal{A}, - \rangle$ with

- $\mathscr{R} = \{\rho_1, \rho_2, \rho_3\};$
- $\mathscr{L} = \{a, b, c, d, not \ a, not \ b, not \ c, not \ d\}$ (this is the Herbrand base of the LP together with all the negation as failure literals that can be constructed from its Herbrand base);
- $\mathscr{A} = \{ not \ a, not \ b, not \ c, not \ d \}$ (this is the set of all negation as failure literals in \mathscr{L});
- $\overline{not X} = X$ for all $X \in \{a, b, c, d\}$.

(Args, Att) can then be obtained from this ABA framework, with:

- $Args = \{\{not \ c\} \vdash_{\{\rho_1, \rho_2\}} a, \{\} \vdash_{\{\rho_2\}} b, \{not \ d\} \vdash_{\{\rho_3\}} d\} \cup \{\{not \ X\} \vdash_{\{\}} not \ X | X \in \{a, b, c, d\}\}$
- $Att = \{ (\{not \ c\} \vdash_{\{\rho_1, \rho_2\}} a, \{not \ a\} \vdash_{\{\}} not \ a), \quad (\{not \ d\} \vdash_{\{\rho_3\}} d, \{not \ d\} \vdash_{\{\}} not \ d), \\ (\{not \ d\} \vdash_{\{\rho_3\}} d, \{not \ d\} \vdash_{\{\rho_3\}} d), \quad (\{\} \vdash_{\{\rho_2\}} b, \{not \ b\} \vdash_{\{\}} not \ b) \}.$

 \mathscr{R} , as a LP, admits no stable model [12], and there is no stable extension [8] of this ABA framework. The well-founded model [11] of \mathscr{R} deems a, b true, c false and d undecided, and the grounded extension [8] of $\langle \mathscr{L}, \mathscr{R}, \mathscr{A}, \overline{-} \rangle$ accepts

$$\{\{\text{not } c\} \vdash_{\{\rho_1,\rho_2\}} a, \{\} \vdash_{\{\rho_2\}} b, \{\text{not } c\} \vdash_{\{\}} \text{not } c\}.$$

The two correspond in the sense that the atomic claims of accepted arguments in the grounded extension are true in the well-founded model, the negation as failure claims of accepted arguments are the complement of false atoms in the well-founded model, and no other atoms are true or false therein (and vice versa, i.e. every true atom and the negation as failure of every false atom in the well-founded model are claims of accepted arguments in the grounded extension, and no other arguments exist therein). Our results will leverage on the correspondence illustrated here (see [3] for formal results, including correspondences between other semantics of LPs and notions of extensions in flat ABA [3]).

³Here *true* stands for the empty body of rules.

⁴ABA semantics were originally defined in terms of sets of assumptions and attacks between them [3], but can be reformulated, for flat ABA frameworks, in terms of sets of arguments and attacks between them (see [22]), as given here.

Probabilistic Abstract Argumentation (PAA). The material in this section is adapted from [9] (focusing on a single juror). A *PAA framework* basically consists of an AA framework and a probability distribution assigning probabilities to subframeworks. Formally, it is a triple (AAF, PS, \Vdash) where:

- AAF = (Args, Att) is an AA framework;
- $PS = (\mathcal{W}, P)$ is a probability space, with \mathcal{W} the world set and P a probability distribution over \mathcal{W} ;

Given a possible world $w \in \mathcal{W}$, the *AAF wrt w*, denoted by $AAF_w = (Args_w, Att_w)$, is defined by restricting *AAF* to the arguments applicable in *w*. More formally, $Args_w = \{\alpha \in Args \mid w \Vdash \alpha\}$ and $Att_w = Att \cap (Args_w \times Args_w)$. We denote the grounded extension of AAF_w by $G(AAF_w)$. Then, the grounded probability of argument $\alpha \in Args$ is defined as follows:

$$Prob_G(\alpha) = \sum_{w \in \mathscr{W}: \alpha \in G(AAF_w)} P(w).$$

Intuitively, $Prob_G(\alpha)$ is the probability that α is accepted in a possible world (under the grounded extension semantics). PAA is a form of probabilistic argumentation under the constellation approach [14].

3 ProbLog-ABA and ProbLog-PAA

Several instances of (flat and non-flat) ABA have been studied [3, 5] (including the flat logic programming instance illustrated in Example 2 [3]). Here, we introduce the following (flat) instance, referred to as *ProbLog-ABA* since, as we will show, it is a first step towards capturing ProbLog programs as PAA.

Definition 1. A ProbLog-ABA framework is a flat ABA framework $\langle \mathscr{L}, \mathscr{R}, \mathscr{A}, \overline{} \rangle$ where

- \mathscr{R} is a (ground)⁵ LP;
- \mathscr{L} is a set of atoms and negation as failure literals; formally, for HB the Herbrand Base of \mathscr{R} and $HB^{not} = \{not \ p | p \in HB\}, \ \mathscr{L} = HB \cup HB^{not} \cup \{\chi\}, \text{ for a special symbol } \chi \notin HB \cup HB^{not};$
- $\mathscr{A} = HB^{not} \cup \mathscr{F}$, for some $\mathscr{F} \subseteq HB$;
- *for any not* $p \in \mathscr{A}$ *,* $\overline{not p} = p$ *; for any* $\phi \in \mathscr{F}$ *,* $\overline{\phi} = \chi$ *.*

Basically, ProbLog-ABA frameworks generalise the ABA frameworks capturing LPs by including additional assumptions (\mathscr{F}), all having the same contrary (χ) not occurring in the LP (\mathscr{R}). These additional assumptions can be seen as playing the role of abducibles in abductive logic programming [15]. They amount to the atoms in probabilistic facts in ProbLog programs $T = R \cup F$, as follows.⁶

Definition 2. *The* ProbLog-ABA framework corresponding to *T* is $\langle \mathcal{L}, \mathcal{R}, \mathcal{A}, \overline{} \rangle$ as in Definition 1 where $\mathcal{R} = R$ and $\mathcal{F} = \{l | (p :: l \leftarrow) \in F\}$.

We can then instantiate PAA with ProbLog programs, so that the AA framework component is drawn from the ProbLog-ABA framework corresponding to a given ProbLog program and the probability space is defined to mirror the probability distribution over LPs captured by the ProbLog program, as follows.

⁵This is in line with standard practices when studying the semantics of LPs: they are assumed to stand for the set of all their ground instances over their Herbrand universe.

⁶Given that we are focusing on semantics, in the remainder we assume that the ProbLog program is ground.

Definition 3. Let $\langle \mathscr{L}^T, \mathscr{R}^T, \mathscr{A}^T, \overset{-T}{} \rangle$ be the ProbLog-ABA framework corresponding to T, for $\mathscr{A}^T = HB^{not} \cup \mathscr{F}$, and let $AAF^T = (Args^T, Att^T)$ be the AA framework for $\langle \mathscr{L}^T, \mathscr{R}^T, \mathscr{A}^T, \overset{-T}{} \rangle$. Then, the PAA framework corresponding to T is (AAF^T, PS^T, \Vdash^T) where $PS^T = (\mathscr{W}^T, P)$ is the probability space with $\mathscr{W}^T = 2^{\mathscr{F}}$

•
$$\mathscr{W} = 2^{\circ}$$
,
• for $w \in \mathscr{W}^T$: $P(w) = \prod_{l \in w, p::l \leftarrow \in F} p \cdot \prod_{l \in \mathscr{F} \setminus w, p::l \leftarrow \in F} (1-p)$,
and \Vdash^T is such that, for $w \in \mathscr{W}^T$, $\alpha \in \operatorname{Args}^T$, $\alpha = A \vdash_{\mathscr{S}} s$: $w \Vdash^T \alpha \operatorname{iff} A \cap \mathscr{F} \subseteq w$.

In line with [9], we assume that the AA frameworks in PAA frameworks corresponding to ProbLog programs are finite. Given such a PAA framework, we can measure the grounded probability of arguments (as in standard PAA), as well as the *grounded probability of queries*, as follows.

Definition 4. Let T be a (ground) ProbLog program and (AAF^T, PS^T, \Vdash^T) be the PAA framework corresponding to T, for $AAF^T = (Args^T, Att^T)$ and $PS^T = (\mathcal{W}^T, P)$. Then, the grounded probability of (ground) query q is

$$Prob_G(q) = \sum_{w \in \mathscr{W}^T: \alpha \in G(AAF_w^T), \alpha = A \vdash_{\mathscr{S}^q}} P(w).$$

This notion is more fine-grained than that of grounded probability of arguments, reflecting the structured nature of our PAA framework. We conjecture (and leave to future work) that this notion is an instance of that of grounded probability of sentences in the Probabilistic ABA of [9].

4 Results

We show that the semantics of ProbLog can be captured in probabilistic argumentation, as follows.

Proposition 1. Let T be a (ground) ProbLog program and (AAF^T, PS^T, \Vdash^T) be the PAA framework corresponding to T, for $AAF^T = (Args^T, Att^T)$ and $PS^T = (\mathscr{W}^T, P)$. Then, for any (ground) query q:

$$P_s(q|T) = Prob_G(q); \tag{1}$$

$$P_{s}(q|T) \leq \sum_{\alpha \in Args^{T}: \alpha = A \vdash \varphi q} Prob_{G}(\alpha).$$
⁽²⁾

Proof. (Sketch) $P_s(q|T) = \sum_{L=F'\cup R,F'\subseteq \{l\leftarrow |p::l\leftarrow \in F\}, L\models q} P(L|T)$ by definition. Given the correspondence between well-founded model of a LP and grounded extension of the AA framework for the ABA framework corresponding to the LP [3], and by definition of the probability space in the PAA framework corresponding to T, we obtain $P_s(q|T) = \sum_{w \in \mathscr{W}^T: \alpha \in G(AAF_w^T), \alpha = A \vdash_{\mathscr{G}} q} P(w)$, proving (1). (1) implies (2) because $\sum_{\alpha \in Args^T: \alpha = A \vdash_{\mathscr{G}} q} Prob_G(\alpha) = \sum_{\alpha \in Args^T: \alpha = A \vdash_{\mathscr{G}} q} \sum_{w \in \mathscr{W}: \alpha \in G(AAF_w)} P(w) = \sum_{w \in \mathscr{W}} P(w) \cdot |\{\alpha \in Args^T \mid \alpha = A \vdash_{\mathscr{G}} q\}| \geq \sum_{w \in \mathscr{W}^T: \alpha \in G(AAF_w^T), \alpha = A \vdash_{\mathscr{G}} q} P(w)$ (there may be multiple arguments for the same claim in the grounded extensions obtained by different choices of worlds).

Thus, the notion of grounded probability of queries in the ProbLog-ABA instance of PAA corresponds exactly to the notion of success probability in ProbLog, whereas grounded probability of arguments in PAA approximates it.

5 Conclusion and Discussion

We have defined a form of PAA, instantiated with a novel form of ABA and probability spaces mirroring ProbLog's probability distributions over logic programs, to re-interpret ProbLog in argumentative terms.

This allows us to broaden the semantics of ProbLog beyond (two-valued) well-founded models, leveraging on other semantics for ABA, notably semantics of *sceptically preferred* and *ideal extensions* (see [4]). Moreover, it opens the way to different forms of explainability for the outputs of ProbLog (under the standard or new semantics). Indeed, argumentative abstractions of various reasoning problems have been shown to lend themselves to diverse explanatory formats, including interactive ones [6], and it is well known that different forms of explanations are needed to deal with different cognitive needs [2].

Future work includes exploring whether reasoning under the new semantics can be efficiently implemented in practice, and whether the new forms of explanations can be beneficially deployed in applications to increase user trust. Also, we have focused on success probability of queries: it would also be interesting to study whether and how explanation probability of queries can be captured argumentatively. It would also be interesting to explore whether ProbLog can be captured directly in Probabilistic ABA of the more general form proposed in [9] (again focusing on a single juror). It would also be interesting to explore whether credulous versions of ProbLog, notably SMProbLog [23], could inform the definition of novel credulous semantics in probabilistic argumentation. Finally, it would be interesting to study whether other languages/tools based on the distribution semantics [21] could also be captured in PAA.

Acknowledgements

Toni and Potyka were supported by the ERC under the EU's Horizon 2020 research and innovation programme (grant No. 101020934). Toni was also supported by J.P. Morgan and the UK RAEng under the Research Chairs and Senior Research Fellowships scheme. Ulbricht was supported by the German Federal Ministry of Education and Research (01/S18026A-F) by funding Big Data and AI "ScaDS.AI" Dresden/Leipzig. Totis was supported by the FWO project N. G066818N and the Flanders AI program.

References

- Laura Antanas, Plinio Moreno, Marion Neumann, Rui Pimentel de Figueiredo, Kristian Kersting, José Santos-Victor & Luc De Raedt (2019): Semantic and geometric reasoning for robotic grasping: a probabilistic logic approach. Auton. Robots 43(6), pp. 1393–1418, doi:10.1007/s10514-018-9784-8.
- [2] Vijay Arya, Rachel K. E. Bellamy, Pin-Yu Chen, Amit Dhurandhar, Michael Hind, Samuel C. Hoffman, Stephanie Houde, Q. Vera Liao, Ronny Luss, Aleksandra Mojsilovic, Sami Mourad, Pablo Pedemonte, Ramya Raghavendra, John T. Richards, Prasanna Sattigeri, Karthikeyan Shanmugam, Moninder Singh, Kush R. Varshney, Dennis Wei & Yunfeng Zhang (2020): AI Explainability 360: An Extensible Toolkit for Understanding Data and Machine Learning Models. J. Mach. Learn. Res. 21, pp. 130:1–130:6. Available at http://jmlr.org/papers/v21/19-1035.html.
- [3] Andrei Bondarenko, Phan Minh Dung, Robert A. Kowalski & Francesca Toni (1997): An Abstract, Argumentation-Theoretic Approach to Default Reasoning. Artif. Intell. 93, pp. 63–101, doi:10.1016/ S0004-3702(97)00015-5.
- [4] Kristijonas Cyras, Xiuyi Fan, Claudia Schulz & Francesca Toni (2017): Assumption-based Argumentation: Disputes, Explanations, Preferences. FLAP 4(8). Available at http://www.collegepublications.co. uk/downloads/ifcolog00017.pdf.
- [5] Kristijonas Cyras, Quentin Heinrich & Francesca Toni (2021): Computational complexity of flat and generic Assumption-Based Argumentation, with and without probabilities. Artif. Intell. 293, doi:10.1016/j.artint.2020.103449.
- [6] Kristijonas Cyras, Antonio Rago, Emanuele Albini, Pietro Baroni & Francesca Toni (2021): Argumentative XAI: A Survey. In: Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI 2021, pp. 4392–4399, doi:10.24963/ijcai.2021/600.

- [7] Yann Dauxais, Clément Gautrais, Anton Dries, Arcchit Jain, Samuel Kolb, Mohit Kumar, Stefano Teso, Elia Van Wolputte, Gust Verbruggen & Luc De Raedt (2019): SynthLog: A Language for Synthesising Inductive Data Models (Extended Abstract). In: Machine Learning and Knowledge Discovery in Databases International Workshops of ECML PKDD 2019, Part I, doi:10.1007/978-3-030-43823-4_9.
- [8] Phan Minh Dung (1995): On the Acceptability of Arguments and its Fundamental Role in Nonmonotonic Reasoning, Logic Programming and n-Person Games. Artif. Intell. 77(2), pp. 321–358, doi:10.1016/ 0004-3702(94)00041-X.
- [9] Phan Minh Dung & Phan Minh Thang (2010): Towards (Probabilistic) Argumentation for Jury-based Dispute Resolution. In: Computational Models of Argument: Proceedings of COMMA 2010, Frontiers in Artificial Intelligence and Applications 216, IOS Press, pp. 171–182, doi:10.3233/978-1-60750-619-5-171.
- [10] Daan Fierens, Guy Van den Broeck, Joris Renkens, Dimitar Sht. Shterionov, Bernd Gutmann, Ingo Thon, Gerda Janssens & Luc De Raedt (2015): *Inference and learning in probabilistic logic programs* using weighted Boolean formulas. Theory Pract. Log. Program. 15(3), pp. 358–401, doi:10.1017/ S1471068414000076.
- [11] Allen Van Gelder, Kenneth A. Ross & John S. Schlipf (1991): The Well-Founded Semantics for General Logic Programs. J. ACM 38(3), pp. 620–650, doi:10.1145/116825.116838.
- [12] Michael Gelfond & Vladimir Lifschitz (1988): *The Stable Model Semantics for Logic Programming*. In: Logic Programming, Proceedings of the Fifth International Conference and Symposium,, pp. 1070–1080.
- [13] Spyros Hadjichristodoulou & David Scott Warren (2012): Probabilistic Logic Programming with Well-Founded Negation. In D. Michael Miller & Vincent C. Gaudet, editors: 42nd IEEE International Symposium on Multiple-Valued Logic, ISMVL 2012, Victoria, BC, Canada, May 14-16, 2012, IEEE Computer Society, pp. 232–237, doi:10.1109/ISMVL.2012.26.
- [14] Anthony Hunter, Sylwia Polberg, Nico Potyka, Tjitze Rienstra & Matthias Thimm (2021): *Probabilistic argumentation: A survey. Handbook of Formal Argumentation 2*, pp. 397–441.
- [15] Antonis C. Kakas, Robert A. Kowalski & Francesca Toni (1998): *The role of abduction in logic programming*. In: *Handbook of logic in artificial intelligence and logic programming*, pp. 35–324.
- [16] Angelika Kimmig & Fabrizio Costa (2012): Link and Node Prediction in Metabolic Networks with Probabilistic Logic. In: Bisociative Knowledge Discovery - An Introduction to Concept, Algorithms, Tools, and Applications, pp. 407–426, doi:10.1007/978-3-642-31830-6_29.
- [17] Hengfei Li, Nir Oren & Timothy J. Norman (2011): Probabilistic Argumentation Frameworks. In: Theories and Applications of Formal Argumentation First International Workshop, TAFA 2011. Revised Selected Papers, Lecture Notes in Computer Science 7132, Springer, pp. 1–16, doi:10.1007/978-3-642-29184-5_1.
- [18] Robin Manhaeve, Sebastijan Dumancic, Angelika Kimmig, Thomas Demeester & Luc De Raedt (2018): DeepProbLog: Neural Probabilistic Logic Programming. In: Advances in Neural Information Processing Systems 31: NeurIPS 2018,, pp. 3753-3763. Available at https://proceedings.neurips.cc/paper/ 2018/hash/dc5d637ed5e62c36ecb73b654b05ba2a-Abstract.html.
- [19] Theofrastos Mantadelis & Stefano Bistarelli (2020): *Probabilistic abstract argumentation frameworks, a possible world view. Int. J. Approx. Reason.* 119, pp. 204–219, doi:10.1016/j.ijar.2019.12.006.
- [20] Luc De Raedt & Angelika Kimmig (2015): Probabilistic (logic) programming concepts. Mach. Learn. 100(1), pp. 5–47, doi:10.1007/s10994-015-5494-z.
- [21] Taisuke Sato (1995): A Statistical Learning Method for Logic Programs with Distribution Semantics. In: Proceedings of the Twelfth International Conference on Logic Programming, pp. 715–729.
- [22] Francesca Toni (2014): A tutorial on Assumption-based Argumentation. Arg. & Comp 5(1), pp. 89–117.
- [23] Pietro Totis, Angelika Kimmig & Luc De Raedt (2023): smProbLog: Stable Model Semantics in ProbLog for Probabilistic Argumentation. Theory and Practice of Logic Programming, p. 1–50, doi:10.1017/ S147106842300008X.