# **CoRD:** Converged RDMA Dataplane for High-Performance Clouds

Maksym Planeta Barkhausen Institut Jan Bierbaum TU Dresden Michael Roitzsch Barkhausen Institut Hermann Härtig TU Dresden

#### Abstract

High-performance networking is often characterized by kernel bypass which is considered mandatory in highperformance parallel and distributed applications. But kernel bypass comes at a price because it breaks the traditional OS architecture, requiring applications to use special APIs and limiting the OS control over existing network connections. We make the case, that kernel bypass is *not* mandatory. Rather, high-performance networking relies on multiple performance-improving techniques, with kernel bypass being the least effective. CoRD removes kernel bypass from RDMA networks, enabling efficient OS-level control over RDMA dataplane.

## 1 Introduction

High Performance Computing (HPC) and Cloud architectures are converging: the former is advancing towards greater elasticity and higher resource utilization [14, 20, 24, 91], while the latter is increasingly geared towards handling high-performance workloads [13, 22, 71]. However, current HPC Cloud systems remain partitioned: vast sections lack high-performance networking support, with only a few segments offering such capabilities [5, 56, 62]. As we push for a holistic integration of HPC and Cloud systems, we realize that their network architectures must converge as well. In this paper, we show how operating systems (OS) can help in such integration by making highperformance networks more accessible. We believe this approach can significantly enhance performance within Cloud environments.

A classical OS provides a socket-based abstraction layer between the applications and the underlying hardware. This layer allows "rich and robust" OS services [2, p. 228], like application portability, resource scheduling, and security policy enforcement. High-performance networks, often represented by Remote Direct Memory Access (RDMA) networks [18,34] subvert this layered OS architecture by granting user-level applications direct access to network devices (NICs). These applications circumvent OS services (including the network stack), instead they come with their own NIC drivers and perform most of the scheduling and resource management themselves [18,61]. This approach forces the OS to rely on the NIC to implement security (IOMMUs [72,80] or VLANs [75] are not sufficient) and resource-sharing policies [30,44,90]. As a result, the OS becomes just an over-engineered bootloader [27,28,37,87].

In response to the demand for flexibility and OS control over high-performance network communication, the OS community has proposed several dataplane architectures [9,18,30,39,52,59,68,83,89]. But few of these solutions have seen widespread adoption [18,39]. The novelty of these architectures and their lack of interoperability with socket-based communication, poses a significant entry barrier, restricting their appeal for conventional Cloud applications. Interestingly, dataplane architectures and traditional RDMA networks share common mechanisms and principles, suggesting a potential for compatibility. So, could we introduce minor, strategic adjustments to the widely-used RDMA networks to make them as flexible and controllable by the OS as socket-based networks? This approach could bridge the current gap and facilitate the convergence of HPC and Cloud architectures.

In this paper, we identify a set of key properties that boost the performance of RDMA networks over socketbased networks. Among these, kernel-bypass is often considered the cornerstone [21, 26, 45, 51]. However, we challenge this prevalent belief and show that kernel-bypass is not indispensible to high-performance applications. Inspired by these insights, we propose the Converged RDMA Dataplane (CoRD), a strategically altered version of the traditional RDMA architecture that directs the dataplane through the kernel. This pivotal shift gives the kernel full control over RDMA communication, enabling it to enforce security policies [55, 76], provide virtualization [30, 54], control resources on a fine-grained level [30, 44], and facilitate application observability [3]. Preliminary measurements reveal that CoRD retains the performance for large-scale applications, effectively converging RDMA and socket-based networks without forsaking the intrinsic advantages of either.

#### 2 RDMA performance breakdown

Compared to traditional socket-based networks, we identify three software properties enabling high-performance communication over RDMA networks: *kernel-bypass* (or *OS-bypass*), *zero-copy*, and *polling*<sup>1</sup>. Each technique improves performance in a different way, can be employed independently of the rest, and comes with its own limitations. This diversity suggests that these techniques may not be equally performance critical in every use case.

*Kernel-bypass* allows the application to access the device directly, avoiding overhead for crossing the userkernel boundary. Zero-copy enables the NIC to access the application memory directly, avoiding overhead for copying the message content between kernel and user memory as done with read and write system calls. With polling, the application continuously checks the NIC's message queues to avoid the overhead of interrupt processing, which happens in the epoll system call. Together, these techniques form an API [15, 53, 89] that is very different from the traditional socket-based API.

A simple example illustrates the role of each of the aforementioned techniques: A high-performance perftest microbenchmark measures (on our local system *L*, see section 5) point-to-point send latency and throughput for different message sizes. To quantify the contribution of each technique, we modified the benchmark to "remove" individual techniques from the typical RDMA mode of operation and measure how the benchmark performance changes. To emulate the removal of zero-copy, our perftest makes an extra memory copy when sending or receiving a message. We emulate the removal of kernel-bypass by adding a getppid system call. Finally, we instruct the benchmarks to wait for an interrupt from the NIC instead of busy-polling, an existing, but rarely used feature in RDMA networks.

Figure 1 shows the results of our experiment. Removing any of the three techniques has a significant influence on small-message throughput (fig. 1b), because this task is CPU-bound. Even the baseline variant (with all techniques active) achieves only 1.4 Gbit/s out of the theoretical maximum of 100 Gbit/s. On the other hand, large message throughput is obstructed significantly only without zero-copy. For latency (fig. 1a), removing busy-polling adds significant overhead from additional interrupt processing, especially for small messages, although the abso-




Figure 1: "Removing" performance-improving techniques compared to having all techniques active




Figure 2: Socket, RDMA, and CoRD control- and dataplanes. To send a message over a socket, the application invokes the high-level kernel network stack (1). The kernel (fig. 2a) or the application (figs. 2b and 2c) request the NIC driver to send the packet (3), which copies the data from pinned (1) memory to send it over the network (4).

lute overhead stays the same even for very large messages. Removing zero-copy adds additional latency proportional to message size (up to  $140 \mu s/MiB$ ) because of additional data movement. Finally, removing kernel bypass adds small constant overhead with minimal overall impact.

We make the following observations from this experiment: Zero copy appears to be the largest contributor to performance, especially for large messages. Kernelbypass is crucial for throughput and latency only for very small messages. Even then, polling is more important than kernel-bypass. These observations identify kernel-bypass as the least performance-critical technique.

### **3** Converged RDMA Dataplane

Our proposed architecture, CoRD integrates OS-level control into high-performance user-level communication dataplane. This section first provides an overview of both socket- and RDMA-based communication (fig. 2). Then, it explains how CoRD modifies the RDMA dataplane to enable control over the RDMA connections.

<sup>&</sup>lt;sup>1</sup>There are also hardware techniques, like *one-sided (or RDMA)* communication, offloading, and lossless congestion control.

In a traditional socket-based API, as shown in fig. 2a, communication starts with the application making a system call (1, e.g., send) which instructs the kernel to dispatch a message over an existing connection (e.g., a TCP socket). Subsequently, the kernel copies (2) the message content into NIC-accessible (*pinned*,  $\blacksquare$ ) memory. Finally, the kernel *triggers* the NIC (3) to start the transmission of message packets (4). This entire operation is managed by a complex kernel-level network stack, designed to maintain scalability and improve resource utilization across a large number of user applications. However, this design philosophy inadvertently hampers network performance.

In contrast to socket-based communication, RDMA networks (fig. 2b) delegate a significant part of control to the application, allowing it to manage pinned memory () and access the NIC directly (3). The NIC can retrieve the message content directly from the user memory (4), thus bypassing the kernel. Note, that while this requires some network stack functionality at the application level, a majority of responsibilities, such as managing concurrent users, are offloaded to the NIC. Despite the complexity added to the application, this architecture ultimately yields the lowest possible communication latency.

CoRD principally mimics the classical RDMA architecture, retaining a majority of its performance attributes. The RDMA application keeps its responsibilities under CoRD, including the management of pinned memory. The drivers at the user level in RDMA (fig. 2b) and at the kernel level in CoRD (fig. 2c) are largely equivalent, thereby ensuring a lightweight and transparently interchangeable layer between the application and the NIC. The critical distinction, however, lies in the NIC access. CoRD mandates a system call from the application (**3**), thereby preventing it from directly accessing the NIC.

In CoRD each dataplane operation goes through the kernel, but the kernel processing is kept to a minimum. In contrast to socket-based communication, CoRD only permits the enforcement of lightweight, non-blocking policies to maintain its high network performance. However, this limitation is not significant, as without system-wide resource sharing CoRD can afford to uphold simpler, more streamlined policies, which we refer to as *CoRD policies*. CoRD policies should be powerful enough to implement QoS, security, and isolation similarly to other dataplane interception techniques [30, 44]. CoRD inevitably adds a constant per-message latency from user-kernel switching. The overhead from the enforcement of CoRD policies depends greatly on the specifics of the implemented functionality, which are beyond the scope of this paper.

## 4 Implementation

The goal of our prototype implementation is to measure the cost of CoRD's architecture, which we expect to be higher than the bare minimum overhead of userkernel transition (see section 2). We modify the user- and kernel-level mlx5 device drivers for NVIDIA's ConnectXseries NICs. These drivers are used by the *ibverbs* library [53] to funnel data-plane operations through the kernel. The ibverbs API is the "narrow waist" of many high-performance user-level network stacks [44], which use it either directly [4,42,58] or through a higher-level API [8,40,60]. As this is a preliminary study, we do not attempt any performance optimizations, so the resulting overhead represents the worst case.

The ibverbs API defines *control- and data-plane* operations: Control-plane operations set up communication; they register device-accessible memory, create communication endpoints (*queue pairs*), etc. Data-plane operations initiate message sending (ibv\_post\_send) and receiving (ibv\_post\_recv) or perform a non-blocking check if any of these operations have completed (ibv\_poll\_cq). Control-plane operations require kernel support, whereas dataplane operations usually bypass the kernel.

Applications request ibverbs control-plane operations using ioctl system call. Unfortunately, the arguments to ibverbs calls are complex data structures that must be *serialized* and *deserialized* to go through the ioctl interface. These operations add to the system-call overhead but are not a performance critical for control-plane operations. On a positive side, the ioctl code path allows the OS to intercept control-plane ibverbs calls and thus enforce security [55, 76], isolation [64], and resource management policies [81]. CoRD extends this existing functionality to data-plane operations.

After entering the kernel, the data-plane operation reaches the kernel-level device driver, which normally provide high-performance networking inside the Linux kernel [57, 74]. We change the driver minimally, so it can work with the ibverbs objects created by the user application. Overall we added or modified ~250 lines in the kernel-level driver and ~20 lines in the user-level driver. Except for the kernel interposition, the ibverbs API remains unchanged and introduces no interrupts or asynchronous invocations on the data plane. In other words, without CoRD policies, the only overhead comes from crossing the user-kernel boundary.

Our implementation depends on the NIC being able to access an application's virtual memory as applications pass message buffers to the NIC by virtual address. This is a common feature for high-performance NICs [36,53], which, in contrast to other approaches (e.g., io\_uring [39]), relieves the kernel from virtual-to-device address translations on the critical path. If the application passes an invalid address, the NIC returns an error but does not access any memory that was not explicitly provided to the application.




Figure 3: Latency overhead on system L (baseline in fig. 1a) when communicating over different transports (RC/UD) using one-sided (Read/Write) or two-sided (Send) communication. Client and server can independently run bypass (BP) or CoRD (CD), " $\rightarrow$ " indicates the direction of communication (from client to server).

## 5 Evaluation

Our goal is to evaluate how CoRD impacts raw communication performance as well as end-to-end application performance. We evaluate two systems. First, a system *L*, comprising two nodes, each with Intel i5-4590 4-core CPUs and 200 Gbit/s NVIDIA ConnectX-6 Dx RoCE NICs communicating at up to 100 Gbit/s due to motherboard limitations. The nodes are back-to-back connected. The system runs vanilla Linux 6.0.0-rc7 with or without our patch to support CoRD in the mlx5 driver. We also disable Turbo Boost, pin all the benchmark processes to dedicated cores, and set the CPU power governor to the highest performance mode.

Second, is a remote two-node system A deployed in the Azure Cloud. We use virtualized HB120 instances with two 64-core AMD EPYC 7V73X CPUs (only 120 cores passed to VM) and virtualized 200 Gbit/s NVIDIA ConnectX-6 Infiniband NICs. In both systems we disable KPTI [29, 38], an expensive kernel-level Meltdown attack [48] mitigation, because modern CPUs do not need it. Specifically, system A's CPU mitigates Meltdown in hardware. We run the benchmarks in the same way as on system L, except for not being able to disable dynamic frequency scaling due to the cloud provider policy.

We first measured the overhead CoRD adds to the pointto-point message latency, using the perftest 4.5 benchmark suite [66]. The communication can go either through Reliable Connection (RC) or Unreliable Datagram (UD) transports. In addition to two-sided send/receive communication, RC supports one-sided RDMA read/write operations. CoRD can independently be enabled on the sender or receiver, allowing us to study which side contributes to la-




Figure 4: CoRD's throughput on system L relative to bypass communication. Communication goes over RC or UD using one-sided (Read/Write) or two-sided (Send) operations. UD supports only up to 4 KiB messages. The overlayed lines show the message rate (right axis) in the bypass configuration.

tency more. Figure 3 shows the absolute latency overhead compared to bypass-to-bypass communication, measured with a message size of 4 KiB. We observed the same numbers for other message sizes.

When CoRD runs only at the server side, RDMA read has no overhead, because the sender's CPU does not participate in sending the message. In contrast, with RDMA write operations, perftest uses two writes to exchange data: One from the client to the server for synchronization, another for the server to fetch the data from the client. For operations except RDMA read, enabling CoRD contributes equally towards overall overhead from each side.

Constant per-message overhead results in significantly lower maximum throughput for large bursts of small messages. Figure 4 corroborates this statement because, with larger messages, bandwidth degradation becomes insignificant. This behavior is similar for all types of communication (RC/UD, Send/Read/Write) as the per-message overhead is similar. Specifically, for 32 KiB messages exchanged using send operations, perftest measured ~370k messages per second and only 1% bandwidth degradation.

System A exhibits similar behavior (fig. 5), except for a few minor differences: Overall per-message overhead is larger, has higher variation, and has two statistical modes (fig. 5a shows them) for small ( $\leq 1$  KiB) and large messages, with the larger messages having smaller overhead. Our initial investigation suggests that CoRD has higher overhead for small messages, because current implementation of CoRD lacks support for inline messages, whereas baseline supports them. At the same message size, system L shows a higher throughput reduction than system A because its network has double the bandwidth. Nevertheless, bandwidth reduction becomes negligible from a certain message size (see fig. 5b).




Figure 5: Latency overhead and relative throughput on system A when communicating over different transports (RC/UD) using one-sided (Read/Write) or two-sided (Send) communication.




Figure 6: Relative runtime of the NPB benchmarks on system A.

To estimate the effect on real-world applications, we measure the performance of the MPI version of the NPB suite [17]. We compare communication over RDMA, CoRD, and IPoIB. To amplify the network effects, we bar the MPI library from using shared memory communication. We picked IPoIB for comparison because it communicates over Infiniband NIC, yet offers fine-grained control over data-plane operations, making it a functionally equivalent competitor to CoRD. Each benchmark has limitations on the number of processes allowed for a run, which in our case ranged from 128 to 240.

For all the benchmarks, CoRD has nearly zero overhead over baseline kernel-bypass communication whereas IPoIB is up to  $2 \times$  slower. IPoIB is the slowest with the IS (integer sorting) and SP (matrix factorization) benchmarks, which are simultaneously data intensive (each process sends 72 Gbit/s and 34 Gbit/s, respectively) and message intensive ( $\approx$ 1300 messages/second per process). EP (embarrassingly parallel), which communicates very little, and CG (conjugate gradient), which communicates using few large messages, see a slight performance boost with CoRD. Similarly to CG, we observe CoRD marginally outperforming kernel bypass in large-message bandwidth microbenchmarks when Turbo Boost is enabled. This behavior suggests that system calls interact with DVFS. Overall, our initial implementation of CoRD has negligible overhead, even for large-scale real-world applications.

#### 6 Discussion and Conclusion

Modern cloud systems predominantly rely on socketbased networking to manage a myriad of distributed applications. Key to this operation is the precise control over application communication channels using tools such as Linux packet filtering [1] or eBPF [82]. Despite persistent enhancements in high-performance TCP/IP [12, 78], it still falls significantly short of the performance of RDMA networks.

High-performance networking is diverse and complex [7,15,18,52,53], so, unsurprisingly, there are no "one size fits all" solutions [79]. Striving for optimal problemspecific solutions, researchers abandoned polling [10,84], zero-copy [33,79], lossless congestion control [25,49], hardware offloading [32,43,47,67], and one-sided operations [19,41,77] to achieve higher flexibility and resource utilization. So, giving up performance-enhancing features is not radically new.

Still, the high-performance networking community adamantly avoids putting the OS kernel on the data path. Instead, existing works add another device on the path of a packet, either in the form of dedicated CPU cores [11, 39, 44, 52, 63, 83] or by offloading complicated data path interception logic to the NIC. Such offloading requires either an expensive SmartNIC [16, 31, 73, 85] or hardware modifications [46, 50, 69].

Our work is based on the idea that the actual problem with system calls is not the cost of user-kernel transitions in hardware, but rather an obsolete and inefficient API; in this case POSIX. This idea is in line with the existing body of work [6, 65, 70, 86, 89], and our early results support the observation of kernel bypass being dispensable.

In the future, we strive for a smaller per-message overhead and incorporate several policies, which we will evaluate with a modern bare-metal system. We intend to assemble a set of real-world benchmark applications that shows the "breaking point" of CoRD. When successful, CoRD concepts can help in other domains like high-performance storage [35, 88], where APIs are built on similar concepts.

### Acknowledgments

The research and the work presented in this paper has been supported by the German priority program 1648 "Software for Exascale Computing" via the research project FFMK [23] (HA-2461/10-2). The authors acknowledge the financial support by the Federal Ministry of Education and Research of Germany in the programme of "Souverän. Digital. Vernetzt.". Joint project 6G-life, project identification number: 16KISK001K This work was supported in part by the German Research Foundation (DFG) within the Collaborative Research Center HAEC and the the Center for Advancing Electronics Dresden (cfaed). The authors acknowledge support from the Oracle for Research for providing cloud computing resources in project 172. We would like to thank the anonymous HotOS and WORDS reviewers for their valuable comments.

## References

- [1] Weave Net: Network containers across any environment. https://www.weave.works/docs/net/latest/overview/, 2014.
- [2] Marcelo Abranches, Oliver Michel, and Eric Keller. Getting back what was lost in the era of highspeed software packet processing. In *Proceedings* of the 21st ACM Workshop on Hot Topics in Networks, pages 228–234, Austin Texas, November 2022. ACM.
- [3] Marcelo Abranches, Oliver Michel, Eric Keller, and Stefan Schmid. Efficient Network Monitoring Applications in the Kernel with eBPF and XDP. In 2021 IEEE Conference on Network Function Virtualization and Software Defined Networks (NFV-SDN), pages 28–34, Chandler, AZ United States, November 2021. IEEE.
- [4] Aleksandar Dragojević, Dushyanth Narayanan, Orion Hodson, and Miguel Castro. FaRM: Fast Remote Memory. In Proceedings of the 11th USENIX Symposium on Networked Systems Design and Implementation, pages 401–414, Seattle, WA, USA, 2014. USENIX Association.
- [5] Amazon Web Services, Inc. Elastic Fabric Adapter. https://aws.amazon.com/hpc/efa/, 2020.

- [6] Vaggelis Atlidakis, Jeremy Andrus, Roxana Geambasu, Dimitris Mitropoulos, and Jason Nieh. POSIX abstractions in modern operating systems: the old, the new, and the missing. In *Proceedings of the Eleventh European Conference on Computer Systems*, pages 1–17, London United Kingdom, April 2016. ACM.
- [7] Brian W Barrett, Ron Brightwell, Ryan E Grant, Scott Hemmert, Kevin Pedretti, Kyle Wheeler, Keith Underwood, Rolf Riesen, Torsten Hoefler, Arthur B Maccabe, and Trammell Hudson. The Portals 4.2 Network Programming Interface. Technical report, Sandia National Laboratories, April 2017.
- [8] Michael Bauer, Sean Treichler, Elliott Slaughter, and Alex Aiken. Legion: Expressing locality and independence with logical regions. In *International Conference for High Performance Computing, Networking, Storage and Analysis*, SC, pages 1–11, Salt Lake City, UT, November 2012. IEEE.
- [9] Adam Belay, George Prekas, Christos Kozyrakis, Ana Klimovic, Samuel Grossman, and Edouard Bugnion. IX: A Protected Dataplane Operating System for High Throughput and Low Latency. In 11th USENIX Symposium on Operating Systems Design and Implementation, OSDI '14, pages 49–65, October 2014.
- [10] Jan Bierbaum, Maksym Planeta, and Hermann Härtig. Towards Efficient Oversubscription: On the Cost and Benefit of Event-Based Communication in MPI. In *Runtime and Operating Systems for Supercomputers*, Dallas, Texas, USA, 2022. IEEE.
- [11] Silas Boyd-Wickizer, Haibo Chen, Rong Chen, Yandong Mao, Frans Kaashoek, Robert Morris, Aleksey Pesterev, Lex Stein, Ming Wu, Yuehua Dai, Yang Zhang, and Zheng Zhang. Corey: An Operating System for Many Cores. In 8th USENIX Symposium on Operating Systems Design and Implementation, San Diego, California, USA, 2008. USENIX Association.
- [12] Qizhe Cai, Midhul Vuppalapati, Jaehyun Hwang, Christos Kozyrakis, and Rachit Agarwal. Towards  $\mu$  s tail latency and terabit Ethernet: disaggregating the host network stack. In *Proceedings of the ACM SIGCOMM 2022 Conference*, pages 767–779, Amsterdam Netherlands, August 2022. ACM.

- [13] Joao Carreira, Pedro Fonseca, Alexey Tumanov, Andrew Zhang, and Randy Katz. Cirrus: a Serverless Framework for End-to-end ML Workflows. In *Proceedings of the ACM Symposium on Cloud Computing*, SoCC '19, pages 13–24, New York, NY, USA, November 2019. Association for Computing Machinery.
- [14] Mohak Chadha, Jophin John, and Michael Gerndt. Extending SLURM for Dynamic Resource-Aware Adaptive Batch Scheduling. arXiv:2009.08289 [cs], September 2020.
- [15] Cray Inc. XC Series GNI and DMAPP API User Guide CLE70UP02 (S-2446), 2019.
- [16] Daniel Firestone, Andrew Putnam, Sambhrama Mundkur, Derek Chiou, Alireza Dabagh, Mike Andrewartha, Vivek Bhanu, Eric Chung, Harish Kumar Chandrappa, Somesh Chaturmohta, Matt Humphrey, Jack Lavier, Norman Lam, Fengfen Liu, Kalin Ovtcharov, Jitu Padhye, Gautham Popuri, Shachar Raindel, Tejas Sapre, Mark Shaw, Gabriel Silva, Madhan Sivakumar, Nisheeth Srivastava, Anshuman Verma, Qasim Zuhair, Deepak Bansal, Doug Burger, Kushagra Vaid, David A. Maltz, and Albert Greenberg. Azure Accelerated Networking: Smart-NICs in the Public Cloud. In 15th USENIX Symposium on Networked Systems Design and Implementation, NSDI'18, pages 51–64, Berkeley, Calif, 2018. USENIX Association.
- [17] David H. Bailey, Eric Barszcz, John T. Barton, D. S. Browning, Robert L. Carter, Leonardo Dagum, Rod A. Fatoohi, Paul O. Frederickson, T. A. Lasinski, Robert S. Schreiber, Horst D. Simon, V Venkatakrishnan, and Sisira K. Weeratunga. The NAS Parallel Benchmarks. 1994.
- [18] DPDK Project. Data Plane Development Kit. https://www.dpdk.org/, 2013.
- [19] Aleksandar Dragojevic, Dushyanth Narayanan, and Miguel Castro. RDMA Reads: To Use or Not to Use? Bulletin of the Technical Committee on Data Engineering, 40(1):3–14, March 2017.
- [20] Kaoutar El Maghraoui, Travis J. Desell, Boleslaw K. Szymanski, and Carlos A. Varela. Dynamic Malleability in Iterative MPI Applications. In Seventh IEEE International Symposium on Cluster Computing and the Grid (CCGrid '07), pages 591–598, May 2007.

- [21] Kevin Elphinstone and Gernot Heiser. From L3 to seL4 what have we learnt in 20 years of L4 microkernels? In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 133–150, Farminton Pennsylvania, November 2013. ACM.
- [22] Lang Feng, Prabhakar Kudva, Dilma Da Silva, and Jiang Hu. Exploring Serverless Computing for Neural Network Training. In 2018 IEEE 11th International Conference on Cloud Computing (CLOUD), pages 334–341, July 2018.
- [23] FFMK Website. https://ffmk.tudos.org, 2013.
- [24] Alvaro Frank, Tim Süss, and André Brinkmann. Effects and Benefits of Node Sharing Strategies in HPC Batch Systems. In 2019 IEEE International Parallel and Distributed Processing Symposium, IPDPS, pages 43–53. IEEE Computer Society, May 2019.
- [25] D. Garcia, P. Culley, R. Recio, J. Hilland, and B. Metzler. A Remote Direct Memory Access Protocol Specification. https://tools.ietf.org/html/rfc5040, October 2007.
- [26] Luis Gerhorst, Benedict Herzog, Stefan Reif, Wolfgang Schröder-Preikschat, and Timo Hönig. Any-Call: Fast and Flexible System-Call Aggregation. In Proceedings of the 11th Workshop on Programming Languages and Operating Systems, PLOS '21, pages 1–8, New York, NY, USA, October 2021. Association for Computing Machinery.
- [27] Balazs Gerofi, Masamichi Takagi, Atsushi Hori, Gou Nakamura, Tomoki Shirasawa, and Yutaka Ishikawa. On the Scalability, Performance Isolation and Device Driver Transparency of the IHK/McKernel Hybrid Lightweight Kernel. In 2016 IEEE International Parallel and Distributed Processing Symposium (IPDPS), pages 1041–1050, Chicago, IL, USA, May 2016. IEEE.
- [28] Mark Giampapa, Thomas Gooding, Todd Inglett, and Robert W. Wisniewski. Experiences with a Lightweight Supercomputer Kernel: Lessons Learned from Blue Gene's CNK. In 2010 ACM/IEEE International Conference for High Performance Computing, Networking, Storage and Analysis, pages 1–10, New Orleans, LA, USA, November 2010. IEEE.

- [29] Daniel Gruss, Moritz Lipp, Michael Schwarz, Richard Fellner, Clémentine Maurice, and Stefan Mangard. KASLR is Dead: Long Live KASLR. In Eric Bodden, Mathias Payer, and Elias Athanasopoulos, editors, *Engineering Secure Software and Systems*, volume 10379, pages 161–176. Springer International Publishing, Cham, 2017.
- [30] Zhiqiang He, Dongyang Wang, Binzhang Fu, Kun Tan, Bei Hua, Zhi-Li Zhang, and Kai Zheng. MasQ: RDMA for Virtual Private Cloud. In Proceedings of the Annual conference of the ACM Special Interest Group on Data Communication on the applications, technologies, architectures, and protocols for computer communication, SIGCOMM '20, pages 1–14, New York, NY, USA, July 2020. Association for Computing Machinery.
- [31] Torsten Hoefler, Salvatore Di Girolamo, Konstantin Taranov, Ryan E. Grant, and Ron Brightwell. sPIN: high-performance streaming processing in the network. In Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis on - SC '17, pages 1–16, Denver, Colorado, 2017. ACM Press.
- [32] Toke Høiland-Jørgensen, Jesper Dangaard Brouer, Daniel Borkmann, John Fastabend, Tom Herbert, David Ahern, and David Miller. The eXpress data path: fast programmable packet processing in the operating system kernel. In *Proceedings of the 14th International Conference on emerging Networking EXperiments and Technologies*, pages 54–66, Heraklion Greece, December 2018. ACM.
- [33] W Huang, G Santhanaraman, and Q Gao. Design and Implementation of High Performance MVA-PICH2 (MPI2 over InfiniBand). In Sixth IEEE International Symposium on Cluster Computing and the Grid, CCGRID '06, page 10, 2006.
- [34] InfiniBand Trade Association. *InfiniBand Architecture Specification*, volume 1. InfiniBand Trade Association, 1.3 edition, March 2015.
- [35] Intel Corporation. oneAPI Specification 1.2-rev-1. Specification.
- [36] Intel Corporation. Intel® Data Streaming Accelerator Architecture Specification. Technical Report 2.0, Intel Corporation, September 2022.

- [37] Muhammad Jamshed, YoungGyoun Moon, Donghwi Kim, Dongsu Han, and KyoungSoo Park. mOS: A Reusable Networking Stack for Flow Monitoring Middleboxes. In Proceedings of the 14th USENIX Symposium on Networked Systems Design and Implementation, Boston, MA, USA, 2017.
- [38] Jonathan Corbet. The current state of kernel page-table isolation [LWN.net]. https://lwn.net/Articles/741878/, December 2017.
- [39] Jonathan Corbet. Ringing in a new asynchronous I/O API. https://lwn.net/Articles/776703/, January 2019.
- [40] Laxmikant V. Kale and Sanjeev Krishnan. A Portable Concurrent Object Oriented System Based On C++. In Conference on Object-Oriented Programming Systems, Languages and Applications, OOPSLA '93, pages 91–108, Washington, DC, USA, 1993. ACM Press.
- [41] Anuj Kalia, Michael Kaminsky, and David G. Andersen. Using RDMA efficiently for key-value services. In *Proceedings of the 2014 ACM conference on SIG-COMM - SIGCOMM '14*, pages 295–306, Chicago, Illinois, USA, 2014. ACM Press.
- [42] Anuj Kalia, Michael Kaminsky, and David G Andersen. FaSST: Fast, Scalable and Simple Distributed Transactions with Two-sided (RDMA) Datagram RPCs. In Proceedings of the 12th USENIX Symposium on Operating Systems Design and Implementation, Savannah, GA, USA, November 2016. USENIX Association.
- [43] Antoine Kaufmann, Tim Stamler, Simon Peter, Naveen Kr. Sharma, Arvind Krishnamurthy, and Thomas Anderson. TAS: TCP Acceleration as an OS Service. In *Proceedings of the Fourteenth EuroSys Conference 2019*, pages 1–16, Dresden Germany, March 2019. ACM.
- [44] Daehyeok Kim, Tianlong Yu, Hongqiang Harry Liu, Yibo Zhu, Jitu Padhye, Shachar Raindel, Chuanxiong Guo, Vyas Sekar, and Srinivasan Seshan. FreeFlow: Software-based Virtual RDMA Networking for Containerized Clouds. In Proceedings of the 16th USENIX Conference on Networked Systems Design and Implementation, NSDI, pages 113–125, Boston, MA, USA, 2019.
- [45] Gregory M. Kurtzer, Vanessa Sochat, and Michael W. Bauer. Singularity: Scientific containers for mobility of compute. *PLOS ONE*, 12(5):e0177459, May 2017.

- [46] Ilya Lesokhin, Haggai Eran, Shachar Raindel, Guy Shapiro, Sagi Grimberg, Liran Liss, Muli Ben-Yehuda, Nadav Amit, and Dan Tsafrir. Page Fault Support for Network Controllers. In Proceedings of the Twenty-Second International Conference on Architectural Support for Programming Languages and Operating Systems, pages 449–466, Xi'an China, April 2017. ACM.
- [47] Linux Foundation. networking:toe [Wiki]. https://wiki.linuxfoundation.org/networking/toe, 2016.
- [48] Moritz Lipp, Michael Schwarz, Daniel Gruss, Thomas Prescher, Werner Haas, Jann Horn, Stefan Mangard, Paul Kocher, Daniel Genkin, Yuval Yarom, Mike Hamburg, and Raoul Strackx. Meltdown: reading kernel memory from user space. *Communications of the ACM*, 63(6):46–56, May 2020.
- [49] Liran Liss. The Linux SoftRoCE Driver, March 2017.
- [50] Liran Liss. On Demand Paging for User-level Networking, 2013.
- [51] Anil Madhavapeddy, Richard Mortier, Charalampos Rotsos, David Scott, Balraj Singh, Thomas Gazagnaire, Steven Smith, Steven Hand, and Jon Crowcroft. Unikernels: library operating systems for the cloud. ASPLOS '13 Proceedings of the eighteenth international conference on Architectural support for programming languages and operating systems, 2013.
- [52] Michael Marty, Steve Gribble, Nicholas Kidd, Roman Kononov, Gautam Kumar, Carl Mauer, Emily Musick, Lena Olson, Erik Rubow, Michael Ryan, Kevin Springborn, Marc de Kruijf, Paul Turner, Valas Valancius, Xi Wang, Amin Vahdat, Jacob Adriaens, Christopher Alfeld, Sean Bauer, Carlo Contavalli, Michael Dalton, Nandita Dukkipati, and William C. Evans. Snap: a microkernel approach to host networking. In *Proceedings of the 27th ACM Symposium on Operating Systems Principles - SOSP* '19, pages 399–413, Huntsville, Ontario, Canada, 2019. ACM Press.
- [53] Mellanox Technologies. RDMA Aware Networks Programming User Manual. Technical Report 1.7, Mellanox Technologies, 2015.
- [54] Sebastiano Miano, Fulvio Risso, Mauricio Vásquez Bernal, Matteo Bertrone, and Yunsong Lu. A Framework for eBPF-Based Network Functions in an Era of Microservices. *IEEE Transactions on Network and Service Management*, 18(1):133–151, March 2021.

- [55] Mick Bauer. Paranoid Penguin: An Introduction to Novell AppArmor. https://dl.acm.org/doi/fullHtml/10.5555/1149826.1149839, 2006.
- [56] Microsoft. High performance computing VM sizes. https://docs.microsoft.com/en-us/azure/virtualmachines/sizes-hpc, August 2020.
- [57] Mike Ko and Alexander Nezhinsky. Internet Small Computer System Interface (iSCSI) Extensions for the Remote Direct Memory Access (RDMA) Specification. https://datatracker.ietf.org/doc/html/rfc7145, 2014.
- [58] Christopher Mitchell, Yifeng Geng, and Jinyang Li. Using One-Sided RDMA Reads to Build a Fast, CPU-Efficient Key-Value Store. In USENIX Annual Technical Conference (USENIX ATC 13), pages 103– 114, 2013.
- [59] Angelas Mouzakitis, Christian Pinto, Nikolay Nikolaev, Alvise Rigo, Daniel Raho, Babis Aronis, and Manolis Marazakis. Lightweight and Generic RDMA Engine Para-Virtualization for the KVM Hypervisor. In 2017 International Conference on High Performance Computing & Simulation (HPCS), pages 737–744, Genoa, Italy, July 2017. IEEE.
- [60] MPI Forum. MPI: A Message-Passing Interface Standard. Technical Report 3.1, Message Passing Interface Forum, June 2015.
- [61] OpenMPI. Open MPI v5.0.x Open MPI 5.0.x documentation. https://docs.open-mpi.org/en/v5.0.x/, 2022.
- [62] Oracle. Compute Shapes. https://docs.oracle.com/enus/iaas/Content/Compute/References/computeshapes.htm, 2023.
- [63] Amy Ousterhout, Joshua Fried, Jonathan Behrens, Adam Belay, and Hari Balakrishnan. Shenango: Achieving High CPU Efficiency for Latencysensitive Datacenter Workloads. In Proceedings of the 16th USENIX Symposium on Networked Systems Design and Implementation, Boston, MA, USA, 2019.
- [64] Parav Pandit. Manpage: rdma-system RDMA subsystem configuration, 2020.

- [65] Pekka Enberg. Ashwin Rao. Jon Crowcroft, and Sasu Tarkoma. Transcending POSIX: The End of an Era? https://www.usenix.org/publications/loginonline/transcending-USENIX Workshop on Hot Topics in Cloud Computposix-end-era, September 2022.
- [66] perftest. https://github.com/linux-rdma/perftest, April 2020.
- [67] Simon Peter, Jialin Li, Irene Zhang, Dan R K Ports, Doug Woos, Arvind Krishnamurthy, Thomas Anderson, and Timothy Roscoe. Arrakis: The Operating System is the Control Plane. In Proceedings of the 11th USENIX Symposium on Operating Systems Design and Implementation, 2014, OSDI '14, pages 2-17, Broomfield, CO, USA, 2014. USENIX Association.
- [68] Jonas Pfefferle, Patrick Stuedi, Animesh Trivedi, Bernard Metzler, Ionnis Koltsidas, and Thomas R. Gross. A Hybrid I/O Virtualization Framework for RDMA-capable Network Interfaces. In Proceedings of the 11th ACM SIGPLAN/SIGOPS International Conference on Virtual Execution Environments, VEE, pages 17-30, Istanbul, Turkey, 2015. ACM Press.
- [69] Maksym Planeta, Jan Bierbaum, Leo Sahaya Daphne Antony, Torsten Hoefler, and Hermann Härtig. MigrOS: Transparent Operating Systems Live Migration Support for Containerised RDMA-applications. In USENIX ATC 2021, pages 47-63, July 2021.
- [70] Maksym Planeta, Till Miemietz, Viktor Reusch, Jan Bierbaum, Michael Roitzsch, and Hermann Härtig. Fast Privileged Function Calls. In Systems for Post-Moore Architectures, Rennes, France, 2022.
- [71] Qifan Pu, Shivaram Venkataraman, and Ion Stoica. Shuffling, Fast and Slow: Scalable Analytics on Serverless Infrastructure. In Proceedings of the 16th USENIX Symposium on Networked Systems Design and Implementation, Boston, MA, USA, 2019.
- [72] Benjamin Rothenberger, Konstantin Taranov, Adrian Perrig, and Torsten Hoefler. ReDMArk: Bypassing RDMA Security Mechanisms. In 30th USENIX Security Symposium, Vancouver, B.C., 2021.
- [73] Hugo Sadok, Zhipeng Zhao, Valerie Choung, Nirav Atre, Daniel S Berger, James C Hoe, Aurojit Panda, and Justine Sherry. We need kernel interposition over the network dataplane. In HotOS, Ann Arbor, MI, USA, 2021.
- [74] Philip Schwan. Lustre: Building a File System for 1,000-node Clusters. In Linux Simposium, 2003.

- [75] Anna Kornfeld Simpson, Adriana Szekeres, Jacob Nelson, and Irene Zhang. Securing RDMA for High-Performance Datacenter Storage Systems. In 12th
- ing, HotCloud 20. USENIX Association, 2020.
- [76] Stephen Smalley, Chris Vance, and Wayne Salamon. Implementing SELinux as a Linux Security Module, 2002.
- [77] Maomeng Su, Mingxing Zhang, Kang Chen, Zhenyu Guo, and Yongwei Wu. RFP: When RPC is Faster than Server-Bypass with RDMA. In Proceedings of the Twelfth European Conference on Computer Systems, EuroSys '17, pages 1-15, New York, NY, USA, April 2017. Association for Computing Machinery.
- [78] Yulin Sun, Qingming Qu, Chenxingyu Zhao, Arvind Krishnamurthy, Hong Chang, and Ying Xiong. TSoR: TCP Socket over RDMA Container Network for Cloud Native Computing, May 2023.
- [79] Konstantin Taranov, Fabian Fischer, and Torsten Hoefler. Efficient RDMA Communication Protocols, December 2022.
- [80] Konstantin Taranov, Benjamin Rothenberger, Adrian Perrig, and Torsten Hoefler. sRDMA - Efficient NIC-based Authentication and Encryption for Remote Direct Memory Access. In 2020 USENIX Annual Technical Conference (USENIX ATC 20), pages 691-704, 2020.
- [81] Tejun Heo. Control Group v2. https://www.kernel.org/doc/Documentation/cgroupv2.txt, October 2015.
- [82] Tigera, Inc. eBPF use cases | Calico Documentation. https://docs.tigera.io/calico/latest/operations/ebpf/usecases-ebpf.
- [83] Shin-Yeh Tsai and Yiying Zhang. LITE Kernel RDMA Support for Datacenter Applications. In Proceedings of the 26th Symposium on Operating Systems Principles - SOSP '17, pages 306-324, Shanghai, China, 2017. ACM Press.
- [84] Akshay Venkatesh, Abhinav Vishnu, Khaled Hamidouche, Nathan Tallent, Dhabaleswar (DK) Panda, Darren Kerbyson, and Adolfy Hoisie. A case for application-oblivious energy-efficient MPI runtime. In Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, pages 1-12, Austin Texas, November 2015. ACM.

- [85] Lluís Vilanova, Lina Maudlej, Shai Bergman, Till Miemietz, Matthias Hille, Nils Asmussen, Michael Roitzsch, Hermann Härtig, and Mark Silberstein. Slashing the disaggregation tax in heterogeneous data centers with FractOS. In *Proceedings of the Seventeenth European Conference on Computer Systems*, pages 352–367, Rennes France, March 2022. ACM.
- [86] Xingda Wei, Fangming Lu, Rong Chen, and Haibo Chen. KRCORE: a microsecond-scale RDMA control plane for elastic computing. arXiv:2201.11578 [cs], December 2021.
- [87] Carsten Weinhold, Adam Lackorzynski, and Hermann Härtig. FFMK: An HPC OS Based on the L4Re Microkernel. In Balazs Gerofi, Yutaka Ishikawa, Rolf Riesen, and Robert W. Wisniewski, editors, *Operating Systems for Supercomputers and High Performance Computing*, pages 335–357. Springer Singapore, Singapore, 2019.
- [88] Ziye Yang, James R. Harris, Benjamin Walker, Daniel Verkamp, Changpeng Liu, Cunyin Chang, Gang Cao, Jonathan Stern, Vishal Verma, and Luse E. Paul. SPDK: A Development Kit to Build High Performance Storage Applications. In 2017 IEEE International Conference on Cloud Computing Technology and Science (CloudCom), pages 154– 161, December 2017.
- [89] Irene Zhang, Amanda Raybuck, Pratyush Patel, Kirk Olynyk, Jacob Nelson, Omar S. Navarro Leija, Ashlie Martinez, Jing Liu, Anna Kornfeld Simpson, Sujay Jayakar, Pedro Henrique Penna, Max Demoulin, Piali Choudhury, and Anirudh Badam. The Demikernel Datapath OS Architecture for Microsecondscale Datacenter Systems. In Proceedings of the ACM SIGOPS 28th Symposium on Operating Systems Principles, SOSP '21, pages 195–211, New York, NY, USA, October 2021. Association for Computing Machinery.
- [90] Yiwen Zhang, Yue Tan, Brent Stephens, and Mosharaf Chowdhury. Justitia: Software multitenancy in hardware kernel-bypass networks. In 19th USENIX Symposium on Networked Systems Design and Implementation (NSDI 22), pages 1307– 1326, 2022.
- [91] Fang Zheng, Hongfeng Yu, Can Hantas, Matthew Wolf, Greg Eisenhauer, Karsten Schwan, Hasan Abbasi, and Scott Klasky. GoldRush: resource efficient in situ scientific data analytics using fine-grained in-

terference aware execution. In *Proceedings of the International Conference on High Performance Computing, Networking, Storage and Analysis*, pages 1– 12, Denver Colorado, November 2013. ACM.