Steffen van Bergerem \square \square

Humboldt-Universität zu Berlin, Germany

Martin Grohe ⊠ [©] RWTH Aachen University, Germany

Nina Runde ⊠ [©] RWTH Aachen University, Germany

— Abstract

Within the model-theoretic framework for supervised learning introduced by Grohe and Turán (TOCS 2004), we study the parameterized complexity of learning concepts definable in monadic second-order logic (MSO). We show that the problem of learning an MSO-definable concept from a training sequence of labeled examples is fixed-parameter tractable on graphs of bounded clique-width, and that it is hard for the parameterized complexity class para-NP on general graphs.

It turns out that an important distinction to be made is between 1-dimensional and higherdimensional concepts, where the instances of a k-dimensional concept are k-tuples of vertices of a graph. For the higher-dimensional case, we give a learning algorithm that is fixed-parameter tractable in the size of the graph, but not in the size of the training sequence, and we give a hardness result showing that this is optimal. By comparison, in the 1-dimensional case, we obtain an algorithm that is fixed-parameter tractable in both.

2012 ACM Subject Classification Theory of computation \rightarrow Logic; Theory of computation \rightarrow Complexity theory and logic; Theory of computation \rightarrow Fixed parameter tractability; Computing methodologies \rightarrow Logical and relational learning; Computing methodologies \rightarrow Supervised learning

Keywords and phrases monadic second-order definable concept learning, agnostic probably approximately correct learning, parameterized complexity, clique-width, fixed-parameter tractable, Boolean classification, supervised learning, monadic second-order logic

Funding Steffen van Bergerem: This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – project number 431183758 (gefördert durch die Deutsche Forschungsgemeinschaft (DFG) – Projektnummer 431183758).

Martin Grohe: Funded by the European Union (ERC, SymSim, 101054974). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council. Neither the European Union nor the granting authority can be held responsible for them.

Nina Runde: This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – project number 453349072 (gefördert durch die Deutsche Forschungsgemeinschaft (DFG) – Projektnummer 453349072).

1 Introduction

We study abstract machine-learning problems in a logical framework with a declarative view on learning, where the (logical) specification of concepts is separated from the choice of specific machine-learning models and algorithms (such as neural networks). Here we are concerned with the computational complexity of learning problems in this logical learning framework, that is, the *descriptive complexity of learning* [8].

Specifically, we consider Boolean classification problems that can be specified in monadic second-order logic (MSO). The input elements for the classification task come from a set \mathbb{X} , the *instance space*. A *classifier* on \mathbb{X} is a function $c: \mathbb{X} \to \{+, -\}$. Given a *training sequence* S of labeled examples $(x, \lambda) \in \mathbb{X} \times \{+, -\}$, we want to find a classifier, called a *hypothesis*, that explains the labels given in S and that can also be used to predict the labels of elements from \mathbb{X} not given as examples. In the logical setting, the instance space \mathbb{X} is a set of tuples from a (relational) structure, called the *background structure*, and classifiers are described by formulas of some logic, in our case MSO, using parameters from the background structure [34] and further studied in [31, 33, 32, 7, 9, 10, 8].

We study these problems within the following well-known settings from computational learning theory. In the consistent-learning model, the examples are assumed to be generated using an unknown classifier, the target concept, from a known concept class. The task is to find a hypothesis that is consistent with the training sequence S, i.e. a function $h: \mathbb{X} \to \{+, -\}$ such that $h(x) = \lambda$ for all $(x, \lambda) \in S$. In Haussler's model of agnostic probably approximately correct (PAC) learning [36], a generalization of Valiant's PAC learning model [52], an (unknown) probability distribution \mathcal{D} on $\mathbb{X} \times \{+, -\}$ is assumed, and training examples are drawn independently from this distribution. The goal is to find a hypothesis that generalizes well, i.e. one is interested in algorithms that return with high probability a hypothesis with a small expected error on new instances drawn from the same distribution. For more background on PAC learning, we refer to [38, 43, 48]. In both settings, we require our algorithms to return a hypothesis from a predefined hypothesis class.

Our Contributions

In this paper, we study the parameterized complexity of the consistent-learning problem MSO-CONSISTENT-LEARN and the PAC-learning problem MSO-PAC-LEARN. In both problems, we are given a graph G (the background structure) and a sequence of labeled training examples of the form (\bar{v}, λ) , where \bar{v} is a k-tuple of vertices from G and $\lambda \in \{+, -\}$. The goal is to find a hypothesis of the form $h_{\varphi,\bar{w}}$ for an MSO formula $\varphi(\bar{x}; \bar{y})$ and a tuple \bar{w} with $h_{\varphi,\bar{w}}(\bar{v}) \coloneqq +$ if $G \models \varphi(\bar{v}; \bar{w})$ and $h_{\varphi,\bar{w}}(\bar{v}) \coloneqq -$ otherwise. For MSO-CONSISTENT-LEARN, this hypothesis should be consistent with the given training examples. For MSO-PAC-LEARN, the hypothesis should generalize well. We restrict the complexity of allowed hypotheses by giving a bound q on the quantifier rank of φ and a bound ℓ on the length of \bar{w} . Both q and ℓ as well as the dimension k of the problem, that is, the length of the tuples to classify, are part of the parameterization of the problems. A detailed description of MSO-CONSISTENT-LEARN is given in Section 3. The problem MSO-PAC-LEARN is formally introduced in Section 5.

▶ **Example 1.1.** Assume we are given the graph G depicted in Figure 1, the training sequence $S = ((v_1, +), (v_3, +), (v_4, -), (v_5, -))$, and k = 1, $\ell = 1$, q = 3. Note that k = 1 indicates that the instances are vertices of the input graph G. Furthermore, $\ell = 1$ indicates that the specification may involve one vertex of the input graph as a parameter. Finally, q = 3 indicates that the formula specifying the hypothesis must have quantifier rank at most 3.



Figure 1 Graph *G* for Example 1.1. Positive examples are shown in purple, and negative examples are shown in orange.

Our choice of a hypothesis $h: V(G) \to \{+, -\}$ consistent with S says that "there is a bipartite partition of the graph such that all positive instances x are on the same side as v_2 and all negative examples are on the other side." This hypothesis can be formally specified in MSO as $h_{\varphi,\bar{w}}$ for the MSO formula $\varphi(x;y) = \exists Z (\psi_{\text{bipartite}}(Z) \land Z(x) \land Z(y))$ and parameter setting $\bar{w} = (v_2)$, where $\psi_{\text{bipartite}}(Z) = \forall z_1 \forall z_2 (E(z_1, z_2) \to \neg(Z(z_1) \leftrightarrow Z(z_2)))$.

For the 1-dimensional case of MSO-CONSISTENT-LEARN, called 1D-MSO-CONSISTENT-LEARN, [32, 31] gave algorithms that are sublinear in the background structures after a linear-time pre-processing stage for the case that the background structure is a string or a tree. This directly implies that 1D-MSO-CONSISTENT-LEARN can be solved in time $f(\ell, q) \cdot n$ for some function f, that is, in fixed-parameter linear time, if the background structure is a string or a tree. Here n is the size of the background structure and ℓ, q are the parameters of the learning problem described above. We generalize the results to labeled graphs of bounded clique-width. Graphs of clique-width c can be described by a *c-expression*, that is, an expression in a certain graph grammar that only uses c labels (see Section 2.1 for details). In our algorithmic results for graphs of bounded clique-width, we always assume that the graphs are given in the form of a *c*-expression. We treat c as just another parameter of our algorithms. By the results of Oum and Seymour [46], we can always compute a $2^{\emptyset(c)}$ -expression for a graph of clique-width c by a fixed-parameter tractable algorithm.

▶ **Theorem 1.2.** Let *C* be a class of labeled graphs of bounded clique-width. Then 1D-MSO-CONSISTENT-LEARN is fixed-parameter linear on *C*.

Since graphs of bounded tree-width also have bounded clique-width, our result directly implies fixed-parameter linearity on graph classes of bounded tree-width.

Our proof for Theorem 1.2 relies on the model-checking techniques due to Courcelle, Makowsky, and Rotics for graph classes of bounded clique-width [23]. To make use of them, we encode the training examples into the graph as new labels. While this construction works for k = 1, it fails for higher dimensions if there are too many examples to encode.

As far as we are aware, all previous results for learning MSO formulas are restricted to the one-dimensional case of the problem. We give the first results for k > 1, presenting two different approaches that yield tractability results in higher dimensions.

As we discuss in Section 5, for the PAC-learning problem MSO-PAC-LEARN in higher dimensions, we can restrict the number of examples to consider to a constant. In this way, we obtain fixed-parameter tractability results for learning MSO-definable concepts in higher dimensions, similar to results for first-order logic on nowhere dense classes [9, 8].

▶ Theorem 1.3. Let \mathcal{C} be a class of labeled graphs of bounded clique-width. Then MSO-PAC-LEARN is fixed-parameter linear on \mathcal{C} .

In the second approach to higher-dimensional tractability, and as the main result of this paper, we show in Section 6 that a consistent hypothesis can be learned on graphs of bounded clique-width with a quadratic running time in terms of the size of the graph.

▶ **Theorem 1.4.** There is a function $g: \mathbb{N}^5 \to \mathbb{N}$ such that, for a Λ -labeled graph G of cliquewidth $\mathsf{cw}(G) \leq c$ and a training sequence S of size |S| = m, the problem MSO-CONSISTENT-LEARN can be solved in time

 $\mathcal{O}((m+1)^{g(c,|\Lambda|,q,k,\ell)}|V(G)|^2).$

While this is not strictly a fixed-parameter tractability result, since we usually do not consider m to be part of the parameterization, we show in Section 7 that this bound is optimal. Technically, this result is much more challenging than Theorems 1.3 and 1.2. While we still use an overall dynamic-programming strategy that involves computing MSO types, here we need to consider MSO types over sequences of tuples. The number of such sequence types is not constantly bounded, but exponential in the length of the sequence. The core of our argument is to prove that the number of relevant types can be polynomially bounded. This fundamentally distinguishes our approach from typical MSO/automata arguments, where types are from a bounded set (and they correspond to the states of a finite automaton).

Lastly, we study MSO-CONSISTENT-LEARN on arbitrary classes of labeled graphs. Analogously to the hardness of learning FO-definable concepts and the relation to the FOmodel-checking problem discussed in [9], we are interested specifically in the relation of MSO-CONSISTENT-LEARN to the MSO-model-checking problem MSO-MC. We show that MSO-MC can already be reduced to the 1-dimensional case of MSO-CONSISTENT-LEARN, even with a training sequence of size two. This yields the following hardness result that we prove in Section 4.

▶ **Theorem 1.5.** 1D-MSO-CONSISTENT-LEARN *is para-NP-hard under fpt Turing reductions.*

Related Work

The model-theoretic learning framework studied in this paper was introduced in [34]. There, the authors give information-theoretic learnability results for hypothesis classes that can be defined using first-order and monadic second-order logic on restricted classes of structures.

Algorithmic aspects of the framework were first studied in [33], where it was proved that concepts definable in first-order logic can be learned in time polynomial in the degree of the background structure and the number of labeled examples the algorithm receives as input, independently of the size of the background structure. This was generalized to first-order logic with counting [7] and with weight aggregation [10]. On structures of polylogarithmic degree, the results yield learning algorithms running in time sublinear in the size of the background structure. It was shown in [32, 7] that sublinear-time learning is no longer possible if the degree is unrestricted. To address this issue, in [32], it was proposed to introduce a preprocessing phase where, before seeing any labeled examples, the background structure is converted to a data structure that supports sublinear-time learning later. This model was applied to monadic second-order logic on strings [32] and trees [31].

The parameterized complexity of learning first-order logic was first studied in [9]. Via a reduction from the model-checking problem, the authors show that on arbitrary relational structures, learning hypotheses definable in FO is AW[*]-hard. In contrast to this, they show that the problem is fixed-parameter tractable on nowhere dense graph classes. This result has been extended to nowhere dense structure classes in [8]. Although not stated as fpt results, the results in [32, 31] yield fixed-parameter tractability for learning MSO-definable concepts on strings and trees if the problem is restricted to the 1-dimensional case where the tuples to classify are single vertices.

The logical learning framework is related to, but different from the framework of *inductive logic programming* (see, e. g., [21, 44, 45]), which may be viewed as the classical logic-learning framework. In the database literature, there are various approaches to learning queries from examples [6, 5, 35, 37, 39, 12, 51, 1, 2, 13, 50, 17]. Many of these are concerned with active learning scenarios, whereas we are in a statistical learning setting. Moreover, most of the results are concerned with conjunctive queries or queries outside the relational database model, whereas we focus on monadic second-order logic. Another related subject in the database literature is the problem of learning schema mappings from examples [3, 14, 18, 19, 30]. In formal verification, related logical learning frameworks [20, 26, 29, 41, 54] have been studied as well. In algorithmic learning theory, related works study the parameterized complexity of several learning problems [4, 40] including, quite recently, learning propositional CNF and DNF formulas and learning solutions to graph problems in the PAC setting [16].

2 Preliminaries

We let \mathbb{N} denote the set of non-negative integers. For $m, n \in \mathbb{N}$, we let $[m, n] \coloneqq \{\ell \in \mathbb{N} \mid m \leq \ell \leq n\}$ and $[n] \coloneqq [1, n]$. For a set V, we let $2^V \coloneqq \{V' \mid V' \subseteq V\}$.

2.1 Clique-Width

In this paper, graphs are always undirected and simple (no loops or parallel edges); we view them as $\{E\}$ -structures for a binary relation symbol E, and we denote the set of vertices of a graph G by V(G). A label set is a set Λ of unary relation symbols, and a Λ -graph or Λ -labeled graph is the expansion of a graph to the vocabulary $\{E\} \cup \Lambda$. A labeled graph is a Λ -graph for any label set Λ .

In the following, we define *expressions* to represent labeled graphs. A base graph is a labeled graph of order 1. For every base graph G, we introduce a base expression β that represents G. Moreover, we have the following operations.

Disjoint union: For disjoint Λ -graphs G_1, G_2 , we define $G_1 \uplus G_2$ to be the union of G_1 and G_2 . If G_1 and G_2 are not disjoint, then $G_1 \uplus G_2$ is undefined.

- Adding edges: For a Λ -graph G and unary relation symbols $P, Q \in \Lambda$ with $P \neq Q$, we let $\eta_{P,Q}(G)$ be the Λ -graph obtained from G by adding an edge between every pair of distinct vertices $v \in P(G)$, $w \in Q(G)$. That is, $E(\eta_{P,Q}(G)) \coloneqq E(G) \cup \{(v,w), (w,v) \mid v \in P(G), w \in Q(G), v \neq w\}$.
- **Relabeling:** For a Λ -graph G and unary relation symbols $P, Q \in \Lambda$ with $P \neq Q$, we let $\rho_{P,Q}(G)$ be the Λ -graph obtained from G by relabeling all vertices in P by Q, that is, $V(\rho_{P,Q}(G)) \coloneqq V(G), \ P(\rho_{P,Q}(G)) \coloneqq \emptyset, \ Q(\rho_{P,Q}(G)) \coloneqq Q(G) \cup P(G), \ \text{and} \ R(\rho_{P,Q}(G)) \coloneqq R(G) \text{ for all } R \in \Lambda \setminus \{P, Q\}.$
- **Deleting labels:** For a Λ -graph G and a unary relation symbol $P \in \Lambda$, we let $\delta_P(G)$ be the restriction of G to $\Lambda \setminus \{P\}$, that is, the $(\Lambda \setminus \{P\})$ -graph obtained from G by removing the relation P(G).

We also introduce a modification of the disjoint-union operator, namely the *ordered-disjoint-union operator* $\textcircled{B}^{<}$, which is used in Section 6 to simplify notations.

Ordered disjoint union: To introduce this operator, we need two distinguished unary relation symbols $P_1^<$ and $P_2^<$. For disjoint Λ -graphs G_1, G_2 , where we assume $P_1^<, P_2^< \notin \Lambda$, we let $G_1 \uplus^< G_2$ be the $(\Lambda \cup \{P_1^<, P_2^<\})$ -expansion of the disjoint union $G_1 \uplus G_2$ with $P_1^<(G_1 \uplus^< G_2) \coloneqq V(G_1)$ and $P_2^<(G_1 \uplus^< G_2) \coloneqq V(G_2)$. By deleting the relations $P_1^<, P_2^<$ immediately after introducing them in an ordered disjoint union, we can simulate a

standard disjoint-union by an ordered disjoint union, that is, $G_1 \uplus G_2 = \delta_{P_1^{<}}(\delta_{P_2^{<}}(G_1 \uplus^{<} G_2)).$

A Λ -expression is a term formed from base expressions β , whose label set is a subset of Λ , using unary operators $\eta_{P,Q}$, $\rho_{P,Q}$, δ_P for $P,Q \in \Lambda$ with $P \neq Q$, and the binary operator \forall . We require Λ -expressions to be well-formed, that is, all base expressions represent base graphs with mutually distinct vertices, and the label sets fit the operators.

Every Λ -expression Ξ describes a Λ' -graph G_{Ξ} for some $\Lambda' \subseteq \Lambda$. Note that there is a one-to-one correspondence between the base expressions in Ξ and the vertices of G_{Ξ} . Actually, we may simply identify the vertices of G_{Ξ} with the base expressions in Ξ . We let $V_{\Xi} := V(G_{\Xi})$ be the set of these base expressions. We may then view an expression Ξ as a tree where V_{Ξ} is the set of leaves of this tree. We let $|\Xi|$ be the number of nodes of the tree. We have $|G_{\Xi}| = |V_{\Xi}| \leq |\Xi|$. In general, we cannot bound $|\Xi|$ in terms of $|G_{\Xi}|$, but for every Λ -expression Ξ , we can find a Λ -expression Ξ' such that $G_{\Xi'} = G_{\Xi}$ and $|\Xi'| \in \mathcal{O}(|\Lambda^2| \cdot |G_{\Xi}|)$.

Each subexpression Ξ' of Ξ describes a labeled graph $G_{\Xi'}$ on a subset $V_{\Xi'} \subseteq V_{\Xi}$ consisting of all base expressions in Ξ' . Note that, in general, $G_{\Xi'}$ is not a subgraph of G_{Ξ} .

For $c \in \mathbb{N}$, a *c*-expression is a Λ -expression for a label set Λ of size $|\Lambda| = c$. It is easy to see that every labeled graph of order n is described by an *n*-expression. The *clique-width* $\mathsf{cw}(G)$ of a (labeled) graph G is the least c such that G is described by a *c*-expression.

We remark that our notion of clique-width differs slightly from the one given by Courcelle and Olariu [24], since we allow vertices to have multiple labels, and we also allow the deletion of labels. Thus, our definition is similar to the definition of *multi-clique-width* [28]. However, for our algorithmic results, the definitions are equivalent, since we have $\mathsf{cw}(G) \leq \mathsf{cw}'(G)$ and $\mathsf{cw}'(G) \in 2^{\mathscr{O}(\mathsf{cw}(G))}$ for every (labeled) graph G, where cw' is the notion of clique-width from [24].

▶ Lemma 2.1 ([46]). For a graph G with n vertices and clique-width c' := cw(G), there is an algorithm that outputs a c-expression for G where $c = 2^{3c'+2} - 1$. The algorithm has a running time of $\mathcal{O}(n^9 \log n)$.

2.2 Monadic Second-Order Logic

We consider monadic second-order (MSO) logic, which is a fragment of second-order logic where we only quantify over unary relations (sets). In MSO, we consider two kinds of free variables, which we call set variables (uppercase X, Y, X_i) and individual variables (lowercase x, y, x_i). The quantifier rank $qr(\varphi)$ of a formula φ is the nesting depth of its quantifiers.

Let τ be a relational vocabulary and $q \in \mathbb{N}$. By $\mathsf{MSO}(\tau, q)$, we denote the set of all MSO formulas of quantifier rank at most q using only relation symbols in τ , and we let $\mathsf{MSO}(\tau) \coloneqq \bigcup_q \mathsf{MSO}(\tau, q)$. By $\mathsf{MSO}(\tau, q, k, s)$, we denote the set of all $\mathsf{MSO}(\tau, q)$ formulas with free individual variables in $\{x_1, \ldots, x_k\}$ and free set variables in $\{X_1, \ldots, X_s\}$. In particular, $\mathsf{MSO}(\tau, q, 0, 0)$ denotes the set of sentences. Moreover, it will be convenient to separate the free individual variables into instance variables (x_1, x_2, \ldots) and parameter variables (y_1, y_2, \ldots) . For this, we let $\mathsf{MSO}(\tau, q, k, \ell, s)$ denote the set of all $\mathsf{MSO}(\tau, q)$ formulas with free instance variables in $\{x_1, \ldots, x_k\}$, free parameter variables in $\{y_1, \ldots, y_\ell\}$, and free set variables in $\{X_1, \ldots, X_s\}$. Furthermore, we write $\varphi(\bar{x}, \bar{y}, \bar{X})$ to denote that the formula φ has its free instance variables among the entries of \bar{x} , its free parameter variables among the entries \bar{X} .

We normalize formulas such that the set of normalized formulas in $MSO(\tau, q, k, \ell, s)$ is finite, and there is an algorithm that, given an arbitrary formula in $MSO(\tau, q, k, \ell, s)$, decides if the formula is normalized, and if not, computes an equivalent normalized formula. In the

following, we assume that all formulas are normalized.

In this paper, all structures we consider will be labeled graphs for some label set Λ . In notations such as $MSO(\tau, ...)$, it will be convenient to write $MSO(\Lambda, ...)$ if $\tau = \{E\} \cup \Lambda$.

2.3 Types

Let G be a Λ -labeled graph and $\bar{v} \in (V(G))^k$. The q-type of \bar{v} in G is the set $\mathsf{tp}_q^G(\bar{v})$ of all formulas $\varphi(\bar{x}) \in \mathsf{MSO}(\Lambda, q, k, 0)$ such that $G \models \varphi(\bar{v})$. A (Λ, q, k) -type is a set $\theta \subseteq \mathsf{MSO}(\Lambda, q, k, 0)$ such that, for each $\varphi \in \mathsf{MSO}(\Lambda, q, k, 0)$, either $\varphi \in \theta$ or $\neg \varphi \in \theta$. We denote the set of all (Λ, q, k) -types by $\mathsf{Tp}(\Lambda, q, k)$. Note that $\mathsf{tp}_q^G(\bar{v}) \in \mathsf{Tp}(\Lambda, q, k)$. For a type $\theta \in \mathsf{Tp}(\Lambda, q, k)$, we write $G \models \theta(\bar{v})$ if $G \models \varphi(\bar{v})$ for all $\varphi(\bar{x}) \in \theta$. Observe that $G \models \theta(\bar{v}) \iff \mathsf{tp}_q^G(\bar{v}) = \theta$. We say that a type $\theta \in \mathsf{Tp}(\Lambda, q, k)$ is *realizable* if there is some Λ -labeled graph G and tuple $\bar{v} \in (V(G))^k$ such that $\theta = \mathsf{tp}_q^G(\bar{v})$. We are not particularly interested in types that are not realizable, but it is undecidable if a type θ is realizable, whereas the sets $\mathsf{Tp}(\Lambda, q, k)$ are decidable. (More precisely, there is an algorithm that, given Λ, q, k and a set θ of formulas, decides if $\theta \in \mathsf{Tp}(\Lambda, q, k)$.) For a (Λ, q, k) -type θ and a Λ -labeled graph G, we let

$$\theta(G) \coloneqq \left\{ \bar{v} \in (V(G))^k \mid G \models \theta(\bar{v}) \right\}.$$

If $\theta(G) \neq \emptyset$, we say that θ is *realizable in G*.

As for formulas, we split the variables for types into two parts, so we consider (Λ, q, k, ℓ) types $\theta \subseteq \mathsf{MSO}(\Lambda, q, k, \ell, 0)$, and we denote the set of all these types by $\mathsf{Tp}(\Lambda, q, k, \ell)$. For a Λ -labeled graph G and tuples $\bar{v} \in (V(G))^k$, $\bar{w} \in (V(G))^\ell$, we often think of $\mathsf{tp}_q^G(\bar{v}, \bar{w})$ as the q-type of \bar{w} over \bar{v} in G. Moreover, we let

$$\theta(\bar{v}, G) \coloneqq \{ \bar{w} \in (V(G))^{\ell} \mid G \models \theta(\bar{v}, \bar{w}) \}.$$

If $\theta(\bar{v}, G) \neq \emptyset$, we say that θ is realizable over \bar{v} in G.

For a vector $\bar{k} = (k_1, \ldots, k_m) \in \mathbb{N}^m$ and a set V, we let $V^{\bar{k}}$ be the set of all sequences $\alpha = (\bar{v}_1, \ldots, \bar{v}_m)$ of tuples $\bar{v}_i \in V^{k_i}$. Let G be a labeled graph, $\alpha = (\bar{v}_1, \ldots, \bar{v}_m) \in V^{\bar{k}}$ for some $\bar{k} \in \mathbb{N}^m$, and $\bar{w} \in (V(A))^{\ell}$. We define the *q*-type of \bar{w} over α in G to be the tuple

$$\mathsf{tp}_q^G(a,\bar{w}) \coloneqq \big(\mathsf{tp}_q^G(\bar{v}_1,\bar{w}),\ldots,\mathsf{tp}_q^G(\bar{v}_m,\bar{w})\big).$$

Again, we need an "abstract" notion of type over a sequence. A $(\Lambda, q, \bar{k}, \ell)$ -type for a tuple $\bar{k} = (k_1, \ldots, k_m) \in \mathbb{N}^m$ is an element of

$$\mathsf{Tp}(\Lambda, q, \bar{k}, \ell) \coloneqq \prod_{i=1}^{m} \mathsf{Tp}(\Lambda, q, k_i, \ell).$$

Let $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$. For a labeled graph G, a sequence $a = (\bar{v}_1, \ldots, \bar{v}_m) \in (V(G))^{\bar{k}}$, and a tuple $\bar{w} \in (V(G))^{\ell}$, we write $G \models \bar{\theta}(a, \bar{w})$ if $G \models \theta_i(\bar{v}_i, \bar{w})$ for all $i \in [m]$. Note that $G \models \bar{\theta}(a, \bar{w}) \iff \mathsf{tp}_q^G(a, \bar{w}) = \bar{\theta}$. For a type $\bar{\theta} \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$, a Λ -labeled graph G, and a sequence $a \in (V(G))^{\bar{k}}$, we let

$$\bar{\theta}(a,G) \coloneqq \left\{ \bar{w} \in (V(G))^{\ell} \mid G \models \theta(a,\bar{w}) \right\}.$$

If $\bar{\theta}(\alpha, G) \neq \emptyset$, we say that $\bar{\theta}$ is realizable over α in G.

2.4 VC Dimension

For $q, k, \ell \in \mathbb{N}$, a formula $\varphi(\bar{x}, \bar{y}) \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$, a Λ -labeled graph G, and a tuple $\bar{w} \in (V(G))^{\ell}$, we let

$$\varphi(G, \bar{w}) \coloneqq \{ \bar{v} \in (V(G))^k \mid G \models \varphi(\bar{v}, \bar{w}) \}.$$

For a set $X \subseteq (V(G))^k$, we let

$$H_{\varphi}(G,X) \coloneqq \left\{ X \cap \varphi(G,\bar{w}) \mid \bar{w} \in (V(G))^{\ell} \right\}.$$

We say that X is shattered by φ if $H_{\varphi}(G, X) = 2^X$. The VC dimension $\operatorname{VC}(\varphi, G)$ of φ on G is the maximum $d \in \mathbb{N}$ such that there is a set $X \subseteq V(G)^k$ of cardinality |X| = d that is shattered by φ . In this paper, we are only interested in finite graphs, but for infinite G, we let $\operatorname{VC}(\varphi, G) \coloneqq \infty$ if the maximum does not exist. For a class \mathscr{C} of Λ -labeled graphs, the VC dimension of φ over \mathscr{C} , $\operatorname{VC}(\varphi, \mathscr{C})$, is the least d such that $\operatorname{VC}(\varphi, G) \leq d$ for all $G \in \mathscr{C}$ if such a d exists, and ∞ otherwise.

▶ Lemma 2.2 ([34, Theorem 17]). There is a function $g: \mathbb{N}^5 \to \mathbb{N}$ such that the following holds. Let Λ be a label set, let \mathscr{C} be the class of all Λ -graphs of clique-width at most c, and let $q, k, \ell \in \mathbb{N}$. Then $\operatorname{VC}(\varphi, \mathscr{C}) \leq g(c, |\Lambda|, q, k, \ell)$ for all $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$.

2.5 Parameterized Complexity

A parameterization κ is a function mapping the input x of a problem to a natural number $\kappa(x) \in \mathbb{N}$. An algorithm \mathbb{A} is an *fpt algorithm with respect to* κ if there is a computable function $f: \mathbb{N} \to \mathbb{N}$ and a polynomial p such that for every input x the running time of \mathbb{A} is at most $f(\kappa(x)) \cdot p(|x|)$.

A parameterized problem is a tuple (Q, κ) . We say $(Q, \kappa) \in \mathsf{FPT}$ or (Q, κ) is fixedparameter tractable if there is an fpt algorithm with respect to κ for Q, and we say (Q, κ) is fixed-parameter linear if the polynomial in the running time of the fpt algorithm is linear. We say $(Q, \kappa) \in \mathsf{para-NP}$ if there is a nondeterministic fpt algorithm with respect to κ for Q. If the parameterization is clear from the context, then we omit it.

For two parameterized problems $(Q, \kappa), (Q', \kappa')$, an *fpt Turing reduction* from (Q, κ) to (Q', κ') is an algorithm \mathbb{A} with oracle access to Q' such that \mathbb{A} decides Q, \mathbb{A} is an fpt algorithm with respect to κ , and there is a computable function $g: \mathbb{N} \to \mathbb{N}$ such that on input $x, \kappa'(x') \leq g((\kappa(x)))$ for all oracle queries with oracle input x'.

For additional background on parameterized complexity, we refer to [27].

3 Tractability for One-Dimensional Training Data on Well-Behaved Classes

We start by formalizing the parameterized version of the problem MSO-CONSISTENT-LEARN described in the introduction. For a training sequence S, a graph G, and a hypothesis $h_{\varphi,\bar{w}}$, we say $h_{\varphi,\bar{w}}$ is consistent with S on G if for every positive example $(\bar{v}, +) \in S$, we have $G \models \varphi(\bar{v}, \bar{w})$, and for every negative example $(\bar{v}, -) \in S$, we have $G \not\models \varphi(\bar{v}, \bar{w})$.

MSO-Consistent-Learn

Instance: Λ -labeled graph $G, q, k, \ell \in \mathbb{N}$, training sequence $S \in (V(G)^k \times \{+, -\})^m$ **Parameter**: $\kappa := |\Lambda| + q + k + \ell$ **Problem**: Return a hypothesis $h_{\varphi,\bar{w}}$ consisting of a formula $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$ and a parameter setting $\bar{w} \in V(G)^{\ell}$ such that $h_{\varphi,\bar{w}}$ is consistent with the training sequence S on G, if such a hypothesis exists. Reject if there is no consistent hypothesis.

The problem 1D-MSO-CONSISTENT-LEARN refers to the 1-dimensional version of the problem MSO-CONSISTENT-LEARN where the arity k of the training examples is 1. The tractability results for 1D-MSO-CONSISTENT-LEARN are significantly more straightforward than those for the higher-dimensional problem. This is due to the fact that the full training sequence can be encoded into the graph by only adding two new labels as follows.

▶ Lemma 3.1. Given a Λ -labeled graph G, an MSO formula $\varphi(x, \bar{y})$ of quantifier rank q_{φ} , and a training sequence $S \in (V(G) \times \{+, -\})^m$, there is

- a label set Λ' of size $|\Lambda| + 2$,
- \blacksquare a Λ' -labeled graph G_S ,

and an MSO formula $\varphi'(\bar{y})$ of quantifier rank $q_{\varphi} + 1$

such that for all $\bar{w} \in V(G)^{\ell}$, we have $G_S \models \varphi'(\bar{w})$ if and only if $h_{\varphi,\bar{w}}$ is consistent with S on G.

Proof. Let $\Lambda' := \Lambda \uplus \{P, N\}$ for two new labels P, N. Furthermore, let G_S be the Λ' -structure with the same vertex set as G, and the labels $R(G_S) = R(G)$ for $R \in \Lambda$, $P(G_S) = \{v \in V(G) \mid (v, +) \in S\}$, and $N(G_S) = \{v \in V(G) \mid (v, -) \in S\}$.

Based on the $\mathsf{MSO}(\Lambda, q_{\varphi}, 1, \ell, 0)$ formula $\varphi(x; \bar{y})$, we define the $\mathsf{MSO}(\Lambda', q_{\varphi} + 1, 0, \ell, 0)$ formula $\varphi'(\bar{y})$ as

$$\varphi'(y_1, \dots, y_\ell) \coloneqq \forall x \Big(\big(P(x) \to \varphi(x, y_1, \dots, y_\ell) \big) \land \\ \big(N(x) \to \neg \varphi(x, y_1, \dots, y_\ell) \big) \Big).$$

Then, we have $G_S \models \varphi'(\bar{w})$ if and only if $h_{\varphi,\bar{w}}$ is consistent with the training sequence S on G.

As discussed in Section 2.2, there is a function $f: \mathbb{N}^4 \to \mathbb{N}$ such that $|\mathsf{MSO}(\Lambda, q, k, \ell, 0)| \leq f(|\Lambda|, q, k, \ell)$. Therefore, to solve 1D-MSO-CONSISTENT-LEARN, we can iterate over all formulas $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$ and focus on finding a parameter setting $\overline{w} \in V(G)^{\ell}$ such that $h_{\varphi,\overline{w}}$ is consistent with S on G. Moreover, if the model-checking problem on a graph class with additional labels is tractable, then finding a consistent parameter setting is tractable as well by performing model checking on the graph with the encoded training sequence.

▶ Lemma 3.2. Let \mathscr{C} be a class of labeled graphs, let \mathscr{C}_i be the class of all extensions of graphs from \mathscr{C} by *i* additional labels for all $i \in \mathbb{N}$, let $f : \mathbb{N} \to \mathbb{N}$ be a function, and let $c \in \mathbb{N}$ such that the MSO-model-checking problem on \mathscr{C}_i can be solved in time $f(|\varphi|) \cdot |V(G)|^c$ for all $i \in \mathbb{N}$, where φ is the MSO sentence and $G \in \mathscr{C}_i$ is the labeled graph given as input. There is a function $g : \mathbb{N}^3 \to \mathbb{N}$ such that 1D-MSO-CONSISTENT-LEARN can be solved on \mathscr{C} in time $g(|\Lambda|, q, \ell) \cdot |V(G)|^{c+1}$.

Proof. We can iterate over all formulas $\varphi \in \mathsf{MSO}(\Lambda, q, 1, \ell, 0)$ and encode the training sequence into the graph using Lemma 3.1, resulting in a Λ' -labeled graph G_S and a formula φ' . There is a consistent parameter setting $\bar{w} \in (V(G))^{\ell}$ if and only if it holds that $G_S \models \exists y_1, \ldots \exists y_\ell \varphi'(y_1, \ldots, y_\ell)$, which can be checked using an algorithm for the MSO-model-checking problem.

We enforce assigning a specific vertex $v_1 \in V(G)$ to the variable y_1 by building a new graph G_{S,v_1} and encoding the parameter choice as a new label P_{y_1} with $P_{y_1}(G_{S,v_1}) = \{v_1\}$. For $\bar{w} = (w_1, \ldots, w_\ell) \in V(G)^\ell$ where $w_1 = v_1$, we have $G_S \models \varphi'(\bar{w})$ if and only if

$$G_{S,v_1} \models \exists y_1 \dots \exists y_\ell (P_{y_1}(y_1) \land \varphi'(y_1, y_2 \dots, y_\ell)).$$

We then perform model checking on G_{S,v_1} to see if we have chosen a vertex v_1 for y_1 that can be extended into a consistent parameter setting. Once such a vertex is found, we can continue with the next variable. In total, we add $\ell + 2$ new labels to the graph. In this way, a consistent parameter setting can be computed in at most $|V(G)| \cdot \ell$ rounds of model checking.

If the input graph is given in the form of a *c*-expression, then the MSO model-checking problem is fixed-parameter linear on classes of bounded clique-width [23]. Therefore, Lemma 3.2 implies that there is a function $g: \mathbb{N}^4 \to \mathbb{N}$ such that 1D-MSO-CONSISTENT-LEARN can be solved in time $g(\mathsf{cw}(G), |\Lambda|, q, \ell) \cdot |G|^2$.

Theorem 1.2 improves this bound for classes of graphs of bounded clique-width even further, showing that the problem 1D-MSO-CONSISTENT-LEARN can be solved in time linear in the size of the graph.

▶ **Theorem 1.2.** Let *C* be a class of labeled graphs of bounded clique-width. Then 1D-MSO-CONSISTENT-LEARN is fixed-parameter linear on *C*.

Since graphs of tree-width c_t have a clique-width of at most $3 \cdot 2^{c_t-1}$ [22], Theorem 1.2 implies that for classes of graphs of bounded tree-width, 1D-MSO-CONSISTENT-LEARN is fixed-parameter linear as well. Moreover, although all background structures we consider in this paper are labeled graphs, we remark that the result for classes of bounded tree-width also holds on arbitrary relational structures and a corresponding version of 1D-MSO-CONSISTENT-LEARN.

The remainder of this section is dedicated to the proof of Theorem 1.2. As argued above, since the number of possible formulas to check can be bounded in terms of $|\Lambda|$, q, and ℓ , it suffices to show how to find a parameter setting \bar{w} for a given formula φ such that the hypothesis $h_{\varphi,\bar{w}}$ is consistent with the training sequence S, or reject if there is no such parameter setting.

3.1 Preprocessing the Input Graph

Let G be a Λ -labeled graph and let $S \in (V(G) \times \{+, 1\})^m$ be the training sequence given as input for 1D-MSO-CONSISTENT-LEARN. We assume that we are given G in form of a c-expression Ξ . Let $\varphi \in \mathsf{MSO}(\Lambda, q, 1, \ell, 0)$ be the formula for which we want to find a consistent parameter setting.

As described in Lemma 3.1, we encode the training sequence S into G. This results in a Λ' -labeled graph G_S (with $|\Lambda'| = |\Lambda| + 2$), a corresponding (c+2)-expression Ξ_S , and an $\mathsf{MSO}(\Lambda', q+1, 0, \ell, 0)$ formula $\varphi_2(\bar{y})$ such that

 $G_S \models \varphi_2(\bar{w}) \iff h_{\varphi,\bar{w}}$ is consistent with S on G.

Further, using the following lemma, we transform φ_2 into a formula φ_3 that has free set variables instead of free individual variables. This allows us to directly use the results from [23].

▶ Lemma 3.3. For a Λ' -labeled graph G_S and an $\mathsf{MSO}(\Lambda', q+1, 0, \ell, 0)$ formula $\varphi_2(y_1, \ldots, y_\ell)$, there is an $\mathsf{MSO}(\Lambda', q+\ell+3, 0, 0, \ell)$ formula $\varphi_3(X_1, \ldots, X_\ell)$ such that for all $v_1, \ldots, v_\ell \in V(G_S)$, we have that

$$G_S \models \varphi_2(v_1, \dots, v_\ell) \iff G_S \models \varphi_3(\{v_1\}, \dots, \{v_\ell\}).$$

Moreover, for all $V_1, \ldots, V_{\ell} \subseteq V(G_S)$, we have $G_S \not\models \varphi_3(V_1, \ldots, V_{\ell})$ if $|V_i| \neq 1$ for any $i \in [\ell]$.

Proof. Let

$$Sing(X_i, y_i) \coloneqq X_i(y_i) \land \forall x \forall y \Big(\big(X_i(x) \land X_i(y) \big) \to x = y \Big)$$

be the formula that enforces that the set variable X_i has exactly one element, which is y_i . Now we can bind all free individual variables and replace them by free set variables by setting

$$\varphi_3(X_1,\ldots,X_\ell) \coloneqq \exists y_1 \ldots \exists y_\ell \Big(\bigwedge_{i \in [\ell]} Sing(X_i,y_i) \land \varphi_2(y_1,\ldots,y_\ell)\Big).$$

This formula satisfies the requirements stated in the lemma.

◀

3.2 Computing the Parameters

For every $\mathsf{MSO}(\Lambda')$ formula $\psi(X_1, \ldots, X_\ell)$ and every Λ' -labeled graph G, we let

$$\psi(G) \coloneqq \{ (V_1, \dots, V_\ell) \mid G \models \psi(V_1, \dots, V_\ell) \}$$

be the set of all parameter settings for which ψ holds in G. Note that any $(V_1, ..., V_\ell) \in \varphi_3(G_S)$ yields a consistent parameter setting for φ .

Computing all possible parameter settings is intractable, as the size of $\varphi_3(G_S)$ might be up to $|V(G_S)|^{\ell}$. Instead, we follow the construction from [23] to compute a subset of $\varphi_3(G_S)$ that is empty if and only if $\varphi_3(G_S)$ is empty. Let $q' \coloneqq q + \ell + 3$. We use the following three results to recursively compute the subset.

▶ Lemma 3.4 ([23]). For every $P, Q \in \Lambda'$ with $P \neq Q$, for every operation $f \in \{\rho_{P,Q}, \eta_{P,Q}\}$, and for every $\psi \in \mathsf{MSO}(\Lambda', q', 0, 0, \ell)$, there is a formula $\psi' \in \mathsf{MSO}(\Lambda', q', 0, 0, \ell)$ of the same quantifier rank such that for all Λ' -labeled graphs G',

 $\psi(f(G')) = \psi'(G').$

Moreover, ψ' can be computed from ψ .

It is easy to see that this also holds for the operation δ_P .

▶ Lemma 3.5. For every $P \in \Lambda'$ and $\psi \in \mathsf{MSO}(\Lambda', q', 0, 0, \ell)$, there is a formula $\psi' \in \mathsf{MSO}(\Lambda', q', 0, 0, \ell)$ of the same quantifier rank such that for all Λ' -labeled graphs G',

 $\psi(\delta_P(G')) = \psi'(G').$

Moreover, ψ' can be computed from ψ by replacing all occurrences of P(x) in ψ by \perp .

▶ Lemma 3.6 ([42], Feferman–Vaught for MSO). For every $\psi \in MSO(\Lambda', q', 0, 0, \ell)$, there are $MSO(\Lambda', q', 0, 0, \ell)$ formulas $\theta_1, \ldots, \theta_m$ and χ_1, \ldots, χ_m such that all formulas have the same free variables as ψ and have quantifier rank no larger than the quantifier rank of ψ , and for every two Λ' -labeled graphs G_1 and G_2 such that G_1 and G_2 are disjoint,

$$\psi(G_1 \uplus G_2) = \bigcup_{i=1}^m \theta_i(G_1) \boxtimes \chi_i(G_2),$$

where

$$A \boxtimes B \coloneqq \{ (A_1 \cup B_1, \dots, A_n \cup B_n) \mid (A_1, \dots, A_n) \in A, (B_1, \dots, B_n) \in B \}$$

Moreover, $\theta_1, \ldots, \theta_m$ and χ_1, \ldots, χ_m can be computed from ψ .

In the following, we view the (c + 2)-expression Ξ_S as a tree of operations which we refer to by \mathscr{T}_{Ξ_S} . We start with assigning the formula φ_3 to the root of the tree \mathscr{T}_{Ξ_S} . From there, we assign formulas to each inner node of the tree. If a node represents an operation $\rho_{P,Q}$, $\eta_{P,Q}$ or δ_P , then we apply Lemma 3.4 or Lemma 3.5 respectively to every formula assigned to the node and assign the resulting formulas to the child node. If the node represents an operation \uplus , then we apply Lemma 3.6 to every formula assigned to the node and assign the formulas $\theta_1, \ldots, \theta_m$ to the first child and χ_1, \ldots, χ_m to the second child. Note that the quantifier rank, the number of free variables, and the vocabulary stay the same in each step. We can bound the number of formulas assigned no each node by $|\mathsf{MSO}(\Lambda', q', 0, 0, \ell)|$, which only depends on $|\Lambda|, q$, and ℓ .

After this step, we have a list of formulas Ψ assigned to each node of \mathcal{F}_{Ξ_S} . Starting at the leafs, which correspond to base graphs G_v that only have a single node v, we compute the sets of consistent parameter settings $\psi(G_v)$ for each formula $\psi \in \Psi$. On a graph with a single node, $\psi(G_v)$ can be computed by a simple brute-force algorithm in time $\mathcal{O}(2^{\ell} \cdot 2^{q'} \cdot |\varphi|)$. We then construct a parameter setting bottom up from the leafs, following Lemmas 3.4–3.6.

▶ Lemma 3.7. With the above-described procedure, we find a consistent parameter setting $\overline{V} \in \varphi_3(G_S)$ if and only if we find a consistent parameter setting in an analogous procedure where, in each node of \mathcal{T}_{Ξ_S} , corresponding to a labeled graph G', we only keep one parameter setting $\overline{V}' \in \varphi'(G')$ for every formula φ' assigned to the node.

Proof. We show that if we can find a parameter setting in the root using all possible parameter settings, we can also find a parameter setting in the root using only a single representative setting per node and formula. Unary operations $\rho_{P,Q}$ and $\eta_{P,Q}$ do not change the number of parameter settings in a node, and the initialization operation is executed only on leafs. Now consider the case of $G_1 \oplus G_2$ with formula ψ and with corresponding formulas $\theta_1, \ldots, \theta_m$ and χ_1, \ldots, χ_m in the children. For all $i \in [m]$, let $\bar{g}_{1,i}$ be the single representative setting saved for θ_i , where $\bar{g}_{1,i} = \emptyset$ if $\theta_i(G_1) = \emptyset$, and $\bar{g}_{1,i} \in \theta_i(G_1)$ else. Analogously, let $\bar{g}_{2,i}$ be the single representative setting saved for χ_i in G_2 .

In the above-described procedure, we find a consistent parameter setting if and only if $\psi(G_1 \uplus G_2) \neq \emptyset$. By Lemma 3.6, this holds if and only if $\theta_i(G_1) \boxtimes \chi_i(G_2) \neq \emptyset$, or, equivalently, $\theta_i(G_1) \neq \emptyset$ and $\chi_i(G_2) \neq \emptyset$, for some $i \in [m]$. This holds if and only if $\overline{g}_{1,i} \neq \emptyset$ and $\overline{g}_{2,i} \neq \emptyset$ for some $i \in [m]$. These are precisely the cases in which we find a consistent parameter setting if we only keep one parameter setting for every formula in every node.

Now, we can reconstruct a parameter setting for the root, following Lemmas 3.4–3.6. Since there is only a constant number of formulas assigned to each node, say $c = g(|\Lambda|, q, \ell)$ for

some $g: \mathbb{N}^3 \to \mathbb{N}$, and we only save at most one parameter setting per formula and node, we compute at most c settings for each node using Lemma 3.4 or Lemma 3.5, and at most c^2 settings for each node using Lemma 3.6, which we can then again reduce to c settings. Hence, all in all, there is a function $f: \mathbb{N}^4 \to \mathbb{N}$ such that a consistent hypothesis $h_{\varphi,\bar{w}}$ is found in time $\mathcal{O}(|V(G)| \cdot f(c, |\Lambda|, q, \ell))$. This concludes the proof of Theorem 1.2.

4 Hardness for One-Dimensional Training Data

Previously, we restricted the input graph of the MSO-learning problem to certain well-behaved classes. Now, we consider the problem MSO-CONSISTENT-LEARN without any restrictions. Van Bergerem, Grohe, and Ritzert showed in [9] that there is a close relation between first-order model checking (FO-MC) and learning first-order formulas. The fpt-reduction in [9] from model checking to learning yields AW[*]-hardness for learning first-order formulas on classes of structures that are not nowhere dense. It is simple to show (and not surprising) that MSO-CONSISTENT-LEARN is at least as hard as FO-MC. The more interesting question is whether MSO-CONSISTENT-LEARN is at least as hard as the model-checking problem for MSO sentences (MSO-MC), which is defined as follows.

MSO-MC

Instance: Λ -labeled graph G, $\mathsf{MSO}(\Lambda)$ sentence φ **Parameter**: $|\varphi|$ **Problem**: Decide whether $G \models \varphi$ holds.

We give a positive answer, which even holds for the MSO-learning problem with only one-dimensional training data where we restrict the training sequence to contain at most two training examples.

▶ Lemma 4.1. The model-checking problem MSO-MC is fpt Turing reducible to 1D-MSO-CONSISTENT-LEARN where we restrict the training sequence S given as input to have length at most 2.

MSO-MC is para-NP-hard under fpt Turing reductions as even for some fixed sentence φ , the corresponding model-checking problem can be NP-hard (for example for a formula defining 3-COLORABILITY, see [27] for details). Hence, Lemma 4.1 proves Theorem 1.5.

Proof of Lemma 4.1. We describe an fpt algorithm with access to a 1D-MSO-CONSISTENT-LEARN oracle that solves MSO-MC. Let G be a Λ -labeled graph, and let φ be an MSO(Λ) sentence. Let n := |V(G)|. W.l.o.g., we may assume that Λ only contains labels that appear in φ and hence, we have $|\Lambda| \leq |\varphi|$. We decide whether $G \models \varphi$ holds recursively by decomposing the input formula. While handling negation and Boolean connectives is easy, the crucial part of the computation is handling quantification. Thus, we assume that $\varphi = \exists x \psi$ or $\varphi = \exists X \psi$ for some MSO formula ψ . For both types of quantifiers, we use the 1D-MSO-CONSISTENT-LEARN oracle to identify a small set of candidate vertices or sets such that ψ holds for any vertex or set if and only if it holds for any of the identified candidates. Then, since the number of candidates will only depend on $|\psi|$, we can check recursively whether ψ holds for any of them and thereby decide MSO-MC with an fpt algorithm.

First, assume that $\varphi = \exists x\psi$. For every pair of distinct vertices $v, v' \in V(G)$, we call the 1D-MSO-CONSISTENT-LEARN oracle with input graph $G, q = qr(\psi), \ell = 0$, and training sequence S = ((v, +), (v', -)). Since $\ell = 0$, the learning algorithm may not use any vertices as parameters in the hypothesis. Thus, the oracle returns a hypothesis if and only if

 $\operatorname{tp}_q^G(v) \neq \operatorname{tp}_q^G(v')$. Note that the oracle answers induce a partition on V(G) where two vertices v and v' are in the same class if and only if the oracle does not return a hypothesis on the input as specified above. The number of classes is the number of vertex q-types in G, which only depends on q and $|\Lambda|$ and can thus be bounded in terms of $|\varphi|$. Finally, since $G \models \psi(v)$ if and only if $G \models \psi(v')$ for all vertices v and v' in the same class, it suffices to check a single candidate per class.

Let $v \in V(G)$ be the candidate for which we want to check whether $G \models \psi(v)$ holds. To be able to run our algorithm for MSO-MC recursively, we encode our choice via labels in the graph and then turn the formula ψ into a sentence. For this, let $\Lambda' \coloneqq \Lambda \uplus \{I_v, N_v\}$. For $v \in V(G)$, let G_v be the Λ' -labeled graph with vertex set $V(G_v) = V(G)$ and labels $R(G_v) \coloneqq R(G)$ for all $R \in \Lambda$, $I_v(G_v) \coloneqq \{v\}$, and $N_v(G_v) \coloneqq \{w \in V(G) \mid (v, w) \in E(G)\}$. W.l.o.g., we assume that the formula $\psi(x)$ does not contain atoms of the form x = x. The formula can then be transformed into a sentence ψ_v by replacing every atom of the form y = x or x = y by $I_v(y)$, and by replacing atoms of the form E(x, y) or E(y, x) by $N_v(y)$. We have $G \models \psi(v)$ if and only if $G_v \models \psi_v$. Furthermore, $|\Lambda'| = |\Lambda| + 2$, and G_v and ψ_v can be computed by an fpt algorithm.

Note that for now, considering only first-order quantifiers, the depth and the degree of the recursion tree can be bounded in terms of $|\varphi|$. Moreover, in all oracle queries, the vertex set of the input graph is V(G), we only use training sequences of length 2, and the parameter of the problem 1D-MSO-CONSISTENT-LEARN can be bounded in terms of $|\varphi|$.

In the remainder of this proof, we describe how to handle second-order quantifiers. Assume that $\varphi = \exists X \psi$. Similarly to the first case, we want to find a small set of candidate sets for X. However, in contrast to the first-order quantifier, querying the oracle for every possible choice would lead to a running time that is exponential in the size of the input graph. To overcome this issue, intuitively, we proceed as follows. We go through the possible choices in n rounds, where in round i, we only consider candidate sets of size i. Overall, we compute nfamilies V_1, \ldots, V_n of candidates, where every single family V_i is small, that is, the size of V_i only depends on $|\varphi|$, say $f(|\varphi|)$. In the first round, we compute V_1 by going through all sets of size 1. Based on answers of the 1D-MSO-CONSISTENT-LEARN oracle, we keep only $f(|\varphi|)$ many candidates. Then, in round i+1 for i>0, we consider all extensions of the sets in V_i by a single element, which are $f(|\varphi|) \cdot n$ many possible choices to consider. Again, using the oracle, we keep only $f(|\varphi|)$ many candidates and call the resulting family of candidates V_{i+1} . After n rounds, all in all, we have $f(|\varphi|) \cdot n$ many candidates. In a last step, we then also compare candidates of different sizes, ending up with at most $f(|\varphi|)$ candidates in total. Similarly to the first-order quantifier, for every candidate, we can encode the candidate via labels in the graph and run our algorithm for MSO-MC recursively. In the following, we formalize every single step of the described procedure.

First, we describe how to find the small number of candidates in each round. For a set $C \subseteq V(G)$, let the *q*-type $\mathsf{tp}_q^G(C)$ of *C* in *G* be the set of all $\mathsf{MSO}(\Lambda, q, 0, 1)$ formulas $\alpha(X)$ with $G \models \alpha(C)$. Now, for every $\mathsf{MSO}(\Lambda, q, 0, 1)$ formula $\gamma(X)$, consider the $\mathsf{MSO}(\Lambda, q+2, 0, 1)$ formula

 $\gamma'(X) = \exists Y \big(\forall x (X(x) \to Y(x)) \land \gamma(Y) \big).$

This formula checks whether any superset of X (including X itself) satisfies γ . Thus, if two sets C_1, C_2 have the same (q+2)-type, then for every superset $C'_1 \supseteq C_1$, there is a superset $C'_2 \supseteq C_2$ of the same q-type. Hence, when computing the families V_i , it suffices to keep only one of the two sets.

To check for two sets $C_1, C_2 \subseteq V(G)$ whether they have the same (q+2)-type, we use the 1D-MSO-CONSISTENT-LEARN oracle. As the input graph, we choose the Λ' -labeled graph



Figure 2 Input graph G' of the 1D-MSO-CONSISTENT-LEARN oracle.

G' with $\Lambda' \coloneqq \Lambda \uplus \{C\}$, vertex set $V(G') \coloneqq \{(v,1), (v,2) \mid v \in V(G)\} \uplus \{w_1, w_2\}$, edge set

$$E(G') \coloneqq \{ ((v,i), (v',i)) \mid (v,v') \in E(G), i \in \{1,2\} \} \\ \cup \{ ((v,i), w_i), (w_i, (v,i)) \mid v \in V(G), i \in \{1,2\} \},\$$

and labels $C(G') := \{(v,1) \mid v \in C_1\} \cup \{(v,2) \mid v \in C_2\}$ and $R(G') := \{(v,1), (v,2) \mid v \in C_2\}$ R(G) for all $R \in \Lambda$.

Intuitively, G' contains two copies of G. For each copy, there is vertex w_i that is connected to every vertex in the copy. Furthermore, the label C encodes the set C_1 in the first copy and C_2 in the second copy. The construction is depicted in Figure 2.

 \triangleright Claim 4.2. For an algorithm solving the problem 1D-MSO-CONSISTENT-LEARN, given G' as the input graph, 2q+6 as the quantifier rank, $\ell=0$, and $S=((w_1,+),(w_2,-))$ as the training sequence, the following holds.

1. If the algorithm rejects, then $\operatorname{tp}_{q+2}^G(C_1) = \operatorname{tp}_{q+2}^G(C_2)$. 2. If $\operatorname{tp}_{2q+6}^G(C_1) = \operatorname{tp}_{2q+6}^G(C_2)$, then the algorithm rejects.

Proof. We prove (1) by showing that the algorithm returns a hypothesis for all C_1, C_2 of different (q+2)-types. Let $C_1, C_2 \subseteq V(G)$ with $\operatorname{tp}_{q+2}^G(C_1) \neq \operatorname{tp}_{q+2}^G(C_2)$, let $\alpha(X) \in \mathcal{C}_2$ $tp_{q+2}^G(C_1) \setminus tp_{q+2}^G(C_2)$, and

$$\beta(x) \coloneqq \exists X \Big(\forall y \big(Xy \leftrightarrow (Cy \land Exy) \big) \land \alpha'(x, X) \Big),$$

where $\alpha'(x, X)$ is computed recursively from $\alpha(X)$ by replacing every subformula of the form $\exists Y \xi$ by $\exists Y (\forall y(Yy \to Exy) \land \xi')$ and replacing every subformula of the form $\exists y \xi$ by $\exists y(Exy \land \xi')$. It holds that $G \models \alpha(C_i)$ if and only if $G' \models \beta(w_i)$ for $i \in [2]$. Furthermore, $qr(\beta) \leq 2 qr(\alpha) + 2 = 2q + 6$. Hence, an algorithm solving 1D-MSO-CONSISTENT-LEARN will return a hypothesis (for example h_{β}).

To prove (2), we assume that $\operatorname{tp}_{2q+6}^{\widetilde{G}}(C_1) = \operatorname{tp}_{2q+6}^G(C_2)$. It suffices to show that $\operatorname{tp}_{2q+6}^{G'}(w_1) = \operatorname{tp}_{2q+6}^{G'}(w_2)$, since an algorithm solving 1D-MSO-CONSISTENT-LEARN will not be able to return a consistent hypothesis in that case and reject. Let $V_i := \{(v, i) \mid v \in V(G)\}$ and $V'_i := V_i \cup \{w_i\}$ for $i \in [2]$. Then, for every $\mathsf{MSO}(\Lambda', 2q + 6, 0, 0)$ sentence χ , we have $G'[V_1] \models \chi$ if and only if $G'[V_2] \models \chi$. To see this, assume that there is an $\mathsf{MSO}(\Lambda', 2q+6, 0, 0)$ sentence χ with $G'[V_1] \models \chi$ and $G'[V_2] \not\models \chi$. Then $\chi'(C) \coloneqq \chi$ is an $\mathsf{MSO}(\Lambda, 2q + 6, 0, 1)$

formula that is contained in $\operatorname{tp}_{2q+6}^G(C_1)$ and not contained in $\operatorname{tp}_{2q+6}^G(C_2)$, which contradicts $\operatorname{tp}_{2q+6}^G(C_1) = \operatorname{tp}_{2q+6}^G(C_2)$.

From this result on $G'[V_1]$ and $G'[V_2]$, for example by considering the corresponding Ehrenfeucht--Fraïssé games, we obtain that $G'[V_1'] \models \chi$ if and only if $G'[V_2'] \models \chi$ and $\operatorname{tp}_{2q+6}^{G'[V_1']}(w_1) = \operatorname{tp}_{2q+6}^{G'[V_2']}(w_2)$. Since G' is the disjoint union of $G'[V_1']$ and $G'[V_2']$, by the Feferman-Vaught Theorem for MSO [42], this implies that $\operatorname{tp}_{2q+6}^{G'}(w_1) = \operatorname{tp}_{2q+6}^{G'}(w_2)$.

To compute the families of candidate sets V_1, \ldots, V_n , in the first round, we set $V_1 = \{\{v\} \mid v \in V(G)\}$. Then, for every pair $C_1, C_2 \in V_1$, we query the oracle as described above. If the algorithm rejects, because of Item (1) of Claim 4.2, for every superset of C_1 , there is a superset of C_2 of the same q-type. Hence, C_2 is not needed anymore in the following computation, and we remove it from V_1 . Because of Item (2) of Claim 4.2, after running the oracle for every pair in V_1 , there is at most one set in V_1 for every (2q + 6)-type of sets of vertices in G. Thus, the number of remaining sets in V_1 can be bounded in terms of $|\varphi|$ without any dependence on |G|.

Next, in round i + 1 for i > 0, we set $V_{i+1} = \{C \cup \{v\} \mid C \in V_i, v \in V(G)\}$. As in the first round, we run the oracle for every pair $C_1, C_2 \in V_{i+1}$, and we remove C_2 from V_{i+1} if the oracle rejects. After the *n*th round, we set $W = \bigcup_{i=1}^n V_i$. Again, we call the oracle for every pair of distinct sets in W, and we remove one of the two sets if the oracle rejects. At the end, the number of sets in W only depends on $|\varphi|$. Furthermore, for every set $V' \subseteq V(G)$, there is a candidate $C \in W$ of the same q-type. The number of oracle calls is quadratic in |G|, the size of the input graphs for the oracle calls is linear in the size of G, and the parameters of the oracle calls can be bounded in terms of $|\varphi|$.

Recall that we assumed the input formula φ to be of the form $\exists X\psi$. For every candidate $C \in W$, we recursively want to check whether $G \models \psi(C)$ holds. For that, we extend the set of labels Λ by a new label X, and we let G_C be the extension of G to the new label set with $X(G_C) = C$. We can then consider ψ as a sentence over the new signature and recursively run our algorithm to check whether $G_C \models \psi$ holds.

Overall, considering both first-order and second-order quantification, we have a recursion tree where both the depth and the degree of the tree can be bounded in terms of $|\varphi|$. In every single recursive call, the number of oracle queries is at most quadratic in |V(G)|, the size of the input graphs for the oracle queries is linear in the size of G, the parameter $|\Lambda| + q + \ell$ for the oracle queries can be bounded in terms of $|\varphi|$, and every oracle query only uses training sequences of length at most 2. Thus, the described procedure yields an fpt Turing reduction from MSO-MC to 1D-MSO-CONSISTENT-LEARN.

5 PAC Learning in Higher Dimensions

So far, we considered the consistent-learning setting, where the goal is to return a hypothesis that is consistent with the given examples. In this section, we study the MSO-learning problem in the agnostic PAC-learning setting. There, for an instance space \mathbb{X} , we assume an (unknown) probability distribution \mathcal{D} on $\mathbb{X} \times \{+, -\}$. The learner's goal is to find a hypothesis $h: \mathbb{X} \to \{+, -\}$, using an oracle to draw training examples randomly from \mathcal{D} , such that h (approximately) minimizes the generalization error

$$\operatorname{err}_{\mathscr{D}}(h) \coloneqq \Pr_{(x,\lambda) \sim \mathscr{D}}(h(x) \neq \lambda).$$

For every Λ -labeled graph G and $q, k, \ell \in \mathbb{N}$, let $\mathscr{H}_{q,k,\ell}(G)$ be the hypothesis class

$$\mathscr{H}_{q,k,\ell}(G) \coloneqq \left\{ h_{\varphi,\bar{w}} \mid \varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0), \bar{w} \in (V(G))^{\ell} \right\}.$$

Formally, we define the MSO PAC-learning problem as follows.

MSO-PAC-LEARN **Instance**: A-labeled graph G, numbers $k, \ell, q \in \mathbb{N}, \delta, \varepsilon \in (0, 1)$, oracle access to probability distribution \mathcal{D} on $(V(G))^k \times \{+, -\}$ **Parameter**: $\kappa \coloneqq |\Lambda| + k + \ell + q + 1/\delta + 1/\varepsilon$ **Problem**: Return a hypothesis $h_{\varphi,\bar{w}} \in \mathscr{H}_{q,k,\ell}(G)$ such that, with probability of at least $1 - \delta$ over the choice of examples drawn i.i.d. from \mathcal{D} , it holds that $\operatorname{err}_{\mathcal{D}}(h_{\varphi,\bar{w}}) \leq \min_{h \in \mathscr{H}_{q,k,\ell}(G)} \operatorname{err}_{\mathcal{D}}(h) + \varepsilon.$

The remainder of this section is dedicated to the proof of Theorem 1.3, that is, we want to show that MSO-PAC-LEARN is fixed-parameter linear on classes of bounded clique-width when the input graph is given as a *c*-expression. To solve the problem algorithmically, we can follow the *Empirical Risk Minimization (ERM)* rule [53, 48], that is, our algorithm should minimize the *training error* (or *empirical risk*)

$$\operatorname{err}_{S}(h) \coloneqq \frac{1}{|S|} \cdot |\{(\bar{v}, \lambda) \in S \mid h(\bar{v}) \neq \lambda\}|$$

on the training sequence S of queried examples. Roughly speaking, an algorithm can solve MSO-PAC-LEARN by querying a sufficient number of examples and then following the ERM rule. To bound the number of needed examples, we combine a fundamental result of statistical learning [11, 48], which bounds the number of needed examples in terms of the VC dimension of a hypothesis class, with Lemma 2.2, a result due to Grohe and Turán [34], which bounds the VC dimension of MSO-definable hypothesis classes on graphs of bounded clique-width.

► Lemma 5.1 ([11, 48]). A hypothesis class \mathcal{H} is (agnostically) PAC-learnable if and only if it has finite VC dimension. Furthermore, if \mathcal{H} has finite VC dimension, then \mathcal{H} can be learned by any algorithm that follows the Empirical Risk Minimization rule with sample complexity (i. e., the number of queried examples needed to fulfil the bounds required for agnostic PAC learnability) $m_{\mathcal{H}}(\varepsilon, \delta) \in \mathcal{O}\left(\frac{\operatorname{VC}(\mathcal{H}) + \log(1/\delta)}{\varepsilon^2}\right)$.

Combined with Lemma 2.2, this implies the following.

▶ Lemma 5.2. There is a computable function $m: \mathbb{N}^5 \times (0,1)^2 \to \mathbb{N}$ such that any algorithm that proceeds as follows solves the problem MSO-PAC-LEARN. Given a Λ -labeled graph Gof clique-width at most c, numbers $k, \ell, q \in \mathbb{N}, \delta, \varepsilon \in (0,1)$, and oracle access to a probability distribution \mathcal{D} on $(V(G))^k \times \{+, -\}$, the algorithm queries at least $m(c, |\Lambda|, q, k, \ell, \delta, \varepsilon)$ many examples from \mathcal{D} and then follows the ERM rule.

Using this lemma, we can now prove Theorem 1.3, showing that MSO-PAC-LEARN is fixed-parameter linear on classes of bounded clique-width if the input graph is given as a c-expression, even for dimensions k > 1.

Proof of Theorem 1.3. Let G be a Λ -labeled graph, let $k, \ell, q \in \mathbb{N}, \delta, \varepsilon \in (0, 1)$, and assume we are given oracle access to a probability distribution \mathcal{D} on $(V(G))^k \times \{+, -\}$. Moreover, let $c \in \mathbb{N}$ and let Ξ be a c-expression given as input that describes G.

Let $s := m(c, |\Lambda|, q, k, \ell, \delta, \varepsilon)$, where *m* is the function from Lemma 5.2. We sample *s* examples from \mathcal{D} and call the resulting sequence of training examples *S*. Then, for every

subsequence S' of S, we will make use of the techniques in Section 3 (adapted to higherdimensional training data) and compute a hypothesis $h_{S'} \in \mathscr{H}_{q,k,\ell}$ that is consistent with S' if such a hypothesis exists. Finally, from all subsequences with a consistent hypothesis, we choose a subsequence S^* of maximum length and return h_{S^*} . Note that this procedure minimizes the training error on the training sequence S, i. e., $\operatorname{err}_S(h_{S^*}) = \min_{h \in \mathscr{H}_{q,k,\ell}} \operatorname{err}_S(h)$. Hence, the procedure follows the ERM rule, and, by Lemma 5.2, it solves MSO-PAC-LEARN.

To apply the techniques from Section 3, we first need to encode the training examples into the graph. For that, we extend the label set Λ by $k \cdot s$ new labels $S_{i,j}$ for $i \in [s]$ and $j \in [k]$, and we call the resulting label set Λ' . Let

$$S' = \left(\left((v_{1,1}, \dots, v_{1,k}), \lambda_1 \right), \dots, \left((v_{s',1}, \dots, v_{s',k}), \lambda_{s'} \right) \right)$$

be a subsequence of S for which we want to find a consistent hypothesis. Furthermore, let $G_{S'}$ be the Λ' -labeled graph with vertex set $V(G_{S'}) = V(G)$, $R(G_{S'}) = R(G)$ for all $R \in \Lambda$, $S_{i,j}(G_{S'}) = \{v_{i,j}\}$ for all $i \in [s']$ and $j \in [k]$, and $S_{i,j}(G_{S'}) = \emptyset$ for all $i \in [s' + 1, s]$ and $j \in [k]$.

Then, for every formula $\varphi(\bar{x}, \bar{y}) \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$, we consider the $\mathsf{MSO}(\Lambda', q + k, 0, \ell, 0)$ formula

$$\varphi'(y_1, \dots, y_\ell) = \forall x_1 \dots \forall x_k$$

$$\left(\left(\bigvee_{\substack{i \in [s'] \\ \lambda_i = +}} \bigwedge_{j=1}^k S_{i,j}(x_j) \right) \to \varphi(x_1, \dots, x_k, y_1, \dots, y_\ell) \right)$$

$$\land \left(\bigvee_{\substack{i \in [s'] \\ \lambda_i = -}} \bigwedge_{j=1}^k S_{i,j}(x_j) \right) \to \neg \varphi(x_1, \dots, x_k, y_1, \dots, y_\ell) \right).$$

Now, for every $w_1, \ldots, w_\ell \in V(G)$, we have $G_{S'} \models \varphi'(w_1, \ldots, w_\ell)$ if and only if $h_{\varphi, \bar{w}}$ with $\bar{w} = (w_1, \ldots, w_\ell)$ is consistent with S'. Hence, analogously to the procedure described in Section 3, we can find a consistent hypothesis, if it exists, by going through all possible formulas φ and computing $w_1, \ldots, w_\ell \in V(G)$ with $G_{S'} \models \varphi'(w_1, \ldots, w_\ell)$.

Given a *c*-expression for *G*, we can compute a $(c + k \cdot s)$ -expression for $G_{S'}$ in linear time. Moreover, $G_{S'}$ and *G* have the same vertex set, and $|\Lambda'|$ only depends on $|\Lambda|$, *k*, and $s = m(c, |\Lambda|, q, k, \ell, \delta, \varepsilon)$. Thus, analogously to Section 3, a consistent hypothesis for a single subsequence *S'* can be computed by an fpt-algorithm with parameters $c, |\Lambda|, k, \ell, q, \delta$, and ε . The number of subsequences to check can be bounded by 2^s . Hence, all in all, the described procedure is an fpt-algorithm that solves MSO-PAC-LEARN.

6 Consistent Learning in Higher Dimensions

In this section, we consider the problem MSO-CONSISTENT-LEARN with dimension k > 1on labeled graphs of bounded clique-width. A brute-force attempt yields a solution in time $g(c, |\Lambda|, q, k, \ell) \cdot (V(G))^{\ell+1} \cdot m$, where m is the length of the training sequence, for some $g: \mathbb{N}^5 \to \mathbb{N}$. This is achieved by iterating over all formulas, then iterating over all parameter assignments, and then performing model checking for each training example. We assume that the graph G is considerably larger in scale than the sequence of training examples S. Therefore, Theorem 1.4 significantly improves the running time to $\mathcal{O}((m+1)^{g(c,|\Lambda|,q,k,\ell)}|V(G)|^2)$. While Theorem 1.4 is not a fixed-parameter tractability result in the classical sense, we show that this is optimal in Section 7. The present section is dedicated to the proof of Theorem 1.4.

Until now, we have viewed the training sequence as a sequence of tuples $S \in ((V(G))^k \times \{+,-\})^m$. In the following, it is useful to split the training sequence into two parts, a sequence of vertex tuples $\alpha \in ((V(G))^k)^m$ and a function $\sigma \colon [m] \to \{+,-\}$ which assigns the corresponding label to each tuple. Let G be a Λ -labeled graph, $\alpha = (\bar{v}_1, \ldots, \bar{v}_m) \in ((V(G))^k)^m$, $\sigma \colon [m] \to \{+,-\}$, and $\varphi(\bar{x},\bar{y}) \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$. We call $(G, \alpha, \sigma) \varphi$ -consistent if there is a parameter setting $\bar{w} \in (V(G))^\ell$ such that for all $i \in [m], G \models \varphi(\bar{v}_i, \bar{w}) \iff \sigma(\bar{v}_i) = +$. We say that \bar{w} is a φ -witness for (G, α, σ) . This notation allows us to state the main technical ingredient for the proof of Theorem 1.4 as follows.

▶ **Theorem 6.1.** There is a computable function $g: \mathbb{N}^5 \to \mathbb{N}$ and an algorithm that, given a Λ -graph G of clique-width $\mathsf{cw}(G) \leq c$, a sequence $\mathfrak{a} = (\bar{v}_1, \ldots, \bar{v}_m) \in ((V(G))^k)^m$, a function $\sigma: [m] \to \{+, -\}$, and a formula $\varphi(\bar{x}, \bar{y}) \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$, decides if $(G, \mathfrak{a}, \sigma)$ is φ -consistent in time $(m + 1)^{g(c, |\Lambda|, q, k, \ell)} |G|$.

Using Theorem 6.1, we can now prove Theorem 1.4.

Proof of Theorem 1.4. Given a Λ -labeled graph G and a training sequence $S = ((\bar{v}_1, \lambda_1), \ldots, (\bar{v}_m, \lambda_m)) \in ((V(G))^k \times \{+, -\})^m$, we let $\alpha := (\bar{v}_1, \ldots, \bar{v}_m) \in ((V(G))^k)^m$ and $\sigma : [m] \rightarrow \{+, -\}, i \mapsto \lambda_i$. We iterate over all formulas $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$ and use Theorem 6.1 to check whether (G, α, σ) is φ -consistent. If there is no φ such that (G, α, σ) is φ -consistent, then we reject the input. Otherwise, let $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$ be such that (G, α, σ) is φ -consistent. We compute a φ -witness following the same construction as in the proof of Lemma 3.2. That is, using a fresh label, we encode the parameter choice of a single variable into the graph, and then we check whether consistency still holds for the corresponding formula φ' that enforces this parameter choice. In total, we perform up to $\ell \cdot |V(G)|$ such consistency checks to compute a φ -witness \bar{w} . The consistent formula φ together with the φ -witness \bar{w} can then be returned as a hypothesis $h_{\varphi,\bar{w}}$ that is consistent with S on G and therefore a solution to MSO-CONSISTENT-LEARN.

The remainder of this section is dedicated to the proof of Theorem 6.1. Intuitively, we proceed as follows.

Let Ξ be a *c*-expression describing the input graph *G*. As described in Section 2.1, we may view Ξ as a tree. In a bottom-up algorithm, starting at the leaves of Ξ , we compute the set of all tuples $\overline{\theta} = (\theta_1, \ldots, \theta_m)$ of (Λ, q, k_i, ℓ) -types θ_i that are realizable over α in *G*. Hence, to check whether (G, α, σ) is φ -consistent, it suffices to check whether there is a realizable type $\overline{\theta}$ such that $\varphi \in \theta_i$ if and only if $\sigma(i) = +$ for all $i \in [m]$. We explain this in more detail in Section 6.3. The difficulty with this approach is that we are talking about *m*-tuples of types. In general, the number of such tuples is exponential in *m*, and hence the size of the set we aim to compute could be exponentially large. Fortunately, this does not happen in graphs of bounded clique-width. By Lemma 2.2, we can bound the VC dimension of a first-order formula over classes of graphs of bounded clique-width. Further, we show in Section 6.1 that this suffices to give a polynomial bound for the number of realizable tuples. Then, in Section 6.2, we show how to compute the set of realizable types in a node of Ξ based on the realizable types in the children of the node.

6.1 Bounding the Number of Realizable Types

In this subsection, we prove the following bound on the number of realizable tuples of types.

▶ Lemma 6.2. Let $d, q, k, \ell \in \mathbb{N}$, let $t := |\mathsf{Tp}(\Lambda, q, k, \ell)|$, and let G be a Λ -labeled graph such that $\operatorname{VC}(\varphi, G) \leq d$ for all $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell, 0)$. Let $a \in (V(G))^{\bar{k}}$ for some $\bar{k} \in \{0, \ldots, k\}^m$. Then at most $(k+1) \cdot g(d,m)^t$ types in $\mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ are realizable over a in G.

The proof of Lemma 6.2 is based on Lemma 6.3.

▶ Lemma 6.3 (Sauer–Shelah Lemma [47, 49]). Let $q \in \mathbb{N}$, $\varphi \in \mathsf{MSO}(\Lambda, q, k, \ell)$, let \mathscr{C} be a class of Λ -labeled graphs, and let $d \in \mathbb{N}$ such that $\mathrm{VC}(\varphi, \mathscr{C}) \leq d$. Then

$$|H_{\varphi}(G,X)| \leq \sum_{i=0}^{d} {|X| \choose i} \in \mathcal{O}(|X|^{d})$$

for all $G \in \mathscr{C}$ and all (finite) $X \subseteq (V(G))^k$.

Further, we need a simple combinatorial argument, which is captured by the following Lemma 6.4. We remark that this argument is known (see [15, Proof of Lemma 23]). For a matrix $M \in \Sigma^{m \times n}$ and a symbol $\sigma \in \Sigma$, we let $M^{(\sigma)} \in \{0, 1\}^{m \times n}$ be the matrix obtained from M by replacing all σ -entries by 1 and all other entries by 0.

▶ Lemma 6.4 ([15]). Let $c, m, n, s \in \mathbb{N}_{>0}$ such that $n > (c-1)^{s-1}$. Furthermore, let Σ be a finite alphabet of size $|\Sigma| = s$, and let $M \in \Sigma^{m \times n}$ be a matrix with mutually distinct columns. Then there is a $\sigma \in \Sigma$ such that $M^{(\sigma)}$ has at least c distinct columns.

Proof. Without loss of generality, we assume that $\Sigma = [s]$. Then, for every column \bar{v} of M, we can write $\bar{v} = \sum_{\sigma=1}^{s} \sigma \bar{v}^{(\sigma)}$, where $\bar{v}^{(\sigma)}$ is the column of $M^{(\sigma)}$ corresponding to \bar{v} .

Suppose for contradiction that for every σ , the set $\mathscr{C}^{(\sigma)}$ of distinct column vectors appearing in $M^{(\sigma)}$ has cardinality at most c-1. Then there are at most $(c-1)^{s-1}$ vectors $\sum_{\sigma=1}^{s} \sigma \bar{v}^{(\sigma)}$ with $\bar{v}^{(\sigma)} \in \mathscr{C}^{(\sigma)}$ that have 1s in mutually disjoint positions, because once we have chosen $\bar{v}^{(1)}, \ldots, \bar{v}^{(s-1)}$, there is only one choice left for $\bar{v}^{(s)}$. This contradicts our assumption that all columns of M are distinct.

In the following, for a set $K \subseteq \mathbb{N}$, we let

$$\mathsf{Tp}(\Lambda, q, K^m, \ell) \coloneqq \bigcup_{\bar{k} \in K^m} \mathsf{Tp}(\Lambda, q, \bar{k}, \ell).$$

Proof of Lemma 6.2. For $0 \leq p \leq k$, let $a^{(p)}$ be the subsequence of a consisting of all entries of length p, and let $m_p \coloneqq |a^{(p)}|$. Every type $\bar{\theta} \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ projects to a type $\bar{\theta}^{(p)} \in \mathsf{Tp}(\Lambda, q, \{p\}^{m_p}, \ell)$.

Suppose for contradiction that more than $b := (k+1) \cdot g(d,m)^t$ types in $\mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ are realizable over a in G.

If $\bar{\theta}$ is realizable over a, then for each p, the projection $\bar{\theta}^{(p)}$ is realizable over $a^{(p)}$. Moreover, if types $\bar{\theta}, \bar{\theta}'$ are distinct, then there is at least one p such that $\bar{\theta}_p$ and $\bar{\theta}'_p$ are distinct. Thus, there is a p such that at least $g(d, m)^t + 1$ types in $\mathsf{Tp}(\Lambda, q, \{p\}^{m_p}, \ell)$ are realizable over $a^{(p)}$.

Suppose $a^{(p)} = (\bar{v}_1, \ldots, \bar{v}_{m_p})$, where $\bar{v}_i \in (V(G))^p$. Let $\bar{\theta}_1, \ldots, \bar{\theta}_n \in \mathsf{Tp}(\Lambda, q, \{p\}^{m_p}, \ell)$ be distinct types and $\bar{w}_1, \ldots, \bar{w}_n \in (V(G))^\ell$ for some $n \geq g(d, m)^t + 1$ such that $\mathsf{tp}_q^G(a^{(p)}, \bar{w}_j) = \bar{\theta}_j$, that is, the types $\bar{\theta}_1, \ldots, \bar{\theta}_r$ are realizable over $a^{(p)}$. Suppose that $\bar{\theta}_j = (\theta_{1j}, \ldots, \theta_{m_pj})$ with $\theta_{ij} \in \mathsf{Tp}(\Lambda, q, p, \ell)$. Then $\mathsf{tp}_q^G(\bar{v}_i, \bar{w}_j) = \theta_{ij}$. Let $\Sigma := \mathsf{Tp}(\Lambda, q, p, \ell)$ and let $M \in \Sigma^{m_p \times n}$ be the matrix with entries $M_{ij} = \theta_{ij}$. Note that $|\Sigma| \leq t$ and that the columns of M are the vectors $\bar{\theta}_j$, which are mutually distinct. Since $n > g(d, m)^t \geq (g(d, m) + 1 - 1)^{t-1}$, by Lemma 6.4, there is a $\theta \in \Sigma$ such that the matrix $M^{(\theta)}$ has at least g(d, m) + 1 distinct columns.

Observe that for $i \in [m_p]$ and $j \in [n]$, if $M_{ij}^{(\theta)} = 1$, then $\mathsf{tp}_q^G(\bar{v}_i, \bar{w}_j) = \theta$, and if $M_{ij}^{(\theta)} = 0$, then $\mathsf{tp}_q^G(\bar{v}_i, \bar{w}_j) \neq \theta$. Let

$$\varphi(\bar{x},\bar{y})\coloneqq \bigwedge_{\psi(\bar{x},\bar{y})\in\theta}\psi(\bar{x},\bar{y}).$$

Then for $\bar{v} \in (V(G))^p$, $\bar{w} \in (V(G))^{\ell}$,

$$G \models \varphi(\bar{v}, \bar{w}) \iff \mathsf{tp}_q^G(\bar{v}, \bar{w}) = \theta$$

Let $X := \{\bar{v}_1, \ldots, \bar{v}_{m_p}\}$. Then for all $j \in [n]$,

$$X \cap \varphi(G, \bar{w}_j) = \{ \bar{v}_i \mid M_{ij}^{(\theta)} = 1 \}.$$

Since the matrix $M^{(\theta)}$ has more than $g(d,m) \ge g(d,m_p)$ distinct columns, it follows that $|H_{\varphi}(G,X)| > g(d,m_p)$, which contradicts Lemma 6.3.

6.2 Compositionality

In the following, we show how the realizable tuples of types for an expression can be computed based on the realizable tuples of types of its subexpressions.

For the operators $\eta_{P,Q}$ and $\rho_{P,Q}$, this is done by adding edges and relabeling.

▶ Lemma 6.5. Let Λ be a label set, $q, k \in \mathbb{N}$, $P, Q \in \Lambda$, and $\xi \in \{\eta, \rho\}$. For every type $\theta \in \mathsf{Tp}(\Lambda, q, k)$, there is a set $T_{\xi, P, Q}(\theta) \subseteq \mathsf{Tp}(\Lambda, q, k)$ such that for every Λ -graph G', for $G \coloneqq \xi_{P,Q}(G')$, and for every $\bar{v} \in (V(G))^k$,

$$\mathsf{tp}_q^G(\bar{v}) = \theta \iff \mathsf{tp}_q^{G'}(\bar{v}) \in T_{\xi,P,Q}(\theta).$$

Furthermore, the mappings $T_{\eta,P,Q}$ and $T_{\rho,P,Q}$ are computable.

Proof. This follows from the Theorem on Syntactic Interpretations [25, Chapter VIII].

Note that, for $\xi \in \{\eta, \rho\}$ and for distinct θ_1, θ_2 , the sets $T_{\xi,P,Q}(\theta_1)$ and $T_{\xi,P,Q}(\theta_2)$ are mutually disjoint up to types that are not realizable. Thus, for every realizable $\theta' \in \mathsf{Tp}(\Lambda, q, k)$, there is at most one $\theta \in \mathsf{Tp}(\Lambda, q, k)$ such that $\theta' \in T_{\xi,P,Q}(\theta)$.

▶ Corollary 6.6. Let Λ be a label set, $q, \ell \in \mathbb{N}$, $P, Q \in \Lambda$, $\xi \in \{\eta, \rho\}$, $\bar{k} \in \mathbb{N}^m$, and $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$. Let G' be a Λ -graph, let $G \coloneqq \xi_{P,Q}(G')$, and $\alpha \in (V(G))^{\bar{k}}$. Then $\bar{\theta}$ is realizable over α in G if and only there is a $\bar{\theta}' = (\theta'_1, \ldots, \theta'_m) \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ such that $\bar{\theta}'$ is realizable over α in G' and $\theta'_i \in T_{\xi, P, Q}(\theta_i)$ for all $i \in [m]$, where $T_{\xi, P, Q}$ is the mapping of Lemma 6.5.

Next, we handle the operator δ_P that deletes the label P.

▶ Lemma 6.7. Let Λ be a label set, let P be a label with $P \notin \Lambda$, and let $q, k \in \mathbb{N}$. For every type $\theta \in \mathsf{Tp}(\Lambda, q, k)$, there is a set $T_{\delta, P}(\theta) \subseteq \mathsf{Tp}(\Lambda \cup \{P\}, q, k)$ such that for every $(\Lambda \cup \{P\})$ -graph G', for $G \coloneqq \delta_P(G')$, and for every $\bar{v} \in (V(G))^k$,

 $\mathsf{tp}_q^G(\bar{v}) = \theta \iff \mathsf{tp}_q^{G'}(\bar{a}) \in T_{\delta,P}(\theta).$

Furthermore, the mapping $T_{\delta,P}$ is computable.

Proof. This follows from the Theorem on Syntactic Interpretations [25].

◀

▶ Corollary 6.8. Let Λ be a label set, let P be a label with $P \notin \Lambda$, let $q, \ell \in \mathbb{N}, \bar{k} \in \mathbb{N}^m$, and $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$. Let G' be a $(\Lambda \cup \{P\})$ -graph, let $G \coloneqq \delta_P(G')$, and $a \in (V(G))^{\bar{k}}$. Then $\bar{\theta}$ is realizable over a in G if and only there is a $\bar{\theta}' = (\theta'_1, \ldots, \theta'_m) \in$ $\mathsf{Tp}(\Lambda \cup \{P\}, q, \bar{k}, \ell)$ such that $\bar{\theta}'$ is realizable over a in G' and $\theta'_i \in T_{\delta, P}(\theta_i)$ for all $i \in [m]$, where $T_{\delta, P}$ is the mapping of Lemma 6.7.

Finally, we handle the ordered-disjoint-union operator \mathbb{H}^{\leq} . For a k-tuple $\bar{v} = (a_1, \ldots, a_k)$ and a set $I \subseteq [k]$, say, $I = \{i_1, \ldots, i_p\}$ with $i_1 < i_2 < \ldots < i_p$, we let $\bar{v}_I \coloneqq (a_{i_1}, \ldots, a_{i_p})$.

▶ Lemma 6.9. Let Λ be a label set with $P_1^<, P_2^< \in \Lambda$. Let $q, k \in \mathbb{N}$ and $K_1 \subseteq [k], K_2 = [k] \setminus K_1$, and let $k_j \coloneqq |K_j|$ for j = 1, 2.

For every type $\theta \in \mathsf{Tp}(\Lambda, q, k)$ and for j = 1, 2, there is a type $T_{\uplus, j, K_j}(\theta) \in \mathsf{Tp}(\Lambda \setminus \{P_1^{<}, P_2^{<}\}, q, k_j)$, such that for every Λ -graph $G = G_1 \uplus^{<} G_2$ and every $\bar{v} \in (V(G))^k$ with $\bar{v}_{K_1} \in (V(G_1))^{k_1}$ and $\bar{v}_{K_2} \in (V(G_2))^{k_2}$, we have

$$\begin{aligned} \mathsf{tp}_q^G(\bar{v}) &= \theta \iff \mathsf{tp}_q^{G_1}(\bar{v}_{K_1}) = T_{\uplus,1,K_1}(\theta) \text{ and} \\ \mathsf{tp}_q^{G_2}(\bar{v}_{K_2}) &= T_{\uplus,2,K_2}(\theta). \end{aligned}$$

Furthermore, for j = 1, 2, the mapping T_{\uplus,j,K_j} is computable.

Proof. This is a version of the Feferman–Vaught Theorem for MSO [42] that can easily be shown using Ehrenfeucht–Fraïssé games.

In the case of disjoint union, it is slightly more complicated to compute the realizable types in $G = G_1 \, \oplus^{<} G_2$ from the realizable types in G_1 and G_2 . We need some additional notation. Let V be a set and $W \subseteq V$. For a tuple $\bar{v} = (v_1, \ldots, v_k) \in V^k$, we let $\bar{v} \cap W \coloneqq \bar{v}_I$ for the set $I = \{i \in [k] \mid v_i \in W\}$. For a sequence $\alpha = (\bar{v}_1, \ldots, \bar{v}_m) \in V^{\bar{k}}$ of tuples, we let

$$a \cap W \coloneqq (\bar{v}_1 \cap W, \dots, \bar{v}_m \cap W).$$

Note that even if all tuples in a have the same length, this is not necessarily the case for $a \cap W$; some tuples in $a \cap W$ may even be empty.

In the following corollary, we consider types in $\mathsf{Tp}(\Lambda, q, k, \ell)$ instead of types in $\mathsf{Tp}(\Lambda, q, k)$. Thus, we need to parameterize the mappings $T_{\forall,j,\ldots}$ by pairs of sets $K_j \subseteq [k], L_j \subseteq [\ell]$: for j = 1, 2, we obtain a mapping $T_{\forall,j,K_j,L_j} \colon \mathsf{Tp}(\Lambda, q, k) \to \mathsf{Tp}(\Lambda \setminus \{P_1^<, P_2^<\}, q, |K_j|, |L_j|)$.

► Corollary 6.10. Let Λ be a label set with $P_1^<, P_2^< \in \Lambda$, let $q, \ell \in \mathbb{N}, \bar{k} = (k_1, \ldots, k_m) \in \mathbb{N}^m$, and let $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$. Let $G = G_1 \uplus^< G_2$ be a Λ -graph and $a = (\bar{v}_1, \ldots, \bar{v}_m) \in (V(G))^{\bar{k}}$. For every $j \in [2]$, $i \in [m]$, let $K_{ji} \subseteq [k_i]$ be such that $\bar{v}_i \cap V(G_j) = (\bar{v}_i)_{K_{ij}}$.

Then $\overline{\theta}$ is realizable over a in G if and only if there are $L_1, L_2 \subseteq [\ell]$ such that $L_2 = [\ell] \setminus L_1$ and for j = 1, 2,

$$\bar{\theta}_j = \left(T_{\uplus,j,K_{j1},L_j}(\theta_1), \dots, T_{\uplus,j,K_{jm},L_j}(\theta_m) \right)$$

is realizable over $a \cap V(G_i)$ in G_i .

6.3 Computing the Realizable Types

For the proof of Theorem 6.1, we use the following result that allows us to compute the realizable types of an expression.

▶ Lemma 6.11. There is a computable function $f : \mathbb{N}^4 \to \mathbb{N}$ and an algorithm that, given $c, q, k, \ell, m \in \mathbb{N}$, a vector $\bar{k} = (k_1, \ldots, k_m) \in \mathbb{N}^m$ with $k_i \leq k$ for all $i \in [m]$, a Λ -expression Ξ with $|\Lambda| \leq c$, and a sequence $a \in (V_{\Xi})^{\bar{k}}$, computes the set of all $\bar{\theta} \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ that are realizable over a in G_{Ξ} in time

$$\mathcal{O}\Big((m+1)^{f(c,q,k,\ell)}\cdot |\Xi|\Big).$$

Proof. As argued in Section 2, we may assume that Ξ only contains ordered-disjoint-union operators and no plain disjoint-union operators.

For every subexpression Ξ' , we let $\Lambda_{\Xi'}$ be the set of labels of Ξ' , that is, the set of unary relation symbols such that $G_{\Xi'}$ is a $\Lambda_{\Xi'}$ -graph. Moreover, let $a_{\Xi'} \coloneqq a \cap V_{\Xi'}$, and let $\bar{k}_{\Xi'} \subseteq \mathbb{N}^m$ such that $a_{\Xi'} \in (V_{\Xi'})^{\bar{k}_{\Xi'}}$.

We inductively construct, for every subexpression Ξ' of Ξ and $0 \leq \ell' \leq \ell$, the set $\mathscr{R}_{\ell'}(\Xi')$ of all types $\bar{\theta} \in \mathsf{Tp}(\Lambda_{\Xi'}, q, \bar{k}_{\Xi'}, \ell')$ that are realizable over $\mathscr{A}_{\Xi'}$ in $G_{\Xi'}$.

- **Case 1:** Ξ' is a base expression. In this case, for each $\ell' \in [\ell]$, we can construct $\mathscr{R}_{\ell'}(\Xi')$ by brute force in time $f_1(c, q, k, \ell) \cdot m$ for a suitable (computable) function f_1 . Let $(k'_1, \ldots, k'_m) := \bar{k}_{\Xi'}$. We compute θ_i by iterating over all formulas φ with $k'_i + \ell'$ free variables and evaluating φ on the single vertex graph $G_{\Xi'}$.
- **Case 2:** $\Xi' = \eta_{P,Q}(\Xi'')$. Let $0 \leq \ell' \leq \ell$, and let $\bar{k}' = (k'_1, \ldots, k'_m) \coloneqq \bar{k}_{\Xi'} = \bar{k}_{\Xi''}$. As we show in Lemma 6.5 and Corollary 6.6, there is a computable mapping $T_{\eta,P,Q}$: $\mathsf{Tp}(\Lambda_{\Xi'}) \to 2^{\mathsf{Tp}(\Lambda_{\Xi''})}$ such that $\mathscr{R}_{\ell'}(\Xi')$ is the set of all $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda_{\Xi'}, q, \bar{k}', \ell')$ such that there is a $\bar{\theta}' = (\theta'_1, \ldots, \theta'_m) \in \mathscr{R}(\Xi'')$ with $\theta'_i \in T_{\eta,P,Q}(\theta_i)$ for all $i \in [m]$. Moreover, for every realizable $\theta' \in \mathsf{Tp}(\Lambda_{\Xi'})$, we guarantee that there is at most one type $\theta \in \mathsf{Tp}(\Lambda_{\Xi''})$ such that $\theta' \in T_{\eta,P,Q}(\theta)$. To compute the set $\mathscr{R}_{\ell'}(\Xi')$, we step through all $\bar{\theta}' \in \mathscr{R}(\Xi'')$. For each such $\bar{\theta}' = (\theta'_1, \ldots, \theta'_m)$, for all $i \in [m]$, we compute the unique $\theta_i \in \mathsf{Tp}(\Lambda_{\Xi'}, q, k'_i, \ell')$ such that $\theta'_i \in T_{\eta,P,Q}(\theta_i)$. If for some $i \in [m]$, no such θ_i exists, we move on to the next $\bar{\theta}'$. Otherwise, we add $\bar{\theta} = (\theta_1, \ldots, \theta_m)$ to $\mathscr{R}(\Xi')$.

Case 3: $\Xi' = \rho_{P,Q}(\Xi'')$. Analogous to Case 2, again using Lemma 6.5 and Corollary 6.6. **Case 4:** $\Xi' = \delta_P(\Xi'')$. Analogous to Case 2, using Lemma 6.7 and Corollary 6.8.

Case 5: $\Xi' = \Xi_1 \, \textcircled{=} \Xi_2$. Let $\Lambda' \coloneqq \Lambda_{\Xi'}, V' \coloneqq V_{\Xi'}, \bar{k}' = (k'_1, \ldots, k'_m) \coloneqq \bar{k}_{\Xi'}$, and $a' \coloneqq (\bar{v}'_1, \ldots, \bar{v}'_m) \coloneqq a_{\Xi'} = a \cap V'$. For j = 1, 2, let $\Lambda_j \coloneqq \Lambda_{\Xi_j}, V_j \coloneqq V_{\Xi_j}, \bar{k}_j \coloneqq (k_{j1}, \ldots, k_{jm}) \coloneqq \bar{k}_{\Xi_j}$, and for all $i \in [m]$, let $K_{ji} \subseteq [k_{ji}]$ such that $\bar{v}'_i \cap V_j = (\bar{v}_i)_{K_{ji}}$. Let $0 \leq \ell' \leq \ell$.

For all $L_1, L_2 \subseteq [\ell']$ such that $L_2 = [\ell'] \setminus L_1$, we let \mathscr{R}_{L_1,L_2} be the set of all $\theta = (\theta_1, \ldots, \theta_m) \in \mathsf{Tp}(\Lambda', q, \bar{k}', \ell')$ such that for j = 1, 2, we have

$$\bar{\theta}_j \coloneqq \left(T_{\uplus,j,L_j,K_{j1}}(\theta_1), \dots, T_{\uplus,j,L_j,K_{jm}}(\theta_m) \right) \in \mathscr{R}_{|L_j|}(\Xi_j),$$

where $T_{\uplus,j,L_j,K_{ji}}$: $\mathsf{Tp}(\Lambda') \to \mathsf{Tp}(\Lambda_j)$ for $i \in [m]$ is a computable mapping that we give in Lemma 6.9. Then, as we show in Corollary 6.10,

$$\mathscr{R}_{\ell'}(\Xi') = \bigcup_{\substack{L_1 \subseteq [\ell']\\L_2 = [\ell'] \setminus L_1}} \mathscr{R}_{L_1, L_2}$$

To compute \mathscr{R}_{L_1,L_2} , we iterate over all $\bar{\theta}_1 = (\theta_{11}, \ldots, \theta_{1m}) \in \mathscr{R}_{|L_1|}(\Xi_1)$. For all $i \in [m]$ we compute the unique $\theta_i \in \mathsf{Tp}(\Lambda', q, k'_i, \ell')$ such that $T_{\uplus, 1, L_1, K_{1i}}(\theta_i) = \theta_{1i}$. If, for some $i \in [m]$, no such θ_i exists, then we move on to the next $\bar{\theta}_1$. Otherwise, we compute

$$\bar{\theta}_2 = \left(T_{\uplus,2,L_2,K_{21}}(\theta_1), \dots, T_{\uplus,2,L_2,K_{2m}}(\theta_m) \right)$$

and check if $\bar{\theta}_2 \in \mathscr{R}_{|L_2|}(\Xi_2)$. If it is, we add $\bar{\theta}$ to \mathscr{R}_{L_1,L_2} . Otherwise, we move on to the next $\bar{\theta}_1$.

This completes the description of our algorithm. To analyze the running time, let

$$r \coloneqq \max_{\Xi'} |\mathscr{R}_{\Xi'}|$$

where Ξ' ranges over all subexpressions of Ξ . By Lemmas 2.2 and 6.2, there is a computable function $f_2 \colon \mathbb{N}^4 \to \mathbb{N}$ such that

 $r < (m+1)^{f_2(c,q,k,\ell)}.$

The running time of each step of the constructions can be bounded by $f_3(c, q, k, \ell) \cdot r$ for a suitable computable function f_3 . We need to make $|\Xi|$ steps. Thus, overall, we obtain the desired running time.

Finally, we can finish the proof of Theorem 6.1 by checking whether the realizable types match with the given formula φ .

Proof of Theorem 6.1. We assume that the input graph G is given as a c-expression. To check whether (G, α, σ) is φ -consistent, we compute the set \mathscr{R} of all $\bar{\theta} \in \mathsf{Tp}(\Lambda, q, \bar{k}, \ell)$ that are realizable over α in G, using Lemma 6.11. Then, for each $\bar{\theta} = (\theta_1, \ldots, \theta_m) \in \mathscr{R}$ we check if $\varphi \in \theta_i \iff \sigma(i) = +$. If we find such a $\bar{\theta}$, then (G, α, σ) is φ -consistent; otherwise it is not.

7 Hardness of Checking Consistency in Higher Dimensions

The following result shows, under the assumption $\mathsf{FPT} \neq \mathsf{W}[1]$, that Theorem 6.1 can not be improved to an fpt-result.

Theorem 7.1. There is a $q \in \mathbb{N}$ such that the following parameterized problem is W[1]-hard.

Instance: graph G of clique-width at most 2, sequence $a = (\bar{a}_1, \ldots, \bar{a}_m) \in ((V(G))^2)^m$, function $\sigma \colon [m] \to \{+1, -1\}$, formula $\varphi(\bar{x}, \bar{y}) \in \mathsf{MSO}(\Lambda, q, 2, \ell, 0)$ **Parameter**: ℓ **Problem**: decide if (G, a, σ) is φ -consistent.

Proof. We prove this by a reduction from the W[1]-complete weighted satisfiability problem for Boolean formulas in 2-conjunctive normal form [27]. The weight of an assignment to a set of Boolean variables is the number of variables set to 1.

WSAT(2-CNF) **Instance**: Boolean formula Φ in 2-CNF **Parameter**: ℓ **Problem**: decide if Φ has a satisfying assignment of weight ℓ .

Given a 2-CNF formula $\Phi = \bigwedge_{i=1}^{m} (L_{i,1} \vee L_{i,2})$ in the variables $\{X_1, \ldots, X_n\}$ and $\ell \in \mathbb{N}$, we construct an instance of the consistency problem from Theorem 7.1 as follows.

We let G be the graph with vertex set

 $V(G) \coloneqq \{X_i, \neg X_i, Y_{i,1}, Y_{i,2}, Z_i \mid i \in [n]\}$

and edge set

$$E(G) \coloneqq \{ (X_i, \neg X_i), (X_i, Y_{i,1}), (X_i, Y_{i,2}), (\neg X_i, Z_i) \mid i \in [n] \}.$$

The graph G is a forest of clique-width at most 2, where the X_i have degree 3, the $\neg X_i$ have degree 2, and all other nodes have degree 1.

We set $\boldsymbol{a} \coloneqq (\bar{a}_1, \dots, \bar{a}_m) \in ((V(G))^2)^m$ with $\bar{a}_i = (L_{i,1}, L_{i,2}), \sigma(i) \coloneqq +1$ for all $i \in [m]$, and

$$\varphi(x_1, x_2, y_1, \dots, y_\ell) \coloneqq \bigwedge_{i=1}^{\ell} \psi_{pos}(y_i) \wedge \bigwedge_{i \neq j} y_i \neq y_j$$
$$\wedge \bigvee_{i=1}^{2} \left(\bigvee_{j=1}^{\ell} x_i = y_j \lor \left(\psi_{neg}(x_i) \land \bigwedge_{j=1}^{\ell} \neg E(y_j, x_i) \right) \right)$$

for $\psi_{pos}(x) \coloneqq \deg_{=3}(x)$ and $\psi_{neg}(x) \coloneqq \deg_{=2}(x)$ with $\deg_{=k}(x) \coloneqq \deg_{\geq k}(x) \land \neg \deg_{\geq k+1}(x)$ and

$$\deg_{\geq k}(x) \coloneqq \exists y_1 \cdots \exists y_k \Big(\bigwedge_{i \neq j} y_i \neq y_j \land \bigwedge_{i=1}^k E(x, y_i)\Big).$$

For every tuple $\bar{b} \in \{X_1, \ldots, X_n\}^{\ell}$, we define an assignment $\beta_{\bar{b}} \colon \{X_1, \ldots, X_n\} \to \{0, 1\}$ by $\beta_{\bar{b}}(X_i) = 1$ if $b_j = X_i$ for some $j \in [\ell]$ and $\beta_{\bar{b}}(X_i) = 0$ otherwise. Note that if the b_j are mutually distinct, then the weight of this assignment is exactly ℓ . Moreover, for all $\bar{b} \in (V(G))^{\ell}$ and all $i \in [m]$, we have

$$G \models \varphi(\bar{a}_i, \bar{b}) \iff \bar{b} \in \{X_1, \dots, X_n\}^\ell$$
 and the entries of \bar{b} are
mutually distinct and $\beta_{\bar{b}}$ satisfies $L_{i,1} \lor L_{i,2}$

Thus, (G, α, σ) is φ -consistent if and only if Φ has a satisfying assignment of weight ℓ .

8 Conclusion

4

Just like model checking and the associated counting and enumeration problems, the learning problem we study here is a natural algorithmic problem for logics on finite structures. All these problems are related, but each has its own challenges requiring different techniques. Where model checking and enumeration are motivated by automated verification and database systems, we view our work as part of a descriptive complexity theory of machine learning [8].

The first problem we studied is 1D-MSO-CONSISTENT-LEARN, where the instances to classify consist of single vertices, and we extended the previous fixed-parameter tractability results for strings and trees [32, 31] to (labeled) graphs of bounded clique-width. Moreover, on general graphs, we showed that the problem is hard for the complexity class para-NP.

For MSO-learning problems in higher dimensions, we presented two different approaches that yield tractability results on graphs of bounded clique-width. For the agnostic PAC-learning problem MSO-PAC-LEARN, we described a fixed-parameter tractable learning algorithm. Furthermore, in the consistent-learning setting for higher dimensions, we gave an algorithm that solves the learning problem and is fixed-parameter tractable in the size of the input graph. However, the algorithm is not fixed-parameter tractable in the size of the training sequence, and we showed that this is optimal.

In the learning problems considered so far, hypotheses are built using MSO formulas and tuples of vertices as parameters. We think that the algorithms presented in this paper for the 1-dimensional case could also be extended to hypothesis classes that allow tuples of sets as parameters. Finally, utilizing the full power of MSO, one could also consider a learning problem where, instead of classifying tuples of vertices, we are interested in classifying sets of vertices. That is, for a graph G, we are given labeled subsets of V(G) and want to find a hypothesis $h: 2^{V(G)} \to \{+, -\}$ that is consistent with the given examples. It is easy to see

that the techniques used in our hardness result also apply to this modified problem, proving that it is para-NP-hard. However, it remains open whether our tractability results could also be lifted to this version of the problem.

— References

- 1 Azza Abouzied, Dana Angluin, Christos H. Papadimitriou, Joseph M. Hellerstein, and Avi Silberschatz. Learning and verifying quantified boolean queries by example. In Proceedings of the 32nd ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems, PODS 2013, New York, NY, USA, June 22–27, 2013, pages 49–60. ACM, 2013. doi:10.1145/ 2463664.2465220.
- 2 Howard Aizenstein, Tibor Hegedüs, Lisa Hellerstein, and Leonard Pitt. Complexity theoretic hardness results for query learning. *Comput. Complex.*, 7(1):19–53, 1998. doi:10.1007/ PL00001593.
- 3 Bogdan Alexe, Balder ten Cate, Phokion G. Kolaitis, and Wang Chiew Tan. Characterizing schema mappings via data examples. ACM Trans. Database Syst., 36(4):23:1–23:48, 2011. doi:10.1145/2043652.2043656.
- 4 Vikraman Arvind, Johannes Köbler, and Wolfgang Lindner. Parameterized learnability of k-juntas and related problems. In Algorithmic Learning Theory, 18th International Conference, ALT 2007, Sendai, Japan, October 1–4, 2007, volume 4754 of Lecture Notes in Computer Science, pages 120–134. Springer, 2007. doi:10.1007/978-3-540-75225-7_13.
- 5 Pablo Barceló, Alexander Baumgartner, Víctor Dalmau, and Benny Kimelfeld. Regularizing conjunctive features for classification. J. Comput. Syst. Sci., 119:97–124, 2021. doi:10.1016/ j.jcss.2021.01.003.
- 6 Pablo Barceló and Miguel Romero. The complexity of reverse engineering problems for conjunctive queries. In 20th International Conference on Database Theory, ICDT 2017, Venice, Italy, March 21–24, 2017, volume 68 of LIPIcs, pages 7:1–7:17. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2017. doi:10.4230/LIPIcs.ICDT.2017.7.
- 7 Steffen van Bergerem. Learning concepts definable in first-order logic with counting. In 34th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS 2019, Vancouver, BC, Canada, June 24–27, 2019, pages 1–13. IEEE, 2019. doi:10.1109/LICS.2019.8785811.
- 8 Steffen van Bergerem. Descriptive Complexity of Learning. PhD thesis, RWTH Aachen University, Germany, 2023. doi:10.18154/RWTH-2023-02554.
- 9 Steffen van Bergerem, Martin Grohe, and Martin Ritzert. On the parameterized complexity of learning first-order logic. In PODS 2022: International Conference on Management of Data, Philadelphia, PA, USA, June 12–17, 2022, pages 337–346. ACM, 2022. doi:10.1145/ 3517804.3524151.
- 10 Steffen van Bergerem and Nicole Schweikardt. Learning concepts described by weight aggregation logic. In 29th EACSL Annual Conference on Computer Science Logic, CSL 2021, Ljubljana, Slovenia (Virtual Conference), January 25–28, 2021, volume 183 of LIPIcs, pages 10:1–10:18. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2021. doi:10.4230/LIPIcs.CSL.2021.10.
- 11 Anselm Blumer, A. Ehrenfeucht, David Haussler, and Manfred K. Warmuth. Learnability and the Vapnik-Chervonenkis dimension. J. ACM, 36(4):929–965, October 1989. doi:10.1145/ 76359.76371.
- 12 Angela Bonifati, Radu Ciucanu, and Aurélien Lemay. Learning path queries on graph databases. In Proceedings of the 18th International Conference on Extending Database Technology, EDBT 2015, Brussels, Belgium, March 23-27, 2015, pages 109-120. OpenProceedings.org, 2015. doi:10.5441/002/edbt.2015.11.
- 13 Angela Bonifati, Radu Ciucanu, and Slawek Staworko. Learning join queries from user examples. ACM Trans. Database Syst., 40(4):24:1–24:38, 2016. doi:10.1145/2818637.

- 14 Angela Bonifati, Ugo Comignani, Emmanuel Coquery, and Romuald Thion. Interactive mapping specification with exemplar tuples. ACM Trans. Database Syst., 44(3):10:1–10:44, 2019. doi:10.1145/3321485.
- 15 Édouard Bonnet, Ugo Giocanti, Patrice Ossona de Mendez, Pierre Simon, Stéphan Thomassé, and Szymon Torunczyk. Twin-width IV: ordered graphs and matrices. In STOC '22: 54th Annual ACM SIGACT Symposium on Theory of Computing, Rome, Italy, June 20–24, 2022, pages 924–937. ACM, 2022. doi:10.1145/3519935.3520037.
- 16 Cornelius Brand, Robert Ganian, and Kirill Simonov. A parameterized theory of PAC learning. In Thirty-Seventh AAAI Conference on Artificial Intelligence, AAAI 2023, Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence, IAAI 2023, Thirteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2023, Washington, DC, USA, February 7-14, 2023, pages 6834-6841. AAAI Press, 2023. doi:10.1609/aaai.v37i6. 25837.
- 17 Balder ten Cate and Víctor Dalmau. Conjunctive queries: Unique characterizations and exact learnability. In 24th International Conference on Database Theory, ICDT 2021, Nicosia, Cyprus, March 23–26, 2021, volume 186 of LIPIcs, pages 9:1–9:24. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2021. doi:10.4230/LIPIcs.ICDT.2021.9.
- 18 Balder ten Cate, Víctor Dalmau, and Phokion G. Kolaitis. Learning schema mappings. ACM Trans. Database Syst., 38(4):28:1–28:31, 2013. doi:10.1145/2539032.2539035.
- 19 Balder ten Cate, Phokion G. Kolaitis, Kun Qian, and Wang-Chiew Tan. Active learning of GAV schema mappings. In Proceedings of the 37th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems, Houston, TX, USA, June 10–15, 2018, pages 355–368. ACM, 2018. doi:10.1145/3196959.3196974.
- 20 Adrien Champion, Tomoya Chiba, Naoki Kobayashi, and Ryosuke Sato. ICE-based refinement type discovery for higher-order functional programs. J. Autom. Reason., 64(7):1393–1418, 2020. doi:10.1007/s10817-020-09571-y.
- 21 William W. Cohen and C. David Page Jr. Polynomial learnability and inductive logic programming: Methods and results. *New Gener. Comput.*, 13(3&4):369-409, December 1995. doi:10.1007/BF03037231.
- 22 Derek G. Corneil and Udi Rotics. On the relationship between clique-width and treewidth. SIAM J. Comput., 34(4):825–847, 2005. doi:10.1137/S0097539701385351.
- 23 Bruno Courcelle, Johann A. Makowsky, and Udi Rotics. Linear time solvable optimization problems on graphs of bounded clique-width. *Theory of Computing Systems*, 33(2):125–150, 2000. doi:10.1007/s002249910009.
- 24 Bruno Courcelle and Stephan Olariu. Upper bounds to the clique width of graphs. Discret. Appl. Math., 101(1-3):77–114, 2000. doi:10.1016/S0166-218X(99)00184-5.
- 25 Heinz-Dieter Ebbinghaus, Jörg Flum, and Wolfgang Thomas. *Mathematical Logic*. Springer, January 2021. doi:10.1007/978-3-030-73839-6.
- 26 P. Ezudheen, Daniel Neider, Deepak D'Souza, Pranav Garg, and P. Madhusudan. Horn-ICE learning for synthesizing invariants and contracts. Proc. ACM Program. Lang., 2(OOPSLA):131:1–131:25, 2018. doi:10.1145/3276501.
- 27 Jörg Flum and Martin Grohe. Parameterized complexity theory. Texts in Theoretical Computer Science. An EATCS Series. Springer, 2006. doi:10.1007/3-540-29953-X.
- 28 Martin Fürer. Multi-clique-width. In 8th Innovations in Theoretical Computer Science Conference, ITCS 2017, Berkeley, CA, USA, January 9–11, 2017, volume 67 of LIPIcs, pages 14:1–14:13. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2017. doi:10.4230/LIPICS. ITCS.2017.14.
- 29 Pranav Garg, Christof Löding, P. Madhusudan, and Daniel Neider. ICE: A robust framework for learning invariants. In Computer Aided Verification - 26th International Conference, CAV 2014, Held as Part of the Vienna Summer of Logic, VSL 2014, Vienna, Austria, July 18-22, 2014, volume 8559 of Lecture Notes in Computer Science, pages 69-87. Springer, 2014. doi:10.1007/978-3-319-08867-9_5.

- **30** Georg Gottlob and Pierre Senellart. Schema mapping discovery from data instances. J. ACM, 57(2):6:1-6:37, 2010. doi:10.1145/1667053.1667055.
- 31 Émilie Grienenberger and Martin Ritzert. Learning definable hypotheses on trees. In 22nd International Conference on Database Theory, ICDT 2019, Lisbon, Portugal, March 26– 28, 2019, volume 127 of LIPIcs, pages 24:1–24:18. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2019. doi:10.4230/LIPIcs.ICDT.2019.24.
- 32 Martin Grohe, Christof Löding, and Martin Ritzert. Learning MSO-definable hypotheses on strings. In International Conference on Algorithmic Learning Theory, ALT 2017, Kyoto University, Kyoto, Japan, October 15-17, 2017, volume 76 of Proceedings of Machine Learning Research, pages 434-451. PMLR, October 2017. ISSN: 2640-3498. URL: https://proceedings. mlr.press/v76/grohe17a.html.
- 33 Martin Grohe and Martin Ritzert. Learning first-order definable concepts over structures of small degree. In 32nd Annual ACM/IEEE Symposium on Logic in Computer Science, LICS 2017, Reykjavík, Iceland, June 20–23, 2017, pages 1–12. IEEE, June 2017. doi: 10.1109/LICS.2017.8005080.
- 34 Martin Grohe and György Turán. Learnability and definability in trees and similar structures. *Theory Comput. Syst.*, 37(1):193–220, January 2004. doi:10.1007/s00224-003-1112-8.
- David Haussler. Learning conjunctive concepts in structural domains. Mach. Learn., 4:7–40, 1989. doi:10.1007/BF00114802.
- 36 David Haussler. Decision theoretic generalizations of the PAC model for neural net and other learning applications. Inf. Comput., 100(1):78–150, 1992. doi:10.1016/0890-5401(92) 90010-D.
- Kouichi Hirata. On the hardness of learning acyclic conjunctive queries. In Algorithmic Learning Theory, 11th International Conference, ALT 2000, Sydney, Australia, December 11-13, 2000, volume 1968 of Lecture Notes in Computer Science, pages 238-251. Springer, 2000. doi:10.1007/3-540-40992-0_18.
- 38 Michael J. Kearns and Umesh V. Vazirani. An Introduction to Computational Learning Theory. MIT Press, 1994. URL: https://mitpress.mit.edu/books/ introduction-computational-learning-theory.
- 39 Benny Kimelfeld and Christopher Ré. A relational framework for classifier engineering. ACM Trans. Database Syst., 43(3):11:1–11:36, 2018. doi:10.1145/3268931.
- 40 Yuanzhi Li and Yingyu Liang. Learning mixtures of linear regressions with nearly optimal complexity. In Conference On Learning Theory, COLT 2018, Stockholm, Sweden, July 6-9, 2018, volume 75 of Proceedings of Machine Learning Research, pages 1125–1144. PMLR, 2018. URL: http://proceedings.mlr.press/v75/li18b.html.
- 41 Christof Löding, P. Madhusudan, and Daniel Neider. Abstract learning frameworks for synthesis. In Tools and Algorithms for the Construction and Analysis of Systems - 22nd International Conference, TACAS 2016, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2016, Eindhoven, The Netherlands, April 2-8, 2016, volume 9636 of Lecture Notes in Computer Science, pages 167–185. Springer, 2016. doi:10.1007/978-3-662-49674-9_10.
- 42 Johann A. Makowsky. Algorithmic uses of the Feferman-Vaught theorem. Ann. Pure Appl. Log., 126(1-3):159-213, 2004. doi:10.1016/j.apal.2003.11.002.
- **43** Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of Machine Learning*. Adaptive computation and machine learning. MIT Press, 2nd edition, 2018.
- 44 Stephen H. Muggleton. Inductive logic programming. New Gener. Comput., 8(4):295–318, February 1991. doi:10.1007/BF03037089.
- Stephen H. Muggleton and Luc De Raedt. Inductive logic programming: Theory and methods. J. Log. Program., 19/20:629–679, 1994. doi:10.1016/0743-1066(94)90035-3.
- 46 Sang-il Oum and Paul D. Seymour. Approximating clique-width and branch-width. J. Comb. Theory, Ser. B, 96(4):514-528, 2006. doi:10.1016/j.jctb.2005.10.006.

- 47 Norbert Sauer. On the density of families of sets. J. Comb. Theory, Ser. A, 13(1):145–147, 1972. doi:10.1016/0097-3165(72)90019-2.
- 48 Shai Shalev-Shwartz and Shai Ben-David. Understanding Machine Learning From Theory to Algorithms. Cambridge University Press, Cambridge, 2014. doi:10.1017/CB09781107298019.
- 49 Saharon Shelah. A combinatorial problem: stability and order for models and theories in infinitary languages. *Pacific Journal of Mathematics*, 41(1):247-261, 1972. doi:10.2140/pjm. 1972.41.247.
- 50 Robert H. Sloan, Balázs Szörényi, and György Turán. Learning Boolean functions with queries. In Boolean Models and Methods in Mathematics, Computer Science, and Engineering, pages 221–256. Cambridge University Press, 2010. doi:10.1017/cbo9780511780448.010.
- 51 Slawek Staworko and Piotr Wieczorek. Learning twig and path queries. In 15th International Conference on Database Theory, ICDT 2012, Berlin, Germany, March 26–29, 2012, pages 140–154. ACM, 2012. doi:10.1145/2274576.2274592.
- 52 Leslie G. Valiant. A theory of the learnable. *Commun. ACM*, 27(11):1134–1142, November 1984. doi:10.1145/1968.1972.
- 53 Vladimir Vapnik. Principles of risk minimization for learning theory. In Advances in Neural Information Processing Systems 4, [NIPS Conference, Denver, Colorado, USA, December 2-5, 1991], pages 831-838, 1991. URL: https://proceedings.neurips.cc/paper_files/paper/ 1991/file/ff4d5fbbafdf976cfdc032e3bde78de5-Paper.pdf.
- 54 He Zhu, Stephen Magill, and Suresh Jagannathan. A data-driven CHC solver. In Proceedings of the 39th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2018, Philadelphia, PA, USA, June 18–22, 2018, pages 707–721. ACM, 2018. doi: 10.1145/3192366.3192416.