SQL former: Deep Auto-Regressive Query Graph Generation for Text-to-SQL Translation

Adrián Bazaga, Pietro Liò, Gos Micklem

University of Cambridge, Cambridge, United Kingdom ${ar989, pl219, gm263}$ @cam.ac.uk

Abstract

In recent years, there has been growing interest in text-to-SQL translation, which is the task of converting natural language questions into executable SQL queries. This technology is important for its potential to democratize data extraction from databases. However, some of its key hurdles include domain generalisation, which is the ability to adapt to previously unseen databases, and alignment of natural language questions with the corresponding SQL queries. To overcome these challenges, we introduce SQL former, a novel Transformer architecture specifically crafted to perform text-to-SQL translation tasks. Our model predicts SQL queries as abstract syntax trees (ASTs) in an autoregressive way, incorporating structural inductive bias in the encoder and decoder layers. This bias, guided by database table and column selection, aids the decoder in generating SQL query ASTs represented as graphs in a Breadth-First Search canonical order. Comprehensive experiments illustrate the state-of-the-art performance of SQL former in the challenging text-to-SQL Spider benchmark. Our implementation is available at https://github.com/AdrianBZG/SQLformer.

1 Introduction

Relational databases are essential tools within various critical sectors like healthcare and industry among others. For those with technical expertise, accessing data from these databases using some form of structured query language, such as SQL, can be efficient. However, the intricate nature of SQL can make it daunting for non-technical users to learn, creating significant barriers to use..

Consequently, there has been a surge in interest in the field of text-to-SQL (Cai et al., 2018; Zelle and Mooney, 1996; Xu et al., 2017; Yu et al., 2018; Yaghmazadeh et al., 2017), which aims to convert natural language questions (NLQs) directly into SQL queries. This has the potential to dramatically reduce the obstacles faced by non-expert users when interacting with relational databases (DBs).

Early work in the field primarily focused on developing and evaluating semantic parsers for individual databases (Hemphill et al., 1990; Dahl et al., 1994; Zelle and Mooney, 1996; Zettlemoyer and Collins, 2012; Dong and Lapata, 2016). However, given the widespread use of DBs, an approach based on creating a separate semantic parser for each database does not scale.

One of the key hurdles in achieving domain generalisation (Wang et al., 2021; Cao et al., 2021; Wang et al., 2022; Cai et al., 2022; Hui et al., 2022) is the need for complex reasoning to generate SQL queries rich in structure. This involves the ability to accurately contextualise a user query against a specific DB by considering both explicit relations (like the table-column relations defined by the DB schema) and implicit relations (like determining if a phrase corresponds or applies to a specific column or table).

Recently, there has been a release of largescale datasets (Yu et al., 2019; Zhong et al., 2017) comprising hundreds of DBs and their associated question-SQL pairs. This has opened up the possibility of developing semantic parsers capable of functioning effectively across different DBs (Guo et al., 2019; Bogin et al., 2019; Zhang et al., 2019; Wang et al., 2021; Suhr et al., 2020; Choi et al., 2020; Bazaga et al., 2021). However, this demands the model to interpret queries in the context of relational DBs unseen during training, and precisely convey the query intent through SQL logic. As a result, cross-DB text-to-SQL semantic parsers cannot simply rely on memorising observed SQL patterns. Instead, they must accurately model the natural language query, the underlying DB structures, and the context of both.

Current strategies for cross-DB text-to-SQL semantic parsers generally follow a set of design principles to navigate these challenges. First, the question and schema representation are contextualised mutually by learning an embedding function conditioned on the schema (Hwang et al., 2019; Guo et al., 2019; Wang et al., 2021). Second, pre-trained language models (LMs), such as BERT (Devlin et al., 2019) or RoBERTa (Liu et al., 2019), have been shown to greatly improve parsing accuracy by enhancing generalisation over language variations and capturing long-range dependencies. Related approaches (Yin et al., 2020; Yu et al., 2021) have adopted pre-training on a BERT architecture with the inclusion of grammar-augmented synthetic examples, which when combined with robust base semantic parsers, have achieved state-of-the-art results.

In this paper, we present SQL former, which integrates the above design principles into a novel Transformer variant for text-to-SQL translation. We conceptualize each NLQ as a graph with multiple relationships, including syntactic dependencies and part-of-speech. The database schema is depicted as a graph, described by the metadata for the tables, columns, and their relations. Drawing inspiration from the image domain (Dosovitskiy et al., 2021), we incorporate two learnable token embeddings for table and column representations into the encoder. These are used to select a set of k_1 and k_2 tables and columns over the target database. Our model learns embeddings for the suggested tables and columns, enriching the decoder input with database information. This guides the decoder by contextualizing the input with the most relevant tables and columns from the given NLQ. Finally, we propose an autoregressive decoder, that predicts the SQL query as an AST. Experimental results on the Spider benchmark show that SQL former achieves 75.6% exact match (EM) accuracy in the test set, surpassing multiple state-of-the-art baselines.

2 Related Work

In earlier research, a sketch-based slot filling approach was commonly used, which employs different modules to predict distinct parts of the generated SQL query. This approach breaks down the task of SQL generation into several independent sketches and utilises different classifiers to predict the separate parts, as shown in methods such as SQLNet (Xu et al., 2017), TypeSQL (Yu et al., 2018), SQLOVA (Hwang et al., 2019), X-SQL (He et al., 2019) or RYANSQL (Choi et al., 2020). However, most of these methods only address simple

queries and struggle to generate accurate queries in the more complex scenarios found in the Spider dataset (Yu et al., 2019). The main challenge lies in the multi-table relations in the Spider dataset queries.

There have been multiple approaches to address the challenges brought by these complex SQL tasks. A common approach has been the use of attentionbased architectures for question-schema encoding, and rule-based structural architectures for query decoding. For instance, IRNet (Guo et al., 2019) separately encodes the question and schema using a LSTM and a self-attention mechanism respectively. Schema linking is accomplished by enhancing the question-schema encoding with custom type embeddings. The rule-based decoder from (Yin and Neubig, 2017a) was then used in order to decode a query into an intermediate representation, attaining a high-level abstraction for SQL.

On the other hand, multiple works make use of graph structures to encapsulate a range of complex relationships. For instance, Global-GNN (Bogin et al., 2019) models the database as a graph, while RAT-SQL (Wang et al., 2021) introduces schema encoding and linking, attributing a relation to every pair of input items. Further developments include LGESQL (Cao et al., 2021), which distinguishes between local and non-local relations using a line graph enhanced hidden module; SADGA (Cai et al., 2022) which utilises contextual and dependency structure to jointly encode the question graph with the database schema graph; S^2SQL (Hui et al., 2022) which incorporates syntactic dependency information in a relational graph attention network architecture (Wang et al., 2020), and RASAT (Qi et al., 2022) which integrates a relation-aware selfattention module into a T5 model (Raffel et al., 2020).

Recent work has demonstrated the effectiveness of fine-tuning pre-trained models. For instance, (Shaw et al., 2021) showed that fine-tuning a pretrained T5-3B model could yield competitive results. Building on this, (Scholak et al., 2021) introduced PICARD, a technique that constrains the auto-regressive decoder by applying incremental parsing during inference time. This approach filters out grammatically incorrect sequences in real time during beam search, improving the quality of the generated SQL.

3 Preliminaries

3.1 Problem Formulation

Given a natural language question Q and a schema S = (T, C) for a relational database, our objective is to generate a corresponding SQL query \mathcal{Y} . Here, the sequence $Q = \{q_1 \dots q_{|Q|}\}$ is a sequence of natural language tokens or words, where |Q| is the length of the question. The database schema is comprised of tables $T = \{t_1, \dots, t_{|T|}\}$ and columns C $= \{c_1, \dots, c_{|C|}\}$, where |T| and |C| are the number of tables and columns in the database, respectively. Each column name $c_i \in C$, is comprised of tokens $\{c_{i,1}, \dots, c_{i,|C_i|}\}$, where $|C_i|$ is the number of tokens in the column name, and similarly table names are also comprised of tokens $\{t_{i,1}, \dots, t_{i,|t_i|}\}$, where $|t_i|$ is the number of tokens in the table name.

3.2 Query Construction

We define the output SQL query \mathcal{Y} as a graph, representing the AST of the query in the context-free grammar of SQL, which our model learns to generate in an autoregressive fashion. The query is an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, of vertices \mathcal{V} and edges \mathcal{E} . Similar to previous works (Yin and Neubig, 2017b; Wang et al., 2021; Qi et al., 2022), the nodes $\mathcal{V} = \mathcal{P} \cup \mathcal{T} \cup \mathcal{C}$ are the possible actions derived from SQL context-free grammar rules (Yin and Neubig, 2017b), P, such as SelectTable, Se*lectColumn*, *Root*, as well as the tables (\mathcal{T}) and the columns (C) of the database schema. P are used to represent non-terminal nodes, depicting rules of the grammar, whereas \mathcal{T} and \mathcal{C} are used for terminal nodes, such as when selecting table or column names to be applied within a specific rule. The edge set $\mathcal{E} = \{(v_i, v_i) \mid v_i, v_i \in \mathcal{V}\}$ defines the connectivity between the different nodes in the graph.

In particular, we choose to represent the graph using an adjacency matrix under a Breadth-First-Search (BFS) node ordering scheme, π , that maps nodes to rows of the adjacency matrix as a sequence (You et al., 2018). This approach permits the modelling of graphs of varying size, such as the ones representing the ASTs of complex SQL queries. Formally, given a mapping f_S from graph, \mathcal{G} , to sequences, \mathcal{S} , and a graph \mathcal{G} with n nodes under BFS node ordering π , we can formulate

$$\mathbf{S}^{\pi} = \mathbf{f}_{\mathbf{S}}(\mathcal{G}, \pi) = (\mathbf{S}_{1}^{\pi}, \dots, \mathbf{S}_{n}^{\pi})$$
(1)

where $S_i^{\pi} \in \{0, 1\}^{i-1}$, $i \in \{1, ..., n\}$ depicts an adjacency vector between node $\pi(v_i)$ and the previ-

ous nodes $\pi(v_j)$, $j \in \{1, ..., i-1\}$ already existing in the graph, so that:

$$\mathbf{S}_{\mathbf{i}}^{\pi} = \mathbf{A}(_{1,\mathbf{i}}^{\pi},\ldots,\mathbf{A}_{\mathbf{i-1},\mathbf{i}}^{\pi})^{\mathbf{T}}, \forall \mathbf{i} \in \{\mathbf{2},\ldots,n\} \quad (2)$$

Then, using S^{π} , we can determine uniquely the SQL graph \mathcal{G} in a sequential form and learn to predict it autoregressively.

4 SQLformer

4.1 Model Overview

In light of recent advancements in the field (Shaw et al., 2021; Scholak et al., 2021; Li et al., 2023), we approach the text-to-SQL problem as a translation task by using an encoder-decoder architecture. Specifically, we extend the original Transformer encoder (see Subsection 4.3) by incorporating learnable table and column tokens in the encoder, used to select the most relevant tables and columns in the database schema given the NLQ. This information is injected as input to the decoder, so that it can be enriched with the representation of the schema-aware question encoding and the most relevant tables and columns in the database schema selected by the model. Moreover, the SQL former decoder extends the original Transformer decoder (see Subsection 4.4) in a way that integrates both node type, adjacency and previous generated action embeddings for generating a SQL query autoregressively as a sequence of actions derived from a SQL grammar (Yin and Neubig, 2017b). The overall architecture of our SQL former model is described in Fig. 1.

4.2 Model Inputs

In this section, we detail how the inputs to our model are constructed, in particular, the construction of both the NLQ and schema graphs are explained.

Question Graph Construction. The natural language question can be formulated as a graph $\mathcal{G}_Q = (\mathcal{Q}, \mathcal{R})$ where the node set \mathcal{Q} are the natural language tokens, and $\mathcal{R} = \{r_1, \ldots, r_{|\mathcal{R}|}\}$, refers to one-hop relations between words. In this work, we employ two groups of relations for the question graph. First, we use syntactic dependencies between the words in the question. Second, we use part-of-speech tagging to incorporate grammatical meaning across the words in the question. We create a joint question graph using both types of



Figure 1: An illustration of SQL former: our model inherits the seq2seq nature of the Transformer architecture, consisting of L layers of encoders and decoders. SQL former encoder introduces database table and column selection as inductive biases to contextualize the embedding of a question. In this example, the question consists of six tokens (see Fig. 2). This schema-conditioned question representation serves as input to the SQL former decoder module. Here we show the decoding timestep t = 4 as an example. The architecture for the decoder module is detailed in Fig. 4.

relations. This graph is then linearized as a Levi graph. Fig. 2 shows an example question graph with some illustrative relationships. To encode the question graph we use a GAT (Veličković et al., 2018), obtaining an embedding for each of the question tokens, $Z_i \in \mathbb{R}^d$, with $i \in \{1, ..., |Q|\}$, where *d* is the hidden size.



Figure 2: An illustration of an example Spider question with six tokens as a graph \mathcal{G} with part-of-speech and dependency relations. In this example, the token *number* has a OBJECT dependency with *Find*, and *Find* and *number* are tagged as verb (VB) and noun (NN), respectively. We do not show all edges and label types to prevent clutter.

Database Schema Graph Construction. Similarly, a database schema graph can be represented by $\mathcal{G}_S = (\mathcal{S}, \mathcal{R})$ where the node set $\mathcal{S} = (\mathcal{T}, \mathcal{C})$ represents the tables, \mathcal{T} , and the columns, \mathcal{C} , in the schema. The edge set $\mathcal{R} = \{r_1, ..., r_{|\mathcal{R}|}\}$ depicts the structural relationships among tables and columns in the schema. Similarly to previous works, we use the common relational databasespecific relations, such as primary/foreign key for column pairs, column types, and whether a column belongs to a specific table. Fig. 3 shows an example database schema graph. We encode the schema graph using a GAT (Veličković et al., 2018) and use global average pooling to obtain a single embedding to represent each database schema.

4.3 Table and Column Selection Encoder

The Transformer encoder (Vaswani et al., 2017) consists of alternating layers of multi-head selfattention (MHA) and Fully-connected Forward Network (FFN) blocks. Before every block, Layer Normalisation (LN) is applied, and after every block, a residual connection is added. More formally, in the



Figure 3: An illustration of an example Spider schema for database *scientist*_1. In this example, there are a total of 3 tables (*scientists*, *projects*, *assigned_to*), with multiple columns for each table and relationships between the tables. For instance, table *scientists* has 2 columns: *name* and *asn*, where *asn* is also a *foreign_key* relationship to table *assigned_to*.

 ℓ^{th} encoder layer, the hidden states are represented as $X_S^{\ell} = \{x_1^{\ell}, \ldots, x_N^{\ell}\}$, where *N* is the maximum length of the inputs. First, a MHA block maps *X* into a query matrix $Q \in \mathbb{R}^{n \times d_k}$, key matrix $K \in \mathbb{R}^{n \times d_k}$ and value matrix $V \in \mathbb{R}^{n \times d_v}$, where *m* is the number of query vectors, and *n* the number of key or value vectors. Then, an attention vector is calculated as follows

$$\begin{aligned} & \text{Attention}(\mathbf{Q},\mathbf{K},\mathbf{V}) {=} \text{softmax}(\mathbf{A})\mathbf{V}, \\ & \mathbf{A} {=} \frac{\mathbf{Q}\mathbf{K}^{\mathrm{T}}}{\sqrt{d_{k}}} \end{aligned} \tag{3}$$

In practice, the MHA block calculates the selfattention over *h* heads, where each head *i* is independently parametrized by $\mathbf{W}_{i}^{\mathbf{Q}} \in \mathbb{R}^{d_m \times d_k}$, $\mathbf{W}_{i}^{\mathbf{K}} \in \mathbb{R}^{d_m \times d_k}$ and $\mathbf{W}_{i}^{\mathbf{V}} \in \mathbb{R}^{d_m \times d_v}$, mapping the input embeddings \mathcal{X} into queries and key-value pairs. Then, the attention for each head is calculated and concatenated, as follows

$$\begin{aligned} \mathbf{Head_{i}} = & \mathbf{Attention}(\mathbf{QW_{i}^{Q}}, \mathbf{KW_{i}^{K}}, \mathbf{VW_{i}^{V}}) \\ \mathbf{MHA}(\mathcal{X}_{\mathcal{S}}^{\ell}) = & \mathbf{Concat}(\mathbf{Head_{1}}, \dots, \mathbf{Head_{h}})\mathbf{W^{U}} \\ & \bar{\mathcal{X}}_{\mathcal{S}}^{\ell} = & \mathbf{MHA}(\mathcal{X}_{\mathcal{S}}^{\ell}) \end{aligned}$$
(4)

where $\mathbf{W}^{\mathbf{U}} \in \mathbb{R}^{d_m^h \times d_m}$ is a trainable parameter matrix. Next, to acquire the semantic hidden states of the input, a FFN block is applied, as follows

$$\mathbf{FFN}(\bar{\mathcal{X}}_{\mathcal{S}}^{\ell}) = \max(\mathbf{0}, \bar{\mathcal{X}}_{\mathcal{S}}^{\ell} \mathbf{W}_{1} + \mathbf{b}_{1}) \mathbf{W}_{2} + \mathbf{b}_{2}$$
(5)

where $\mathbf{W_1} \in \mathbb{R}^{d_m \times d_{ff}}$ and $\mathbf{W_2} \in \mathbb{R}^{d_{ff} \times d_m}$ are linear weight matrices. Finally, layer normalisation and residual connection are applied as follows

$$\tilde{\mathcal{X}}_{\mathcal{S}}^{\ell} = \mathbf{LayerNorm}(\bar{\mathcal{X}}_{\mathcal{S}}^{\ell} + \mathbf{FFN}(\bar{\mathcal{X}}_{\mathcal{S}}^{\ell}))$$
 (6)

In the SQL former encoder, we receive as input the previously the 1D sequence of natural language token embeddings, Z, and we prepend two learnable tokens to the sequence of embeddings: Z_{tables} and Z_{cols} . The state of these tokens at the output of the Transformer encoder, depicted here as \tilde{X}_{tables} and $\tilde{X}_{columns}$ for tables and columns, respectively, serve as input to two Multi Layer Perceptron (MLP) blocks, that are responsible for, given the NLQ, selecting k_1 and k_2 tables and columns, respectively. k_1 and k_2 are both hyperparameters to the model. Sinusoidal vectors are added to the sequence embeddings to retain the original positional information of the question.

Therefore, after L encoder layers, we obtain the input question embedding as $\tilde{\mathcal{X}}_{S}^{\ell}$. Where the first and second tokens correspond to $\tilde{\mathcal{X}}_{tables}$ and $\tilde{\mathcal{X}}_{columns}$, and the remaining tokens correspond to the natural language question tokens embeddings, depicted as $\tilde{\mathcal{X}}_{Q} \in \mathbb{R}^{d \times Q}$. $\tilde{\mathcal{X}}_{T}$ and $\tilde{\mathcal{X}}_{C}$ are the input of two MLP blocks, $\mathbf{MLP_{T}} \in \mathbb{R}^{d \times |\mathcal{T}|}$ and $\mathbf{MLP_{C}} \in \mathbb{R}^{d \times |\mathcal{C}|}$, where d is the hidden size of the token embeddings, and $|\mathcal{T}|$ and $|\mathcal{C}|$ are the sizes of the tables and columns vocabularies, respectively. Both MLP blocks project the embeddings for the additional tokens into two separate vectors of probabilities, as follows

$$\mathbf{P_{tables} = softmax}(\mathbf{MLP_T}(\tilde{\mathcal{X}_T})) \\ \mathbf{P_{columns} = softmax}(\mathbf{MLP_C}(\tilde{\mathcal{X}_C}))$$
(7)

Then, the top k_1 and k_2 tables and columns, respectively, are selected according to $\mathbf{P_{tables}}$ and $\mathbf{P_{columns}}$. Next, two embedding lookup tables, $\mathbf{E_T} \in \mathbb{R}^{|\mathcal{T}| \times \mathbf{d_t}}$ and $\mathbf{E_C} \in \mathbb{R}^{|\mathcal{C}| \times \mathbf{d_c}}$, are used for mapping the k top tables and columns, respectively, into embeddings, as $\tilde{\mathcal{X}}_T^k \in \mathbb{R}^{\mathbf{k_1} \times \mathbf{d}}$ and $\tilde{\mathcal{X}}_C^k \in \mathbb{R}^{\mathbf{k_2} \times \mathbf{d}}$, where d is the size of the learnable embeddings. These are aggregated and concatenated, giving the final representation for the schema, depicted as $\tilde{\mathcal{X}}_{schema}$

Finally, \tilde{X}_Q and \tilde{X}_{schema} are aggregated to effectively contextualize the natural language question embedding by the embedding of the most likely tables and columns in the schema being mentioned. The result of this aggregation is given as input to the decoder module as part of the cross-attention.

4.4 Autoregressive Query Graph Generation Decoder

During the decoding phase, previous works (e.g. Wang et al. (2021); Cao et al. (2021); Hui et al. (2022); Cai et al. (2022)) widely adopt the LSTMbased tree decoder from Yin and Neubig (2017a) to generate SQL grammar rules. In contrast, the SQLformer decoder (see Fig. 4) extends the original Transformer decoder to predict the SQL grammar rules autoregressively.

This approach has two main advantages. First, it is able to maintain the context of previously generated parts of the query for longer sequences than LSTM-based decoders. This is especially important for long SQL queries, such as these containing sub-queries. Second, the Transformer encourages permutation invariance which is desirable for processing the node embeddings of the SQL graph, as the graph is invariant under any permutation of the nodes.

In the SQL former decoder, each of the nodes in the query are described by three attributes: node type, node adjacency and the action taken in the previous timestep. First, nodes are assigned a type, represented as $N^V = \{V_0, V_1, \dots, V_N\}$, where N is the number of nodes and V_i is a one-hot representation of the node type for node *i*. Specifically, nodes are grouped as non-terminal or terminal, where terminal types include *table_id* and column id, which denote the index of tables and columns in the database, respectively. Embeddings for node types are calculated by using a learnable transformation $\Psi(N^V) \in \mathbb{R}^{|\mathbf{V}| \times \mathbf{d}_{\mathbf{V}}}$, where d_V is the embedding dimensionality and |V| is the number of possible node types. The objective of V is to include the information about the AST node types into the decoding process. Next, node adjacency is represented as $N^A = \{A_0, A_1, \dots, A_N\}$, where N is the number of nodes and $A_i \in \{0, 1\}^M$. M is the maximum frontier of the BFS ordering. Embeddings for node adjacency are obtained from another learnable function $\Phi(N^A) \in \mathbb{R}^{1 \times d_A}$, with d_A as the embedding dimensionality. The embedding of the action taken in the previous timestep, a_{t-1} , is given by the learnable transformation function $\mathbf{\Omega}(N^R) \in \mathbb{R}^{1 \times \mathbf{d_T}}$, where N^R is the SQL grammar rule chosen in the previous timestep and d_T is the embedding dimensionality.

In order to incorporate the node type, adjacency and previous action embeddings to represent a node at each timestep, we extend the Transformer de-



Figure 4: Overview of the SQL former decoder architecture. The inputs to the decoder are the node adjacencies and types in the current timestep of the generation process, as well as the previous action embedding. The node type and adjacency embeddings are integrated with the previous action embedding into the aggregation process of the MHA mechanism as a bias term. The node embedding is then transformed through a series of L decoding layers with H heads. The final representation is used to generate the probability distribution of actions to take in the next timestep.

coder architecture and adapt it for SQLformer. In particular, inspired by (Ying et al., 2021), we include the node type and adjacency embeddings in the multi head self-attention aggregation process as a bias term (see Fig. 4).

Formally, we modify Eq. 3 so that $\Psi(N^V)$ and $\Phi(N^A)$ act as a bias term in the attention calculation, as follows

Then, the updated residuals for the node embedding, \mathbf{n}_t^{ℓ} , at layer ℓ , can be formalised as

$$\mathbf{n}_{t}^{\ell} = \mathbf{n}_{t}^{\ell-1} + \mathbf{O}^{\ell} \|_{\mathbf{k}=1}^{\mathbf{K}} \sum_{j=1}^{\mathbf{N}} \left(\mathbf{G}^{\mathbf{k},\ell} \mathbf{V}^{\mathbf{k},\ell} \right) \quad (9)$$
$$\mathbf{G}^{\mathbf{k},\ell} = \mathbf{softmax}(\mathbf{A}^{\mathbf{k},\ell})$$

where \parallel means concatenation, and *K* is the number of attention heads.

Consequently, the decoder state at the current timestep after L decoder layers, \mathbf{n}_t^L , is fed to an action output MLP head which computes the distribution $P(a_{t+1})$ of next timestep actions based on the node type, adjacency and previous action at timestep t. Formally, $P(a_{t+1})$ is calculated as follows

$$\mathbf{P}(\mathbf{a_{t+1}} \mid \mathbf{n}_t^L) = \mathbf{softmax}(\mathbf{W_an_t^L}) \qquad (10)$$

Finally, the prediction of the SQL query AST can be decoupled into a sequence of actions $a = (a_1, \ldots, a_{|a|})$, yielding the training objective for the task as

$$\mathcal{L} = -\sum_{\mathbf{p}=1}^{|\mathbf{a}|} \log \mathbf{P}(\mathbf{a}_{\mathbf{p}} \mid \mathbf{a}_{<\mathbf{p}}, \mathcal{S}, \mathcal{Q})$$
(11)

5 Experiments

In this section, we show our model performance on the Spider text-to-SQL dataset (Yu et al., 2019). Also, we present ablation studies to analyse the importance of the different components of the SQLformer architecture.

5.1 Experimental Setup

Dataset. Our experiments use the Spider dataset, a large-scale cross-domain text-to-SQL benchmark. This dataset also incorporates multiple text-to-SQL datasets. The Spider dataset contains 8,659 training examples of question and SQL query pairs (along with the corresponding database schemas), 1,034 development (dev) examples and 2,147 test examples, spanning 300 complex databases across 138 different domains.

Evaluation Metrics. Following previois works (Yu et al., 2019), we report results using the same metrics on the test set. In particular we compute Exact Match (EM) accuracy on all examples, as well as grouped by difficulty levels. EM can evaluate how much a predicted SQL query is comparable to the ground truth query. Similarly to previous work (Wang et al., 2021) on Spider, these metrics do not take into account the model's performance on generating the constant values in the SQL query. In our ablation study experiments, we also use the EM accuracy metric over the development set.

Implementation Details. We implemented SQLformer in PyTorch (Paszke et al., 2019). For the graph neural network components, we use PyTorch Geometric (Fey and Lenssen, 2019). The questions, column and table names are tokenized and lemmatized using stanza (Qi et al., 2020). For dependency parsing and part-of-speech tagging, stanza (Qi et al., 2020) is used. We find the best set of hyperparameters on a randomly sampled subset of 10% samples from the dev dataset. For training, we set the maximum input length as 1024, maximum number of generated AST nodes to 200, maximum previous AST nodes in the BFS ordering as 30, batch size as 32, and maximum training steps to 20,000. The number of layers for the encoder and decoder are both set to 6 and number of heads is 8. The dimensionality of the encoder and the decoder are set to 512. k_1 and k_2 are set to 20. The embedding sizes for tables and columns are set to 512. The node adjacency, node type and action embeddings sizes are 512. The output MLP for generating the next output action during decoding has 2 layers and hidden dimensionality of 512. Tokens embeddings are initialized with ELECTRA (Clark et al., 2020) using the official weights from the HuggingFace library (Wolf et al., 2020). We use teacher forcing in the decoder for higher training stability. Results are on the test set unless stated otherwise.

5.2 Overall Performance

The EM accuracy results on the Spider benchmark are presented in Table 1. As shown in the table, our proposed model SQL former achieves competitive performance in EM accuracy. On the test set, compared with RAT-SQL (Wang et al., 2021), our model's EM increases from 68.7% to 75.6%, achieving 6.9% absolute improvement. When compared to approaches that fine-tune a Language Model (LM) with a much larger amount of parameters, such as T5-3B (71.9%), we achieve a 3.7% absolute improvement. This effectively shows the benefit of our proposed architecture for solving text-to-SQL tasks with fewer amount of parameters.

Furthermore, we provide a breakdown of accuracy by query difficulty level, i.e. easy, medium, hard and extra hard, as defined by Yu et al. (2019). In Table 2 we provide a comparison between our approach and state-of-the-art baselines on the EM accuracy metric, for the four query difficulty subsets. As expected, performance drops significantly with increasing query difficulty, dropping from 92.7% to 51.2% accuracy on easy and extra queries, respectively. Focusing on the most complex types of queries, when compared with RAT-SQL, SQLformer achieves an absolute improvement of 9.7% and 8.3% on hard and extra queries, respectively. This consolidates our motivation to employ a Transformer-based SQL decoder, allowing the model to capture longer dependencies. Therefore, SQL former surpasses the baseline methods across all four subsets by a significant margin, giving supporting evidence for the effectiveness of our approach.

Table 1: Exact Match (EM) results on Spider's test and dev dataset splits. We compare our approach with some state-of-the-art baseline methods.

Method				EM accuracy (%)			
				Dev	v Test		
SADGA + GAP (Cai et al., 2022)				73.1		70.1	
RAT-SQL + GraPPa (Yu et al., 2021)				73.4	.4 69.6		
RAT-SQL + GAP + NatSQL (Shi et al., 2021)				73.7	.7 68.7		
SMBOP + GraPPa (Rubin and Berant, 2021)				74.7		59.7	
DT-Fixup SQL-SP + RoBERTa (Xu et al., 2021)				75.0		70.9	
LGESQL + ELECTRA (Cao et al., 2021)				75.1		72.0	
RASAT + PICARD (Qi et al., 2022)				75.3		70.9	
T5-3B + PICARD (Scholak et al., 2021)				75.5		71.9	
S ² SQL + ELECTRA (Hui et al., 2022)				76.4		72.1	
GRAPHIX-3B + PICARD (Li et al., 2023)				77.1 74.		74.0	
SQLformer (our approach)				78.2		75.6	
Method	Easy	Medium	Haı	d Ex	ktra	All	
RAT-SQL + BERT	86.4	73.6	62.	1 42	2.9	69.7	
SADGA	90.3	72.4	63.	8 4	9.4	71.6	
LGESQL	91.5	76.7	66.	7 43	8.8	74.1	
GRAPHIX-T5-3B	91.9	81.6	61.	5 5	50	75.6	

Table 2: EM accuracy on the Spider queries across different levels of difficulty as defined by Yu et al. (2019).

82.9

71.8

51.2

76.8

92.7

5.3 Ablation Study

SQLformer

In order to better validate the importance of each component in our architecture, we perform a series of ablation studies on the best performing SQL- former model. In Table 3, we compare 4 different design choices that we believe are critical in our architecture. In particular, we assess the impact of removing the table and column selection component from the encoder, the part-of-speech question encoding, and the dependency graph question encoding.

Method	EM accuracy (%)		
SQLformer	$\textbf{78.2} \pm \textbf{0.75}$		
SQLformer w/o dependency graph	77.5 ± 0.72		
SQLformer w/o Part-of-Speech graph	77.3 ± 0.63		
SQLformer encoder + LSTM-based decoder	74.2 ± 0.38		
SQLformer w/o table + column selection	72.3 ± 0.38		

Table 3: EM accuracy (and \pm 95% confidence interval) of SQLformer ablation study on the development set.

As shown in Table 3, the component that has the biggest impact in the architecture is the table and column selection. Upon removing this component, the EM accuracy drops from 78.2% to 72.3%, leading to a 5.9% absolute performance drop. We hypothesise that such mechanism injects the notion of schema-question linking, which has been demonstrated to be critical in text-to-SQL domain. Therefore, without schema linking, the joint contextualisation of question and schema is missing, increasing significantly the difficulty of the task. On the other hand, the effect of removing the dependency graph and part-of-speech question encodings have less impact on performance, leading to an absolute performance decrease of 0.7% and 0.9%, respectively. When swapping our decoder with the one in (Yin and Neubig, 2017a) performance decreases by 4%, showcasing the effectiveness of using a Transformer-based decoder.

6 Conclusion

In this work, we introduced SQLformer, a new model for text-to-SQL generation, unique compared to previous models due to its autoregressive Transformer-based prediction of the SQL query. With a specially designed encoder, SQLformer links questions and schema, utilizing pre-trained models for effective representation. A novel decoder layer integrates node adjacency, type and previous action information during learning, and is conditioned on top-selected tables, columns, and schema-aware question encoding to generate SQL queries. Notably, SQLformer outperformed other competitive text-to-SQL baselines, showcasing its state-of-the-art performance.

Limitations

One of the main limitations of our work is its focus on the English language, as it is the language used by most publicly available datasets. A potential way to alleviate this is by using multi-language PLMs for processing the questions. Also, this work focuses specifically on grammar-based text-to-SQL decoding, without using large pre-trained language models or prompt-based techniques with large models such as GPT-3.

References

- Adrián Bazaga, Nupur Gunwant, and Gos Micklem. 2021. Translating synthetic natural language to database queries with a polyglot deep learning framework. *Scientific Reports*, 11(1).
- Ben Bogin, Matt Gardner, and Jonathan Berant. 2019. Global Reasoning over Database Structures for Textto-SQL Parsing. ArXiv:1908.11214 [cs].
- Ruichu Cai, Boyan Xu, Xiaoyan Yang, Zhenjie Zhang, Zijian Li, and Zhihao Liang. 2018. An Encoder-Decoder Framework Translating Natural Language to Database Queries. ArXiv:1711.06061 [cs].
- Ruichu Cai, Jinjie Yuan, Boyan Xu, and Zhifeng Hao. 2022. SADGA: Structure-Aware Dual Graph Aggregation Network for Text-to-SQL. ArXiv:2111.00653 [cs].
- Ruisheng Cao, Lu Chen, Zhi Chen, Yanbin Zhao, Su Zhu, and Kai Yu. 2021. LGESQL: Line Graph Enhanced Text-to-SQL Model with Mixed Local and Non-Local Relations. ArXiv:2106.01093 [cs].
- DongHyun Choi, Myeong Cheol Shin, EungGyun Kim, and Dong Ryeol Shin. 2020. RYANSQL: Recursively Applying Sketch-based Slot Fillings for Complex Text-to-SQL in Cross-Domain Databases. ArXiv:2004.03125 [cs].
- Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. 2020. ELECTRA: Pretraining text encoders as discriminators rather than generators. In *ICLR*.
- Deborah A. Dahl, Madeleine Bates, Michael Brown, William Fisher, Kate Hunicke-Smith, David Pallett, Christine Pao, Alexander Rudnicky, and Elizabeth Shriberg. 1994. Expanding the Scope of the ATIS Task: The ATIS-3 Corpus. In *Human Language Technology: Proceedings of a Workshop held at Plainsboro, New Jersey, March 8-11, 1994.*
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. ArXiv:1810.04805 [cs].

- Li Dong and Mirella Lapata. 2016. Language to Logical Form with Neural Attention. ArXiv:1601.01280 [cs].
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. 2021. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale. ArXiv:2010.11929 [cs].
- Matthias Fey and Jan Eric Lenssen. 2019. Fast Graph Representation Learning with PyTorch Geometric. ArXiv:1903.02428 [cs, stat].
- Jiaqi Guo, Zecheng Zhan, Yan Gao, Yan Xiao, Jian-Guang Lou, Ting Liu, and Dongmei Zhang. 2019. Towards Complex Text-to-SQL in Cross-Domain Database with Intermediate Representation. ArXiv:1905.08205 [cs].
- Pengcheng He, Yi Mao, Kaushik Chakrabarti, and Weizhu Chen. 2019. X-SQL: reinforce schema representation with context. ArXiv:1908.08113 [cs].
- Charles T. Hemphill, John J. Godfrey, and George R. Doddington. 1990. The ATIS Spoken Language Systems Pilot Corpus. In Speech and Natural Language: Proceedings of a Workshop Held at Hidden Valley, Pennsylvania, June 24-27, 1990.
- Binyuan Hui, Ruiying Geng, Lihan Wang, Bowen Qin, Bowen Li, Jian Sun, and Yongbin Li. 2022. S\$^2\$SQL: Injecting Syntax to Question-Schema Interaction Graph Encoder for Text-to-SQL Parsers. ArXiv:2203.06958 [cs].
- Wonseok Hwang, Jinyeong Yim, Seunghyun Park, and Minjoon Seo. 2019. A Comprehensive Exploration on WikiSQL with Table-Aware Word Contextualization. ArXiv:1902.01069 [cs].
- Jinyang Li, Binyuan Hui, Reynold Cheng, Bowen Qin, Chenhao Ma, Nan Huo, Fei Huang, Wenyu Du, Luo Si, and Yongbin Li. 2023. Graphix-t5: Mixing pretrained transformers with graph-aware layers for textto-sql parsing. arXiv preprint arXiv:2301.07507.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A Robustly Optimized BERT Pretraining Approach. ArXiv:1907.11692 [cs].
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. 2019. PyTorch: An Imperative Style, High-Performance Deep Learning Library. ArXiv:1912.01703 [cs, stat].

- Jiexing Qi, Jingyao Tang, Ziwei He, Xiangpeng Wan, Yu Cheng, Chenghu Zhou, Xinbing Wang, Quanshi Zhang, and Zhouhan Lin. 2022. RASAT: Integrating Relational Structures into Pretrained Seq2Seq Model for Text-to-SQL. ArXiv:2205.06983 [cs].
- Peng Qi, Yuhao Zhang, Yuhui Zhang, Jason Bolton, and Christopher D. Manning. 2020. Stanza: A Python Natural Language Processing Toolkit for Many Human Languages. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: System Demonstrations, pages 101–108, Online. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. ArXiv:1910.10683 [cs, stat].
- Ohad Rubin and Jonathan Berant. 2021. SmBoP: Semiautoregressive bottom-up semantic parsing. In Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 311–324, Online. Association for Computational Linguistics.
- Torsten Scholak, Nathan Schucher, and Dzmitry Bahdanau. 2021. PICARD: Parsing Incrementally for Constrained Auto-Regressive Decoding from Language Models. ArXiv:2109.05093 [cs].
- Peter Shaw, Ming-Wei Chang, Panupong Pasupat, and Kristina Toutanova. 2021. Compositional Generalization and Natural Language Variation: Can a Semantic Parsing Approach Handle Both? ArXiv:2010.12725 [cs].
- Peng Shi, Patrick Ng, Zhiguo Wang, Henghui Zhu, Alexander Hanbo Li, Jun Wang, Cicero Nogueira dos Santos, and Bing Xiang. 2021. Learning contextual representations for semantic parsing with generationaugmented pre-training. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(15):13806– 13814.
- Alane Suhr, Ming-Wei Chang, Peter Shaw, and Kenton Lee. 2020. Exploring Unexplored Generalization Challenges for Cross-Database Semantic Parsing. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 8372–8388, Online. Association for Computational Linguistics.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. ArXiv:1706.03762 [cs].
- Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. 2018. Graph Attention Networks. ArXiv:1710.10903 [cs, stat].

- Bailin Wang, Richard Shin, Xiaodong Liu, Oleksandr Polozov, and Matthew Richardson. 2021. RAT-SQL: Relation-Aware Schema Encoding and Linking for Text-to-SQL Parsers. ArXiv:1911.04942 [cs].
- Kai Wang, Weizhou Shen, Yunyi Yang, Xiaojun Quan, and Rui Wang. 2020. Relational Graph Attention Network for Aspect-based Sentiment Analysis. ArXiv:2004.12362 [cs].
- Lihan Wang, Bowen Qin, Binyuan Hui, Bowen Li, Min Yang, Bailin Wang, Binhua Li, Fei Huang, Luo Si, and Yongbin Li. 2022. Proton: Probing Schema Linking Information from Pre-trained Language Models for Text-to-SQL Parsing. ArXiv:2206.14017 [cs].
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. Transformers: State-of-the-Art Natural Language Processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 38–45, Online. Association for Computational Linguistics.
- Peng Xu, Dhruv Kumar, Wei Yang, Wenjie Zi, Keyi Tang, Chenyang Huang, Jackie Chi Kit Cheung, Simon J.D. Prince, and Yanshuai Cao. 2021. Optimizing deeper transformers on small datasets. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 2089– 2102, Online. Association for Computational Linguistics.
- Xiaojun Xu, Chang Liu, and Dawn Song. 2017. SQL-Net: Generating Structured Queries From Natural Language Without Reinforcement Learning. ArXiv:1711.04436 [cs].
- Navid Yaghmazadeh, Yuepeng Wang, Isil Dillig, and Thomas Dillig. 2017. SQLizer: query synthesis from natural language. *Proceedings of the ACM on Programming Languages*, 1(OOPSLA):63:1–63:26.
- Pengcheng Yin and Graham Neubig. 2017a. A Syntactic Neural Model for General-Purpose Code Generation. ArXiv:1704.01696 [cs].
- Pengcheng Yin and Graham Neubig. 2017b. A syntactic neural model for general-purpose code generation. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 440–450, Vancouver, Canada. Association for Computational Linguistics.
- Pengcheng Yin, Graham Neubig, Wen-tau Yih, and Sebastian Riedel. 2020. TaBERT: Pretraining for Joint Understanding of Textual and Tabular Data. ArXiv:2005.08314 [cs].

- Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. 2021. Do Transformers Really Perform Bad for Graph Representation? ArXiv:2106.05234 [cs].
- Jiaxuan You, Rex Ying, Xiang Ren, William L. Hamilton, and Jure Leskovec. 2018. GraphRNN: Generating Realistic Graphs with Deep Auto-regressive Models. ArXiv:1802.08773 [cs].
- Tao Yu, Zifan Li, Zilin Zhang, Rui Zhang, and Dragomir Radev. 2018. TypeSQL: Knowledgebased Type-Aware Neural Text-to-SQL Generation. ArXiv:1804.09769 [cs].
- Tao Yu, Chien-Sheng Wu, Xi Victoria Lin, Bailin Wang, Yi Chern Tan, Xinyi Yang, Dragomir Radev, Richard Socher, and Caiming Xiong. 2021. GraPPa: Grammar-Augmented Pre-Training for Table Semantic Parsing. ArXiv:2009.13845 [cs].
- Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. 2019. Spider: A Large-Scale Human-Labeled Dataset for Complex and Cross-Domain Semantic Parsing and Text-to-SQL Task. ArXiv:1809.08887 [cs].
- John M. Zelle and Raymond J. Mooney. 1996. Learning to parse database queries using inductive logic programming. In *Proceedings of the thirteenth national conference on Artificial intelligence - Volume* 2, AAAI'96, pages 1050–1055, Portland, Oregon. AAAI Press.
- Luke S. Zettlemoyer and Michael Collins. 2012. Learning to Map Sentences to Logical Form: Structured Classification with Probabilistic Categorial Grammars. ArXiv:1207.1420 [cs].
- Rui Zhang, Tao Yu, He Yang Er, Sungrok Shim, Eric Xue, Xi Victoria Lin, Tianze Shi, Caiming Xiong, Richard Socher, and Dragomir Radev. 2019. Editing-Based SQL Query Generation for Cross-Domain Context-Dependent Questions. ArXiv:1909.00786 [cs].
- Victor Zhong, Caiming Xiong, and Richard Socher. 2017. Seq2SQL: Generating Structured Queries from Natural Language using Reinforcement Learning. ArXiv:1709.00103 [cs].