Minimax Sequential Testing for Poisson Processes

Hongwei Mei[∗]

November 8, 2023

Abstract

Suppose we observe a Poisson process in real time for which the intensity may take on two possible values λ_0 and λ_1 . Suppose further that the priori probability of the true intensity is not given. We solve a minimax version of Bayesian problem of sequential testing of two simple hypotheses to minimize a linear combination of the probability of wrong detection and the expected waiting time in the worst scenario of all possible priori distributions. An equivalent characterization for the least favorable distributions is derived and a sufficient condition for the existence is concluded.

Keywords Sequential testing, minimax optimization, least favorable distribution, optimal stopping, Poisson processes

1 Introduction

Suppose that we observe a continuous-time Poisson process X whose intensity may take on two possible values λ_0 or λ_1 (assume $\lambda_1 > \lambda_0 > 0$ without loss of generality). Given that the process X is observed in real time, the problem is to detect the correct drift coefficient as soon as possible and with minimal probabilities of incorrect terminal decisions. The above problem is usually called by *sequential testing problems* for two simple hypotheses which has been solved in [\[16\]](#page-11-0) if a priori distribution on the true intensity is given (the probability of $\lambda = \lambda_0$ is $1 - \pi$ and the probability of $\lambda = \lambda_1$ is π). The key step of solving such a sequential testing problem lies in deriving an equivalent optimal stopping problem through a Bayesian formulation. Then the optimal stopping time obtained for the optimal stopping problem determines an optimal testing rule for the sequential testing problem subsequently. Using the similar idea, [\[2,](#page-11-1) [3\]](#page-11-2) solve the sequential testing problems for compound Poisson process subsequently.

Besides Poisson process, there also exists a well-established body of literature on the so-called Wiener sequential testing problem for which the observed process X satisfies a stochastic differential equations. For example, to test the true drift(s) of a Brownian motion or a stochastic differential equation with Gaussian noise, the testing problems for one-dimensional or multidimensional observed processes have been studied in [\[1,](#page-11-3) [4,](#page-11-4) [9,](#page-11-5) [10,](#page-11-6) [12,](#page-11-7) [13\]](#page-11-8). It is worth mentioning that Bayesian formulations are also adopted in those papers thanks to the priori distribution.

[∗]Department of Mathematics and Statistics, Texas Tech University, Lubbock, TX 79409, USA; email: hongwei.mei@ttu.edu. The author is partially supported by Simons Foundation's Travel Support for Mathematicians Program (No. 00002835).

While it is more commonly seen that the priori distribution on the two possible hypotheses is not feasible in practice. This paper is in part motivated by the following question: is it possible (within the Bayesian setting) to reformulate the statement of the sequential testing problem so that the solution to the optimal stopping problem does not depend on knowledge of the a priori distribution π ? The answer is in the affirmative when one considers its minimax version by taking consideration of all possible priori distributions. The prior distribution of π which yields the worst scenario among all possible a priori distributions is called the *least favorable distribution* (see, for example, [\[15\]](#page-11-9) and references therein).

The study on minimax testing problems could date back to [\[11\]](#page-11-10) and then has aroused great interests of mathematicians afterwards. The readers are referred to the review paper [\[8\]](#page-11-11) and references therein for the recent developments if the observation is a discrete-time sequence and admits some general Markovian structure. Compared to the sequential testing problems with a priori distribution, the additional efforts for minimax sequential testing problems are devoted to identifying the least favorable distribution first. After a least favorable distribution is discovered, the optimal testing rule can be determined by a sequential testing problem directly. For the most recent developments on the discrete-time models, one may refer to [\[6\]](#page-11-12) when the observations are i.i.d and to [\[7\]](#page-11-13) when the observations admit a general Markovian structure. In the continuous-time model, when the observed process is a continuous-time process satisfying a stochastic differential equation, the minimax sequential testing problem for the drift has been solved in [\[5\]](#page-11-14). In this paper, we aim at extending the minimax sequential testing theory for the intensity of a Poisson process. Similar to [\[6,](#page-11-12) [7,](#page-11-13) [5\]](#page-11-14), our main effort is devoted in deriving the least favorable distributions. To the best knowledge of the authors, the problem has not been considered in the literature.

We will follow the approaches adopted in [\[5\]](#page-11-14) while several new features have to be addressed in this paper. First, the sample paths of Poisson process are not continuous. Second, when working on the optimal stopping problem, we will see that the probabilistic regularity of the optimal stopping boundary, which is an essential step in [\[5\]](#page-11-14), fails in our case. Some new methods are needed here. Third, we will see that $1/2$ and $1/2$ is not the least favorable priori distribution even if the performance functional is symmetric. Such a result implies that the minimax sequential testing problem for Poisson process is not symmetric, different from the linear minimax Wiener sequential testing problems in [\[5\]](#page-11-14) for stochastic differential equations. Working on those new features, we will present an equivalent characterization of the least favorable distribution and present a sufficient condition for its existence. Moreover, we will propose a numerical method for a least favorable distribution from its characterization.

The rest of the paper is arranged as follows. We will present the explicit formulation of our minimax sequential testing problem in Section [2.](#page-2-0) Then the optimal stopping theory of sequential testing problem is recalled in Section [3](#page-4-0) and some new results are introduced as a preparation of minimax sequential testing problem. In Section [4,](#page-7-0) we present our main results for minimax sequential testing problem: deriving an equivalent characterization for the least favorable distribution and concluding a sufficient condition for its existence. Then a numerical example is presented in Section [5](#page-9-0) to illustrate our main results. Finally some concluding remarks are made in Section [6.](#page-10-0)

2 Formulation

Recall that the intensity λ of Poisson process X may take either $\lambda_1 > \lambda_0 > 0$. The detection problem is to test the following two simple hypotheses:

$$
H_0: \lambda = \lambda_0 \text{ versus } H_1: \lambda = \lambda_1.
$$

We will formulate the sequential testing problem first and then the minimax sequential testing problem.

1. We adopt the Bayesian formulation in [\[16\]](#page-11-0) and assume the intensity λ admits a priori distribution

(2.1)
$$
P(\lambda = \lambda_0) = 1 - \pi \text{ and } P(\lambda = \lambda_1) = \pi
$$

for some $\pi \in (0,1)$. We write $\psi = \pi/(1-\pi)$. One can easily see that π and ψ are essentially equivalent. Based on such a priori distribution, we define a new probability measure P_{ψ} by

(2.2)
$$
P_{\psi}(\cdot) = \frac{1}{1+\psi} P(\cdot | \lambda = \lambda_0) + \frac{\psi}{1+\psi} P(\cdot | \lambda = \lambda_1)
$$

Then

(2.3)
$$
P_{\psi}(\lambda = \lambda_0) = \frac{1}{1 + \psi} \text{ and } P_{\psi}(\lambda = \lambda_1) = \frac{\psi}{1 + \psi}
$$

for some $\psi \in (0,\infty)$. Such a priori distribution only depends on a parameter ψ . Therefore we will call ψ as the priori distribution of λ if its distribution satisfies [\(2.3\)](#page-2-1).

The sequential testing problem aims at detecting the true parameter λ based on the continuous observation of the state process. This yields that a decision to make consists of two perspectives: a stopping time τ and the decided index $d = 0$ or 1 (i.e. 0 stands for accepting H_0 and 1 stands for accepting H_1). To evaluate the performance of the decision couple (τ, d) , we define the performance functional by a linear combination of *the expected waiting time* and *the expected probabilities of false detection*:

(2.4)
$$
J(\varphi; \tau, d) = \mathsf{E}_{\varphi} \big[\tau + aI(d = 0; \lambda = \lambda_1) + bI(d = 1; \lambda = \lambda_0) \big]
$$

for some given $a, b > 0$. The two constants a, b stand for the costs for two possible types of wrong detection. If $a = b$, the cost functional is called *symmetric* as the costs of false detection are same. The sequential testing problem is to find an optimal (τ^*, d^*) such that the performance functional $J(\cdot)$ is minimized.

2. The above sequential testing problem has been solved in [\[16\]](#page-11-0). The main approach is to derive an equivalent optimal stopping problem through a measure-change method. Let us summarize the key steps as follows.

Write S by the set of all stopping time X and \mathcal{F}_t^X by the natural filtration of X. The likelihood *ratio process* L_t , the posteriori probability process Π_t , and the posteriori probability ratio process Ψ_t can be written by

$$
L_t = \frac{d\mathsf{P}(\cdot|\lambda=\lambda_1)}{d\mathsf{P}(\cdot|\lambda=\lambda_0)}\Big|_{\mathcal{F}_t^X}, \ \Pi_t := \mathsf{P}(\lambda=\lambda_1|\mathcal{F}_t^X) \text{ and } \Psi_t = \frac{\Pi_t}{1-\Pi_t}.
$$

From (2.14) and (2.16) in [\[16\]](#page-11-0), we see that he posteriori probability ratio process Ψ satisfies

(2.5)
$$
\Psi_t = \psi L_t = \psi \exp\left\{ (X_t - X_0) \log \left(\frac{\lambda_1}{\lambda_0} \right) - (\lambda_1 - \lambda_0) t \right\},
$$

$$
d\Psi_t = \left(\frac{\lambda_1}{\lambda_0} - 1 \right) \Psi_t - d(X_t - \lambda_0 t).
$$

Similar to of (2.9) in [\[4\]](#page-11-4), we are able to derive a new form of the \bar{J} by changing the measure from E_{ψ} to E_0 . First we note that

$$
J(\varphi; \tau, d) = \mathsf{E}_{\psi} \left[\tau + aI(d = 0; \lambda = \lambda_1) + bI(d = 1; \lambda = \lambda_0) \right]
$$

= $\mathsf{E}_{\psi} [\tau + a\Pi_t I(d = 0) + b(1 - \Pi_t)I(d = 1)]$
 $\geq \mathsf{E}_{\psi} \left(\tau + [a\pi_{\tau}] \wedge [b(1 - \pi_{\tau})] \right) =: \bar{J}(\psi; \tau)$

The inequality holds if and only $d = 0$ if $a\Pi_\tau < b\Pi_\tau$, $d = 1$ if $a\Pi_\tau > b\pi_\tau$ and $d = 0$ or 1 if $a\Pi_{\tau} = b\Pi_{\tau}$. Now it follows that

$$
\bar{J}(\psi;\tau) = \mathsf{E}_{\psi}\Big(\tau + [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) \n= \frac{1}{1 + \psi} \mathsf{E}_{0}\Big(\int_{0}^{\tau} ds + [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) + \frac{\psi}{1 + \psi} \mathsf{E}_{1}\Big(\int_{0}^{\tau} ds + [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) \n= \frac{1}{1 + \psi} \mathsf{E}_{0}\Big(\int_{0}^{\tau} 1 ds + [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) \n+ \frac{\psi}{1 + \psi} \mathsf{E}_{0}\Big(\int_{0}^{\tau} L_{s} ds + L_{\tau} \times [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) \n= \frac{1}{1 + \psi} \mathsf{E}_{0}\Big(\int_{0}^{\tau} (1 + \Psi_{s}) ds + (1 + \Psi_{\tau}) \times [a\Pi_{\tau}] \wedge [b(1 - \Pi_{\tau})]\Big) \n= \frac{1}{1 + \psi} \mathsf{E}_{0}\Big[\int_{0}^{\tau} (1 + \Psi_{t}) dt + (a\Psi_{\tau}) \wedge b\Big).
$$

We note that X_t is a Poisson process with intensity λ_0 under P_0 and subsequently Φ is a strong Markov process under P_0 . Combining (2.5) with (2.6) , we obtained the equivalent optimal stopping problem for the sequential testing problem if the priori distribution is given:

ST: Find a $\tau^* \in \mathbb{S}$ such that

(2.7)
$$
\bar{J}(\psi;\tau^*) = \inf_{\tau \in \mathbb{S}} \bar{J}(\psi;\tau).
$$

3. For ST, it is proved in [\[16\]](#page-11-0) that there exists two positive numbers α^* and β^* such that the optimal stopping time is

$$
\tau^* = \inf\{t \ge 0 : \Phi_t \notin (\alpha^*, \beta^*)\}
$$

and the optimal decision d^* at τ^* satisfies

$$
d_{\tau^*}^* = \begin{cases} 1, & \text{if } \Psi_{\tau^*} > b/a; \\ 0, & \text{if } \Psi_{\tau^*} < b/a; \\ \text{either 0 or 1, if } \Psi_{\tau^*} = b/a. \end{cases}
$$

It is worth mentioning that $\bar{J}(\psi; \tau) = J(\psi; \tau, d^*_{\tau}).$

4. With the above preparation in hand, we turn to the formulation of the minimax sequential testing problem. The objective of the minimax formulation is to minimize the performance functional $J(\psi; \cdot)$ in the *worst case scenario* of all prior distributions ψ . This leads to the following optimal stopping problem.

MinimaxST: Find a $(\psi^*; \tau^*) \in (0, \infty) \times \mathbb{S}$ such that

(2.8)
$$
\bar{J}(\psi^*; \tau^*) = \inf_{\tau \in \mathcal{S}} \sup_{\psi > 0} \bar{J}(\psi; \tau).
$$

5. The optimization problem in [\(2.8\)](#page-4-1) belongs to the class of minimax optimization problems. By the well-known saddle-point property, (ψ^*, τ^*) is optimal if and only if

(2.9)
$$
\bar{J}(\psi; \tau^*) \leq \bar{J}(\psi^*; \tau^*) \leq \bar{J}(\psi^*; \tau) \text{ for any } (\psi, \tau) \in (0, \infty) \times \mathbb{S}.
$$

The saddle-point property consists of two perspectives:

(1) τ^* is the optimal stopping time for **ST** if $\psi = \psi^*$. This can be concluded from the sequential testing problem directly. While we will still need to conclude some auxiliary results for the future minimax sequential testing problem.

(2) Given $\tau^* \in \mathbb{S}, \psi = \psi^*$ is the *least favorable distribution* in $\bar{J}(\psi; \tau^*)$, i.e.

$$
\bar{J}(\psi; \tau^*) \le \bar{J}(\psi^*; \tau^*)
$$
 for any $\psi \in (0, \infty)$.

This is our main focus in the paper. The idea is to take the derivative of $\bar{J}(\cdot;\tau^*)$ and investigate its monotonicity on $[0, \infty)$. We will see this later.

This paper's key result for the minimax sequential testing problem for Poisson processes, given by Theorem [4.1,](#page-9-1) is that there exists a φ_0 which is the least favorable distribution for the stopping time $\tau^*(\varphi_0)$. While we want to emphasize that $\varphi_0 = 1$ is not necessarily the least favorable distribution even if the performance functional is symmetric (i.e. $a = b$). This is to say the intuitive 1/2-1/2 rule for symmetric costs is not true in general. This will be justified by a numerical example in Section [5.](#page-9-0)

3 Sequential testing and some auxiliary results

In this section, we will recall the optimal stopping theory for sequential testing problem for the intensity of Poisson processes from [\[16\]](#page-11-0). Additionally, we will present some auxiliary results which are useful for our minimax sequential testing problem in the next section.

The following theorem characterizes the optimal stopping boundary which is a consequence Theorem 2.1 in [\[16\]](#page-11-0).

Theorem 3.1. *Suppose the priori distribution* ψ *is given.* (1) *If*

$$
\lambda_1 - \lambda_0 \le \frac{1}{a} + \frac{1}{b},
$$

the stopping time $\tau^* = 0$ *is optimal for the sequential testing problem in* [\(2.7\)](#page-3-2)*.*

$$
(2) \, \text{If}
$$

$$
\lambda_1 - \lambda_0 > \frac{1}{a} + \frac{1}{b},
$$

then the stopping time

$$
\tau^* = \inf \left\{ t \ge 0 : \psi L_t \notin (\alpha^*, \beta^*) \right\}
$$

is optimal for the sequential testing problem in [\(2.7\)](#page-3-2) <i>for some unique α^*, β^* *satisfying* $0 < \alpha^* <$ $b/a < \beta^*$.

In above theorem, the closed forms of α^* and β^* may not be obtainable, while they can be found through some numerical algorithms (see [\[16,](#page-11-0) [2\]](#page-11-1)). Therefore we will treat them as given constants in the sequel. Because Ψ_t is strictly decreasing between two jumps, the optimal lower stopping boundary α^* is probabilistic regular while the optimal upper stopping boundary β^* is not probabilistic regular (see Section 4.2 in [\[14\]](#page-11-15)), i.e. for $\tau = \inf\{t \geq 0 : L_t > \beta^*\}$, it follows that

$$
P_0(\tau > 0 | L_t = \beta^*) = 1 \neq 0.
$$

The probabilistic regularity is a critical property used in [\[5\]](#page-11-14) and thus we need to provide a different approach here.

Now define

$$
\tau^*(\varphi_0) := \inf \Big\{ t \geq 0 : \varphi_0 L_t \notin (\alpha^*, \beta^*) \Big\}.
$$

Note that L is decreasing between each jumps and L only jumps to a larger value at each jump time. At $t = \tau^*(\varphi_0)$, we have either $L_t = \alpha^*/\varphi_0$ or $L_t \geq \beta^*/\varphi_0$. We proceed with the following proposition.

Proposition 3.2. (1) *For any* $\varphi_0 \in (\alpha^*, \beta^*)$,

$$
\tau^*(\varphi) \to \tau^*(\varphi_0), \quad \mathsf{P}_0 \text{ - a.s. as } \varphi \to \varphi_0.
$$

(2) *It follows that*

$$
\tau^*(\varphi) \to 0, \quad \mathsf{P}_0 \text{ - a.s. as } \varphi \downarrow \alpha^*.
$$

(3) *It follows that*

$$
\lim_{\varphi \uparrow \beta^*} \tau^*(\varphi) = \inf \left\{ t \ge 0 : L_t \notin (\alpha^*/\beta^*, 1] \right\} =: \theta(\beta^*) \; \mathsf{P}_0\text{-}a.s..
$$

Proof. (1) Note that

$$
\tau^*(\varphi) := \inf \left\{ t \geq 0 : L_t \notin (\alpha^*/\varphi, \beta^*/\varphi) \right\}.
$$

Because L is left-continuous on stopping times a.s. and is right-continuous, we have

$$
\lim_{\varphi \downarrow \varphi_0} \tau^*(\varphi) = \inf \left\{ t \ge 0 : L_t \notin [\alpha^*/\varphi_0, \beta^*/\varphi_0) \right\},\
$$

$$
\lim_{\varphi \uparrow \varphi_0} \tau^*(\varphi) = \inf \left\{ t \ge 0 : L_t \notin (\alpha^*/\varphi_0, \beta^*/\varphi_0) \right\} =: \theta(\varphi_0).
$$

Because α^*/φ_0 is a probabilistic boundary for $[\alpha^*/\varphi_0, \beta^*/\varphi_0]$, it follows that $\lim_{\varphi\downarrow\varphi_0} \tau^*(\varphi)$ $\tau^*(\varphi_0)$. Note that $\tau(\varphi_0) \leq \theta(\varphi_0)$, it suffices to show that

(3.3)
$$
P_0(L_{\tau(\varphi_0)} = \beta^*/\varphi_0) = 0.
$$

Since L_t is strictly decreasing between each jumps and there are at most countable many jumps for each possible path of L, $\{L_t = \ell\}$ happens only for countable many t for any $\ell \geq 0$. Since $\beta^*/\varphi_0 > 1$, before $\theta(\varphi_0)$, the only possibility for L_t attaining β^*/φ_0 is that a jump happens exactly at the time when L_t hits $\beta^* \lambda_0/(\varphi_0 \lambda_1)$. As L_t hits $\beta^* \lambda_0/(\varphi_0 \lambda_1)$ at most countable many times on the whole time horizon $(0, \infty)$ and the probability that a jump happened at those stopping times are 0, this yields [\(3.3\)](#page-6-0). Therefore we have proved that

$$
\lim_{\varphi \to \varphi_0} \tau^*(\varphi) = \tau^*(\varphi_0) \; \mathsf{P}_0\text{-a.s.}.
$$

Π

It is evident that (2) and (3) are special cases of (1). The proof is complete.

Remark 3.3. We remark that the above results do not hold for $\varphi_0 = \beta^*$ because $\tau^*(\beta^*) = 0$ a.s. and $\lim_{\varphi \uparrow \beta^*} \tau^*(\varphi) > 0$ a.s. (we need wait for the first jump).

In order to work on the minimax sequential tetsing problem in the next section, we proceed with the following two differential equations:

(3.4)
$$
\begin{cases} (\lambda_0 - \lambda_1)\varphi f_0'(\varphi) + \lambda_0[f_0(\lambda_1\varphi/\lambda_0) - f_0(\varphi)] = 0 \text{ in } (\alpha^*/\beta^*, 1), \\ f_0(1) = 1; \quad f_0(\varphi) = 0, \text{ for } \varphi > 1. \end{cases}
$$

and

(3.5)
$$
\begin{cases} (\lambda_0 - \lambda_1)\varphi f_1'(\varphi) + \lambda_0[f_1(\lambda_1\varphi/\lambda_0) - f_1(\varphi)] + (\varphi - 1) = 0 \text{ in } (\alpha^*/\beta^*, 1), \\ f_1(1) = 0; \quad f_1(\varphi) = -b, \text{ for } \varphi > 1. \end{cases}
$$

Note that $\lambda_1 > \lambda_0 > 0$, it can be easily seen that the above two differential equations admit unique continuous solutions f_0 and f_1 on $\left[\alpha^*/\beta^*, 1\right]$. We also can conclude the monotonicity of f_0 and f_1 as follows.

Lemma 3.4. *The solutions* f_0 *and* f_1 *to* [\(3.4\)](#page-6-1) *and* [\(3.5\)](#page-6-2) *respectively are strictly decreasing on* $\lbrack \alpha^*/\beta^*,1 \rbrack$.

Proof. Note that $\lambda_1 > \lambda_0 > 0$. Suppose that φ_0 is the largest φ in $(\alpha^*/\beta^*, 1)$ such that $f'_0(\varphi_0) = 0$. This is to say that $f_0'(\varphi) < 0$ for any $\varphi \in (\varphi_0, 1)$ which says that f is strictly decreasing on $(\varphi_0, 1]$. In this case, $f'_{0}(\varphi_{0}) = 0$ leads to

$$
f_0(\lambda_1\varphi_0/\lambda_0) - f_0(\varphi_0) = 0,
$$

which is a contradiction. Therefore $f'(\varphi) < 0$ for all $\varphi \in (\alpha^*/\beta^*, 1)$. The proof for f_1 is same and thus omitted here. L

With above lemma, we define

(3.6)
$$
\gamma^* := \frac{a\alpha^*/\beta^* - f_1(\alpha^*/\beta^*)}{f_0(\alpha^*/\beta^*)}.
$$

Note that γ^* is well-defined because $f_0(\alpha^*/\beta^*) \ge f_0(1) = 1$. We proceed with the following lemma.

Lemma 3.5. *Recall*

$$
\theta(\beta^*) = \inf \left\{ t \ge 0 : L_t \notin (\alpha^*/\beta^*, 1] \right\} \text{ with } L_0 = 1.
$$

Then it follows that

$$
\gamma^* = \left(\frac{a\alpha^*}{\beta^*} + b\right) P_0(L_{\theta(\beta^*)} = \alpha^*/\beta^*) - b + \mathsf{E}_0 \int_0^{\theta(\beta^*)} (L_t - 1) dt.
$$

Proof. The proof is based on applying Itô's formula to

$$
t \mapsto \gamma^* f_0(L_t) + f_1(L_t).
$$

By Dynkin's formula, noting that $P_0(L_{\theta(\beta^*)} = 1) = 0$ (see [\(3.3\)](#page-6-0)), we have

$$
E_0 \int_0^{\theta(\beta^*)} (L_t - 1) dt = \gamma^* - E_0 \Big(\gamma^* f_0(L_{\theta(\beta^*)}) + f_1(L_{\theta(\beta^*)}) \Big)
$$

= $\gamma^* - [\gamma^* f_0(\alpha^*/\beta^*) + f_1(\alpha^*/\beta^*)] P_0(L_{\theta(\beta^*)} = \alpha^*/\beta^*) + b(1 - P_0(L_{\theta(\beta^*)} = \alpha^*/\beta^*))$
= $\gamma^* - (a\alpha^*/\beta^* + b) P_0(L_{\theta(\beta^*)} = \alpha^*/\beta^*) + b.$

The proof is complete.

4 Minimax sequential testing

In this section, we will solve the minimax sequential testing problem. Our goal is to characterize the least favorable distribution and prove its existence.

As proved in the previous section, $\tau^*(\varphi_0)$ is the optimal stopping time if the priori distribution is φ_0 . We aim to characterize the least favorable distribution φ_0 in the sense that

$$
\bar{J}(\psi; \tau^*(\varphi_0)) \leq \bar{J}(\varphi_0; \tau^*(\varphi_0))
$$
 for any $\psi > 0$.

From Theorem [3.1,](#page-4-2) we have two different cases.

(1) When [\(3.1\)](#page-4-3) holds, $\tau^*(\varphi_0) = 0$ is the optimal decision for any φ_0 . In this case, we have

(4.1)
$$
\bar{J}(\psi;0) = \frac{b \wedge (a\psi)}{1 + \psi}.
$$

Therefore the maximum point $\varphi_0 = b/a$ of $\bar{J}(\cdot; 0)$ is the unique least favorable distribution.

(2) Suppose [\(3.2\)](#page-5-0) holds. In this case we have

$$
\bar{J}(\psi;\tau^*(\varphi_0)) = \frac{1}{1+\psi} \mathsf{E}_{0}\Big[\int_0^{\tau^*(\varphi_0)} (1+\psi L_t)dt + b \wedge (a\psi L_{\tau^*(\varphi_0)})\Big].
$$

First we claim that the least favorable distribution φ_0 must fall in (α^*, β^*) . Suppose $\varphi_0 \notin$ (α^*, β^*) . Then we have $\tau^*(\varphi_0) = 0$ and $\bar{J}(\psi; 0)$ takes the same form as [\(4.1\)](#page-7-1) whose maximum point is $b/a \in (\alpha^*, \beta^*)$. Therefore φ_0 can not be a least favorable distribution.

Г

Then we only need to consider $\varphi_0 \in (\alpha^*, \beta^*)$. Our idea is to find the (left and right) derivatives of $\bar{J}(\cdot;\tau(\varphi_0)).$ Note that

$$
\lim_{\delta \to 0^+} \frac{1}{\delta} \Big[E_0 \Big(b \wedge (a(\psi + \delta) L_{\tau^*(\varphi_0)}) \Big) - E_0 \Big(b \wedge (a \psi L_{\tau^*(\varphi_0)}) \Big) \Big]
$$
\n
$$
= \lim_{\delta \to 0^+} \frac{1}{\delta} \Big[a \delta E_0 \Big(L_{\tau^*(\varphi_0)} I[L_{\tau^*(\varphi_0)} \le \frac{b}{a(\psi + \delta)}] \Big) + E_0 \Big((b - a \psi L_{\tau^*(\varphi_0)}) I[\frac{b}{a(\psi + \delta)} < L_{\tau^*(\varphi_0)} < \frac{b}{a \psi}] \Big) \Big]
$$
\n
$$
= a E_0 \Big(L_{\tau^*(\varphi_0)} I[L_{\tau^*(\varphi_0)} < \frac{b}{a \psi}] \Big).
$$

Taking the right derivative of $\bar{J}(\cdot;\tau(\varphi_0)),$ we have

$$
\frac{\partial^+ \bar{J}}{\partial \psi}(\psi; \tau^*(\varphi_0))
$$
\n
$$
= \frac{1}{(1+\psi)^2} \Big[a(1+\psi) \mathsf{E}_0 \Big(L_{\tau^*(\varphi_0)} I(\psi L_{\tau^*(\varphi_0)} < b/a) \Big) - \mathsf{E}_0 \Big(b \wedge (a\psi L_{\tau^*(\varphi_0)}) \Big) - \mathsf{E}_0 \int_0^{\tau^*(\varphi_0)} (1 - L_t) dt \Big]
$$
\n
$$
= \frac{1}{(1+\psi)^2} \Big[a \mathsf{E}_0 \Big(L_{\tau^*(\varphi_0)} I[\psi L_{\tau^*(\varphi_0)} < b/a] \Big) - b \mathsf{P}_0 (\psi L_{\tau^*(\varphi_0)} \ge b/a) - \mathsf{E}_0 \int_0^{\tau^*(\varphi_0)} (1 - L_t) dt \Big]
$$

Note that

$$
\lim_{\delta \to 0^+} \frac{1}{\delta} \Big[E_0[b \wedge (a\psi L_{\tau^*(\varphi_0)})] - E_0[b \wedge (a(\psi - \delta) L_{\tau^*(\varphi_0)})] \Big]
$$
\n
$$
= \lim_{\delta \to 0^+} \frac{1}{\delta} \Big[a\delta E_0 \Big(L_{\tau^*(\varphi_0)} I[L_{\tau^*(\varphi_0)} \le \frac{b}{a\psi}] \Big) + E_0 \Big((b - a\psi L_{\tau^*(\varphi_0)}) I[\frac{b}{a\psi} < L_{\tau^*(\varphi_0)} < \frac{b}{a(\psi - \delta)}] \Big) \Big]
$$
\n
$$
= aE_0 \Big(L_{\tau^*(\varphi_0)} I[L_{\tau^*(\varphi_0)} \le \frac{b}{a\psi}] \Big).
$$

Similarly, taking the left derivative with respect to ψ , we have

$$
\frac{\partial^{-} \bar{J}}{\partial \psi}(\psi; \tau^{*}(\varphi_{0})) = \frac{1}{(1+\psi)^{2}} \Big[a \mathsf{E}_{0} \Big(L_{\tau^{*}(\varphi_{0})} I(\psi L_{\tau^{*}(\varphi_{0})} \le b/a) \Big) - b \mathsf{P}_{0} (\psi L_{\tau^{*}(\varphi_{0})} > b/a) - \mathsf{E}_{0} \int_{0}^{\tau^{*}(\varphi_{0})} (1 - L_{t}) dt \Big].
$$

We notice that that the $\frac{\partial^{\pm} \bar{J}}{\partial \psi}(\cdot; \tau^*(\varphi_0))$ are decreasing on (α^*, β^*) and for $\varphi_0 \in (\alpha^*, \beta^*)$,

(4.2)
$$
P_0(\varphi_0 L_{\tau^*(\varphi_0)} = b/a) = 0 \text{ and } \varphi_0 L_{\tau^*(\varphi_0)} = \alpha^* \text{ on } {\varphi_0 L_{\tau^*(\varphi_0)} < b/a}.
$$

Therefore, $\bar{J}(\cdot; \tau^*(\varphi_0))$ takes a maximum at φ_0 if and only if

$$
h(\varphi_0) := \left(\frac{a\alpha^*}{\varphi_0} + b\right) P_0(\varphi_0 L_{\tau^*(\varphi_0)} < b/a) - b + \mathsf{E}_0 \int_0^{\tau^*(\varphi_0)} (L_t - 1) dt = 0.
$$

By Proposition [3.2](#page-5-1) and [\(4.2\)](#page-8-0), invoking dominant convergence, we know $h(\cdot)$ is continuous with respect to $\varphi_0 \in [\alpha^*, \beta^*)$ with

$$
h(\alpha^*) = a > 0.
$$

Note that $\tau^*(\varphi_0) \to \theta(\beta^*)$ as $\varphi_0 \uparrow \beta^*$. By the definition of γ^* and [\(4.2\)](#page-8-0), it also follows that

(4.3)
$$
h(\beta^{*-}) = \left(\frac{a\alpha^{*}}{\beta^{*}} + b\right) P_{0}(\beta^{*} L_{\theta(\beta^{*})} < b/a) - b + \mathsf{E}_{0} \int_{0}^{\theta(\beta^{*})} (L_{t} - 1) dt = \gamma^{*}.
$$

By the mean-value theorem, all above calculations yield the main results for the minimax sequential testing problem as follows.

Theorem 4.1. (1) If $\lambda_1 - \lambda_0 \leq 1/a + 1/b$, the stopping time $\tau^* = 0$ is the optimal stopping *time for the minimax sequential testing problem in* [\(2.8\)](#page-4-1) where $\varphi_0 = b/a$ *is the least favorable distribution.*

(2) If $\lambda_1 - \lambda_0 > 1/a + 1/b$, the stopping time $\tau^*(\varphi_0)$ is the optimal stopping time for the minimax *sequential testing problem in* [\(2.8\)](#page-4-1) *if and only if* $h(\varphi_0) = 0$. *Moreover, if* $\gamma^* < 0$ *, there exists at least one least favorable distribution* $\varphi_0 \in (\alpha^*, \beta^*).$

Finally, let us conclude the section with a numerical algorithm to find the least favorable distribution φ_0 if $\lambda_1 - \lambda_0 > 1/a + 1/b$. (1) We find the optimal stopping boundary α^* and β^* numerically. (2) We find γ^* from a Monte-Carlo method. (3) If γ^* < 0, we can proceed a bisection search for the zero-point of h on (α^*, β^*) which is a least favorable distribution.

5 Example

In this section, we present a concrete example to illustrate our theory. The example is also used in [\[16\]](#page-11-0) (see Figure 2 there). Suppose

$$
\lambda_0 = 1, \lambda_1 = 5, a = b = 2.
$$

In such case $\lambda_1 - \lambda_0 > 1/a + 1/b$, and we have

$$
L_t = \exp\Big\{ (X_t - X_0) \log 5 - 4t \Big\}.
$$

The observed process X_t has intensity $\lambda_0 = 1$ under P_0 . The numerical method yields that

$$
\alpha^* \thickapprox 0.297, \ \ \beta^* \thickapprox 2.390, \ \ \frac{\alpha^*}{\beta^*} \thickapprox 0.124.
$$

Through a Monte-Carlo method, we find that $\gamma^* = -0.788 < 0$. This concludes the existence of a least favorable distribution φ_0 . A bisection search yields that the least favorable distribution $\varphi_0 = 0.977$. Therefore, the optimal stopping time for **MinimaxST** is

$$
\tau^* = \left\{ t \ge 0 : L_t \notin (0.304, 2.440) \right\}.
$$

Moreover, we find that $h(1) = -0.03 \neq 0$. Therefore the minimax sequential testing problem is not symmetric even if $a = b$.

6 Concluding remarks

In this paper, we solved the minimax sequential testing problem for the intensity of a Poisson process. We find an equivalent characterization of the least favorable distribution and present a sufficient condition for its existence. Moreover, a numerical algorithm is proposed for the least favorable distribution. For further study on minimax sequential testing problems of continuoustime models, we would like to consider the minimax sequential problems for more general processes such as compound Poisson processes and Lévy processes.

References

- [1] Buonaguidi, B., & Muliere, P. (2016). Bayesian sequential testing for L´evy processes with diffusion and jump components. *Stochastics*, 88(7), 1099-1113.
- [2] Dayanik, S., & Sezer, S. O. (2006). Sequential testing of simple hypotheses about compound Poisson processes. *Stochastic processes and their applications*, 116(12), 1892-1919.
- [3] Dayanik, S., Poor, H. V., & Sezer, S. O. (2008). Sequential multi-hypothesis testing for compound Poisson processes. *Stochastics: An International Journal of Probability and Stochastic Processes*, 80(1), 19-50.
- [4] Ernst, P. A., Peskir, G., & Zhou, Q. (2020). Optimal real-time detection of a drifting Brownian coordinate. *The Annals of Applied Probability*, 30(3), 1032–1065.
- [5] Ernst, P. A. & Mei, H., The Minimax Wiener Sequential Testing Problem.
- [6] Fauss, M., & Zoubir, A. M. (2016). Old bands, new tracks—Revisiting the band model for robust hypothesis testing. *IEEE Transactions on Signal Processing*, 64(22), 5875-5886.
- [7] Fauss, M., Zoubir, A. M., & Poor, H. V. (2020). Minimax optimal sequential hypothesis tests for Markov processes. *The Annals of Statistics*, 48(5), 2599-2621.
- [8] Fauss, M., Zoubir, A. M., & Poor, H. V. (2021). Minimax robust detection: Classic results and recent advances. *IEEE Transactions on Signal Processing*, 69, 2252-2283.
- [9] Gapeev, P. V., & Peskir, G. (2004). The Wiener sequential testing problem with finite horizon. *Stochastics and stochastic reports*, 76(1), 59–75.
- [10] Gapeev, P. V., & Shiryaev, A. N. (2011). On the sequential testing problem for some diffusion processes. *Stochastics: An International Journal of Probability and Stochastic Processes*, 83(4-6), 519–535.
- [11] Huber, P. J. (1965). A robust version of the probability ratio test. *The Annals of Mathematical Statistics*, 1753-1758.
- [12] Johnson, P. & Peskir, G. (2018). Sequential testing problems for Bessel processes. *Transactions of the American Mathematical Society*, 370(3), 2085–2113.
- [13] Johnson, P., Pedersen, J. L., Peskir, G., & Zucca, C. (2022). Detecting the presence of a random drift in Brownian motion. *Stochastic Processes and their Applications*, 150, 1068–1090.
- [14] Karatzas, I., & Shreve, S. E. (1998). *Brownian motion. In Brownian Motion and Stochastic Calculus* (pp. 47-127). Springer, New York, NY.
- [15] Lehmann, E.L. (1959) *Testing Statistical Hypotheses*. John Wiley & Sons.
- [16] Peskir, G., & Shiryaev, A. N. (2000). Sequential testing problems for Poisson processes. *Annals of Statistics*, 837-859.
- [17] Wald, A. *Sequential Analysis.* Wiley, Hoboken, NJ, USA, 1947.