

Assessing the reliability of multistate flow networks considering distance constraints

Majid Forghani-elahabad^a

^a*Center of Mathematics, Computing, and Cognition, Federal University of ABC, Santo André, 09280-550, SP, Brazil*

Abstract

Evaluating the reliability of complex technical networks, such as those in energy distribution, logistics, and transportation systems, is of paramount importance. These networks are often represented as multistate flow networks (MFNs). While there has been considerable research on assessing MFN reliability, many studies still need to pay more attention to a critical factor: transmission distance constraints. These constraints are typical in real-world applications, such as Internet infrastructure, where controlling the distances between data centers, network nodes, and end-users is vital for ensuring low latency and efficient data transmission. This paper addresses the evaluation of MFN reliability under distance constraints. Specifically, it focuses on determining the probability that a minimum of d flow units can be transmitted successfully from a source node to a sink node, using only paths with lengths not exceeding a predefined distance limit of λ . We introduce an effective algorithm to tackle this challenge, provide a benchmark example to illustrate its application and analyze its computational complexity.

Keywords: Multistate flow networks, Network reliability, Distance limitation, Minimal paths, Algorithms

1. Introduction

Stochastic or multistate flow network flow networks (MFNs) in which the arcs and maybe the nodes, and accordingly the entire network, can have more than two states have been desirable in the past decades due to their ability to model many real-world systems such as communication and telecommunication, logistic and transportation, power transmission and distribution,

manufacturing systems and so forth [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 7, 15, 16]. For instance, in a manufacturing supply chain, nodes can represent suppliers or sources of raw materials, production or manufacturing facilities, distribution centers, warehouses, storage facilities, and markets or destinations. The arcs can represent the connections from suppliers to production facilities, from facilities to distribution centers or warehouses, and from distribution centers to customers or markets. In such a network, each node and arc can exist in various states. For instance, node states can vary depending on the availability of resources, production rate, machine reliability, etc. Arc states can vary due to factors such as road conditions, transformer availability, and their capacities.

Reliability indices are of great importance in evaluating the performance and quality of service of real-world systems, among which the s - t terminal network reliability has been desirable in MFNs in recent decades. The basic definition of this index, denoted normally by R_d , is the probability of successfully transmitting a minimum of a given d units of goods, commodities, or data from a source node to a destination node through the network. Engineers and designers can make informed decisions on network design, maintenance, and operation by accurately assessing the R_d to ensure reliable and efficient performance. Many exact and approximation algorithms have been proposed in the literature based on minimal paths (MPs) [5, 8, 15, 17, 18, 19, 20, 21, 22, 23, 24] or minimal cuts [11, 13, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34] to compute R_d . Chen et al. [35] employed the breadth-first search technique to introduce an enhanced MP-based algorithm that avoids generating duplicate solution vectors. Niu et al. [17] established a connection between reliability assessment and circulation problems, resulting in an efficient algorithm capable of solving feasible circulations for flow network reliability evaluation. The authors in [36] introduced a novel direct decomposition algorithm for assessing network reliability without the prerequisite of having MPs or MCs in advance. In [23], the authors delved into MP-based techniques and harnessed vectorization strategies to enhance the solution's performance. The authors then improved their algorithm by employing parallelization techniques and providing an efficient technique to avoid generating duplicate solutions [5]. Yeh [19] presented an innovative method for determining d -MPs, using a cycle-checking approach to validate each candidate. Bai et al. [37] explored the simultaneous determination of d -MPs for all possible demand levels d , proposing a recursive technique. Niu et al. [38] tackled the issue by providing lower bounds on arc capacities and introducing a novel technique to

identify duplicate solutions, thus presenting an efficient MC-based algorithm for problem-solving. The authors in [39] reviewed several available results in the literature and showed that some results need to be revised in some cases. They then proposed an efficient MC-based algorithm for the reliability evaluation of MFNs that uses an improved approach for detecting duplicate solutions. The authors improved this algorithm in [11]. Huang et al. [33] proposed a novel algorithm for the reliability evaluation of MFNs using a group approach that combines concepts from both MC and MP techniques.

To enhance the practicality of the problem, several researchers have explored the integration of cost (budget) constraints into the reliability assessment of MFNs [4, 8, 13, 24, 31, 40]. Niu and Xu [40] contributed by proposing an enhanced algorithm for MFN reliability evaluation under cost constraints, incorporating a cycle-checking technique into their approach. Considering budget constraints, Forghani-elahabad and Kagan [8] introduced an improved algorithm for MFN reliability assessment. Furthermore, they outlined how this algorithm could be effectively employed for evaluating the reliability of communication networks within smart grids. In a real-world application, [31] modeled a manufacturing system, incorporating unreliable and multistate nodes and arcs with cost attributes. They presented an MP-based algorithm to assess the system’s reliability while considering budget constraints. In [24], the author conducted a comprehensive review of MP- and MC-based approaches in the literature for calculating reliability under budget and maintenance cost constraints. Moreover, some researchers have considered the time limitation on the flow transmission on a path resulting in the quickest path reliability problem and its extensions [34, 41, 42, 43, 44, 45].

In addition to time and cost considerations, the limitation on transmission distance plays a pivotal role in shaping the performance of an MFN. The distance between nodes within the network can exert a significant influence on the flow of goods and commodities, subsequently impacting the network’s overall efficiency and reliability [46, 47]. To illustrate, let us consider a transportation network scenario where a delivery truck must cover extensive distances to reach its destination. As the distance increases, the likelihood of delays or breakdowns escalates, leading to a heightened risk of system failure and a decrease in the transportation network’s performance. Thus, optimizing transmission distances stands as a crucial imperative in the design and management of MFNs across various real-world applications, encompassing transportation, communication, and distribution networks.

While the distance limitation is essential in several real-world systems

such as Internet infrastructure, a few researchers have considered and studied this constraint in the reliability evaluation of MFNs [47]. However, many researchers have investigated this issue in assessing the reliability of binary-state flow networks [46, 48, 49, 50]. In a binary-state network, the components, including nodes and arcs, and consequently the entire network, exhibit just two states. These two states often signify a binary choice, such as whether the component is open or closed [29, 46, 51]. The authors in [46] proposed an innovative algorithm aimed at identifying and eliminating irrelevant arcs in the process of evaluating the reliability of a binary-state flow network when subjected to distance constraints. Studying the distance limitation in MFNs, the authors in [47] have introduced the concept of irrelevant arcs in such networks and presented a strategy to remove them. Then, the authors proposed an approximation algorithm to evaluate the network reliability under distance constraints.

Expanding upon the foundational concept of MFN reliability, we define $R_{(d,\lambda)}$ as the reliability of an MFN with a demand level of d while subject to a distance constraint of λ . This reliability measure quantifies the likelihood of successfully transmitting a minimum of d flow units from a source node to a target destination node, considering only the MPs with lengths not exceeding λ . A commonality in research on both binary-state flow networks MFNs is the identification of irrelevant arcs, defined as arcs that do not contribute to flow transmission due to distance constraints. Researchers have typically offered methods to detect and eliminate these irrelevant arcs, subsequently assessing the network’s reliability post-removal. However, it is essential to acknowledge that these strategies often come with technical challenges in defining irrelevant arcs and the associated detection methods, not to mention their computationally expensive nature. In this work, we introduce the notion of irrelevant MPs and propose an alternative approach that eliminates the need to identify or remove irrelevant arcs. Instead, our method directly sets the flow on irrelevant MPs to zero to satisfy the distance limitation. We demonstrate the correctness of our method through several results, compute its complexity results, and illustrate it through a known benchmark example.

We consider the following assumptions throughout this work.

1. Each node is considered deterministic and exhibits perfect reliability.
2. The capacity of each arc follows a random integer value distribution based on a predefined probability function.
3. The capacities of individual arcs are statistically independent from one

another.

4. The network adheres to the flow conservation law [52].
5. All minimal paths are predetermined and provided in advance.
6. Every arc within the network is part of at least one minimal path connecting node 1 to node n .

The remainder of this paper is structured as follows. Section 2 introduces the necessary notations and terminology and lays out the foundational concepts for the problem's formulation. Section 3 offers the primary findings and outlines an effective algorithm to tackle the problem. An illustrative example and the complexity results are given in Section 4. We conclude the work with the final remarks in Section 5.

2. Network modeling and problem formulation

2.1. Notations and nomenclature

Let us consider a multistate flow network (MFN), represented as $G(N, A, M, L)$. Here, $N = \{1, 2, \dots, n\}$ signifies the collection of nodes and $A = \{a_1, a_2, \dots, a_m\}$ represents the ensemble of arcs within the network. The vector $M = (M_1, M_2, \dots, M_m)$ encompasses the maximum arcs' capacities, where M_i denotes the utmost capacity of arc a_i , applicable to all $i = 1, 2, \dots, m$. Correspondingly, the vector $L = (l_1, l_2, \dots, l_m)$ serves as the length vector, with l_i denoting the length of arc a_i , spanning $i = 1, 2, \dots, m$. Notably, n and m denote the total number of nodes and arcs within the network, while nodes 1 and n are expressly designated as the source and sink nodes, respectively. For instance, as depicted in Fig. 1, the network comprises the set of nodes $N = \{1, 2, 3, 4, 5\}$ and the set of arcs $A = \{a_1, \dots, a_8\}$. One can consider $M = (3, 2, 2, 1, 2, 1, 3, 2)$ and $L = (1, 2, 1, 3, 2, 1, 2, 1)$ respectively as the capacity and length vectors for this network. This way, for instance, $M_5 = 2$ and $l_5 = 2$ signify respectively the maximum capacity and the length of arc a_5 .

Consider a current system state vector (SSV) denoted as $X = (x_1, x_2, \dots, x_m)$, where each component x_i is a random integer ranging from 0 to M_i , representing the current capacity of arc a_i . For example, in the context of Fig. 1, an SSV like $X = (2, 2, 0, 0, 1, 0, 2, 0)$ is valid, adhering to the constraint $0 \leq X \leq M$. A path is defined as a sequence of adjacent arcs that connect node 1 to node n , while a minimal path (MP) is a path that does not contain any cycles. For instance, $P = a_1, a_4, a_6, a_7$ represents an

MP in Fig. 1. Let us denote all the MPs in the network as P_1, P_2, \dots, P_p , so p is the total number of MPs. For each P_j , let LP_j represent its length and $CP_j(X)$ denote its capacity under the SSV, X , for $j = 1, 2, \dots, p$. Hence, one notes that the maximum capacity of P_j within the network $G(N, A, M, L)$ is $CP_j(M)$. The length of P_j and its capacity under X are computed as follows.

$$LP_j = \sum_{i: a_i \in P_j} l_i \quad \& \quad CP_j(X) = \min\{x_i | a_i \in P_j\} \quad (1)$$

For instance, we have $LP_1 = l_1 + l_4 + l_6 + l_7 = 1 + 3 + 1 + 2 = 7$ and $CP_1(M) = \min\{M_1, M_4, M_6, M_7\} = \min\{3, 1, 1, 3\}$ for the network given in Fig. 1 with $M = (3, 2, 2, 1, 2, 1, 3, 2)$ and $L = (1, 2, 1, 3, 2, 1, 2, 1)$. Let $e_i = (0, \dots, 0, 1, 0, \dots, 0)$ be an SSV in which the capacity level is 1 for a_i and 0 for the other arcs. Let also d be a non-negative integer number that represents the required flow to be transmitted from node 1 to node n through the network, and λ be a given transmission distance limit. Assume that Finally, let $V(X)$ be the maximum flow of the network from node 1 to node n , and $e_i = (0, \dots, 0, 1, 0, \dots, 0)$ be an SSV in which the capacity level is 1 for a_i and 0 for the other arcs. For instance, for the network of Fig. 1 and $X = (2, 2, 0, 0, 1, 0, 2, 0)$, we have $V(X) = 3$ and $V(X - e_2) = 1$.




Figure 1: A benchmark network example taken from [20].

For any pair of system state vectors (SSVs), denoted as $X = (x_1, x_2, \dots, x_m)$ and $Y = (y_1, y_2, \dots, y_m)$, we define X as less than or equal to Y , represented by $X \leq Y$, when $x_i \leq y_i$ holds for each $i = 1, 2, \dots, m$. Additionally, we state that X is strictly less than Y , indicated by $X < Y$, when $X \leq Y$ and there exists at least one index $j = 1, 2, \dots, m$ for which $x_j < y_j$. A vector $X \in \Psi$ earns the label of “minimal” if there is no other vector $Y \in \Psi$ such that $Y < X$. It is important to note that for a vector X to be considered minimal within Ψ , X does not need to be less than or equal to every other vector; instead, the crucial criterion is that no other vector in Ψ is less than X .

2.2. Preliminaries

Supposing that d units of flow are transmitting from node 1 to node n through the network, one notes that these flow should be divided among all the MPS P_1, P_2, \dots, P_p . Letting f_j denote the amount of flow being transmitted through P_j , we have a vector $F = (f_1, f_2, \dots, f_p)$ which is called the feasible flow vector (FFV) at transmitting d units of flow and denoted by d -FFV. Let us begin with the case with no distance limitations. To compute the reliability of an MFN in such a case, the concept of d -MP has been defined as follows in the literature [8, 15, 17, 20, 53, 54].

Definition 1. A system state vector X is a d -MP if and only if $V(X) = d$ and $V(X - e_i) = d - 1$ for every i with $x_i > 0$.

Lemma 1. Assume that $\Psi(G, d) = \{X \mid 0 \leq X \leq M \ \& \ V(X) \geq d\}$ and $\Psi_{\min}(G, d)$ is the set of all the minimal vectors in $\Psi(G, d)$. Then, X is a d -MP if and only if $X \in \Psi_{\min}(G, d)$.

Proof. If X is a d -MP, then $V(X) = d$. On the other hand, for every $Y < X$, there exists an index $1 \leq i \leq m$ such that $Y \leq X - e_i < X$, and hence $V(Y) \leq V(X - e_i) = d - 1 < d$. Accordingly, $Y \notin \Psi(G, d)$ signifying that X is a minimal vector in $\Psi(G, d)$. Now, let $X \in \Psi_{\min}(G, d)$. If $V(X) > d$, then there exists an index $1 \leq i \leq m$ such that $V(X - e_i) \geq d$ which contradicts X being a minimal vector in $\Psi(G, d)$. Thus, $V(X) = d$. Similarly, one can show that $V(X - e_i) < d$ for every i with $x_i > 0$, and thus X is a d -MP. \square

As a result, if one finds all the d -MPs, say $\Psi_{\min}(G, d) = \{X^1, \dots, X^\sigma\}$, and let $S_i = \{X \mid X^i \leq X \leq M\}$, then it is easy to see that $\Psi(G, d) = \cup_{i=1}^\sigma S_i$, and therefore the network reliability for the case with no distance limitations, denoted by R_d , can be computed by calculating a union probability. Hence, the determination of all the d -MPs turns out to be an essential stage of indirect reliability evaluation approaches.

Many algorithms in the literature have used the following results to search for all the d -MPs in an MFN [2, 8, 15, 17, 19, 20, 24, 45, 55].

Theorem 1. If $X = (x_1, \dots, x_m)$ is a d -MP, then there exists a d -FFV, say $F = (f_1, \dots, f_p)$, that satisfies the following systems.

$$\begin{cases} (i) & f_1 + f_2 + \dots + f_p = d, \\ (ii) & 0 \leq f_j \leq \min\{CP_j(M), d\}, \quad j = 1, 2, \dots, p, \\ (iii) & \sum_{j: a_i \in P_j} f_j \leq M_i, \quad i = 1, 2, \dots, m, \\ (iv) & x_i = \sum_{j: a_i \in P_j} f_j, \quad i = 1, 2, \dots, m. \end{cases} \quad (2)$$

It is essential to recognize that while any d -MP, say X , corresponds to a d -FFV, say F , satisfying the system (2), the reverse may not hold. In other words, not every X obtained by solving the system above is necessarily a d -MP. Therefore, the available algorithms in the literature first find all the solutions of this system and then check each solution for being a d -MP [2, 8, 15, 17, 19, 20, 24, 45, 53, 55]. One of the most efficient techniques to check each solution of the system (2) to be a d -MP is the following lemma, which was presented in [19] and improved in [15].

Lemma 2. *A solution X of the system (2) is a d -MP if and only if no directed cycle exists in the network G under X .*

Extending these results to the case with distance limitations and presenting the concept of *irrelevant* MPs, we propose an efficient algorithm to compute the system reliability of an MFN under the distance limit.

3. Searching for all the (d, λ) -MPs

Definition 2. *The transmission distance for transferring d units of flow from node 1 to node n within the network G is defined as the length of the longest MP through which at least one flow unit is being transmitted.*

One notes that there may exist different ways to transmit d units of flow from node 1 to node n through the network. However, once we are given the corresponding d -FFV, we know exactly how many flow units are being sent through each MP. To illustrate it, consider the network given in Fig. 2 with $M = (4, 3, 4, 5, 3, 4)$ and $L = (2, 1, 3, 2, 1, 2)$. It is easy to see that the maximum flow of the network from node 1 to node 4 is $V(M) = 9$ and that there are five MPs in the network; $P_1 = a_1, a_4, a_6$, $P_2 = a_1, a_5$, $P_3 = a_2, a_4, a_5$, $P_4 = a_2, a_6$, and $P_5 = a_3$. Now, to send four flow units from node 1 to node 4, we have 67 different scenarios, including $F_1 = (0, 0, 0, 0, 4)$, $F_2 = (0, 3, 0, 1, 0)$, and $F_3 = (4, 0, 0, 0, 0)$. The associated transmission distance with F_1, F_2 , and F_3 are respectively one, two, and three. Therefore, it is the corresponding d -FFV that determines the transmission distance. Therefore, we denote this parameter by $\Delta(G, d, F)$.

Proposition 1. *Assume that d units of flow is transmitting from node 1 to node n within the network G and that $F = (f_1, f_2, \dots, f_p)$ is its corresponding d -FFV. The transmission distance is equal to*

$$\Delta(G, d, F) = \max\{LP_j \mid f_j > 0, j = 1, 2, \dots, p\} \quad (3)$$




Figure 2: A simple benchmark example.

Proof. It is concluded directly from the definition. □

Definition 3. A system state vector X is a (d, λ) -MP candidate when there exists a d -FFV, say F , satisfying the system (2) and $\Delta(G, d, F) \leq \lambda$.

Definition 4. A (d, λ) -MP candidate, say X , is a (real) (d, λ) -MP if $V(X) = d$ and $V(X - e_i) < d$ for every i with $x_i > 0$.

Lemma 3. A (d, λ) -MP candidate is a (real) (d, λ) -MP if no directed cycle exists in the network under it.

Proof. It can be concluded directly from the above definitions and Lemma 2. □

As explained earlier, even for a small benchmark network, there are numerous scenarios to transmit a given flow of magnitude d . It is important to note that the transmission distance varies depending on the specific d -FFV being considered, each representing a unique scenario. Consequently, the task of finding all possible d -FFV and their corresponding SSVs by solving the system (2), subsequently verifying them for distance limitations and ensuring their status as (real) (d, λ) -MP, becomes a highly time-consuming endeavor. To simplify this complexity, Zhang and Shao [47] introduced the concept of irrelevant arcs in the context of MFNs. They classified these irrelevant arcs into two cases: (1) arcs not belonging to any MP and (2) arcs exclusive to MPs with lengths exceeding λ , which signifies the distance constraint. Subsequently, they proposed an approach to detect and eliminate these irrelevant arcs from the network. However, it is noteworthy to highlight that verifying all the MPs to identify every irrelevant arc is also a time-consuming process.

In light of Proposition 1, it becomes evident that the transmission distance depends on the specific d -FFV and is determined via the lengths of MPs. Therefore, if one were to nullify the components of $F = (f_1, \dots, f_p)$

associated with MPs of lengths exceeding λ , the distance constraint would unquestionably be met by all computed d -FFV. With this in mind, we introduce a novel concept: the *irrelevant MP* (IMP), as defined below.

Definition 5. *An MP is deemed irrelevant if its length exceeds the specified distance limitation. In other words, P_j is classified as irrelevant when $LP_j = \sum_{i: a_i \in P_j} l_i > \lambda$.*

Therefore, one can first solve the following system instead of the system (2) to calculate all the d -FFVs that satisfy the distance limitation.

$$\begin{cases} (i) f_j = 0, & \text{if } LP_j > \lambda \\ (ii) f_1 + f_2 + \dots + f_p = d, \\ (iii) 0 \leq f_j \leq \min\{CP_j(M), d\}, & j = 1, 2, \dots, p, \\ (iv) \sum_{j: a_i \in P_j} f_j \leq M_i, & i = 1, 2, \dots, m. \end{cases} \quad (4)$$

Then, the corresponding SSV to every calculated d -FFV can be computed as follows.

$$x_i = \sum_{j: a_i \in P_j} f_j, \quad \forall i = 1, 2, \dots, m. \quad (5)$$

3.1. The proposed algorithm

Now, we are ready to propose an efficient algorithm to address the problem of calculating all the (d, λ) -MPs in an MFN.

Algorithm 1

Input: $G(N, A, M, L)$, its MPs, the demand level of d , and the distance limitation of λ .

Output: All the (d, λ) -MPs.

Step 0. Calculate $LP_j = \sum_{i: a_i \in P_j} l_i$, for $j = 1, 2, \dots, p$, and compute $KP_j(M)$ only for the MPs with $LP_j \leq \lambda$. Let $S = \phi$.

Step 1. Find a solution F by solving the system (4). If no more solutions are found, stop.

Step 2. Calculate corresponding X to F via Eq. (5).

Step 3. If there is a directed cycle in G under X , then go to Step 1 to find the next solution.

Step 4. If X is not duplicated, add it to S .

We should emphasize that steps 1 and 2 of the algorithm build upon the preceding discussion, while Step 3 relies on Lemma 3. Furthermore, since it is feasible to generate the same SSV corresponding to various d -FFVs, Step 4 of the algorithm eliminates duplicates. Consequently, we can formulate the following theorem.

Theorem 2. *Algorithm 1 calculates all the (d, λ) -MPs with no duplicates.*

4. An illustrative example and the complexity results

4.1. An illustrative example

A helpful method for gaining a deeper understanding of a novel approach is to examine its application through a simple benchmark network example.

Example 1. *Consider the depicted network in Fig. 1 with five nodes and eight arcs. Assume that the maximum capacity vector and the length vector are given respectively $M = (3, 2, 2, 1, 2, 1, 3, 2)$ and $L = (1, 2, 1, 3, 2, 1, 2, 1)$. One needs to compute the reliability of this network for transmitting six units of flow from node 1 to node 5 with a transmission distance of not more than six. To solve this example, we need to find all the $(6, 6)$ -MP, for which Algorithm 1 is utilized as follows.*

Solution: The demand level and distance limitation are respectively $d = 6$ and $\lambda = 6$. We have nine MPs in this network: $P_1 = \{a_1, a_5\}$, $P_2 = \{a_2, a_7\}$, $P_3 = \{a_3, a_8\}$, $P_4 = \{a_1, a_4, a_8\}$, $P_5 = \{a_2, a_6, a_2\}$, $P_6 = \{a_3, a_4, a_5\}$, $P_7 = \{a_3, a_6, a_7\}$, $P_8 = \{a_1, a_4, a_6, a_7\}$, and $P_9 = \{a_2, a_6, a_4, a_5\}$.

Step 0. *The MPs' lengths are calculated as follows. $LP_1 = 3$, $LP_2 = 4$, $LP_3 = 2$, $LP_4 = 5$, $LP_5 = 4$, $LP_6 = 6$, $LP_7 = 4$, $LP_8 = 7$, and $LP_9 = 8$. The capacities of only the MPs with their length less than λ are calculated as $KP_1(M) = 5$, $KP_2(M) = 5$, $KP_3(M) = 4$, $KP_4(M) = 6$, $KP_5(M) = 5$, $KP_6(M) = 5$, and $KP_7(M) = 6$.*

Step 1. *The system (4) has six solutions: $(2, 2, 0, 1, 0, 0, 1, 0, 0)$, $(1, 2, 1, 1, 0, 0, 1, 0, 0)$, $(2, 2, 1, 0, 0, 0, 1, 0, 0)$, $(2, 1, 1, 1, 0, 0, 1, 0, 0)$, $(2, 2, 2, 0, 0, 0, 0, 0, 0)$, and $(2, 2, 1, 1, 0, 0, 0, 0, 0)$.*

Step 2. *The corresponding SSVs to the calculated solutions in Step 2 are respectively: $(3, 2, 1, 1, 2, 1, 3, 1)$, $(2, 2, 2, 1, 1, 1, 3, 2)$, $(2, 2, 2, 0, 2, 1, 3, 1)$, $(3, 1, 2, 1, 2, 1, 2, 2)$, $(2, 2, 2, 0, 2, 0, 2, 2)$, and $(3, 2, 1, 1, 2, 0, 2, 2)$.*

Step 3. All the obtained SSVs meet the verification criteria, confirming that each is a $(6, 6)$ -MP.

Step 4. There are no duplicates, meaning that the solution set includes all the computed vectors in Step 2.

4.2. Complexity results

We first recall that m , n , and p are respectively the number of arcs, nodes, and MPs in the network. The time complexity of calculating the length or capacity of each MP is $O(m)$, and accordingly, Step 0 is of the order of $O(mp)$. System (4) can be considered one constrained Diophantine equation and thus can be solved by the proposed approach of [56]. Hence, the time complexity for calculating each solution in the worst case, and thus the time complexity of Step 1 is $O(p)$. The time complexity of Step 2 is $O(mp)$. The time complexity of Step 3 is $O(n)$ [19]. We use the proposed approach of [5], and thus, the time complexity of removing the duplicates in Step 4 is $O(m\sigma)$, where σ is the number of obtained solutions including the duplicates. It is noteworthy that steps 0 and 4 are executed in parallel with other steps and that steps 1 to 3 are executed σ times in the worst case. Therefore, the time complexity of Algorithm 1 is $O(mp + \sigma(p + mp + n) + m\sigma) = O(mp\sigma)$, and we can formulate the following theorem.

Theorem 3. *The time complexity of Algorithm 1 is $O(mp\sigma)$.*

5. Conclusion

While distance limitations have been a subject of extensive research when it comes to evaluating the reliability of binary-state flow networks, this crucial aspect has received less attention in the context of multistate flow networks (MFNs). Given the significance of distance constraints in real-world systems like Internet infrastructure, this study dived into the problem of assessing the reliability of MFNs under these constraints. In this work, we introduced the concept of irrelevant minimal paths (MPs). We presented an algorithm that sets the flow to zero on all relevant MPs to calculate all the (d, λ) -MPs in an MFN. We also outlined how the network's reliability can be calculated using these (d, λ) -MPs. To validate the proposed approach, we demonstrated its correctness and provided an illustration through a well-known benchmark example. Additionally, we offered insights into the computational complexity of the algorithm.

Acknowledgments

The author thanks CNPq (grant 306940/2020-5) for supporting this work.

References

- [1] Z. Hao, W. C. Yeh, Z. Liu, M. Forghani-elahabad, General multi-state rework network and reliability algorithm, *Reliability Engineering & System Safety* 203 (2020) 107048.
- [2] C. C. Jane, Y.-W. Laih, Distribution and reliability evaluation of maxflow in dynamic multi-state flow networks, *European Journal of Operational Research* 259 (3) (2017) 1045–1053.
- [3] M. Forghani-elahabad, W. C. Yeh, An improved algorithm for reliability evaluation of flow networks, *Reliability Engineering & System Safety* 221 (2022) 108371.
- [4] Y. F. Niu, X.-Z. Xu, C. He, D. Ding, Z.-Z. Liu, Capacity reliability calculation and sensitivity analysis for a stochastic transport network, *IEEE Access* 8 (2020) 133161–133169.
- [5] M. Forghani-elahabad, E. Franceschini, Usage of task and data parallelism for finding the lower boundary vectors in a stochastic-flow network, *Reliability Engineering & System Safety* (2023) 109417.
- [6] B. Xu, T. Liu, G. Bai, J. Tao, Y. Zhang, Y. Fang, A multistate network approach for reliability evaluation of unmanned swarms by considering information exchange capacity, *Reliability Engineering & System Safety* 219 (2022) 108221.
- [7] W. C. Yeh, Z. Hao, M. Forghani-elahabad, G.-G. Wang, Y.-L. Lin, Novel binary-addition tree algorithm for reliability evaluation of acyclic multistate information networks, *Reliability Engineering & System Safety* 210 (2021) 107427.
- [8] M. Forghani-elahabad, N. Kagan, Reliability evaluation of a stochastic flow network in terms of minimal paths with budget constraint, *IIEE Transactions* 51 (5) (2019) 547–558.

- [9] Y. F. Niu, Z.-Y. G., W. H. K. Lam, Evaluating the reliability of a stochastic distribution network in terms of minimal cuts, *Transportation Research Part E: Logistics and Transportation Review* 100 (2017) 75–97.
- [10] C. T. Yeh, Y.-K. Lin, L. C.-L. Yeng, P.-T. Huang, Rail transport network reliability with train arrival delay: A reference indicator for a travel agency in tour planning, *Expert Systems with Applications* 189 (2022) 116107.
- [11] M. Forghani-elahabad, N. Mahdavi-Amiri, An improved algorithm for finding all upper boundary points in a stochastic-flow network, *Applied Mathematical Modelling* 40 (4) (2016) 3221–3229.
- [12] C. T. Yeh, Y.-K. Lin, L. C.-L. Yeng, P.-T. Huang, Reliability evaluation of a multistate railway transportation network from the perspective of a travel agent, *Reliability Engineering & System Safety* 214 (2021) 107757.
- [13] M. Forghani-elahabad, N. Kagan, Assessing reliability of multistate flow networks under cost constraint in terms of minimal cuts, *International Journal of Reliability, Quality and Safety Engineering* 26 (05) (2019) 1950025.
- [14] T. Xiahou, Y. X. Zheng, Y. Liu, H. Chen, Reliability modeling of modular k-out-of-n systems with functional dependency: A case study of radar transmitter systems, *Reliability Engineering & System Safety* 233 (2023) 109120.
- [15] M. Forghani-elahabad, L. H. Bonani, Finding all the lower boundary points in a multistate two-terminal network, *IEEE Transactions on Reliability* 66 (3) (2017) 677–688.
- [16] F. Nazarizadeh, A. Alemtabriz, M. Zandieh, A. Raad, An analytical model for reliability assessment of the rail system considering dependent failures (case study of iranian railway), *Reliability Engineering & System Safety* 227 (2022) 108725.
- [17] Y. F. Niu, X.-Y. Wan, X.-Z. Xu, D. Ding, Finding all multi-state minimal paths of a multi-state flow network via feasible circulations, *Reliability Engineering & System Safety* 204 (2020) 107188.

- [18] M. Forghani-elahabad, N. Mahdavi-Amiri, An algorithm to search for all minimal cuts in a flow network, *Advances in Systems Science and Applications* 20 (4) (2020) 1–10.
- [19] W. C. Yeh, A novel method for the network reliability in terms of capacitated-minimum-paths without knowing minimum-paths in advance, *Journal of the Operational Research Society* 56 (10) (2005) 1235–1240.
- [20] M. Forghani-elahabad, N. Kagan, N. Mahdavi-Amiri, An MP-based approximation algorithm on reliability evaluation of multistate flow networks, *Reliability Engineering & System Safety* 191 (2019) 106566.
- [21] Y. F. Niu, C. He, D. Q. Fu, Reliability assessment of a multi-state distribution network under cost and spoilage considerations, *Annals of Operations Research* (2021) 1–20.
- [22] W. C. Yeh, A simple minimal path method for estimating the weighted multi-commodity multistate unreliable networks reliability, *Reliability Engineering & System Safety* 93 (1) (2008) 125–136.
- [23] M. Forghani-elahabad, E. Francesquini, An improved vectorization algorithm to solve the d-mp problem, *Trends in Computational and Applied Mathematics* 24 (1) (2023) 19–34.
- [24] P. M. Kozyra, The usefulness of (d, b)-mcs and (d, b)-mps in network reliability evaluation under delivery or maintenance cost constraints, *Reliability Engineering & System Safety* 234 (2023) 109175.
- [25] M. Forghani-elahabad, N. Mahdavi-Amiri, A new efficient approach to search for all multi-state minimal cuts, *IEEE Transactions on Reliability* 63 (1) (2014) 154–166.
- [26] P. M. Kozyra, An innovative and very efficient algorithm for searching all multistate minimal cuts without duplicates, *IEEE Transactions on Reliability* (2021).
- [27] M. Forghani-elahabad, N. Kagan, An approximate approach for reliability evaluation of a multistate flow network in terms of minimal cuts, *Journal of Computational Science* 33 (2019) 61–67.

- [28] Y. Lamalem, K. Housni, S. Mbarki, An efficient method to find all d-MPs in multistate two-terminal networks, *IEEE Access* 8 (2020) 205618–205624.
- [29] W. C. Yeh, C.-M. Du, S.-Y. Tan, M. Forghani-elahabad, Application of lstm based on the bat-mcs for binary-state network approximated time-dependent reliability problems, *Reliability Engineering & System Safety* (2022) 108954.
- [30] M. Forghani-elahabad, 1 exact reliability evaluation of multistate flow networks, in: *Systems Reliability Engineering*, De Gruyter, 2021, pp. 1–24.
- [31] Y.-K. Lin, Two-commodity reliability evaluation of a stochastic-flow network with varying capacity weight in terms of minimal paths, *Computers & Operations Research* 36 (4) (2009) 1050–1063.
- [32] S. M. Mansourzadeh, S. H. Nasserri, M. Forghani-elahabad, A. Ebrahimnejad, A comparative study of different approaches for finding the upper boundary points in stochastic-flow networks, *International Journal of Enterprise Information Systems (IJEIS)* 10 (3) (2014) 13–23.
- [33] D.-H. Huang, C.-F. Huang, Y.-K. Lin, Reliability evaluation for a stochastic flow network based on upper and lower boundary vectors, *Mathematics* 7 (11) (2019) 1115.
- [34] M. Forghani-Elahabad, 3 the disjoint minimal paths reliability problem, in: *Operations Research*, CRC Press, 2022, pp. 35–66.
- [35] X. Chen, J. Tao, G. Bai, Y. Zhang, Search for d-MPs without duplications in multistate two-terminal networks, in: *2017 Second International Conference on Reliability Systems Engineering (ICRSE)*, IEEE, 2017, pp. 1–7.
- [36] C. C. Jane, Y.-W. Laih, A practical algorithm for computing multi-state two-terminal reliability, *IEEE Transactions on reliability* 57 (2) (2008) 295–302.
- [37] G. Bai, Z. Tian, M. J. Zuo, An improved algorithm for finding all minimal paths in a network, *Reliability Engineering & System Safety* 150 (2016) 1–10.

- [38] Y. F. Niu, Z. Y. Gao, W. H. K. Lam, A new efficient algorithm for finding all d-minimal cuts in multi-state networks, *Reliability Engineering & System Safety* 166 (2017) 151–163.
- [39] M. Forghani-elahabad, N. Mahdavi-Amiri, On search for all d-mcs in a network flow, *Iranian Journal of Operations Research* 4 (2) (2013) 108–126.
- [40] Y.-F. Niu, X.-Z. Xu, Reliability evaluation of multi-state systems under cost consideration, *Applied Mathematical Modelling* 36 (9) (2012) 4261–4270.
- [41] M. Forghani-elahabad, N. Mahdavi-Amiri, A new algorithm for generating all minimal vectors for the q smps reliability problem with time and budget constraints, *IEEE Transactions on Reliability* 65 (2) (2015) 828–842.
- [42] Y.-K. Lin, Extend the quickest path problem to the system reliability evaluation for a stochastic-flow network, *Computers & Operations Research* 30 (4) (2003) 567–575.
- [43] M. Forghani-elahabad, N. Mahdavi-Amiri, An efficient algorithm for the multi-state two separate minimal paths reliability problem with budget constraint, *Reliability Engineering & System Safety* 142 (2015) 472–481.
- [44] W. C. Yeh, W.-W. Chang, C.-W. Chiu, A simple method for the multistate quickest path flow network reliability problem, in: *2009 8th International Conference on Reliability, Maintainability and Safety, IEEE, 2009*, pp. 108–110.
- [45] M. Forghani-elahabad, An improved algorithm for the quickest path reliability problem, *Proceeding Series of the Brazilian Society of Computational and Applied Mathematics* 9 (1) (2022).
- [46] H. Cancela, M. El Khadiri, L. A. Petingi, Polynomial-time topological reductions that preserve the diameter-constrained reliability of a communication network, *IEEE Transactions on Reliability* 60 (4) (2011) 845–851.

- [47] Z. Zhang, F. Shao, A diameter-constrained approximation algorithm of multistate two-terminal reliability, *IEEE Transactions on Reliability* 67 (3) (2018) 1249–1260.
- [48] E. Canale, F. Robledo, P. Romero, P. Sartor, Monte carlo methods in diameter-constrained reliability, *Optical Switching and Networking* 14 (2014) 134–148.
- [49] H. Cancela, F. Robledo, G. Rubino, P. Sartor, Monte carlo estimation of diameter-constrained network reliability conditioned by pathsets and cutsets, *Computer Communications* 36 (6) (2013) 611–620.
- [50] E. Canale, H. Cancela, F. Robledo, P. Romero, P. Sartor, Diameter constrained reliability: Complexity, distinguished topologies and asymptotic behavior, *Networks* 66 (4) (2015) 296–305.
- [51] W. C. Yeh, S.-Y. Tan, M. Forghani-elahabad, M. El Khadiri, Y. Jiang, C.-S. Lin, New binary-addition tree algorithm for the all-multiterminal binary-state network reliability problem, *Reliability Engineering & System Safety* 224 (2022) 108557.
- [52] R. Ahuja, T. Magnanti, J. Orlin, *Network flows: theory, algorithms and applications*, Prentice Hall, 1995.
- [53] J. S. Lin, C. C. Jane, J. Yuan, On reliability evaluation of a capacitated-flow network in terms of minimal pathsets, *Networks* 25 (3) (1995) 131–138.
- [54] W. C. Yeh, An improved sum-of-disjoint-products technique for the symbolic network reliability analysis with known minimal paths, *Reliability Engineering & System Safety* 92 (2) (2007) 260–268.
- [55] Y.-K. Lin, C. T. Yeh, Using minimal cuts to optimize network reliability for a stochastic computer network subject to assignment budget, *Computers & Operations Research* 38 (8) (2011) 1175–1187.
- [56] M. Forghani-elahabad, L. H. Bonani, Simple novel algorithm for a special diophantine system appeared in the system reliability problem, *Proceeding Series of the Brazilian Society of Computational and Applied Mathematics* 3 (2) (2015).