End-to-End Speech-to-Text Translation: A Survey

Nivedita Sethiya, Chandresh Kumar Maurya,

^aIndian Institute of Technology Indore, India

Abstract

Speech-to-Text (ST) translation pertains to the task of converting speech signals in one language to text in another language. It finds its application in various domains, such as hands-free communication, dictation, video lecture transcription, and translation, to name a few. Automatic Speech Recognition (ASR), as well as Machine Translation(MT) models, play crucial roles in traditional ST translation, enabling the conversion of spoken language in its original form to written text and facilitating seamless cross-lingual communication. ASR recognizes spoken words, while MT translates the transcribed text into the target language. Such integrated models suffer from cascaded error propagation and high resource and training costs. As a result, researchers have been exploring end-to-end (E2E) models for ST translation. However, to our knowledge, there is no comprehensive review of existing works on E2E ST. The present survey, therefore, discusses the works in this direction. We have attempted to provide a comprehensive review of models employed, metrics, and datasets used for ST tasks, providing challenges and future research direction with new insights. We believe this review will be helpful to researchers working on various applications of ST models.

Keywords: Speech-to-Text Translation, Automatic Speech Recognition, Machine Translation, Modality Bridging

1. Introduction

The Speech-to-Text (ST) translation task aims to convert a speech in one language into text in another language. It finds its applications in various areas such as *automatic subtitling, dictations, video lecture translations, tourism, telephone conversations*, to name a few. There are many facets under which the ST problem can be cast. For example, are we performing ST translation online (aka simultaneous translation) or offline? The former is required in live video streaming, while



Figure 1: History of E2E ST models. Blue color models correspond to streaming models discussed in §7.1.2. Note that here we have listed only a few selected representative models.

the latter is helpful for movies where some latency may be allowed. The ST problem is further exacerbated by noisy inputs, low-resource/code-mix languages, and the presence of multiple speakers.

Historically, the ST problem has been solved by pipelining ASR and MT models together where ASR models take speech in a source language as input and generate the transcript. Whereas MT models translate the transcript into the target language. Such a cascade model suffers from problems like *error propagation*, *higher training, and inference latency*. Therefore, the current trend in developing the ST model is toward the E2E system which is defined as

Definition 1. A unified E2E ST model is implemented, facilitating combined training and recognition processes aimed at consistently reducing the anticipated error rate, thereby bypassing the need for independently acquired sources of knowledge.

Therefore, the main goal of the E2E ST model is to achieve a reduced error rate, with secondary objectives potentially including decreased training/inference duration and memory usage.

There has been a lot of work building E2E ST models (as shown in fig. 1), datasets, and metrics in recent years. However, a systematic and comprehensive review of E2E ST works is missing. The authors found that a review paper (Xu et al., 2023b) on ST was published recently. The review mentioned above categorizes existing works mainly based on modeling, data, and application issues. They do not cover the data sets available for the ST tasks nor provide any insights into the cascade vs. E2E model performances. Also, the future open problems provided by them are limited. On the other hand, our work comprehensively reviews



Figure 2: Organization of the survey paper

the existing models for ST tasks, evaluation methods, metrics, and datasets from a completely different perspective and critically analyzes the existing works; after that, we identify several challenges and future research directions. Thus, our work may be deemed complimentary to (Xu et al., 2023b).

The following review is structured following the taxonomy in fig. 2. In §2, we establish the foundation of the ST task through a formal definition, and we subsequently delve into the various metrics and loss functions adopted by different researchers in §3. A comparative discussion between cascade and end-to-end models is presented in §4. Training of E2E ST models suffers from data issues and how to combat them is elaborated in §5. Speech and Text segmentation and representation is an important task in ST model development discussed in §6. In §7, we delve into the strategies employed to tackle the ST problem. We categorize these approaches based on the frameworks utilized and the characteristics of the data involved. Data and toolkits required for ST modeling are discussed in §9. Finally, in §10, we explore the prospects for future research and open problems

within the field.

2. Background

This section describes the ST task formally and presents the loss functions and evaluation metrics commonly employed to optimize ST models.

2.1. Task Definition

ST task can be defined as translating the given input speech U in one language to translated text V in another language with the transcription text X (optionally). Formally, it is defined as follows: Given a dataset $D = \{(\mathbf{u}^i, \mathbf{x}^i, \mathbf{v}^i) | i = 1, 2, ..., n\}$ of pairs of input speech features $\mathbf{u} = (u_1, u_2, ..., u_{T_u})$ in a language and output text tokens $\mathbf{v} = (v_1, v_2, ..., v_{T_v})$ in a different language, the objective of the ST task is to minimize the conditional probability given below:

$$p(\mathbf{v}|\mathbf{u};\theta) = \prod_{t=1}^{T_v} p(v_t|v_{< t}, \mathbf{u};\theta)$$
(1)

In the above equation, T_u , T_v , and θ are the lengths of input features, the number of output tokens, and the model parameter, respectively. Note that the problem formulation given in (1) is for *Autoregressive* (AR) models ¹. Usually, it is assumed that there are *n* parallel speech-text pairs in our corpus, and the model is optimized for negative log-likelihood over these pairs as

$$\ell(\theta|D) = -\sum_{i=1}^{n} \log P(\mathbf{v}^{i}|\mathbf{u}^{i};\theta)$$
(2)

The above optimization is usually solved using an encoder-decoder with an attention approach. Essentially, an encoder maps speech input to a hidden state representation h followed by a decoder which takes the previously generated text tokens $v_{< t}$, encoder hidden state h and attention vector α (Vaswani et al., 2017). Offline ST translation can look at the whole speech before producing output text tokens, whereas streaming ST can start translation of partial speech signal.

¹Non-autoregressive (NAR) models are an alternative modeling approach that has been proposed in the past few years for the ST task. Only a sparse number of works exist in the literature. We discuss NAR briefly in §7.1

3. Evaluation Metrics

This section discusses various metrics used to evaluate the E2E ST models. The metrics to evaluate E2E ST models are categorized into two types: **quality** and **latency**. The quality of the E2E ST models is the measure of how close the ST translation is to the target sentence. The latency is the time elapsed between the pronunciation of a word and the generation of its textual translation.

3.1. Quality-based metrics

The quality-based metrics measure how close the translation is to the target sentence. Most of the existing literature evaluates these scores on *detokenized* output which is the string formed by combining the tokens. Standard metrics for evaluating ST task performance are commonly used MT evaluation metrics such as Bi-lingual Evaluation Understudy (BLEU) (Papineni et al., 2002), Translation Error Rate (TER) (Snover et al., 2006) via sacreBLEU, Metric for Evaluation of Translation with Explicit word Ordering (METEOR) (Banerjee and Lavie, 2005), and CHaRacter-level F-score (CHRF), and CHRF++ (Popović, 2015). Recently BERTScore has shown promising results on comparing with human evaluations. The BERTScore (Zhang et al., 2019) is an automatic evaluation metric that scores the similarity between the translated text and the referenced text. It takes into account the Recall, Precision, and Fscore. There are a few other evaluation metrics such as TRANSTAC (Schlenoff et al., 2009) and which are less frequently reported.

3.2. Latency-based metrics

For streaming ST tasks, researchers report a metric for measuring *latency*, which is defined as the delay incurred in starting to produce the translation. Let \mathbf{u}, \mathbf{v} and $\hat{\mathbf{v}}$ denote the input speech sequence, ground truth text sequence, and system-generated hypothesis sequence, respectively. In the streaming ST task, models produce output with partial input. Suppose $\mathbf{u}_{1:t} = \{(u_1, \dots, u_t), t < T_u\}$ has been read when generating v_s , the delay in v_s is defined as (Ma et al., 2020a)

$$d_s = \sum_{k=1}^t T_k \tag{3}$$

where T_k is the duration of the speech frame u_k . The latency metrics are calculated using a method that analyzes a sequence of time delays $[d_1, \ldots, d_{T_v}]$.

• Average Proportion (AP) (Cho and Esipova, 2016a) calculates the mean fraction of the source input that is read during the target prediction generating process.

$$AP = \frac{1}{T_v \sum_{k=1}^{T_u} T_k} \sum_{s=1}^{T_v} d_s$$
(4)

• Average Lagging (AL) measures the distance between the speaker and the user based on the number of words used in the conversation (Ma et al., 2018).

$$AL = \frac{1}{\tau(T_u)} \sum_{s=1}^{\tau(T_u)} d_s - \hat{d}_s$$
(5)

Where $\tau(T_u) = \min\{s \mid d_s = \sum_{k=1}^{T_u} T_k\}$ and \hat{d}_s are the delays of an ideal policy defined as (Ma et al., 2020a)

$$\hat{d}_s = (s-1) \sum_{k=1}^{T_u} \frac{T_k}{T_v}$$
(6)

• Differentiable Average Lagging (DAL) One issue with AL is that it is not differentiable because of the min function. To solve this, (Cherry and Foster, 2019) introduces a minimum delay of $1/\gamma$ after each operation and defines DAL as

$$DAL = \frac{1}{T_v} \sum_{s=1}^{T_v} d'_s - \frac{s-1}{\gamma}$$
(7)

where

$$d'_{s} = \begin{cases} d_{s}, & s = 0\\ \max(d_{s}, d'_{s-1} + \gamma), & s > 0 \end{cases}$$
(8)

and $\gamma = T_v / \sum_{k=1}^{T_u} T_k$

• Length-Adaptive Average Lagging (LAAL) One issue with AL metric for simultaneous translation is that though it can handle the *under-generation*² problem, it is unable to handle *over-generation* and produces biased score.

 $^{^{2}}$ Under/Over-generation problem refers to the length of the generated text compared to the reference translation text.

To alleviate this issue, (Papi et al., 2022a) propose LAAL which modifies (6) as

$$\hat{d}_s = (s-1) \sum_{k=1}^{T_u} \frac{T_k}{\max\{T_v, \hat{T}_v\}}$$
(9)

Essentially, it divides (6) by the maximum length of the reference and predicted text. As such, it can handle both over and under-generation problems.

• Average Token Delay (ATD) AL metric does not take into account the length of the partial translation output, i.e., it does not consider the latency caused by longer outputs. To remedy this issue, ATD (Kano et al., 2023), defined below, has been proposed recently.

$$ATD = \frac{1}{T_v} \sum_{s=1}^{T_v} (T(v_s) - T(u_{a(s)}))$$
(10)

where

$$a(s) = \min(s - f(s), d_s) \tag{11}$$

$$f(s) = (s-1) - a(s-1)$$
(12)

 $T(\cdot)$ in (10) represents the ending time of each input or output token. The token is a sub-segment in speech, a character, or a word in text. a(s) represents the index of the input token corresponding to v_s in the time difference calculation and a(0) = 0. f(s) in (11) represents how much longer the duration of the previous translation prefix is than that of the previous input prefix.

3.3. Loss Functions

Let D = (u, x, v) be a tuple where u, x, and v are the speech, the transcription text, and the translation text, respectively. The following are the various loss functions that are used to optimize the performance of the E2E ST models:

• **Distillation Loss** (Liu et al., 2019) The student model not only matches the ground truth, but also the teacher models's output probabilities, which reduces the variance of the gradients.

$$L_{KD} = -\sum_{(x,v)\in D} \sum_{t=1}^{N} \sum_{k=1}^{|V|} S(v_t = k | v_{< t}, x) \log T(v_t = k | v_{< t}, x)$$
(13)

where S and T denote the output distribution of student and teacher models, respectively.

• **CTC Loss** (Ren et al., 2020) computes the most likely alignment of output text sequence given input speech sequence by summing over the all possible output sequence paths.

$$L_{CTC} = -\sum_{(u,x)\in D} \sum_{z\in\phi(x)} \log p(z|u)$$
(14)

• **Cross-Modal Adaptation Loss** (Liu et al., 2020d) is defined as the sum of all the Mean Squared Errors of the speech and the transcription texts.

$$L_{AD} = \begin{cases} \sum_{(u,x)\in D} MSE(\bar{h_u}, \bar{h_x}); & \text{seq-level} \\ \sum_{(u,x)\in D} MSE(\bar{h_u}, h_x); & \text{word-level} \end{cases}$$
(15)

where h_u and h_x are the speech and word embeddings, and $\bar{h_u}$ and $\bar{h_x}$ are the average speech and word embeddings, respectively. MSE represents the difference between the two embeddings.

• **Cross-Entropy Loss** (Ye et al., 2021) is the negative likelihood of the data combined over all the subtasks such as ASR, MT, ST and also from external-MT.

$$L_{\theta} = -\sum_{x,v \in D' \cup D_{MT-ext}} \log p(x|v;\theta), \tag{16}$$

where $D' = D_{ASR} \cup D_{MT} \cup D_{ST}$ is the superset of all the parallel subsets data.

• **Contrastive Loss** (Ye et al., 2022a) is computed between the speech and the transcription text bringing them closer, and pushing the unrelated pairs farther.

$$L_{CON} = -\sum_{(u,x)\in D} \log \frac{\exp(\cos(\bar{h_u}, \bar{h_x})/\kappa)}{\sum_{\forall x_j \notin \bar{h_x}} \exp(\cos(\bar{h_u}, \bar{h_x}(x_j))/\kappa)}, \qquad (17)$$

where cos and κ denote the cosine similarity and temperature hyperparameter, respectively.



Figure 3: Generic architecture of (a) Cascade (d) E2E ST model

• **ST Loss** (Ouyang et al., 2023) is defined as the negative log-likelihood of the translation text given the source speech as follows

$$L_{ST} = -\sum_{(u,v)\in D} \log p(v|u) \tag{18}$$

• **MT Loss** (Ouyang et al., 2023) is defined as the negative log-likelihood of the translation text given the source transcript as follows

$$L_{MT} = -\sum_{(x,v)\in D} \log p(v|x) \tag{19}$$

• ASR Loss (Ouyang et al., 2023) is defined as the negative log-likelihood of the transcription text given the source speech as follows

$$L_{ASR} = -\sum_{(u,x)\in D} \log p(x|u) \tag{20}$$

4. Cascade vs. End-to-End

The traditional ST translation methods involve a cascade approach–First, applying ASR on the given speech and then performing MT on the transcription produced by ASR (see fig. 3a) Such a cascade model is prone to several issues, such as (a) error in the ASR model can propagate to the MT model, (b) higher training time, (d) inability to capture non-lexical cues such as prosody, and (d) resources required for training. To mitigate such issues, various researchers propose using E2E models (see fig. 3b) for ST task (Bérard et al., 2016; Anastasopoulos

et al., 2016; Bérard et al., 2018; Gangi et al., 2019; Bentivogli et al., 2021). An E2E model offers joint training from scratch; avoids separately trained knowledge sources; and produces the output in a single pass (Prabhavalkar et al., 2024). Because of simpler training, lower memory footprint, and cost, E2E model development has gained significant momentum in the research community.

Despite E2E models demonstrating superiority over cascade ST models based on the aforementioned criteria, they still fall short in comparison to the latter in terms of both automatic and human evaluation metrics (Etchegoyhen et al., 2022; Agrawal et al., 2023). In particular, (Lam et al., 2020; Etchegoyhen et al., 2022) show that the cascade model outperforms E2E in a low-resource setting (Basque \rightarrow Spanish) while employing in-domain and out-of-domain data for training the ASR and MT components. The gap is more significant when models are trained using unrestricted data. However, as shown by (Bentivogli et al., 2021) on three language directions, the gap between cascade and E2E is closed, though primarily on English on one side. The same conclusion is found by (Tsiamas et al., 2024) as well. Another study (Zhou et al., 2024) shows that E2E models can capture paralinguistic features of speech and outperform cascade models in disambiguating wh-phrases. Such a study alludes to further comparative study involving more languages and domains to assert the claim that the performance gap is indeed closed.

5. Data Issues

The lack of adequate parallel speech-text corpora, essential in large quantities for training direct ST models, significantly impedes the performance of such models. The necessity for supervised ST data poses challenges in applying E2E ST systems to low-resource languages, where creating labeled parallel speechtext corpora demands substantial investments of time, money, and expertise. To address data scarcity, various techniques such as data augmentation, pre-training, back-translation, knowledge distillation, etc., are employed. These methods are elaborated as follows.

5.1. Augmentation

Data augmentation is a technique in machine learning to synthetically create more data points by applying the class-preserving transformations (Cui et al., 2015). The objective is to increase the variability in the data so that the generalization and robustness of the model may be enhanced. Data augmentation can be applied to both speech and text.



Figure 4: Strategies for addressing data paucity in ST task modelling. (a) Data augmentation, (b) Self-training, (c) Back-translation, and (d) Knowledge distillation. The dashed arrow indicates that the model is used for inference.

5.1.1. Augmenting speech data

Speech data can be augmented in various ways. For example, by adding noise, speed and pitch perturbation, time and frequency masking to name a few. SpeechAugment (Park et al., 2019) policy consists of warping the features, masking blocks of frequency channels, and time steps. It has been successfully used both for ASR (Vincent et al., 2017) and ST tasks (Bahar et al., 2019b). MixSpeech (Meng et al., 2021) as shown in Fig. 4(a) takes the weighted combination of two different speech features as input and two recognition losses with the same weights. A generalization of MixSpeech (Xie and Hansen, 2023) called MixRep applies the mixup idea to the acoustic feature and hidden layers inputs. MixRep combination with a regularization term along the time axis further improves ASR performance. Both MixSpeech and MixRep have been shown to perform well for low-resource ASR and their effectiveness is still to be tested for ST tasks. M3ST (Cheng et al., 2022) applies two levels of Fine-Tuning (FT) using mixup dataword, sentence, and frame level mix data in the first FT level and source speech and transcription mixup in the second FT level. M3ST achieves SOTA on MuST-C compared to baselines.

5.1.2. Augmenting speech and text data

It is possible to augment both speech and text simultaneously and create new paired data. For example, sample, translate, and recombine (Lam et al., 2022b) first samples a *suffix replacement* from *suffix memory* corresponding to a *pivot* token from transcription. It then translates the combined new utterance (pre-fix+pivot+replacement suffix) to generate a new target sentence. The corresponding audio pair is obtained by concatenating the audio frames of the prefix, pivot, and replacement suffix. The interesting thing about the proposed method is that it can generate *real-looking* sentences contrary to *pseudo-sentences*. **Concatenation** of original ST data has been used to augment the entire training data (Lam et al., 2022a). In particular, (Lam et al., 2022a) proposes *CatSpeaker* that uses single speaker information and *CatRandom* that randomly generates audio-text pairs spoken by different speakers.

5.2. Pre-training

Pre-training is an approach to handle data scarcity for low-resource problems and is deemed as a form of transfer learning (Bozinovski and Fulgosi, 1976). Data used for pre-training may consist of either speech, text, or both. Once the models are pre-trained leveraging augmented data, it enhances the robustness of the model on downstream tasks. We find that SOTA ST models often use pre-training on a large amount of ASR/MT corpus. In ST, pre-training has been used by many researchers (Paulik and Waibel, 2013; Bansal et al., 2017; Anastasopoulos and Chiang, 2018; Wang et al., 2020d; Dong et al., 2021; Zhang et al., 2022a; Tang et al., 2022). Pre-training has been applied in two flavors by different researchers: Independently and Jointly.

In **independent** pre-training, individual modules (encoder, decoder, semantic decoder, etc.) are pre-trained using auxiliary data such as ASR and MT data. Such an approach has been followed by (Wang et al., 2020d; Chen et al., 2020; Zheng et al., 2021a). In particular, (Wang et al., 2020d) pre-trains the encoder using ASR data for learning semantic concepts. (Chen et al., 2020) propose a self-supervised method called Masked Acoustic Modeling (MAM), which randomly masks part of the speech spectrogram and then recovers it on top of the encoder. Whereas (Zheng et al., 2021a) unifies speech and text representation through masked language modeling. Besides pre-training the encoder and the decoder, various researchers also exploit pre-trained feature extractors such as Wav2vec (Schneider et al., 2019) used by (Zhang et al., 2023b) and (Liu et al., 2020b) HuBERT (Hsu et al., 2021) used by (Zhang et al., 2023a). Very recently, (Tsiamas et al., 2024)

proposed an ST model that pre-trains the speech encoder using optimal transport and CTC. They claim to surpass supervised ST models requiring no paired speech-text data in a **zero-shot** setting.

In **joint** pre-training, the entire model is first pre-trained in an E2E fashion followed by fine-tuning over the ST corpus (Fang and Feng, 2023; Bapna et al., 2021). It is often accompanied by multitasking pre-training with ASR, MT, and masked language modeling tasks (Chung et al., 2021), using supervised as well as unsupervised speech and text data. The (Tang et al., 2022) pre-trains on speech/text-to-text/speech, text-to-text, speech self-supevised learning (SSL), and speech-to-phoneme. SpeechT5 (Ao et al., 2021) pre-trains on ASR, ST, textto-speech, speech conversion, and speech enhancement tasks. Wave2Seq (Wu et al., 2022) pre-trains jointly using pseudo-languages. Multi-modal multi-task pre-training leverages five tasks: self-supervised speech-to-pseudo-codes (S2C), phoneme-to-text (P2T), self-supervised masked speech prediction (MSP), supervised phoneme prediction (PP), and ST task (Zhou et al., 2022b).

5.3. Self-training and Back-translation

Both the Self-Training and Back-translation (BT) methods are approaches employed to harness monolingual data for training models that necessitate supervised data but encounter limitations in the availability of a sufficient supervised parallel corpus, as illustrated in Fig.4(b) and (c). The self-training method is utilized to make use of source monolingual data, while the back-translation method is applied to target monolingual data. In the end, both methods are employed synergistically to generate augmented data.

More specifically, given a speech-text parallel corpus $D_p = \{(\mathbf{u}^i, \mathbf{v}^i) | i = 1, 2, ..., n\}$, monolingual source speech corpus $D_s = \{\mathbf{u}^i_s | i = 1, 2, ..., m\}$ and monolingual target text corpus $D_t = \{\mathbf{v}^i_t | i = 1, 2, ..., p\}$, where m, p >> n. In self-training, first, a translation model $f_{u \to v}$ is trained on D_p . It is then used to generate "pseudo labels" \mathbf{v}^i_s for D_s by applying $f_{u \to v}$ leading to auxiliary data $A_s = \{(\mathbf{u}^i_s, \mathbf{v}^i_s) | i = 1, 2, ..., m\}$. The combined data $D_p \cup A_s$ is then used to re-train the model $f_{u \to v}$. Whereas in back-translation, D_t is translated using a backward translation model $f_{v \to u}$ creating auxiliary data $A_t = \{(\mathbf{u}^i_t, \mathbf{v}^i_t) | i = 1, 2, ..., p\}$ for training the forward translation model $f_{u \to v}$ on the combined data $D_p \cup A_t$.

Back-translation on discrete units to train a unit-to-text translation model is applied in (Zhang et al., 2023a) which is on par with methods leveraging large-scale external corpus. (Fang and Feng, 2023) proposes a back-translation strategy for target-to-unit and unit-to-speech synthesis for low-resource language translation

without transcript. (Wang et al., 2021b) extract speech features using wav2vec 2.0 pretraining, a single iteration of self-training and decoding with a language model. Cyclic feedback from MT output is used as a self-training mechanism for a cascade of ASR-MT model that shows how to exploit the direct speech-translation data in (Lam et al., 2020).

5.4. Knowledge distillation

Knowledge Distillation(KD) transfers learned knowledge from a large ensemble model (called teacher) to a smaller single model (called student) as shown in Fig.4 (d) (Hinton et al., 2015). This process encompasses both model compression (Bucilă et al., 2006) and transfer-learning. More details of recent works utilizing KD approaches for ST tasks are given in §7 (ST with MT) and §6.2.3.

6. Segmentation and Representation Learning

E2E ST models rely on segmented inputs because handling long inputs is a challenging task (Kim et al., 2017; Tsiamas et al., 2022c). Segmentation is the problem of splitting the long speech/text sequence into smaller and more manageable segments whose representations can be learned. This section will shed some light on the segmentation and representation issues and offer some advice on how to tackle them.

6.1. Segmentation Learning

As discussed above, segmentation is an important issue while building ST models. Segmentation of text is easy-they can be split based on the strong punctuation. This is what current MT models rely on. Similarly, ASR models give lower importance to segmentation due to the small local context window required for the task. The cascaded ST model can perform segmentation by applying ASR followed by monolingual translation to restore the lost punctuation followed by segmentation on them (Matusov et al., 2007, 2018). On the other side, the E2E ST models require sophisticated segmentation of the speech primarily due to the importance of out-of-order word relation between the input and output that exist as well as the absence of linguistic features.

Traditionally, segmentation of speech is done manually. Due to the cumbersome task, segmentation learning is warranted. Segmentation is done based on either *length* which splits the speech at fixed-lengths or *pause* which splits the speech based on Voice Activity Detection (VAD) (Sohn et al., 1999). The third approach to segment the speech is *hybrid* mode in that length and linguistic contents are taken into account (Potapczyk and Przybysz, 2020; Gaido et al., 2021; Tsiamas et al., 2022c). The hybrid approach surpasses the length and pause-based approaches to segmentation in terms of performance (Gaido et al., 2021). Concretely, (Tsiamas et al., 2022c) learns the manual segmentation using a binary classifier and *probabilistic divide-and-conquer* algorithm (Gaido et al., 2021) is used at inference time to decide the split point. However, there is still a gap in the hybrid and manual approaches to segmentations, and future work may consider paying attention to this.

Our discussion above focuses on segmentation in the *offline E2E models*. Segmentation of speech in *streaming E2E models* is presented in §7.1.2.

6.2. Representation Learning

Representation learning is a type of machine learning where algorithms are supposed to discover and extract useful features automatically from the raw data. It has been successfully applied in computer vision (Wu, 2020), natural language processing (Liu et al., 2021b), and speech (Mohamed et al., 2022). Representation learning is an important issue in ST tasks because speech and text are two distinct modalities of data that reside in different embedding spaces. Hence, we not only need better representation learning methods for speech and text but also their joint representation learning. Many of the works in ST apply speech/text representation learning methods before actually applying encoder-decoder or transducer-based methods (explained later in §7) for the ST task. Below, we provide details of such representation learning methods used for ST tasks.

6.2.1. Text Representation

ST models often use ASR transcripts and MT translations as auxiliary data which needs to be fed to the encoder and decoder, respectively. To learn representation for such text data, existing works rely on word embedding (Zhang et al., 2023c; Bérard et al., 2016), LSTM (Kim et al., 2017; Weiss et al., 2017; Bérard et al., 2018; Jia et al., 2019), and Transformer (Wang et al., 2021b; Liu et al., 2021a; Zeng et al., 2021). Text data is often tokenized and fed as either a word or as a character (Bérard et al., 2018). The output of the decoder could be graphene, characters, or words.

6.2.2. Speech Representation

ST models take speech as input and utilize various speech-based feature representation methods to convert speech into a vector representation. Traditional speech feature extraction methods such as Perceptual Linear Prediction, (PLP), Fbank, and Mel-Filter Cepstral Coefficient (MFCC) (Rabiner and Schafer, 2010) have been used after normalization to extract speech features by many (Duong et al., 2016; Bérard et al., 2016; Kim et al., 2017; Bérard et al., 2018; Anastasopoulos and Chiang, 2018; Bansal et al., 2019; Jia et al., 2019; Inaguma et al., 2019; Liu et al., 2020d; Dong et al., 2021; Le et al., 2023b; Parcollet et al., 2024), sometimes combining them with pitch features and speech augmentation methods as described in §5. These feature extraction methods are sometimes being replaced by distributed feature representation methods such as speech word2vec (Chung and Glass, 2018) owing to their dense continuous feature representation capability.

It is difficult to get a large amount of labeled speech data to learn supervised speech feature representation. Therefore, more recent works exploit speech features learned via unsupervised and self-supervised ways, mapping continuous speech signal to *discrete units*– akin to words and sub-words in the text domain. Such a representation facilitates tools developed in NLP to borrow in the speech domain. Among them the most popular is Wav2Vec (Schneider et al., 2019) and its variants such as w2v-BERT (Chung et al., 2021) and Wav2vec 2.0 (Baevski et al., 2020) used in (Tran et al., 2020; Le et al., 2020; Li et al., 2020; Han et al., 2021; Popuri et al., 2022; Zhang et al., 2023c). Interestingly, Wav2Vec and its variants can be used as an encoder in a Seq2Seq framework alone or combined with adapters and CNN for *Length shrinking*³. A few works such as CSTNet (Khurana et al., 2020; Wang et al., 2020d) use CNN for feature extraction and length shrinking.

More recent works in ST are employing HuBERT (Hsu et al., 2021) for speech representation (among other benefits of HuBERT) (Zhang et al., 2023a). Hubert offers stable training and better targets than Wav2Vec 2.0 since it uses hidden layers representation during the clustering process. For encoding long-speech signals, Conformers (Gulati et al., 2020) can be used as they provide local context through convolution block and global context through an attention mechanism. Seamless4MT (Barrault et al., 2023) uses conformer for speech encoding.

Other speech representation techniques such as VQ-VAE (van den Oord et al., 2017), WavLM (Chen et al., 2022), data2vec (Baevski et al., 2022), Robust data2vec

³Length shrinking is an important issue in ST task since speech is a much longer sequence than text. Therefore, existing works employ various techniques such as *length adapters, CNN, CTC* for length shrinking



Figure 5: Modality Bridging

(Zhu et al., 2023), SpeechLM (Zhang et al., 2024b), may also be explored while encoding speech for ST tasks.

6.2.3. Joint Speech-Text Representation

The speech and text in an ST task are semantically related because both of them refer to the same thing. Therefore, it is imperative to learn a joint speech-text representation in the hope of bridging the modality gap between them. A method for learning a combined representation of text and speech is called **modal-ity bridging** (see fig.5). Hence, a good ST model should learn a representation such that embeddings of both modalities for similar speech-text pairs lie close to each other. It is believed that low performance on ST tasks is due to models not learning aligned representations of speech and text. Therefore, different authors have devised different ways to fill the gap, which fall into five major approaches: (a) adapters, (b) contrastive learning, (c) knowledge-distillation, (d) optimal transport, and (e) mix-up strategy. Below we discuss the works utilizing these approaches and show the pros and cons.

- (a) Adapters are small modules integrated with pre-trained networks for specific tasks (Houlsby et al., 2019). They have performed on par with fineturning-based approaches while requiring only a fraction of trainable parameters. For example, in (Gállego et al., 2021; Zhao et al., 2022; Sarkar et al., 2023), the modality gap is filled using *adapter layers*, which is a *multi-headed self-attention* with pooling operation. The author uses Wav2Vec 2.0 (Baevski et al., 2020) for speech-feature extraction, wherein self-attention layers in the transformer are equipped with pooling operation for dimensionality reduction to match the text representation.
- (b) **Contrastive learning** approximates the "semantic" distance in the input space using a simple distance in the target space after mapping input patterns onto

the target space (Chopra et al., 2005). It tries to bring positive instances closer while pushing negative ones apart. It has been used excessively in both supervised and unsupervised settings for learning representations. For example, (Zhang et al., 2023c) performs the *explicit knowledge transfer* through contrastive learning. It learns frame and sentence-level speech feature representation and uses whitening (Su et al., 2021) to alleviate the MT representation degeneration. (Liu et al., 2019) decouples the encoder representation into three parts: acoustic encoder, shrinking (done via CTC) of acoustic encoder output, and semantic encoder for modality-gap bridging. Using a contrastive learning architecture, Chimera (Han et al., 2021) trains a semantic memory module which is shared for overcoming the modality distance. XST-Net (Ye et al., 2021) augmented with contrastive loss (Ye et al., 2022a) investigates three different methods: span masked representation, word-repetition and *cut-off*. It claims that contrastive loss is better than CTC and L2 loss. Word-aligned contrastive learning (WACO) (Ouyang et al., 2023) bridges the modality gap by forming average speech and word embedding of the same word as the positive pair while of different words as negative pairs. CST-Net is a *self-supervised* learning framework based on contrastive learning (using a mix of triplet losses)(Khurana et al., 2020). On top of the CTC loss, the boundary-based speech length shrinking mechanism is applied in (Zeng et al., 2022). The authors claim that if boundary-based shrinking is applied with other modality-bridging techniques, such as contrastive loss, it can further improve the model performance. The approach presented achieves lower inference speed and memory footprint. (Yin et al., 2023) proposes a novel integration of speech and text, referred to as a third modality. This fusion is achieved through the application of Cross-modal Contrastive Learning (Sohn, 2016) and Cross-Attentive Regularization (Tang et al., 2021a). Additionally, the method incorporates techniques such as Knowledge Distillation and Jensen-Shannon Divergence (Lin, 1991; Liu et al., 2019; Gaido et al., 2020a) to bridge the modality gap, addressing challenges related to input representation, semantics, and hidden states.

- (c) **Knowledge-distillation** (Hinton et al., 2015) is a mechanism to *distill* information from a trained and large "teacher" model to a smaller and efficient "student" model. It has been used with L_2 loss in (Huzaifah and Kukanov, 2023) to address the modality gap issue.
- (d) **Optimal transport** (OT) (Peyré et al., 2019) is a mechanism for comparing two *probability distributions*. In the ST task, speech and text representations may be deemed as two probability distributions, and therefore, OT can

Models/Techniques	Problem Solved	Dataset	Language Pair	Speech (hours)	Metric (BLEU)
M-Adapter + W2V2 + mBart (Baevski et al., 2020)	training gap between Pre- training & Fine-tuning the modality	MuST-C	En→De	408	25.9
			En→Ro	432	24.62
			$En \rightarrow Fr$	492	37.34
Chimera (Han et al., 2021)	projecting audio & text to a common semantic repre- sentation	MuST-C	En→De	408	27.1
			$En \rightarrow Fr$	492	35.6
			En→Ru	489	17.4
			En→Es	504	30.6
			En→It	465	25.0
			En→Ro	432	24.0
			$En \rightarrow Pt$	385	30.2
	1 1 1.	N OT C	En→NI	442	29.2
Cons1 (XS1Net + Constrastive Loss) (Ye et al., 2021)	closes modality gap	MuST-C	En→De	408	28.3
			$En \rightarrow Es$	504	32.0
			En→Fr	492	38.3
			$En \rightarrow It$	465	21.2
			$En \rightarrow INI$ En $\rightarrow Dt$	442	31.7
			Ell→Ft En \Po	365	25.6
			$E_{II} \rightarrow K_{U}$	432	23.0
W2V2 + mBart + Adapter (Gállego	slow convergence speed	MuST-C	En→De	409	28.22
et al 2021 : Theo et al 2022)	slow convergence speed	Musi-C	Lli→De	408	28.22
WACO (Ouyang et al., 2023)	limited parallel data (1-	MuST-C	En→De	1	17.5
AdaTrans (Zeng et al., 2022)	closing gap between length of speech & text	MuST-C	En→De	408	28.7
			En→Fr	492	38.7
			En→Ru	489	19.0
STEMM (Fang et al., 2022)	Speech representation	MuST-C	En→De	408	28.7
			En→Fr	492	37.4
			En→Ru	489	17.8
			En→Es	504	31.0
			En→lt	465	25.8
			En→Ro	432	24.5
			En→Pt	385	31.7
CTC 1 C C 1 T	··· · · · · · · · · · · · · · · · · ·	MOTO	En→NI	442	30.5
CTC loss + Optimal Transport (Siamese-PT) (Le et al., 2023b)	tecture	MuSI-C	En→De	408	27.9
			$En \rightarrow Es$	504	31.8
			$En \rightarrow Fr$	492	39.2 27.7
			$En \rightarrow II$	403	21.7
			$E_{II} \rightarrow INI$ $E_{II} \rightarrow Pt$	442 385	34.2
			$E_{n} \rightarrow R_{0}$	432	27.0
			En→Ru	489	18.5
Fine & Coarse Granularity Con- trastive Learning (Zhang et al., 2023c)	limited knowledge transfer ability	MuST-C	En→De	408	29.0
			En→Fr	492	38.3
			En→Ru	489	19.7
			En→Es	504	31.9
			En→It	465	27.3
			En→Ro	432	26.8
			$En \rightarrow Pt$	385	32.7
			En→Nl	442	31.6

Table 1: Performance of the ST models using modality bridging. The datasets, language pairs, duration of speech, and metric(BLEU) are shown.

be applied. More formally, suppose α and β denote the discrete probability distributions corresponding to speech and text representations. The masses at each position u_i and v_i are a_i and b_j respectively such that $\sum_{i=1}^m a_i = 1$ and $\sum_{j=1}^n b_j$. Suppose further that the cost of transporting a unit of mass from u_i to v_j is $c(u_i, v_j)$, where c is some cost function such as Euclidean distance. Let $Z_{ij} \ge 0$ be the quantity of mass to be transported from u_i to v_j then the goal of OT is to move all masses from α to β such that the following objective function is minimized

$$\min_{Z} \langle C, Z \rangle, \qquad Z \mathbf{1}_n = a, Z^T \mathbf{1}_m = b, Z \ge 0$$
(21)

In the above eq., C and Z are the matrices whose elements are $c_{ij} = c(u_i, v_j)$ and Z_{ij} , respectively. 1 denotes the vector of ones. In ST task, $c(u_i, v_j) = ||u_i - v_j||_p$ for some $p \ge 1$. The loss corresponding to (21) is called **Wassertein** loss optimizing which is costly. Hence an entropy-regularized upper-bound approximation is often optimized

$$\min_{Z} \{ \langle C, Z \rangle - \lambda H(Z) \}$$
(22)

where λ is a regularization parameter and $H(\cdot)$ is the von-Neuman entropy matrix.

Recent works make use of the OT as presented above. For example, (Le et al., 2023b) uses optimal transport and CTC together to close the modality gap during the pre-training phase. They show significant gains in BLEU score when the ST model is fine-tuned without any external data compared to multitask learning. Similarly, (Tsiamas et al., 2024, 2023) uses OT+CTC to align the speech-encoder representation space with the MT embedding space whereas (Zhou et al., 2023) aligns the two representations via OT followed by cross-modal mix-up at the token level.

(e) **Mix-up strategy:** Speech-Text Manifold Mixup (STEMM) (Fang et al., 2022) strategy uses speech embedding. It mixes embeddings of speech and text into the encoder-decoder of a translation model for bridging the modality gap under the *self-supervised learning* framework. PromptST (Yu et al., 2023) presents a linguistic probing learning strategy, referred to as *Speech-Senteval*, inspired by the approach introduced by (Conneau et al., 2018). This strategy is implemented on the higher layer of the encoder within pre-trained ST models, specifically targeting the challenges associated with learning linguistic properties that these models often struggle with at the higher layers.

Table 1 presents the performance scores of ST models based on modalitybridging techniques. We can observe that mixup strategy achieves the highest BLEU score on En-De pair. Whereas boundary-based speech length shrinking mechanism matches the score when combined with other modality-bridging techniques.

Discussion: The study finds that adapters can shrink the speech length as well as the modality distance between the text and speech representations while requiring a small number of trainable parameters. The contrastive loss is found to be better than CTC and L_2 loss for modality-bridging. The boundary-based speech length shrinking combined with contrastive loss may improve the ST task performance. Finally, it is possible to build ST models requiring zero parallel ST data (Tsiamas et al., 2024).

7. End-to-End ST Models

End-to-end models for ST as discussed previously are gaining traction comparably to cascade models. This section presents an overview of E2E models. We categorize them under two major E2E themes: framework-based and databased. The first category is further divided on whether the framework used is offline or streaming. The second category is based on the nature of the data. The sub-categorization presented in the data-based section depends upon which component boosts the ST task performance, as claimed in the papers. As such, the demarcation is not strict, and there may be overlaps in the subcategories. In addition, our emphasis in the present review of existing works is highlighting the core contribution and limitations as claimed by the authors. That means we look for answers to the question: what is the main technical contribution of authors to solve the ST problem? Thus, wherever possible, we have limited the mathematical description and believe such details can be found in the related papers. We attempt to provide a succinct and clear picture of what works and what does not while addressing the ST problem.

7.1. E2E ST Models based on Frameworks

As mentioned in the previous section, E2E ST models based on the framework are further divided into whether the framework is offline or streaming. Below, we discuss both of these categories in detail.



Figure 6: E2E offline framework. The dashed arrow denotes optional components.

7.1.1. Offline Frameworks

Offline frameworks perform ST tasks where output tokens are produced after having seen the entire speech utterance. These frameworks heavily rely on Seq2Seq architecture as shown in Fig. 6. It has an encoder for speech input, a decoder for text output, and an optional shared/semantic decoder connecting the encoder and the decoder. The model is usually optimized for the ST loss or sometimes in a **multitask learning** framework where ASR/MT/CTC (Graves et al., 2006) losses are combined with ST loss. Other times **Transfer learning** is utilized for leveraging pre-trained models for ST tasks. Another approach that has been gaining a lot of attention is **Non-Autoregressive modeling** (NAR) for the E2E ST task which gives faster inference. The following section will delve deeper into these approaches.

The Seq2Seq-based ST models proposed in the literature either use specialized encoders such as transformers or attention mechanisms which we discuss next.

(a) Attention mechanism is used to concentrate on specific sections of the input data instead of the entire data (Larochelle and Hinton, 2010; Mnih et al., 2014; Vaswani et al., 2017). It has been a successful strategy for getting state-of-the-art (SOTA) results in NLP, computer vision, and other areas. There exist various types of attention in the literature such as soft, hard, local, monotonic, multihead, self- and cross-attention, inter alia. For more details, interested readers are encouraged to skim through (Mnih et al., 2014; Vaswani et al., 2017; Brauwers and Frasincar, 2022). Below we provide efforts made to handle ST tasks using the attention mechanism within the Seq2Seq framework. The *convolutional* attention to "remember" and avoid translating the signal twice is used within Seq2Seq by (Bérard et al., 2016), which outperforms a hierarchical encoder with better results on *synthetic data* without using transcripts. The same author in (Bérard et al., 2018) uses source transcript and achieves results close to cascade models on LibriSpeech data. In (Duong et al., 2016), the author proposes phone-to-text alignment with a *structural*

bias feature in the attention model. The measurement of alignment has been explored in (Anastasopoulos et al., 2016), which uses IBM's translation model as well as *dynamic time warping*⁴. Seq2seq with attention trained using *multitask learning* achieves promising results in (Weiss et al., 2017). These models, however, struggle with *noisy inputs* and *long acoustic signals* (Kim et al., 2017). They use a joint CTC-attention model (Graves et al., 2006) trained through multitask learning by incorporating *regularizers*. The author uses two decoders where the second decoder seeks *higher level representation* (*HLR*) from the first decoder besides the encoder via the attention mechanism. *Attention-Passing Model* (APM) (Sperber et al., 2019), which only passes high-attention vectors from the audio encoder to the translation text for decoding demands a smaller amount of data for training.

(b) Transformer is the architecture based on multi-headed self-attention (Vaswani et al., 2017) which produces contextualized representation of the input. Because of parallelization and contextual representation, transformers have outperformed RNNs on several NLP tasks. This entails us applying transformers for the ST task as well. Transformer-based Seq2Seq with attention is proposed in (Cattoni et al., 2021). The architecture has a quadratic memory complexity, which involves: (a) CNN to downsample the input, and (b) 2-D attention to address short-range dependencies of spectrograms. In (Alastruey et al., 2022), the weight of some attention is avoided for speech tasks, hence decreasing the size of the attention matrix. The transformer encodes the speech features, thereby introducing *local self-attention* with a suitable window size for each layer to reduce the computational complexity. Other transformer variants which reduce its quadratic complexity such as *perceivers* (Jaegle et al., 2021) have been used as an encoder (Tsiamas et al., 2022b). Besides quadratic complexity, transformers require lossy downsampling of speech features thus potentially throwing useful linguistic information. To tackle such issues, Speechformers have been proposed (Papi et al., 2021a) which aggregates information at higher layers based on more informed linguistic criteria.

As discussed earlier, **multitask learning** combines the optimization of ST loss with an auxiliary loss such as ASR/MT/CTC loss. Another direction that has been explored by ST researchers is **transfer learning** in that Seq2Seq encoder/decoders

⁴dynamic time warping (DTW) is an algorithm for measuring similarity between two temporal sequences, which may vary in speed.

are first *pre-trained* using ASR/MT data respectively and then the entire model is *fine-tuned* using ST data. Below, we discuss works based on multitask/transfer learning frameworks.

- (a) **ST with ASR:** ST with ASR models make use of the transcript data along with speech-text pairs for pre-training. For example, curriculum pre-training (Wang et al., 2020d) refers to using ASR data for pre-training a Seq2Seq model, allowing it to learn transcription. The author argues that if the model is further pre-trained on learning semantic concepts (via frame-based masked language modeling) and word alignment (via frame-based bilingual lexical translation), it boosts the ST task performance. Specifically, existing E2E models either pre-train the encoder or use multi-task learning for ST tasks. As such, the encoder cannot isolate the learning of three tasks: transcription, semantic concept, and alignment, which are segregated by *dividing the labor*, and experiments prove the theoretical claims. Listen, Understand, and Translate (LUT) (Dong et al., 2021) uses the Seq2Seq model with external ASR loss. Their primary contribution is to introduce a *semantic encoder network*, whose task is to use the encoder's output from transcription to minimize the mean-squared loss between the semantic representations and the BERT embeddings of the target text. Such a strategy implicitly builds and trains an NMT model for translation. Pre-training using ASR and/or MT has also been found useful in low-resource scenarios (Zhang et al., 2022a).
- (b) **ST using MT:** This section discusses approaches that use either MT data for pre-training or directly using a pre-trained MT model in the ST decoder. These approaches rely on the idea of generating *pseudotext* and then translating them using MT. For example, Unsupervised Term Discovery (UTD) (Bansal et al., 2017) groups repeated words into pseudo-text, which is subsequently used for training an MT model using the parallel pseudo-text and target translations. The main advantage of such a system is that it can translate some content words under low-resource settings. The overall results are not very promising on the Spanish-English Call-Home dataset. Another limitation of this work is that the approach is not an E2E in a true sense as it involves two models- a UTD and an MT model. A weakly supervised learning method for ST (Jia et al., 2019) that outperforms multi-task learning takes advantage of the pre-trained MT and TTS synthesis module. Pre-trained MT model is used as a *teacher* to guide the *student* ST model in (Liu et al., 2019) (such an approach is dubbed as knowledge distillation (KD)). They, however, rely on source language text and do not improve upon

the pipeline system. Following along, (Gaido et al., 2020b) explores *word, sentence* and *sequence-interpolation* based KD approaches for transferring knowledge from pre-trained MT to ST model.

(c) **ST using both MT and ASR:** This section discusses works employing MT and ASR pre-trained models (Bahar et al., 2020; Tsiamas et al., 2022a) or losses for transfer or multitask learning.

Multitask learning proves to be effective when CTC loss is combined with ASR and MT loss in (Bahar et al., 2019a) using various E2E ST architectures such as direct, multitask many-to-one, one-to-many, tied-cascade, and tied-triangle. They show that pre-trained models with ASR and MT losses achieve promising results. Contrary to claims of (Anastasopoulos and Chiang, 2018), *tied-triangle* architecture is no better than a direct model when fine-tuned properly. Since the ST task is similar to the MT task from the output perspective, works such as XSTNet (Ye et al., 2021) utilize external MT data to pre-train the encoder-decoder network extensively, then fine-tune it using parallel corpus data of MT, ST, ASR, and external MT data for optimizing the model using what they call *progressive training*. They achieve impressive performance on MuST-C and augmented Librispeech data. They also demonstrate improved performance on auxiliary tasks of MT and ASR. STPT model (Tang et al., 2022) proposes four sub-tasks for multitask pre-training: text-totext (T2T), which is self-supervised; speech-to-phoneme which is supervised; acoustic learning, which is self-supervised, and ST which is supervised. Only T2T and ST tasks would subsequently be used for fine-tuning. Despite pretraining on "unlabeled" speech data, they obtained superior results on MuST-C data for the ST task. COSTT (Dong et al., 2020) pre-trains encoder using ASR data, the decoder using paired MT data, and then fine-tunes for the joint transcription-translation task. ComSL is a composite ST model relying on multitask learning with three losses $(L_{ASR}, L_{MT}, L_{ST})$ combined with crossmodality loss to bridge the gap (Le et al., 2023a). It is worth mentioning that ComSL does not require forced-align ST data and learns the cross-modality alignment during training. This however requires optimizing four different losses, viz. Masked Token Prediction, Speech to Text Mapping, Encoder Representation Matching, and Decoder Distribution Matching⁵ similar to (Tang et al., 2021b). Fused acoustic and text encoding-ST (FAT-ST) (Zheng et al., 2021b) follows the similar pre-training and fine-tuning idea as ComSL except

⁵please see (Le et al., 2023a) paper for more details.

that they propose to use any combination of training data from $D_{2^{\{u,x,v\}}}$ ⁶. Essentially, they rely on masked language modeling (MLM) and translation language modeling (TLM) for pre-training (Conneau and Lample, 2019).

(d) Non-Autoregressive Modeling⁷ As discussed in the background section, an alternative approach to Autoregressive (AR) modeling is Non-Autoregressive (NAR) modeling. AR assumes that the output tokens are conditional dependent on the previously generated tokens. However, it causes significant latency during inference. NAR models solve this problem by outputting all the translated tokens in parallel thus speeding up the inference. Formally, they are given by (23)

$$p(\mathbf{v}|\mathbf{u};\theta) = \prod_{t=1}^{T_v} p(v_t|,\mathbf{u};\theta)$$
(23)

There has been a surge in applying the non-autoregressive models (AR) in ASR and MT and it has prompted ST researchers to apply to it too. For example, (Inaguma et al., 2020a, 2021) trains NAR and autoregressive decoding conditioned on a shared speech encoder. Another line of NAR works (Chuang et al., 2021) explores CTC with ASR as an auxiliary task. CTC-based encoder only architecture ((Inaguma et al., 2020a, 2021) use encoder and decoder both) for NAR E2E ST task is shown to perform comparably or better than strong AR models in (Xu et al., 2023a).

Discussion: Our study of Seq2Seq-based frameworks for ST task reveals that (a) structural bias can be obtained by stacked/pyramidal RNN and alignment smoothing, (b) regularizers such as transitivity and invertibility improves Character Error Rate, (c) HLR helps in transcription as well as translation, and (d) changing the self-attention of the encoder with a logarithmic distance penalty enhances translation, (e) Progressive training needs a huge data and training time to achieve superior results, and (f) multitask pre-training can be used to leverage unlabeled speech data. (Zhang et al., 2022a) shows that ST models trained from scratch using only ST tasks perform on par with or surpass pre-trained models. To achieve such results, proposed best practices include a smaller vocabulary, a wider feedforward layer, a deep speech encoder with the post-layer norm, CTC-based regularization, and parameter-distance penalty. Pre-training is still useful

 $^{{}^{6}2^{\{}u,x,v\}}$ is the power set of triplets.

⁷We present the discussion of NAR within the multitask learning framework because all NAR E2E ST models are optimized within the multitask framework.



Figure 7: Incremental Decoding Framework. CP stands for the common prefix. Fig. adapted from (Guo et al., 2024)

in low-resource data regimes. Transferring knowledge via KD from pre-trained MT to ST causes gender bias, omission of sentences, and generic verbal-tense choice. Use of **large vocabulary and models** is effective for NAR E2E ST task (Inaguma et al., 2020a). It indicates that leveraging NAR with LLMs may be a future direction to explore.

7.1.2. Streaming frameworks

Streaming frameworks for ST tasks start outputting target tokens on seeing only partial inputs, that is, the translation of the input as soon as it arrives without waiting for the entire input. They are also known as Simultaneous ST (SimulST or SST)⁸ (Goldman-Eisler, 1972; Fügen et al., 2007; Tsiartas et al., 2013; Grissom II et al., 2014). It finds application in online speech translation and video dubbing, to name a few. Traditionally, the streaming ST problem has been solved by feeding the segmented output of a streaming ASR model to a streaming MT model (Oda et al., 2014; Iranzo-Sánchez et al., 2020). However, due to the cascade nature of the model, it is prone to high latency and error propagation (Arivazhagan et al., 2019b, 2020; Zaidi et al., 2022). The SST problem faces several issues in practical implementation; **reordering, acoustic ambiguity, and variable speech rate, and long inputs** being prominent among them. Our literature survey reveals that most of the existing works focus on handling *long streaming inputs* and therefore, the discussion underneath revolves around that. Other issues mentioned above may also be considered for designing practical SST models. Existing streaming

⁸Note that in MT literature, some works such as (Iranzo-S'anchez et al., 2022) differentiate between *Streaming* and *Simultaneous* setting where sentences are treated independently from each other. However, in ST, we find that existing works make no differentiation between them.

frameworks intervene Seq2Seq framework at various places to design SST models. These are (a) encoder-level, (b) decoder-level, and (c) input/latent-level.

- (a) **Encoder-level:** SOTA SST models use transformers as encoders. Due to the *self-attention* operation which looks at the entire utterance, it is unsuitable for streaming inputs. There exist some works that design encoders specialized for streaming inputs. For example, *augmented memory transformer* (Wu et al., 2020; Ma et al., 2020c) splits the utterance U into smaller-segments $S = [s_1, \ldots]$. Each segment s_n consists of left context I_n , main context c_n , and right context r_n . Self-attention is calculated at the segment level only thereby reducing the time complexity. Augmented memory propagates the information from one segment to the other. *Incremental transformer* (Zhang et al., 2020) leverages a unidirectional encoder based on unidirectional-attention with future context masked for handling streaming inputs.
- (b) **Decoder-level:** Instead of modifying encoders, some works such as (Dalvi et al., 2018; Liu et al., 2020a; Nguyen et al., 2021; Guo et al., 2024) propose incremental decoding (see fig. 7). In this framework, input speech is divided into fixed-size chunks and decoded every time a new chunk arrives. To avoid distractions from constantly changing hypotheses, selected chunk-level predictions are committed to and no longer modified. The decoding of the next chunk is conditioned by the predictions committed. Instead of conditioning on all chunk-level predictions, a prefix function is chosen to select a partial hypothesis because early chunks contain limited information (Liu et al., 2020a). There exist several strategies for choosing the *prefix* function. For example, Hold-n and LA-n (Liu et al., 2020a), SP-n (Nguyen et al., 2021) and Regularized Batched Inputs (R-BI) (Guo et al., 2024). Of these, Hold-n either withholds or deletes the last n tokens in each chunk, LA-n involves displaying the agreeing prefixes of n consecutive chunks. SP-n stands for *shared* prefix of all best-ranked hypotheses. Contrary to these, RB-I applies various augmentations to input chunks to achieve regularization and SOTA results on the IWSLT SimulST task.
- (c) Input/latent-level: Since speech input is too fine-grained, deciding when to READ and WRITE is challenging. The existing works introduce predecision module which segments the input speech at fixed-chunks (*fixed*) or word-boundary (*flexible*). Similarly, READ/WRITE policy can be *fixed* or *adaptive* (Ma et al., 2020b). Most research in SST concentrates on either improving speech encoding or pre-decision while relying on fixed policies such as wait-k. In this section, we discuss fixed and adaptive pre-decisions/policies.



Figure 8: (a) wait-k based Streaming ST (d) RNN-T based Streaming ST

These techniques are combined with Seq2Seq frameworks to devise streaming ST models.

Wait-*k* policy (Ma et al., 2018) (shown in fig. 9) learns the parameters θ of the model by optimizing the negative log-likelihood $-\sum_{(\mathbf{u},\mathbf{v})\in D} \log p(\mathbf{v}|\mathbf{u};k;\theta)$, where *k* is the number of segments to look before starting translation (see Fig. 9). The probability $p(\cdot)$ is calculated as

$$p(\mathbf{v}|\mathbf{u};k;\theta) = \prod_{t=1}^{T_v} p(v_t|v_{< t}, u_{t+k};\theta)$$
(24)

wait-k policy guarantees that the model can look at t + k - 1 speech segments while predicting token v_t (Ren et al., 2020). However, one limitation of the wait-k policy is that it fails to do a beam search while decoding except for long-tail (Ma et al., 2018). To solve this problem, (Zeng et al., 2021) proposes a wait-k stride-N policy. It essentially is a wait-k policy with the addition of N READ and WRITE operations until the end of the sentence after reading the first k-segments. To determine the k-segments, (Chen et al., 2021b) leverages streaming ASR to guide the direct simultaneous ST decoding via beam search.

As discussed above, determining when to write is crucial for efficient SST. Contrary to wait-k policy which is a **fixed-policy**, **Segmentation** can be performed on the embedded speech using CTC (Ren et al., 2020), attention mechanism (Papi et al., 2022b), or incremental BEAM search (Yan et al., 2023). Essentially, these works **adapt offline ST to SST** showing spectacular performance on benchmark datasets. Note that the models proposed in (Papi et al., 2022b; Yan et al., 2023) train models in a cascade manner while the inference is E2E. Another issue with the fixed policy is that the model can not speed up or slow down appropriately with the input types. Other exam-



Figure 9: wait-k strategy for streaming ST setting. In this, the decoder waits for k input speech segments before starting to output. Thereafter, it produces one token for every source segment. The figure showcases the scenario with k = 2.

ples of **fixed-policy** are Wait-If* (Cho and Esipova, 2016b) and Monotonic Chunkwise Attention (MoChA) (Chiu and Raffel, 2018) that has been used in simultaneous MT and may be explored for SST.

The works mentioned above require that encoded speech be segmented so that the decoder can apply the wait-k policy. The goal of segmentation is to identify the word, sub-word, or phone boundary which are usually not even (due to silences, longer syllables, etc.). That means the number of acoustic units varies with time in each segment. Monotonic-segmented Streaming ST (MoSST) (Dong et al., 2022) is based on learning when to translate, which has a monotonic segmentation module located between the acoustic encoder and the transformer. It has an Integrate-and-Fire (IF) neuron (Abbott, 1999), which fires above a threshold when the context is developed. If the context is not developed, the neuron receives signals and accumulates the acoustic vectors, thus mimicking adaptive policy for READ-WRITE operation. IF strategy has shown impressive performance in simultaneous ASR (Dong and Xu, 2019) and ST (Chang and yi Lee, 2022). It can be used for monotonic segmentation of the speech input along with adaptive decision strategy (Dong et al., 2022). Another adaptive policy-based technique is Monotonic Infinite Lookback Attention (MILk) (Arivazhagan et al., 2019b) used in simultaneous MT can be explored for SST. It essentially is a Monotonic Attention mechanism (Raffel et al., 2017) that extends to infinite encoder states, theoretically, in the past and trains the MT model along with the MILk. It achieves better guality-latency trade-offs than MoCHA thanks to its soft attention to all the encoder states and hard attention. Monotonic Multihead Attention (MMA)

(Ma et al., 2019) that extends MILK to multiple heads has been used for SST by (Ma et al., 2020b). Its variants Efficient MMA (Ma et al., 2023) solve numerical stability and biased monotonic alignment issues present in MMA but have not been explored for SST tasks. Adaptive segmentation based on an adaptive policy that takes into account acoustic features and translation history (called *meaningful units*) is another effective mechanism for SST (Zhang et al., 2022b).

Both fixed and adaptive policy mechanisms employ segmentation modules that are outside the translation module. As such, it breaks the acoustic integrity and potentially may drop the translation performance. Therefore, efforts such as (Zhang and Feng, 2023) propose **differentiable segmentation** (DiSeg) learned jointly with the translation model using **expectation training**. DiSeg essentially predicts a Bernoulli random variable $\sigma(FFN(u_i))$, via a feed-forward network (FFN), to decide when to segment. After segmentation, they apply segmented attention which combines unidirectional and bidirectional attention into one while masking future speech frames. Expectation training first constrains the number of segments followed by learning segmentation from the translation model both at semantic and acoustic levels (Zhang and Feng, 2023).

The discussion so far covered encoder, and decoder level changes, and fixed and adaptive policies used for segmentation, to develop SST models within the Seq2Seq frameworks. Another way to design SST models is by **Transduction**. It is the process of mapping a sequence to another sequence (Jurafsky and Martin, 2008). A transducer is a special type of Seq2Seq model that solves a few inherent problems. For example, online processing of the long inputs and monotonic sequence alignment is the biggest problem with Seq2Seq models (Graves, 2012), solved by transducers. Below we discuss a special type of transducer called **RNN-T** and its improvements.

RNN-T is a transducer that can learn alignment between two sequences in an online/streaming fashion (Graves, 2012) as shown in fig. 10 (a). Formally, it learns the conditional probability $p(\mathbf{v}|\mathbf{u})$ by marginalizing all possible alignment paths $A(\mathbf{u}, \mathbf{v})$ including blank symbol ϕ as

$$p(\mathbf{v}|\mathbf{u}) = \sum_{\hat{\mathbf{v}} \in A(\mathbf{u}, \mathbf{v})} p(\hat{\mathbf{v}}|\mathbf{u})$$
(25)

RNN-T differs from Seq2Seq in the sense that it divides the decoder into a *predic*tor and a *joiner*. The predictor takes the previous time step output and yields the



Figure 10: Architecture of (a) RNN-T (b) CAAT. Fig. adapted from (Liu et al., 2021a).

representation to be consumed by the joiner along with the hidden representation of the input from the encoder. Since the predictor does not look at the input, it can be pre-trained on the *text-only* data in a low-data scenario. There have been several SST models proposed based on variants of RNN-T which we discuss next.

One of the main issues with RNN-T is the strict *monotonic* alignment between the input and output sequences which makes them unsuitable for tasks requiring reordering such as MT, ST, etc. For example, Cross-Attention Augmented Transducer (CAAT shown in fig. 10(b)) optimizes translation and policy models in tandem (Liu et al., 2021a). It eliminates the RNN-T's strict monotonic restriction for reordering in the translation. Using transformers as encoders to reduce the multi-step memory footprint causes a significant delay for CAAT. The use of regularization terms and substantial hyperparameter adjustment are some other limitations of CAAT. An extension of it in (Xue et al., 2022) leverages Transformer Transducer (TT) networks with attention pooling for streaming E2E ST tasks. Attention divides the input audio into chunks of specific sizes. At any time, processing any input frame u_t can only see frames within its chunk and a fixed number of left chunks. By sharing the encoder, they also propose a variant to handle E2E ST tasks in **multilingual** settings. The adaptive READ and WRITE policy choices between encoder output and ground truth contribute to its success. The same authors (Wang et al., 2023) propose to combine the benefits of *language-specific* and *language-agnostic* encoders within the TT framework. A shared encoder takes LIDs as gating values and computes weights for each language through the source LID scheduling scheme. The empirical results demonstrate superior performance and a smaller number of trainable parameters than bilingual ST. Adaptive (dynamic) policy for segmenting speech input has recently been explored in a Seq2Seq transduction setting by (Tan et al., 2024). It essentially applies a cross-attention mechanism to decide when to segment the input followed by dynamic compression via *anchor* representation. Thus, it saves memory and achieves a better latency-quality trade-off.

Besides Transducer and Seq2Seq models, **re-translation** is another approach adapted for SST task by (Niehues et al., 2016, 2018; Arivazhagan et al., 2019a, 2020) though in a cascade setting. In this approach, the translated output can be re-generated after a fixed amount of time and displayed later for better quality. Though it reduces latency by being greedy to display the partial translation, the output is highly unstable and causes *flickring* effect. This may give rise to a bad user experience. To mitigate instability, (Arivazhagan et al., 2020) propose a metric called *erasure* which takes into the length of the suffix deleted during re-translation. Dynamic masking of MT output in a cascade of streaming ASR and MT for improving stability has been explored in (Yao and Haddow, 2020). Another approach to reducing instability is luminance contrast and the Discrete Fourier Transform used in (Liu et al., 2023).

Evaluation of SST models: SST models in the literature have been evaluated using the quality and latency metrics presented in §3. Often showing a trade-off between quality and latency. Most of the existing works attempt to balance the quality and latency ignoring the visualization and cognitive load on the viewer when displayed on a screen. Towards this end, (Papi et al., 2021b) emphasizes considering visualization as a metric to be evaluated along with the latency and quality. However, little effort has been made in this direction by the SST community. Therefore, we wish to draw the researcher's attention to also consider visualization as an evaluation metric for SST models. Towards this end, (Liu et al., 2023) propose tokenized alignment, word updates with semantic similarity, and smooth animation of live captions. They find that it leads to a reduction in fatigue, and distractions while increasing the viewer's reading comfort.

Discussion: SST is a challenging problem and in that, E2E SST poses a further impediment. Our findings suggest that using *adaptive* policy significantly improves the latency-quality trade-off. Learned policy mechanisms have been an ongoing research and adapting them for true long-form SST may open new possibilities. Exploring differentiable segmentation for long sequences is still tapped and requires more investigation. Re-translation is found to be on par with or better than SOTA streaming models (Arivazhagan et al., 2020) under a very low revision rate. Such a finding alludes to considering re-translation in an E2E SST system design.

7.2. ST Models based on the Nature of Available Data

In the previous section, we provided an overview of the ST models based on the frameworks used. The present section provides readers with another perspective on E2E ST models. In particular, it discusses the E2E ST models categorized based on the nature of the data, such as data is low-resource, streaming, multilingual, etc. Given the specific challenges they pose, we believe such a categorization might be interesting to researchers.

7.2.1. ST in Low-Resource settings

A low-resource language (LRL) is one where speech and/or text data are scarcely available – usually not enough to pre-train Seq2Seq models. As such, LRLs present challenges of their own such as overfitting and poor generalization. This section will discuss works where ST models are developed especially for low-resource languages. The proposed models under this category have generic architecture as shown in Fig.11a which is similar to Seq2Seq ST models. We find the approaches mainly use pre-training the encoder on high-resource ASR data and subsequent fine-tuning on ST data. Another approach that has emerged in recent years to tackle LRL issues is SSL. For example, (Bansal et al., 2019) empirically demonstrates 100% performance improvement on ST tasks. They find that if the ASR language differs from the source and target languages, then pretraining on ASR data enhances ST task performance. Though the BLEU score is improved, the absolute BLEU score is only 7.1. In (Wang et al., 2022), the unsupervised ST is implemented for low-resource settings using pseudo-labels from unsupervised cascade models. SSL with *discrete-speech unit* (DSU) has been used to fine-tune the ST model on limited ST data (Lam et al., 2024).

7.2.2. Code-mix ST

Code-mix language refers to speech where one *primary* language is used, but words or phrases from *other* (*embedded*) languages are also included. This phenomenon arises from a multitude of challenges, encompassing ambiguous vocabulary, fluctuating lexical representations, intermingling of languages at the word level, redundancy, and alterations in word sequencing. Therefore, it is non-trivial to handle code-mixing while building ST models.

We find that there exist only a few works on code-mix ST. In (Weller et al., 2022), the code-mix dataset is created with the existing publicly available corpora



Figure 11: E2E ST Models based on the nature of the data. (a) Low-resource ST, (b) Code-Mix ST, (c) Unsupervised ST, and (f) Multilingual ST. The dashed arrow denotes optional components.

Fisher (Cieri et al., 2004) and Miami⁹. As shown in Fig. 11b, code-mix ST models feed language ID in addition to speech input to the encoder of the Seq2Seq model (Weller et al., 2022). The Wav2Vec 2.0, an acoustic encoder, and mBART, a multilingual decoder, are used for both languages with an attention layer applied for the *embedded* language. The use of multilingual encoders and decoders is a common practice while building code-mix ST models (Yang et al., 2023). In particular, self-supervised multilingual pre-training with adapters may be explored further.

7.2.3. Unsupervised ST

There is an abundance of unlabeled speech and text data. Since manual annotation and creating a parallel corpus is costly, the natural instinct is to exploit unlabeled data for training ST models. This section reviews works where researchers make use of the *unlabeled* speech data to advance the ST task performance.

For unsupervised ST tasks, it is common to leverage large-scale self-supervised and semi-supervised learning. For example, speech encoders such as Wav2vec 2.0

⁹https://github.com/apple/ml-code-switched-speech-translation

have been pre-trained in a self-supervised manner on Librilight data (Kahn et al., 2019) and used by (Li et al., 2020; Wang et al., 2021b) whereas the decoder is randomly initialized. The entire model is optimized on CoVoST 2 ST data, and the encoder is *frozen*. Thereby, *self-training* is executed to generate pseudo-labels for Libri-light data. The Wav2Vec 2.0 is a "*student*" model which is fine-tuned with ground truth CoVoST 2 data and pseudo labels. Finally, a language model (LM) is trained on *CommonCrawl* data and combined with the ST model to generate text via *beam-search* decoding. Following along, for training the E2E model, (Wang et al., 2021b) produces pseudo-labels by cascading ASR, text *de-normalization*, and MT in an *Unsupervised* manner. Wav2Vec 2.0 and mBART are optimized for domain adaption using *in-domain* data (Li et al., 2020). According to experimental results, the proposed method is effective for E2E models without pre-training. However, between supervised and unsupervised pre-trained models, performance gap is encountered, which may be investigated in future works.

7.2.4. Multilingual ST

The multilingual ST model aims to translate from/to multiple speech input/output languages. It can be one of many-to-one, one-to-many, or many-to-many. The ST models solve multilinguality issues using mainly three approaches: (a) language ID, (b) dual-decoder, and (c) pre-trained models.

- (a) Language ID (LID) is the *identification label* that allows one to identify the target language and explicitly translate the speech simultaneously. The existing works handle *multilinguality* using LID either with encoder or decoder. In (Inaguma et al., 2019), the model uses LID in the decoder for one-to-many and many-to-many translation. They demonstrate impressive performance in translation from high-resource to low-resource languages without using any transcript data from LRL. However, using the LID embedding in the decoder (Gangi et al., 2019) is shown to underperform than using it in the encoder. The author shows that LID can be either *concatenated* or *merged* with the inputs and, when pre-trained with ASR data, can result in superior performance than the one-to-one system. The model, however, performs poorly when trained on many *unrelated* target languages. One-to-many and many-to-one multilingual ST systems of (Wang et al., 2020c,a) provide a good set of baselines for research purposes.
- (b) Dual-decoder model is the transformer with two decoders, one for each ASR and ST, and the *dual-attention* mechanism. In (Le et al., 2020), a dual-decoder model is proposed to optimize it for ASR and ST tasks jointly. The author
hypothesizes that a dual-attention mechanism can benefit each task by transferring knowledge instantly or in *wait-k* policy mechanism. Their model generalizes earlier models proposed for one-to-many and bilingual ST models.

(c) Pre-trained Multilingual Models use a pre-trained encoder and decoder for acoustic modeling and language modeling, respectively. In (Li et al., 2020; Tran et al., 2020), the author shows that efficiently fine-tuning *mBART*, which is a pre-trained multilingual decoder (Liu et al., 2020c) can achieve SOTA results on CoVoST data on *zero-shot* cross-lingual and multilingual translation tasks. Along similar lines, (Le et al., 2021) shows that inserting *adapters* in between layers of the encoder-decoder framework and tuning them can improve the ST task performance over bilingual ST models. SeamlessM4T (Barrault et al., 2023), Whisper (Radford et al., 2023), and other foundation models are built using many of these concepts like language ID in the decoder, multilingual, multimodal, and multitask pre-training.

7.3. Discussion

The works presented so far show that E2E ST models have been improved tremendously. ST models' improved performance is likely due to leveraging pretrained ASR/MT models or the respective corpus to train ST encoders/decoders. Weakly labelled/pseudo labels are another way to create more data for training ST models. Contrastive learning, mix-up strategy, adapters, and optimal transport are a few ways to bridge the modality gap.

Applying unsupervised ASR and MT with the Wav2Vec 2.0 encoder and mBART decoder in a low-resource setting yields good results for ST models. When considering online data streaming, using the IF neuron for context building and translation improves results compared to using CAAT, which had latency issues due to reordering for translation tasks introduced by RNN-T. The mBART handles multilingual settings well by using a dual attention mechanism that facilitates knowledge transfer. Additionally, inserting adapters between the encoder and decoder layers improves performance. In the unsupervised ST setting, the SOTA results were achieved by training Wav2Vec 2.0 on data within the same domain as the speech. We see that the wait-*k* policy is used in the streaming settings with segmentation and Multilingual settings with a dual-attention mechanism. In both cases, it yields good results. Also, *adapters* are used in modality bridging and multilingual settings with pre-trained models, which improves the performance. As shown in (Sun et al., 2023), multilingual E2E ST for LRLs can benefit when trained jointly with *related* HRLs.

7.4. Overall Performance Trend of E2E ST approaches in Common Benchmarks

In this section, we analyse the performance evolution of ST models over the MuST-C dataset, as depicted in Figure 12. We selected the MuST-C dataset due to its widespread adoption by researchers since its introduction in 2019.

Figure 12 reveals the overall performance of ST models over time has steadily improved across all 8 languages, with a few remarkable gains. The first significant gain was observed in 2021-adapter method (Le et al., 2021). This high jump in performance is achieved due to use of adapter layers within the *multilingual* models that shows transferability of knowledge across related language pairs (note that not all proposed models tested their models across all 8 languages). It also shows that Chimera (Han et al., 2021), which is a modality bridging model, performs poorly compared to adapter based models. That means, semantic shared network proposed in (Han et al., 2021) is not as good as adapters with multilingual models and there still is a gap between text and speech modality.

The next jump we see is due to ConST (Ye et al., 2022a) (for languages like Es, It, Pt, and Ru). This particular model achieved superior results by incorporating contrastive learning to bridge the modality gap the first time. The cross-modal speech-text retrieval accuracy jumps from 4% to 88%! and better way to bridge the gap than Chimera. The drop in performance in STEMM compared to ConST is that both are from the same authors and were proposed in the same year. In fact, ConST is an improvement over XSTNet and STEMM by the use of cross-model contrastive loss. FCCL (medium model) (Zhang et al., 2023c) further improves the performance, by applying contrastive learning over both the sentence- and frame-level, over ConST which applies contrastive learning only at the sentence level. Finally, OT based model outperforms contrastive learning based models on all languages except De and Ru. Looking closely, we find that OT based model (Le et al., 2023b) is able to close the modality-gap only partially compared to ConST and FCCL for a few languages. Hence, as a recommendation, coarseand fine-grained contrastive learning and ASR pre-training with CTC loss via OT approaches may be explored to build better ST models. Note that LLM-based ST models are not compared here due to primarily their pre-training over massive amount of data and we want a fair comparison where pre-training over external ASR and MT corpus leads to higher performance as we find in ConST and FCCL models.

7.5. SOTA Performance of E2E ST Models on Low-Resource Languages

In Table 2, we present the SOTA performance of various ST models on lowresource language pairs as of November 2023. The table indicates which models,

Language Pair	Model/Technique	Dataset	Speech (hours)	Setting	Metric (BLEU)
Ainu→En	Tied Multitask Learning with reg- ularizers (Anastasopoulos and Chi- ang, 2018)	Glossed Audio Corpus	2.5	ST with ASR & MT	20.3
Mboshi→Fr		Godard Corpus	4.4		24.7
Mt→En	WACO (Ouyang et al., 2023)	IWSLT	1	Modality Bridging	13.3
Et→En	Unsupervised + W2V2 + mBart (Wang et al., 2022)	CoVoST-2	3	Low-Resource	19.0
Lv→En	-		2		25.0
En→Ar	Teacher-Student (W2V2 + self- training + dec w/o LM) (Kahn et al., 2019)	CoVoST-2	430	Unsupervised	20.8
En→Ca					35.6
$En \rightarrow Tr$					18.9
Sl→En	LNA + Zero Shot Learning (Li et al., 2020)	CoVoST-2	2	Multi-Lingual	5.6
Sv→En			2		5.9
Fa→En			49		11.0
Tr→En			4		11.2
Mn→En			3		1.2
Ar→En			2		6.4
Cy→En			2		9.0
Ta→En			2		0.9
Ja→En			1		2.1
Id→En			1		3.7
En→Cy			430		30.6
$En \rightarrow Et$			430		22.2
En→Fa			430		21.5
En→Id			430		29.9
En→Ja			430		39.3
En→Lv			430		21.5
En→Mn			430		14.8
En→Sl			430		25.1
En→Sv			430		30.4
En→Ta			430		17.8

Table 2: SOTA performance in Low-Resource Language Pairs: Dataset, Models, Speech Duration, Settings, and BLEU Score

utilizing specific techniques, achieve SOTA performance. This provides a comprehensive overview of the current status of ST models for low-resource languages (LRLs). From Table 2, it is evident that the BLEU scores for many LRLs, such as Mn, Si, Ta, Id, Ja, and Sv, are relatively low. This is more likely due to small amount of speech data available for these (as seen in Speech (hours) column)) compared to other LRLs where higher amount of speech data is used for training the LNA+Zero shot model. This highlights the need for improving the performance of ST models for these languages by increasing the data and designing better models.

8. Deployment of E2E ST Models

Deployment of offline E2E ST models incurs several challenges. The first challenge is handling Cross-talk, noise, and background music removal and getting a clean speech. If the speaker is having stuttering, different dialect and accent



Figure 12: Performance of ST models over MuST-C dataset

Datasets	Source	Target Lan-	Speech	Speakers	Validation Gender Age		
	Language (Speech)	guage (Text)	(hours)	_			Group
MuST-C	En	14 lang	0.4K	1.6K	X	X	X
Librispeech	En	Fr	0.2K	1.4K	1	1	1
CoVost	En	11 lang	0.7K	11K	1	1	1
CoVost2	21 lang	En	2.8K	11K	1	1	1
	En	15 lang	0.7K	78K	1	1	1
EuroparlST	4 lang	4 lang	0.25K	X	X	X	X
VoxPopuli	En	15 lang	1.79K	4.3K	X	X	X
Kosp2e	Ко	En	0.2K	0.2K	X	X	X
GigaST	En	De, Zh	10K	X	X	X	X
Prabhupadavani	en-bn-sn code- mix	25 lang	0.09K	0.13K	X	X	X
How2	En	Pt	2K	X	X	X	X
FLEURS	102 lang	102 lang	1.4K	0.3K	1	1	X
BSTC	Zn	En	98	X	1	X	X
Indic-TEDST	En	9 lang	189	1.64K	×	×	X

Table 3: Dataset statistics (\checkmark means that feature is available for the dataset and \checkmark means that the feature is unavailable for the dataset)

then the same ST model may not work effectively. The second challenge is related to the distance of the speaker from the microphone and movements of the speaker around the microphone which can hamper the input speech quality. As a solution to these problems, the ST model may be trained over a variety of speakers in various acoustic conditions. The third challenge is related to memory consumption especially when considering LLM-based ST model deployment. To deploy memory-intensive and LLM-based ST models on edge devices, pruning, quantization, and knowledge distillation techniques may be used (Zhou et al., 2022a) which significantly reduces the memory load.

Streaming ST models on the other hand are used as a submodule within the automatic subtitling. Hence their deployment has challenges of subtitling tasks which is considered harder. For example, subtitling requires the following challenges to be solved: (a) firstly, translated text should be segmented such that it reduces the cognitive load and maximizes the user experience like reading speech and synchronization with the speech (b) how many characters and lines to display? These constraints are usually decided by the media industries. For example, displaying a maximum of 2 lines of subtitles, 42 characters per line at max, and a maximum reading speech of 21 characters/second is used by TEDx (Agrawal et al., 2023).

9. Resources for ST

9.1. Datasets for ST Tasks

There have been several datasets created for the ST task. Some of them are listed below, and we describe them here briefly. Table 3 provides information on various dataset statistics, such as hours of speech, the number of speakers, whether the dataset was manually or machine validated, the gender, and the age range to which the speaker belongs. Additionally, the tools required for creating these datasets are (a) *Gentle* (Ochshorn and Hawkins, 2017) for audio-transcription alignment, and (b) *BertAlign*¹⁰ for transcription-translation alignment.

- How2 (Sanabria et al., 2018) is an ST corpus of English instructional videos having Portuguese translations.
- Augmented Librispeech (Kocabiyikoglu et al., 2018) is obtained from the LibriSpeech corpus (Panayotov et al., 2015). It is a speech recognition repository generated using audiobooks of *Gutenberg Project*¹¹. This dataset is designed to translate English speech into written French text.
- CoVoST and CoVoST 2 (Wang et al., 2020a,c), the datasets are based on *Common Voice* project ¹². CoVoST is a many-to-one dataset covering 11 languages, while CoVoST 2 offers one-to-many and many-to-one translations for 15 languages.
- **Europarl-ST** (Iranzo-Sánchez et al., 2020) is a collection that contains speech and text data from *European Parliament proceedings* between 2008 and 2012 in four languages. It includes multiple sources and targets for both speech and text.
- **MuST-C** (Cattoni et al., 2021) It is a large *multilingual* ST translation corpus available. It contains translations from English into fourteen additional languages and is compiled from TED Talks. mTEDx (Salesky et al., 2021) is one such multilingual dataset from TED talks.
- **VoxPopuli** (Wang et al., 2021a) dataset is an expansion of Europarl-ST. It includes data from European parliament sessions spanning from 2009 to 2020.

¹⁰https://github.com/bfsujason/bertalign

¹¹https://www.gutenberg.org/

¹²https://commonvoice.mozilla.org/en

- Kosp2e (Cho et al., 2021) is a Korean (ko) to English(en) ST translation corpus, which contains Korean speech with parallel English texts. The corpus contains data from four different domains: *Zeroth* from news/newspaper, *KSS* (Park, 2018) from textbooks, emphStyleKQC (Cho et al., 2022) from AI applications, and *Covid-ED* (Lee et al., 2021) from covid diaries of people which have emotions.
- **BSTC** (Zhang et al., 2021) is a Baidu Speech Translation Corpus, a largescale Chinese-English speech translation dataset. This dataset is constructed based on a collection of licensed videos of talks or lectures, their manual transcripts, and translations into English, as well as automated transcripts by an automatic speech recognition (ASR) model.
- **GigaST** (Ye et al., 2022b) corpus is a collection of speech translations from English to German and Chinese. It is created using the English ASR GigaSpeech(Chen et al., 2021a), which features 10,000 hours of transcribed speech from various sources such as audioPortugesebooks, podcasts, and YouTube.
- **Prabhupadavani** (Sandhan et al., 2022) is an ST dataset where speech is *multilingual and Code-Mix* with three different languages, English is the primary language, and words and phrases from Sanskrit and Bengali are interjected. The text part has sentences in 25 languages.
- FLEURS (Conneau et al., 2022) FLEURS stands as a multilingual speech dataset, offering parallel recordings across 102 languages. Developed as an extension of the FLoRes-101 MT benchmark, it encompasses about 12 hours of annotated speech data for each language.
- Indic-TEDST Sethiya et al. (2024) is a low-resource ST translation dataset across 9 Indic languages: Bengali (bn), Gujarati (gu), Hindi (hi), Kannada (kn), Malayalam (ml), Marathi (mr), Punjabi (pa), Tamil (ta), and Telugu (te).

Besides these popular ST datasets, there are some other *smaller* size datasets such as *Fisher*(Cieri et al., 2004), *Call-Home*¹³, *Gordard Corpus*(Godard et al., 2018),

¹³https://ca.talkbank.org/access/CallHome/eng.html

*Glosse Audio Corpus*¹⁴, *BTEC*¹⁵, *WSJ*¹⁶, *IWSLT*¹⁷, *Miami Corpus*(Deuchar, 2008), and *MSLT Corpus* (Federmann and Lewis, 2016).

9.2. Toolkits for ST

To facilitate building and training ST models, various researchers have proposed a few toolkits. The toolkits for ST create an environment where the dataset for ST tasks can be pre-processed, and models can be trained, fine-tuned, and evaluated. We provide a short description of these toolkits to make the survey a place for a one-stop-shop for ST modeling.

- **SLT.KIT**¹⁸(Zenkel et al., 2018) offers ASR, MT and ST models along with some specific features such as CTC and Attention based ASR, ASR with punctuation and a neural MT system.
- EspNet-ST¹⁹ toolkit (Inaguma et al., 2020b) is developed as there was no toolkit available for performing the sub-tasks of ST. EspNet-ST provides ASR, LM, E2E-ST, Cascade-ST, MT, and TTS along with examples. It also provided pre-trained transformer-based models on various datasets like MUST-C, Libri-trans, Fisher, CALL-HOME, and How2.
- FairSeq S2T²⁰ (Wang et al., 2020b) toolkit is an extension to FairSeq(Ott et al., 2019) in which all the functions of EspNet-ST are available. Additionally, it provides the Non-Autoregressive MT, Online ST, and Speech Pretraining. The toolkit also provides state-of-the-art ST models based on RNN, transformers, and conformers. It has an in-built data loader for MuST-C, Librispeech, and CoVoST datasets.
- **NeurST**²¹ (Zhao et al., 2021) is a lightweight toolkit, as it has no dependency on kaldi toolkit (Zheng et al., 2011). It has high computation efficiency using mixed precision and accelerated linear algebra and achieves

¹⁴https://ainu.ninjal.ac.jp/folklore/en/ ¹⁵http://universal.elra.info/product_info.php?cPath=37_39& products_id=80 ¹⁶https://catalog.ldc.upenn.edu/LDC93s6a ¹⁷https://iwslt.org/ ¹⁸https://github.com/isl-mt/SLT.KIT ¹⁹https://github.com/espnet/espnet ²⁰https://github.com/facebookresearch/fairseq/tree/main/ examples/speech_to_text

²¹https://github.com/bytedance/neurst

faster training on large-scale datasets using Horovod (Sergeev and Balso, 2018).

10. Future Directions for Research

This section highlights challenges that need the attention of researchers working on ST problems.

10.1. Cascade vs End-to-End Models

As argued and presented through comprehensive experiments by (Bentivogli et al., 2021), the performance gaps between cascade and E2E ST models are bridged. However, as shown by (Agrawal et al., 2023) in a recent IWSLT 2023 subtitling generation task, the performance of cascade models is far superior to E2E models for offline ST tasks evaluated on all metrics. Furthermore, as far as our understanding, no thorough assessment has been done for low-resource languages that use E2E and cascade models. It may be interesting to compare E2E and cascade ST models on various ST datasets to assert the claims in the literature.

10.2. ST on Code-Mix data

We find that there exists limited study on the ST model that uses code-mix data as an input. A code-mix data has problems, such as different lexicons, syntax, and scarcity of labeled data. Therefore, it will be interesting to (a) create Code-Mix ST datasets incorporating more languages, (b) see how the existing ST models perform on code-mix ST data?, and (c) Can pre-training in many languages assist in tackling the code-mixing issue?

10.3. Domain-Invariant Models

ST models developed for one domain do not scale well to other domains, as shown in the recent IWSLT 2023. Here domain in-variance setting is the ST model which is trained in some language combination (say Eng-De) and needs to be adapted to other language combinations (e.g., Eng-Hi). Transfer learning/continual learning can be explored to develop generic models.

10.4. Discrepancy between Automatic and Human Evaluation

There may be discrepancies and disagreements among various metrics used to report ST task results. They do not match the mean option score (MOS) provided by human evaluators (Agrawal et al., 2023). For example, if a system evaluates the BLEU score between a ground truth sentence "*Police shot the culprit with a gun*"

and hypothesis sentence "*Police use a gun to shot the culprit*", it is 0! However, both sentences above might be deemed appropriate translations of an utterance *semantically* by an ST system. Such an argument is supported by dubbing artists who often change the voice of the sentence to simplify it or make it more pleasing. ²²

As highlighted in (Marie et al., 2021), the BLEU score is being reported by more than 99% of MT papers without accounting for statistical significance testing or human evaluation. Our survey of ST papers indicates the same trend being followed. Therefore, we call for the attention of researchers to develop and use metrics that match human evaluations semantically. An approach could be to subject the ground truth and hypothesis sentences under *semantic textual similarity* tasks and score them accordingly.

10.5. Handling Ambient Noise

In our literature survey, we find that little has been done to deal with ambient noises. Ambient noise, background music, cross-talk, and non-verbal sounds may create difficulty in ST model learning. The model must distinguish between a meaningful utterance and ambient noise– a non-trivial task.

10.6. Handling Multiple Speakers

It is common in the real world where the audio/video has multiple speakers, each of which may have its own accent (cf., An Asian and American talking to each other in English), dialect, pitch, and accent. Performing *speech separation* may be useful before feeding it to the ST model for improved performance.

10.7. Handling Speaker Diarization

Speaker diarization refers to demarcating the timing of speakers in a multiplespeaker speech. So far, the datasets for ST do not have speaker boundary marks. Creating speaker-diarized ST data in a multilingual setting will be interesting to test the ST models' robustness.

²²In the movie "Pirates of the Caribbean", Jack Sparrow asks Bloom how long he can go for the girl. The original answer from Bloom is "I can die for her!". Whereas Hindi dubbing is "Till the dying breadth"

10.8. Multilingual and Simultaneous ST

Multilingual ST has gained momentum recently due to its importance in the real world. For example, a single speech must be broadcast to multilingual communities (e.g., a conference is attended by a diverse group of people). It can be one-to-many, many-to-one, and many-to-many languages ST. Our literature survey shows that only a few works exist in this space. Besides, there is an opportunity to explore simultaneous multilingual ST, which is the most practical setting.

10.9. Low-resource ST Datasets and Models

Most existing works have focused on building ST models and datasets for high-resource languages. As we know, the success of ST models relies on the parallel speech-text corpus; building ST datasets for low-resource languages requires more attention. Further, a few works, such as (Bansal et al., 2019), have reported ST task results on the Mboshi-French pair; however, the BLEU score is poor. Therefore, building models that transfer learning from language pairs with high to low resources is warranted.

10.10. LLMs for ST tasks

In the last few years, large language models (LLMs) have emerged as a promising solution to many NLP tasks including ST. LLMs show in-context learning (ICL) when trained over a massive amount of data. This process unlocks their hidden *emergent abilities* (Wei et al., 2022) and enables them for few-shot and zero-shot learning capability via prompting. There exist a few works (Zhang et al., 2023b; Wu et al., 2023; Huang et al., 2023) (see (Gaido et al., 2024) for a comparative discussion) which explore LLMs for ST task. Concretely, all of these models leverage a speech foundation model (SLM) followed by length adapter, modality adaptation, mixing the two modalities, and then LLMs for generating the output. GenTranslate (Hu et al., 2024) builds upon the Seamless4MT by integrating an LLM on top and performing N-best hypothesis tuning. Initial results are plausible. However, it remains to see how various components affect the downstream task performance, what is the best strategy for prompt design, and how to pretrain/fine-tune them in a parameter-efficient way for ST tasks. Further, the use of LLMs for SimulMT has been recently proposed (Agostinelli et al., 2023) and it remains to see how to adapt SimulMT to SimulST.

10.11. Really long Context Modelling

As mentioned in the streaming section, SST models need to handle long input sequences. Current speech encoders lack infinite context modeling capability due to their quadratic complexity of self-attention. There have been recent improvements to handle the problem of infinite context. For example, Mamba (Zhang et al., 2024a), Infini-attention (Munkhdalai et al., 2024), and TransforerFAM (Hwang et al., 2024) show some promising results in long context modeling. These models may be explored for SST task as well.

11. Conclusion

This survey paper delves into the most recent advancements in E2E ST translation works. Our discussion includes models, evaluation metrics, and datasets used to train ST models. We review various frameworks for ST models and highlight previous research in this field. The categorization of ST models is based on the kind of data they handle and the models employed. Additionally, we discuss potential future directions for improving speech-to-text translation. Our findings suggest that the gap between cascade and E2E system performance in both online and offline settings is narrowing. However, for some language pairs, the gap is still wide and therefore, additional work is warranted. Our goal in the present ST survey is to offer valuable insight into this topic and drive advancements in ST research. We believe that such reviews will be interesting to researchers.

References

- Abbott, L.F., 1999. Lapicque's introduction of the integrate-and-fire model neuron (1907). Brain Research Bulletin 50, 303–304.
- Agostinelli, V., Wild, M., Raffel, M., Fuad, K.A.A., Chen, L., 2023. Simul-Ilm: A framework for exploring high-quality simultaneous translation with large language models. ArXiv abs/2312.04691.
- Agrawal, S., Anastasopoulos, A., Bentivogli, L., Bojar, O., Borg, C., Carpuat, M., Cattoni, R., Cettolo, M., Chen, M., Chen, W., Choukri, K., Chronopoulou, A., Currey, A., Declerck, T., Dong, Q., Duh, K., Estève, Y., Federico, M., Gahbiche, S., Haddow, B., Hsu, B., Mon Htut, P., Inaguma, H., Javorský, D., Judge, J., Kano, Y., Ko, T., Kumar, R., Li, P., Ma, X., Mathur, P., Matusov, E., McNamee, P., P. McCrae, J., Murray, K., Nadejde, M., Nakamura, S., Negri, M., Nguyen, H., Niehues, J., Niu, X., Kr. Ojha, A., E. Ortega, J., Pal, P., Pino,

J., van der Plas, L., Polák, P., Rippeth, E., Salesky, E., Shi, J., Sperber, M., Stüker, S., Sudoh, K., Tang, Y., Thompson, B., Tran, K., Turchi, M., Waibel, A., Wang, M., Watanabe, S., Zevallos, R., 2023. FINDINGS OF THE IWSLT 2023 EVALUATION CAMPAIGN, in: Proceedings of the 20th International Conference on Spoken Language Translation (IWSLT 2023), Association for Computational Linguistics, Toronto, Canada (in-person and online). pp. 1–61.

- Alastruey, B., Ferrando, J., Gállego, G.I., Costa-jussà, M.R., 2022. On the locality of attention in direct speech translation, in: Louvan, S., Madotto, A., Madureira, B. (Eds.), Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics: Student Research Workshop, Association for Computational Linguistics, Dublin, Ireland. pp. 402–412. doi:10.18653/ v1/2022.acl-srw.32.
- Anastasopoulos, A., Chiang, D., 2018. Tied multitask learning for neural speech translation, in: Walker, M., Ji, H., Stent, A. (Eds.), Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), Association for Computational Linguistics, New Orleans, Louisiana. pp. 82–91. doi:10.18653/v1/N18-1008.
- Anastasopoulos, A., Chiang, D., Duong, L., 2016. An unsupervised probability model for speech-to-translation alignment of low-resource languages, in: Su, J., Duh, K., Carreras, X. (Eds.), Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, Association for Computational Linguistics, Austin, Texas. pp. 1255–1263. doi:10.18653/v1/D16-1133.
- Ao, J., Wang, R., Zhou, L., Wang, C., Ren, S., Wu, Y., Liu, S., Ko, T., Li, Q., Zhang, Y., et al., 2021. Speecht5: Unified-modal encoder-decoder pre-training for spoken language processing. arXiv preprint arXiv:2110.07205.
- Arivazhagan, N., Cherry, C., I, T., Macherey, W., Baljekar, P.N., Foster, G.F., 2019a. Re-translation strategies for long form, simultaneous, spoken language translation. ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7919–7923.
- Arivazhagan, N., Cherry, C., Macherey, W., Chiu, C.C., Yavuz, S., Pang, R., Li, W., Raffel, C., 2019b. Monotonic infinite lookback attention for simultaneous machine translation, in: Annual Meeting of the Association for Computational Linguistics.

- Arivazhagan, N., Cherry, C., Macherey, W., Foster, G.F., 2020. Re-translation versus streaming for simultaneous translation, in: International Workshop on Spoken Language Translation.
- Baevski, A., Hsu, W.N., Xu, Q., Babu, A., Gu, J., Auli, M., 2022. Data2vec: A general framework for self-supervised learning in speech, vision and language, in: International Conference on Machine Learning, PMLR. pp. 1298–1312.
- Baevski, A., Zhou, H., Mohamed, A., Auli, M., 2020. wav2vec 2.0: a framework for self-supervised learning of speech representations, in: Proceedings of the 34th International Conference on Neural Information Processing Systems, Curran Associates Inc., Red Hook, NY, USA.
- Bahar, P., Bieschke, T., Ney, H., 2019a. A comparative study on end-to-end speech to text translation, in: 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), IEEE. pp. 792–799.
- Bahar, P., Wilken, P., Alkhouli, T., Guta, A., Golik, P., Matusov, E., Herold, C., 2020. Start-before-end and end-to-end: Neural speech translation by apptek and rwth aachen university, in: International Workshop on Spoken Language Translation.
- Bahar, P., Zeyer, A., Schlüter, R., Ney, H., 2019b. On using SpecAugment for end-to-end speech translation, in: Niehues, J., Cattoni, R., Stüker, S., Negri, M., Turchi, M., Ha, T.L., Salesky, E., Sanabria, R., Barrault, L., Specia, L., Federico, M. (Eds.), Proceedings of the 16th International Conference on Spoken Language Translation, Association for Computational Linguistics, Hong Kong.
- Banerjee, S., Lavie, A., 2005. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments, in: Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization, pp. 65–72.
- Bansal, S., Kamper, H., Livescu, K., Lopez, A., Goldwater, S., 2019. Pretraining on high-resource speech recognition improves low-resource speech-totext translation, in: Burstein, J., Doran, C., Solorio, T. (Eds.), Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and

Short Papers), Association for Computational Linguistics, Minneapolis, Minnesota. pp. 58–68. doi:10.18653/v1/N19-1006.

- Bansal, S., Kamper, H., Lopez, A., Goldwater, S., 2017. Towards speech-to-text translation without speech recognition, in: Lapata, M., Blunsom, P., Koller, A. (Eds.), Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers, Association for Computational Linguistics, Valencia, Spain. pp. 474–479.
- Bapna, A., Chung, Y.A., Wu, N., Gulati, A., Jia, Y., Clark, J., Johnson, M., Riesa, J., Conneau, A., Zhang, Y., 2021. Slam: A unified encoder for speech and language modeling via speech-text joint pre-training. ArXiv abs/2110.10329.
- Barrault, L., Chung, Y.A., Meglioli, M.C., Dale, D., Dong, N., Duquenne, P.A., ElSahar, H., Gong, H., Heffernan, K., Hoffman, J., Klaiber, C., Li, P., Licht, D., Maillard, J., Rakotoarison, A., Sadagopan, K.R., Wenzek, G., Ye, E., Akula, B., Chen, P.J., Hachem, N.E., Ellis, B., Gonzalez, G.M., Haaheim, J., Hansanti, P., Howes, R., Huang, B., Hwang, M.J., Inaguma, H., Jain, S., Kalbassi, E., Kallet, A., Kulikov, I., Lam, J., Li, S.W., Ma, X., Mavlyutov, R., Peloquin, B., Ramadan, M., Ramakrishnan, A., Sun, A., Tran, K.M., Tran, T., Tufanov, I., Vogeti, V., Wood, C., Yang, Y., Yu, B., Andrews, P.Y., Balioglu, C., Costajussà, M.R., Çelebi, O., Elbayad, M., Gao, C., Guzm'an, F., Kao, J.T., Lee, A., Mourachko, A., Pino, J.M., Popuri, S., Ropers, C., Saleem, S., Schwenk, H., Tomasello, P., Wang, C., Wang, J., Wang, S., 2023. Seamlessm4t: Massively multilingual&multimodal machine translation.
- Bentivogli, L., Cettolo, M., Gaido, M., Karakanta, A., Martinelli, A., Negri, M., Turchi, M., 2021. Cascade versus direct speech translation: Do the differences still make a difference?, in: Annual Meeting of the Association for Computational Linguistics.
- Bérard, A., Besacier, L., Kocabiyikoglu, A.C., Pietquin, O., 2018. End-to-end automatic speech translation of audiobooks, in: 2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 6224– 6228.
- Bérard, A., Pietquin, O., Besacier, L., Servan, C., 2016. Listen and Translate: A Proof of Concept for End-to-End Speech-to-Text Translation, in: NIPS Workshop on end-to-end learning for speech and audio processing, Barcelona, Spain.

- Bozinovski, S., Fulgosi, A., 1976. The influence of pattern similarity and transfer learning upon training of a base perceptron b2, in: Proceedings of Symposium Informatica, pp. 121–126.
- Brauwers, G., Frasincar, F., 2022. A general survey on attention mechanisms in deep learning. IEEE Transactions on Knowledge and Data Engineering 35, 3279–3298.
- Bucilă, C., Caruana, R., Niculescu-Mizil, A., 2006. Model compression. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining 2006, 535–541. doi:10.1145/1150402.1150464.
- Cattoni, R., Di Gangi, M.A., Bentivogli, L., Negri, M., Turchi, M., 2021. Must-c: A multilingual corpus for end-to-end speech translation. Computer speech & language 66, 101155.
- Chang, C.C., yi Lee, H., 2022. Exploring continuous integrate-and-fire for adaptive simultaneous speech translation. ArXiv abs/2204.09595.
- Chen, G., Chai, S., Wang, G., Du, J., Zhang, W.Q., Weng, C., Su, D., Povey, D., Trmal, J., Zhang, J., et al., 2021a. Gigaspeech: An evolving, multidomain asr corpus with 10,000 hours of transcribed audio. arXiv preprint arXiv:2106.06909.
- Chen, J., Ma, M., Zheng, R., Huang, L., 2020. Mam: Masked acoustic modeling for end-to-end speech-to-text translation. arXiv preprint arXiv:2010.11445.
- Chen, J., Ma, M., Zheng, R., Huang, L., 2021b. Direct simultaneous speech-totext translation assisted by synchronized streaming ASR, in: Zong, C., Xia, F., Li, W., Navigli, R. (Eds.), Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, Association for Computational Linguistics, Online. pp. 4618–4624. doi:10.18653/v1/2021.findings-acl.406.
- Chen, S., Wang, C., Chen, Z., Wu, Y., Liu, S., Chen, Z., Li, J., Kanda, N., Yoshioka, T., Xiao, X., Wu, J., Zhou, L., Ren, S., Qian, Y., Qian, Y., Wu, J., Zeng, M., Yu, X., Wei, F., 2022. Wavlm: Large-scale self-supervised pre-training for full stack speech processing. IEEE Journal of Selected Topics in Signal Processing 16, 1505–1518. doi:10.1109/JSTSP.2022.3188113.

- Cheng, X., Dong, Q., Yue, F., Ko, T., Wang, M., Zou, Y., 2022. M3st: Mix at three levels for speech translation. ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 1–5.
- Cherry, C., Foster, G.F., 2019. Thinking slow about latency evaluation for simultaneous machine translation. ArXiv abs/1906.00048.
- Chiu, C.C., Raffel, C., 2018. Monotonic chunkwise attention, in: International Conference on Learning Representations.
- Cho, K., Esipova, M., 2016a. Can neural machine translation do simultaneous translation? arXiv preprint arXiv:1606.02012.
- Cho, K., Esipova, M., 2016b. Can neural machine translation do simultaneous translation? ArXiv abs/1606.02012.
- Cho, W.I., Kim, S.M., Cho, H., Kim, N.S., 2021. kosp2e: Korean Speech to English Translation Corpus, in: Proc. Interspeech 2021, pp. 3705–3709. doi:10.21437/Interspeech.2021-1040.
- Cho, W.I., Moon, S., Kim, J., Kim, S., Kim, N.S., 2022. StyleKQC: A stylevariant paraphrase corpus for Korean questions and commands, in: Calzolari, N., Béchet, F., Blache, P., Choukri, K., Cieri, C., Declerck, T., Goggi, S., Isahara, H., Maegaard, B., Mariani, J., Mazo, H., Odijk, J., Piperidis, S. (Eds.), Proceedings of the Thirteenth Language Resources and Evaluation Conference, European Language Resources Association, Marseille, France. pp. 7122–7128.
- Chopra, S., Hadsell, R., LeCun, Y., 2005. Learning a similarity metric discriminatively, with application to face verification, in: 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05), IEEE. pp. 539–546.
- Chuang, S.P., Chuang, Y.S., Chang, C.C., Lee, H.y., 2021. Investigating the reordering capability in CTC-based non-autoregressive end-to-end speech translation, in: Zong, C., Xia, F., Li, W., Navigli, R. (Eds.), Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, Association for Computational Linguistics, Online. pp. 1068–1077. doi:10.18653/v1/2021. findings-acl.92.

- Chung, Y.A., Glass, J., 2018. Speech2Vec: A Sequence-to-Sequence Framework for Learning Word Embeddings from Speech, in: Proc. Interspeech 2018, pp. 811–815. doi:10.21437/Interspeech.2018–2341.
- Chung, Y.A., Zhang, Y., Han, W., Chiu, C.C., Qin, J., Pang, R., Wu, Y., 2021. w2v-bert: Combining contrastive learning and masked language modeling for self-supervised speech pre-training. 2021 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), 244–250.
- Cieri, C., Miller, D., Walker, K., 2004. The fisher corpus: A resource for the next generations of speech-to-text., in: LREC, pp. 69–71.
- Conneau, A., Kruszewski, G., Lample, G., Barrault, L., Baroni, M., 2018. What you can cram into a single vector: Probing sentence embeddings for linguistic properties. arXiv preprint arXiv:1805.01070.
- Conneau, A., Lample, G., 2019. Cross-lingual language model pretraining. Curran Associates Inc., Red Hook, NY, USA.
- Conneau, A., Ma, M., Khanuja, S., Zhang, Y., Axelrod, V., Dalmia, S., Riesa, J., Rivera, C., Bapna, A., 2022. Fleurs: Few-shot learning evaluation of universal representations of speech, in: 2022 IEEE Spoken Language Technology Workshop, SLT 2022 Proceedings, IEEE. pp. 798–805. doi:10.1109/ SLT54892.2023.10023141.
- Cui, X., Goel, V., Kingsbury, B., 2015. Data augmentation for deep neural network acoustic modeling. IEEE/ACM Transactions on Audio, Speech, and Language Processing 23, 1469–1477.
- Dalvi, F., Durrani, N., Sajjad, H., Vogel, S., 2018. Incremental decoding and training methods for simultaneous translation in neural machine translation, in: Walker, M., Ji, H., Stent, A. (Eds.), Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers), Association for Computational Linguistics, New Orleans, Louisiana. pp. 493–499. URL: https://aclanthology.org/N18-2079, doi:10.18653/v1/N18-2079.
- Deuchar, M., 2008. The miami corpus: Documentation file. Bangortalk, bangortalk. org. uk/docs/Miami_doc. pdf.

- Dong, L., Xu, B., 2019. Cif: Continuous integrate-and-fire for end-to-end speech recognition. ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 6079–6083.
- Dong, Q., Wang, M., Zhou, H., Xu, S., Xu, B., Li, L., 2020. Consecutive decoding for speech-to-text translation, in: AAAI Conference on Artificial Intelligence.
- Dong, Q., Ye, R., Wang, M., Zhou, H., Xu, S., Xu, B., Li, L., 2021. Listen, understand and translate: Triple supervision decouples end-to-end speech-to-text translation, in: AAAI Conference on Artificial Intelligence.
- Dong, Q., Zhu, Y., Wang, M., Li, L., 2022. Learning when to translate for streaming speech, in: Muresan, S., Nakov, P., Villavicencio, A. (Eds.), Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Dublin, Ireland. pp. 680–694. doi:10.18653/v1/2022.acl-long.50.
- Duong, L., Anastasopoulos, A., Chiang, D., Bird, S., Cohn, T., 2016. An attentional model for speech translation without transcription, in: Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pp. 949–959.
- Etchegoyhen, T., Arzelus, H., Gete, H., Alvarez, A., Torre, I.G., Martín-Doñas, J.M., González-Docasal, A., Fernandez, E.B., 2022. Cascade or direct speech translation? a case study. Applied Sciences 12, 1097.
- Fang, Q., Feng, Y., 2023. Back translation for speech-to-text translation without transcripts, in: Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics.
- Fang, Q., Ye, R., Li, L., Feng, Y., Wang, M., 2022. STEMM: Self-learning with speech-text manifold mixup for speech translation, in: Muresan, S., Nakov, P., Villavicencio, A. (Eds.), Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Dublin, Ireland. pp. 7050–7062. doi:10.18653/v1/2022.acl-long.486.
- Federmann, C., Lewis, W., 2016. Microsoft speech language translation (mslt) corpus: The iwslt 2016 release for english, french and german, in: Proceedings of the 13th International Conference on Spoken Language Translation.

- Fügen, C., Waibel, A.H., Kolss, M., 2007. Simultaneous translation of lectures and speeches. Machine Translation 21, 209–252.
- Gaido, M., Di Gangi, M.A., Negri, M., Turchi, M., 2020a. End-to-end speech-translation with knowledge distillation: FBK@IWSLT2020, in: Federico, M., Waibel, A., Knight, K., Nakamura, S., Ney, H., Niehues, J., Stüker, S., Wu, D., Mariani, J., Yvon, F. (Eds.), Proceedings of the 17th International Conference on Spoken Language Translation, Association for Computational Linguistics, Online. pp. 80–88. doi:10.18653/v1/2020.iwslt-1.8.
- Gaido, M., Gangi, M.A.D., Negri, M., Turchi, M., 2020b. On knowledge distillation for direct speech translation. ArXiv abs/2012.04964.
- Gaido, M., Negri, M., Cettolo, M., Turchi, M., 2021. Beyond voice activity detection: Hybrid audio segmentation for direct speech translation, in: International Conference on Natural Language and Speech Processing.
- Gaido, M., Papi, S., Negri, M., Bentivogli, L., 2024. Speech translation with speech foundation models and large language models: What is there and what is missing? ArXiv abs/2402.12025.
- Gállego, G.I., Tsiamas, I., Escolano, C., Fonollosa, J.A.R., Costa-jussà, M.R., 2021. End-to-end speech translation with pre-trained models and adapters: Upc at iwslt 2021, in: Proceedings of the 18th International Conference on Spoken Language Translation (IWSLT 2021), Association for Computational Linguistics, Bangkok, Thailand (online). pp. 110–119. doi:10.18653/v1/2021. iwslt-1.11.
- Gangi, M.A.D., Negri, M., Turchi, M., 2019. One-to-many multilingual end-toend speech translation. 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), 585–592.
- Godard, P., Adda, G., Adda-Decker, M., Benjumea, J., Besacier, L., Cooper-Leavitt, J., Kouarata, G.N., Lamel, L., Maynard, H., Mueller, M., Rialland, A., Stueker, S., Yvon, F., Zanon-Boito, M., 2018. A very low resource language speech corpus for computational language documentation experiments, in: Calzolari, N., Choukri, K., Cieri, C., Declerck, T., Goggi, S., Hasida, K., Isahara, H., Maegaard, B., Mariani, J., Mazo, H., Moreno, A., Odijk, J., Piperidis, S., Tokunaga, T. (Eds.), Proceedings of the Eleventh International Conference on

Language Resources and Evaluation (LREC 2018), European Language Resources Association (ELRA), Miyazaki, Japan.

- Goldman-Eisler, F., 1972. Segmentation of input in simultaneous translation. Journal of Psycholinguistic Research 1, 127–140.
- Graves, A., 2012. Sequence transduction with recurrent neural networks. ArXiv abs/1211.3711.
- Graves, A., Fernández, S., Gomez, F., Schmidhuber, J., 2006. Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks, in: Proceedings of the 23rd International Conference on Machine Learning, Association for Computing Machinery, New York, NY, USA. p. 369–376.
- Grissom II, A., He, H., Boyd-Graber, J., Morgan, J., Daumé III, H., 2014. Don't until the final verb wait: Reinforcement learning for simultaneous machine translation, in: Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), Association for Computational Linguistics, Doha, Qatar. pp. 1342–1352. doi:10.3115/v1/D14–1140.
- Gulati, A., Qin, J., Chiu, C.C., Parmar, N., Zhang, Y., Yu, J., Han, W., Wang, S., Zhang, Z., Wu, Y., Pang, R., 2020. Conformer: Convolution-augmented Transformer for Speech Recognition, in: Proc. Interspeech 2020, pp. 5036– 5040. doi:10.21437/Interspeech.2020-3015.
- Guo, J., Wu, Z., Li, Z., Shang, H., Wei, D., Chen, X., Rao, Z., Li, S., Yang, H., 2024. R-bi: Regularized batched inputs enhance incremental decoding framework for low-latency simultaneous speech translation. ArXiv abs/2401.05700.
- Han, C., Wang, M., Ji, H., Li, L., 2021. Learning shared semantic space for speech-to-text translation, in: Findings of the Association for Computational Linguistics: ACL-IJCNLP.
- Hinton, G., Vinyals, O., Dean, J., 2015. Distilling the knowledge in a neural network URL: https://arxiv.org/abs/1503.02531v1.
- Houlsby, N., Giurgiu, A., Jastrzebski, S., Morrone, B., De Laroussilhe, Q., Gesmundo, A., Attariyan, M., Gelly, S., 2019. Parameter-efficient transfer learning for nlp, in: International Conference on Machine Learning, PMLR. pp. 2790– 2799.

- Hsu, W.N., Bolte, B., Tsai, Y.H.H., Lakhotia, K., Salakhutdinov, R., Mohamed, A., 2021. Hubert: Self-supervised speech representation learning by masked prediction of hidden units. IEEE/ACM Transactions on Audio, Speech, and Language Processing 29, 3451–3460.
- Hu, Y., Chen, C., Yang, C.H.H., Li, R., Zhang, D., Chen, Z., Chng, E.S., 2024. Gentranslate: Large language models are generative multilingual speech and machine translators. ArXiv abs/2402.06894.
- Huang, Z., Ye, R., Ko, T., Dong, Q., Cheng, S., Wang, M., Li, H., 2023. Speech translation with large language models: An industrial practice. ArXiv abs/2312.13585.
- Huzaifah, M., Kukanov, I., 2023. An analysis of semantically-aligned speech-text embeddings, in: 2022 IEEE Spoken Language Technology Workshop (SLT), IEEE. pp. 747–754.
- Hwang, D., Wang, W., Huo, Z., Sim, K.C., Mengibar, P.M., 2024. Transformerfam: Feedback attention is working memory. arXiv:2404.09173.
- Inaguma, H., Duh, K., Kawahara, T., Watanabe, S., 2019. Multilingual end-to-end speech translation. 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), 570–577.
- Inaguma, H., Higuchi, Y., Duh, K., Kawahara, T., Watanabe, S., 2020a. Orthros: non-autoregressive end-to-end speech translation with dual-decoder. ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7503–7507.
- Inaguma, H., Higuchi, Y., Duh, K., Kawahara, T., Watanabe, S., 2021. Non-autoregressive end-to-end speech translation with parallel autoregressive rescoring. ArXiv abs/2109.04411. URL: https://api. semanticscholar.org/CorpusID:237453587.
- Inaguma, H., Kiyono, S., Duh, K., Karita, S., Yalta, N., Hayashi, T., Watanabe, S., 2020b. ESPnet-ST: All-in-one speech translation toolkit, in: Celikyilmaz, A., Wen, T.H. (Eds.), Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: System Demonstrations, Association for Computational Linguistics, Online. pp. 302–311. doi:10.18653/v1/2020. acl-demos.34.

- Iranzo-S'anchez, J., Saiz, J.C., Juan, A., 2022. From simultaneous to streaming machine translation by leveraging streaming history, in: Annual Meeting of the Association for Computational Linguistics.
- Iranzo-Sánchez, J., Silvestre-Cerda, J.A., Jorge, J., Roselló, N., Giménez, A., Sanchis, A., Civera, J., Juan, A., 2020. Europarl-st: A multilingual corpus for speech translation of parliamentary debates, in: ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 8229–8233.
- Jaegle, A., Gimeno, F., Bfrock, A., Zisserman, A., Vinyals, O., Carreira, J., 2021. Perceiver: General perception with iterative attention. CoRR abs/2103.03206. URL: https://arxiv.org/abs/2103.03206, arXiv:2103.03206.
- Jia, Y., Johnson, M., Macherey, W., Weiss, R.J., Cao, Y., Chiu, C.C., Ari, N., Laurenzo, S., Wu, Y., 2019. Leveraging weakly supervised data to improve endto-end speech-to-text translation, in: ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 7180–7184.
- Jurafsky, D., Martin, J.H., 2008. Speech and language processing, 2nd edition.
- Kahn, J., Rivière, M., Zheng, W., Kharitonov, E., Xu, Q., Mazar'e, P.E., Karadayi, J., Liptchinsky, V., Collobert, R., Fuegen, C., Likhomanenko, T., Synnaeve, G., Joulin, A., rahman Mohamed, A., Dupoux, E., 2019. Libri-light: A benchmark for asr with limited or no supervision. ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7669–7673.
- Kano, Y., Sudoh, K., Nakamura, S., 2023. Average token delay: A duration-aware latency metric for simultaneous translation. ArXiv abs/2311.14353.
- Khurana, S., Laurent, A., Glass, J., 2020. Cstnet: Contrastive speech translation network for self-supervised speech representation learning. arXiv preprint arXiv:2006.02814.
- Kim, S., Hori, T., Watanabe, S., 2017. Joint ctc-attention based end-to-end speech recognition using multi-task learning, in: 2017 IEEE international conference on acoustics, speech and signal processing (ICASSP), IEEE. pp. 4835–4839.

- Kocabiyikoglu, A.C., Besacier, L., Kraif, O., 2018. Augmenting librispeech with French translations: A multimodal corpus for direct speech translation evaluation, in: Calzolari, N., Choukri, K., Cieri, C., Declerck, T., Goggi, S., Hasida, K., Isahara, H., Maegaard, B., Mariani, J., Mazo, H., Moreno, A., Odijk, J., Piperidis, S., Tokunaga, T. (Eds.), Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018), European Language Resources Association (ELRA), Miyazaki, Japan.
- Lam, T.K., Birch, A., Haddow, B., 2024. Compact speech translation models via discrete speech units pretraining. ArXiv abs/2402.19333.
- Lam, T.K., Schamoni, S., Riezler, S., 2020. Cascaded models with cyclic feedback for direct speech translation. ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7508–7512.
- Lam, T.K., Schamoni, S., Riezler, S., 2022a. Make more of your data: Minimal effort data augmentation for automatic speech recognition and translation. ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 1–5.
- Lam, T.K., Schamoni, S., Riezler, S., 2022b. Sample, translate, recombine: Leveraging audio alignments for data augmentation in end-to-end speech translation, in: Annual Meeting of the Association for Computational Linguistics.
- Larochelle, H., Hinton, G.E., 2010. Learning to combine foveal glimpses with a third-order boltzmann machine, in: Neural Information Processing Systems.
- Le, C., Qian, Y., Zhou, L., LIU, S., Qian, Y., Zeng, M., Huang, X., 2023a. ComSL: A composite speech-language model for end-to-end speech-to-text translation, in: Thirty-seventh Conference on Neural Information Processing Systems. URL: https://openreview.net/forum?id=6Qx7G1xrAk.
- Le, H., Pino, J., Wang, C., Gu, J., Schwab, D., Besacier, L., 2020. Dual-decoder transformer for joint automatic speech recognition and multilingual speech translation, in: Scott, D., Bel, N., Zong, C. (Eds.), Proceedings of the 28th International Conference on Computational Linguistics, International Committee on Computational Linguistics, Barcelona, Spain (Online). pp. 3520–3533. doi:10.18653/v1/2020.coling-main.314.
- Le, H., Pino, J., Wang, C., Gu, J., Schwab, D., Besacier, L., 2021. Lightweight adapter tuning for multilingual speech translation, in: Zong, C., Xia, F., Li, W.,

Navigli, R. (Eds.), Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers), Association for Computational Linguistics, Online.

- Le, P.H., Gong, H., Wang, C., Pino, J., Lecouteux, B., Schwab, D., 2023b. Pretraining for speech translation: Ctc meets optimal transport, in: Proceedings of the 40th International Conference on Machine Learning, JMLR.org.
- Lee, Y.K., Jung, Y., Lee, I., Park, J.E., Hahn, S., 2021. Building a psychological ground truth dataset with empathy and theory-of-mind during the covid-19 pandemic, in: Proceedings of the Annual Meeting of the Cognitive Science Society.
- Li, X., Wang, C., Tang, Y., Tran, C., Tang, Y., Pino, J.M., Baevski, A., Conneau, A., Auli, M., 2020. Multilingual speech translation from efficient finetuning of pretrained models, in: Annual Meeting of the Association for Computational Linguistics.
- Lin, J., 1991. Divergence measures based on the shannon entropy. IEEE Transactions on Information theory 37, 145–151.
- Liu, D., Du, M., Li, X., Li, Y., Chen, E., 2021a. Cross attention augmented transducer networks for simultaneous translation, in: Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pp. 39–55.
- Liu, D., Spanakis, G., Niehues, J., 2020a. Low-latency sequence-to-sequence speech recognition and translation by partial hypothesis selection, in: Interspeech.
- Liu, X.B., Zhang, J., Ferrer, L., Xu, S., Bahirwani, V., Smus, B., Olwal, A., Du, R., 2023. Modeling and improving text stability in live captions. Extended Abstracts of the 2023 CHI Conference on Human Factors in Computing Systems
- Liu, Y., Gu, J., Goyal, N., Li, X., Edunov, S., Ghazvininejad, M., Lewis, M., Zettlemoyer, L., 2020b. Multilingual denoising pre-training for neural machine translation. Transactions of the Association for Computational Linguistics 8, 726–742.

- Liu, Y., Gu, J., Goyal, N., Li, X., Edunov, S., Ghazvininejad, M., Lewis, M., Zettlemoyer, L., 2020c. Multilingual denoising pre-training for neural machine translation. Transactions of the Association for Computational Linguistics 8, 726–742.
- Liu, Y., Xiong, H., Zhang, J., He, Z., Wu, H., Wang, H., Zong, C., 2019. Endto-End Speech Translation with Knowledge Distillation, in: Proc. Interspeech 2019, pp. 1128–1132. doi:10.21437/Interspeech.2019-2582.
- Liu, Y., Zhu, J., Zhang, J., Zong, C., 2020d. Bridging the modality gap for speechto-text translation. arXiv preprint arXiv:2010.14920.
- Liu, Z., Lin, Y., Sun, M., 2021b. Representation learning for natural language processing. CoRR abs/2102.03732. URL: https://arxiv.org/abs/ 2102.03732, arXiv:2102.03732.
- Ma, M., Huang, L., Xiong, H., Zheng, R., Liu, K., Zheng, B., Zhang, C., He, Z., Liu, H., Li, X., Wu, H., Wang, H., 2018. Stacl: Simultaneous translation with implicit anticipation and controllable latency using prefix-to-prefix framework, in: Annual Meeting of the Association for Computational Linguistics.
- Ma, X., Dousti, M.J., Wang, C., Gu, J., Pino, J.M., 2020a. Simuleval: An evaluation toolkit for simultaneous translation, in: Conference on Empirical Methods in Natural Language Processing.
- Ma, X., Pino, J., Koehn, P., 2020b. SimulMT to SimulST: Adapting simultaneous text translation to end-to-end simultaneous speech translation, in: Wong, K.F., Knight, K., Wu, H. (Eds.), Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing, Association for Computational Linguistics, Suzhou, China. pp. 582–587.
- Ma, X., Pino, J.M., Cross, J., Puzon, L., Gu, J., 2019. Monotonic multihead attention. ICLR abs/1909.12406.
- Ma, X., Sun, A.Y., Ouyang, S., Inaguma, H., Tomasello, P., 2023. Efficient monotonic multihead attention. ArXiv abs/2312.04515.
- Ma, X., Wang, Y., Dousti, M.J., Koehn, P., Pino, J.M., 2020c. Streaming simultaneous speech translation with augmented memory transformer. ICASSP

2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7523–7527.

- Marie, B., Fujita, A., Rubino, R., 2021. Scientific credibility of machine translation research: A meta-evaluation of 769 papers, in: Zong, C., Xia, F., Li, W., Navigli, R. (Eds.), Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), Association for Computational Linguistics, Online. pp. 7297–7306. doi:10.18653/v1/2021. acl-long.566.
- Matusov, E., Hillard, D., Magimai-Doss, M., Hakkani-Tür, D.Z., Ostendorf, M., Ney, H., 2007. Improving speech translation with automatic boundary prediction, in: Interspeech.
- Matusov, E., Wilken, P., Bahar, P., Schamper, J., Golik, P., Zeyer, A., Silvestre-Cerdà, J.A., Martinez-Villaronga, A.A., Pesch, H., Peter, J.T., 2018. Neural speech translation at apptek, in: International Workshop on Spoken Language Translation.
- Meng, L., Xu, J., Tan, X., Wang, J., Qin, T., Xu, B., 2021. Mixspeech: Data augmentation for low-resource automatic speech recognition. ICASSP 2021 -2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 7008–7012.
- Mnih, V., Heess, N.M.O., Graves, A., Kavukcuoglu, K., 2014. Recurrent models of visual attention, in: Neural Information Processing Systems.
- Mohamed, A., Lee, H.y., Borgholt, L., Havtorn, J.D., Edin, J., Igel, C., Kirchhoff, K., Li, S.W., Livescu, K., Maaloe, L., Sainath, T.N., Watanabe, S., 2022. Selfsupervised speech representation learning: A review. IEEE Journal of Selected Topics in Signal Processing 16, 1179–1210. doi:10.1109/jstsp.2022. 3207050.
- Munkhdalai, T., Faruqui, M., Gopal, S., 2024. Leave no context behind: Efficient infinite context transformers with infini-attention. arXiv:2404.07143.
- Nguyen, T.S., Stüker, S., Waibel, A., 2021. Super-Human Performance in Online Low-Latency Recognition of Conversational Speech, in: Proc. Interspeech 2021, pp. 1762–1766. doi:10.21437/Interspeech.2021-1114.

- Niehues, J., Nguyen, T.S., Cho, E., Ha, T.L., Kilgour, K., Müller, M., Sperber, M., Stüker, S., Waibel, A.H., 2016. Dynamic transcription for low-latency speech translation, in: Interspeech.
- Niehues, J., Pham, N.Q., Ha, T.L., Sperber, M., Waibel, A., 2018. Low-Latency Neural Speech Translation, in: Proc. Interspeech 2018, pp. 1293–1297. doi:10.21437/Interspeech.2018–1055.
- Ochshorn, R., Hawkins, M., 2017. Gentle forced aligner. github. com/lowerquality/gentle.
- Oda, Y., Neubig, G., Sakti, S., Toda, T., Nakamura, S., 2014. Optimizing segmentation strategies for simultaneous speech translation, in: Annual Meeting of the Association for Computational Linguistics.
- van den Oord, A., Vinyals, O., Kavukcuoglu, K., 2017. Neural discrete representation learning, in: Proceedings of the 31st International Conference on Neural Information Processing Systems, Curran Associates Inc., Red Hook, NY, USA. p. 6309–6318.
- Ott, M., Edunov, S., Baevski, A., Fan, A., Gross, S., Ng, N., Grangier, D., Auli, M., 2019. fairseq: A fast, extensible toolkit for sequence modeling. arXiv preprint arXiv:1904.01038.
- Ouyang, S., Ye, R., Li, L., 2023. WACO: Word-aligned contrastive learning for speech translation, in: Rogers, A., Boyd-Graber, J., Okazaki, N. (Eds.), Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Toronto, Canada. pp. 3891–3907. doi:10.18653/v1/2023.acl-long. 216.
- Panayotov, V., Chen, G., Povey, D., Khudanpur, S., 2015. Librispeech: an asr corpus based on public domain audio books, in: 2015 IEEE international conference on acoustics, speech and signal processing (ICASSP), IEEE. pp. 5206– 5210.
- Papi, S., Gaido, M., Negri, M., Turchi, M., 2021a. Speechformer: Reducing information loss in direct speech translation, in: Conference on Empirical Methods in Natural Language Processing.

- Papi, S., Gaido, M., Negri, M., Turchi, M., 2022a. Over-generation cannot be rewarded: Length-adaptive average lagging for simultaneous speech translation, in: Ive, J., Zhang, R. (Eds.), Proceedings of the Third Workshop on Automatic Simultaneous Translation, Association for Computational Linguistics, Online. pp. 12–17. doi:10.18653/v1/2022.autosimtrans-1.2.
- Papi, S., Negri, M., Turchi, M., 2021b. Visualization: The missing factor in simultaneous speech translation. ArXiv abs/2111.00514.
- Papi, S., Negri, M., Turchi, M., 2022b. Attention as a guide for simultaneous speech translation, in: Annual Meeting of the Association for Computational Linguistics.
- Papineni, K., Roukos, S., Ward, T., Zhu, W.J., 2002. Bleu: a method for automatic evaluation of machine translation, in: Proceedings of the 40th annual meeting of the Association for Computational Linguistics, pp. 311–318.
- Parcollet, T., Nguyen, H., Evain, S., Boito, M.Z., Pupier, A., Mdhaffar, S., Le, H., Alisamir, S., Tomashenko, N., Dinarelli, M., et al., 2024. Lebenchmark 2.0: A standardized, replicable and enhanced framework for self-supervised representations of french speech. Computer Speech & Language, 101622.
- Park, D.S., Chan, W., Zhang, Y., Chiu, C.C., Zoph, B., Cubuk, E.D., Le, Q.V., 2019. Specaugment: A simple data augmentation method for automatic speech recognition, in: Interspeech.
- Park, K., 2018. Kss dataset: Korean single speaker speech dataset.
- Paulik, M., Waibel, A., 2013. Training speech translation from audio recordings of interpreter-mediated communication. Computer Speech & Language 27, 455–474.
- Peyré, G., Cuturi, M., et al., 2019. Computational optimal transport: With applications to data science. Foundations and Trends® in Machine Learning 11, 355–607.
- Popović, M., 2015. chrf: character n-gram f-score for automatic mt evaluation, in: Proceedings of the tenth workshop on statistical machine translation, pp. 392–395.

- Popuri, S., Chen, P.J., Wang, C., Pino, J., Adi, Y., Gu, J., Hsu, W.N., Lee, A., 2022. Enhanced Direct Speech-to-Speech Translation Using Self-supervised Pre-training and Data Augmentation, in: Proc. Interspeech 2022, pp. 5195– 5199. doi:10.21437/Interspeech.2022-11032.
- Potapczyk, T., Przybysz, P., 2020. Srpol's system for the iwslt 2020 end-to-end speech translation task, in: International Workshop on Spoken Language Translation.
- Prabhavalkar, R., Hori, T., Sainath, T.N., Schlüter, R., Watanabe, S., 2024. End-to-end speech recognition: A survey. IEEE/ACM Transactions on Audio, Speech, and Language Processing 32, 325–351. doi:10.1109/TASLP. 2023.3328283.
- Rabiner, L., Schafer, R., 2010. Theory and applications of digital speech processing. Prentice Hall Press.
- Radford, A., Kim, J.W., Xu, T., Brockman, G., McLeavey, C., Sutskever, I., 2023. Robust speech recognition via large-scale weak supervision, in: Proceedings of the 40th International Conference on Machine Learning, JMLR.org.
- Raffel, C., Luong, M.T., Liu, P.J., Weiss, R.J., Eck, D., 2017. Online and lineartime attention by enforcing monotonic alignments, in: International Conference on Machine Learning.
- Ren, Y., Liu, J., Tan, X., Zhang, C., Qin, T., Zhao, Z., Liu, T.Y., 2020. Simulspeech: End-to-end simultaneous speech to text translation, in: Annual Meeting of the Association for Computational Linguistics.
- Salesky, E., Wiesner, M., Bremerman, J., Cattoni, R., Negri, M., Turchi, M., Oard, D.W., Post, M., 2021. Multilingual tedx corpus for speech recognition and translation, in: Proceedings of Interspeech.
- Sanabria, R., Caglayan, O., Palaskar, S., Elliott, D., Barrault, L., Specia, L., Metze, F., 2018. How2: A Large-scale Dataset for Multimodal Language Understanding, in: NeurIPS, Montréal, Canada.
- Sandhan, J., Daksh, A., Paranjay, O.A., Behera, L., Goyal, P., 2022. Prabhupadavani: A code-mixed speech translation data for 25 languages, in: Degaetano, S., Kazantseva, A., Reiter, N., Szpakowicz, S. (Eds.), Proceedings of the 6th Joint SIGHUM Workshop on Computational Linguistics for Cultural Heritage,

Social Sciences, Humanities and Literature, International Conference on Computational Linguistics, Gyeongju, Republic of Korea. pp. 24–29.

- Sarkar, B., Maurya, C.K., Agrahri, A., 2023. Direct speech to text translation: Bridging the modality gap using simsiam, in: Proceedings of the 6th International Conference on Natural Language and Speech Processing (ICNLSP 2023), pp. 250–255.
- Schlenoff, C., Sanders, G., Weiss, B., Proctor, F., Steves, M.P., Virts, A., 2009. Evaluating speech translation systems: Applying score to transtac technologies, in: Proceedings of the 9th Workshop on Performance Metrics for Intelligent Systems, pp. 223–230.
- Schneider, S., Baevski, A., Collobert, R., Auli, M., 2019. wav2vec: Unsupervised pre-training for speech recognition. arXiv preprint arXiv:1904.05862.
- Sergeev, A., Balso, M.D., 2018. Horovod: fast and easy distributed deep learning in tensorflow. CoRR abs/1802.05799. URL: http://arxiv.org/abs/ 1802.05799, arXiv:1802.05799.
- Sethiya, N., Nair, S., Maurya, C., 2024. Indic-TEDST: Datasets and baselines for low-resource speech to text translation, in: Calzolari, N., Kan, M.Y., Hoste, V., Lenci, A., Sakti, S., Xue, N. (Eds.), Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), ELRA and ICCL, Torino, Italia. pp. 9019–9024.
- Snover, M., Dorr, B., Schwartz, R., Micciulla, L., Makhoul, J., 2006. A study of translation edit rate with targeted human annotation, in: Proceedings of the 7th Conference of the Association for Machine Translation in the Americas: Technical Papers, pp. 223–231.
- Sohn, J., Kim, N.S., Sung, W., 1999. A statistical model-based voice activity detection. IEEE Signal Processing Letters 6, 1–3.
- Sohn, K., 2016. Improved deep metric learning with multi-class n-pair loss objective. Advances in neural information processing systems 29.
- Sperber, M., Neubig, G., Niehues, J., Waibel, A., 2019. Attention-passing models for robust and data-efficient end-to-end speech translation. Transactions of the Association for Computational Linguistics 7, 313–325.

- Su, J., Cao, J., Liu, W., Ou, Y., 2021. Whitening sentence representations for better semantics and faster retrieval. arXiv:2103.15316.
- Sun, H., Zhao, X., Lei, Y., Zhu, S., Xiong, D., 2023. Towards a deep understanding of multilingual end-to-end speech translation, in: Bouamor, H., Pino, J., Bali, K. (Eds.), Findings of the Association for Computational Linguistics: EMNLP 2023, Association for Computational Linguistics, Singapore. pp. 14332–14348. doi:10.18653/v1/2023.findings-emnlp.956.
- Tan, W., Chen, Y., Chen, T., Qin, G., Xu, H., Zhang, H.C., Durme, B.V., Koehn, P., 2024. Streaming sequence transduction through dynamic compression. ArXiv abs/2402.01172.
- Tang, Y., Gong, H., Dong, N., Wang, C., Hsu, W.N., Gu, J., Baevski, A., Li, X., Mohamed, A., Auli, M., Pino, J., 2022. Unified speech-text pre-training for speech translation and recognition, in: Muresan, S., Nakov, P., Villavicencio, A. (Eds.), Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Dublin, Ireland. pp. 1488–1499. doi:10.18653/v1/2022.acl-long.105.
- Tang, Y., Pino, J., Li, X., Wang, C., Genzel, D., 2021a. Improving speech translation by understanding and learning from the auxiliary text translation task, in: Zong, C., Xia, F., Li, W., Navigli, R. (Eds.), Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), Association for Computational Linguistics, Online. pp. 4252–4261. doi:10.18653/v1/2021.acl-long.328.
- Tang, Y., Pino, J.M., Li, X., Wang, C., Genzel, D., 2021b. Improving speech translation by understanding and learning from the auxiliary text translation task. ArXiv abs/2107.05782.
- Tran, C., Wang, C., Tang, Y., Tang, Y., Pino, J.M., Li, X., 2020. Crossmodal transfer learning for multilingual speech-to-text translation. ArXiv abs/2010.12829.
- Tsiamas, I., Gállego, G.I., Escolano, C., Fonollosa, J., Costa-jussà, M.R., 2022a. Pretrained speech encoders and efficient fine-tuning methods for speech translation: UPC at IWSLT 2022, in: Salesky, E., Federico, M., Costa-jussà, M. (Eds.),

Proceedings of the 19th International Conference on Spoken Language Translation (IWSLT 2022), Association for Computational Linguistics, Dublin, Ireland (in-person and online). pp. 265–276. doi:10.18653/v1/2022.iwslt-1. 23.

- Tsiamas, I., Gállego, G.I., Fonollosa, J.A.R., Costa-juss'a, M.R., 2022b. Efficient speech translation with dynamic latent perceivers. ICASSP 2023 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 1–5.
- Tsiamas, I., Gállego, G.I., Fonollosa, J.A.R., Costa-jussà, M.R., 2022c. Shas: Approaching optimal segmentation for end-to-end speech translation, in: Interspeech.
- Tsiamas, I., Gállego, G.I., Fonollosa, J.A.R., Costa-jussà, M.R., 2024. Pushing the limits of zero-shot end-to-end speech translation. ArXiv abs/2402.10422.
- Tsiamas, I., I. Gállego, G., Fonollosa, J., R. Costa-jussá, M., 2023. Speech translation with foundation models and optimal transport: UPC at IWSLT23, in: Salesky, E., Federico, M., Carpuat, M. (Eds.), Proceedings of the 20th International Conference on Spoken Language Translation (IWSLT 2023), Association for Computational Linguistics, Toronto, Canada (in-person and online). pp. 397–410. doi:10.18653/v1/2023.iwslt-1.38.
- Tsiartas, A., Ghosh, P., Georgiou, P., Narayanan, S., 2013. High-quality bilingual subtitle document alignments with application to spontaneous speech translation. Computer Speech & Language 27, 572–591.
- Vaswani, A., Shazeer, N.M., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., Polosukhin, I., 2017. Attention is all you need, in: NIPS.
- Vincent, E., Watanabe, S., Nugraha, A.A., Barker, J., Marxer, R., 2017. An analysis of environment, microphone and data simulation mismatches in robust speech recognition. Computer Speech & Language 46, 535–557.
- Wang, C., Inaguma, H., Chen, P.J., Kulikov, I., Tang, Y., Hsu, W.N., Auli, M., Pino, J., 2022. Simple and effective unsupervised speech translation. arXiv preprint arXiv:2210.10191.

- Wang, C., Pino, J.M., Wu, A., Gu, J., 2020a. Covost: A diverse multilingual speech-to-text translation corpus, in: International Conference on Language Resources and Evaluation.
- Wang, C., Rivière, M., Lee, A., Wu, A., Talnikar, C., Haziza, D., Williamson, M., Pino, J.M., Dupoux, E., 2021a. Voxpopuli: A large-scale multilingual speech corpus for representation learning, semi-supervised learning and interpretation, in: Annual Meeting of the Association for Computational Linguistics.
- Wang, C., Tang, Y., Ma, X., Wu, A., Popuri, S., Okhonko, D., Pino, J., 2020b. Fairseq s2t: Fast speech-to-text modeling with fairseq. arXiv preprint arXiv:2010.05171.
- Wang, C., Wu, A., Pino, J.M., 2020c. Covost 2 and massively multilingual speechto-text translation. arXiv: Computation and Language .
- Wang, C., Wu, A., Pino, J.M., Baevski, A., Auli, M., Conneau, A., 2021b. Largescale self- and semi-supervised learning for speech translation, in: Interspeech.
- Wang, C., Wu, Y., Liu, S., Zhou, M., Yang, Z., 2020d. Curriculum pre-training for end-to-end speech translation. arXiv preprint arXiv:2004.10093.
- Wang, P., Sun, E., Xue, J., Wu, Y., Zhou, L., Gaur, Y., Liu, S., Li, J., 2023. LAMASSU: A Streaming Language-Agnostic Multilingual Speech Recognition and Translation Model Using Neural Transducers, in: Proc. INTER-SPEECH 2023, pp. 57–61. doi:10.21437/Interspeech.2023-2004.
- Wei, J., Tay, Y., Bommasani, R., Raffel, C., Zoph, B., Borgeaud, S., Yogatama, D., Bosma, M., Zhou, D., Metzler, D., hsin Chi, E.H., Hashimoto, T., Vinyals, O., Liang, P., Dean, J., Fedus, W., 2022. Emergent abilities of large language models. ArXiv abs/2206.07682.
- Weiss, R.J., Chorowski, J., Jaitly, N., Wu, Y., Chen, Z., 2017. Sequence-to-Sequence Models Can Directly Translate Foreign Speech, in: Proc. Interspeech 2017, pp. 2625–2629. doi:10.21437/Interspeech.2017-503.
- Weller, O., Sperber, M., Pires, T., Setiawan, H., Gollan, C., Telaar, D., Paulik, M., 2022. End-to-end speech translation for code switched speech. arXiv preprint arXiv:2204.05076.

- Wu, C., Wang, Y., Shi, Y., Yeh, C.F., Zhang, F., 2020. Streaming Transformer-Based Acoustic Models Using Self-Attention with Augmented Memory, in: Proc. Interspeech 2020, pp. 2132–2136. doi:10.21437/Interspeech. 2020-2079.
- Wu, F., 2020. Deep representation learning in computer vision and its applications.
- Wu, F., Kim, K., Watanabe, S., Han, K.J., McDonald, R.T., Weinberger, K.Q., Artzi, Y., 2022. Wav2seq: Pre-training speech-to-text encoder-decoder models using pseudo languages. ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 1–5.
- Wu, H., Chang, K.W., Wu, Y.K., yi Lee, H., 2023. Speechgen: Unlocking the generative power of speech language models with prompts. ArXiv abs/2306.02207.
- Xie, J., Hansen, J.H.L., 2023. Mixrep: Hidden representation mixup for lowresource speech recognition. INTERSPEECH 2023.
- Xu, C., Liu, X., Liu, X., Sun, Q., Zhang, Y., Yang, M., Dong, Q., Ko, T., Wang, M., Xiao, T., Ma, A., Zhu, J., 2023a. CTC-based non-autoregressive speech translation, in: Rogers, A., Boyd-Graber, J., Okazaki, N. (Eds.), Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Toronto, Canada. pp. 13321–13339. doi:10.18653/v1/2023.acl-long.744.
- Xu, C., Ye, R., Dong, Q., Zhao, C., Ko, T., Wang, M., Xiao, T., Zhu, J., 2023b. Recent advances in direct speech-to-text translation. ArXiv abs/2306.11646.
- Xue, J., Wang, P., Li, J., Post, M., Gaur, Y., 2022. Large-scale streaming end-to-end speech translation with neural transducers. arXiv preprint arXiv:2204.05352.
- Yan, B., Shi, J., Maiti, S., Chen, W., Li, X., Peng, Y., Arora, S., Watanabe, S., 2023. Cmu's iwslt 2023 simultaneous speech translation system, in: International Workshop on Spoken Language Translation.
- Yang, C.K., Huang, K.P., Lu, K.H., Kuan, C.Y., Hsiao, C.Y., yi Lee, H., 2023. Investigating zero-shot generalizability on mandarin-english code-switched asr and speech-to-text translation of recent foundation models with self-supervision and weak supervision. ArXiv abs/2401.00273.

- Yao, Y., Haddow, B., 2020. Dynamic masking for improved stability in online spoken language translation, in: Conference of the Association for Machine Translation in the Americas.
- Ye, R., Wang, M., Li, L., 2021. End-to-end speech translation via cross-modal progressive training, in: Proc. of INTERSPEECH.
- Ye, R., Wang, M., Li, L., 2022a. Cross-modal contrastive learning for speech translation, in: Carpuat, M., de Marneffe, M.C., Meza Ruiz, I.V. (Eds.), Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Association for Computational Linguistics, Seattle, United States. pp. 5099–5113. doi:10.18653/v1/2022.naacl-main.376.
- Ye, R., Zhao, C., Ko, T., Meng, C., Wang, T., Wang, M., Cao, J., 2022b. Gigast: A 10,000-hour pseudo speech translation corpus. arXiv preprint arXiv:2204.03939.
- Yin, W., Liu, Z., Zhao, C., Wang, T., Tong, J., Ye, R., 2023. Improving speech translation by fusing speech and text, in: The 2023 Conference on Empirical Methods in Natural Language Processing.
- Yu, T., Ding, L., Liu, X., Chen, K., Zhang, M., Tao, D., Zhang, M., 2023. Promptst: Abstract prompt learning for end-to-end speech translation, in: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pp. 10140–10154.
- Zaidi, M.A., Lee, B., Kim, S., Kim, C., 2022. Cross-modal decision regularization for simultaneous speech translation, in: Interspeech.
- Zeng, X., Li, L., Liu, Q., 2021. RealTranS: End-to-end simultaneous speech translation with convolutional weighted-shrinking transformer, in: Zong, C., Xia, F., Li, W., Navigli, R. (Eds.), Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, Association for Computational Linguistics, Online. pp. 2461–2474. doi:10.18653/v1/2021.findings-acl.218.
- Zeng, X., Li, L., Liu, Q., 2022. Adatrans: Adapting with boundary-based shrinking for end-to-end speech translation. ArXiv abs/2212.08911.
- Zenkel, T., Sperber, M., Niehues, J., Müller, M., Pham, N.Q., Stüker, S., Waibel, A., 2018. Open source toolkit for speech to text translation. Prague Bull. Math. Linguistics 111, 125–135.
- Zhang, B., Haddow, B., Sennrich, R., 2022a. Revisiting end-to-end speech-to-text translation from scratch, in: International Conference on Machine Learning, PMLR. pp. 26193–26205.
- Zhang, D., Ye, R., Ko, T., Wang, M., Zhou, Y., 2023a. Dub: Discrete unit backtranslation for speech translation, in: Findings of ACL.
- Zhang, H., Si, N., Chen, Y., Zhang, W., Yang, X., Qu, D., Jiao, X., 2023b. Tuning large language model for end-to-end speech translation. ArXiv abs/2310.02050.
- Zhang, H., Si, N., Chen, Y., Zhang, W., Yang, X., Qu, D., Zhang, W.Q., 2023c. Improving speech translation by cross-modal multi-grained contrastive learning. IEEE/ACM Transactions on Audio, Speech, and Language Processing 31, 1075–1086.
- Zhang, R., He, Z., Wu, H., Wang, H., 2022b. Learning adaptive segmentation policy for end-to-end simultaneous translation, in: Annual Meeting of the Association for Computational Linguistics.
- Zhang, R., Wang, X., Zhang, C., He, Z., Wu, H., Li, Z., Wang, H., Chen, Y., Li, Q., 2021. BSTC: A large-scale Chinese-English speech translation dataset, in: Wu, H., Cherry, C., Huang, L., He, Z., Liu, Q., Elbayad, M., Liberman, M., Wang, H., Ma, M., Zhang, R. (Eds.), Proceedings of the Second Workshop on Automatic Simultaneous Translation, Association for Computational Linguistics, Online. pp. 28–35. doi:10.18653/v1/2021.autosimtrans-1.5.
- Zhang, S., Feng, Y., 2023. End-to-end simultaneous speech translation with differentiable segmentation, in: Annual Meeting of the Association for Computational Linguistics.
- Zhang, S., Feng, Y., Li, L., 2020. Future-guided incremental transformer for simultaneous translation. ArXiv abs/2012.12465.
- Zhang, T., Kishore, V., Wu, F., Weinberger, K.Q., Artzi, Y., 2019. Bertscore: Evaluating text generation with bert. arXiv preprint arXiv:1904.09675.

- Zhang, X., Zhang, Q., Liu, H., Xiao, T., Qian, X., Ahmed, B., Ambikairajah, E., Li, H., Epps, J., 2024a. Mamba in speech: Towards an alternative to selfattention. arXiv:2405.12609.
- Zhang, Z., Chen, S., Zhou, L., Wu, Y., Ren, S., Liu, S., Yao, Z., Gong, X., Dai, L., Li, J., et al., 2024b. Speechlm: Enhanced speech pre-training with unpaired textual data. IEEE/ACM Transactions on Audio, Speech, and Language Processing.
- Zhao, C., Wang, M., Dong, Q., Ye, R., Li, L., 2021. NeurST: Neural speech translation toolkit, in: Ji, H., Park, J.C., Xia, R. (Eds.), Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing: System Demonstrations, Association for Computational Linguistics, Online. pp. 55–62. doi:10.18653/v1/2021.acl-demo.7.
- Zhao, J., Yang, H., Haffari, G., Shareghi, E., 2022. M-Adapter: Modality Adaptation for End-to-End Speech-to-Text Translation, in: Proc. Interspeech 2022, pp. 111–115. doi:10.21437/Interspeech.2022-592.
- Zheng, R., Chen, J., Ma, M., Huang, LiangPovey, D., Ghoshal, A., Boulianne, G., Burget, L., Glembek, O., Goel, N., Hannemann, M., Motlicek, P., Qian, Y., Schwarz, P., Silovsky, J., Stemmer, G., Vesely, K., 2011. The kaldi speech recognition toolkit, in: IEEE 2011 Workshop on Automatic Speech Recognition and Understanding, IEEE Signal Processing Society.
- Zheng, R., Chen, J., Ma, M., Huang, L., 2021a. Fused acoustic and text encoding for multimodal bilingual pretraining and speech translation, in: International Conference on Machine Learning, PMLR. pp. 12736–12746.
- Zheng, R., Chen, J., Ma, M., Huang, L., 2021b. Fused acoustic and text encoding for multimodal bilingual pretraining and speech translation, in: International Conference on Machine Learning.
- Zhou, G., Lam, T.K., Birch, A., Haddow, B., 2024. Prosody in cascade and direct speech-to-text translation: a case study on korean wh-phrases, in: Findings of EACL.
- Zhou, X., Liu, H., Shi, C., Liu, J., 2022a. Deep Learning on Edge Computing Devices: Design Challenges of Algorithm and Architecture. Elsevier.

- Zhou, X., Wang, J., Cui, Z., Zhang, S., Yan, Z., Zhou, J., Zhou, C., 2022b. Mmspeech: Multi-modal multi-task encoder-decoder pre-training for speech recognition. ArXiv abs/2212.00500.
- Zhou, Y., Fang, Q., Feng, Y., 2023. Cmot: Cross-modal mixup via optimal transport for speech translation, in: Annual Meeting of the Association for Computational Linguistics.
- Zhu, Q.S., Zhou, L., Zhang, J., Liu, S.J., Hu, Y.C., Dai, L.R., 2023. Robust data2vec: Noise-robust speech representation learning for asr by combining regression and improved contrastive learning, in: ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 1–5.