Measuring Distributional Shifts in Text: The Advantage of Language Model-Based Embeddings

Gyandev Gupta $^{1^\star}$, Bashir Rastegarpanah $^{2^\star}$, Amalendu Iyer 2 , Joshua Rubin 2 , Krishnaram Kenthapadi 2

¹Indian Institute of Technology - Bombay, ²Fiddler AI $\bar{\mathcal{L}}$ Equal Contribution

gyandevgupta.iitb23@gmail.com, bashir@bu.edu, amal@fiddler.ai, josh@fiddler.ai, krishnaram@fiddler.ai

ABSTRACT

An essential part of monitoring machine learning models in production is measuring input and output data drift. In this paper, we present a system for measuring distributional shifts in natural language data and highlight and investigate the potential advantage of using large language models (LLMs) for this problem. Recent advancements in LLMs and their successful adoption in different domains indicate their effectiveness in capturing semantic relationships for solving various natural language processing problems. The power of LLMs comes largely from the encodings (embeddings) generated in the hidden layers of the corresponding neural network. First we propose a clustering-based algorithm for measuring distributional shifts in text data by exploiting such embeddings. Then we study the effectiveness of our approach when applied to text embeddings generated by both LLMs and classical embedding algorithms. Our experiments show that general-purpose LLM-based embeddings provide a high sensitivity to data drift compared to other embedding methods. We propose drift sensitivity as an important evaluation metric to consider when comparing language models. Finally, we present insights and lessons learned from deploying our framework as part of the Fiddler ML Monitoring platform over a period of 18 months.

1 INTRODUCTION

With the increasing deployment of AI systems in high-stakes settings such as healthcare, autonomous systems, lending, hiring, and education, we need to make sure that the underlying machine learning (ML) models are not only accurate but also reliable, robust, and deployed in a trustworthy manner. While ML models are typically validated and stress-tested before deployment, they may not be sufficiently scrutinized after deployment. A common assumption when deploying ML models is that the underlying data distribution observed during deployment remains unchanged compared to that of the training data. The violation of this assumption often results in unexpected model behaviors and can potentially cause subsequent changes, such as degradation in model performance or unacceptable model outputs. Hence, early detection of distributional shifts in data observed during deployment is an essential part of monitoring deployed ML systems [\[5,](#page-7-0) [20,](#page-8-0) [23,](#page-8-1) [32–](#page-8-2)[34\]](#page-8-3). In many real-world settings, it may not be feasible to obtain immediate user feedback signals or human judgments, or incorporate other mechanisms for continuous assessment of the quality of the ML model. In such scenarios, detecting distributional shifts could serve as an early indicator of the model's performance degradation or unexpected behavior and help protect against potential catastrophic failures, e.g., by gracefully deferring to human experts in the case of human-AI hybrid systems.

Natural language processing (NLP) models are increasingly being used in ML pipelines, and the advent of new technologies, such as large language models (LLMs), has greatly extended the adaption of NLP solutions in different domains. Consequently, the problem of distributional shift ("data drift") discussed above must be addressed for NLP data to avoid performance degradation after deployment [\[39\]](#page-8-4). Examples of data drift in NLP data include the emergence of a new topic in customer chats, the emergence of spam or phishing email messages that follow a different distribution compared to that used for training the detection models, and differences in the characteristics of prompts issued to an LLM application during deployment compared to the characteristics of prompts used during testing and validation.

In the case of structured data consisting of categorical and numerical features, a common approach to monitor data drift is to estimate the univariate distribution of input features (e.g., by using a histogram binning) for both a baseline dataset and the data at production time, and then quantify drift using distributional distance metrics such as the Jensen-Shannon divergence (JSD). However, in the case of unstructured data like text, estimating the data distribution using histogram binning is not a trivial task.

Modern NLP pipelines process text inputs in steps. Text is typically converted to tokens, which are mapped into a continuous (high-dimensional) embedding space to get a numerical vector representation, which ML models can consume. Distributional shifts in text data can be measured in this embedding space. However, estimating the data distribution using a binning procedure becomes challenging when the data is in a high-dimensional space for the following reasons. The number of bins increases exponentially with the number of dimensions, and the appropriate binning resolution cannot be selected a priori.

We propose a novel method for measuring distributional shifts in embedding spaces. We use a data-driven approach to detect highdensity regions in the embedding space of the baseline data, and track how the relative density of such regions changes over time. In particular, we apply k-means clustering to partition the embedding space into disjoint regions of high-density in the baseline data. The cluster centroids are then used to design a binning strategy which allows us to calculate a drift value for subsequent observations.

As in many other NLP problems, having access to high-quality text embeddings is crucial for measuring data drift as well. The more an embedding model is capable of capturing semantic relationships, the higher the sensitivity of clustering-based drift monitoring. Recent developments in LLMs have shown that the embeddings that are generated internally by such models are capable of capturing semantic relationships. In fact, some LLMs are specifically trained to provide general-purpose text embeddings.

We perform an empirical study for comparing the effectiveness of different embedding models in measuring distributional shifts in text. We use three real-world text datasets and apply our proposed clustering-based algorithm to measure both the existing drift in the real data and the synthetic drift that we introduce by modifying the distribution of text data points. We compare multiple embedding models (both classical and LLM-based models) and measure their sensitivity to distributional shifts at different levels of data drift. Our experiments show that LLM-based embeddings in general outperform classical embeddings when sensitivity to data drift is considered. We also highlight insights and lessons learned from deploying our system as part of the Fiddler ML Monitoring platform [\[13\]](#page-8-5) for 18 months.

In summary, the key contributions of this paper are:

- Proposing a novel clustering-based method and system for measuring data drift in embedding spaces.
- Highlighting the application of LLM-based embeddings for data drift monitoring.
- Introducing sensitivity to drift as an evaluation metric for comparing embeddings models.
- An empirical study of the effectiveness of different embedding models in detecting data drift.
- Presenting insights and lessons learned from deploying our system in practice.

2 RELATED WORK

Distributional Shift Detection for Categorical and Numerical Data There is extensive work on detecting distributional shifts in categorical and numerical data (refer Breck et al. [\[5\]](#page-7-0), Cormode et al. [\[8\]](#page-7-1), Gama et al. [\[14\]](#page-8-6), Karnin et al. [\[19\]](#page-8-7), Rabanser et al. [\[29\]](#page-8-8), Tsym-bal [\[38\]](#page-8-9), Webb et al. [\[41\]](#page-8-10), Žliobaite et al. [\[43\]](#page-8-11) for an overview). For practical ML applications, there is often a need to verify the validity of model inputs, which can be done by checking if the value is within a specified range and performing other user-defined tests [\[31\]](#page-8-12). Statistical hypothesis testing and confidence intervalbased approaches are often used to detect changes in the features or model outputs. While simpler tests such as Student's t-test and Kolmogorov–Smirnov test are employed for univariate or low dimensional data [\[27,](#page-8-13) [40\]](#page-8-14), advanced tests such as Maximum Mean Discrepancy are useful for higher dimensional data [\[16\]](#page-8-15). As hypothesis testing approaches require fine-tuning, confidence interval-based approaches are often preferred in practice [\[11,](#page-7-2) [28\]](#page-8-16). In general, the above change detection methods require density estimation, which is commonly obtained using histograms [\[35\]](#page-8-17). For multivariate data, the number of histogram bins grows exponentially with the dimensionality of data, and hence tree-based [\[3,](#page-7-3) [4\]](#page-7-4) and clustering-based [\[22\]](#page-8-18) data partitioning approaches have been proposed to scale well for high-dimensional data. While the clustering-based approach proposed in Liu et al. [\[22\]](#page-8-18) has similarities to our approach, this work focuses exclusively on multi-variate categorical and numerical data whereas our main focus is on measuring distributional shifts in text. Finally, while our approach is designed to be model-agnostic, there is also work on making use of model internals to detect drifts and take corrective actions [\[15,](#page-8-19) [21,](#page-8-20) [30,](#page-8-21) [42\]](#page-8-22).

Robustness in NLP Models In light of the recent advances in NLP models (including LLMs) and the associated practical applications, there is a rich literature on techniques for measuring and improving robustness in NLP models (see [\[39\]](#page-8-4) and references therein). This line of work is motivated by the fact that NLP models (including LLMs) are often brittle to out-of-domain data, adversarial attacks, or small perturbations to the input. While this work largely pertains to measuring robustness prior to deploying NLP models, our work focuses on the related but complementary problem of measuring distributional shifts in text once the models are deployed.

Tools for Monitoring Deployed ML Models Several open source and commercial tools provide users with the ability to monitor predictions of deployed ML models, e.g., Amazon SageMaker Model Monitor [\[28\]](#page-8-16), Arize Monitoring [\[1\]](#page-7-5), Deequ [\[31\]](#page-8-12), Evidently [\[12\]](#page-7-6), Fiddler's Explainable Monitoring [\[13\]](#page-8-5), Google Vertex AI Model Monitoring [\[36\]](#page-8-23), IBM Watson OpenScale [\[18\]](#page-8-24), Microsoft Azure MLOps [\[10\]](#page-7-7), TruEra Monitoring [\[37\]](#page-8-25), and Uber's Michelangelo platform [\[17\]](#page-8-26).

3 DATA DRIFT MEASUREMENT METHODOLOGY

Unstructured data such as images and text can be represented as semantically sensitive vectors by a variety of means. In natural language, these vectors can be simple term frequencies or summed word-level embeddings from off-the-shelf libraries. Increasingly practitioners use internal, context-sensitive, learned representations computed by deep learning models for this task as they are maximally sensitive to application specific semantics. Taking advantage of this semantic sensitivity, we treat the problem of unstructured data drift as tracking distributional shift in multi-dimensional vector distributions.

Histogram-based methods are commonly used for measuring distributional shifts where distributional distance metrics such as the Jensen-Shannon divergence (JSD) are applied to quantify data drift. In this approach, one needs to first find a histogram approximation of the two distributions at hand. In the case of univariate tabular data (i.e., one-dimensional distributions), generating these histograms is fairly straightforward and is achieved via a binning procedure where data points are assigned to histogram bins defined as a particular interval of the variable range.

However, generalizing this procedure to higher dimensional distributions requires identifying an efficient multivariate binning strategy. Grid-based space partitioning algorithms are impractical as the number of bins increases exponentially with the number of dimensions. Tree-based approaches are inefficient as, unlike for structured data, structure in semantic vector distributions is rarely axis-aligned.

3.1 Clustering-based Vector Monitoring

The core idea behind our vector monitoring method is a novel binning procedure in which instead of using fixed interval bins, bins are defined as regions of high-density in the data space. The densitybased bins are automatically detected using standard clustering algorithms such as k-means. Once we achieve the histogram bins for both baseline and production data, we can apply any of the

distributional distance metrics used for measuring the discrepancy between two histograms. In the following we provide an step by step introduction to our vector monitoring algorithm using an illustrative example.

Figure 1: A data drift scenario in two dimensions.

Consider the example of a multi-dimensional data drift scenario presented in Figure [1](#page-2-0) where, for the sake of simplicity, the vector data points are 2-dimensional. Comparing the baseline data (left plot) with the example production data (right plot), we see a shift in the data distribution where more data points are located around the center of the plot. Note that in practice the vector dimensions are usually much larger than two and such a visual diagnosis is impossible. We would like to have an automatic procedure that precisely quantifies the amount of data drift in a scenario like this.

The first step of our clustering-based drift detection algorithm is to detect regions of high density (data clusters) in the baseline data. We achieve this by taking all the baseline vectors and partitioning them into a fixed number of well populated clusters using the kmeans clustering algorithm.

Figure [2](#page-2-1) shows the output of the clustering step $(k=3)$ applied to our illustrative example where data points are colored by their cluster assignments. After baseline data are partitioned into clusters, the relative frequency of data points in each cluster (i.e., the relative cluster size) is assigned to the corresponding histogram bin. As a result, we obtain a 1-dimensional binned histogram of baseline data.

As our goal is to monitor for shifts in the data distribution, we track how the relative data density changes over time in different partitions (clusters) of the space. The number of clusters can be interpreted as the resolution by which the drift monitoring will be performed; the higher the number of clusters, the higher the sensitivity to data drift.

Figure 2: Applying k-means algorithm on baseline data.

After running k-means algorithm on the baseline data with a given number of clusters k , we obtain k cluster centroids. We use these cluster centroids in order to generate the binned histogram

Input: baseline dataset D_{base} , number of clusters k **Output**: centroids $C = [c_1, \ldots, c_k]$, normalized frequencies $F = [f_1, \ldots, f_k]$ 1: Apply k-means ($n_{clusters} = k$) on D_{base} 2: Let $C :=$ cluster centroids found by k -means 3: Initialize F with a size k vector of 0's. 4: for d in D_{base} do 5: find the centroid $c_i \in C$ that minimizes $||c_i - d||_2$ 6: Let $F[i] := F[i] + 1$ 7: end for 8: $F :=$ F $|D_{b}$ _{gs}

Algorithm 2 ComputeDrift

Input: baseline dataset D_{base} , production dataset D_{prod} , number of clusters k

Output: drift value v

9: return C, F

1: $C, F_{base} := InitializeClusters(D_{base}, k)$ 2: Initialize F_{prod} with a size k vector of 0's. 3: for d in $\hat{D_{\text{prod}}}$ do 4: find the centroid $c_i \in C$ that minimizes $||c_i - d||_2$ 5: Let $F_{prod}[i] := F_{prod}[i] + 1$ 6: end for 7: $F_{prod} := \frac{F_{prod}}{ID}$ $|\overrightarrow{D}_{prod}|$ 8: return Jensen-Shannon-Divergence(F_{base} , F_{prod})

of the production data. In particular, fixing the cluster centroids detected from the baseline data, we assign each incoming data point to the bin whose cluster centroid has the smallest distance to the data point. Applying this procedure to the example production data from Figure [1,](#page-2-0) and normalizing the bins, we obtain the cluster frequency histogram for the production data (Figure [3\)](#page-2-2).

Figure 3: Assigning production data to baseline clusters.

Finally, we can use a conventional distance measure like JSD between baseline and production histograms to get a drift value (Figure [4\)](#page-3-0). This drift value helps identify any changes in the relative density of cluster partitions over time.

Algorithms [1](#page-2-3) and [2](#page-2-4) present the above procedure for computing data drift for a given baseline dataset D_{base} and a dataset D_{prod} of observations at deployment for which we want to measure the distributional shift.

3.2 Choosing the Number of Clusters

Running the k-means algorithm requires specifying the number of clusters. Since we use clustering as a method to partition the embedding space for measuring data drift, the number of clusters in our algorithm can be seen as a tuning parameter that specifies the resolution of our measurement. That is, the higher the number of clusters, the higher the sensitivity of our measurement method to shifts in the data distribution.

From a practical perspective, the number of clusters can be increased until there are enough data points in each cluster such that there is sufficient (statistical) evidence for a measured drift value. Therefore, a binary search can be used to find the largest number of clusters that ensures sufficient evidence in each cluster.

Figure 4: Quantify data drift using distribution distance metrics.

4 EMPIRICAL EVALUATIONS

We next perform an empirical study of the effectiveness of the data drift measurement method proposed in [§3.](#page-1-0) In particular, we use three real-world text datasets and apply our clustering-based drift measurement algorithm to quantify both synthetic and real drifts using several text embedding models.

First we describe the datasets and embedding models used in our experiments, and the procedure used for creating synthetic drift. Then we present three sets of experiments in which we (i) compare the sensitivity of different embedding models to data drift, (ii) study the effect of number of clusters on drift measurement, and (iii) study the effect of embedding dimensions on drift measurement.

In brief, across three datasets, we observe:

- The drift sensitivity of Word2Vec is generally poor.
- TF-IDF and BERT perform well in certain scenarios and badly in others.
- The other embedding models Universal Sentence Encoder, Ada-001, and Ada-002 – all have good performance, though the none of them was consistently the best.
- Sensitivity improves (approximately) monotonically with the number of bins, k , but reaches a point of diminishing returns in the range $6 \leq k \leq 10$ across all datasets and models tested.
- Increasing the size of embedding vector also improves model performance monotonically, beginning to saturate around 256 components.
- (Interestingly) for models with large embedding sizes (e.g., Ada-002), drift saturation occurs at a much lower number

of dimensions when sampled randomly. This suggests that their sensitivity is not directly connected to their embedding size and that significant redundancy may be present.

4.1 Datasets

Three real-world text datasets are used to perform the following experiments:

20newsgroup is available in the scikit-learn package. It has 18K news group posts and a target label indicating to which of 20 groups each post belongs. We only consider the training subset and group the data points into five general categories ("science", "computer", "religion", "forsale", and "recreation") leaving 8966 news text and their corresponding general category label.

Civil comments $[2]$ is part of the WILDS^{[1](#page-3-1)} dataset. It contains online comments where a toxicity binary target and a demographic identity from 8 categories ("male", "female", "LGBTQ", "Christian", "Muslim", "other religions", "Black", and "White") are assigned to every comment.

Amazon Fine Food Reviews [\[24\]](#page-8-27) consists of reviews of fine foods from Amazon over a ten year period ending October 2012. Reviews include product and user information, ratings, and a plain text review^{[2](#page-3-2)}.

4.2 Text Embeddings

We chose three popular embedding baselines namely Word2Vec [\[26\]](#page-8-28), BERT [\[9\]](#page-7-9), and Universal Sentence Encoder [\[7\]](#page-7-10). We also use embeddings generated by Large Language Models hosted by OpenAI under the model names, text-embedding-ada-001 and text-embedding-ada-002^{[3](#page-3-3)} [\[6\]](#page-7-11). Additionally, for comprehensiveness we also consider sparse representations generated by Term Frequency-Inverse Document Frequency (TF-IDF).

4.3 Simulating Data Drift Measurement Scenarios

We next explain how we use the three real-world datasets to simulate different data drift measurement scenarios. For two of the datasets, 20newsgroup and Civil comments, we use the metadata information to simulate drift that may be encountered during deployment. For the Amazon Reviews dataset, we use reviews from 2006 and 2007 as the baseline and reviews from subsequent years as production data.

Generating synthetic data drift in 20newsgroup dataset. For this dataset, we adopt the following procedure:

- We randomly split the dataset into a baseline set and a production set. The baseline set is 40% of the total data points.
- We chose a subset of categories and used them to introduce synthetic drift by either oversampling or undersampling these selected categories.
- We generate different scenarios of data drift by modifying the relative percentage of samples that are drawn from the

 $^{\rm 1}$ https://wilds.stanford.edu/datasets/

²https://www.kaggle.com/datasets/snap/amazon-fine-food-reviews

³https://platform.openai.com/docs/guides/embeddings

selected categories. Each production scenario contains 4000 data points in total.

Generating synthetic data drift in Civil comments dataset. For this dataset, we adopt the following procedure:

- We split the dataset into a baseline set and production set. The baseline contains 40% of the total data points.
- We selected a subset of tags and used them to introduce synthetic drift by either oversampling or undersampling these selected tags.
- We generate different scenarios of data drift by modifying the relative percentage of samples that are drawn from the selected tags. Each production scenario contains 600 data points in total.

4.4 Comparing Drift Sensitivity of Embedding Models

In this experiment, we compare the sensitivity of our drift measurement algorithm when applied to six different embeddings of different production data that correspond to drift scenarios introduced previously. In order to control the effect of the embedding vector size, in this experiment we use 300 dimensional vectors for all embeddings (larger embedding vectors are truncated at this length). Additionally, the number of clusters is set to 10.

Figure [5](#page-5-0) presents the results of this experiment for each of the three datasets. In the synthetic data drift scenarios, we also plot the drift value in the actual label distributions. Furthermore, the vertical line indicates the data distribution that corresponds to the distribution of the baseline data.

We find that Universal Sentence Encoder, Ada-001, and Ada-002 all perform quite well and that word2vec performs consistently poorly. TF-IDF and BERT are inconsistent. This could be related to specific vocabulary or model settings.

4.5 Effect of Number of Clusters

While increasing the number of clusters generally increases the sensitivity to drift, we expect there to be saturation point after which improvement diminishes rapidly.

For 20Newsgroup (Figure [6a\)](#page-5-1), the production dataset was comprised of a fixed 60% from the "science" category and the remainder from others. We observe that from beyond 10 clusters, there was not a significant improvement in drift sensitivity. This observation informed our choice of 10 clusters for the sensitivity assessment in the prior section.

For Civil Comments (Figure [6b\)](#page-5-1), the production dataset was comprised of 60% of 600 examples with the female label and the remainder from the others. Here, also around 10 clusters, there was not any significant push in the drift detection.

For Amazon Reviews (Figure [6c\)](#page-5-1), the production dataset was taken to be the 2010 reviews. Saturation occurs around 6-7 clusters.

In conclusion, we found that there is a saturation point for drift detection with increasing clusters. The number of clusters required for optimal drift detection depends somewhat on the dataset and the embeddings used but is in a narrow range around between $k = 6$ and 10. We also observe instability in the TF-IDF plots. This may be the result of specific tokens having special significance and falling across cluster boundaries in important ways. In comparison, information of particular importance for the embedding models could be better distributed over their components.

4.6 Effect of Embedding Dimension

Different models generate embedding vectors of different lengths. Ada-002's embedding vectors have 1536 components, Ada-001's have 1024, BERT's have 768, and Universal Sentence Encoder's have 512. The length of TF-IDF vectors correspond to the number of tokens – we've chosen to take 300. To provide plots vs. embedding length, we randomly sample a set of d components for each model whose whose embedding vectors have a length $\geq d$. In order to capture the uncertainty introduced by this sampling as well as variation in the k -means procedure, we perform the dimension sampling and drift calculation five times for each value of d , reporting the mean and standard deviation. We define the "production data" as we do in the previous section and sweep over this embedding vector length d.

We find that the vector length, d , reaches a point of diminishing returns across the datasets and models around 256 components, regardless of the native size of the model's output. This suggests that the sensitivity of the large models in not due to their large embedding size and that they may be storing redundant information. In principle, this could also be connected to the fixed 10 cluster procedure. We plan to explore this in future work. As in the previous section we see see some instability in the TF-IDF scans.

5 DEPLOYMENT CASE STUDY

The goal of this case study is to investigate a concrete scenario involving a real-world NLP model and demonstrate how data scientists can use our framework (deployed in the Fiddler ML Monitoring platform) to detect input data drift for a multi-class classification NLP model trained over the 20 Newsgroups dataset.

As noted earlier, the 20 Newsgroups dataset contains labeled text documents from different topics. We use OpenAI embeddings to vectorize text data, and then train a multi-class classifier model that predicts the probability of each label for a document at production. In particular, we obtain embeddings by querying OpenAI's textembedding-ada-002 model (which is a hosted LLM that outperforms its previous models) using the Python API.

We keep the classification task simple by grouping the original targets into five general class labels: 'computer', 'for sale', 'recreation', 'religion', and 'science'. Given the vectorized data and class labels we train a model using a training subset of the 20 Newsgroups dataset.

For monitoring purposes, we typically use a reference (or baseline) dataset with which to compare subsequent data. We create a baseline dataset by randomly sampling 2500 examples from the five subgroups specified in the 20 Newsgroup dataset.

To simulate a data drift monitoring scenario, we manufacture synthetic drift by adding samples of specific text categories at different time intervals in production. Then we assess the performance of the model in the Fiddler ML monitoring platform and track data drift at each of those time intervals. The implementation of our NLP monitoring framework ([§3\)](#page-1-0) in the Fiddler platform supports easy integration of different NLP embedding model APIs (such as the ones provided by OpenAI). The user just needs to specify the

Figure 5: Drift sensitivity of embedding models.

Figure 6: Cluster saturation of different embeddings.

Figure 7: Effect of embedding dimension on drift sensitivity.

input columns to be monitored (by defining a "custom feature" for NLP embeddings using the Fiddler API), and the associated tasks (obtaining the embeddings, performing clustering, and computing the data drift metric such as JSD) are handled by the platform.

Figure [8](#page-6-0) shows the data drift chart within the Fiddler platform for the 20 Newsgroups multi-class model. More specifically, the chart is showing the drift value (in terms of JSD) for each interval of production events, where production data is modified to simulate

Figure 8: Monitoring OpenAI embeddings reveals distributional shifts in the samples drawn from the 20 Newsgroups dataset.

data drift. The call outs show the list of label categories from which production data points are sampled in each time interval.

5.1 Gaining more insights into data drift using UMAP visualization

In the monitoring example presented above, since data drift was simulated by sampling from specific class labels, we could recognize the intervals of large JSD value and associate them with known intervals of manufactured drift. However, in reality, oftentimes the underlying process that caused data drift is unknown. In such scenarios, the drift chart is the first signal that is available about a drift incident which can potentially impact model performance. Therefore, providing more insight about how data drift has happened is an important next step for root cause analysis and maintenance of NLP models in production.

The high-dimensionality of OpenAI embeddings (the Ada-002 embeddings have 1536 dimensions) makes it challenging to visualize and provide intuitive insight into monitoring metrics such as data drift. In order to address this challenge, we use Uniform Manifold Approximation and Projection (UMAP) [\[25\]](#page-8-29) to project OpenAI embeddings into a 2-dimensional space while preserving the neighbor relationships of the data as much as possible.

Figure [9a](#page-7-12) shows the 2D UMAP visualization of the baseline data colored by class labels. We see that the data points with the same class labels are well-clustered by UMAP in the embedded space although a few data points from each class label are mapped to areas of the embedded space that are outside the visually recognizable clusters for that class. This is likely due to the approximation involved in mapping 1536-dimensional data points into a 2D space. Another explanation is that the Ada-002 embedding model has identified semantically distinct subgroups within topics.

In order to show how UMAP embeddings can be used to provide insight about data drift in production, we will take a deeper look at the production interval that corresponds to samples from "science" and "religion" categories. Figure [9b](#page-7-12) shows the UMAP projection of

these samples into the UMAP embeddings space that was created using the baseline samples. We see that the embedding of unseen data is aligned fairly well with the regions that correspond to those two class labels in the baseline, and a drift in the data distribution is visible when comparing the production data points and the whole cloud of baseline data. That is, data points are shifted to the regions of space that correspond to "science" and "religion" class labels.

Next, we perform the same analysis for the interval that contains samples from the "religion" category only, which showed the highest level of JSD in the drift chart in Figure [8.](#page-6-0) Figure [9c](#page-7-12) shows how these production data points are mapped into the UMAP space; indicating a much higher drift scenario.

Notice that although UMAP provides an intuitive way to track, visualize and diagnose data drift in high-dimensional data like text embeddings, it does not provide a quantitative way to measure a drift value. On the other hand, our clustering-based NLP monitoring approach provides data scientists with a quantitative metric for measuring drift, and thereby enables them to configure alerts to be triggered when the drift value exceeds a desired threshold.

6 DEPLOYMENT INSIGHTS AND LESSONS LEARNED

We next present the key insights and lessons learned from deploying the framework described in the previous sections as part of the Fiddler ML monitoring platform [\[13\]](#page-8-5) over a period of 18 months. In one such real-world deployment, the system was tasked with detecting distributional shifts in the text queries being typed by the users into the search bar of a popular online design platform. The text queries were encoded into a 384-dimensional embedding vector with the help of a deep neural network (trained on the proprietary data of the design platform). The cluster centroids and the baseline distribution were determined on a baseline dataset of 500K queries. The production data consisted of 1.3M queries over a period of 2.5 months. Drift was then computed with a window size of 24 hours and plotted as a time-series (corresponding to one JSD value for

Figure 9: 2D UMAP embeddings of baseline and production vectors obtained from OpenAI

each day of the 2.5 month period). Using this approach, the monitoring system flagged a bump in drift that was first detected in the fifth week of traffic and persisted from then on. Inspecting the clusterbased histograms pointed to one cluster which contributed to most of the observed drift. It turned out that this particular cluster corresponded to queries that were either gibberish or from a language other than English. On further investigation, it was revealed that certain data pipeline changes were made for such queries during the fifth week, causing the new production distribution to differ significantly from the baseline distribution.

During the course of development and deployment of the system, we realized that users benefit from not just knowing the JSD values and getting alerts when these values exceed the desired thresholds, but also from the ability to analyze the underlying reasons for the drift. In particular, users expressed interest in associating semantically meaningful information for each cluster. We addressed this need by (1) highlighting representative examples from each cluster and (2) providing a human interpretable summary of the cluster. We decided to provide such a summary in the form of the top distinctive terms (obtained using TF-IDF applied over the set of text data points in the cluster) since the resulting summary was informative and could be generated with low cost and latency. Further, we observed that providing a visualization tool that plots baseline and production samples using UMAP [\[25\]](#page-8-29), a dimensionality reduction technique, enables the user to interactively perform debugging. The key insight is that such analysis, debugging, and visualization tools, along with the technical approach outlined in this paper, can help the user to fully benefit from the system – namely, to not just observe drift values over time and get alerts but also diagnose and mitigate the underlying causes.

7 CONCLUSION

Motivated by the increasing adoption of NLP models in practical applications and the need for ensuring that these models perform well and behave in a trustworthy manner after deployment, we proposed a clustering-based framework to measure distributional shifts in natural language data and showed the benefit of using LLM-based embeddings for data drift monitoring. We introduced sensitivity to drift as a new evaluation metric for comparing embedding models and demonstrated the efficacy of our approach over three real-world datasets. We implemented our system as part of the Fiddler ML Monitoring platform, and presented a case study, insights, and lessons learned from deployment over a period of 18 months. As our approach has been developed, evaluated, and deployed to address the needs of customers across different industries, the insights and experience from our work are likely to be useful for researchers and practitioners working on NLP models as well as on LLMs.

Our findings shed light on a novel application of LLMs – as a promising approach for drift detection, especially for high-dimensional data, and open up several avenues for future work. A few promising directions include: (1) whether domain-specific LLM embeddings are desirable for detecting drift in a given NLP application, (2) combining information across multiple NLP models in an application setting to detect drift, and (3) exploring embedding based drift detection approaches for image, voice, and other modalities as well as multi-modal settings.

REFERENCES

- [1] Arize. 2023. Arize Monitoring.<https://arize.com/ml-monitoring/>
- [2] Sara Beery, Elijah Cole, and Arvi Gjoka. 2020. The iWildCam 2020 Competition Dataset. arXiv preprint arXiv:2004.10340 (2020).
- [3] Giacomo Boracchi, Diego Carrera, Cristiano Cervellera, and Danilo Maccio. 2018. QuantTree: Histograms for change detection in multivariate data streams. In ICML.
- [4] Giacomo Boracchi, Cristiano Cervellera, and Danilo Macciò. 2017. Uniform histograms for change detection in multivariate data. In International Joint Conference on Neural Networks (IJCNN).
- [5] Eric Breck, Neoklis Polyzotis, Sudip Roy, Steven Whang, and Martin Zinkevich. 2019. Data Validation for Machine Learning.. In MLSys.
- [6] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language Models are Few-Shot Learners. arXiv[:2005.14165](https://arxiv.org/abs/2005.14165) [cs.CL]
- [7] Daniel Cer, Yinfei Yang, Sheng yi Kong, Nan Hua, Nicole Limtiaco, Rhomni St. John, Noah Constant, Mario Guajardo-Cespedes, Steve Yuan, Chris Tar, Yun-Hsuan Sung, Brian Strope, and Ray Kurzweil. 2018. Universal Sentence Encoder. arXiv[:1803.11175](https://arxiv.org/abs/1803.11175) [cs.CL]
- [8] Graham Cormode, Zohar Karnin, Edo Liberty, Justin Thaler, and Pavel Vesely. 2021. Relative Error Streaming Quantiles. In PODS.
- [9] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. BERT: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805 (2018).
- [10] Jordan Edwards et al. 2023. MLOps: Model management, deployment, lineage, and monitoring with Azure Machine Learning.<https://tinyurl.com/57y8rrec>
- [11] Bradley Efron and Robert J Tibshirani. 1994. An introduction to the bootstrap. CRC press.
- [12] Evidently. 2023. Evidently AI: Open-Source Machine Learning Monitoring. [https:](https://evidentlyai.com) [//evidentlyai.com](https://evidentlyai.com)
- [13] Fiddler. 2023. NLP and CV Model Monitoring. [https://www.fiddler.ai/natural](https://www.fiddler.ai/natural-language-processing-and-computer-vision-model-monitoring)[language-processing-and-computer-vision-model-monitoring](https://www.fiddler.ai/natural-language-processing-and-computer-vision-model-monitoring)
- [14] João Gama, Indre Žliobaitė, Albert Bifet, Mykola Pechenizkiy, and Abdelhamid Bouchachia. 2014. A survey on concept drift adaptation. ACM Computing Surveys (CSUR) 46, 4 (2014), 1–37.
- [15] Saurabh Garg, Yifan Wu, Sivaraman Balakrishnan, and Zachary Lipton. 2020. A Unified View of Label Shift Estimation. In NeurIPS.
- [16] Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. 2012. A kernel two-sample test. The Journal of Machine Learning Research 13, 1 (2012), 723–773.
- [17] Jeremy Hermann and Mike Del Balso. 2017. Meet Michelangelo: Uber's Machine Learning Platform. [https://eng.uber.com/michelangelo-machine-learning](https://eng.uber.com/michelangelo-machine-learning-platform/)[platform/](https://eng.uber.com/michelangelo-machine-learning-platform/)
- [18] IBM. 2023. Validating and monitoring AI models with Watson OpenScale. [https:](https://www.ibm.com/docs/SSQNUZ_3.5.0/wsj/model/getting-started.html) [//www.ibm.com/docs/SSQNUZ_3.5.0/wsj/model/getting-started.html](https://www.ibm.com/docs/SSQNUZ_3.5.0/wsj/model/getting-started.html)
- [19] Zohar Karnin, Kevin Lang, and Edo Liberty. 2016. Optimal quantile approximation in streams. In FOCS.
- [20] Eren Kurshan, Hongda Shen, and Jiahao Chen. 2020. Towards self-regulating AI: Challenges and opportunities of AI model governance in financial services. In Proceedings of the First ACM International Conference on AI in Finance.
- [21] Zachary Lipton, Yu-Xiang Wang, and Alexander Smola. 2018. Detecting and correcting for label shift with black box predictors. In ICML.
- [22] Anjin Liu, Jie Lu, and Guangquan Zhang. 2020. Concept drift detection via equal intensity k-means space partitioning. IEEE transactions on cybernetics 51, 6 (2020), 3198–3211.
- [23] Sasu Mäkinen, Henrik Skogström, Eero Laaksonen, and Tommi Mikkonen. 2021. Who Needs MLOps: What Data Scientists Seek to Accomplish and How Can MLOps Help?. In IEEE/ACM Workshop on AI Engineering-Software Engineering for AI (WAIN).
- [24] Julian John McAuley and Jure Leskovec. 2013. From amateurs to connoisseurs: modeling the evolution of user expertise through online reviews. In Proceedings of the 22nd international conference on World Wide Web. 897–908.
- [25] Leland McInnes, John Healy, Nathaniel Saul, and Lukas Großberger. 2018. UMAP: Uniform Manifold Approximation and Projection. Journal of Open Source Software 3, 29 (2018).
- [26] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In NeurIPS.
- [27] Kevin P Murphy. 2012. Machine learning: A probabilistic perspective. MIT press.
- [28] David Nigenda, Zohar Karnin, Muhammad Bilal Zafar, Raghu Ramesha, Alan Tan, Michele Donini, and Krishnaram Kenthapadi. 2022. Amazon SageMaker Model Monitor: A System for Real-Time Insights into Deployed Machine Learning Models. In KDD.
- [29] Stephan Rabanser, Stephan Günnemann, and Zachary Lipton. 2019. Failing loudly: An empirical study of methods for detecting dataset shift. In NeurIPS.
- [30] Sashank Reddi, Barnabas Poczos, and Alex Smola. 2015. Doubly robust covariate shift correction. In AAAI.
- [31] Sebastian Schelter, Dustin Lange, Philipp Schmidt, Meltem Celikel, Felix Biessmann, and Andreas Grafberger. 2018. Automating large-scale data quality verification. In VLDB.
- [32] David Sculley, Gary Holt, Daniel Golovin, Eugene Davydov, Todd Phillips, Dietmar Ebner, Vinay Chaudhary, Michael Young, Jean-Francois Crespo, and Dan Dennison. 2015. Hidden technical debt in machine learning systems. In NeurIPS.
- [33] Shreya Shankar, Rolando Garcia, Joseph M Hellerstein, and Aditya G Parameswaran. 2022. Operationalizing machine learning: An interview study. arXiv preprint arXiv:2209.09125 (2022).
- [34] Murtuza N Shergadwala, Himabindu Lakkaraju, and Krishnaram Kenthapadi. 2022. A Human-Centric Perspective on Model Monitoring. In HCOMP.
- [35] Bernard W Silverman. 2018. Density estimation for statistics and data analysis. Routledge.
- [36] Ankur Taly, Kaz Sato, and Claudiu Gruia. 2021. Monitoring feature attributions: How Google saved one of the largest ML services in trouble. [https://tinyurl.](https://tinyurl.com/awt3f5ex) [com/awt3f5ex](https://tinyurl.com/awt3f5ex) Google Cloud Blog..
- [37] TruEra. 2023. TruEra Monitoring.<https://truera.com/monitoring/>
- [38] Alexey Tsymbal. 2004. The problem of concept drift: definitions and related work. Computer Science Department, Trinity College Dublin 106, 2 (2004), 58.
- [39] Xuezhi Wang, Haohan Wang, and Diyi Yang. 2022. Measure and Improve Robustness in NLP Models: A Survey. In NAACL.
- [40] Larry Wasserman. 2004. All of statistics: A concise course in statistical inference. Vol. 26. Springer.
- [41] Geoffrey I Webb, Roy Hyde, Hong Cao, Hai Long Nguyen, and Francois Petitjean. 2016. Characterizing concept drift. Data Mining and Knowledge Discovery 30, 4 (2016), 964–994.
- [42] Yifan Wu, Ezra Winston, Divyansh Kaushik, and Zachary Lipton. 2019. Domain adaptation with asymmetrically-relaxed distribution alignment. In ICML.
- [43] Indre Žliobaitė, Mykola Pechenizkiy, and Joao Gama. 2016. An overview of concept drift applications. Big data analysis: new algorithms for a new society

(2016), 91–114.