A Modular Approach to Metatheoretic Reasoning for Extensible Languages

Dawn Michaelson

Gopalan Nadathur

Eric Van Wyk

Abstract

This paper concerns the development of metatheory for extensible languages. It uses as its starting point a view that programming languages tailored to specific application domains are to be constructed by composing components from an open library of independently-developed extensions to a host language. In the elaboration of this perspective, static analyses (such as typing) and dynamic semantics (such as evaluation) are described via relations whose specifications are distributed across the host language and extensions and are given in a rule-based fashion. Metatheoretic properties, which ensure that static analyses accurately gauge runtime behavior, are represented in this context by formulas over such relations. These properties may be fundamental to the language, introduced by the host language, or they may pertain to analyses introduced by individual extensions. We expose the problem of modular metatheory, i.e., the notion that proofs of relevant properties can be constructed by reasoning independently within each component in the library. To solve this problem, we propose the twin ideas of decomposing proofs around language fragments and of reasoning generically about extensions based on broad, a priori constraints imposed on their behavior. We establish the soundness of these styles of reasoning by showing how complete proofs of the properties can be automatically constructed for any language obtained by composing the independent parts. Mathematical precision is given to our discussions by framing them within a logic that encodes inductive rule-based specifications via least fixed-point definitions. We also sketch the structure of a practical system for metatheoretic reasoning for extensible languages based on the ideas developed.

1 Introduction

This paper concerns the *simultaneous treatment* of the notions of metatheory and language extensibility, two concepts that have been noted to be important to modern programming languages. Metatheory pertains to the association of properties with a programming language that apply to *all* programs written in the language. A conventional application of metatheory is in ensuring that relevant static analyses of programs can be used to draw sound conclusions about their runtime behavior. Language extensibility, on the other hand, refers to the provision of a framework for smoothly adding new features to a language to satisfy particular needs of users. The ability to provide such a framework has taken on a special significance with the modern-day permeation of computing into varied domains and the corresponding need to tailor languages to particular groups of users. While mechanisms for establishing properties of programming languages and for building in language extensibility have been investigated independently in the past, the focus on treating the two issues *simultaneously* raises interesting new questions. This paper articulates some of these questions and provides answers to them.

The discussions in this paper are based on a particular approach to supporting extensibility that has an established versatility [4, 5, 9]. This approach assumes a common core—identified as the *host language*—to every language that is of interest. It then assumes an *open library of*

independently-developed extensions around the host language. In this context, a language for a particular computational task is obtained by combining a selected set of extensions with the host language. Coherence in this model requires attempts to create such combinations will always succeed, *i.e.* there will not be unwanted interference between any of the participating components. More specifically, extensions typically contribute new syntactic constructs and may also add to the semantic attributes and analyses based on such attributes. Well-definedness in this context requires such additions interact constructively; for instance, compositions should not lead to syntactic ambiguity, should not preclude deterministic parsing, and semantic attributes should be well-defined for the resulting language. Moreover, the ability to interact should be determinable *locally* for each component, independently of knowledge about the specific components in a particular composite language. These desiderata have been considered in past work (*e.g.*, see [17, 10]), and we assume that means for ensuring such coherence have been employed as the starting point for our work.

Metatheoretic properties for a language are usually stated with respect to the syntactic constructs it offers and are based on their associated semantic attributes. The traditional approach to developing proofs for such properties relies fundamentally on a *closed world* assumption: the constructs provided by the language and the semantic attributes associated with them are known completely at the time a proof is constructed. This assumption, which is reasonable when the language is provided as a monolithic whole, is not an acceptable one relative to an extensibility framework. In this context, the complete language is known only when different pieces are composed together, a point at which it is too late to try to establish its metatheoretic properties. A related observation is that the process of reasoning about a specific fragment of a language is best carried out by the designer(s) of that fragment rather than someone who is using it in a composition. Thus, to serve the extensionality context properly, it seems necessary to *modularize* the reasoning process. More specifically, a means must be provided for each component to develop what will ultimately constitute a part of the proof of a property for a composite language while being oblivious, in a sense, to what other components may constitute the overall language. Moreover, devices should exist for *automatically* stitching together these separately-developed proof fragments to yield a proof of the property for the full language at the time the composition is determined.

Our objective in this paper is to realize the vision described above. In developing our ideas, we distinguish between two kinds of properties. The first sort of property is that which is intrinsic to the character of the language and hence should be known to the host language as well as to each extension as it is conceived. A canonical example of such a property is *type preservation*, *i.e.*, the proposition that the types of program fragments are preserved under evaluation steps. We refer to such properties as *foundational properties*. For a property of this kind, it is possible to realize an obvious form of modularization: each component contributes a "partial proof" that pertains to the constructs it introduces and these different pieces are combined on demand into a complete proof. Note, however, that care must be exercised in constructing the partial proofs in the absence of the closed world assumption. One of the constraints on the manner in which semantic attributes are specified and proofs are constructed that suffice to enforce such care. In particular, it is shown, when these constraints are followed, there is a sound means for combining the different proof fragments to yield a complete proof for any combination of the component parts.

We also consider another variety of properties, ones that might be introduced at a later stage of development, typically by an extension. As an example, consider an extension that layers "security" capabilities on a pre-existing language structure. Such an extension may also introduce a special form of static analysis meant to ensure that programs are well-behaved from a security perspective and a corresponding metatheoretic property verifying the soundness of this analysis. We refer to such properties here as *auxiliary properties*. A modularization of the kind just discussed is not

possible for the proof of such a property. Instead, the proof must be provided in its entirety by the extension introducing it. However, to be effective in constructing such a proof, that component must still get help from the other components with which it could be interacting. One important question in this context is how constructs from a priori unknown extensions are to be modeled in the reasoning process. The extensibility framework allows extensions to describe "projections" into the host language for their constructs as a means for other extensions to understand them at a distance. We propose to use such projections as a vehicle for circumscribing the behavior of extensions relative to the host language. In this context, the host language posits *projection constraints* as foundational properties to which extensions contribute to the proof by showing the behavior of their constructs is compatible with the projection constraints.

We develop these ideas in the rest of the paper. We begin by describing the framework for extensibility that provides the basis for our work in Section 2. Section 3 elaborates on the issue of metatheory and challenges in its modular realization relative to this extensibility framework. Showing how these challenges can be met requires us to be more specific about the logical structure of properties and proofs. Towards this end, we base our discussions on a specific logic for reasoning about relational specifications [1, 6], which we describe in Section 4. The next two sections take up a discussion of the two kinds of metatheoretic properties we have described above, in the process playing out the ideas to their modular treatment that we have sketched. The technical developments in Sections 2 through 6 are grounded by a running example comprising a simple host language for imperative programming; an extension for building, inspecting, and manipulating lists; and another extension for annotating variable declarations with a security level (either *public* or *private*) and a static information-flow analysis is intended to ensure that values in private variables do not leak into public ones. In this context, we use type preservation and the soundness of the information-flow analysis as vehicles for illustrating the modular development of proofs for the two kinds of properties. Section 7 discusses how the ideas developed in this paper can be deployed in a framework for modular reasoning and, more specifically, introduces the *Extensibella* and *Sterling* systems [14] that embody some of this thinking. Finally, Section 8 discusses related work and Section 9 summarizes this paper and discusses directions for future work.

2 A Framework for Extensibility

Language specifications are typically based on describing the relevant syntactic expressions and then describing relations over these expressions; these relations identify statically-determined attributes and constraints that must be satisfied by them for an expression to be well-formed or dynamicallydetermined attributes that formalize notions such as the evaluation of expressions. In the framework that provides the basis for the work in this paper, expression forms and the relations associated with them may be introduced by the host language or by extensions. The formal specification in both cases is provided via a 7-tuple written as $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R}, \mathscr{T}, \mathbb{T}, \mathbb{S} \rangle$, with specific constraints on how this form is to be used in the case of a host language or an extension. The first two elements of this 7-tuple identify the syntactic constructs introduced by the language component and the next two describe the relations relevant to the collection of expressions. It is possible in our framework for an extension to introduce relations applying to constructs from other extensions in the same language library that it does not know about directly. The last three items in the specification provide a means for realizing this possibility.

In the rest of this section, we explain the details of this scheme for language specification and show how it moulds itself naturally to providing for a framework for language extensibility. The specification mechanisms are illustrated by a small host language and a couple of simple extensions that will also lend themselves to illustrations of the mechanisms for modular reasoning developed later in the paper.

2.1 The Specification of Syntax

In descriptions meant for a language user, the focus is usually on spelling out the concrete structure of expressions. The view that is relevant to this paper is of a different kind. Here we are concerned with abstract syntax that identifies the principle constructs and the participating components of each expression. Moreover, this internal view will have to pay attention not only to expression categories that manifest themselves explicitly in language constructs, but also those that play a role in describing attributes that are to be associated with language expressions.

The formal description of these aspects is entrusted to the first two components in the 7-tuple presentation (\mathscr{C} and \mathbb{C}). The first step in this direction is to identify the set of syntactic categories, a task accomplished through \mathscr{C} . A set of constructors is then associated with each expression category by \mathbb{C} . These constructors take as arguments expressions of other known syntactic categories. We depict the association in a form that looks like a datatype declaration in a functional programming language. A presentation in this form should be understandable without further comment for the host language. Some of the sets of constructors for syntactic categories given by the host language will be the complete set, while others may be extended by extensions. The syntactic categories for which extensions may introduce new constructors are determined by the \mathscr{T} element of the tuple, as discussed below.

Extensions are part of a library built around a given host language. Thus, all the host language syntactic categories and expression constructors are assumed to be known at the outset in an extension. An extension can augment this collection by including new syntactic categories in the \mathscr{C} corresponding to it. \mathbb{C} may add to the expression forms for extensible host language categories and also identify such forms for the categories it adds. We will write category(c) for a constructor $c \in \mathbb{C}$ to indicate the syntactic category in \mathscr{C} of the phrase the constructor c builds.

We illustrate the structure described above by considering the example of a language library with a host language and two extensions. The host language has a few statement forms and some simple expression forms. One extension adds lists and the other augments variables with security annotations to support an information-flow analysis. The syntax specification pertinent to these components is shown in Figure 1; we write \mathscr{C}^H and \mathbb{C}^H for the specification for the host language, \mathscr{C}^L and \mathbb{C}^L for that for the list extension, and \mathscr{C}^S and \mathbb{C}^S for the extension that introduces security annotations. The host language has extensible categories for statements (*s*), expressions (*e*), and types (*ty*). There are also (unspecified) categories for the names of variables (*n*) and integer literals (*i*), as well as categories for typing contexts (Γ) mapping names to types and value contexts (γ) mapping names to values, a subset of expressions. Note the categories Γ and γ that correspond to typing and value contexts do not usually have a manifestation in the externally visible syntax for the language. They are primarily needed in specifying typing and related properties for expression forms as we shall see in the next subsection and are thus part of the specification of the (internal) syntax. The latter four categories are non-extensible, *i.e.*, extensions may not add constructors building expressions of these types.

The intended interpretation of most of the constructs introduced by the host language should be self-explanatory, though some explanation may be useful. The constructor *decl* serves to represent the declaration of a new variable n of type ty with its initial value given by expression e, seq is for representing the sequential composition of statements, *ifte* is for representing a conditional statement, and *while* is for representing a while loop. Constructs representing variable references

$\mathscr{C}^{H} = \{s, e, n, i, ty, \Gamma, \gamma\}$			$\mathscr{C}^L = \{\}$		
$ \overset{\mathbb{C}^{H}:}{s} e $::= 	skip decl(n, ty, e) assign(n, e) seq(s, s) ifte(e, s, s) while(e, s) var(n) intlit(i) true false add(e, e) eq(e, e) gt(e, e) not(e)	ty s $\mathscr{C}^{S} =$ \mathbb{C}^{S} :	$ $ $::=$ $::=$ $= \{sl,$	cons(e, e) null(e) head(e) tail(e) list(ty) splitlist(n, n, e)
ty	::= 	int bool	sl		public private
Γ		$\begin{array}{l} nilty\\ consty(n,ty,\Gamma) \end{array}$	Σ		nilsec $conssec(n, sl, \Sigma)$
γ	::= 	$nilval n:e; \ \gamma$			

Figure 1: The syntax of the example host language (H), the list extension (L), and the security extension (S). Note that we use the notation n : e; γ for evaluation contexts γ rather than a named constructor for conciseness in writing rules.

(var), integer (*intlit*) and Boolean literals, and some traditional binary and unary operators, are provided.

The list extension introduces constructs representing the creation and inspection of lists and their names should indicate their intended meaning. It also introduces a new type for list types and a new statement form representing simultaneous assignment to two variables the head and tail of a list (*i.e. splitlist*(hd, tl, e) represents evaluating e into a list and assigning the first element to hdand the rest of the list to tl), but does not add any new syntactic categories and thus \mathscr{C}^L is empty. The security extension augments the host language category s to allow variables to be identified as ones whose contents must be protected (*private*) or ones whose contents may be viewed by the world (*public*) through a new construct for variable declarations that includes this information. It also adds new syntactic categories for the security level indicators as well as *security contexts* mapping names to security levels and thus \mathscr{C}^S is $\{sl, \Sigma\}$.

2.2 Describing Semantic Relations

Relations between expressions in different syntactic categories play varied roles in language specifications. In our framework, such relations will be represented by predicates that are typed by syntactic categories. The element \mathscr{R} in the specification $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R}, \mathscr{T}, \mathbb{T}, \mathbb{S} \rangle$ identifies these predicates and their types. We shall assume also that these relations are defined in a syntax-directed and rule-based fashion, a practice common in language descriptions. The element \mathbb{R} in the 7-tuple presents the definitions of relations in this form.

As with the syntax description, relations identified by the host language are assumed to be part of the vocabulary of an extension in the same language library. Thus the \mathbb{R} component of an extension may include rules for these relations, in addition to ones for the relations it introduces. There is, however, a constraint on rules of the former kind. In the extensibility framework, we would like to hold as fixed in a meaningful sense the definition of host-introduced relations on host-introduced constructs. Towards realizing this desiderata, we require the identification of one of the arguments of each relation as its *primary component*. The intuition here is that the relation is *about* that argument; for example, a typing relation is about the term it types. In keeping with this intuition, we shall refer to the relation as one *for* the primary component category. In writing relations in specifications, we shall indicate their primary component by annotating it with an asterisk. The stipulation then is that an extension may include a rule for a relation introduced by the host language only if it pertains to a constructor added to the syntactic category by that extension.

To illustrate this aspect of our framework, we build on the syntax specification of the example host language and extensions from the previous subsection. The full language specification may be found in Appendix A, including all the rules for the host language and both extensions. Figure 2 gives the relations introduced by the host language and some rules the host language introduces. It introduces relations for looking up types in typing contexts $(lkpTy(\Gamma^*, n, ty))$ and value contexts $(lkpVal(\gamma^*, n, e))$, as well as a relation for checking a name is not bound in a typing context $(notBoundTy(\Gamma^*, n))$. Additionally, the host language introduces a relation for updating assignments in value contexts $(update(\gamma^*, n, e, \gamma))$ using a relation to remove the old binding $(remove(\gamma^*, n, \gamma))$.

The host language also introduces relations over expressions and statements. One of these, $value(e^*)$, identifies expression forms which are values. In the host language, these are integer and Boolean constants. We will refer to expressions e for which value(e) holds as values. Another relation over expressions, $vars(e^*, ns)$, identifies the names used in an expression. Some rules for both of these relations are shown in Figure 2.

Our host language also introduces typing relations over expressions and statements. These are the respective primary components of the two relations, as typing is *about* the term being typed. Expression typing, written $\Gamma \vdash e^* : ty$, that an expression e has type ty under the typing context Γ , has the expected rules for the host language constructs. Statement typing, written $\Gamma \vdash s^*, \Gamma'$, indicates the statement s is well-typed under the initial typing context Γ , producing the typing context Γ' with updated type bindings for variables. There are a couple of things to note with this relation. First, in rule TS-DECL in Figure 2, we see that declaring a new variable requires the variable not already be assigned a type in the context ($notBoundTy(\Gamma, n)$). Then, in rule TS-IFTE, we see we throw away any updates to the typing context from the branches, similar to how new scopes are treated in languages like C and Java. These choices allow us to keep the example simple, avoiding the complications of encoding explicit scopes into the typing and evaluation contexts.

Finally, the host language also introduces relations and rules specifying possibly-nonterminating big-step evaluation for expressions and statements, some rules for which are shown in Figure 2. As

with typing, evaluation is *about* the expression or statement being evaluated, and thus these are the primary components of the relation. The relation $\gamma \vdash e^* \Downarrow e$ specifies how the primary-component expression evaluates to a value in the context of the value store γ , with rules as expected. Similarly, $(\gamma, s^*) \Downarrow \gamma'$ describes the execution of a statement in the context of a value store γ , relating this and the statement s to a store that results from the execution containing updated values.

These relations must also be defined with respect to terms in the relevant syntactic categories built using constructors introduced by the list extension L and security extension S, some rules for which are shown in Figure 3 and Figure 4 respectively. Here we see our extensions satisfy the constraint that they may only add rules for the host language's relations (those in \mathscr{R}^H) such that the primary component of the conclusion of the rule is a pattern matching a construct introduced by that extension. This means extensions may define host relations for their constructs only; they cannot change the rules for constructs from the host language nor those introduced by other extensions. Note this also precludes extending relations over non-extensible types, such as the relation for looking up types $lkpTy(\Gamma, n, ty)$ with its primary component being the non-extensible type-context category Γ , as new constructors cannot be introduced by the extension for which to define such relations. We see, for example, some rules for typing list constructs in Figure 3, identifying which list forms are values, what their variables are, and how they are evaluated. The security extension introduces only one construct in a host-language-introduced category (s) and thus provides rules in Figure 4 for typing and evaluation for that one construct, the secure declaration form. These rules encode behavior that mimic the ones for the constructs of the host language.

2.3 Viewing Extensions at a Distance via Projections

An extension may want to introduce new relations and to define them in meaningful ways even in the presence of other extensions, even though it does not know the details of these other extensions. For example, the security extension may want to introduce new relations as a vehicle for utilizing the functionality provided by the host language and other extensions in the language library but with the additional provision that the visibility of sensitive data can be monitored. These relations would identify a static analysis similar to typing, where the relations are expected to indicate that information from private variables does not escape into public ones in a given program.

The first step in extensions introducing new relations is describing how the relations are defined for constructs the extension knows, those introduced by itself and the host language. Figure 5 shows relations the security extension might introduce and define to build the kind of static analysis described above. As for typing and values, there is a relation for looking up values in a security context $(lkpSec(\Sigma^*, n, sl))$ and one for checking names are not assigned levels $(notBoundSec(\Sigma^*, n))$. The security equivalent of typing an expression, written $\Sigma \vdash level(e^*, sl)$, determines a security level sl, either *public* or *private*, for the expression e under the security context Σ . This determines whether any variables used in e are assigned *private* in Σ . We can see, in rule L-EQ, that this relation uses the *join* relation relating two security levels to the more secure of the two.

The secure relation, $\Sigma sl \vdash secure(s^*, \Sigma')$, determines that a statement s, its primary component, is "secure" with respect to information flow in a security context Σ when executed at a particular security level sl. As with typing, this relation also has a new security context Σ' with the updated security bindings from any declarations within the statement. The intent of this analysis is to identify, conservatively, those programs in which data from variables declared as *private* (using the *secdecl* construct) do not influence those that are *public*. We see the mapping of names to security levels in rules S-DECL, S-SECDECL-PRIVATE, and S-SECDECL-PUBLIC in Figure 5, and how the security level at which the statement will be executed affects the assignments allowed in S-ASSIGN-PRIVATE and S-ASSIGN-PUBLIC. $\begin{aligned} \mathscr{R}^{H} &= \{ lkpTy(\Gamma^{*}, n, ty), \quad notBoundTy(\Gamma^{*}, n), \quad lkpVal(\gamma^{*}, n, e), \quad value(e^{*}), \quad vars(e^{*}, 2^{n}), \\ \Gamma \vdash e^{*}: ty, \quad \Gamma \vdash s^{*}, \Gamma, \quad update(\gamma^{*}, n, e, \gamma), \quad remove(\gamma^{*}, n, \gamma), \quad \gamma \vdash e^{*} \Downarrow e, \quad (\gamma, \ s^{*}) \Downarrow \gamma \} \end{aligned}$

 \mathbb{R}^H includes $value(e^*)$ $vars(e^*, ns)$ $\frac{1}{value(intlit(i))}$ V-INT $\frac{1}{vars(var(n), \{n\})}$ VR-VAR $\frac{1}{value(true)}$ V-TRUE $\overline{vars(intlit(i), \emptyset)}$ VR-INTLIT $\frac{vars(e_1, vr_1) \quad vars(e_2, vr_2)}{vars(e_1, e_2), (vr_1 \cup vr_2))} \text{VR-EQ}$ $\overline{value(false)}$ V-FALSE $\gamma \vdash e^* \Downarrow e$ $\Gamma \vdash e^*: ty$ $\frac{\Gamma \vdash e_1 : int \quad \Gamma \vdash e_2 : int}{\Gamma \vdash e_q(e_1, e_2) : bool} \text{ T-EQ} \qquad \frac{\gamma \vdash e_1 \Downarrow v_1 \quad \gamma \vdash e_2 \Downarrow v_2 \quad v_1 = v_2}{\gamma \vdash e_q(e_1, e_2) \Downarrow true} \text{ E-EQ-TRUE}$ $\frac{\Gamma \vdash e: bool}{\Gamma \vdash not(e): bool} \text{ T-NOT} \qquad \qquad \frac{\gamma \vdash e_1 \Downarrow v_1 \quad \gamma \vdash e_2 \Downarrow v_2 \quad v_1 \neq v_2}{\sim \vdash eq(e_1, e_2) \Downarrow false} \text{ E-EQ-FALSE}$ $\frac{\Gamma \vdash e_1 : int \qquad \Gamma \vdash e_2 : int}{\Gamma \vdash add(e_1 - e_2) : int} \text{ T-ADD}$ $\frac{\gamma \vdash e_1 \Downarrow intlit(i_1)}{\gamma \vdash e_2 \Downarrow intlit(i_2)} \frac{\gamma \vdash e_2 \Downarrow intlit(i_2)}{\gamma \vdash add(e_1, e_2) \Downarrow intlit(i)} \text{ E-ADD}$ $\Gamma \vdash s^*, \Gamma$ $(\gamma, \ s^*) \Downarrow \gamma$ $\frac{\Gamma \vdash e: ty \quad notBoundTy(\Gamma, n)}{\Gamma \vdash decl(n, ty, e), consty(n, ty, \Gamma)} \text{TS-DECL}$ $\frac{(\gamma, s_1) \Downarrow \gamma' \quad (\gamma', s_2) \Downarrow \gamma''}{(\gamma \quad seq(s_1 \quad s_2)) \Downarrow \gamma''} X-seq$ $\frac{\Gamma \vdash e : bool}{\frac{\Gamma \vdash s_1, \Gamma' \quad \Gamma \vdash s_1, \Gamma''}{\Gamma \vdash ifte(e, s_1, s_2) \Gamma}} \text{TS-IFTE}$

$$\frac{\gamma \vdash e \Downarrow true}{(\gamma, \ s_1) \Downarrow \gamma'} X\text{-IFTE-TRUE}$$
$$\frac{\gamma \vdash e \Downarrow true}{(\gamma, \ ifte(e, s_1, s_2)) \Downarrow \gamma'} X\text{-IFTE-TRUE}$$

Figure 2: Relations introduced by the host language (\mathscr{R}^H) and selected rules defining them (\mathbb{R}^H) . The full set of rules may be found in Appendix A. \mathbb{R}^L includes

$$\begin{array}{cccc} \hline value(e^*) & value(e^*) \\ \hline value(nil) & \text{V-NL} & vars(e_1, vr_1) & vars(e_2, vr_2) \\ \hline value(nil) & \text{V-NL} & vars(e_1, vr_1) & vars(e_2, vr_2) \\ \hline value(cons(e_1, e_2)) & \text{V-CONS} & vars(e, vr) \\ \hline value(cons(e_1, e_2)) & \text{V-CONS} & vars(head(e), vr) & \text{VR-HEAD} \\ \hline \hline \Gamma \vdash e^* : ty & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline \Gamma \vdash e^* : ty & & \\ \hline T \vdash ty & & \\ \hline \Gamma \vdash ty & & \\ \hline T \vdash ty & ty & \\ \hline$$

Figure 3: Selected rules given by the list extension (\mathbb{R}^L) for the relations introduced by the host language (\mathscr{R}^H) . The full set may be found in Appendix A.

 \mathbb{R}^S includes

$$\label{eq:started_st$$

Figure 4: Rules given by the security extension (\mathbb{R}^S) for the relations introduced by the host language (\mathscr{R}^H) .

In determining if loops are secure, if a private variable is used in the condition, no public variables may be assigned in the body as this could leak information about the value of the private variable. Thus in rule S-WHILE the security level at which the loop is executed, sl'', is joined with the security level of the condition (sl) and the security level of the context of the loop itself (sl') to determine the level at which the body of the loop will be executed. For example, if the condition contains a private variable then the loop body must be secure in a *private* context, preventing any assignment to public variables. A similar analysis is done for conditionals, with rules in Appendix A.

Observe the security extension defines the *level* and *secure* relations over statements and expressions; these are their respective primary components and are syntactic categories introduced by the host language. Because only the extension introducing a relation is aware of its existence, the extension must bear the burden of defining it completely. This includes introducing rules defining it for constructs introduced by the host language, as we have seen with rules like L-VAR and S-WHILE. However, having noted this, we immediately see a difficulty in defining a new relation, such as *secure*, completely. There may be several different extensions participating in a library and modularity requires they must not use knowledge of each other in their construction, yet multiple extensions may participate in a composite language. How then is a relation defined by one extension to be assessed with respect to expression forms introduced by another extension? With specific reference to the example at hand, how are we to perform a security analysis of statement and expression forms introduced by the list extension?

To address this issue, our framework includes a mechanism, inspired by forwarding in attribute grammars [20], for viewing extensions "at a distance." One component of this mechanism is a projection of extension constructs that will then be the basis for their view in other extensions. Each extensible category in the host language has a projection relation relating a term built by an extension-introduced construct to its projection in the same category. These projection relations are identified in the fifth item (\mathscr{T}) of its tuple $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R}, \mathscr{T}, \mathbb{T}, \mathbb{S} \rangle$. The existence of a projection relation in \mathscr{T} is, in fact, what determines in our framework whether a category is extensible: those with projection relations are extensible, those without are not. Extensions do not introduce projection relations, and thus this part of the specification is empty for them. Of course, the projection relation must be defined to be useful. The rules that do so constitute the sixth item (\mathbb{T}) in the specification of an extension; note this part of the language specification is irrelevant to the host language. The final piece to the mechanism is a description of how relations defined by an extension should be defined for constructs from other extensions. This part, which is meaningful only to extensions that are introducing new relations, is represented by the S item in the language specification. Specifically, S comprises a collection of *projection rules* that identify the definitions of the relevant relations, each rule using the projection relation for the category of the relation's primary component. At a technical level, projections in such rules are permitted only on the primary component of the relation and this component is required to be a schematic variable in the conclusion of the rule. Thus these rules copy the definition of the relation from the projection.

We illustrate this aspect of the framework in Figure 6 by showing the projection relations introduced by the host language and the rules defining them in the extensions, as well as completing the definitions of the relations described by the security extension. The host language provides the projection relations $proj_e(e, e)$ for expressions, $proj_s(s, s)$ for statements, and $proj_{ty}(ty, ty)$ for types in \mathscr{T}^H shown in Figure 6. Because the other syntactic categories introduced by the host language are not intended to be extensible, we do not introduce projection relations for them. The projection relations in our example language take the most basic form of projection relations and do not involve any additional arguments, but this can be useful in some cases. For example, a host language might permit the use of an expression's type in determining its projection, and in that $\begin{aligned} \mathscr{R}^S &= \{ lkpSec(\Sigma^*,n,sl), \quad notBoundSec(\Sigma^*,n), \quad join(sl^*,sl,sl), \quad \Sigma \vdash level(e^*,sl), \\ \Sigma \ sl \vdash secure(s^*,\Sigma) \} \end{aligned}$

 \mathbb{R}^{S}

$$\begin{split} \hline \Sigma \vdash level(e^*, sl) & join(sl^*, sl, sl) \\ \hline \Sigma \vdash level(intlit(i), public) & L^{-1NT} & join(public, public, public) & J^{-PUBLIC} \\ \hline \Sigma \vdash level(intlit(i), public) & L^{-1NT} & join(private, l, private) & J^{-PRIVATE-L} \\ \hline \Sigma \vdash level(var(n), l) & L^{-VAR} & join(l, private, l, private) & J^{-PRIVATE-L} \\ \hline \Sigma \vdash level(e_1, l_1) & join(l, private, private) & J^{-PRIVATE-R} \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_2), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} & L^{-EQ} & \\ \hline \Sigma \vdash level(e_1, e_1), l) & L^{-EQ} &$$

Figure 5: Selected rules in \mathbb{R}^S for security relations introduced by $S(\mathscr{R}^S)$. The full set of rules can be found in Appendix A.

Projection relations in \mathscr{T}^{H} : { $proj_{e}: e, proj_{s}: s, proj_{ty}: ty$ }

Projection relation rules in \mathbb{T}^L :

$$\frac{1}{proj_{e}(null(e), e)} \xrightarrow{\text{P-NULL}} \frac{1}{proj_{e}(tail(e), e)} \xrightarrow{\text{P-TAIL}} \frac{1}{proj_{e}(cons(e_{1}, e_{2}), eq(e_{1}, e_{2}))} \xrightarrow{\text{P-CONS}}$$

$$\frac{1}{proj_{e}(head(e), e)} \xrightarrow{\text{P-HEAD}} \frac{1}{proj_{e}(nil, true)} \xrightarrow{\text{P-NIL}} \frac{1}{proj_{ty}(list(ty), ty)} \xrightarrow{\text{P-LIST}}$$

$$\frac{n_{hd} \neq n_{tl}}{proj_{ty}(list(ty), ty)} \xrightarrow{\text{P-LIST}} \xrightarrow{\text{P-SPLITLIST}}$$

 $proj_{s}(splitlist(n_{hd}, n_{tl}, e), seq(seq(assign(n_{hd}, e), assign(n_{tl}, tail(var(n_{hd})))), assign(n_{hd}, head(var(n_{hd}))))))$

Projection relation rule in \mathbb{T}^S :

$$\overline{proj_s(secdecl(n,ty,sl,e), decl(n,ty,e))}$$
P-SECDECL

Projection rules in \mathbb{S}^S :

$$\frac{\operatorname{proj}_{e}(e,e') \quad \Sigma \vdash \operatorname{level}(e',\ell)}{\Sigma \vdash \operatorname{level}(e,\ell)} \operatorname{P-LEVEL} \qquad \qquad \frac{\operatorname{proj}_{s}(s,s') \quad \Sigma \ sl \vdash \operatorname{secure}(s',\Sigma')}{\Sigma \ sl \vdash \operatorname{secure}(s,\Sigma')} \operatorname{P-secure}$$

Figure 6: Projection relations and rules defining them and projection rules for host H and extensions L and S. Note \mathscr{T}^L , \mathscr{T}^S , \mathbb{T}^H , \mathbb{S}^H , and \mathbb{S}^L are all empty and thus not shown.

case the relation for expressions might include a typing context argument to permit determining an expression's type (this would be written as $proj_e(\Gamma, e, e)$).

Consider the projection rule P-SPLITLIST for relation $proj_s$ for the list-splitting construct *splitlist* introduced by L in \mathbb{T}^L in Figure 6. A representation of a list split $splitlist(n_{hd}, n_{tl}, e)$ is projected to an encoding of a sequence of assignments accomplishing the splitting of the list. The *secure* relation is then defined for the *splitlist* construct by taking its projection to the constructs representing this sequence of assignments, checking the security of that sequence, then using it to define security for the *splitlist* construct. This is achieved by the projection rule P-SECURE that indicates a statement s is secure if its projection s' is secure.

There is a subtlety concerning projections illustrated by the rules for list expression forms. These rules project expression forms contributed by the extension to seemingly unrelated ones in the host language: for example, null(e) is projected to e and $cons(e_1, e_2)$ is projected to $eq(e_1, e_2)$. The way to understand these projections is that their purpose is to preserve enough information about the expressions built using the contructors from the extension so analyses described by other extensions through the projections are still meaningful. Thus, consider the *level* relation from the security extension. This is intended to assess the security status of an expression which, in the case of $cons(e_1, e_2)$, would depend on the subexpressions e_1 and e_2 . Thus the key to a good projection in this case is that these subexpressions be preserved. Of course, an extension does not have a direct means for assessing the kinds of analyses other extensions might want to carry out. We will see later how meta-theoretic properties can help identify the desiderata for good projections.

2.4 Well-Formedness and Language Composition

We conclude this section by making precise the preceding informal description of the extensibility framework. The framework is exercised by describing a *language library* that comprises a single host language and a collection of extensions via tuples of the form $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R}, \mathscr{T}, \mathbb{T}, \mathbb{S} \rangle$. We assume the host language to be given by the tuple $\langle \mathscr{C}^H, \mathbb{C}^H, \mathscr{R}^H, \mathbb{R}^H, \mathscr{T}^H, \mathbb{T}^H, \mathbb{S}^H \rangle$. We describe below the constraints that must be satisfied for such a collection to be deemed well-formed and we then explain how a standalone language description is to be constructed from the composition of a collection of extensions with the host language.

2.4.1 Well-Formedness for Host Language and Extension Descriptions

In the very first instance, there must be a unique identification for every constructor and relation that is identified in the specification of the host language and the different extensions. Thus, the constructors identified by \mathbb{C} in each component must be distinct as also must be the relations identified by \mathscr{R} and \mathscr{T} . The specification of constructors in the \mathbb{C} set of the components and of predicates in the \mathscr{R} and \mathscr{T} sets impose typing constraints on the symbols identified. Wellformedness requires that these symbols be used in a way respecting their typing throughout the language library's specifications.

There is one further requirement of the host language specification: \mathscr{T}^H identifies at most one projection relation for each category in \mathscr{C}^H . These relations associate terms in a particular category with their projections, but may do so in a manner that is parameterized by other terms, which may be used in defining projection rules as we explain below. A syntactic category that does not have an associated projection relation is considered to be non-extensible.

An extension specification for an extension E, on the other hand, must satisfy conditions beyond the basic ones mentioned at the outset to be deemed well-formed. For an extension E, its specification being $\langle \mathscr{C}^E, \mathbb{C}^E, \mathscr{R}^E, \mathbb{R}^E, \mathscr{T}^E, \mathbb{T}^E, \mathbb{S}^E \rangle$, these conditions are the following:

- 1. For each constructor c in \mathbb{C}^{E} building a syntactic category introduced by the host language $(category(c) \in \mathscr{C}^{H})$, the category is an extensible category (there is a projection relation in \mathscr{T}^{H} for category(c)).
- 2. For a rule in \mathbb{R}^E that has $R(t_1, \ldots, t_n)$ as its conclusion where $R \in \mathscr{R}^H$ and the *i*th argument of R is its primary component, it must be the case that t_i has a constructor in \mathbb{C}^E as its top-level symbol. This is a formal rendition of the requirement that an extension must not modify the definition of a relation introduced by the host language as it pertains to host language constructs.
- 3. For each rule introduced by an extension defining a projection (rule in \mathbb{T}^E), it must be the case that the projecting argument has a constructor in \mathbb{C}^E as its top-level symbol.
- 4. For each $R \in \mathscr{R}^E$ that has a host-language-introduced syntactic category as its primary component, there must be a rule for R in the set of projection rules \mathbb{S}^E .
- 5. Each rule in \mathbb{S}^E for a relation R whose primary component is its i^{th} argument must have the form

$$\frac{T(x,x')}{R(t_1,\ldots,t_{i-1},x',t_{i+1},\ldots,t_n)}$$

where x and x' are schematic variables and T is to be read as a predicate that uses the relevant projection relation from \mathscr{T}^H to indicate that x projects to x' under conditions determined

by the additional parameters for the relation. For example, if *proj* is a three-place projection relation whose second and third arguments identify the projected term and its projection and the first argument is an auxiliary parameter, then proj(s, x, x') may be the instantiation of T(x, x'), where s is a term whose structure identifies a dependency on the conclusion of the rule.

Note we do not require an extension to introduce rules defining the projection for the constructors it introduces. Choosing not to define the projection relation for a new constructor limits the extensibility of the language, as relations introduced by other extensions cannot hold for the new syntax. This is, however, a choice left to an extension writer.

Well-formedness as defined above can be statically assessed and in isolation for the host language specification and with knowledge of the host language alone for an extension specification. This is an important feature: the well-formedness of a component in an open language library should be assessible as it is developed, independently of other components. We will assume the specifications in a library have been determined to be well-formed before any meta-theoretic analysis related to them is undertaken. This is similar to an approach to determining independently the wellformedness of language components specified using attribute grammars [8, 10].

2.4.2 Language Composition

The host language H and a collection of extensions E_1, \ldots, E_n in a library can be composed to form a *complete* language by the process we describe below. The language that results from such a composition is denoted by $H \triangleleft \{E_1, \ldots, E_n\}$. A complete language is represented by a tuple of the form $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R} \rangle$. The components \mathscr{T}, \mathbb{T} , and \mathbb{S} in specifications impact the composition process but they have do not have a role in a complete language.

The composition process will *instantiate* projection rules from one extension with new constructors from another to specify how a relation introduced by the former is defined on the constructs introduced by the latter. These instantiated rules, denoted $\mathbb{R}^{\mathbb{S}}$, will be part of \mathbb{R} and are defined as follows:

$$\mathbb{R}^{\mathbb{S}} := \{ r[c(\overline{y})/x] \mid i \in \{1..n\}, j \in \{1..n\}, i \neq j, r \in \mathbb{S}^{E_i}, c \in \mathbb{C}^{E_j}, category(c) \in \mathscr{C}^H \\ category(x) = category(c), \overline{y} \text{ is a sequence of variables not} \\ appearing in r of length the arity of c \}.$$

Here $r[c(\overline{y})/x]$ represents the rule that results from a projection rule by replacing the schematic variable x that appears in the primary component position in the conclusion of the rule with the term $c(\overline{y})$. Observe this instantiation is done only for extension constructs for host language categories, and only when doing so is syntactically valid (*category*(x) = *category*(c)).

An example is perhaps useful in understanding the intent underlying the instantiation of projection rules. Recall the list *head* constructor in \mathbb{C}^L and the *level* projection rule P-LEVEL in \mathbb{S}^S from Figure 6. Both are over the host category *e* for expressions. The instantiation process above will create a new rule for *level* over the *head* construct in \mathbb{R}^S :

$$\frac{proj_{e}(head(e), e') \qquad \Sigma \vdash level(e', sl)}{\Sigma \vdash level(head(e), sl)} \text{ L-HEAD}$$

This illustrates how we apply the projection rules to new syntax to complete the definitions of the extension-introduced relations. Note that in the language composition each instance of a projection rule that is added has its primary component built by a specific constructor introduced by a different extension.

Given $\mathbb{R}^{\mathbb{S}}$, the definition of the complete language $\langle \mathscr{C}, \mathbb{C}, \mathscr{R}, \mathbb{R} \rangle$ resulting from the composition $H \triangleleft \{E_1, \ldots, E_n\}$ is straightforward:

- $\mathscr{C} := \mathscr{C}^H \cup \bigcup_{i=1}^n \mathscr{C}^{E_i}$. The set of syntax categories is the union of all the syntax categories in the host language and all the extensions.
- $\mathbb{C} := \mathbb{C}^H \cup \bigcup_{i=1}^n \mathbb{C}^{E_i}$. The set of syntax constructors is the union of all the syntax constructors in the host language and all the extensions.
- $\mathscr{R} := \mathscr{R}^H \cup \mathscr{T}^H \cup \bigcup_{i=1}^n \mathscr{R}^{E_i}$. The set of relations in the composed language is the union of all the semantic relations in the host language and all the extensions, both the regular relations and the projection relations.
- $\mathbb{R} := \mathbb{R}^* \cup \mathbb{T}^* \cup \mathbb{R}^{\mathbb{S}}$ where
 - $-\mathbb{R}^* := \mathbb{R}^H \cup \bigcup_{i=1}^n \mathbb{R}^{E_i}$. This is all the semantic relation rules in the host language and all the extensions.
 - $-\mathbb{T}^* := \bigcup_{i=1}^n \mathbb{T}^{E_i}$. This is the collection of all the projection rules in all the extensions.

The construction of the set of relation rules \mathbb{R} includes the rules from three sources: the rules given by the host language and extensions in their respective rule sets (\mathbb{R}^*), the projection relation rules from the extensions (\mathbb{T}^*), and the instantiations of the projection rules for constructors from distinct extensions in $\mathbb{R}^{\mathbb{S}}$ as defined above.

In the sequel, we will need to talk about the language identified by a library component. If that component is the host language H, this will mean the language $H \triangleleft \emptyset$. If it is an extension E (and H is the host language), then it will mean the language $H \triangleleft \{E\}$.

3 Metatheoretic Properties and Modular Reasoning

As we have seen in the previous section, language specifications begin with a description of syntax and then extend into the presentation of semantics for expressions. One objective of the semantic component is to formalize the execution behavior of programs and program fragments; this is the role, for instance, of the evaluation relation on expressions and statements in the example in Section 2. However, semantic relations have an important additional purpose: they provide for a statically-determined attribution of properties to expressions that are intended to translate into assurances of good dynamic behavior. For example, the property of well-typing for a program is supposed to guarantee its execution will be free of type-related errors. There is, however, a distance between the results of static analyses and what actually happens with a program at runtime. Metatheoretic properties, which relate different semantic features of programs, are a means for closing this gap. For example, in translating well-typing of programs into the intended guarantee of their error-free execution, it is important to *verify* that types of expressions do not change under evaluation. The metatheoretic property of type preservation relating the typing and evaluation relations for program fragments has exactly this purpose.

We are interested in this paper in a broad exploitation of static analyses in the style described above. In this context, metatheoretic properties will relate relations over syntactic expressions. We will specifically focus on proving such properties that are expressed via formulas of the form

 $\forall \overline{x}. R(\overline{t}) \supset F$

where \overline{x} is a sequence of variables, $R(\overline{t})$ is an atomic formula that has R as its predicate or relation symbol and the sequence of terms \overline{t} as its arguments and is constructed using the variables in \overline{x} and a vocabulary identified by specifications of the kind discussed in the previous section, and Fis an arbitrary formula constructed over the same vocabulary and variables. We shall refer to the relation $R(\overline{t})$ as the *key relation* of such a property. We restrict attention to formulas in this form for simplicity in discussion. Note, however, that such a formula is equivalent to one with the more general structure $\forall \overline{x_1}. F_1 \supset \cdots \supset \forall \overline{x_m}. F_m \supset F$ where F_i is $R(\overline{t})$ for some *i* between 1 and *m*. Thus, our discussions in reality extend to formulas with this richer syntax.

Proofs of the kind of properties in which we are interested must depend on the definitions of the relations that participate in them. Of particular importance is the manner in which the definition of the relation R plays a role in the argument. There are two important ingredients to the typical treatment of this relation when it is defined in a rule-based and syntax-directed fashion. First, it is assumed the relation is completely specified by the rules pertaining to it, *i.e.* that a closed-world assumption applies to these rules. This assumption justifies a case analysis style of argument based on the definition of the relation. Second, for the argument to be effective, it is usually necessary to invoke induction with respect to the relation. This induction is based, again, on the definition of the relation: the assumption generally is the property of interest holds for any instance of the relation R that appears in the definition of the instance for which it is being proved.¹

In the traditional setting for such proofs, the definition of a language is assumed to be provided in its entirety at the outset. The closed-world assumption has an obvious validity in this situation. However, this assumption breaks down in our language extensibility framework. In this context, the identification of syntactic constructs, as well as the relations over them, is typically distributed across language components that come together at a much later point in the overall design. This is too late a stage to be contemplating metatheoretic properties or proofs for them for at least two reasons. First, metatheoretic properties often play an intrinsic role in the design of the language and are not meant to be "stuck on" after the fact. Second, delaying the verification task till the point of composition means the original designers of the particular language component, who likely understand its functionality the best, will not have a role to play in it.

The main thrust of this work is to address the issue identified above. We first consider the properties we have identified as foundational ones. We assume these properties to be spelled out by the host language, based on semantic relations that are identified when the framework starts to be elucidated. For example, the host language specified in Section 2 may introduce the following property using as atomic formulas relations it has introduced:

$$\begin{aligned} \forall \Gamma, e, ty_e, \gamma, v_e. \gamma \vdash e \Downarrow v_e \supset \Gamma \vdash e: ty_e \supset \\ (\forall x, ty_x, v_x. \, lkpTy(\Gamma, x, ty_x) \land lkpVal(\gamma, x, v_x) \supset nilty \vdash v_x: ty_x) \supset nilty \vdash v_e: ty_e \quad (1) \end{aligned}$$

This is a type preservation property over expressions: it asserts that if an expression e evaluates to a value v_e , e has type ty_e , and the evaluation context respects the typing determined by the typing context, then v_e must also have type ty_e . As we have noted, the proof of a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ will usually call for a case analysis over the definition of the relation R. We propose to modularize the proof effort by delegating the responsibility for dealing with the case for each particular syntactic construct to the component, whether the host language or an extension, that introduces it. Thus, in the example presented, the argument for the cases of the evaluation

¹ Inductive arguments are often based on the structure of expressions in the syntactic category corresponding to one of the variables in \overline{x} . This is a special case of what is described here: these situations can be visualized as ones in which the structure of the syntactic category is made explicit via a predicate and the property to be proved is relativized to the validity of that predicate.

relation for different expression forms will be constructed independently within the host language and the list and security extensions. For this idea to work, there must of course be a mechanism for automatically combining the individual proof fragments into an actual proof of the property for a complete language. Care is needed in the construction of the proof fragments for this to be possible. For instance, a component that develops a proof fragment must be sensitive to the fact that it has only a partial view of the full language. Thus, any further case analysis that is needed must use a properly delimited version of the closed-world assumption. Fortunately, it is possible to describe criteria that are automatically enforceable and not unduly restrictive towards ensuring this property, as we show in Section 5.

We next consider auxiliary properties, those introduced by extensions. As a concrete example of why such a capability may be useful, consider the security extension described in Section 2 that provides mechanisms for dealing with sensitive data while using the programming capabilities afforded by the host language and other extensions. That extension also introduces the *secure* relation that encapsulates a static analysis meant to ensure the secrecy of data in the course of execution. The soundness of this analysis needs, of course, to be validated. Letting *eqpublicvals*($\Sigma, \gamma_A, \gamma_B$) be a shorthand for the formula

$$\forall x. \, lkpSec(\Sigma, x, public) \supset (\forall v. \, lkpVal(\gamma_A, x, v) \supset lkpVal(\gamma_B, x, v)) \land (\forall v. \, lkpVal(\gamma_B, x, v) \supset lkpVal(\gamma_A, x, v))$$

we may encapsulate this soundness in the following metatheoretic property:

$$\forall s, \Sigma, sl, \gamma_A, \gamma_B, \Sigma', \gamma'_A, \gamma'_B. (\gamma_A, s) \Downarrow \gamma'_A \supset (\gamma_B, s) \Downarrow \gamma'_B \supset \Sigma \ sl \vdash secure(s, \Sigma') \supset eqpublicvals(\Sigma, \gamma_A, \gamma_B) \supset eqpublicvals(\Sigma', \gamma'_A, \gamma'_B)$$
(2)

This formula formalizes the fact that information from private variables does not leak into public data during the evaluation of a program that satisfies the *secure* relation: the formula holds if it is the case that, when a "secure" statement is executed in two different states (γ_A and γ_B) that assign the same values to public variables $(eqpublicvals(\Sigma, \gamma_A, \gamma_B))$ but possibly differing values to private variables, then the resulting states will also assign the same values to the public variables $(eqpublicvals(\Sigma, \gamma'_A, \gamma'_B))$. Now, the proof of such a property can obviously not be distributed to the different components in a composite language. However, the extension introducing the property would also not quite be able to construct a proof of it by itself because it does not have a priori knowledge of all the extensions with which it will be composed. The approach we develop for overcoming this difficulty uses projections to describe constraints on the behavior of extensions. More specifically, the host language identifies formulas relating the attributes associated with extension constructs to those of the host language constructs to which they project. The task of verifying these formulas hold is then delegated to each extension that builds on the host language. Once such properties have been established, the extension responsible for proving an auxiliary property gets to use them in the course of reasoning about the behavior of extensions about which it otherwise knows nothing. We develop a structure for modular reasoning based on these ideas and establish its soundness in Section 6.

An important aspect of our soundness arguments for the reasoning structures we develop, whether for foundational or for auxiliary properties, is that they are constructive: in particular, they yield a method for assembling proofs developed independently for each component into proofs for the relevant properties for the complete language once its parts have been identified.

4 A Structure for Reasoning about Relational Specifications

The technical developments in this paper require us to be more specific about the structure of proofs. Towards this end, we will frame such reasoning within a logic called \mathcal{G} [6] that provides the basis for the Abella proof assistant [1]. We present this logic below in a manner suitable for its use in this paper, in the process also motivating its choice for the kind of metatheoretic reasoning that is of interest. We will utilize the consistency result for the logic [6] implicitly in our soundness arguments in later sections. In particular, we will read soundness for the methodology that we articulate as the ability to generate a proof in the logic for a metatheorem for a complete language from the (partial) proofs that are provided by each participating component.

While \mathcal{G} is a logic that is based on the simply-typed lambda calculus and includes logical devices for treating binding notions, only a limited, first-order version of it is needed in this work and we will therefore present it as such. From this perspective, its collection of terms and atomic formulas are determined in the usual way for a typed first-order logic once a set of sorts and a set of constant and predicate or relation symbols with associated types have been identified. There is a natural correspondence between the sorts in the logic and the syntactic categories identified in the component \mathscr{C} of a language specification in the style of Section 2. Further, this correspondence extends to one between the constructors in the collection $\mathbb C$ in the language specification and the constants in the logic and, similarly, the relations in \mathscr{R} and \mathscr{T} in the language specification and predicate symbols in the logic. Arbitrary formulas are constructed from atomic formulas using the logical constants \top and \perp ; the (infix) connectives \land , \lor , and \supset ; and existential and universal quantification. Formulas of the last two kinds are written as $\exists x : \alpha, F$ and $\forall x : \alpha, F$, respectively, where α denotes the sort associated with the variable. While it is essential to identify the types associated with quantified variables, we shall often assume these can be determined from the context, writing the quantified formulas as $\exists x. F$ and $\forall x. F$ instead, and we will also abbreviate formulas of the form $\mathcal{Q}x_1,\ldots,\mathcal{Q}x_n$. F where \mathcal{Q} is \exists or \forall as $\mathcal{Q}x_1,\ldots,x_n$. F. The logic treats as indistinguishable two formulas that can be made identical by a consistent, capture-avoiding renaming of the variables that are bound by quantifiers in them, a fact that will be used implicitly in our discourse.

Definition 1 (Substitutions, Unification). A substitution identifies a finite sequence of terms t_1, \ldots, t_n over the vocabulary determined by a suitable language L with a sequence of variables x_1, \ldots, x_n that are pairwise of the same type; such a substitution is denoted by $\{\langle x_1, t_1 \rangle, \ldots, \langle x_n, t_n \rangle\}$ and it has x_1, \ldots, x_n as its domain and t_1, \ldots, t_n as its range. The application of a substitution θ to a term t or a formula F, written, respectively, as $t[\theta]$ and $F[\theta]$, corresponds to the replacement in t or F of the variables identified by θ by the corresponding terms, taking care in the latter case to rename quantified variables to avoid inadvertent capture. The composition of two substitutions θ_1 and θ_2 , denoted by $\theta_2 \circ \theta_1$ is a substitution θ such that $e[\theta] = e[\theta_1][\theta_2]$ for any term or formula e; such a substitution can always be provided explicitly. A unification problem \mathcal{U} is a collection $\{\langle e_1^1, e_1^2 \rangle, \ldots, \langle e_m^1, e_m^2 \rangle\}$ of pairs of atomic formulas or terms of identical type. A unifier for \mathcal{U} is a substitution θ such that $e^1[\theta] = e^2[\theta]$ for every pair $\langle e^1, e^2 \rangle$ in \mathcal{U} . \mathcal{U} is said to be solvable and the pairs of terms in \mathcal{U} are said to be unifiable if there is a unifier for \mathcal{U} can be obtained by composition with another substitution, i.e. there is a substitution θ'' such that $\theta' = \theta'' \circ \theta$. It is a known fact that, in the context of interest, \mathcal{U} has a most general unifier if it is solvable.

The logic \mathcal{G} is formulated in the style of a sequent calculus. Sequents have the form $\Sigma : \Gamma \longrightarrow F$, where Γ is a multiset of *assumption formulas*, F is a *conclusion* or *goal* formula, and Σ is a collection of (typed) variables called the *eigenvariable context* that represents universal quantification at the

Figure 7: The rules in \mathcal{G} for the logical symbols

$$\frac{\Sigma[\theta]:\Gamma\longrightarrow B[\theta]}{\Sigma:\Gamma\longrightarrow A} \ def\mathcal{R}$$

 $\forall \overline{x}. H \triangleq B$ is a variant of a clause in \mathcal{D} and θ is a substitution such that $A = H[\theta]$

$$\left\{ \begin{array}{l} \Sigma[\theta]: \Gamma[\theta], B[\theta] \longrightarrow C[\theta] \mid \forall \overline{x}. H \triangleq B \text{ is a variant of a clause in } \mathcal{D} \\ \text{named away from } \Sigma \text{ and } \theta \text{ is an mgu for } \left\{ \langle A, H \rangle \right\} \end{array} \right\} \\ \overline{\Sigma: \Gamma, A \longrightarrow C}$$

Figure 8: The rules for introducing atomic formulas based on a definition \mathcal{D}

proof level. For the sequent to be well-formed, the formulas in $\Gamma \cup \{F\}$ must be well-formed relative to a given collection of constant and predicate symbols and the variables in Σ . We shall limit our attention to well-formed sequents; specifically, we will consider the proofs of only wellformed sequents and the rules of the logic are such that they preserve this property. From a proof search perspective, a sequent represents a state in the process of proving a formula F; the process starts out with the sequent $\emptyset : \cdot \longrightarrow F$ and evolves through the use of inference rules into a set of obligations represented by other sequents.

The core of \mathcal{G} comprises a set of rules that interpret the logical symbols. These rules are shown in Figure 7. The premise sequents in the rules $\forall \mathcal{L}$ and $\forall \mathcal{R}$ require the instantiation of the quantified formulas with terms. These terms must be of the same type as the quantified variable and they must be constructed using only the constants of the logic and the variables in the eigenvariables set of the sequent. The $\forall \mathcal{R}$ and $\exists \mathcal{L}$ rules have a proviso that the quantified variable must be fresh to the eigenvariable set of the conclusion sequent. This requirement can always be achieved by a renaming of the bound variable. The id rule, which recognizes that a sequent in which the conclusion formula is included in the assumption formulas has a trivial proof, requires the conclusion formula to be atomic. While this requirement is not essential, it will simplify some of the later arguments. Finally, we will often write the eigenvariable context of a sequent as a listing of just its variables, assuming their types can be determined unambiguously from their occurrences in the formulas in the sequent.

An aspect of \mathcal{G} that sets it apart from other first-order logic is its treatment of atomic predicates or relations through fixed-point definitions. Formally, \mathcal{G} is a logic that is parameterized by a definition \mathcal{D} that comprises a set of *definitional clauses* of the form $\forall \overline{x}. H \triangleq B$, where H is an atomic formula and B is an arbitrary formula;² H is called the head of a clause in this form, B is called its body and the sequence of variables \overline{x} is called its binder. Two clauses that differ only in the names chosen for the variables in their binders are considered to be equivalent and are referred to as variants of each other. Further, a clause is said to be named away from a sequence of variables Σ if the variables in its binder are distinct from those in Σ . Each definitional clause is intended to be a partial specification of the relation denoted by the predicate symbol of H, with all such clauses determining its complete definition. This interpretation is made precise by the rules in Figure 8 for "introducing" atomic formulas on the left and right sides of a sequent. In these rules, we take the application of a substitution θ to an eigenvariable context Σ to be the removal from Σ of the variables in the domain of θ and the addition to Σ of the variables in its range. The application of a substitution to a multiset of formulas corresponds to its application to each member of the multiset. The $def\mathcal{R}$ rule encodes the idea that we may prove an instance of the head of a clause by proving its body. The $def\mathcal{L}$ rule is the more novel and consequential part of the treatment of fixed-point definitions. Specifically, it encodes the property that an atomic formula holds only by virtue of one of the clauses in the definition. As such, it provides the basis for a case analysis style of reasoning as we shall see presently.

The logic actually builds in a *least fixed-point* interpretation of definitions, thereby providing the basis for reasoning inductively about them. This capability is realized by associating a measure via annotations with atomic formulas and building in the idea that this measure decreases when an assumption formula is unfolded via a definitional clause.³ The annotations are of the form $@^i$ and $*^i$ for non-zero natural numbers *i*, where the superscript is indicates the number of repetitions of @ and *, respectively. These annotations work in tandem, the latter constituting a smaller measure

 $^{^{2}}$ Definitions must satisfy certain "stratification" conditions for the logic to be consistent. We elide a discussion of this matter, noting only that these conditions will always be satisfied in the use we make of definitions to encode simple rule-based specifications of relations in language presentations.

³For simplicity of presentation, we limit ourselves in this paper to the particular realization of induction in Abella, rather than the more general logical treatment originating from [18].

$$\frac{\overline{\Sigma:\Gamma,A^{*^{i}}\longrightarrow A^{*^{i}}}^{id^{**}}}{\Sigma:\Gamma,A^{@^{i}}\longrightarrow A^{@^{i}}}^{id^{@}}} \frac{id^{@}}{\Sigma:\Gamma,A^{*^{i}}\longrightarrow A}^{id^{*}}}{\Sigma:\Gamma,A^{*^{i}}\longrightarrow A}^{id^{*}} \frac{\overline{\Sigma:\Gamma,A^{@^{i}}\longrightarrow A}}^{id^{@}}}{\Sigma:\Gamma,A^{@^{i}}\longrightarrow A}^{id^{@}}}$$

 $\{ \Sigma[\theta] : \Gamma[\theta], (B[\theta])^{*^{i}} \longrightarrow C[\theta] \mid \forall \overline{x}. H \triangleq B \text{ is a variant of a clause in } \mathcal{D}$ named away from Σ and θ is an mgu for $\{\langle A, H \rangle\} \}$ $\Sigma : \Gamma, A^{*^{i}} \longrightarrow C$ $def\mathcal{L}^{*^{i}}$

$$\{ \Sigma[\theta] : \Gamma[\theta], (B[\theta])^{*^{i}} \longrightarrow C[\theta] \mid \forall \overline{x}. H \triangleq B \text{ is a variant of a clause in } \mathcal{D}$$
 named away from Σ and θ is an mgu for $\{\langle A, H \rangle\} \}$
 $\Sigma : \Gamma, A^{@^{i}} \longrightarrow C$ $def\mathcal{L}^{@}$

$$\frac{\Sigma:\Gamma,\forall\overline{x_1}.F_1\supset\cdots\supset\forall\overline{x_m}.A^{*^i}\supset F\longrightarrow\forall\overline{x_1}.F_1\supset\cdots\supset\forall\overline{x_m}.A^{@^i}\supset F}{\Sigma:\Gamma\longrightarrow\forall\overline{x_1}.F_1\supset\cdots\supset\forall\overline{x_m}.A\supset F} ind_m^i, A \text{ is atomic}$$

Annotations of the form $*^i$ and $@^i$ must not already appear in the conclusion sequent

Figure 9: The induction rule and associated rules for annotated formulas

than the former. Annotations are introduced into formulas by the rule ind_m^i shown in Figure 9. This rule reduces the task of proving a formula of the form $\forall \overline{x_1}, F_1 \supset \cdots \supset \forall \overline{x_m}, A \supset F$, where A is an atomic formula, to showing this formula holds when A has the measure $@^i$ associated with it under the assumption that it holds when A has the smaller measure $*^i$. The measure associated with an atomic assumption formula decreases when it is unfolded using a definition, a fact encoded in the $def\mathcal{L}^{@^i}$ variant of the $def\mathcal{L}$ rule; the annotation notation on a possibly non-atomic formula that is used in this rule denotes the distribution of the annotation to its atomic constituents. The $def\mathcal{L}^{*^i}$ rule reflects the fact that the lower measure is maintained through further unfoldings. The remaining rules adapt the *id* rule to the situation where atomic formulas may have annotations and the content of each of them follows easily from the interpretation of the annotations. In all these rules, A is used as a schematic variable for an atomic formula.

The treatment of fixed-point definitions makes \mathcal{G} a logic that is well-suited to the task of reasoning about rule-based specifications. Towards illuminating this aspect, we consider a simple example built around the definition of the *append* predicate that relates three lists. A rule-based definition of this predicate is shown below:

$$\frac{\text{append}(L_1, L_2, L_3)}{\text{append}(\text{cons}(X, L_1), L_2, \text{cons}(X, L_3))}$$

In these rules, *nil* is a constructor of list type that represents the empty list and *cons* is a constructor that represents a list obtained by adding a head element to an existing list. Moreover, tokens that begin with uppercase letters represent schematic variables. This definition can be rendered into a definition in \mathcal{G} that comprises the following two clauses:

$$\forall \ell. append(nil, \ell, \ell) \triangleq \top \\ \forall x, \ell_1, \ell_2, \ell_3. append(cons(x, \ell_1), \ell_2, cons(x, \ell_3)) \triangleq append(\ell_1, \ell_2, \ell_3)$$

When these clauses are used to simplify the conclusion formula in a sequent, they have the flavor of logic programming: essentially, they figure in a backchaining-style search for a proof of the formula. When they are used on the left of a sequent to analyze an assumption formula, they realize a closed-world interpretation that is usually implied in rule-based systems and that is beyond the capabilities of logic programming. In this particular instance, they enforce the requirement that an *append* relation can be true only by virtue of these rules. Moreover, the logic supports the ability to reason inductively on the derivation of such a relation.

Towards bringing these aspects of the logic out, let us consider proving the following formula

$$\forall \ell_1, \ell_2, \ell_3, \ell_4. append(\ell_1, \ell_2, \ell_3) \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4$$

which asserts that once the first two arguments to *append* are fixed, the relation holds for a unique third argument. The attempt to prove this statement starts with the following sequent:

 $\varnothing: \cdot \longrightarrow \forall \ell_1, \ell_2, \ell_3, \ell_4. \operatorname{append}(\ell_1, \ell_2, \ell_3) \supset \operatorname{append}(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4.$

An informal argument will proceed by induction on the derivation of either the first or the second antecedent of the formula. In the formal system, we may use the ind_1^1 rule to reduce the proof obligation to the following sequent:

$$\begin{split} \varnothing : \forall \ell_1, \ell_2, \ell_3, \ell_4. \ append(\ell_1, \ell_2, \ell_3)^* \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4 \longrightarrow \\ \forall \ell_1, \ell_2, \ell_3, \ell_4. \ append(\ell_1, \ell_2, \ell_3)^{@} \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4 \end{split}$$

Using rules for logical symbols on the right of the sequent, we may further reduce the task to proving the sequent

$$\begin{split} \ell_1, \ell_2, \ell_3, \ell_4 : \\ \forall \ell_1, \ell_2, \ell_3, \ell_4. \ append(\ell_1, \ell_2, \ell_3)^* \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4, \\ append(\ell_1, \ell_2, \ell_3)^@, append(\ell_1, \ell_2, \ell_4) \longrightarrow \ell_3 = \ell_4 \end{split}$$

An informal proof would proceed at this point by unfolding the second assumption formula, the one annotated with @, something that can be achieved within \mathcal{G} by using the rule $def\mathcal{L}^{@}$. Doing so leads to the obligation to prove the sequent

 $\ell_1, \ell_2, \ell_3, \ell_4:$ $\forall \ell_1, \ell_2, \ell_3, \ell_4. append(\ell_1, \ell_2, \ell_3)^* \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4,$ $append(nil, \ell_2, \ell_4) \longrightarrow nil = \ell_4$

and the sequent

$$\begin{array}{l} \ell_1, \ell_2, \ell_3, \ell_4, x, \ell_5, \ell_6: \\ \forall \ell_1, \ell_2, \ell_3, \ell_4. \ append(\ell_1, \ell_2, \ell_3)^* \supset append(\ell_1, \ell_2, \ell_4) \supset \ell_3 = \ell_4, \\ append(cons(x, \ell_5), \ell_2, \ell_4), append(\ell_5, \ell_2, \ell_6)^* \longrightarrow cons(x, \ell_6) = \ell_4 \end{array}$$

Observe how the unfolding causes the annotation on the assumption formula that has replaced the original one in the second sequent to change to a *. Since it is in this form, it can be used to discharge the first antecedent in the induction hypothesis. The proof can now be completed by invoking case analysis, *i.e.* the *defL* rule, with respect to the second assumption formula in the two sequents and, in the second case, "invoking" the induction hypothesis through uses of the $\supset \mathcal{L}$ and relevant variants of the *id* rule.

We present below a substitution operation on proofs and some metatheorems about \mathcal{G} that will be useful in later discussions.

Definition 2 (Proof Substitutions). Let π be a proof in \mathcal{G} and let θ be a substitution. The application of θ to π , denoted by $\pi[\theta]$ is defined recursively on the structure of π as follows:

- Suppose the last rule is defL or one of its variants and the conclusion of this rule is the sequent Σ : Γ, A^a → C, where a is the empty string or one of *ⁱ and @ⁱ. Further, suppose that the premise derivations for the rules are π₁,..., π_n, where π_i derives a sequent obtained by considering a clause in the definition of the form ∀x_i. H_i ≜ B_i and an mgu θ_i for {⟨A, H_i⟩}. For each i, 1 ≤ i ≤ n, if {⟨A[θ], H_i⟩} has a unifier, then there must be a substitution ρ_i such that ρ_i ∘ θ_i is its mgu. In this situation, the rule is to be replaced by a rule-like structure in which the conclusion sequent is Σ[θ] : Γ[θ], A^a[θ] → C[θ] and that has as premise derivations π_i[ρ_i] for each i such that {⟨A[θ], H_i⟩} has a unifier.
- 2. In all other cases, if the conclusion sequent is $\Sigma : \Gamma, A \longrightarrow C$ and the premise derivations are π_1, \ldots, π_n , then this rule is replaced by a rule-like structure that has $\Sigma[\theta] : \Gamma[\theta], A[\theta] \longrightarrow C[\theta]$ as the conclusion sequent and $\pi_1[\theta], \ldots, \pi_n[\theta]$ as premise derivations.

Theorem 1. Consider a well-formed sequent S of the form $\Sigma : \Gamma \longrightarrow F$.

- 1. If S has a proof π , then any well-formed sequent $\Sigma' : \Gamma' \longrightarrow F'$ where the formulas in $\Gamma' \cup \{F'\}$ are obtained by renaming the free variables in $\Gamma \cup \{F\}$ in a consistent and logically correct way, i.e., in a way that avoids inadvertent capture, has a proof whose structure is identical to that of π .
- 2. If S has a proof of height h then, for any substitution θ , the sequent $\Sigma[\theta] : \Gamma[\theta] \longrightarrow F[\theta]$ has a proof of height at most h.

Proof. The first claim is proved by a straightforward induction on the structure of π . For the second claim, it suffices to show that for any proof π , the structure $\pi[\theta]$ is also a proof. This can be seen again via an induction on the structure of π . Note that $\pi[\theta]$ may lose some branches at $def\mathcal{L}$ rules in comparison with π . While the structure of the proof may change in this manner, the height of the transformed proof will be at most that of the original one.

The first clause in the theorem assures us the particular names chosen for the variables in the formulas in a sequent do not matter and neither does the specific extent of the eigenvariable context so long as it suffices to ensure the sequent is well-formed. A consequence of the second clause is that we may adjust the choice of mgu in the use of the $def\mathcal{L}$ rule and its variants in a proof without increasing its height. We will use these properties in later sections.

We have already noted how the syntactic categories in \mathscr{C} and the constructors in \mathbb{C} and the relations in \mathscr{R} and \mathscr{T} in a language specification translate into the vocabulary of \mathcal{G} . The example we have considered indicates how the the rules in \mathbb{R} and \mathbb{T} translate into definitional clauses. Once all the rules for each relation have been assembled together, *i.e.*, when we are reasoning about a composite language, the clauses deriving from them can be collected into a definition in \mathcal{G} . We will exploit these correspondences in our discussions to transit seamlessly between a language specification and its formalization in the logic. One specific manifestation of this is that we will treat formulas of the kind shown in Section 3, *i.e.*, formulas constructed using logical symbols over relations and other vocabulary identified in Section 2, directly as if they are formulas in \mathcal{G} even though an actual implementation needs an intermediate encoding step.

Following the discussion in the previous section, the metatheoretic properties whose proofs we will consider will be represented by formulas of the form $\forall \overline{x}. R(\overline{t}) \supset F$ where $R(\overline{t})$ denotes an atomic predicate. We shall consider constructing proofs of a specific form for such properties. These proofs will end with a case analysis over a possibly-annotated version of $R(\bar{t})$, followed by rules that introduce logical symbols in the conclusion formula and some number of uses of the induction rule; the preceding part of the proof will obviously be distinct branches or fragments that establish each of the sequents that arise from considering the different cases in the definition of $R(\bar{t})$. We shall refer to a proof that has this form as one in *canonical form*. In the general situation, a proof of this kind will be attempted after some other properties have been established and can therefore be used as lemmas by virtue of the *cut* rule. If L is the specification of the composite language encoded in \mathcal{G} and P represents the metatheoretic property, we shall write $proven(L, \mathcal{L}, P, \pi)$ to denote the fact that π is a complete canonical form proof of P and where the properties in the set \mathcal{L} are used as lemmas.

5 Modular Proofs for Foundational Properties

The approach to modularizing the proof of foundational properties we had outlined in Section 3 can now be given concreteness. The main part of a canonical-form proof for a formula of the form $\forall \overline{x}. R(\overline{t}) \supset F$ is the proof of a collection of sequents, one corresponding to each of the rules defining R that is applicable to the derivation of $R(\overline{t})$. Now, the rules relevant to a composite language are obtained by combining the ones in the host language and each of the extensions. We propose accordingly to let each language component produce a proof of sequents corresponding to its new rules independently, with the expectation we can combine the different fragments into a complete proof for a composite language at the time the composition is determined.

As has been previously noted, there is an issue that needs to be addressed to make this scheme work. When a component attempts to construct a proof for a sequent associated with a particular case in the definition of R, it does so without knowledge of how other extensions might add to the definitions of relations that are in the shared vocabulary, *i.e.*, that are identified by the host language. However, proofs in \mathcal{G} are sensitive to the extent of a definition. Thus, if we do not properly restrict the manner in which proof fragments are constructed in isolated components, we will not be able to combine these into a valid proof for the complete language.

An observation that allows us to overcome this difficulty is that the extensibility framework limits the way in which the definitions for relations introduced by the host language can be enhanced: additional rules can be added by an extension only for those cases where the primary component for the relation is constructed using a syntactic form introduced by that extension. Thus, if we limit the use of case analysis to those situations where we know the top-level structure of the primary component argument is a constructor introduced by the extension or the host language, then we can be certain the case analysis will be comprehensive even when other components are added to the mix. The following definition identifying "valid" proof fragments is a rendition of this idea.

Definition 3 (Proofs for cases for foundational properties). Let M be the host language or an extension (relative to some host language) in a library constructed within the extensibility framework and let L be the language identified by M. Further, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary determined by the host language in the library. Finally, let P have a canonical proof relative to L and the lemmas in \mathcal{L} in which case analysis over a relation $R'(\overline{t'})$ in the proofs of the sequents resulting from the case analysis over $R(\overline{t})$ occurs only in the following situations:

- 1. the term in the primary component position for R' in $R'(\overline{t'})$ has a constructor as its top-level symbol, or
- 2. M is an extension E and R' and its primary component type have been introduced by E.

Then we denote the fact that π_1, \ldots, π_m are the proofs for the sequents arising from the case analysis on $R(\bar{t})$ using the rules introduced by M in such a proof by writing $pp_M(L, \mathscr{L}, P, \{\pi_1, \ldots, \pi_m\})$.

To demonstrate the kinds of case analysis disallowed by this definition, consider proving type preservation, Property 1, for the sequent arising from the E-ADD rule given by the host language. Our initial sequent is

$$\begin{split} & \Gamma, e_1, e_2, ty, \gamma, i_1, i_2, i: \gamma \vdash e_1 \Downarrow intlit(i_1), \gamma \vdash e_2 \Downarrow intlit(i_2), plus(i_1, i_2, i), \Gamma \vdash add(e_1, e_2): ty, \\ & \forall x, ty_x, v_x. \, lkpTy(\Gamma, x, ty_x) \supset lkpVal(\gamma, x, v_x) \supset nilty \vdash v_x: ty_x \longrightarrow nilty \vdash intlit(i): ty \end{split}$$

The case analysis that produced this sequent instantiated the expression e from the original property with $add(e_1, e_2)$ and introduced premises that both e_1 and e_2 evaluate to integer literals, as well as the expression as a whole evaluates to an integer literal of their sum. Case analysis is *not* permitted on either $\gamma \vdash e_1 \Downarrow intlit(i_1)$ or $\gamma \vdash e_2 \Downarrow intlit(i_2)$ because the evaluation relation is introduced by the host language and the terms in their primary components, e_1 and e_2 , do not have constructors as their top-level symbols. What expressions can instantiate e_1 and e_2 and how evaluation may be defined on them is dependent on other extensions that may be added in a composite language, so any case analysis carried out in the context of the host language alone cannot predict all the relevant rules. Conversely, case analysis *is* permitted on the typing assumption $\Gamma \vdash add(e_1, e_2) : ty$ because the argument in its primary component position, $add(e_1, e_2)$, has the *add* constructor as its top-level symbol, and thus no rule introduced by an extension can pertain to it. This case analysis shows *ty* must, in fact, be *int*. Then we can simplify the conclusion with the T-INTLIT rule, finishing the proof.

The following lemma makes explicit the rationale for the restrictions on proof fragments.

Lemma 2. Let H be the host language and let $\{E_1, \ldots, E_n\}$ be a collection of extensions in a library constructed in the extensibility framework. Let M be H or an E_i for some i such that $1 \le i \le n$, let L be the language identified by M, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary determined by the host language, and let ρ be a collection of proofs such that $pp_M(L, \mathscr{L}, P, \rho)$ holds. Then

- 1. the sequents that arise from the rules for R in M in a case analysis over $R(\bar{t})$ in a canonical proof for P in the context of the language $H \triangleleft \{E_1, \ldots, E_n\}$ are exactly the same as the ones that are proved by the proof fragments in ρ , and
- 2. each proof π in ρ constitutes a complete proof of the corresponding sequent S even in the context of the language $H \triangleleft \{E_1, \ldots, E_n\}$.

Proof. The definition of R in the language $H \triangleleft \{E_1, \ldots, E_n\}$ is obtained exactly by collecting together all the clauses for it in each of the components. It is obvious from this that (1) holds.

The reason why the second clause is true can be seen by considering the inference steps in the logic. The only inference rules that are dependent on the definition parameterizing the logic are $def\mathcal{R}$ and the variants of $def\mathcal{L}$. In the first case, the clause that provides the basis for the $def\mathcal{R}$ rule in π will also be available relative to the larger language, so the proof step is still valid. We consider the other cases below, noting the distinction between the variants of $def\mathcal{L}$ is irrelevant to the argument.

We note first that the definition of a relation whose primary component is introduced by an extension cannot change with the addition of more extensions. Thus, any case analysis over such relations within an extension will remain unchanged when the language context is determined by the addition of other extensions. If a relation is introduced by an extension but its primary component type is introduced by the host language, the relation is defined for other extensions by instantiating the projection rule with each new constructor they introduce. Thus any new rules added in the composition cannot apply in case analysis in the language of M where the primary component had to be built by a constructor known in the language of M. Similarly, in the case a relation and its primary component type are introduced by the host language, case analysis must in general consider how the relation is modified by rules for it that are introduced by other extensions. However, the extensibility framework does not permit an extension to introduce rules that apply to expression forms introduced by other components in the library in this situation. For this reason, the restriction that case analysis be used in this case only when the argument at the location of the primary component has a rigid structure ensures that a case analysis that is carried out ignoring other extensions must remain unchanged when they are added to the mix. In summary, the restrictions on proof fragments ensure that case analysis carried out locally is complete even when the context is expanded to include other extensions.

We can now define the idea of combining proof fragments to yield a purported proof for a foundational property relative to a composite language.

Definition 4 (Proof composition). Let H be the host language and let E_1, \ldots, E_n be a collection of extensions in a library constructed in the extensibility framework. Further, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary determined by the host language. Finally, let ρ_0 be such that $pp_H(H \triangleleft \emptyset, \mathscr{L}, P, \rho_0)$ holds and for $1 \leq i \leq n$ let ρ_i be such that $pp_{E_i}(H \triangleleft \{E_i\}, \mathscr{L}, P, \rho_i)$ holds. Then $compose(\rho_0, \ldots, \rho_n)$ represents a proof structure for P that ends with a case analysis on $R(\overline{t})$ followed by rules for introducing logical symbols in the conclusion formula and some number of invocations of the induction rule, and where the proof obligations deriving from the case analysis on $R(\overline{t})$ are discharged by the proofs in $\rho_0 \cup \rho_1 \cup \ldots \cup \rho_n$.

Note that clause (1) of Lemma 2 ensures the coherence of the above definition: there is a one-to-one correspondence between the cases that arise for the composite language and the proof fragments for each of the components participating in that language.

Theorem 3. Let H be the host language and let E_1, \ldots, E_n be a collection of extensions in a library constructed in the extensibility framework. Further, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary determined by the host language. Finally, let ρ_0 be such that $pp_H(H \lhd \emptyset, \mathscr{L}, P, \rho_0)$ holds and, for $1 \le i \le n$, let ρ_i be such that $pp_{E_i}(H \lhd \{E_i\}, \mathscr{L}, P, \rho_i)$ holds. Then proven $(L, \mathscr{L}, P, \text{ compose}(\rho_0, \ldots, \rho_n))$ holds.

Proof. As previously noted, the sequents that need to be proved in the kind of proof of P that $compose(\rho_0, \ldots, \rho_n)$ is intended to be correspond exactly to the sequents the proof fragments in $\rho_0 \cup \ldots \cup \rho_n$ prove. Thus, the theorem would be true if these proof fragments, which are constructed relative to smaller languages, are also proofs of the corresponding sequents relative to the composed language. That this is the case is verified by Lemma 2.

Theorem 3 provides the theoretical basis for our approach to the modular development of proofs for foundational metatheoretic properties. In this approach, the host language articulates the desired metatheorem at the outset. The designers of the host language and of each extension, who build on the host language and hence must be cognizant of the metatheorem, then develop proofs for the cases within the canonical proof structure for the theorem relative to the language they each identify, taking care to adhere to the restrictions imposed by Definition 3. These "proof fragments," which are stored by the components that developed them, can then be automatically combined as per Definition 4 to yield a proof of the property for the composite language at the time

when the composition is determined. Of course, it is not necessary actually to construct a proof for the metatheoretic property for the composite language: by virtue of Theorem 3, the existence of proof fragments with each component is already a guarantee such a proof exists for the overall language.

To illustrate the above ideas, let us consider the construction of a proof for type preservation for languages resulting from our example library. The host language proves type preservation for each evaluation rule it introduces, adhering to the restrictions given by Definition 3, and thus these proofs are still valid in the context of the composed language. To see an example of this, look at the proof for the case of the E-ADD rule above. The initial sequent is the same, as it comes from the same rule in the context of the composed language as in the setting of the host language alone. In the limited setting, we analyzed the typing derivation $\Gamma \vdash add(e_1, e_2) : ty$, where the only applicable rule was T-ADD. In the composed language, this is still the only applicable typing rule, so the case analysis has the same result. Similarly, we used the T-INTLIT rule to simplify $nilty \vdash intlit(i)$: int; this rule is also part of the composed language, so we can use it for simplification in the expanded setting as well. Thus our modular proof is still applicable even though we have expanded the language in which we are applying it. The list extension also proves type preservation for each rule it introduces, adhering to the restrictions so its proofs remain valid, but with knowledge of both itself and the host language. The security extension introduces no expression evaluation rules, and thus has no cases to prove for this property. The full set of cases we have in the composed language is the union of those for the rules introduced by the host language and the list extension. as proved in Lemma 2. Since each case also has a proof given by the host language or list extension, depending on which one introduced the rule giving rise to the case, we can build the full proof from their modular proofs.

A question that arises in this context is if the limitations on case analysis in support of modular proofs severely curtail the proofs that can be developed. Our experimentation indicates this not to be the case, with two apparent reasons why this is so. First, the use of the induction hypothesis—which applies to all expressions, including the ones constructed using the vocabulary of (other) extensions—often obviates a "second-level" case analysis. In the typical proof scenario, the purpose of the initial case analysis is to produce assumptions with which we may use the induction hypothesis, and thus which need not be further analyzed. Second, in situations where such a second-level case analysis is necessary, it can often be extracted into an auxiliary lemma, proved separately according to our requirements, and used in the main proof. For example, in proving decidability of equality for two expressions e_1 and e_2 , we would generally consider cases on both their forms, but our requirements for modular proofs do not permit this. We can instead prove auxiliary lemmas that the *form* of an expression is decidable, then use these in the equality proof. For example, we can prove an expression is built by the *add* constructor or not, then use this lemma for e_2 in the decidability proof with a top-level case analysis on the form of e_1 when e_1 is built by *add*, avoiding the disallowed second case analysis on e_2 .

6 Modular Proofs for Auxiliary Properties

We now take up the consideration of modularizing reasoning about a metatheoretic property that is introduced by an extension. To recall, extensions different from the one that introduces such a property cannot participate directly in proving it. However, the extension that introduces the property would have difficulty in proving it without help: it does not know the details of the extensions with which it may interact in a composition. To overcome this difficulty, we propose to extend the idea introduced in Section 2 of using projection relations to "understand" extensions at a distance.

The basic structure for auxiliary properties and the proofs we will seek to construct for them will remain the same as that for foundational properties: these properties will still have the form $\forall \overline{x}. R(\overline{t}) \supset F$, and their proofs will end with a case analysis on the definition of R followed by rules that simplify the conclusion formula and some number of uses of the induction rule. The distinguishing characteristic for an auxiliary property is that the case analysis has to be carried out completely within the extension that introduces it. There is no difficulty in doing this if both the relation R and the category for the primary component for R are introduced by the extension because the definition of such a relation remains unchanged under the inclusion of other extensions.⁴ We will therefore not consider this situation further. The only other situations that are possible are those in which the relation is introduced by either the host language or the extension and has as its primary component a syntactic category is introduced by the host language. In these cases, the approach will be to reason specifically for each construct in the primary component category that is volunteered by the extension or the host language and to construct a "generic" argument to cover the cases of constructs introduced by extensions whose form is unknown before an actual composition. The key to the soundness of this method for organizing the reasoning will be to show the generic argument can, in fact, be elaborated automatically into specific ones when all the constructs are known.

For this style of reasoning to be successful, it is important to identify an approach that can support the construction of generic arguments of interesting and useful properties. To facilitate this, we propose the notion of *projection constraints* as a vehicle for reasoning about an extension even when its details are unknown. From a methodological perspective, these constraints, which are based on projection relations, are intended to be ones that afford extensions freedom in defining their semantic attributes while still circumscribing behavior relative to the images in the host language of the constructs they introduce. Concretely, projection constraints take the shape of foundational properties that can be assumed to have been established prior to the attempt to prove an auxiliary property. In this context, our approach to proving an auxiliary property amounts conceptually to proving the property relative to the constructs from the host language and those of the extension that introduces it and then to lifting the proof to all constructs in a composition by exploiting the projection constraints. This lifting, is in, fact the content of the generic argument. The soundness of this "lifting" step can be established directly when the relation R is identified by the extension: in this situation, the projection relation figures specifically in the definition of the relation via the projection rule for the extension and the reasoning therefore has a straightforward inductive structure. The matter is more complicated when the relation R is introduced by the host language. In this case, the relation would have its own definition in other participating extensions and it is necessary to demonstrate that reasoning about it through the projection of the primary component is legitimate.

We develop these ideas in the rest of the section. We introduce the notion of projection constraints in the first subsection below. We then describe a method for constructing a proof for an auxiliary property within the logic \mathcal{G} that accommodates a generic component. The remaining two subsections are devoted to showing the resulting proof, which we call a *proof skeleton*, can be viewed as an actual proof. This is, in fact, the case without qualifications when the relation R is introduced by the extension, as we show in Section 6.3. We describe an additional condition in Section 6.4 whose validity ensures the soundness of proof skeletons when the relation is introduced by the host language; to close the gap, it is necessary to demonstrate that this condition also holds.

⁴Reasoning within the proofs of the sequents that result from the case analysis on $R(\bar{t})$ must still be properly circumscribed, but this matter is no different from that in the case of foundational properties that was discussed in the previous section.

The arguments in both cases are constructive: they identify a method for obtaining a complete proof of the metatheoretic property for any composed language from the proof skeleton constructed within the extension introducing the property.

6.1 **Projection Constraints**

There is often a need to be able to model one extension in the context of another in the extensibility framework. We have seen an example of this in Section 2.3, where it was necessary to have a view of the syntax of another extension to be able to define a new relation in a manner that covered all possible cases in a composite language. There can also be a need to "understand" semantic attributes of static and dynamic varieties for expressions from other extensions. Consider, for instance, the definition of the visibility level of an expression in the security extension in the example library described in Section 2. This definition depends on the variables appearing in an expression. While it can be defined by a projection rule for expressions from other extensions, its coherence depends on the variables in an expression being preserved under projections. As another example, consider Property 2 in Section 3, which asserts that if a program fragment passes a security analysis then it must be the case it will not leak private information. We can try to conduct the necessary reasoning about constructs from other extensions through their projections but this will work only if we can relate the behavior of such constructs to their images. Thus we may need to know the evaluation of the projection of a statement form will terminate if the evaluation of the original form terminates and also that the states resulting from the evaluation in the two cases will be identical.

We have already seen how projections and projection rules help address the first of the two requirements. Projection constraints constitute our proposal to address the second. These are metatheorems that are, once again, of the form $\forall \overline{x}. R(\overline{t}) \supset F$, with the proviso that the relation $R(\overline{t})$ is a projection relation in these properties. One way to look at these properties is that they place constraints on the behavior of extension constructs relative to that of the host language constructs that model them. These constraints are foundational in nature because they are articulated by the host language to set expectations prior to the description of any extension. Moreover, these properties force the extension developer to think carefully about how the constructs they introduce are best modelled in the host language, *i.e.*, about what the appropriate projections are for these constructs from this perspective.

Some examples illustrating the structure and possible uses of projection constraints are relevant at this point. Relative to the extension library from Section 2, the property that the set of variables in an expression are preserved under a projection can be expressed by the following formula:

$$\forall e, e', vs, vs'. \operatorname{proj}_e(e, e') \supset \operatorname{vars}(e, vs) \supset \operatorname{vars}(e', vs') \supset vs \subseteq vs'$$
(3)

The statement of this property uses a "subset" relation not introduced previously but that has an obvious definition. The property that the evaluation of the projection of a statement must terminate, *i.e.*, result in producing a final state, if the evaluation of the statement itself terminates can be expressed as follows:

$$\forall s, s', \gamma, \gamma'. \operatorname{proj}_{s}(s, s') \supset (\gamma, s) \Downarrow \gamma' \supset \exists \gamma''. (\gamma, s') \Downarrow \gamma'' \tag{4}$$

Finally, the requirement that the final state resulting from an evaluation of a statement must be preserved under a projection is captured by the following formula:

$$\forall s, s', \gamma, \gamma_1, \gamma_2, n, v. \operatorname{proj}_s(s, s') \supset (\gamma, s) \Downarrow \gamma_1 \supset (\gamma, s') \Downarrow \gamma_2 \supset lkpVal(\gamma_2, n, v) \supset lkpVal(\gamma_1, n, v)$$
(5)

Observe that all these properties are predicated on projection relations for the relevant categories of expressions; as such, these can be read genuinely as constraints on the behavior of extension constructs based on the behavior of host language constructs that model them. We note also that such properties can be useful in reasoning about the soundness of security analyses within the security extension even when the details of the other extensions participating in a composed language are not known, an aspect on which we elaborate in later subsections.

Projection contraints can help in determining the purpose of a projection relation and, hence, the form that its definition should take. For example, recall that the projection of the expression $cons(e_1, e_2)$ was identified as $eq(e_1, e_2)$ in the list extension in Section 2. This appears strange at the outset. However, the choice becomes a much more natural one in the context of a projection constraint asserting that the variables appearing in an expression are preserved under projections, a property that is itself important to ensuring the soundness of many forms of static analysis. Another thing to note is that, while the predominant use of projection constraints is to provide a means for thinking about extension constructs via their images, their use is not limited to this purpose. Thus, consider the property expressed by the following formula:

$$\forall e, e_1, e_2. \operatorname{proj}_e(e, e_1) \supset \operatorname{proj}_e(e, e_2) \supset e_1 = e_2 \tag{6}$$

This formula expresses the constraint that projections of expressions in our example library must be unique. Such a property can play a role in demonstrating that the security level of an expression is unique, as we shall see later in this section.

For projection constraints to be useful in subsequent arguments, it is, of course, necessary to demonstrate their validity. This can be done in a manner similar to other foundational properties. Conceptually, this task devolves into each extension needing to demonstrate that the constructs it introduces obey the constraints.

6.2 **Proof Skeletons for Auxiliary Properties**

The main content of a canonical proof for a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ is the consideration of the cases that arise out of the rules defining R. If R is a relation whose primary component is in a category introduced by the host language, then these cases must encompass behavior on constructs in the category contributed by all extensions in a composition. However, when the proof is being constructed within a single extension, that extension cannot have specific knowledge of what might be introduced by other extensions. As indicated earlier, we propose to overcome this difficulty by reasoning about such cases in a generic way through their projections, utilizing projection constraints in the process. This subsection makes precise how this style of reasoning may be supported. The soundness of the method is taken up in the next two subsections.

Support for a generic form of argument is realized in two steps. First, a means is provided for representing terms whose structure cannot be examined. Concretely, this is done by adding a special constant ι_{τ} for each syntactic category τ introduced by the host language; in what follows, knowing the specific syntactic category will often be unimportant and we will therefore write the constant (ambiguously) as just ι . Second, a mechanism is provided for treating an arbitrary term via such a constant in the reasoning process, to be interpreted through its projections. Both steps are realized by identifying a "generic" extension relative to a host language.

Definition 5 (Generic Extension). Let $H = \langle \mathscr{C}^H, \mathbb{C}^H, \mathscr{R}^H, \mathbb{R}^H, \mathscr{T}^H, \mathbb{T}^H, \mathbb{S}^H \rangle$ be the host language and E be an extension in a library constructed in the extensibility framework. Then GenExt(H, E), a generic extension relative to H and E, is identified to be an extension $\langle \varnothing, \mathbb{C}, \varnothing, \mathbb{R}, \varnothing, \varnothing, \varnothing \rangle$ such that

- 1. $\mathbb{C} = \{\iota_{\tau} \mid \tau \in \mathscr{C}^H\}$ where each ι_{τ} is a distinct constant different also from all the constants introduced by H and E, and
- 2. \mathbb{R} comprises exactly the rules of the form

$$\frac{T(\iota_{\tau}, y) \quad R(x_1, \dots, x_{i-1}, y, x_{i+1}, \dots, x_k)}{R(x_1, \dots, x_{i-1}, \iota_{\tau}, x_{i+1}, \dots, x_k)}$$

for each $R \in \mathscr{R}^H$ whose i^{th} argument is its primary component, where $T \in \mathscr{T}^H$ is the projection relation for τ and $x_1, \ldots, x_{i-1}, x_{i+1}, \ldots, x_k$ and y are distinct (schematic) variables. T may correspond here to a projection relation with additional parameters. In this case, the host language is required to have specified what these parameters should be in terms of the variables $x_1, \ldots, x_{i-1}, x_{i+1}, \ldots, x_k$.

Let H be a host language and E be an extension and consider the collection of rules in the language $H \triangleleft \{E, GenExt(H, E)\}$ for a relation R that is introduced either by H or by E and whose primary component category is one introduced by H. In addition to the rules explicitly provided by H and E this collection will also include one of the form

$$\frac{T(\iota, y) \quad R(t_1, \dots, t_{i-1}, y, t_{i+1}, \dots, t_k)}{R(t_1, \dots, t_{i-1}, \iota, t_{i+1}, \dots, t_k)}$$

where T is the projection relation for the category of ι . Moreover, there will be exactly one such rule for each relation. When this rule is used in a case analysis, it will lead to a situation where $T(\iota, y)$ and the appropriate instance of $R(t_1, \ldots, t_{i-1}, y, t_{i+1}, \ldots, t_k)$ is added to the assumption set of the sequent. Thus, such a rule provides the basis for reasoning about a generic term representing one introduced by another extension via a property that may be associated with its projection.

Definition 6 (Proof skeleton, generic case). Let H be the host language and E be an extension in a library constructed in the extensibility framework and let L be the language $H \triangleleft \{E, GenExt(H, E)\}$. Further, let P be a formula of the form $\forall \overline{x}. R(\overline{t}) \supset F$ where R is a relation introduced either by Hor by E whose primary component category is introduced by H. By a proof skeleton for P relative to L and a set of lemmas \mathscr{L} we mean a canonical proof for P in the described context in which the clauses encoding the rules from GenExt(H, E) are not used in defR rules in the proofs of sequents resulting from the case analysis over a possibly annotated version of $R(\overline{t})$ and the def \mathcal{L} rule and its variants are used relative to a relation $R'(\overline{t'})$ in these proofs only in the following situations:

- 1. the primary component argument of $R'(\overline{t'})$ is a term whose top-level symbol is a constructor that is introduced by H or E,
- 2. R' and its primary component type are introduced by E, or
- 3. the primary component argument of $R'(\overline{t'})$ is ι and R' is a relation introduced by E.

The restrictions on the use of the def \mathcal{R} and (variants of the) def \mathcal{L} rules described above are referred to in the sequel as "the constraints imposed by the definition on proof fragments". If one of the sequents arising from the case analysis over $R(\bar{t})$ corresponds to the situation where the primary component of R matches ι , we refer to this as the "generic case."

The limitation to case analysis within the proof fragments in a proof skeleton has the purpose of ensuring such an analysis will be complete even when other extensions participate in a composition. Note especially that in the last two cases the relation R' is completely determined by the extension. To see the effectiveness of generic reasoning that is facilitated by Definition 6, we consider example properties that might be introduced by the security extension in the language library described in Section 2. As the first example, consider the following formula

$$\forall \Sigma, e, sl_1, sl_2. \left(\Sigma \vdash level(e, sl_1)\right) \supset \left(\Sigma \vdash level(e, sl_2)\right) \supset sl_1 = sl_2 \tag{7}$$

asserting that the security level of an expression is unique. This is a property whose key relation is defined by the extension and its primary component is introduced by the host language. There will be a generic case for this property: cases of expressions arising from a priori unknown extensions have also to be reasoned about. Focusing on this case, we see that it requires us to show that $sl_1 = sl_2$ must hold if we know $proj_e(\iota, y)$, $\Sigma \vdash level(y, sl_1)$, and $\Sigma \vdash level(\iota, sl_2)$ hold and that the induction hypothesis can be invoked relative to $\Sigma \vdash level(y, sl_1)$. Because the security level relation is introduced by the security extension, a case analysis of the last of these relations, the second derivation of *level*, is possible and it yields that, for some y', $proj_e(\iota, y')$ and $\Sigma \vdash level(y', sl_2)$ must hold; intuitively the only way in which the relation $\Sigma \vdash level(\iota, sl_2)$ could have been defined is by the projection rule from the security extension, since ι represents a term from some other extension. We may now utilize Projection Constraint 6 to show y = y' and then invoke the induction hypothesis to conclude that $sl_1 = sl_2$.

As another example, recall the auxiliary property 2 from Section 3 that essentially asserts that private information cannot leak out from the evaluation of a secure statement. This is a metatheoretic property posited by the security extension but whose key relation is introduced by the host language. Here too there will be a generic case. The analysis for this case is based on the rule introduced by the generic extension, leading to the replacement of the premise $(\gamma_A, s) \Downarrow \gamma'_A$ by $proj_s(\iota, y)$ and $(\gamma_A, y) \Downarrow \gamma'_A$. This process also instantiates the second premise to $(\gamma_B, \iota) \Downarrow \gamma'_B$. While it may seem this relation can also be analyzed by the rule from the generic extension, such an analysis is not guaranteed to be sound: the rule in the generic extension assumes a simulation of behavior by the projection, which needs to be verified before it can be used.⁵ Such a case analysis is prohibited by Definition 6 for this reason. However, we can use Projection Constraint 4 to show the expression y to which ι projects must also evaluate under γ_B to yield a new environment γ''_B . After analyzing the derivation of *secure* for y, the inductive hypothesis tells us both γ'_A and γ''_B have the same values for all public variables. Projection Constraint 5 lets us show γ'_B and γ''_B have the same values for all variables, so γ'_A and γ''_B have the same values for all variables.

We will need the following observation in later discussions when using these modular proofs to build proofs for composed languages.

Lemma 4. Let H be the host language and E be an extension in a library constructed in the extensibility framework. Further, let S be a sequent that has a proof π relative to the language $H \triangleleft \{E, GenExt(H, E)\}$ and the set of lemmas \mathscr{L} in which the constraints imposed by Definition 6 on proof fragments are satisfied. Finally, let θ be a substitution determined by some language that extends the vocabulary determined by $H \triangleleft \{E, GenExt(H, E)\}$. Then $\pi[\theta]$ is a proof of the sequent $S[\theta]$ based on the definitions of relations determined by the language $H \triangleleft \{E, GenExt(H, E)\}$ and using the lemmas in \mathscr{L} that satisfies the constraints imposed by Definition 6 on proof fragments.

Proof. This is a refinement of clause 2 of Theorem 1 that follows from examining its proof and the definition of substitution into derivations. \Box

 $^{{}^{5}}$ A similar observation applies to the case analysis at the outermost level, but a verification of the soundness of the simulation in that case will be carried out in a complete proof, as discussed in Section 6.4.

6.3 Proof Elaboration for Extension-Introduced Relations

In our scheme, a proof skeleton for a metatheoretic property is to be taken as a complete demonstration of the validity of the property in any well-behaved composition in the case where the key relation is introduced by the extension constructing the proof skeleton. We show this assessment to be justified in this subsection. More specifically, we show a proof skeleton can be elaborated into a complete proof for the property relative to any composite language. The main observation underlying this fact is that the proof of the sequent arising from rules for the key relation contributed by an a priori unknown extension can be generated via a suitable instantiation of the proof of the generic case in a proof skeleton. We demonstrate this in Lemma 5 below.

Definition 7 (Term Replacement). If t_1 and t_2 are two terms of the same type and s is another term, then $s[t_1/t_2]$ denotes the replacement of all occurrences of t_2 in s by t_1 ; this operation has an obvious recursive definition. The operation extends to formulas with the proviso that quantified variables must be renamed so they do not get confused with the ones that appear in t_1 or t_2 , to sets of formulas by its application to each member of the set, to unification problems by its distribution to the terms in each pair in the set, and to substitutions by its application to the terms in the range of a substitution. The notation for terms is extended to these cases: if F is a formula, Γ is a set of formulas, \mathcal{U} is a unification problem and θ is a substitution, then the replacement of t_1 by t_2 in each is denoted by $F[t_1/t_2], \Gamma[t_1/t_2], \mathcal{U}[t_1/t_2], and <math>\theta[t_1/t_2]$, respectively.

Definition 8 (Instance of a (Generic) Sequent). A sequent S' is an instance of S determined by the term t, a relationship denoted by $S \sim_t S'$, if S is $\Sigma : \Gamma \longrightarrow F$ and S' is $\Sigma' : \Gamma[t/\iota]] \longrightarrow F[t/\iota]];$ Σ' must, of course, include all the variables needed to ensure that S' is well-formed.

An example illustrating Definition 8 is in order. Assuming IH represents the formula

$$\forall \Sigma, e, sl_1, sl_2. \ (\Sigma \vdash level(e, sl_1))^* \supset \Sigma \vdash level(e, sl_2) \supset sl_1 = sl_2,$$

let \mathcal{S} be the sequent

$$\Sigma, sl_1, sl_2, x: IH, proj_e(\iota, x), (\Sigma \vdash level(x, sl_1))^*, \Sigma \vdash level(\iota, sl_2) \longrightarrow sl_1 = sl_2;$$

this sequent would be the one proved in the generic case in a proof skeleton for Property 7. In the proof of the property for a language determined by composition with actual extensions, this sequent would have to be replaced by ones resulting from it by instantiating ι with specific terms. Thus, if the composition includes the list extension, the *tail* constructor in that extension will require a proof of the following sequent, denoted by S', to be constructed:

$$\Sigma, sl_1, sl_2, x, l : IH, proj_e(tail(l), x), (\Sigma \vdash level(x, sl_1))^*, \Sigma \vdash level(tail(l), sl_2) \longrightarrow sl_1 = sl_2 = s$$

Here, \mathcal{S}' is an instance of \mathcal{S} determined by tail(l), *i.e.*, the relation $\mathcal{S} \sim_{tail(l)} \mathcal{S}'$ holds.

Lemma 5. Let H be the host language and E, E_1, \ldots, E_n be extensions in a library constructed in the extensibility framework. Further, let S be a sequent that has a proof relative to the language $H \triangleleft \{E, GenExt(H, E)\}$ and the lemmas in \mathscr{L} in which the constraints imposed by Definition 6 on proof fragments are satisfied. Then

1. if ι does not occur in S, then S has a proof relative to the language $H \triangleleft \{E, E_1, \ldots, E_n\}$ and the lemmas in \mathscr{L} ; and

2. if t is a term in the language $H \lhd \{E, E_1, \ldots, E_n\}$ that has as its top-level symbol a constant introduced by E_i for some i such that $1 \le i \le n$ and is such that no variables in the eigenvariable context of S occur in it, then there must be a proof relative to $H \lhd \{E, E_1, \ldots, E_n\}$ and the lemmas in \mathscr{L} for any sequent S' such that $S \sim_t S'$ holds.

Proof. The first part of the lemma can be proved by a simple adaptation of the argument for the second part. Alternatively, it follows from the application of the second part with a suitable (even if fictitious) term t. We therefore focus below only on proving the second part.

Let π be the proof of S in the proof skeleton \mathcal{P} . The argument is by induction on the height of π and proceeds by examining the last rule used. The conclusion is obvious if this rule is some variant of the *id* rule: for example, if S is of the form $\Sigma : \Gamma \longrightarrow F$ where F is a member of Γ , then S' must be of the form $\Sigma' : \Gamma[t/\iota] \longrightarrow F[t/\iota]$ and $F[t/\iota]$ must be a member of $\Gamma[t/\iota]$. For the remaining cases, it suffices to show that the same rule as was used to derive S can be used to derive S', possibly from premises that are \sim_t related to the premises in the derivation of S. This is easy to see for all the rules in Figure 7 other than *id* and for the ind_m^i rule. Note the use of lemmas is encompassed by the *cut* rule.

The only remaining rules are those pertaining to definitions. Here, we must consider the fact that the set of clauses in the definition associated with $H \triangleleft \{E, GenExt(H, E)\}$ that can be used in π differs from the ones associated with $H \triangleleft \{E, E_1, \ldots, E_n\}$. The clauses that can be used in π are those corresponding to the rules for relations introduced by H or E and the projection rules for Einstantiated with ι . For $H \lhd \{E, E_1, \ldots, E_n\}$, a clause of the form $\forall \overline{x}. H \triangleq B$ that is derived from the projection rules for E in the collection for $H \lhd \{E, GenExt(H, E)\}$ is replaced by ones of the form $\forall \overline{x}, \overline{y}. H[[c(\overline{y})/\iota]] \triangleq B[[c(\overline{y})/\iota]]$ for each constructor c of the right type that is introduced by the extensions E_1, \ldots, E_n ; the variables in \overline{y} must be chosen to be distinct from those in \overline{x} and we are assuming the precise order of the variables in a binder for a clause is irrelevant here. Additionally, the clauses for $H \lhd \{E, E_1, \ldots, E_n\}$ will include ones deriving from the relation defining rules introduced by E_1, \ldots, E_n and instantiations of the projection rules of these extensions. However, these clauses turn out to be irrelevant because of the restrictions on the use of case analysis in a proof skeleton, a fact that is implicit in the argument below.

Now suppose that π ends with the $def\mathcal{R}$ rule. In this case, \mathcal{S} must have the form $\Sigma : \Gamma \longrightarrow A$ for some atomic formula A and it must be derived from a sequent of the form $\Sigma' : \Gamma \longrightarrow B[\theta]$ using a clause $\forall \overline{x}. H \triangleq B$ from the available collection relative to $H \triangleleft \{E, GenExt(H, E)\}$, where θ is such that $A = H[\theta]$. Using Theorem 1, clause (1), we may assume the domain of θ to be disjoint from the set of variables appearing in t. Using Theorem 10 (Appendix B), we then see that $A[t/\iota]] = H[t/\iota][\theta[t/\iota]]$. Now, corresponding to the clause $\forall \overline{x}. H \triangleq B$, there is one in the collection available relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ that has the clause $\forall \overline{x}. H[t/\iota]] \triangleq B[t/\iota]$ as an instance; this is trivially the case for the clauses corresponding to the rules introduced by H and E since ι does not appear in such clauses, and it can be arranged via suitable substitutions for the ones derived from the projection rules for E. But then, using the substitution $\theta[t/\iota]$, we see that the sequent \mathcal{S}' , which is, in fact, of the form $\Sigma' : \Gamma[t/\iota] \oplus [t/\iota]$ relative to the language $H \lhd \{E, E_1, \ldots, E_n\}$. By Theorem 10, $B[t/\iota][\theta[t/\iota]] = B[\theta][t/\iota]] = B[\theta][t/\iota]$. Thus, \mathcal{S}' may be derived using a $def\mathcal{R}$ rule from a premise sequent that is related by \sim_t to the one used in π , as desired.

To complete the proof, we must consider the case where π ends with some version of the $def\mathcal{L}$ rule. The versions differ only in that some formulas may be annotated and that annotations may be affected by the rule. However, annotations are not relevant to the objective at hand and we will ignore them in our argument. Now, in this case, S must be of the form $\Sigma : \Gamma, R'(\overline{t'}) \longrightarrow C$ with the $def\mathcal{L}$ rule in π pertaining to $R'(\overline{t'})$. Then S' must be of the form $\Sigma' : \Gamma[t/\iota], R'(\overline{t'})[t/\iota]] \longrightarrow C[t/\iota]$ and we will want to show that it can be derived by a $def\mathcal{L}$ rule from premises that are related by \sim_t to the premises for the $def\mathcal{L}$ rule in π . The argument proceeds by considering each of the cases for $def\mathcal{L}$ in π that are permitted by Definition 6.

The primary component argument of R'(t) has a constructor introduced by H or E as its top-level symbol. Clearly, the primary component argument of R'(t) [t/t] will continue to have the same constructor as its top-level symbol. Now, every rule given by an extension for a relation identified by the host language must have a term in the primary component location that has a constructor the extension introduces as its top-level symbol. From this and from the manner in which projection rules are transformed into actual rules in a composition, it follows that the only clauses relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ that could be relevant to a case analysis on $R'(\overline{t'})[t/\iota]$ are the ones arising from the rules in H and E, *i.e.*, the same clauses considered in the def \mathcal{L} rule in π . Let $\forall \overline{x}. H \triangleq B$ be one of these clauses. Since ι does not appear in $H, H = H[t/\iota]$. By Theorem 12 (Appendix B), $\{\langle R'(t) | [t/\iota] \rangle\}$ has a unifier only if $\{\langle R'(t) \rangle\}$ has one; in applying the theorem, we note the top-level symbol for t cannot appear in $R'(\overline{t'})$ because S is well-formed relative to the language $H \triangleleft \{E, GenExt(H, E)\}$. Thus, there is a premise arising from this clause in the def \mathcal{L} rule we are considering for deriving \mathcal{S}' only if there is one in the def \mathcal{L} rule in π . Suppose that there is such a premise in the def \mathcal{L} rule in π . Then this premise would have the form $\Sigma[\theta]: \Gamma[\theta], B[\theta] \longrightarrow C[\theta]$, for some mgu θ for $\{\langle R'(t), H \rangle\}$. Using Theorem 1, Theorem 14, and Lemma 4, we may assume θ is such that $\theta[t/\iota]$ is an equ for $\{\langle R'(\overline{t'})[t/\iota], H[t/\iota]\}\}$; the variables in \overline{x} would need to be disjoint from those appearing in \overline{t} , but this is easily arranged. Note also that the domain of θ can be limited to the variables in Σ and in \overline{x} , and hence to be disjoint from the variables appearing in \overline{t} . Now, we may pick $\Sigma'[\theta[t/\iota]] : \Gamma[t/\iota][\theta[t/\iota]], B[t/\iota][\theta[t/\iota]] \longrightarrow C[t/\iota][\theta[t/\iota]]$ as the premise based on this clause in the derivation we are wanting to construct for \mathcal{S}' . Using Theorem 10, we see that this sequent is the same as $\Sigma'[\theta[t/\iota]] : \Gamma[\theta][t/\iota]B[\theta][t/\iota]] \longrightarrow C[\theta][t/\iota]$, which is obviously related by \sim_t to the corresponding premise in π . Since this argument is independent of the particular clause selected, the desired result follows.

R' and its primary component type are introduced by E. In this case, again, the clauses that are available in the case analysis of $R'(\overline{t'})[t/\iota]$ are identical to those available for case analysis of $R'(\overline{t'})$ and ι does not appear in these clauses. An argument identical to the previous situation suffices to show what is needed.

R' is a relation introduced by E and the primary component argument of $R'(\overline{t'})$ is ι . Clauses of two varieties can figure in the $def\mathcal{L}$ rule in π in this situation. First, the clause may encode a rule contributed directly by E. Such a clause will persist unchanged in the definition corresponding to the language $H \triangleleft \{E, E_1, \ldots, E_n\}$ and ι will not occur in it. We can argue as before in this case that if the clause gives rise to a premise for the $def\mathcal{L}$ rule that we want to use for deriving \mathcal{S}' then there must be a premise for the def \mathcal{L} rule in π to which it is related by \sim_t . Second, the clause may have arisen from a projection rule in E. Here we observe the following easily established fact: if a clause of the form $\forall \overline{x}. H \triangleq B$ arising from such a projection rule is relevant to the analysis of $R'(\overline{t'})$ relative to $H \triangleleft \{E, GenExt(H, E, \})$, then it is only a clause of the form $\forall \overline{x}. H[t/\iota] \triangleq B[t/\iota]$ that will be relevant to the analysis of $R'(\overline{t'})[t/\iota]$ relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$. Although the details in this situation differ from that in the earlier cases— ι appears in the clause $\forall \overline{x}. H \triangleq B$ and it is a clause after a replacement of ι that must be considered relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ —that argument can now be easily adapted to show that if the latter clause results in a premise sequent in a derivation of \mathcal{S}' by a def \mathcal{L} rule, then there must be a premise for the def \mathcal{L} rule in π that is related by \sim_t to it.

We can now state and prove the main result of this subsection.

Theorem 6. Let H be the host language and E, E_1, \ldots, E_n be extensions in a library constructed in the extensibility framework, and let $L = H \lhd \{E, E_1, \ldots, E_n\}$. Further, let P be a formula of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary of $H \lhd \{E\}$ with R being a relation introduced by E. Finally, let \mathcal{P} be a proof skeleton for P relative to $H \lhd \{E, GenExt(H, E)\}$ and the lemmas in \mathcal{L} . Then there is a proof of P relative to L and the lemmas in \mathcal{L} .

Proof. As in \mathcal{P} , the proof of P relative to L may end with rules for introducing the top-level logical symbols in P and some number of uses of the induction rule. This would leave a obligation to provide a proof for a sequent of the form $\Sigma : \Gamma, R(\overline{t}) \longrightarrow F$ or $\Sigma : \Gamma, (R(\overline{t}))^{\otimes i} \longrightarrow F$ that is identical to the one in \mathcal{P} . We shall assume the sequent to have the former form below; the argument in the other case is similar. Now, in \mathcal{P} , this sequent is proved by the use of the def \mathcal{L} rule relative to $R(\overline{t})$. We may consider using the def \mathcal{L} rule in the proof relative to L as well. Noting R is introduced by E, we see there are two sources for the premises for the def \mathcal{L} rule in the two cases: they either derive from clauses that encode the rules for R in E or the rules generated from the projection rule for E through instantiation relative to $H \lhd \{E, GenExt(H, E)\}$ and L, respectively. The premise sequents resulting from the former must be identical and they must also not contain ι . Since these must also have a proof relative to the language $H \lhd \{E, E_1, \ldots, E_n\}$.

Thus it only remains to be shown the premises in the proposed use of $def\mathcal{L}$ relative to L that derive from the clauses that encode the rules for R generated from the projection rule in E have derivations. There is a relationship between the clauses that come from the projection rule relative to the language $H \triangleleft \{E, GenExt(H, E)\}$ and L: a clause of the form $\forall \overline{x}. H \triangleq B$ in the former case will be replaced by a family of clauses of the form $\forall \overline{x}, \overline{y}, H[c(\overline{y})/\iota]] \triangleq B[c(\overline{y})/\iota]$ in the latter, with one such clause for each constant c of the appropriate type introduced by the extensions in E_1, \ldots, E_n . Moreover, H should have R as its top-level predicate symbol and ι should be the argument in the primary component location for R. Since neither ι nor c can appear in $R(\bar{t})$, the heads of these clauses can unify with $R(\bar{t})$ only if the argument in the primary component location for R is a variable. Using arguments similar to those seen in the proof of Lemma 5, it can be established that the clauses deriving from the projection rule will yield premise sequents relative to L only if there is a premise sequent corresponding to it relative to $H \triangleleft \{E, GenExt(H, E)\}$. Moreover, it can be arranged such that if the premise sequent is \mathcal{S} in the latter case and they are S_1, \ldots, S_n in the former case, then $S_i \sim_{c_i(\overline{y_i})} S$ holds with c_i and the variables in $\overline{y_i}$ not appearing in \mathcal{S} . The existence of the proof skeleton \mathcal{P} assures us that \mathcal{S} has a proof. Using Lemma 5, we may conclude that, for $1 \leq i \leq n$, S_i must have a proof.

Substantiating earlier comments, we note that the proofs of Lemma 5 and Theorem 6 provide the basis for automatically constructing a proof for the property relative to the full language from a proof skeleton once the components comprising the language are known.

6.4 Proof Elaboration for Host-Introduced Relations

We now consider the soundness of treating a proof skeleton for a metatheoretic property whose key relation is introduced by the host language as a demonstration of the validity of the property in any language composition. In the construction of the proof skeleton in this case, the behavior of the key relation in an arbitrary undetermined extension is modelled by the rule for it that is provided by the generic extension. Two assumptions underlie the treatment through this rule. First, it is assumed that the behavior of the relation is equivalent to that when the term that is its primary component is replaced by a term to which it projects. Second, it is assumed that the definition of the relation when such a replacement is done is smaller in an inductive ordering. Clearly, for the proof skeleton to constitute an adequate demonstration of the property, it will be necessary to show these assumptions are justified.

We describe an approach to meeting the above requirement in this subsection. The starting point for our approach is to associate with the key relation a new relation that builds in the described assumptions; we refer to the latter as the *projection version* of the original relation. One obligation in the overall scheme is to show the equivalence of the two relations. This obligation has the structure of a foundational property that we expect to be validated in a modular manner along the lines discussed in Section 5. Assuming the equivalence of the relation and its projection version, we then show a proof skeleton for the property can be used to generate a complete proof for it relative to a language that includes other well-behaved extensions.

The rest of this subsection develops these ideas. We first define the notion of a projection version of a relation. We then show how a proof skeleton can be elaborated into a complete proof when the two relations are equivalent. We conclude the subsection by discussing what is involved in showing the equivalence of a relation and its projection version and reflecting on what the reliance on such a property entails for the generality of the approach we propose.

6.4.1 The Projection Version of a Relation

The validity of the reasoning embodied in a proof skeleton is dependent on viewing the key relation through the projection of its primary component. To capture this requirement, we build it into the definition of a new relation we will use as a proxy in the reasoning process.

Definition 9. Let H be a host language and E_1, \ldots, E_n be a set of extensions in a library constructed in the extensibility framework. The projection version of the relation R introduced by the host language $(R \in \mathscr{R}^H)$ is written as R_P . Further, the definition of this relation is derived from that of R as follows. Assuming that the *i*th argument of R is its primary component, let

$$\frac{\overline{R(\overline{s})} \quad \overline{U}}{R(t_1, \dots, t_{i-1}, t_i, t_{i+1}, \dots, t_m)}$$

be a rule for it, where $R(\overline{s})$ denotes a set of premises in which R appears and \overline{U} denotes the remaining premises. If this is a rule in the collection corresponding to the host language, then the definition of R_P includes the rule

$$\frac{\overline{R_P(\overline{s})} \quad \overline{U}}{R_P(t_1, \dots, t_{i-1}, t_i, t_{i+1}, \dots, t_m)};$$

in other words, the definition of R_P includes an identical rule, except that R is replaced in it by R_P . If this rule is in the collection corresponding to one of the extensions E_1, \ldots, E_n on the other hand, then the counterpart rule for R_P has the form

$$\frac{\overline{R_P(\overline{s})}}{R_P(t_1,\ldots,t_{i-1},t_i,t_{i+1},\ldots,t_m)},$$

where T represents the projection relation for the category of the primary component of R and x is a variable that is fresh to the rule. If T corresponds here to a projection relation with additional parameters, these parameters must be filled in adherence to the dependencies on the arguments of R specified by the host language and that are utilized also in constructing the generic extension. Observe the additional premises in this case encode the requirement that the behavior of R_P must remain the same as that under a projection of its primary component and that the definition of the relation for the projection must be smaller in the inductive ordering.

$$\begin{aligned} \frac{(\gamma, s_1) \Downarrow \gamma' \quad (\gamma', s_2) \oiint \gamma''}{(\gamma, seq(s_1, s_2)) \Downarrow \gamma''} X-\text{SEQ} \\ \frac{(\gamma, s_1) \oiint \gamma \quad (\gamma', s_2) \lor \gamma''}{(\gamma, seq(s_1, s_2)) \Downarrow \gamma''} X-\text{SEQ} \\ \frac{(\gamma, s_1) \oiint \gamma' \quad (\gamma', s_2) \lor \gamma''}{(\gamma, seq(s_1, s_2)) \Downarrow \gamma''} X-\text{SEQ} \\ \frac{\gamma \vdash e \Downarrow \cos(v_1, v_2) \quad n_{hd} \neq n_{tl}}{(\gamma, splitlist(n_{hd}, n_{tl}, e)) \Downarrow n_{hd} : v_1; n_{tl} : v_2; n_{hd} : \cos(v_1, v_2); \gamma} X-\text{SPLITLIST} \\ \frac{\gamma \vdash e \Downarrow \cos(v_1, v_2) \quad n_{hd} \neq n_{tl} \quad proj_s(splitlist(n_{hd}, n_{tl}, e), x_T)}{(\gamma, splitlist(n_{hd}, n_{tl}, e)) \Downarrow p \quad n_{hd} : v_1; n_{tl} : v_2; n_{hd} : \cos(v_1, v_2); \gamma} X-\text{SPLITLIST} \\ \frac{\gamma \vdash e \Downarrow v}{(\gamma, splitlist(n_{hd}, n_{tl}, e)) \Downarrow p \quad n_{hd} : v_1; n_{tl} : v_2; n_{hd} : \cos(v_1, v_2); \gamma} X-\text{SPLITLIST}_P \\ \frac{\gamma \vdash e \Downarrow v}{(\gamma, secdecl(n, ty, sl, e)) \Downarrow n : v; \gamma} X-\text{SECDECL} \\ \frac{\gamma \vdash e \Downarrow v \quad proj_s(secdecl(n, ty, sl, e)) \Downarrow p \quad n : v; \gamma}{(\gamma, secdecl(n, ty, sl, e)) \Downarrow p \quad n : v; \gamma} X-\text{SECDECL}_P \end{aligned}$$

Figure 10: Some evaluation rules for the example language library and their projection versions

Figure 10 illustrates the above definition by showing some of the rules for statement evaluation (denoted by \Downarrow) for our example language library and their correlates in the definition of the projection version of this relation (denoted by \Downarrow_P). Corresponding to the X-SEQ rule, which is introduced by the host language, is the X-SEQ_P rule with the same structure except that it defines the projection version of the relation. Corresponding to the two extension-introduced rules X-SPLITLIST (introduced by the list extension) and X-SECDECL (introduced by the security extension), we have the rules X-SPLITLIST_P and X-SECDECL_P that include two additional premises identifying the behavior of the projection version of the relation with that under projections.

We desire to use R_P in the reasoning process as a proxy for R. Our ability to do so will depend on showing the two relations to be equivalent. One part of the equivalence, which we call the dropP(R) property, is given by the following formula:

$$\forall \overline{x}. R_P(\overline{x}) \supset R(\overline{x})$$

This property must obviously be true—the premises for R_P include all that is required of R and possibly more—and a modular proof for it can be constructed in a mechanical fashion. We shall assume this has been done and use dropP(R) freely as a lemma in what follows. The other part of the equivalence, the addP(R) property, is expressed by the formula

$$\forall \overline{x}. R(\overline{x}) \supset R_P(\overline{x})$$

This property is more substantive and must be proved explicitly. We shall assume it has been proved in the next subsection and will return later to the question of how this might be done.

6.4.2 Converting a Proof Skeleton into a Complete Proof

While our ultimate goal is to prove a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$, we shall focus here on transforming a proof skeleton into a proof of the property $\forall \overline{x}. R_P(\overline{t}) \supset F$ instead. Once we have a

proof of the latter as well as of the addP(R) property, we can easily obtain one of the property of real interest.

The proofs we want to construct will end as usual with a case analysis on a possibly-annotated version of the key relation, which now will be R_P , followed by rules that introduce logical symbols in the conclusion formula, and some number of uses of the induction rule. As before, the proof skeleton provides the information from which the proof is to be constructed automatically. However, additional care is needed now in elaborating this process. One reason for such care is that the key relation for the property verified by the proof skeleton is replaced in the context of the composite language by its proxy. This change can be accommodated, as we shall see, by invoking the dropP(R) and addP(R) lemmas at relevant places. The more complex issue is that of constructing a proof fragment for the cases arising from the rules for R_P contributed by the extensions in the composition that are different from the ones based on which the proof skeleton was developed. While similar in spirit to the ideas developed in Section 6.3, there are differing details to be considered. The rule that gives rise to the generic proof fragment in the proof skeleton is one that has the form

$$\frac{T(\iota, y) \quad R(x_1, \dots, x_{i-1}, y, x_{i+1}, \dots, x_k)}{R(x_1, \dots, x_{i-1}, \iota, x_{i+1}, \dots, x_k)},$$

where the x_i 's and y are distinct (schematic) variables. In the actual language obtained by composition with extensions E_1, \ldots, E_n , this rule is replaced by ones of the form

$$\frac{\overline{R_P(\overline{s})}}{R_P(t_1,\ldots,t_{i-1},t_i,t_{i+1},\ldots,t_m)},$$

where, once again, y is a variable that is fresh to the rule. Ignoring the distinction between R and R_P , we see the conclusion of the latter rule is obtained from the former not just by replacing ι by t_i but also by substituting the terms $t_1, \ldots, t_{i-1}, t_{i+1}, \ldots, t_m$, respectively, for the variables $x_1, \ldots, x_{i-1}, x_{i+1}, \ldots, x_m$. Thus the generic proof fragment would have proved a more general sequent than would arise in the case of the actual language identified by the composition.

We define a relation between sequents that helps us bridge the first of these differences.

Definition 10 (Projection version of a sequent). Let $S = \Sigma : \Gamma \longrightarrow F$ and $S' = \Sigma' : \Gamma' \longrightarrow F'$ be two sequents that are well-formed with respect to some given vocabulary. We say that S' is an R-projection version of S, a relationship denoted by $S \sqsubseteq_R S'$, if there is a subset $\widehat{\Gamma'}$ of Γ' such that $\widehat{\Gamma'}$ and F' result from Γ and F as follows: for each i > 0 either every formula of the form $(R(\overline{t}))^{*i}$ and $(R(\overline{t}))^{@i}$ in them has been replaced respectively by $(R_P(\overline{t}))^{*i}$ and $(R_P(\overline{t}))^{@i}$ or none has been so replaced, and some occurrences of formulas of the form $R(\overline{t})$ have been replaced by $R_P(\overline{t})$.

We illustrate this definition using sequents that might arise in the context of trying to prove Property 2 and its projection version. Let IH represent the formula

$$\forall s, \Sigma, sl, \gamma_A, \gamma_B, \Sigma', \gamma'_A, \gamma'_B. ((\gamma_A, s) \Downarrow \gamma'_A)^* \supset (\gamma_B, s) \Downarrow \gamma'_B \supset \Sigma \ sl \vdash secure(s, \Sigma') \supset eqpublicvals(\Sigma, \gamma_A, \gamma_B) \supset eqpublicvals(\Sigma', \gamma'_A, \gamma'_B).$$

Then the sequent that arises in case analysis when the statement evaluation relation is considered to be derived using the rule for the *seq* construct introduced by the host language (rule X-SEQ in Figure 10) is the following:

$$\Sigma, sl, \gamma_A, \gamma_B, \Sigma', \gamma'_A, \gamma'_B, s_1, s_2, \gamma''_A :$$

$$IH, ((\gamma_A, s_1) \Downarrow \gamma''_A)^*, ((\gamma''_A, s_2) \Downarrow \gamma'_A)^*, (\gamma_B, seq(s_1, s_2)) \Downarrow \gamma'_B, \Sigma \ sl \vdash secure(seq(s_1, s_2), \Sigma'),$$

$$eqpublicvals(\Sigma, \gamma_A, \gamma_B) \longrightarrow eqpublicvals(\Sigma', \gamma'_A, \gamma'_B) \quad (8)$$

There would be a corresponding sequent if we were to try to construct a proof for the projection version of Property 2 in the context of the composed language. If IH' is the formula

$$\forall s, \Sigma, sl, \gamma_A, \gamma_B, \Sigma', \gamma'_A, \gamma'_B. ((\gamma_A, s) \Downarrow_P \gamma'_A)^* \supset (\gamma_B, s) \Downarrow \gamma'_B \supset \Sigma \ sl \vdash secure(s, \Sigma') \supset eqpublicvals(\Sigma, \gamma_A, \gamma_B) \supset eqpublicvals(\Sigma', \gamma'_A, \gamma'_B),$$

then the sequent that arises during case analysis from considering X-SEQ_P in Figure 10, *i.e.*, the rule for the projection version of the relation \Downarrow , as the basis for evaluation is the following:

$$\Sigma, sl, \gamma_A, \gamma_B, \Sigma', \gamma'_A, \gamma'_B, s_1, s_2, \gamma''_A :$$

$$IH', ((\gamma_A, s_1) \Downarrow_P \gamma''_A)^*, ((\gamma''_A, s_2) \Downarrow_P \gamma'_A)^*, (\gamma_B, seq(s_1, s_2)) \Downarrow \gamma'_B, \Sigma \ sl \vdash secure(seq(s_1, s_2), \Sigma'),$$

$$eqpublicvals(\Sigma, \gamma_A, \gamma_B) \longrightarrow eqpublicvals(\Sigma', \gamma'_A, \gamma'_B) \quad (9)$$

If S is the sequent in the display numbered 8 and S' is the sequent in the display numbered 9, then $S \sqsubseteq_{eval} S'$ holds.

Lemma 7. Let H be the host language and E, E_1, \ldots, E_n be extensions in a library constructed in the extensibility framework. If there is a proof for a sequent S relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ and a set of lemmas that includes dropP(R) and addP(R), then there must be a proof relative to the same language and set of lemmas for any sequent S' such that $S \sqsubseteq_R S'$ holds.

Proof. Let π be the derivation for S. We prove the lemma by induction on the height of π . The argument proceeds by considering the cases for the last inference rule in π .

We first deal collectively with the situations where the last rule is not $def\mathcal{R}$ or some variant of $def\mathcal{L}$ or *id*. In all these cases, it is easy to see there is a counterpart in \mathcal{S}' to the formula in \mathcal{S} to which the rule pertains that enables it to be used in proving \mathcal{S}' from premises related via \sqsubseteq_R to the premises for \mathcal{S} in π . Obvious applications of the induction hypothesis now complete the proof.

Suppose the last rule in π is some variant of $def\mathcal{L}$. If this formula is not of the form $(R(\bar{t}))^{*^i}$, $(R(\bar{t}))^{@^i}$, or $R(\bar{t})$ that has been replaced by $(R_P(\bar{t}))^{*^i}$, $(R_P(\bar{t}))^{@^i}$, or $R_P(\bar{t})$ in \mathcal{S}' , then the same rule can be used to prove \mathcal{S}' from premises that must, again, have proofs by virtue of the induction hypothesis. If the assumption formula is of the form $(R(\bar{t}))^{*^i}$ or $(R(\bar{t}))^{@^i}$ and has been replaced by $(R_P(\bar{t}))^{*^i}$ or $(R_P(\bar{t}))^{@^i}$ and has been replaced by $(R_P(\bar{t}))^{*^i}$ or $(R_P(\bar{t}))^{@^i}$ in \mathcal{S}' , then, noting the relationship between the rules for R and R_P , it can be seen that a $def\mathcal{L}^{*^i}$ or a $def\mathcal{L}^{@^i}$ rule can be used to derive \mathcal{S}' from premise sequents related via \sqsubseteq_R to those for \mathcal{S} in π . Invocations to the induction hypothesis help complete the proof in this case. A virtually identical argument yields the desired conclusion when the formula in \mathcal{S} is $R(\bar{t})$ and has been replaced by $R_P(\bar{t})$ in \mathcal{S}' .

Suppose the last inference rule in π is a $def\mathcal{R}$ rule. Then the conclusion formula for \mathcal{S} must not be of the form $(R(\bar{t}))^{*^i}$ or $(R(\bar{t}))^{@^i}$. If the same atomic formula is the conclusion formula of \mathcal{S}' , an identical $def\mathcal{R}$ rule would be applicable the sequent, leading to a premise sequent that is related via \sqsubseteq_R to that for \mathcal{S} in π . The argument can, once again, be completed by invoking the induction hypothesis. The only remaining possibility is that the conclusion formula is of the form $R(\bar{t})$ in \mathcal{S} and of the form $R_P(\bar{t})$ in \mathcal{S}' . Here we use the argument just outlined to construct a proof for a sequent like \mathcal{S}' except the conclusion formula has been replaced by $R(\bar{t})$ and then use addP(R) as a lemma to extend this into a proof for \mathcal{S}' .

Finally, suppose that π ends with some variant of the *id* rule. If the conclusion formula in S is not of the form $R(\bar{t})$, it is easy to see that S' must be derivable by the same variant of the *id* rule. If the conclusion formula in S is of the form $R(\bar{t})$, it could be matched with an identical assumption formula or with one of the form $(R(\bar{t}))^{*^i}$ or $(R(\bar{t}))^{@^i}$. In the first case, $R(\bar{t})$ in the assumption

set or in the conclusion may have been replaced by $R_P(\bar{t})$ in S'. Taking recourse to the lemmas addP(R) and dropP(R) we may reduce the provability of S' in either situation to that of a sequent in which $R(\bar{t})$ appears in both the assumption set and as the conclusion formula. In the remaining two cases, the argument is obvious if $(R(\bar{t}))^{*i}$ or $(R(\bar{t}))^{@i}$ persist in S'. Otherwise, either $(R_P(\bar{t}))^{*i}$ or $(R_P(\bar{t}))^{@i}$ must appear in the assumption set in S' and the conclusion formula may be either $R_P(\bar{t})$ or $R(\bar{t})$. Thus S' is already in a form to which the id^* or $id^{@i}$ rule applies or the provability of S' can be reduced to that of a sequent to which the id rule applies by using an id^* or an $id^{@}$ rule and the dropP(R) lemma.

We can now state and prove the main result of this subsection.

Theorem 8. Let H be a host language and let E, E_1, \ldots, E_n be extensions in a library constructed in the extensibility framework. Further, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ in the vocabulary of the language $H \lhd \{E\}$ with R being a relation introduced by H. Finally let \mathcal{P} be a proof skeleton for P relative to the language $H \lhd \{E, \text{GenExt}(H, E)\}$ and the set of lemmas \mathscr{L} that includes dropP(R) and addP(R). Then there must be a proof for $\forall \overline{x}. R_P(\overline{t}) \supset F$ relative to the language $H \lhd \{E, E_1, \ldots, E_n\}$ and \mathscr{L} .

Proof. The proof skeleton \mathcal{P} ends with rules for introducing the top-level logical symbols in Pand some number of uses of the induction rule. The proof of P relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ and \mathscr{L} may end similarly. The preceding part of \mathcal{P} is a proof of a sequent \mathcal{S} that is of the form $\Sigma : \Gamma, (R(\overline{t}))^{\otimes i} \longrightarrow F$ or $\Sigma : \Gamma, R(\overline{t}) \longrightarrow F$. In the proof we are wanting to construct for P relative to $H \triangleleft \{E, E_1, \ldots, E_n\}$ and \mathscr{L} , it can easily be ascertained that we will be left with an obligation to construct a proof for a sequent \mathcal{S}' that is of the form $\Sigma' : \Gamma', (R_P(\overline{t}))^{\mathbb{Q}^i} \longrightarrow F'$ or $\Sigma' : \Gamma', R_P(\overline{t}) \longrightarrow F'$ where Γ' and F' are identical to Γ and F except that, for some i, all occurrences of formulas of the form $(R(\overline{s}))^{*^{i}}$ and $(R(\overline{s}))^{@^{i}}$ in them have been replaced by $(R_{P}(\overline{s}))^{*^{i}}$ and $(R_P(\overline{s}))^{\otimes i}$ respectively, and some occurrences of formulas of the form $R(\overline{s})$ have been replaced by $R_P(\overline{s})$. We note here that neither S nor S' can have occurrences of ι or any of the constants introduced by the extensions E_1, \ldots, E_n . Now, the last step in the proof of S in \mathcal{P} is a $def\mathcal{L}^{\mathbb{Q}^i}$ or a def \mathcal{L} rule based on the atomic formula $(R(\bar{t}))^{\otimes i}$ or $R(\bar{t})$. The premises in this rule are sequents resulting from considering clauses for R that come from two sources: the clause could be one that is contributed directly by H and E, or it could be the "pseudo" projection rule for R contributed by GenExt(H, E). Using the fact that all these sequents have derivations, we will show that we can construct a proof for \mathcal{S}' by using a $def\mathcal{L}^{@i}$ or $def\mathcal{L}$ rule oriented around the formula $(R_P(\bar{t}))^{@i}$ or $R_P(\overline{t})$, thereby verifying the theorem.

Similar to the $def\mathcal{L}^{@^i}$ or $def\mathcal{L}$ rule that concludes the proof of \mathcal{S} , the premises for the proposed $def\mathcal{L}^{@^i}$ or $def\mathcal{L}$ rule for deriving \mathcal{S}' arise from considering clauses from two sources. These could be ones contributed by H and E or they could be ones contributed by one of the extensions E_1, \ldots, E_n . We have to show each of these premises has a proof. Given the relationship between the definition of R_P and R (in the complete language), it is easy to see that if \mathcal{S}'_1 is a premise that results from considering a clause for R_P from H or E, then there must be a premise \mathcal{S}_1 for the rule that derives \mathcal{S} in \mathcal{P} that is such that $\mathcal{S}_1 \sqsubseteq_R \mathcal{S}'_1$ holds. Moreover, ι cannot appear in either of these sequents. Since \mathcal{S}_1 has a proof relative to $H \lhd \{E, GenExt(H, E)\}$ in which the constraints imposed by Definition 6 on proof fragments are satisfied, it follows from Lemma 5 that \mathcal{S}'_1 has a proof relative to the same language.

It only remains to be shown that any premise for the $def\mathcal{L}^{@i}$ or $def\mathcal{L}$ rule in the proof we are wanting to construct for S' that derives from a clause for R_P from one of the extensions in E_1, \ldots, E_n has a proof. We will do this assuming the rule is $def\mathcal{L}^{@i}$; the argument if it is $def\mathcal{L}$ is

similar. Let S'_2 be any one of these premises. If there is such a premise, we claim there must be a premise sequent S_2 for the $def\mathcal{L}^{@^i}$ rule in \mathcal{P} that arises from the clause corresponding to the rule for R from GenExt(H, E) and that S_2 has associated with it a sequent S''_2 , a substitution θ , and a term t with a constant introduced by one of E_1, \ldots, E_n as its top-level symbol and all of whose variables are distinct from those in the eigenvariable context for S_2 , that together are such that $S_2[\theta] \sim_t S''_2$ and $S''_2 \sqsubseteq_R S'_2$ hold. If this claim is true, then using Lemmas 4, 5, and 7 and the fact that S_2 has a proof, it follows that there must be one for S'_2 as well.

To verify the claim, we examine the clause encoding the rule for R from GenExt(H, E) and, correspondingly, the clauses encoding the rules for R_P from E_1, \ldots, E_n . If the former has the form $\forall \overline{x}. H \triangleq B$, then the latter have the form $\forall \overline{x'}. \hat{H}[\rho_1][\![c(\overline{y})/\iota]\!] \triangleq (\hat{B} \land B')[\rho_1][\![c(\overline{y})/\iota]\!]$, where c is a constant introduced by one of the extensions E_1, \ldots, E_n , H and \hat{H} and, similarly, B and \hat{B} are identical formulas except that occurrences of R in the first formulas in the pairs have been replaced by R_P in the second formulas in the pairs, and \overline{y} is a sequence of variables fresh to $H[\rho_1]$ (and hence also to $\hat{H}[\rho_1]$). We may also assume that the variables in \overline{x} and $\overline{x'}$ have been named away from Σ and Σ' , the eigenvariable contexts of the two sequents S and S'. Now, a premise of the kind S'_2 must result from the use of a clause of the second form relative to the sequent S', *i.e.*, $\Sigma': \Gamma', (R_P(\overline{t}))^{\otimes i} \longrightarrow F'$. In this case, there must be an mgu for $\{\langle \hat{H}[\rho_1][\![c(\overline{y})/\iota]\!]$, where ρ_2 is an mgu for $\{\langle \hat{H}[\rho_1], R_P(\overline{t})\rangle\}$; we make use of the fact that ι does not occur in $R_P(\overline{t})$ and, hence, $R_P(\overline{t}) = R_P(\overline{t})[\![c(\overline{y})/\iota]\!]$ as also the observation that ρ_2 , being an mgu for $\{\langle \hat{H}[\rho_1], R_P(\overline{t})\rangle\}$, must not include variables not appearing in the unification problem in its domain. Using such an mgu, we may determine S'_2 to be a sequent of the form

$$\Sigma_{2}^{\prime}: \Gamma^{\prime}[\rho_{2}\llbracket c(\overline{y})/\iota \rrbracket], (B^{\prime}[\rho_{1}]\llbracket c(\overline{y})/\iota \rrbracket[\rho_{2}\llbracket c(\overline{y})/\iota \rrbracket])^{*^{i}}, (\hat{B}[\rho_{1}]\llbracket c(\overline{y})/\iota \rrbracket[\rho_{2}\llbracket c(\overline{y})/\iota \rrbracket])^{*^{i}} \longrightarrow F^{\prime}[\rho_{2}\llbracket c(\overline{y})/\iota \rrbracket].$$

Since there are no occurrences of ι or the variables in the domain of ρ_1 in Γ' and F', we may write these respectively as $\Gamma[\rho_1][[c(\overline{y})/\iota]]$ and $F[\rho_1][[c(\overline{y})/\iota]]$. But then, using Theorem 10, S'_2 may be rewritten as

$$\Sigma_2': \Gamma'[\rho_2 \circ \rho_1] \llbracket c(\overline{y})/\iota \rrbracket, (B'[\rho_2 \circ \rho_1] \llbracket c(\overline{y})/\iota \rrbracket)^{*^i}, (\hat{B}[\rho_2 \circ \rho_1] \llbracket c(\overline{y})/\iota \rrbracket)^{*^i} \longrightarrow F'[\rho_2 \circ \rho_1] \llbracket c(\overline{y})/\iota \rrbracket.$$

Now, since $R_P(\overline{t})$ is unaffected by ρ_1 and ρ_2 unifies $\{\langle \hat{H}[\rho_1], R_P(\overline{t})\rangle\}$, it follows that $\rho_2 \circ \rho_1$ is a unifier for $\{\langle \hat{H}, R_P(\overline{t})\rangle\}$. Hence, there must be an mgu for $\{\langle \hat{H}, R_P(\overline{t})\rangle\}$ or, identically for $\{\langle H, R(\overline{t})\rangle\}$ and there must therefore be a premise of the form \mathcal{S}_2 claimed to exist for the $def\mathcal{L}^{\otimes^i}$ rule in \mathcal{P} . In more detail, \mathcal{S}_2 must be a sequent of the form $\Sigma_2 : \Gamma[\delta], (B[\delta])^{*^i} \longrightarrow F[\delta]$ where δ is some mgu for $\{\langle H, R(\overline{t})\rangle\}$. Since $\rho_1 \circ \rho_2$ must be a unifier for $\{\langle H, R(\overline{t})\rangle\}$, there must be a substitution δ' such that $\rho_2 \circ \rho_1 = \delta' \circ \delta$. But then, if we pick t to be the term $c(\overline{y}), \theta$ to be the substitution δ' and \mathcal{S}''_2 to be the sequent $\mathcal{S}_2[\delta'][[c(\overline{y})/\iota]]$, it can be verified that $\mathcal{S}_2[\theta] \sim_t \mathcal{S}''_2$ and $\mathcal{S}''_2 \sqsubseteq_R \mathcal{S}'_2$ hold.

The proofs of Theorem 8 and the lemmas on which it depends are clearly constructive, implying thereby that there is a procedure for extracting a proof of the formula $\forall \overline{x}. R_P(\overline{t}) \supset F$ relative to a composite language once we have a proof skeleton for the formula. We can, in turn, use this and addP(R) to build a proof of the original property.

Theorem 9. Let H be a host language and let E, E_1, \ldots, E_n be extensions in a library constructed in the extensibility framework. Further, let P be a property of the form $\forall \overline{x}. R(\overline{t}) \supset F$ where R is a relation introduced by H and let \mathcal{P} be a proof skeleton constructed for P by E using a set of lemmas \mathscr{L} that includes dropP(R) and addP(R). Then there must be a proof of P relative to the language $H \lhd \{E, E_1, \ldots, E_n\}$ using the lemmas in \mathscr{L} . *Proof.* Using \mathcal{P} and Theorem 8, we can construct a proof for $P' = \forall \overline{x}. R_P(\overline{t}) \supset F$. If we are given $R(\overline{t}), addP(R)$ allows us to conclude that $R_P(\overline{t})$ holds. We can now use this and P' to derive F, thereby concluding that $\forall \overline{x}. R(\overline{t}) \supset F$ must hold.

6.4.3 Showing that Behavior is Preserved Through a Projection

The scheme we have identified for an extension to prove a metatheoretic property whose key relation, R, is introduced by the host language relies crucially on showing this relation is preserved under projections and that the definition of the relation is inductively smaller when viewed through projections; this is, in fact, the real content of the addP(R) property. The requirement that R satisfies these conditions is obviously a foundational one and, in particular, has the character of a projection constraint. As such, any mechanism for proving such properties modularly may be used to establish addP(R). However, there are aspects of this property that merit special treatment for which we identify the structure described below.

The only systematic way to prove a property of the form $\forall \overline{x}. R(\overline{x}) \supset R_P(\overline{x})$ would be to use an induction on the definition of the relation $R(\overline{x})$. A difficulty with doing this directly is that the definition of $R(\overline{x})$ does not give us a handle on the projections that are possible on the primary component of the relation, something playing a critical role in the definition of the relation $R_P(\overline{x})$. To deal with this situation, we introduce an intermediate relation that additionally records the number of possible projection steps.

Definition 11 (Extension Size of a Relation). Let H be a host language and E_1, \ldots, E_n be a set of extensions in a library constructed in the extensibility framework. The extension size version of a relation R introduced by the host language $(R \in \mathscr{R}^H)$, written R_{ES} , is a relation that adds a natural number argument to those of R and is defined by rules derived from those for R as follows.⁶ Assuming the i^{th} argument of R is its primary component, let

$$\frac{\overline{R(\overline{s})}}{R(\overline{t})} \quad \overline{U}$$

be a rule for it, where $\overline{R(\overline{s})}$ denotes a set of premises in which R appears and \overline{U} denotes the remaining premises. If this is a rule in the collection corresponding to the host language, then the definition of R_{ES} includes the rule

$$\frac{\overline{R_{ES}(\overline{s}, n_i)}}{R_{ES}(\overline{t}, n)} \frac{\overline{U}}{R_{ES}(\overline{t}, n)}$$

If the rule is in the collection corresponding to one of the extensions E_1, \ldots, E_n , on the other hand, then the counterpart rule for R_{ES} has the form

$$\frac{\overline{R_{ES}(\overline{s}, n_i)}}{R_{ES}(\overline{t}, n)} \frac{\overline{U}}{n = 1 + \sum n_i}$$

Observe the definition of R_{ES} builds in a count of the number of projections that are possible in the definition of $R(\bar{t})$.

⁶We assume the usual inductive encoding of natural numbers using a constant z to denote 0 and the unary constructor s to denote the successor operation. Moreover, addition and ordering relations on terms denoting natural numbers are defined in the obvious way. The equality relation and the summation operation on natural numbers are shorthands for a more elaborate presentation using the addition relation.

The proof of addP(R) can now be split into showing the following two properties:

$$\forall \overline{x}. R(\overline{x}) \supset \exists n. R_{ES}(\overline{x}, n) \\ \forall \overline{x}, n. R_{ES}(\overline{x}, n) \supset R_P(\overline{x})$$

The first of these has an obvious inductive proof and, in fact, one that can be automatically generated based on the relationship between the definitions of R and R_{ES} . The second property has a structure similar to addP(R), except that we now have the capability of basing an inductive proof not just on the derivation of the relation but also on the natural number argument that counts the number of possible projections.

In a modular proof, arguments for different cases for the definition of R_{ES} will have to be provided by the host language and each extension, as for any other foundational property. The treatment in the case of the host language can be based on an induction on the definition of R_{ES} and has a straightforward, formulaic structure. The treatment in the case of an extension is more complex and this is actually where the substance of the argument lies. In this case, the projection described by the extension would have to be analyzed explicitly and shown to have a behavior identical to that described for R directly in the extension. In establishing this, the induction on the natural number argument of R_{ES} will allow for the assumption of the property on any embedded projections.

6.4.4 Assessing the Proposed Proof Construction Approach

The approach we have described to establishing a metatheoretic property introduced by an extension and whose key relation is introduced by the host language is useful only when two requirements are met. First, there should be relations basic to the language structure that the host language may describe and whose behavior on extension-introduced constructs it can tightly constrain. Second, extensions should be able to describe interesting metatheoretic properties oriented around such relations. There are paradigmatic situations in which the first of these requirements is readily obtained. One example of this is that where extensions preserve the basic structure of the host language but provide both convenience in syntax and new abstraction mechanisms. Semantic attributes that adhere to the syntactic structure of expressions and identify static characteristics in such cases may not have the desired property. However, ones describing dynamic behavior, such as evaluation relations, often do. We posit that metatheoretic properties with which an extension might want to associate a conglomeration of a priori unknown language components will usually be based not on the specific syntactic characteristics of expressions but rather on their dynamic semantics.

We see this in our example language library with statement evaluation. Statement evaluation can be viewed as simply updating the evaluation context and branching, in which case it is clear that any behavior an extension might introduce for a new statement form should be achievable by some combination of existing statement forms. It is also natural for extensions to describe interesting properties oriented around evaluation, as our security extension does. That extension is able to introduce a property oriented around statement evaluation, demonstrating its new static analysis accurately reflect the dynamic behavior of a program as far as information flow from private to public variables is concerned.

7 A Practical Realization of Modular Reasoning

The results of this paper are meant to provide the basis for an actual system for the metatheoretic analysis of extensible languages and we have in fact begun an implemention towards this end. We sketch this work below to provide a sense of how we expect our theoretical results to be utlized; a comprehensive description is orthogonal to the focus of this paper.

Our implementation comprises two systems called *Sterling* and *Extensibella* [14]. Sterling can be viewed as providing a front-end to the verification system: this system provides facilities for developers to identify the host language and extensions for particular language libraries and further to specify each of these components in the style described in Section 2. More specifically, for each component, the developer identifies its syntactic categories and their associated constructors, the semantic relations with their types and primary components, and the rules defining these relations. Sterling checks these specifications are well-formed and fit together in the sense explained in Section 2.4. If a component passes this test, it is converted into a form that can provide the basis for reasoning within the logic \mathcal{G} described in Section 4.

Extensibella is the system that supports the actual development of proofs. In substance, Extensibella supports the interactive proof development style intrinsic to Abella [1], the proof assistant for the logic \mathcal{G} . Abella is a system that supports a tactics-style development of a proof: a state in the proof assistant is characterized by an ordered collection of sequents to be proved, and a tactic command is invoked to replace the first of these with a sequence of new sequents representing proof obligations relative to an inference rule. Extensibella retains this structure. In fact, Extensibella implements its functionality by delegating the realization of proof steps to Abella. However, the development of proofs in the extensibility context must adhere to constraints not imposed in Abella. One such constraint is that proofs constructed in the different components for foundational properties. Finally, uses of case analysis must be restricted as per Definition 3 when a proof is being constructed for a foundational property and as per Definition 6 when a proof is being constructed for an auxiliary property. Extensibella checks these constraints are satisfied before utilizing Abella to realize the proof step.

There is additional structure relevant to the development of proofs for auxiliary properties. The proofs of these properties are the responsibility of only the extensions that introduce them. However, within that context, it is necessary to include a proof of the generic case if this is relevant for the formula to be proved. Further, when an extension introduces a property where the key relation R is introduced by the host language, a proof must be generated for the dropP(R) property and it must be ascertained that the addP(R) property is available as a property introduced by the host language. These tasks are also the responsibility of Extensibella.

Much of the discussion up to this point has been oriented around the proof of a single property, with others being available as lemmas. However, the reality is that it is a *collection* of properties associated with languages. Moreover, there must be a notion of ordering associated with this collection that allows some properties to be used as lemmas in the proofs of others. This ordering is realized as follows. First, the host language identifies the order for the foundational properties it introduces. Then each extension uses this order and intersperses the properties it introduces between host language properties. Of course, an extension property that needs to use a host language property in its proof must appear later in the sequence; this must be the relationship, for example, between addP(R) and an auxiliary property whose key relation is R. Once the ordering is determined and checked for the properties, the developer of each component can construct their proofs in the manner discussed in this paper, using properties earlier in the ordering as lemmas. If each extension's ordering is consistent with that inherited from the host language, we are guaranteed there will be an overall ordering for the properties that will work for any composition.

Our implementation does not currently span all the aspects of what is needed in a completely configured system for the modular development of metatheory for extensible languages. At the moment, it provides the functionality needed to develop proof fragments for foundational properties and proof skeletons for auxiliary properties. The mechanism for composing proof fragments for foundational properties and for elaborating proof skeletons using the constructive content of Theorems 3, 6, and 9 is under development. We would also like to build an interface for automatically generating language specifications for Extensibella from those provided using formalisms such as attribute grammars and that are used in systems such as Silver [19] to support concrete realizations of extensible languages in the style considered in this paper.

8 Related Work

The work described in this paper builds around a particular vision for programming languages, that where extensibility is realized by providing targeted features by picking particular extensions from a library built around a basic core. Within this context, we have also taken it as a given that the compatibility of an extension in the library with the core, represented by a host language, and with other extensions should be determinable at the time of its conception rather than when a composition is attempted. These perspectives have three important consequences with regard to our approach to metatheory. First, it should be possible to think of metatheoretic properties pertinent to features introduced by an extension in addition to those that apply to the language as a whole. Second, it should be possible to modularize and thereby to distribute the work associated with verifying properties to each component in the library so it can be carried out as the component is being elaborated. Finally, such independently-performed verification work must still provide a guarantee of the relevant properties for any composite language, *i.e.*, the soundness of proof composition and elaboration is essential to our work.

While there has been other work related to metatheoretic analysis for extensible languages, our effort is distinctive in what it takes as fundamental requirements. The particular focus and the results obtained are therefore also different from that in most other work in this realm. We bring this observation out by discussing such work specifically below. These other efforts may be characterized broadly based on the view they take of language extensibility, whether this is realized by combining parts with equal status at a linguistic level or by building around a core language as in this paper. We break down our discussion accordingly.

8.1 Extensibility via the Combination of Complementary Components

In languages built by complementary components, no portion of the language is more essential than any other, so there is no requirement for an identified host language. The language components build on a shared set of declarations of syntactic categories and semantic analyses. Each component declares a portion of the language, adding constructors for the syntactic categories and rules for the semantic analyses for those constructors. For example, one component might introduce Boolean expressions and declare rules for typing and evaluating them, while another might introduce arithmetic expressions with their typing and evaluation rules. Because the shared base limits the semantics the components can describe, there isn't a possibility for them to add new analyses. Correspondingly, in this setting, the idea of associating properties with such analyses—the notion of auxiliary properties in this paper—is not meaningful.

Work has nevertheless been done on developing proofs for metatheoretic properties for extensible language that are obtained through this kind of composition. Like their syntactic categories and semantic analyses, properties for such languages are declared ahead of the components being written, with the proof work distributed across the components. This makes them similar to our foundational properties, those introduced by a host language. One early work, Proof Weaving [15], has each component provide a full proof of each property in Coq, then pulls these proofs apart to try to rebuild them into a proof for a composed language. However, there is no notion corresponding to the soundness of proof composition in this paper: the process described can fill out the structure of the full proof and the portions known when each component proof was written but can, and often does, leave holes the language composer would need to fill to complete the proof.

Another work, Meta-Theory a la Carte [2, 3], also requires each language component to provide proofs for their properties in Coq. However, the encoding used for the language description and proofs prevents examining the shape of sub-terms and how values are computed. This is similar to our restrictions on case analysis, and allows the proofs to be composed automatically to form a working proof. There is one wrinkle in this work, however, as the authors note canonical forms lemmas (*e.g.*, a value of an integer type is an integer) cannot be stated to be shared by all components, as their statements rely on the specific vocabularies introduced by certain components; thus the proofs must be produced in an ad hoc manner at composition time. Similar work was done in Agda at the same time [16], but the authors report they did not succeed in getting Agda to accept the composed proofs.

8.2 Extensibility by Building around a Core Language

One example of this approach is the FPOP [7] system that encodes a version of extensible languages in Coq using the ideas of inheritance and family polymorphism, translating this down into basic Coq. Extensions inherit from a base language, adding to its inductive types for syntax and adding new cases to functions defining semantics, all without needing to modify the inherited definitions. Properties are proven in the context of the base language and each extension. An extension may either reuse an inherited proof or override it. Unlike our approach, FPOP does not have automatic composition of language semantics nor a guarantee of properties introduced by an extension holding for a composition. Compositions of both semantics and proofs rely on glue code for new constructors. Because new semantic definitions and proof cases must be written for constructors from other extensions, it is sometimes the case that a property given by one extension will not hold for a constructor from another extension. Thus FPOP is most useful for adding features to a language one at a time, with each building on the last, as opposed to our view where features are added independently of each other and able to be added to a composition or left out as desired.

Another exemplar of this approach to extensibility, with an extensibility model much more similar to ours than FPOP's model, is the SoundX [12] system. This system allows extensions to introduce new syntax and typing rules for that syntax, which then desugar to the host language. The focus in this work is to provide an automatic method for checking that a well-typed term in the extended language desugars into a well-typed term in the host language. This property permits the host language designer to prove properties about typing, such as type soundness, for the host language alone. Programs written using extension-introduced syntax then have these properties when their desugared versions are run without proving the properties for the extension-introduced syntax because the desugared versions are well-typed. We can prove properties similarly in our framework; however, our framework goes beyond this model in allowing evaluation to be defined on the extended syntax, with the properties about typing proven for the extended syntax directly. Note also SoundX is limited to just this one property. Moreover, because the approach is based on desugaring, extensions cannot introduce new analyses and properties about them, as is done in the security extension example.

Finally, another framework for proving properties [11] works for extensible languages written in attribute grammars specified in Silver. It allows the host language or any extension to introduce properties and prove them only for constructs from the host language. The property then transfers to other constructs across projection, called forwarding [20] in the setting of attribute grammars,

by requiring attribute values to be essentially equal across projection and proving each property holds when relevant values are essentially equal. We share some of the same broad outlines of ideas, with properties carrying across projection, but our system is less restrictive. Rather than requiring values to be essentially equal, we allow the language designer to decide how values should be related—this idea is embedded in the notion of projection constraints. This may lead to more complex proof work as a trade-off, since the extension designer introducing a property must show why it holds across translation rather than relying on values being basically the same.

9 Conclusion and Future Work

We have presented a modular approach to proving properties for programming languages constructed from a host language through the addition of a collection of independently-developed extensions. This approach allows both the host language and each extension to introduce properties and to reason about them in the context of the host language alone or the host language augmented by the extension, with a guarantee the reasoning will ensure the properties will hold for any composition of extensions with the host language without any additional work required of the person determining the composition. More specifically, we have shown how the modular reasoning can be used automatically to extract proofs of the relevant properties for any composed language.

While the approach we have described is quite broad, its actual realization in this paper is limited. We intend to address some of these limitations in future work. One limitation we would like to ease arises from the restricted form we permit for projection rules. We currently require the rules to have exactly two premises, one that determines a projection and another that ensures the relation of interest holds for the projection, with all other arguments being identical. A particularly limiting form of this requirement is seen in the pseudo projection rules used in the generic extension to reason about the behavior in undetermined extensions of relations introduced by the host language. As we have seen in Section 6.4 and discussed more specifically in Section 6.4.4, this requires the behavior of the relation to be identical to that of the projection. However, in many reasoning examples, we can do with weaker requirements. An example of this is provided by Property 5, where the requirement is only that the evaluation of a statement and its projection should produce states that bind variables to the same values. Easing the restriction on projection rules should allow languages more freedom in their definitions and should also expand the reasoning ability.

Another current limitation is our restriction to a host language and extensions that build on only it, where each extension is independent of every other extension. Systems implementing extensible languages, such as the Silver attribute grammar system [19] or the Sterling system we use for language specifications for our implementation, permit extensions to build on other extensions in addition to the host language. A use of this capability can be seen in the ABLEC [9] extensible specification of C written in Silver, where some extensions build on other extensions that provide intermediate levels of abstraction between them and the lower-level C host language. Our framework will be applicable to more language specifications if we can handle more general extension schemes.

In another direction, we intend to continue developing examples of the use of our framework for proving properties. These examples will allow us to explore the trade-off between the strength of projection constraints and the freedom extensions have for defining their semantics. Strong projection constraints make the semantics of extensions easier to model even without detailed knowledge of them, and thus make it easier for other extensions to introduce and prove properties. For example, we might have a constraint for expression evaluation requiring evaluation results to be closely related across projections. This would support properties about the values resulting from evaluation, something Projection Constraint 3, that preserves only variables under a projection, would not support. However, strong projection constraints will also restrict the semantic definitions extension writers can create, and may make it impossible to construct some extensions. We believe the example language we have used in this paper leans toward loose projection constraints, but further investigation of the trade-offs is needed.

References

- BAELDE, D., CHAUDHURI, K., GACEK, A., MILLER, D., NADATHUR, G., TIU, A., AND WANG, Y. Abella: A system for reasoning about relational specifications. *Journal of Formalized Reasoning* 7, 2 (December 2014).
- [2] DELAWARE, B. *Feature Modularity in Mechanized Reasoning*. PhD thesis, University of Texas at Austin, Austin, Texas, USA, 2013.
- [3] DELAWARE, B., D. S. OLIVEIRA, B. C., AND SCHRIJVERS, T. Meta-theory à la carte. In Proceedings of the 40th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (New York, NY, USA, 2013), POPL '13, ACM, pp. 207–218.
- [4] EKMAN, T., AND HEDIN, G. The JastAdd extensible Java compiler. In Proceedings of the Conference on Object Oriented Programming, Systems, Languages, and Systems (OOPSLA) (2007), ACM, pp. 1–18.
- [5] ERDWEG, S., RENDEL, T., KASTNER, C., AND OSTERMANN, K. SugarJ: Library-based syntactic language extensibility. In Proceedings of the Conference on Object Oriented Programming, Systems, Languages, and Systems (OOPSLA) (2011), ACM, pp. 391–406.
- [6] GACEK, A., MILLER, D., AND NADATHUR, G. Nominal abstraction. Information and Computation 209, 1 (2011), 48–73.
- [7] JIN, E., AMIN, N., AND ZHANG, Y. Extensible metatheory mechanization via family polymorphism. Proc. ACM Program. Lang. 7, PLDI (jun 2023).
- [8] KAMINSKI, T. Reliably Composable Language Extensions. PhD thesis, University of Minnesota, Minneapolis, Minnesota, USA, 2017.
- [9] KAMINSKI, T., KRAMER, L., CARLSON, T., AND VAN WYK, E. Reliable and automatic composition of language extensions to C: The ableC extensible language framework. *Proceedings* of the ACM on Programming Languages 1, OOPSLA (Oct. 2017), 98:1–98:29.
- [10] KAMINSKI, T., AND VAN WYK, E. Modular well-definedness analysis for attribute grammars. In Proceedings of the 5th International Conference on Software Language Engineering (SLE) (Sept. 2012), vol. 7745 of Lecture Notes in Computer Science, Springer-Verlag, pp. 352–371.
- [11] KAMINSKI, T., AND VAN WYK, E. Ensuring non-interference of composable language extensions. In Proceedings of the 10th ACM SIGPLAN International Conference on Software Language Engineering (SLE) (October 2017), ACM, pp. 163–174.
- [12] LORENZEN, F., AND ERDWEG, S. Sound type-dependent syntactic language extension. SIG-PLAN Not. 51, 1 (Jan. 2016), 204–216.
- [13] MARTELLI, A., AND MONTANARI, U. An efficient unification algorithm. ACM Transactions on Programming Languages and Systems 4, 2 (Apr. 1982), 258–282.

- [14] MICHAELSON, D., NADATHUR, G., AND VAN WYK, E. Modular metatheory for extensible languages webpage, Dec. 2023. http://mmel.cs.umn.edu.
- [15] MULHERN, A. Proof Weaving. In Proceedings of the First Informal ACM SIGPLAN Workshop on Mechanizing Metatheory (Portland, Oregon, September 2006), The Eleventh ACM SIGPLAN International Conference on Functional Programming.
- [16] SCHWAAB, C., AND SIEK, J. G. Modular Type-Safety Proofs in Agda. In Proceedings of the 7th Workshop on Programming Languages Meets Program Verification (New York, NY, USA, 2013), PLPV '13, ACM, pp. 3–12.
- [17] SCHWERDFEGER, A., AND VAN WYK, E. Verifiable composition of deterministic grammars. In Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI) (2009), ACM, pp. 199–210.
- [18] TIU, A. A Logical Framework for Reasoning about Logical Specifications. PhD thesis, Pennsylvania State University, May 2004.
- [19] VAN WYK, E., BODIN, D., GAO, J., AND KRISHNAN, L. Silver: an extensible attribute grammar system. Science of Computer Programming 75, 1–2 (January 2010), 39–54.
- [20] VAN WYK, E., DE MOOR, O., BACKHOUSE, K., AND KWIATKOWSKI, P. Forwarding in attribute grammars for modular language design. In *Proceedings of the 11th Conference on Compiler Construction (CC)* (2002), vol. 2304 of *Lecture Notes in Computer Science*, Springer-Verlag, pp. 128–142.

A Full Language Library

We have here the details of the host language and each extension included in our language library.

A.1 Host Language H

A.1.1 Syntax

 $\begin{aligned} \mathscr{C}^{H} &= \{s, e, n, i, ty, \Gamma, \gamma\} \\ \mathbb{C}^{H} &: \\ s &::= skip \mid decl(n, ty, e) \mid assign(n, e) \mid seq(s, s) \mid ifte(e, s, s) \mid while(e, s) \\ e &::= var(n) \mid intlit(i) \mid true \mid false \mid add(e, e) \mid eq(e, e) \mid gt(e, e) \mid not(e) \\ ty &::= int \mid bool \\ \Gamma &::= nilty \mid consty(n, ty, \Gamma) \\ \gamma &::= nilval \mid n : e; \gamma \end{aligned}$

A.1.2 Relations

$$\begin{aligned} \mathscr{R}^{H} &= \{ lkpTy(\Gamma^{*}, n, ty), \quad notBoundTy(\Gamma^{*}, n), \quad lkpVal(\gamma^{*}, n, e), \quad value(e^{*}), \quad vars(e^{*}, 2^{n}), \\ \Gamma \vdash e^{*}: ty, \quad \Gamma \vdash s^{*}, \Gamma, \quad update(\gamma^{*}, n, e, \gamma), \quad remove(\gamma^{*}, n, \gamma), \quad \gamma \vdash e^{*} \Downarrow e, \quad (\gamma, \ s^{*}) \Downarrow \gamma \} \end{aligned}$$

 \mathbb{R}^H contains the following rules:

$$lkpTy(\Gamma^*,n,ty)$$

$$\frac{n \neq n' \quad lkpTy(consty(n, ty, \Gamma), n, ty)}{lkpTy(consty(n', ty', \Gamma), n, ty)} \text{ LT-CONS-TAIL}$$

$$\frac{n \neq n' \quad lkpTy(consty(n', ty', \Gamma), n, ty)}{lkpTy(consty(n', ty', \Gamma), n, ty)} \text{ LT-CONS-TAIL}$$

$$\frac{n \neq n' \quad notBoundTy(\Gamma, n)}{notBoundTy(consty(n', ty', \Gamma), n)} \text{ NBT-CONS}$$

$$\frac{lkpVal(\gamma^*, n, e)}{n \neq n' \quad lkpVal(\gamma, n, v)}$$

 $\overline{lkpVal((n:v; \gamma), n, v)}$ LV-Cons-Head

$$\frac{n \neq n'}{lkpVal((n':v'; \gamma), n, v)} \text{ LV-Cons-Tail}$$

$update(\gamma^*, n, v, \gamma)$	γ)
$\frac{remove(\gamma, n, \gamma')}{update(\gamma, n, v, (n : v; \gamma'))} \text{ Update}$	
$remove(\gamma^*,n,\gamma$	$\frac{remove(\gamma, n, \gamma')}{nove((n':v'; \gamma), n, (n':v'; \gamma'))} \text{ R-Cons-Tail}$
$\overline{remove((n:v; \gamma), n, \gamma)} $ R-Cons-Head \overline{rem}	$nove((n':v'; \gamma), n, (n':v'; \gamma'))$ R-CONS-TAIL
$value(e^*)$	
$\overline{value(intlit(i))}$ V-INT $\overline{value(true)}$ V-	-TRUE $\overline{value(false)}$ V-False
$vars(e^*, ns)$	
$\overline{vars(var(n), \{n\})}$ VR-VAR	$\overline{vars(true, \varnothing)}$ VR-TRUE
$\overline{vars(intlit(i), \varnothing)}$ VR-INTLIT	$\overline{vars(false, \varnothing)}$ VR-false
$\frac{vars(e_1, vr_1) vars(e_2, vr_2)}{vars(add(e_1, e_2), (vr_1 \cup vr_2))} \text{VR-ADD}$	$\frac{vars(e_1, vr_1) vars(e_2, vr_2)}{vars(gt(e_1, e^2), (vr_1 \cup vr_2))} \text{ VR-GT}$
$\frac{vars(e_1, vr_1) vars(e_2, vr_2)}{vars(eq(e_1, e_2), (vr_1 \cup vr_2))} \text{ VR-EQ}$	$\frac{vars(e, vr)}{vars(not(e), vr)}$ VR-NOT
$\Gamma \vdash e^*: ty$	
$\frac{lkpTy(\Gamma, n, ty)}{\Gamma \vdash var(n) : ty} \text{ T-VAR}$	$\overline{\Gamma \vdash true : bool} \ ^{\text{T-TRUE}}$
$\overline{\Gamma \vdash intlit(i) : int} \ \mathrm{T-INTLIT}$	$\overline{\Gamma \vdash false : bool} \ ^{\text{T-FALSE}}$
$\frac{\Gamma \vdash e_1 : int \qquad \Gamma \vdash e_2 : int}{\Gamma \vdash add(e_1, e_2) : int} \text{ T-ADD}$	$\frac{\Gamma \vdash e_1 : int \qquad \Gamma \vdash e_2 : int}{\Gamma \vdash gt(e_1, e_2) : bool} \text{ T-gr}$

$$\frac{\Gamma \vdash e_1 : int \quad \Gamma \vdash e_2 : int}{\Gamma \vdash eq(e_1, e_2) : bool} \text{ T-EQ} \qquad \qquad \frac{\Gamma \vdash e : bool}{\Gamma \vdash not(e) : bool} \text{ T-NOT}$$

 $\Gamma \vdash s^*, \Gamma$

$$\frac{\Gamma \vdash e: ty \quad lkpTy(\Gamma, n, ty)}{\Gamma \vdash assign(n, e), \Gamma} \text{TS-assign}$$

$$\frac{\Gamma \vdash s_1, \Gamma' \qquad \Gamma' \vdash s_2, \Gamma''}{\Gamma \vdash seq(s_1, s_2), \Gamma''} \text{ TS-seq}$$

$$\frac{\Gamma \vdash e: bool \quad \Gamma \vdash s_1, \Gamma' \quad \Gamma \vdash s_1, \Gamma''}{\Gamma \vdash ifte(e, s_1, s_2), \Gamma} \text{ TS-IFTE}$$

 $\frac{\Gamma \vdash e: ty \quad notBoundTy(\Gamma, n)}{\Gamma \vdash decl(n, ty, e), consty(n, ty, \Gamma)} \text{ TS-DECL}$

$$\frac{\Gamma \vdash e: bool \qquad \Gamma \vdash s, \Gamma'}{\Gamma \vdash while(e, s), \Gamma} \text{ TS-WHILE}$$

$$\gamma \vdash e^* \Downarrow e$$

 $\frac{lkpVal(\gamma, n, v)}{\gamma \vdash var(n) \Downarrow v}$ E-VAR

 $\frac{1}{\gamma \vdash \textit{true} \Downarrow \textit{true}} \to \text{E-true}$

 $\frac{1}{\gamma \vdash intlit(i) \Downarrow intlit(i)} \to \text{E-INTLIT}$

$$\frac{\gamma \vdash e_1 \Downarrow v_1}{\gamma \vdash e_2 \Downarrow v_2} \frac{v_1 = v_2}{v_1 \vdash eq(e_1, e_2) \Downarrow true}$$
E-EQ-TRUE

$$\frac{\gamma \vdash e_1 \Downarrow intlit(i_1)}{\gamma \vdash e_2 \Downarrow intlit(i_2) \quad i_1 > i_2} \xrightarrow{\gamma \vdash gt(e_1, e_2) \Downarrow true} \text{E-GT-TRUE}$$

$$\frac{\gamma \vdash e \Downarrow \mathit{false}}{\gamma \vdash \mathit{not}(e) \Downarrow \mathit{true}} \to \mathsf{E-not-True}$$

$$\overline{\gamma \vdash false \Downarrow false} \to FALSE$$

$$\frac{\gamma \vdash e_1 \Downarrow v_1}{\gamma \vdash e_2 \Downarrow v_2} \xrightarrow{v_1 \neq v_2} \text{E-EQ-FALSE}$$

$$\frac{\gamma \vdash e_1 \Downarrow intlit(i_1)}{\gamma \vdash e_2 \Downarrow intlit(i_2) \quad i_1 \leq i_2} \xrightarrow{\gamma \vdash gt(e_1, e_2) \Downarrow false} \text{E-GT-FALSE}$$

 $\frac{\gamma \vdash e \Downarrow true}{\gamma \vdash not(e) \Downarrow false} \to \text{E-not-False}$

$$\frac{\gamma \vdash e_1 \Downarrow intlit(i_1) \qquad \gamma \vdash e_2 \Downarrow intlit(i_2) \qquad plus(i_1, i_2, i)}{\gamma \vdash add(e_1, e_2) \Downarrow intlit(i)} \to \text{E-ADD}$$

$(\gamma,\ s^*)\Downarrow\gamma$

$$\frac{1}{(\gamma, skip) \Downarrow \gamma} X-SKIP$$

$$\frac{\gamma \vdash e \Downarrow true \quad (\gamma, \ s_1) \Downarrow \gamma'}{(\gamma, \ ifte(e, s_1, s_2)) \Downarrow \gamma'} \text{ X-IFTE-TRUE}$$

$$\frac{(\gamma, s_1) \Downarrow \gamma' \quad (\gamma', s_2) \Downarrow \gamma''}{(\gamma, seq(s_1, s_2)) \Downarrow \gamma''} X-seq$$

$$\frac{\gamma \vdash e \Downarrow false}{(\gamma, ifte(e, s_1, s_2)) \Downarrow \gamma'} X\text{-IFTE-FALSE}$$

$$\frac{\gamma \vdash e \Downarrow true \quad (\gamma, \ s) \Downarrow \gamma'}{(\gamma', \ while(e, s)) \Downarrow \gamma''} X-\text{WHILE-TRUE}$$

$$\frac{\gamma \vdash e \Downarrow v \quad update(\gamma, n, v, \gamma')}{(\gamma, \ assign(n, e)) \Downarrow \gamma'} \text{ X-ASSIGN}$$

 $\frac{\gamma \vdash e \Downarrow v}{(\gamma, \ decl(n, ty, e)) \Downarrow n : v; \ \gamma} \text{ X-DECL}$

$$\frac{\gamma \vdash e \Downarrow false}{(\gamma, while(e, s)) \Downarrow \gamma} X\text{-while-False}$$

A.1.3 Projections

$$\begin{split} \mathcal{T}^{H} &= \{ proj_{e}: e, \ proj_{s}: s, \ proj_{ty}: ty \} \\ \mathbb{T}^{H} &= \varnothing \\ \mathbb{S}^{H} &= \varnothing \end{split}$$

A.2 List Extension L

A.2.1 Syntax

 $\mathscr{C}^L = \varnothing$

A.2.2 Relations

$$\mathscr{R}^L = \varnothing$$

 \mathbb{R}^L contains the following rules:

$$\begin{array}{c} \hline \Gamma \vdash e^*:ty \\ \hline \Gamma \vdash nil: list(ty) \end{array} \overset{}{} T\text{-NIL} & \frac{\Gamma \vdash e_1:ty \quad \Gamma \vdash e_2: list(ty)}{\Gamma \vdash cons(e_1, e_2): list(ty)} \end{array} \overset{}{} T\text{-cons} \\ \hline \Gamma \vdash e: list(ty) \\ \hline \Gamma \vdash e: list(ty) \\ \hline \Gamma \vdash head(e):ty \end{array} \overset{}{} T\text{-HAD} & \frac{\Gamma \vdash e: list(ty)}{\Gamma \vdash tail(e): list(ty)} \end{array} \overset{}{} T\text{-TAL} \\ \hline \frac{\Gamma \vdash e: list(ty)}{\Gamma \vdash null(e): bool} \end{array} \overset{}{} T\text{-NULL} \\ \hline \frac{value(e^*)}{value(cons(e_1, e_2))} \end{aligned} \overset{}{} \text{V-cons} \\ \hline \frac{vars(e^*, 2^n)}{vars(head(e), vr)} \overset{}{} \text{VR-HAD} & \frac{vars(e, vr)}{vars(head(e), vr)} \end{aligned} \overset{}{} \text{VR-HAD} \\ \frac{vars(e_1, vr_1) \quad vars(e_2, vr_2)}{vars(cons(e_1, e_2), (vr_1 \cup vr_2))} \end{aligned} \overset{}{} \text{VR-cons} & \frac{vars(e, vr)}{vars(tail(e), vr)} \end{aligned} \overset{}{} \text{VR-TAL} \\ \hline \frac{vars(e, vr)}{vars(null(e), vr)} \lor \end{aligned} \overset{}{} \text{VR-NULL} \\ \hline \frac{\gamma \vdash e^* \Downarrow e}{\gamma \vdash head(e) \Downarrow v_1} \overset{}{} \text{E-HEAD} \\ \hline \end{array}$$

$$\frac{\gamma \vdash e_{1} \Downarrow v_{1} \qquad \gamma \vdash e_{2} \Downarrow v_{2}}{\gamma \vdash cons(e_{1}, e_{2}) \Downarrow cons(v_{1}, v_{2})} \text{ E-CONS} \qquad \qquad \frac{\gamma \vdash e \Downarrow cons(v_{1}, v_{2})}{\gamma \vdash tail(e) \Downarrow v_{2}} \text{ E-TAIL}$$

$$\frac{\gamma \vdash e \Downarrow nil}{\gamma \vdash null(e) \Downarrow true} \text{ E-NULL-TRUE} \qquad \qquad \frac{\gamma \vdash e \Downarrow cons(v_{1}, v_{2})}{\gamma \vdash null(e) \Downarrow false} \text{ E-NULL-FALSE}$$

$$\frac{\Gamma \vdash s^{*}, \Gamma}{\Gamma \vdash splitlist(n_{hd}, ty) \qquad lkpTy(\Gamma, n_{tl}, list(ty))} \text{ TS-SPLITLIST}$$

$$\frac{(\gamma, s^{*}) \Downarrow \gamma}{(\gamma, s^{*}) \Downarrow \gamma}$$

 $\frac{\gamma \vdash e \Downarrow cons(v_1, v_2) \quad n_{hd} \neq n_{tl}}{(\gamma, \ splitlist(n_{hd}, n_{tl}, e)) \Downarrow n_{hd} : v_1; \ n_{tl} : v_2; \ \gamma} \text{ X-splitlist}$

A.2.3 Projections

 $\mathscr{T}^L = \varnothing$

 \mathbb{T}^L contains the following rules:

$$\overline{proj_e(null(e), e)}$$
P-NULL $\overline{proj_e(nil, true)}$ P-NIL $\overline{proj_e(head(e), e)}$ P-HEAD $\overline{proj_e(cons(e_1, e_2), eq(e_1, e_2))}$ P-CONS $\overline{proj_e(tail(e), e)}$ P-TAIL $\overline{proj_{ty}(list(ty), ty)}$ P-LIST

$$\frac{n_{hd} \neq n_{tl}}{proj_s(splitlist(n_{hd}, n_{tl}, e), seq(seq(assign(n_{hd}, e), assign(n_{tl}, tail(var(n_{hd})))), assign(n_{hd}, head(var(n_{hd})))))} P-SPLITLIST$$

 $\mathbb{S}^L = \varnothing$

A.3 Security Extension S

A.3.1 Syntax

 $\mathscr{C}^S = \{sl, \Sigma\}$

 \mathbb{C}^{S} :

::= secdecl(n, ty, sl, e)ssl ::= public | private Σ ::= nilsec | conssec(n, sl, Σ)

A.3.2 Relations

 $\mathscr{R}^{S} = \{ lkpSec(\Sigma^{*}, n, sl), notBoundSec(\Sigma^{*}, n), join(sl^{*}, sl, sl), \Sigma \vdash level(e^{*}, sl), level(e^{*}, sl), undSec(\Sigma^{*}, n), level(e^{*}, sl), undSec(\Sigma^{*}, n), undSec(\Sigma^{*}, n)$ $\Sigma \ sl \vdash secure(s^*, \Sigma) \}$

 \mathbb{R}^S contains the following rules:

$$\label{eq:started_st$$

$$(\gamma,\ s^*) \Downarrow \gamma$$

$$\frac{\gamma \vdash e \Downarrow v}{(\gamma, \ secdecl(n, ty, sl, e)) \Downarrow n : v; \ \gamma} \text{ X-secdecl}$$

$$lkpSec(\Sigma^*,n,sl)$$

 $\frac{n \neq n' \quad lkpSec(\Sigma, n, sl)}{lkpSec(conssec(n, sl, \Sigma), n, sl)} \text{ LS-Cons-Head} \qquad \frac{n \neq n' \quad lkpSec(\Sigma, n, sl)}{lkpSec(conssec(n', sl', \Sigma), n, sl)} \text{ LS-Cons-Tail}$

 $notBoundSec(\Sigma^*,n)$

$$\overline{notBoundSec(nilsec, n)}$$
 NBS-NIL

 $\frac{n \neq n' \quad notBoundSec(\Sigma, n)}{notBoundSec(conssec(n', ty', \Sigma), n)} \text{ NBS-CONS}$

$$\frac{\Sigma \vdash level(e, public) \qquad lkpSec(\Sigma, n, public)}{\Sigma \ public \vdash secure(assign(n, e), \Sigma)} \ S-ASSIGN-PUBLIC$$

$$\frac{\Sigma \vdash level(e,\ell) \quad join(\ell',\ell,\ell'') \quad \Sigma \ \ell'' \vdash secure(s_1,\Sigma_1) \quad \Sigma \ \ell'' \vdash secure(s_2,\Sigma_2)}{\Sigma \ \ell' \vdash secure(ifte(e,s_1,s_2),\Sigma)}$$
S-IFTE

$$\frac{\Sigma \vdash level(e, \ell) \quad join(\ell', \ell, \ell'') \quad \Sigma \ \ell'' \vdash secure(s, \Sigma')}{\Sigma \ \ell' \vdash secure(while(e, s), \Sigma)} \text{ S-while}$$

$$\frac{\Sigma \vdash level(e,\ell) \quad notBoundSec(\Sigma,n)}{\Sigma \ \ell' \vdash secure(secdecl(n,ty,private,e),conssec(n,private,\Sigma))} \text{ S-secdecl-private}$$

 $\frac{\Sigma \vdash level(e, public) \quad notBoundSec(\Sigma, n)}{\Sigma \ public \vdash secure(secdecl(n, ty, public, e), conssec(n, public, \Sigma))} \text{ S-secdecl-public}$

A.3.3 Projections

 $\mathscr{T}^S = \varnothing$

 \mathbb{T}^S contains the following rule:

$$\frac{1}{proj_s(secdecl(n,ty,\ell,e),decl(n,ty,e))} P-SECDECL$$

 \mathbb{S}^S contains the following rules:

$$\frac{\operatorname{proj}_{e}(e,e')}{\Sigma \vdash \operatorname{level}(e,\ell)} \xrightarrow{\Sigma \vdash \operatorname{level}(e',\ell)} \operatorname{P-LEVEL} \qquad \frac{\operatorname{proj}_{s}(s,s')}{\Sigma \ell \vdash \operatorname{secure}(s,\Sigma')} \xrightarrow{\Sigma \ell \vdash \operatorname{secure}(s',\Sigma')} \operatorname{P-SECURE}$$

B Substitution, Unification and Term Replacement

This appendix contains observations used in the proof of Lemma 5 in Section 6.3.

We first show a distributivity property for term replacement.

Theorem 10. Let θ be a substitution whose domain does not contain any of the variables that appear in the sequence of terms \overline{t} . Then

- 1. for any term $s, s[\![c(\overline{t})/\iota]\!] = s[\theta][\![c(\overline{t})/\iota]\!] = s[\theta][\![c(\overline{t})/\iota]\!].$
- 2. for any formula F, $F[[c(\overline{t})/\iota]][\theta[[c(\overline{t})/\iota]]] = F[\theta][[c(\overline{t})/\iota]]$.
- 3. for any unification problem $\mathcal{U}, \mathcal{U}[\![c(\overline{t})/\iota]\!] = \mathcal{U}[\theta][\![c(\overline{t})/\iota]\!] = \mathcal{U}[\theta][\![c(\overline{t})/\iota]\!]$.

Proof. The second and third clauses follow easily from the first. We prove the first clause by induction on the structure of s.

If s is a variable, the argument is straightforward: essentially, both sides of the equation reduce to x if x is not in the domain of θ and to $t'[[c(\bar{t})/\iota]]$ if $\langle x, t' \rangle \in \theta$. If s is ι , then both sides reduce to $c(\bar{t})$; we make use of the fact that no variables in t appear in the domain of θ to ensure that the lefthand side of the equation reduces to this term. If s is some other constant c', then both sides reduce to c'. Finally, suppose that s is a compound term of the form $c'(r_1, \ldots, r_n)$. In this case, we make use of the fact that substitution and term replacement distribute to the arguments of the term and the induction hypothesis to conclude that the equality holds; to allow for the application of the induction hypothesis, we note that, for $1 \leq i \leq n$, the variables that appear in r_i are included in the collection of variables that appear in s.

We next show that the unifiability of $\mathcal{U}[\![c(\bar{t})/\iota]\!]$ implies the unifiability of \mathcal{U} in the case the constructor c and the variables in \bar{t} do not appear. In the proof, we will find a "generalized inversion of replacement" operation on terms, useful.

Definition 12 (Inversion of Term Substitution). The "inversion" of a term s is an operation that replaces all subterms of t of the form $c(\overline{t'})$ for any sequence of terms $\overline{t'}$, i.e., any term in which c appears as the top-level symbol, with ι . We will write the result of this operation applied to s as s_{inv}^c . This operation is extended to substitutions, unification problems, etc., by essentially distributing it to the terms in them. The notation is also lifted accordingly; e.g., we write θ_{inv}^c to denote the inversion applied to θ .

Lemma 11. Let s be a term in which c and the variables in the sequence of terms \overline{t} do not appear. Then, for any substitution θ , it is the case that $(s[[c(\overline{t})/\iota]][\theta])_{inv}^c = s[\theta_{inv}^c]$.

Proof. By induction on the structure of s. We consider by cases this structure.

Suppose s is a variable x. In this case, $s[c(\bar{t})/\iota] = x$. Now the analysis breaks up into two subcases, depending on whether or not x is in the domain of θ . If it is not in this domain, then it will also not be in the domain of θ_{inv}^c and both $(s[c(\bar{t})/\iota][\theta])_{inv}^c$ and $s[\theta_{inv}^c]$ will be x. Alternatively, let $\langle x, t \rangle \in \theta$. Then $\langle x, t_{inv}^c \rangle \in \theta_{inv}^c$ The desired conclusion now follows by observing that $(s[c(\bar{t})/\iota][\theta])_{inv}^c = (x[\theta])_{inv}^c = s[\theta_{inv}^c]$.

Suppose s is a constant, which includes the case where s is ι . In this case, we claim that both $(s[[c(\bar{t})/\iota]][\theta])_{inv}^c$ and $s[\theta_{inv}^c]$ are identical to s. This is obvious when s is a constant different from ι . When s is ι , the claim follows easily from observing $s[[c(\bar{t})/\iota]] = c(\bar{t})$, substitution into $c(\bar{t})$ preserves the top-level symbol, and that $(\cdot)_{inv}^c$ only looks at this symbol, reducing the term to ι if it is c.

The last case to consider is that when s is of the form $c'(r_1, \ldots, r_n)$. Here we use the induction hypothesis to conclude that, for $1 \leq i \leq n$, $(r_i [c(\bar{t})/\iota]][\theta])_{inv}^c = r_i [\theta_{inv}^c]$. Noting substitution and the $(\cdot)_{inv}^c$ operation preserve the top-level symbol in a compound term when this symbol is different from c and that they distribute to the arguments now suffices to complete the proof.

Theorem 12. If \mathcal{U} is a unification problem in which c and the variables in the sequence of terms \overline{t} do not appear and θ unifies $\mathcal{U}[\![c(\overline{t})/\iota]\!]$, then θ_{inv}^c unifies \mathcal{U} .

Proof. We associate a measure given by a pair of natural numbers $\langle n_1, n_2 \rangle$ with a unification problem when n_1 sums up the sizes of the terms in the problem and n_2 counts the number of pairs of terms. The proof is by lexicographic induction on the measure associated with \mathcal{U} . The argument is based on picking a pair $\langle s_1, s_2 \rangle$ in \mathcal{U} and reducing the truth of the lemma for \mathcal{U} to its truth on a smaller unification problem.

Suppose that one of s_1 and s_2 is a variable x. Without loss of generality, let this be s_1 . Then we have the following cases for s_2 :

- 1. s_2 is ι . In this case, $\langle s_1, s_2 \rangle [\![c(\bar{t})/\iota]\!]$ will be a pair of the form $\langle x, c(\bar{t'}) \rangle$. Since θ makes these two terms equal, it must have a substitution of the form $\langle x, c(\bar{t''}) \rangle$ in it for x. But, then, θ_{inv}^c must have the pair $\langle x, \iota \rangle$ in it.
- 2. s_2 is a variable y. In this case, $\langle s_1, s_2 \rangle$ is also a member of $\mathcal{U}\llbracket c(\overline{t})/\iota \rrbracket$ and, since θ is a unifier for this problem, it must be the case that $\theta[s_1] = \theta[s_2]$. From this it follows easily that $\theta_{inv}^c[s_1] = \theta_{inv}^c[s_2]$.
- 3. s_2 is a term different from a variable and ι . In this case, θ must have a pair of the form $\langle x, \theta[s_2[\![c(\bar{t})/\iota]\!]] \rangle$ in it. But, then, θ_{inv}^c will have the pair $\langle x, (\theta[s_2[\![c(\bar{t})/\iota]\!]])_{inv}^c \rangle$ in it. By Lemma 11, this pair is the same as $\langle x, \theta_{inv}^c[s_2] \rangle$, *i.e.*, θ_{inv}^c must unify the two terms in this pair.

Thus, in all these cases, the truth of the lemma is dependent on its truth for the unification problem that results from \mathcal{U} by leaving out the pair $\langle s_1, s_2 \rangle$. We may therefore invoke the induction hypothesis to complete the proof.

The cases that remain are those where s_1 and s_2 both have a constant or a constructor as their top-level symbol. If either of them is a constant, then the other must be an identical constant else θ cannot unify $s_1[[c(\bar{t})/\iota]]$ and $s_2[[c(\bar{t})/\iota]]$; if the constant is ι , we need to observe that the top-level symbol will become c under the replacement and the only way the other term will have the same top-level symbol is if it too is ι . Thus, in this situation, θ_{inv}^c must unify this pair and we are left to show the lemma holds for a smaller unification problem, which must be the case by the induction hypothesis.

To conclude the proof, we have to consider the case where s_1 and s_2 are both compound terms. Since the replacement of ι by $c(\overline{t})$ must preserve the top-level function symbol and θ unifies \mathcal{U} , this symbol in s_1 and s_2 must be identical. Thus, s_1 and s_2 must be terms of the form $c'(r_1^1, \ldots, r_n^1)$ and $c'(r_1^2, \ldots, r_n^2)$, respectively. Since θ unifies $s_1[\![c(\overline{t})/\iota]\!]$ and $s_2[\![c(\overline{t})/\iota]\!]$, it easily follows that it must unify $\{\langle r_1^1[\![c(\overline{t})/\iota]\!], r_1^2[\![c(\overline{t})/\iota]\!]\rangle, \ldots, \langle r_n^n[\![c(\overline{t})/\iota]\!], r_n^2[\![c(\overline{t})/\iota]\!]\rangle\}$. Letting \mathcal{U}' represent the unification problem obtained from \mathcal{U} by removing $\langle s_1, s_2 \rangle$, it then follows that θ must unify $(\{\langle r_1^1, r_1^2 \rangle, \ldots, \langle r_n^1, r_n^2 \rangle\} \cup \mathcal{U}')[\![c(\overline{t})/\iota]\!]$. Now, the sum of the sizes of the terms in the unification problem $\{\langle r_1^1, r_1^2 \rangle, \ldots, \langle r_n^1, r_n^2 \rangle\} \cup \mathcal{U}'$ is smaller than that of \mathcal{U} , and hence the induction hypothesis can be applied to it. Doing so implies that θ_{inv}^c is a unifier for this problem, from which it easily follows that θ_{inv}^c is a unifier for \mathcal{U} .

Finally we show there is an mgu for \mathcal{U} from which we can get an mgu for $\mathcal{U}[\![c(\bar{t})/\iota]\!]$ under suitable circumstances.

Lemma 13. Let x be a variable that does not appear in the terms in the sequence \overline{t} . Then x occurs in a term s if and only if it occurs in $s \|c(\overline{t})/\iota\|$.

Proof. By an easy induction on the structure of s.

Theorem 14. Let \mathcal{U} be a unification problem in which the variables in the sequence of terms \overline{t} do not appear. If \mathcal{U} is unifiable, then there is an mgu θ for \mathcal{U} whose domain does not contain variables appearing in \overline{t} and is such that $\theta[[c(\overline{t})/\iota]]$ is an mgu for $\mathcal{U}[[c(\overline{t})/\iota]]$; note the domain of this mgu for $\mathcal{U}[[c(\overline{t})/\iota]]$ must also be disjoint from the collection of variables appearing in t.

Proof. The theorem is vacuously true if \mathcal{U} is not unifiable. We therefore assume it is. We then use the property proved in [13] that an mgu for it can be obtained by applying the following transformations in any order:

- **Reorder** If there is a pair of terms $\langle s, x \rangle$ where s is not a variable and x is one, replace it with $\langle x, s \rangle$.
- **Drop Trivial** If there is a pair of the form $\langle x, x \rangle$ where x is a variable, drop the pair.
- **Variable Elimination** If there is a pair of the form $\langle x, s \rangle$ where x is a variable, s is not x and x does not occur in s but it does occur in a term in some other pair in the current unification problem, transform the problem by applying the substitution $\{\langle x, s \rangle\}$ to it. Note that x must not appear in s for this step to be applicable but this is guaranteed to be the case because the original unification problem is solvable.
- **Term Reduction** If there is a pair of the form $\langle c'(r_1^1, \ldots, r_n^1), c'(r_1^2, \ldots, r_n^2) \rangle$ for some constructor c', then transform the unification problem by replacing this pair with the set of pairs $\{\langle r_1^1, r_1^2 \rangle, \ldots, \langle r_n^1, r_n^2 \rangle\}$; in the degenerate case, the two terms may be constants, in which case the pair gets dropped. Once again, this must be the only case for a pair of terms with a constructor as the top-level symbol because the original problem is unifiable.

The application of these steps is guaranteed to terminate. When they do, what will be left behind will be a collection of pairs of terms whose first component is a variable that does not appear anywhere else in the collection. A unification problem in this form is called a *solved form* and if the transformation steps yield a unification problem in such a form, it is an mgu for the original problem. Since none of the steps introduce any new variables, the domain of the mgu that is produced in this way for \mathcal{U} must be limited to the variables appearing in \mathcal{U} and hence must be disjoint from the collection of variables that occur in \overline{t} .

We will show below that if \mathcal{U}' is a unification problem in which neither the constructor c nor the variables in \overline{t} appear and it can be transformed into the unification problem \mathcal{U}'' by the application of one of the steps described, then $\mathcal{U}'[[c(\overline{t})/\iota]]$ can be transformed into $\mathcal{U}''[[c(\overline{t})/\iota]]$ by the application of a finite sequence of these steps. Using Lemma 13, it is easy to see that if \mathcal{U} is in solved form then $\mathcal{U}'[[c(\overline{t})/\iota]]$ must also be in solved form. The theorem follows from these facts.

It only remains to be shown that a transformation step applied to \mathcal{U}' can be mimicked with respect to $\mathcal{U}'[c(\bar{t})/\iota]$. Since the term replacement operation leaves variables unchanged, this is obvious for the *reorder* and *drop trivial* steps. For variable elimination, we observe first that if a pair of the form $\langle x, s \rangle$ appears in \mathcal{U}' , then the pair $\langle x, s[c(\bar{t})/\iota]] \rangle$ must appear in $\mathcal{U}'[c(\bar{t})/\iota]$. Further, using Lemma 13, we see that the conditions for the application of the same transformation step to $\mathcal{U}'[c(\bar{t})/\iota]$ must be satisfied. Applying it will yield the unification problem $\mathcal{U}'[c(\bar{t})/\iota][\{x, s[c(\bar{t})/\iota]\})]$ which, by Theorem 10, must be the same as $\mathcal{U}'[\{\langle x, s \rangle\}][c(\bar{t})/\iota]$. But this is, in fact, nothing other than $\mathcal{U}''[c(\bar{t})/\iota]$. Finally, for *term reduction* we use the fact that term replacement leaves constructors other than ι unchanged and distribute to the arguments. In the only case that escapes this consideration, *i.e.*, when the pair is $\langle \iota, \iota \rangle$, the observation is that the corresponding pair in $\mathcal{U}'[c(\bar{t})/\iota]$ will be $\langle c(\bar{t}), c(\bar{t}) \rangle$. However, this pair can be eliminated from the unification problem by repeated applications of *term reduction* and *drop trivial*.