# A Survey on Large Language Models for Software Engineering

Quanjun Zhang, Chunrong Fang, Yang Xie, Yaxin Zhang, Yun Yang, Weisong Sun, Shengcheng Yu, Zhenyu Chen

Abstract—Software Engineering (SE) is the systematic design, development, maintenance, and management of software applications underpinning the digital infrastructure of our modern world. Very recently, the SE community has seen a rapidly increasing number of techniques employing Large Language Models (LLMs) to automate a broad range of SE tasks. Nevertheless, existing information of the applications, effects, and possible limitations of LLMs within SE is still not well-studied.

In this paper, we provide a systematic survey to summarize the current state-of-the-art research in the LLM-based SE community. We summarize 62 representative LLMs of Code across three model architectures, 15 pre-training objectives across four categories, and 16 downstream tasks across five categories. We then present a detailed summarization of the recent SE studies for which LLMs are commonly utilized, including 947 studies for 112 specific code-related tasks across five crucial phases within the SE workflow. We also discuss several critical aspects during the integration of LLMs into SE, such as empirical evaluation, benchmarking, security and reliability, domain tuning, compressing and distillation. Finally, we highlight several challenges and potential opportunities on applying LLMs for future SE studies, such as exploring domain LLMs and constructing clean evaluation datasets. Overall, our work can help researchers gain a comprehensive understanding about the achievements of the existing LLM-based SE studies and promote the practical application of these techniques. Our artifacts are publicly available and will be continuously updated at the living repository: https://github.com/iSEngLab/AwesomeLLM4SE.

Index Terms—Software Engineering, Large Language Model, AI and Software Engineering, LLM4SE

#### **1** INTRODUCTION

Software engineering (SE) stands as an essential pursuit focused on systematically and predictably designing, developing, testing, and maintaining software systems [1]. As software increasingly becomes the infrastructure of various industries (*e.g.*, transportation, healthcare, and education) nowadays, SE plays a crucial role in modern society by ensuring software systems are built in a systematic, reliable, and efficient manner [2]. As a very active area, SE has been extensively investigated in the literature and has sustained attention from both the academic and industrial communities for several decades [3], [4].

Very recently, one of the most transformative advancements in the realm of SE is the emergence of large language models (LLMs). Advanced LLMs (*e.g.*, BERT [5], T5 [6] and GPT [7]) have significantly improved performance across a wide range of natural language processing (NLP) tasks, such as machine translation and text classification. Typically, such models are pre-trained to derive generic language

representations by self-supervised training on large-scale unlabeled data and then are transferred to benefit multiple downstream tasks by supervised fine-tuning on limited labeled data. Inspired by the success of LLMs in NLP, many recent attempts have been adopted to boost numerous code-related tasks (e.g., code summarization and code search) with LLMs (e.g., CodeBERT [8] and CodeT5 [9]). The application of LLMs to SE has had a profound impact on the field, transforming how developers approach coderelated tasks automatically. For example, ChatGPT [10], one of the most notable LLMs with billions of parameters, has demonstrated remarkable performance in a variety of tasks, showcasing the potential of LLMs to revolutionize the SE industry. Overall, the SE community has seen a rapidly increasing number of a broad range of SE studies equipped with LLMs, already yielding substantial benefits and further demonstrating a promising future in follow-up research.

However, the complex SE workflow (*e.g.*, software development, testing, and maintenance) and a mass of specific code-related tasks (*e.g.*, vulnerability detection, fault localization, and program repair) make it difficult for interested researchers to understand state-of-the-art LLM-based SE research and improve upon them. Besides, the constant emergence of advanced LLMs with different architectures, training methods, sources, and a plethora of fine-tuning methods brings challenges in keeping pace with and effectively utilizing these advancements. For example, researchers have conducted various studies to extensively investigate the effectiveness of LLMs in the field of program repair [11], [11], [12]. These studies encompass different research aspects (*e.g.*, empirical and technical studies [13]), types of LLMs

Quanjun Zhang, Chunrong Fang, Yang Xie, Yaxin Zhang, Shengcheng Yu and Zhenyu Chen are with the State Key Laboratory for Novel Software Technology, Nanjing University, China.
 E-mail: quanjun.zhang@smail.nju.edu.cn, fangchunrong@nju.edu.cn, serialxy@outlook.com, zhangyaxin032@gmail.com, yusc@smail.nju.edu.cn, zychen@nju.edu.cn

Weisong Sun is with the School of Computer Science and Engineering, Nanyang Technological University. E-mail: weisong.sun@ntu.edu.sg.

Yun Yang is with the Department of Computing Technologies, Swinburne University of Technology, Melbourne, VIC 3122, Australia. E-mail: yyang@swin.edu.au

(*e.g.*, open-source or closed-source [11]), mode architectures (*e.g.*, encoder-decoder or encoder-only [12]), model parameters (*e.g.*, CodeT5-60M and InCoder-6B [14]), types of bugs (*e.g.*, semantic bugs and security vulnerabilities [15]), and utilization paradigms (*e.g.*, fine-tuning [16], few-shot [17] and zero-shot [18]).

In this paper, we summarize existing work and provide a retrospection of the LLM-based community field after years of rapid development. Community researchers can have a thorough understanding of the advantages and limitations of the existing LLM-based SE techniques. We discuss how LLMs are integrated into specific tasks in the typical workflow of SE research. Based on our analysis, we point out the current challenges and suggest possible future directions for LLM-based SE research. Overall, our work provides a comprehensive review of the current progress of the LLM-based SE community, enabling researchers to obtain an overview of this thriving field and make progress toward advanced practices.

**Contributions.** To sum up, the main contributions of this paper are as follows:

- *Survey Methodology.* We conduct a detailed analysis of 1009 relevant SE studies empowered with LLMs in terms of publication trends and distribution of venues until mytime.
- *LLM Perspective.* We summarize 62 representative LLMs of Code for the SE community according to different aspects, such as model architectures, pre-training objectives, downstream tasks, and open science.
- *SE Perspective.* We explore the typical application of leveraging the advance of recent LLMs to automate the SE research, involving 947 relevant studies for 112 code-related tasks across five SE phases, *i.e.*, software requirements and design, software development, software test-ing, software maintenance and software management.
- *Integration Perspective.* We discuss some crucial aspects when LLMs are integrated into the SE field, such as evaluation, benchmarking, security and reliability, and domain tuning.
- Outlook and challenges. We pinpoint open research challenges and provide several practical guidelines on applying LLMs for future SE studies.

Comparison with Existing Surveys. In 2022, Watson et al. [19], Wang et al. [20] and Yang et al. [3] present a systematic literature review of research at the intersection of SE and ML&DL. Such surveys mainly concentrate on the application of ML or DL techniques in SE rather than more powerful and rapidly emerging LLMs. Besides, Niu et al. [21] and Zan et al. [22] present a survey to summarize 20 and 27 LLMs for natural-language-to-code (NL4Code) tasks. Such surveys are limited to a narrow research scope, *i.e.*, NL2Code, thus ignoring the more complex and challenging SE domain. Thus, our work focuses on the foundations of recently emerged LLMs within the crucial SE research, particularly covering 112 specific tasks across five crucial SE phases, *i.e.*, software requirement & design, development, testing, maintenance and management phases, as well as corresponding integration studies.

In addition to the aforementioned published papers, we notice there exist some pre-print works that explore the integration of LLMs with SE. While these unpublished papers are concurrent with our work, there remain some fundamental differences. Wang et al. [4] provide a review of LLMs in software testing, while our work targets the whole SE scope rather than a single SE phase. Fan *et al.* [23] discuss the achievements and challenges of LLMs in SE, and Hou et al. [24] conduct a systematic literature review on LLM4SE. Despite the close relevance of these two works to this paper, the key distinction lies in our three-fold focus on LLMs (*i.e.*, Section 3), SE (*i.e.*, Section 4), and the integration of both (*i.e.*, Section 5), Unlike the first work only taking a bird'seye view of the LLM-based SE achievements or the second work involving complicated aspects, e.g., data processing and metrics. We also release the first public repository to track the latest progress through crowd-sourcing, and we believe it will contribute to the ongoing development of the community. Lastly, our survey summarizes the existing studies until August 2024.

**Paper Organization.** The remainder of this paper is organized as follows. Section 2 provides a detailed exposition of three research questions and the methodology employed for conducting the survey. Sections 3 summarize existing LLMs of source code. Section 4 illustrates existing SE studies empowered with LLMs. Section 5 summarizes the crucial aspects during the integration of LLMs into SE. Section 6 highlights the challenges and promising opportunities for future research. Section 7 draws the conclusions.

**Availability.** All artifacts of this study are available in the following public repository. The living repository continuously updates the latest research on LLMs, LLM4SE, and related studies.

https://github.com/iSEngLab/AwesomeLLM4SE

### 2 SURVEY METHODOLOGY

#### 2.1 Research Questions

To provide a comprehensive overview of LLMs and the current achievements in SE, our work aims to address the following research questions (RQs):

- **RQ1 (LLM Perspective):** What LLMs are designed to support SE tasks?
  - RQ1.1: What LLMs have been released?
  - RQ1.2: What pre-training tasks have been used to train LLMs?
  - RQ1.3: What downstream tasks are LLMs spread to?
  - RQ1.4: How are LLMs open-sourced to support the open science community?
- **RQ2 (SE Perspective):** What SE tasks are facilitated by LLMs?
- **RQ3 (Integration Perspective):** What are the key factors during the integration of LLMs into SE?

To answer RQ1, we summarize LLMs in the SE literature from four aspects: LLM categories in Section 3.1, pretraining tasks in Section 3.2, downstream tasks in Section 3.3, and open-science in Section 3.4. To answer RQ2, we investigate SE tasks that have been facilitated by LLMs from five aspects: software requirements & design in Section 4.1, software development in Section 4.2, software testing in Section 4.3, software maintenance in Section 4.4 and software management in Section 4.5. To answer RQ3,



Fig. 1: Number of collected papers over years

we analyze challenges and achievements during the integration of LLMs into SE from four aspects: *i.e.*, evaluation and benchmarking in Section 5.1, security and reliability in Section 5.2, domain tuning in Section 5.3, compressing and distillation in Section 5.4.

#### 2.2 Search Strategy

Following existing DL for SE surveys [20], [3], [19], we divide the search keywords used for searching papers into two groups: (1) a SE-related group containing some commonly used keywords related to SE research; and (2) an LLM-related group containing some keywords related to LLM research. Besides, considering a significant amount of relevant papers from SE, AI, and NLP communities, following Zhang et al. [25], we attempt to identify some preliminary search keywords from three sources: (1) existing LLM surveys [22] to derive LLM-related keywords; (2) existing SE surveys [20], [19] to derive SE-related keywords; (3) a limited number of LLM-based SE research papers manually collected from top-tier conferences and journals beforehand to refine LLM-related and SE-related keywords. The search strategy can capture the most relevant studies from existing surveys while achieving better efficiency than a purely manual search. Finally, the complete set of search keywords is as follows.

- SE-related Keywords: Software Engineering, SE, Software Requirements, Software Design, Software Development, Software Testing, Software Maintenance, Code generation, Code Search, Code Completion, Code Summarization, Fault Detection, Fault Localization, Vulnerability Prediction, Testing Minimization, Test Generation, Fuzzing, GUI testing, NLP testing, Program Repair, Code Review, Vulnerability Repair, Patch Correctness.
- *LLM-related Keywords:* LLM, Large Language Model, Language Model, LM, PLM, Pre-trained model, Pretraining, Natural Language Processing, NLP, Machine Learning, ML, Deep Learning, DL, Artificial Intelligence, AI, Transformer, BERT, Codex, GPT, T5, Chat-GPT.

Our survey focuses on LLMs in the field of SE, encompassing existing LLMs and their applications in SE workflow. Thus, we classify papers that need to be summarized into two categories. For LLMs research, we search for papers whose titles contain the second keyword set. For LLM-based SE research, a paper is considered relevant only if it contains both sets of keywords. Then we conduct an automated search on three widely used databases until August 2024, *i.e.*, Google Scholar repository, ACM Digital Library, and IEEE Explorer Digital Library. Finally, we retrieve a total of 32,560 papers from three databases by automated keyword searching.

#### 2.3 Study Selection

Once the potentially relevant studies based on our search strategy are collected, we conduct a three-stage paper filtering to further determine which papers are relevant to this survey. First, we attempt to filter out the papers before 2017, considering that the Transformer architecture [26] is proposed in 2017, which is the foundation of LLMs. Second, we automatically filter out any paper less than 7 pages and duplicated papers. Third, we inspect the remaining papers manually to decide whether they are relevant to the LLM-based SE field according to some quality assessment criteria. The manual inspection is conducted independently by two authors, and any paper with different decisions will be handed over to a third author to make the final decision. As a result, we collect 59 papers related to the code LLM research and 912 papers related to the LLM-based SE research.

To mitigate potential omissions in our automated search and to ensure a thorough collection of papers, we further employed a snowballing search strategy [19]. Snowballing involves meticulously reviewing the reference lists and citations of each paper to uncover additional relevant studies that our initial search may have missed. In particular, we look at every reference within the collected papers and determine if any of those references are relevant to our study. Through this rigorous manual analysis, we succeed in additionally identifying three papers related to LLMs and

Acronym	Venues	Туре	# Publications
arXiv	N.A.	N.A.	382
ICSE	International Conference on Software Engineering	С	95
FSE	International Conference on the Foundations of Software Engineering	С	51
ACL	Meeting of the Association for Computational Linguistics	С	31
ASE	International Conference on Automated Software Engineering	С	30
ISSTA	International Symposium on Software Testing and Analysis	С	28
TSE	Transactions on Software Engineering	J	26
ICLR	International Conference on Learning Representations	C	20
TOSEM	Transactions on Software Engineering Methodology	С	20
SANER	International Conference on Software Analysis, Evolution, and Reengineering	С	17
EMNLP	Empirical Methods in Natural Language Processing	С	16
ICML	International Conference on Machine Learning	С	15
ICSME	International Conference on Software Maintenance and Evolution	С	15
MSR	Mining Software Repositories	С	15
JSS	Journal of Systems and Software	J	12
NeurIPS	Neural Information Processing Systems	C	12
ICPC	International Collegiate Programming Contest	С	11
AAAI	Association for the advance of Artificial Intelligence	С	10
COMPSAC	International Computer Software and Applications Conference	С	9
USENIX	USENIX Security Symposium	С	9
ICST	International Conference on Software Testing	С	8
Internetware	Asia-Pacific Symposium on Internetware	С	8
ISSRE	International Symposium on Software Reliability Engineering	С	8
IST	Information and Software Technology	J	8
NAACL	North American Association of computational linguistics	C	8
APSEC	Asia-Pacific Software Engineering Conference	С	7
AUSE	Automated software engineering	J	6
ESEM	International Symposium on Empirical Software Engineering and Measurement	Ċ	6
EASE	International Conference on Evaluation and Assessment in Software Engineering	С	5
EMSE	Empirical Software Engineering	J	5

36 papers related to LLM-based SE, thereby enriching our survey with a diverse range of insights.

#### 2.4 Trend Observation

We finally obtain 1009 relevant research papers after automated searching and manual inspection. Figure 1 shows the number of collected papers from 2020 to 2024, It can be observed that studies on proposing LLMs and their applications in SE have rapidly increased since 2020, indicating the growing recognition among researchers of LLMs as a viable and promising approach to automating SE tasks. One possible reason is that DL technologies have already shown promising performance in various SE tasks over the past several years [19]. As a derivative of DL, LLMs bring more powerful code understanding capabilities with larger model sizes and training datasets, demonstrating the potential of being a brand-new way to address SE problems. The second reason is the recent flourishing of the open-source community, which provides millions or even hundreds of millions of open-source code snippets, laying the foundation for training such LLMs.

Table 1 further shows the number of collected papers across different venues. The first two columns list the venue and its acronym, the third column indicates whether it is a conference or journal, and the final column shows the number of publications. We only present the top-30 venues with the highest number of publications due to page limitations. First, we find that these papers span multiple research fields, including SE, NLP, AI, and Security, which indicates the wide range of attention this direction has received. Second, unlike previous work [27], [28], it can be found that a significant number of papers (382/1009) have not been peer-reviewed. The reason behind this phenomenon lies in the rapid development in this field, especially after the release of the ChatGPT model at the end of 2022, which has stimulated a considerable amount of research in SE. Third, the top five venues are top-tier conferences (ICSE, FSE, ACL, ASE and ISSTA), and 25 venues among the top-30 ones are conferences, indicating a current inclination towards conferences in this field due to the timeliness of conference proceedings.

## 3 RQ1: LLM PERSPECTIVE

In this section, we summarize existing representative LLMs of Code in Section 3.1, pre-training tasks in Section 3.2, finetuning tasks in Section 3.3, and discuss the open science issue in Section 3.4. The detailed taxonomy is presented in Figure 2, including the three sub-RQs and their corresponding categorizations.

## 3.1 RQ1.1: What LLMs have been released to support SE?

Typically, existing LLMs can be classified into three types according to the model architecture, *i.e.*, encoder-only, decoder-only, and encoder-decoder models. Table 2 presents the summary and comparison of these representative



5



Fig. 2: Taxonomy of RQ1

LLMs<sup>1</sup>. The columns summarize the year of release, model name, the publisher or the conference where the model is introduced, the architecture types, and the initialization method or the base model used for pre-training.

From Table 2, it can be found that these LLMs are usually derived from foundational architectures in the NLP community and trained with some code-aware objectives. A considerable number of LLMs (*e.g.*, CodeBERT and CodeT5) are introduced by leading companies (*e.g.*, Microsoft and Google). The possible reason is that the resources to train these highly parametric models and to collect vast datasets far exceed the capabilities of the academic community. Third, inspired by the success of foundational LLMs like ChatGPT, the size of model parameters continues to set new benchmarks, and decoder-only architectures are gaining increasing popularity. In the following, we summarize these LLMs according to their model architectures. More detailed information about these specific LLMs is included in Appendix A.

#### 3.1.1 Encoder-only LLMs

Encoder-only LLMs refer to a class of LLMs that utilize only the encoder stack of the Transformer architecture. Regarding architecture, encoder-only models use multiple layers of encoders and each encoder layer consists of a multi-head selfattention mechanism followed by feed-forward neural networks. Regarding training, encoder-only LLMs are typically pre-trained on a massive corpus using a masked language modeling (MLM) task, which is used to learn to predict the identity of masked words based on their context. Regarding usage, because encoder-only LLMs generate fixedsize representations for variable-length input text, they are particularly suited for tasks that require understanding the context or meaning of a piece of text without generating new text, such as code search and vulnerability detection.

Among various encoder-only LLMs, BERT [5] has been acknowledged as a foundational work in the NLP field and provides crucial guidance for the conception and development of follow-up code-related LLM works. For example, CuBERT [29] is the first adaption of BERT from NLP to the source code domain by replicating the training procedure of BERT on a Python code corpus. CodeBERT [8] is a bimodal variant of BERT that takes into account both natural language and programming language. GraphCodeBERT [30] is a structure-aware extension of CodeBERT that incorporates data flow graphs to capture the structural and semantic relationships within the source code.

#### 3.1.2 Encoder-decoder LLMs

Encoder-decoder LLMs refer to a class of LLMs that utilize both the encoder and decoder parts of the Transformer architecture, working in tandem to transform one sequence into another. In particular, the encoder takes the input sequence and compresses its information into a fixed-size hidden state, which can capture the essence or meaning of the input sequence, while the decoder takes the hidden state and produces the corresponding output sequence, step by step, often using attention mechanisms to refer back to parts of the input sequence as needed. Thus, this architecture is particularly suited for sequence-to-sequence tasks in NLP

<sup>1.</sup> We note that some general-purpose LLMs (not limited to source code) have been applied in the field of SE, such as PaLM, Qwen, LLaMA, and Gemini. However, such LLMs have already been extensively reviewed in NLP and AI communities, so they fall outside the scope of our work. For more details, please refer to the relevant works [84], [85].

TABLE 2: A Summar	y and Comp	oarison of	LLMs o	f Code.
-------------------	------------	------------	--------	---------

Year	Model	Publisher	Architecture	Size	Tokenizer	Init	Organization	Public
2020	CodeBERT	ICMI	Encoder-only	350M	N A	BERT	Google IISC	Ves
2020	CUBERT	EMNLP	Encoder only	125M	WordPiece	Scratch	HIT Migrosoft	Voc
2020	CRTC	ENINEI	Deceder only	266M	PDE	CPT 2	Microsoft	No
2020	GFI-C	FJE	Decoder-only	3001/1	DFE	GF I-2	Microsoft	INO
2020	PyM15	EMNLP	Encoder-Decoder	374M	BBPE	GP1-2	Microsoft	No
2021	CodeGPT	NeurIPS	Decoder-only	124M	BBPE	GPT-2	PKU, Microsoft	Yes
2021	CodeT5	EMNLP	Encoder-Decoder	60M,220M	BBPE	Scratch	Salesforce	Yes
2021	Codex	arXiv	Decoder-only	12M,25M,42M,85M, 300M.679M.2.5B.12B	BBPE	GPT-3	OpenAI	No
2021	GraphCodeBERT	ICLR	Encoder-only	125M	WordPiece	Scratch	Microsoft, SYSU	Yes
2021	PLBART	NAACL	Encoder-Decoder	140M,406M	SentencePiece	Scratch	UC	Yes
2021	T5-Learning	ICSE	Encoder-Decoder	60M	SentencePiece	Τ5	USI	Yes
2022	AlphaCode	Science	Encoder-Decoder	300M 3B 9B 41B	SentencePiece	Scratch	DeenMind	No
2022	BLOOM	NourIPS	Encoder Decoder	770M	BBDE	CodeT5	Salasforca	Voc
2022	CodePI	ACE	Encoder Decoder	22014	DDIE	CodeT5	LTowas	Vac
2022	COUEKL	ASE	Encoder-Decoder	220101	DDFE	Code15	Diexas	ies
2022	Codit15	ACL	Encoder-Decoder	560M	SentencePiece	Scratch	Baidu	Yes
2022	JuPy15	arXiv	Encoder-Decoder	300M	BBPE	PyM15	Microsoft	Yes
2022	PaLM-Coder	arXiv	Decoder-only	8B,62B,540B	SentencePiece	Scratch	Google	No
2022	PanGu-Coder	arXiv	Decoder-only	317M,2.6B	SentencePiece	Scratch	Huawei	No
2022	PolvCoder	ICLR	Decoder-only	41B.160M.400M	BPE	GPT-2	CMU	Yes
2022	PvCodeGPT	IICAI	Decoder-only	110M	BPE	GPT-Neo	Microsoft CAS	Yes
2022	SPT-Code	ICSE	Encoder-Decoder	262M	BPE	Scratch	Nanjing University	Voc
2022	UnivCoder	ACI	Encoder Decoder	125M	WordBiogo	Scratch	Microsoft EVEL	Vac
2022	UnixCoder	ACL	Encoder-Decoder	125M	wordPiece	Scratch	MICrosoft, 5150	res
2023	CC15	arXiv	Decoder-only	13B,7B,34B	SentencePiece	Llama2	Meta	Yes
2023	Code Llama	ICSE	Decoder-only	13B	BPE	GPT-NeoX	Ant Group	Yes
2023	CodeFuse	KDD	Decoder-only	13B	BBPE	GPT-2	Tsinghua, Zhipu.AI	Yes
2023	CodeGen	ICLR	Decoder-only	350M,2.7B,6.1B,16.1B	BPE	Scratch	Salesforce	Yes
2023	CodeGen2	ICLR	Decoder-only	16B.3.7B.7B	BPE	Scratch	Salesforce	Yes
2023	CodeShell	arXiv	Decoder-only	78	BPF	GPT-2	PKI	Yes
2023	CodeT5	EMNIP	Encoder Decoder	770M 2B 6B 16B	BBDE	CodeT5	Salasforsa	Voc
2023	EDNIE Cada		Dasa dan anlar	(7P 1 2P	DDIL	Coucis	CMU Mata UM	Van
2023	EKINE-Code	ICLR	Decoder-only	0.7 D,1.3 D	DDFE	Scratch	CMU, Meta, UW	res
2023	InCoder	ICLK	Decoder-only	70B	BBPE	Llama2	HKU	res
2023	PanGu-Coder2	ICML	Decoder-only	7B	BPE	CodeLlama,DeepSeekCoder	UIUC	Yes
2023	PPOCoder	ICLR	Decoder-only	16B	BBPE	StarCoder	Hugging Face	Yes
2023	RLTF	ICLR	Decoder-only	6B	BBPE	CodeGeeX2	Hugging Face	Yes
2023	SantaCoder	arXiv	Decoder-only	15B	SentencePiece	PanGu-Coder	Huawei	No
2023	SOBertBase	TMLR	Encoder-Decoder	770M 220M	BBPE	CodeT5	Virginia Tech	Yes
2023	StarCoder	TMLR	Encoder-Decoder	770M	N A	CodeT5	Tencent	Voc
2023	AlchamictCodor	ICLP	Deceder only	1 10	DDE	Coucis	Hugging Easo	Vac
2024	Actemist	TMD	Decoder-only	1.1D 15 5D	DFE	CDT 2		les
2024	AS1-15	IMLK	Decoder-only	15.5B	BBPE	GP1-2	Hugging Face	res
2024	AutoCoder	ICLR	Decoder-only	15B	BBPE	StarCoder CodeLlama Llama?	Microsoft, HKBU	Yes
2024	B-Coder	arXiv	Decoder-only	7B,6.7B	N.A.	DeepSeekCoder	Tongji University	Yes
2024	CodeGeeX	ICML	Encoder-Decoder	277M	BPE	T5	UC Berkeley, Meta	Yes
2024	CodeGemma	arXiv	Decoder-only	6.7B,33B	BPE	DeepSeekCoder	UCONN	Yes
2024	CodeQwen1.5	ICLR	Encoder-Decoder	770M	BBPE	T5	UIC	Yes
2024	CodeSage	arXiv	Decoder-only	2B.7B	BPE	Gemma	DeepMind	Yes
2024	CoLSBERT	arXiv	Decoder-only	7B	BPE	Owen1.5	Alibaba	Yes
2024	DeepSeek-Coder	ICLR	Encoder-only	130M 356M 1 3B	SentencePiece	Scratch	AWS ALL abs	Yes
2021	DeepSeek Coder V2	arVin	Encoder only	254M 757M 124M 1 5P	DDE	Scratch	IDEA	Vac
2024	DeepSeek-Coder-V2		Data dan anlar	1 20 ( 70 220	DIL	Caratala	DEA	Vee
2024	DolphCoder	arAiv	Decoder-only	1.30,0.70,330	DPE	Scratch	PKU	ies
2024	Grammar15	arXiv	Decoder-only	16B,236B	BPE	DeepSeek-V2	PKU	Yes
2024	Granite	ACL	Decoder-only	7B,13B	N.A.	CodeLlama	BUPT	Yes
2024	InverseCoder	arXiv	Decoder-only	3B,8B,20B,34B	BPE	Scratch	IBM	Yes
2024	Lemur	arXiv	Decoder-only	6.7B,7B	N.A.	CodeLlama,DeepSeekCoder	UCAS, CAS	Yes
2024	Magicoder	arXiv	Decoder-only	1.1B	BBPE	StarCoder	Infosys Limited	Yes
2024	NT-Iava	arXiv	Decoder-only	3B.7B.15B	BBPE	StarCoder	Hugging Face	Yes
2024	OctoCoder	ACI	Decoder-only	6 7B	N A	DeepSeekCoder	Fudan	Yes
2024	OctoCooX	FCE	Encoder Decoder	22014	BBDE	CodeT5	NILIDT	Vec
2024	Char Collogeen	1 JE	Dana d	1760	DDFE	Couers Couers		V
2024	StarCoder2	arxiv	Decoder-only	1/60	BPE	Scratch	Digocience workshop	res
2024	StepCoder	arXiv	Encoder-only	109M,762M	BPE	Scratch	CMU	No
2024	UniCoder	ACL	Decoder-only	6.7B,7B	BPE	DeepSeekCoder	BUAA	Yes
2024	WaveCoder	ACL	Decoder-only	15B,7B,6.7B,13B	BBPE	StarCoder,CodeLiama, DeepSeekCoder	Microsoft	Yes
2024	WizardCoder	ACI	Decoder-only	1 3B	BPF	DeepSeekCoder	LIILIC	Yes
2024	YFT	ICSE	Encoder Decoder	60M 220M	BBDE	CodeT5	PK11	Vec
2024	A1'1	ICOL	Encouer Decouer	00141,220141	DDIE	Couers	i KU	105

and SE, where the input and output sequences can be of different lengths and structures, such as code summarization and program repair.

Among existing encoder-decoder LLMs, T5 (Text-to-Text Transfer Transformer) is a significant development in the NLP field and serves as a catalyst for follow-up coderelated works. For example, similar to CuBERT [29] in the encoder-only LLM domain, PYMT5 [33] is the first attempt to apply T5 to source code by replicating the pre-training process of T5 on a code corpus. In parallel with PYMT5 [33], T5-learning [34] empirically investigate how T5 performs when pre-trained with CodeSearchNet and fine-tuned to support four code-related tasks. PLABRT [35] is pre-trained with the denoising objective and built on the BART architecture. CodeT5 [8] represents a well-known adaption of T5 from NLP to the source code domain by leveraging the code semantics from the developer-assigned identifiers. CoditT5 [39] is a variant of CodeT5 particularly trained to tackle code editing tasks, such as code review. Researchers also release some encoder-decoder LLM for specific scenarios, such as AlphaCode [40] is introduced by DeepMind to generate solutions for competitive programming problems and JuPyT5 [42] for Jupyter Notebook.

#### 3.1.3 Decoder-only LLMs

Decoder-only LLMs refer to a class of LLMs that utilize only the decoder portion of the Transformer architecture. Unlike encoder-decoder models, which map an input sequence to an output sequence, decoder-only models primarily focus on generating text based on a given context or prompt.

Category	Task
Code Sequence Modeling and Prediction	Causal Language Modeling (CLM) Masked Language Modeling (MLM) Masked Span Prediction (MSP) Masked Identifier Prediction (MIP) Replaced Token Detection (RTD) Modified Masked Sequence-to-Sequence (MASS) Span Denoising (SD)
Bidirectional Understanding and Generation between Code and Natural Language	Bimodal Dual Generation (BDG) The Method Name Generation (MNG)
Code Structure and Relationship Understanding	Identifier Tagging (IT) Edge Prediction (EP) Node Alignment (NA) Code-AST Prediction (CAP)
Cross-modal Representation Learning	Multi-modal Contrastive Learning (MCL) Cross-modal generation (CMG)

In particular, decoder-only models use multiple layers of decoders from the Transformer architecture. Each decoder layer consists of a multi-head self-attention mechanism followed by feed-forward neural networks. These models are designed to generate text autoregressively, meaning they produce one token at a time and use what has been generated so far as context for subsequent tokens.

Among existing decoder-only LLMs, GPT (Generative Pre-trained Transformer) and its subsequent versions (like GPT-2, GPT-3, and so on) are the most well-known examples of decoder-only LLMs. Early efforts focus on adapting the GPT series models for the code domain, leading to LLMs such as GPT-C [50], CodeGPT [51], PolyCoder [53], and PyCodeGPT [55]. Subsequent advancements have seen the introduction of various specialized LLMs tailored for code generation and understanding tasks with advanced training techniques and large-scale datasets. Examples include CodeGen [54], InCoder [14], SantaCoder [56], Star-Coder [57], CodeGeeX [61], and CodeGen2 [62]. Recently, with the development of general-purpose LLMs, several variants have been released specifically in handling coderelated tasks, such as CodeLlama [86], PaLM-Coder [60], PanGu-Coder [58], PanGu-Coder2 [59].

Answer to RQ1.1: Overall, existing LLMs are mainly developed along three directions, the encoder-decoder represented by Google's T5, the encoder-only represented by OpenAI's GPT. While different model architectures excel in their own areas, it is challenging to pinpoint a single best LLM for all tasks. For example, encoder-only models (like BERT) focus on representing input text and are typically not used for sequence generation tasks, while decoder-only models (like GPT) are primarily used for generating sequences of text without a separate encoding step.

## 3.2 RQ1.2: How are LLMs used in pre-training tasks?

In this section, we summarize some representative pretraining tasks utilized to train LLMs of Code in the literature. Table 3 categorizes pre-training tasks into four major classes, including code sequence modeling and prediction in Section 3.2.1, bidirectional understanding and generation in Section 3.2.2, code structure and relationship understanding in Section 3.2.3 and cross-modal representation learning in Section 3.2.4. Now, we list and summarize these pre-training tasks as follows.

#### 3.2.1 Code Sequence Modeling and Prediction

Such tasks involve predicting and completing code fragments, such as masked spans or identifiers, so as to enhance LLMS' ability to understand and fill in missing parts of code.

**Causal Language Modeling (CLM).** CLM<sup>2</sup> attempts to predict the next most probable token in a sequence based on the context provided by the previous tokens. Such a task has usually been utilized to train decoder-only LLMs (*e.g.*, Code-Gen and CodeGPT) to generate complete programs from the beginning to the end for supporting auto-regressive tasks, such as code completion. For a sequence  $x = (x_1, \ldots, x_n)$ with *n* tokens, the task is to predict the token  $x_i$  given previous tokens (xj : j < i). For example, CLM predicts x for the given piece of incomplete code int add(int x, int y) { return.

Masked Language Modeling (MLM). MLM attempts to predict the original masked word from an artificially masked input sequence and is utilized in encoder-only LLMs such as CodeBERT. Similar to the original BERT, 15% of the code tokens from the input sequence are masked out. As the prediction of masked tokens is made based on the bidirectional contextual tokens, LLMs need to take into account the tokens forward and backward from the masked token in the input sequence. MLM is instrumental in training the model to comprehend not merely isolated code tokens, but also the relationships between tokens within a piece of code.

Masked Span Prediction (MSP). MSP attempts to predict the masked code tokens in the input code snippet and is utilized in encoder-decoder LLMs such as CodeT5. As mentioned in CodeT5 [9], MSP randomly masks spans with arbitrary lengths and then predicts these masked spans combined with some sentinel tokens at the decoder. The

<sup>2.</sup> The training objective is called causal language modeling in LLMs such as CodeGen2, but also referred to as next token prediction in LLMs such as CodeGen, and unidirectional language modeling in LLMs such as UniXcoder.

input of LLMs is the original sequence, the mask sequence is processed by the noise function, and the output is the denoised sequence.

Masked Identifier Prediction (MIP). Instead of randomly masking spans like in MSP, MIP masks all identifiers in the code snippet, using a unique sentinel token for each different mask. Inspired by the insight that changing identifier names does not impact code semantics, LLMs are tasked to predict the original identifiers from the masked input in an auto-regressive manner. MIP is a more challenging task as it requires the model to comprehend the code semantics based on obfuscated code and link the occurrences of the same identifiers together.

Replaced Token Detection (RTD). Originally proposed by Clark et al. [87], RTD attempts to predict whether a word is the original word or not, and is utilized in LLMs such as CodeBERT. RTD replaces the original word at the location of the mask with an alternative text, and perform a binary classification problem by training a discriminator to determine if a word is the original one. The discriminator is trained as a binary classifier to distinguish between original and generated tokens. The process involves sampling alternative tokens  $\hat{w}_i$  from  $p_{Gw}(w_i|w_{masked})$  for positions *i* in  $m_w$ , and sampling alternative tokens  $\hat{c}_i$  from  $p_{Gc}(c_i|c_{masked})$ for positions *i* in  $m_c$ . Then, the corrupted input  $x_{corrupt}$  is formed by replacing the masked words in w and c with their corresponding alternatives. The RTD objective aims to improve the efficiency of training by replacing masked tokens with plausible alternatives, enabling the model to benefit from both bimodal and unimodal data during the learning process.

**Modified Masked Sequence-to-Sequence (MASS).** MASS attempts to reconstruct a sentence fragment by predicting the masked tokens in the encoder-decoder model architectures and is utilized in LLMs such as SPT-Code. Given a code snippet C, the modified version  $C_{origin}^{u:v}$  is obtained by masking the fragment from position u to v. The model is pre-trained using this modified version to predict the fragment of C from u to v As a result, the model learns to predict masked parts of code sequences, enhancing its ability to understand and generate complex code structures accurately.

**Span Denoising (SD)**. SD involves randomly masking a span of tokens in the input and then training the model to reconstruct the original tokens, and is utilized in LLMs such as CodeT5+. In the SD task, 15% of the tokens in the encoder inputs are randomly replaced with indexed sentinel tokens, and the decoder is required to recover these masked tokens by generating a combination of spans. SD helps in learning deeper contextual representations of code snippets, enhancing LLMs' understanding of language structure and semantics. In CodeT5+, spans are sampled for masking, where the span lengths are determined by a uniform distribution with a mean of 3, so as to avoid masking partial words and enhance the model's understanding of whole words in the code.

## 3.2.2 Bidirectional Understanding and Generation between Code and Natural Language

Such tasks involve the conversion and understanding between source code and natural language, including generating method names.

**Bimodal Dual Generation (BDG).** BDG attempts to perform bidirectional translation between PL and NL and is utilized in LLMs such as CodeT5. Specifically, the NL->PL generation and PL->NL generation are treated as dual tasks, and LLMs are optimized simultaneously on both tasks. For each NL->PL bimodal data point, two training instances are created with reverse directions, and language identifiers (*e.g.*, <java> and <en> for Java PL and English NL, respectively) are included. The main objective of BDG is to enhance the alignment between the NL and PL, so as to generate syntactically correct NL descriptions for code snippets and code snippets for NL queries in downstream tasks.

Method Name Generation (MNG). MNG attempts to leverage method names to enhance LLMs' understanding of code intent and functionality, and has been utilized in LLMs such as SPT-Code. In the MNG task, the model takes the input representation, denoted as Input = C, [SEP], A, [SEP], N, where C is the code snippet, A is the corresponding AST sequence, and N is a natural language.

#### 3.2.3 Code Structure and Relationship Understanding

Such tasks usually involve understanding the structure and relationships within source code, including the arrangement of code elements and their connections.

**Identifier Tagging (IT).** IT attempts to make LLMs learn whether a code token is an identifier or not and is utilized in LLMs such as CodeT5 [9], which is inspired by the syntax highlighting in some coding tools. IT can help LLMs to learn the code syntax and the data flow structures of source code.

Edge Prediction (EP). EP attempts to learn representations from data flow in the context of code understanding and is utilized in LLMs such as GraphCodeBERT [30]. The primary motivation behind this task is to encourage the model to learn structure-aware representations that capture the relationships of "where-the-value-comes-from" in the code, thus enhancing its ability to comprehend code. In this pre-training task, a graph representing the data flow is constructed, where nodes represent variables or data elements, and edges represent the flow of data between these nodes. The objective is to predict the edges that are masked (hidden) in the graph. To do this, approximately 20% of the nodes in the data flow graph are randomly sampled, and the direct edges connecting these sampled nodes are masked by adding an infinitely negative value in the mask matrix.

Node Alignment (NA). Similar to EP, NA attempts to align representations between source code and data flow, and is utilized in LLMs such as GraphCodeBERT [30]. This alignment helps the model better understand the relationships between code tokens and nodes in the data flow, leading to improved comprehension of code semantics. In the NA pre-training task, a graph is constructed representing the data flow, and nodes in this graph represent variables or data elements. Additionally, code tokens in the source code are considered as another set of nodes. The objective is to predict the edges between code tokens and nodes, representing the alignment of variables in the code with their data flow counterparts. **Code-AST Prediction (CAP).** Inspired by the NSP task, CAP attempts to incorporate structural information of source code into the pre-training input and is utilized in LLMs such as SPT-Code [37]. The input of CAP includes code and its corresponding abstract syntax tree (AST) representation. The CAP task is formulated as a binarized task that can be easily generated from any given code. In constructing the input representation, the format used is as [Input = C, [SEP], A, [SEP], N], where C represents the code snippet, A represents the corresponding AST sequence, and N is a natural language description.

## 3.2.4 Cross-modal Representation Learning

Such tasks involve understanding source code and other modalities (such as comments) together, enhancing the model's capabilities in understanding and representing code.

Multi-modal Contrastive Learning (MCL). MCL attempts to learn semantic embedding of code fragments by distinguishing between positive and negative samples, and has been utilized by LLMs such as UniXcoder [36]. The positive sample refers to the same input but uses a different hidden dropout mask, while the negative sample refers to other representations in the batch. In UniXcoder [36], MCL encodes the mapped AST sequence and then applies an average pooling layer on the hidden state of the source input to obtain semantic embedding.

**Cross-modal Generation (CMG).** CMG attempts to generate comments for code segments to aid LLMs in understanding the code semantics. The generation of the comment is conditioned on the code, integrating semantic information into the hidden states of code. Besides, to expose LLMs to diverse contexts, a strategy is employed where the source and target inputs are randomly swapped with a 50% probability.

Answer to RQ1.2: Overall, the recent trends of pretraining tasks for Code LLMs reflect a significant shift from early NLP-derived objectives towards more codeaware objectives. Initially, LLMs are pre-trained with language modeling objectives from NLP tasks, including CLM for decoder-only LLMs (*e.g.*, CodeGPT), MLM for encoder-only LLMs (*e.g.*, CodeBERT), and MSP for encoder-decoder LLMs (*e.g.*, CodeT5). The follow-up works evolve to consider code variables and structural features specifically, as well as cross-modal learning for source code and natural language. This progression signifies a continuous advancement towards LLMs that not only process code as a sequence of tokens but deeply understand its semantic and functional aspects, bridging the gap between source code and natural language.

#### 3.3 RQ1.3: How are LLMs used in downstream tasks?

Once LLMs are trained on a vast corpus, it is critical to evaluate the effectiveness and applicability of LLMs on downstream tasks. Fine-tuning is the primary method for transferring the knowledge acquired during pre-training to downstream tasks, requiring LLMs to demonstrate code understanding, reasoning, and generation capabilities. A downstream task can be categorized by the task type (*i.e.*, code understanding and code generation) or data type (*i.e.*, code-code, code-text, text-code, and code-labels). We summarize 15 representative downstream tasks that are evaluated by existing LLMs in their original papers according to a well-maintained repository<sup>3</sup>, detailed as follows.

Code-Code. Code-code tasks involve the process of transforming one code snippet into another. For example, code translation attempts to convert code from one programming language into another while preserving its functionality. This task has been adopted as a downstream task in LLMs like CodeT5 [9], CodeBERT [8], and CodeT5 [9]. Code refinement (also known as program repair) attempts to refine existing code that might contain errors, and has been explored in LLMs like CodeT5 [9], GraphCodeBERT [30] and SPT-Code [37]. Cloze test aims to predict a missing token in a code snippet and has been adopted in LLMs like CodeGPT [61]. Mutant generation attempts to generate mutants by introducing small artificial faults, such as replacing the + operator with -, and has been adopted in LLMs like T5-learning [34]. Assert generation generates assert statements to verify the correctness of programs and validate certain assumptions, and has been adopted in LLMs, like T5-learning [34].

**Text-Code**. Text-code tasks involve the process of transforme human language descriptions into code snippets. For example, Code generation attempts to directly produce code snippets based on natural language descriptions, such as docstrings. It has been widely adopted as a downstream task in LLMs, including PyMT5 [33], CodeT5 [9], Codex [52]. Code search refers to the retrieval of relevant code samples from a codebase that matches a given natural language query, and haven been adopted in LLMs like CodeT5+ [41], CodeGPT [51], UnixCoder [36] and SPT-Code [37].

**Code-Text**. Code-text tasks involve the process of transforme code snippets into human language descriptions. For example, code summarization is the task of automatically generating a concise and accurate natural language description, or docstring, that encapsulates the actions and purpose of a given source code snippet. It has been explored in various LLMs, including CodeT5 [9], GraphCodeBERT [30], PLBART [35], CodeGPT [51], UnixCoder [36], SPT-Code [37] and ERNIE-Code [43].

**Code-Label**. Code-label tasks involve the process of performing classifications of code snippets. For example, clone detection identifies whether two code snippets are functionally or semantically similar based on similarity analysis and has been adopted in LLMs like CodeBERT [8], CodeT5 [9] and CodeT5+ [41]. Defect detection predicts whether a piece of source code contains bugs that could potentially make software systems vulnerable to attacks and has been adopted in LLMs like CodeGT [9], PLBART [35], and CodeGPT [51].

**Answer to RQ1.3:** Overall, as the direct applications of LLMs, these downstream tasks can be categorized into four classes according to input-output types, *i.e.*, codecode, code-test, test-code and code-labels, or into two classes according to task types, *i.e.*, code understanding and code generation. We observe some trends in

3. https://microsoft.github.io/CodeXGLUE/

a majority of existing downstream tasks where LLMs can be directly applied. First, these tasks involve only code snippets or the corresponding natural language comments. Second, these tasks are usually evaluated automatically using well-designed metrics (e.g., BLUE for generation tasks and Accuracy for classification tasks), thus supporting the large-scale evaluation benchmarks. Third, these tasks can effectively reduce the programming efforts of developers and can be integrated into modern IDEs as plug-ins to aid programming. Finally, these tasks have received attention and have been investigated in both the fields of SE and artificial intelligence. LLMs have shown preliminarily promising results on these tasks, importantly indicating their potential in a wider and more in-depth range of SE tasks, detailed in Section 4.

## 3.4 RQ1.4: How are LLMs open-sourced to support the open science community?

Very recently, the literature has seen a surge in the application of LLMs for a variety of SE problems. LLM brings a fresh perspective on the challenges associated with coderelated tasks, shifting the focus from traditional learningbased and rule-based approaches to a new pre-trainingand-fine-tuning paradigm. However, this shift also presents unique reproducibility challenges, distinct from those in traditional studies. For example, training complex LLMs can require substantial computational resources, often exceeding what academic institutions and most businesses can provide. Besides, the need for extensive data collection and hyper-parameter tuning adds complexity and feasibility issues for replication. Given these challenges, there is a growing imperative to adhere to open science principles in the LLM-driven SE field. Open science encourages researchers to share their artifacts (e.g., datasets, trained models, scripts) with the broader research community, fostering reproducibility and free knowledge exchange. While numerous LLMs have been proposed for automating coderelated tasks with promising results, there is a need for more support to address the critical issue of open science. In particular, we investigate the extent to which LLMs make their artifacts publicly available and how they provide this information.

Among 62 investigated LLMs, 54 of them provide the corresponding open-source repositories, which are summarized in Table 4. For each LLM we collect, we check whether an accessible link for its model or data is provided in the main text or footnotes of the paper. We only present the studies that provide the link of publicly available data or tools due to limited space, listed in the first column. The second column lists which hosting site the available artifact is uploaded to for public access (e.g., GitHub). The third column lists whether the source code (e.g., training scripts) is available in the artifacts. The fourth column lists whether the dataset (e.g., raw data and training data) is available in the artifacts. The fifth column lists whether the trained model is available in the artifacts, and the sixth column lists the corresponding site. We also list the accessible URL links in the last column. After carefully checking the collected papers, we find that 54 of 62 LLMs have made their artifacts

available to the public. Almost all studies upload their artifacts on Github, which is the most popular platform for hosting open-source code publicly. Similar to GitHub, nearly all checkpoints of LLMs are hosted on Hugging Face, with which developers can conveniently download these trained models and conduct training or inference on their own machines. Meanwhile, we find that several papers fail to provide the source code, dataset, or already trained models [41], perhaps due to commercial reasons.

Answer to RQ1.4: Overall, compared with traditional DL studies, the need for high-quality artifacts in LLMs is even more vital for replication and future research. While numerous LLms have been introduced for code-related tasks, there remains a significant gap in their adherence to open science principles. On one hand, abundant training time and expensive equipment (*e.g.*, GPUs) are required to train LLMs, making it much harder to reproduce existing works. On the other hand, some LLMs require complex environment settings (*e.g.*, the hyperparameters and the random seed) and high-quality datasets. Therefore, we hope that researchers can provide high-quality open-source code and detailed instructions for convenient reproduction.

## 4 RQ2: SE PERSPECTIVE

In this section, we summarize existing SE studies empowered with LLMs, which can be categorized into five crucial phases within the SE life cycle, including software requirements and design in Section 4.1, software development in Section 4.2, software testing in Section 4.3, software maintenance in Section 4.4, and software management in Section 4.5. Each SE phase contains several distinct coderelated tasks, such as fault localization and program repair in the software maintenance phase. Table 5 presents the taxonomy of this section, categorizing 947 LLM-based SE studies into 112 distinct SE tasks across five SE phases. More detailed information about all specific studies is included in Appendix B.

#### 4.1 Software Requirements & Design

Software requirements refer to specific descriptions of conditions or capabilities needed by users, systems, or system components, typically presented in document form. These requirements are categorized into functional and nonfunctional requirements. The purpose of software requirements is to ensure that the developed software can meet the expectations of users and relevant stakeholders, as well as the conditions and capabilities specified in contracts, standards, regulations, or other formal documents. Software design involves the process of defining the structure, components, functionalities, interfaces, and their relationships within a software system. During the software design phase, software engineers need to create detailed plans and design blueprints based on software requirements and specifications to ensure that the software system can meet the users' needs and expectations.

codeBERT         CitHub         Yes         Yes <thyes< th="">         Yes         Yes         <thy< th=""><th>Model</th><th>Hosting Site</th><th>CA</th><th>DA</th><th>MA</th><th>Model Site</th><th>URL only for Public</th></thy<></thyes<>	Model	Hosting Site	CA	DA	MA	Model Site	URL only for Public
CubERTGifflubYesYesYesCodeCode/CodeCode/Code/Code/Code/Code/Code/Code/Code/	CodeBERT	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/microsoft/CodeBERT
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	CuBERT	GitHub	Yes	Yes	Yes	Google Cloud	https://github.com/google-research/google-research
	PyMT5	GitHub	Yes	Yes	Yes	PyPi	https://github.com/devcartel/pymt5
CodeT5CitHubYesYesYesYesHugging Facehttps://github.com/microsoft/CodeT5CraphCodeBERTCitHubYesYesYesGoogle Drivehttps://github.com/microsoft/CodeEERTTSLearningCitHubYesYesYesGoogle Drivehttps://github.com/antonio-masthopado/T5-learning-ICSE_2021CodeL1CitHubYesYesYesGoogle Drivehttps://github.com/antonio-masthopado/T5-learning-ICSE_2021CodeL3CitHubYesYesYesHugging Facehttps://github.com/incosoft/DataScienceProblemsPyCodeC4CitHubNoNoNoNAhttps://github.com/incosoft/DataScienceProblemsPyCodeC4CitHubNoYesYesHugging Facehttps://github.com/incosoft/DodeEERT/tree/master/LinXcoderCodeLumaCitHubNoYesYesHugging Facehttps://github.com/incosoft/CodeEERT/tree/master/LinXcoderCodeCanCitHubNoYesYesHugging Facehttps://github.com/incosoft/CodeEERT/tree/master/LinXcoderCodeCanCitHubNoYesYesHugging Facehttps://github.com/incosoft/CodeEERTCodeCanCitHubNoYesYesHugging Facehttps://github.com/incosoft/CodeEERTCodeCanCitHubNoNoYesYesHugging Facehttps://github.com/incosoft/CodeEERTCodeCanCitHubNoNoNoNoNoNoNoNoCodeCanCitHubNoNo <t< td=""><td>CodeGPT</td><td>GitHub</td><td>No</td><td>No</td><td>Yes</td><td>Hugging Face</td><td>https://github.com/microsoft/CodeXGLUE</td></t<>	CodeGPT	GitHub	No	No	Yes	Hugging Face	https://github.com/microsoft/CodeXGLUE
CraphCodeBERT       CitHub       Yes       Yes       Yes       Yes       Orogle Drive       https://github.com/wasiahmad/PLBART         T5-Learning       CitHub       Yes       Yes       Google Drive       https://github.com/salesfore/CodeBL         CoddKL       CitHub       Yes       Yes       Google Cloub       https://github.com/salesfore/CodeKL         CoditT5       CitHub       No       No       No       No       No         PcCodeCPT       CitHub       No       Yes       Hugging Face       https://github.com/microsoft/CodeBERT/mer/master/UniXcoder         CitHub       No       Yes       Yes       Hugging Face       https://github.com/microsoft/CodeBERT/mer/master/UniXcoder         CitHub       No       Yes       Yes       Hugging Face       https://github.com/microsoft/CodeBERT/mer/master/UniXcoder         CodeCen       CitHub       No       Yes       Yes       Hugging Face       https://github.com/salesforec/CodeGen         CodeCen       CitHub       No       Yes       Yes       Hugging Face       https://github.com/salesforec/CodeGen         CodeCen       CitHub       No       Yes       Yes       Hugging Face       https://github.com/salesforec/CodeSen         CodeCen       CitHub       Yes       Y	CodeT5	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/salesforce/CodeT5
PLEARTCitHubYesYesYesGoogle Drivehttps://jthub.com/antonic-masthmad/PLEARTCodeRLCitHubYesYesYesGoogle Drivehttps://jthub.com/antonic-masthmad/PLEARTCodeRLCitHubYesYesYesGoogle Drivehttps://jthub.com/antonic-masthmad/PLEARTJulyT5CitHubNoNoNoNAhttps://jthub.com/incosoft/DataScienceProblemsPhyCoderCitHubNoYesYesHugging Facehttps://jthub.com/incosoft/PycodegptPyCodeCiTCitHubYesYesYesHugging Facehttps://jthub.com/incosoft/PycodegptCodeFuseCitHubNoYesYesHugging Facehttps://jthub.com/incosoft/OcdeEERT/tree/master/LoiXoderCodeFuseCitHubNoYesYesHugging Facehttps://jthub.com/salesfore/CodeCan2CodeCoraCitHubNoYesYesHugging Facehttps://jthub.com/salesfore/CodeCan2CodeCoraCitHubNoYesYesHugging Facehttps://jthub.com/salesfore/CodeCan2InCoderCitHubNoYesYesHugging Facehttps://jthub.com/salesfore/CodeCan2PPCOderCitHubYesYesYesHugging Facehttps://jthub.com/salesfore/CodeCan2PPCOderCitHubNoNoNoNoAhttps://jthub.com/salesfore/CodeCan2CodeCan2CitHubNoNoNoNoAhttps://jthub.com/salesfore/CodeCan2PPCOderCi	GraphCodeBERT	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/microsoft/CodeBERT
T5-LearningCitHubYesYesYesGoogle Cloudhttps://jthub.com/salestore/CodeRLCodelLCitHubYesYesYesGoogle Cloudhttps://jthub.com/salestore/CodeRLCodiT5CitHubNoNoNoNoNoPolyCodeCitHubNoYesYesHugging FacePolyCodeCitHubNoYesYesHugging FacePryCodeCitHubNoYesYesHugging FacePryCodeCitHubYesYesYesNoCodeCaeCitHubYesYesHugging FaceCodeCaeCitHubNoYesYesHugging FaceCodeCaeCitHubNoYesYesHugging FaceCodeCaeCitHubNoYesYesHugging FaceCodeCaeCitHubNoYesYesHugging FacePhOCoderCitHubNoYesYesHugging FacePhOCoderCitHubNoNoNoNaFLTFCitHubNoNoNoNaFLTFCitHubNoNoNoNaFLTFCitHubNoNoNoNaFLTFCitHubNoNoNoNaFLTFCitHubNoNoNoNaCodeCaeCitHubNoNoNoNaAlchenisCoderCitHubNoNoNoCodeCaeCitHubNoNoNo<	PLBART	GitHub	Yes	Yes	Yes	Google Drive	https://github.com/wasiahmad/PLBART
CodeRLGifHubYesYesYesYesYesYesCodifTSGifHubNoNoNoNAhttps://jtitub.com/engineeringsoftwarc/codift5JuPyT5GifHubNoNoNAhttps://jtitub.com/microsoft/DatsScienceProblemsPolyCoderGifHubNoYesYesHugging Facehttps://jtitub.com/Wielendoom/Code-LMsPyCodeGPTGifHubNoYesYesYesHugging Facehttps://jtitub.com/microsoft/DatsScienceProblemsPyCodeGPTGifHubNoYesYesHugging Facehttps://jtitub.com/microsoft/CodeBRT/Tree/master/UniXcoderCodeFuseGifHubNoYesYesHugging Facehttps://jtitub.com/aslesforce/CodeCenCodeGranGifHubNoYesYesHugging Facehttps://jtitub.com/aslesforce/CodeCenCodeGranGifHubNoYesYesHugging Facehttps://jtitub.com/aslesforce/CodeCenCodeGranGifHubNoYesYesHugging Facehttps://jtitub.com/aslesforce/CodeCenCodeCareGifHubYesYesYesHugging Facehttps://jtitub.com/aslesforce/CodeCenPOCoderGifHubYesYesYesHugging Facehttps://jtitub.com/iedu/abe/ade/pade/pade/starcoderHUTFGifHubYesYesYesHugging Facehttps://jtitub.com/iedu/abe/ade/pade/starcoderAlchemistCoderGifHubNoNoNoNAhttps://jtitub.com/iedu/abe/ade/pade/starcoderAlchem	T5-Learning	GitHub	Yes	Yes	Yes	Google Drive	https://github.com/antonio-mastropaolo/T5-learning-ICSE_2021
	CodeRL	GitHub	Yes	Yes	Yes	Google Cloud	https://github.com/salesforce/CodeRL
$      juPy75 \qquad \qquad \mbox{Figure 2} Gifflub No $	CoditT5	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/engineeringsoftware/coditt5
PolyCoded PT GitHub No Yes Yes Hugging Face https://github.com/Vitellendoom/Code-LMs SPT-Code GitHub Yes Yes Yes OneDrive Https://github.com/NougatCA/SPT-Code GitHub Yes Yes Yes OneDrive https://github.com/NougatCA/SPT-Code Code Lama GitHub Yes No Yes Hugging Face https://github.com/facebookresearch/codellama GitHub No Yes Yes Hugging Face https://github.com/salesforce/CodeGen GitHub No Yes Yes Hugging Face https://github.com/salesforce/CodeGen CodeTs+ GitHub No Yes Yes Yes Hugging Face https://github.com/salesforce/CodeGen CodeTs+ GitHub No Yes Yes Yes Hugging Face https://github.com/salesforce/CodeTs/Hee/main/CodeT5%2B Https://github.com/salesforce/CodeTs/Hee/main/CodeT5%2B Https://github.com/salesforce/CodeTs/Hee/main/CodeT5%2B AutoCoder GitHub No Yes Yes Yes Hugging Face https://github.com/salesforce/CodeCen2 AlebensicCoder GitHub No Yes Yes Yes Hugging Face https://github.com/salesforce/CodeTs/Hee/main/CodeT5%2B AutoCoder GitHub No No No No No No No No AlebensicCoder GitHub No No Yes Yes Hugging Face https://github.com/facede-project/starcoder AlebensicCoder GitHub No No Yes Yes Hugging Face https://github.com/bigcode-snatecoder AlebensicCoder GitHub No No Yes Nes Hugging Face https://github.com/bigcode-snatecoder AlebensicCoder GitHub No No Yes Nes Hugging Face https://github.com/facederDiscoder AlebensicCoder GitHub No No Yes Nes Hugging Face https://github.com/facederDiscoder AlebensicCoder GitHub No No Yes Nes Hugging Face https://github.com/faceOderDiscoder AlebensicCoder GitHub No No Yes Yes Hugging Face https://github.com/faceDoderDiscoder CodeSeg GitHub Yes Yes Yes Hugging Face https://github.com/faceDoderDiscoderDiscoder CodeSeg GitHub No No No Yes Nes Hugging Face https://github.com/faceDoderDiscoderDiscoder CodeSeg GitHub Yes Yes Yes Hugging Face https://github.com/fac	JuPyT5	GitHub	No	No	No	N.A.	https://github.com/microsoft/DataScienceProblems
PyCodeGPTGitHubNoYesYesYesHugging Facehttps://github.com/Norcosoft/QvcodegptSPT-CodeGitHubNoYesYesOveDirvehttps://github.com/Norcosoft/CodeBERT/tree/master/UniXcoderCodeLamaGitHubYesNoYesHugging Facehttps://github.com/facebookresearch/OcdelamaCodeFuseGitHubYesNoYesHugging Facehttps://github.com/facebookresearch/OcdeGenCodeGen2GitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeGenCodeGen2GitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeGen2CodeGradGitHubNoYesYesHugging Facehttps://github.com/radels/ala-code-reade-modelsPPOCoderGitHubNoYesYesHugging Facehttps://github.com/rade/ala-code-reade-modelsRLTFGitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeToStarCoderGitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeToAlchemistCoderGitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeToAlchemistCoderGitHubNoNoNoNoNoNoCodeGeexGitHubNoNoNoNoNoCodeGeexGitHubNoNoNoNoNoCodeGeexGitHubNoNoNoNoNo </td <td>PolyCoder</td> <td>GitHub</td> <td>No</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://github.com/VHellendoorn/Code-LMs</td>	PolyCoder	GitHub	No	Yes	Yes	Hugging Face	https://github.com/VHellendoorn/Code-LMs
SPT-Code       GitHub       Yes       Yes       Yes       Hugging Face       https://github.com/NougatCA/SPT-Code         CodeLlama       GitHub       Yes       No       Yes       Hugging Face       https://github.com/incresoft/CodeERT/tree/master/UniXcoder         CodeCa       GitHub       No       Yes       Yes       Hugging Face       https://github.com/adefuse-ai         CodeCa       GitHub       No       Yes       Yes       Hugging Face       https://github.com/adefuse-ai         CodeCa       GitHub       No       Yes       Yes       Hugging Face       https://github.com/salesforce/CodeGn2         CodeTo       GitHub       No       Yes       Yes       Hugging Face       https://github.com/salesforce/CodeGn2         RCoder       GitHub       Yes       Yes       Yes       Hugging Face       https://github.com/iedu/ada/code-research/PPOCoder         RLTF       GitHub       Yes       Yes       Yes       Hugging Face       https://github.com/jes/cotAlRLTF         StarCoder       GitHub       Yes       Yes       Hugging Face       https://github.com/jes/cotAlRLTF         AlchemistCoder       GitHub       Yes       Yes       Hugging Face       https://github.com/iedu/ada/code/santacoder         AlchemistCoder	PyĆodeGPT	GitHub	No	Yes	Yes	Hugging Face	https://github.com/microsoft/pycodegpt
UnixCoderCitHubNoYesYesHugging Facehttps://github.com/incrosoft/CodeBERT/tnee/master/UniXcoderCodeFuseCitHubYesNoYesHugging Facehttps://github.com/acebookresearch/codeIlamaCodeGen2CitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeGen2CodeF3+CitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeGen2CodeF5+CitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeF3/tree/main/CodeT5%2BFRNIE-CodeCitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeF3/tree/main/CodeT5%2BFRNIE-CodeCitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeF3/tree/main/CodeT5%2BSantaCoderHitugging Facehttps://github.com/salesforce/CodeFaceAch/PPOCoderhttps://github.com/salesforce/CodeFaceAch/POCoderStarCoderCitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeFaceAch/POCoderAlchemistCoderCitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeFaceAch/POCoderCodeGeeXCitHubNoNoYesHugging Facehttps://github.com/salesforce/CodeFaceAch/POCoderCodeGeeXCitHubNoNoNoNoHugging Facehttps://github.com/salesforce/CodeFaceAch/POCoderCodeGeeXCitHubNoNoNoNoNoNoCodeGeeXCitHub <td>SPT-Code</td> <td>GitHub</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td>OneDrive</td> <td>https://github.com/NougatCA/SPT-Code</td>	SPT-Code	GitHub	Yes	Yes	Yes	OneDrive	https://github.com/NougatCA/SPT-Code
Code LlamaCitHubYesNoYesHugging Facehttps://github.com/facebookresearch/codellamaCodeGenCitHubNoYesYesHugging Facehttps://github.com/alesforce/CodeGen2CodeGen2CitHubNoYesYesHugging Facehttps://github.com/alesforce/CodeGen2CodeT5+CitHubNoYesYesHugging Facehttps://github.com/alesforce/CodeGen2CodeT5+CitHubYesYesHugging Facehttps://github.com/alesforce/CodeGen2InCoderCitHubYesYesYesHugging Facehttps://github.com/alesforce/CodeFotdedE/POCoderCitHubYesYesYesHugging Facehttps://github.com/alesforce/CodeFotdedEPOCoderCitHubYesYesYesHugging Facehttps://github.com/alesforce/CodeFotarcoderAlchemistCoderCitHubYesYesHugging Facehttps://github.com/alesforce/CodeCoderAlchemistCoderCitHubNoNoNoNoNoAutoCoderCitHubNoNoNoNoCodeGeennaHugging Facehttps://github.com/alesforce/CodeCoderSitHubCodeGeennaHugging Facehttps://github.com/alesforce/CodeCoderCodeGeennaHugging Facehttps://github.com/alesforce/CodeGeenCodeGeennaHugging Facehttps://github.com/alesforce/CodeGeenCodeGeennaHugging Facehttps://github.com/alesforce/CodeGeenCodeGeendCitHubNoNoNo<	UnixCoder	GitHub	No	Yes	Yes	Hugging Face	https://github.com/microsoft/CodeBERT/tree/master/UniXcoder
CodeFuseGitHubYesNoYesHugging Facehttps://github.com/codefuse-aiCodeGen2GitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeGen2CodeGer2GitHubNoYesYesHugging Facehttps://github.com/salesforce/CodeT5/ree/main/CodeT5%2BERNIE-CodeGitHubYesYesYesHugging Facehttps://github.com/salesforce/CodeT5/ree/main/CodeT5%2BPPOCoderGitHubYesYesYesHugging Facehttps://github.com/radde-laddle/Paddle/NLP/AlchemistCoderHugging FaceHugsing Facehttps://github.com/Zyq-scut/RLTFSantaCoderGitHubNoNoNo.SantaCoderGitHubYesYesHugging FaceAlchemistCoderGitHubNoNoNo.AutoCoderGitHubNoNoYesAutoCoderGitHubNoNoYesCodeGearxGitHubNoNoYesCodeGearxGitHubNoNoYesCodeGearxGitHubNoNoYesCodeGearyGitHubYesYesYesCodeGearyGitHubNoNoYesCodeGearyGitHubNoNoYesCodeGearyGitHubNoNoYesCodeGearyGitHubNoNoYesCodeGearyGitHubNoNoYesCodeGearyGitHubYesYesYes <t< td=""><td>Code Llama</td><td>GitHub</td><td>Yes</td><td>No</td><td>Yes</td><td>Hugging Face</td><td>https://github.com/facebookresearch/codellama</td></t<>	Code Llama	GitHub	Yes	No	Yes	Hugging Face	https://github.com/facebookresearch/codellama
CodeGenGitHubNoYesYesHugging Facehttps://github.com/salesforec/CodeGenCodeGr2GitHubNoYesYesHugging Facehttps://github.com/salesforec/CodeGen2CodeT5+GitHubNoYesYesHugging Facehttps://github.com/salesforec/CodeT6/1/rrer/main/CodeT5%2BERNIE-CodeGitHubYesYesHugging Facehttps://github.com/reddP-lab-code-research/IPOCoderHTTGitHubYesYesHugging Facehttps://github.com/reddy-lab-code-research/IPOCoderStarCoderGitHubYesYesHugging Facehttps://github.com/isgode-project/starcoderStarCoderGitHubYesYesHugging Facehttps://github.com/ligcode-project/starcoderAlchemistCoderGitHubYesYesHugging Facehttps://github.com/lint2apple/AutoCoderAutoCoderGitHubNoNoYesHugging Facehttps://github.com/lint2apple/AutoCoderCodeGeeXGitHubNoNoYesHugging Facehttps://github.com/lamzon-scince/CodeSageCodeGeeXGitHubNoNoYesHugging Facehttps://github.com/lamzon-scince/CodeSageCodeGeeXGitHubNoYesYesHugging Facehttps://github.com/lamzon-scince/CodeSageCodeGeeXGitHubNoNoYesHugging Facehttps://github.com/lamzon-scince/CodeSageCodeSageGitHubNoNoNoNoHugging FaceCodeGeeXGitHubNo <td>CodeFuse</td> <td>GitHub</td> <td>Yes</td> <td>No</td> <td>Yes</td> <td>Hugging Face</td> <td>https://github.com/codefuse-ai</td>	CodeFuse	GitHub	Yes	No	Yes	Hugging Face	https://github.com/codefuse-ai
CodeCen2GitHubNoYesYesHugging Facehttps://github.com/salesfore/CodeCen2CodeTs+GitHubYesNoN.A.https://github.com/alesfore/CodeT5/tree/main/CodeT5%2BERNIE-CodeGitHubYesYesHugging Facehttps://github.com/alesfore/CodeT5/tree/main/CodeT5%2BPPOCoderGitHubYesYesYesHugging Facehttps://github.com/reddy-labe-code-research/PPOCoderRLTFGitHubYesYesYesHugging Facehttps://github.com/age.co/bigcode/santacoderSantaCoderGitHubYesYesYesHugging Facehttps://github.com/ligoade-project/starcoderAlchemistCoderGitHubYesYesYesHugging Facehttps://github.com/ligoade-project/starcoderAutoCoderGitHubNoNoYesYesHugging Facehttps://github.com/ligoade-project/starcoderCodeGeexAGitHubNoNoYesYesHugging Facehttps://github.com/logoade-project/starcoderCodeGeemaHugging FaceNoNoNoNoHugging Facehttps://github.com/logoade-project/starcoderCodeGeemaGitHubNoNoNoNoNoHugging Facehttps://github.com/logoade-project/starcoderCodeGeent1.5GitHubYesYesYesHugging Facehttps://github.com/logoade-project/starcoderCodeGeent3.5GitHubYesYesYesHugging Facehttps://github.com/logoade-project/starcoderCodeSage </td <td>CodeGen</td> <td>GitHub</td> <td>No</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://github.com/salesforce/CodeGen</td>	CodeGen	GitHub	No	Yes	Yes	Hugging Face	https://github.com/salesforce/CodeGen
CodeT5+GitHubNoYesYesHugging Facehttps://jeithub.com/salesfore/CodeT5/tree/main/CodeT5%2BERNIE-CodeGitHubNoYesYesHugging Facehttps://jeithub.com/raddle/Pa	CodeGen2	GitHub	No	Yes	Yes	Hugging Face	https://github.com/salesforce/CodeGen2
ERNIE-Code       GiHlub       Yes       No       No.       N.A.       https://github.com/PaddlePaddle/PaddleNIP/         InCoder       GiHlub       Yes       Yes       Yes       Hugging Face       https://github.com/reddy-lab-code-research/PPOCoder         RLTF       GiHlub       Yes       Yes       Yes       Hugging Face       https://github.com/Zyq-scut/RLTF         SantaCoder       GiHlub       No       No       No       No.       NA.         AlchemistCoder       GiHlub       Yes       Yes       Hugging Face       https://github.com/Zyq-scut/RLTF         AlchemistCoder       GiHlub       Yes       Yes       Yes       Hugging Face       https://github.com/Zyq-scut/RLTF         Autocoder       GiHlub       Yes       Yes       Yes       Hugging Face       https://github.com/Zyg-scut/RLTF         CodeGeexA       GiHlub       No       No       Yes       Hugging Face       https://github.com/Jon/Zag-poict/starcoder         CodeGeenna       Hugging Face       No       No       Yes       Hugging Face       https://github.com/Idue/GeeA         CodeSage       GiHlub       Yes       Yes       Yes       Hugging Face       https://github.com/deepseek-ai/DeepSeek-Coder-V2         DolphCoder       GiHlub <td>CodeT5+</td> <td>GitHub</td> <td>No</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://github.com/salesforce/CodeT5/tree/main/CodeT5%2B</td>	CodeT5+	GitHub	No	Yes	Yes	Hugging Face	https://github.com/salesforce/CodeT5/tree/main/CodeT5%2B
InCoderGifHubNoYesYesHugging Facehttps://github.com/redy-lab-code-resetch/PPOCoderPPOCoderGifHubYesYesN.A.https://github.com/Zyq-scut/RLFSantaCoderGifHubYesYesHugging Facehttps://github.com/Jzyq-scut/RLFSantaCoderGifHubYesYesHugging Facehttps://github.com/bigcode-project/StarcoderAlchemistCoderGifHubYesYesYesHugging FaceAsT-T5GifHubYesYesYesHugging FaceAutoCoderGifHubNoNoYesHugging FaceCodeGeeXGifHubNoNoYesHugging FaceCodeGeeXGifHubNoNoYesHugging FaceCodeGeeXGifHubNoNoYesHugging FaceCodeGeaXGifHubYesYesYesHugging FaceCodeSageGifHubYesYesYesHugging FaceCodeSageGifHubYesYesYesHugging FaceDeepSeek-CoderGifHubYesYesYesDeepSeek-CoderGifHubNoNoNoNoNoNoYesHugging FaceDiphCoderGifHubNoNoNoColSBERTGifHubNoNoNoColSBERTGifHubNoNoNoColSBERTGifHubNoNoNoColSBERTGifHubNoNoNo	ERNIE-Code	GitHub	Yes	No	No	N.A.	https://github.com/PaddlePaddle/PaddleNLP/
PPOCoderGitHubYesYesN.A.https://github.com/zvg-sut/RLTFSantaCoderHugging FaceNoYesYesHugging FaceSantaCoderGitHubNoNoNoN.A.https://github.com/zvg-sut/RLTFStarCoderGitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoderAlchemistCoderGitHubYesYesYesHugging Facehttps://github.com/local2anple/AutoCoderAutoCoderGitHubNoNoYesNoNohttps://github.com/local2anple/AutoCoderCodeGeexAGitHubNoNoYesNa.https://github.com/IHUDM/CodeGeeXCodeGeenmaHugging FaceNoNoNoYesCodeSageGitHubYesYesYesHugging faceCodeSageGitHubYesYesYesHugging FaceDeepSeek-Coder-V2GitHubNoNoNoNa.DolphCoderGitHubNoNoNoNa.CoLSBERTGitHubYesYesYesNa.DolphCoderGitHubNoNoNoNa.CoLSBERTGitHubYesYesYesNa.DolphCoderGitHubNoNoNoNa.CoLSBERTGitHubYesYesYesNa.GitHubNoYesYesYesNa.Hugging FaceHugging FaceNtps://github.com/kingbo/CCT5BLOOM <td>InCoder</td> <td>GitHub</td> <td>No</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://sites.google.com/view/incoder-code-models</td>	InCoder	GitHub	No	Yes	Yes	Hugging Face	https://sites.google.com/view/incoder-code-models
RLTFGitHubYesYesHugging Facehttps://github.com/Zyq-scut/RLTFSantaCoderGitHubNoNoNoNo.No.No.StarCoderGitHubYesYesHugging Facehttps://github.com/bigode-project/starcoderAlchemistCoderGitHubYesYesYesHugging Facehttps://github.com/polinyuan.st.t5AutoCoderGitHubNoNoYesHugging Facehttps://github.com/polinyuan.st.t5AutoCoderGitHubNoNoYesHugging Facehttps://github.com/polinyuan.st.t5CodeGeeXGitHubNoNoYesHugging Facehttps://github.com/QwenLM/CodeGeeXCodeGamaHugging FaceNoNoYesHugging Facehttps://github.com/Auxon/THUDM/CodeGeeXCodeSageGitHubYesYesYesHugging Facehttps://github.com/Auxon/Yeepseek-ai/DeepSeek-CoderCodESBERTGitHubYesYesYesHugging Facehttps://github.com/Auxon/Yeepseek-ai/DeepSeek-CoderDeepSeek-CoderGitHubNoNoNoNoNahttps://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesYesYesGraniteGitHubYesYesYesYesHugging FaceInverseCoderGitHubYesYesYesYesYesGraniteGitHubYesYesYesYesYesInverseCoderGitHubYesYesYes<	PPOCoder	GitHub	Yes	Yes	Yes	N.A.	https://github.com/reddy-lab-code-research/PPOCoder
SantaCoderHugging FaceNoVesYesHugging Facehttps://jtitub.com/bigcode/santacoderStarCoderGitHubYesYesHugging Facehttps://github.com/bigcode-project/starcoderAlchemistCoderGitHubYesYesHugging Facehttps://github.com/bigcode-project/starcoderAttoCoderGitHubNoNoYesHugging Facehttps://github.com/gonglinyuan/ast_t5AutoCoderGitHubNoNoYesHugging Facehttps://github.com/JILODM/CodeGeeXCodeGeenmaHugging FaceNoNoYesHugging Facehttps://github.com/JILODM/CodeQwen1.5CodeGeenmaGitHubYesYesYesHugging Facehttps://github.com/JetneTutrodeepseck-CoderCodeSageGitHubYesYesYesHugging Facehttps://github.com/deepseck-ai/DeepSeck-CoderDeepSeek-Coder-V2GitHubYesYesYesHugging Facehttps://github.com/deepseck-ai/DeepSeck-CoderDolphCoderGitHubYesYesYesYesHugging Facehttps://github.com/langface.co/bigscience/bloomCoLSBERTGitHubYesYesYesYesYesHugging Facehttps://github.com/langicoderInverseCoderGitHubYesYesYesYesHugging Facehttps://github.com/langicoderInverseCoderGitHubYesYesYesYesHugging Facehttps://github.com/langicoderInverseCoderGitHubYesYesYes<	RLTF	GitHub	Yes	Yes		Hugging Face	https://github.com/Zyq-scut/RLTF
StarCoderGitHubNoNoNoNAhttps://github.com/bigcde-project/starcoderAlchemistCoderGitHubYesYesHugging Facehttps://github.com/InternLM/AlchemistCoderAutoCoderGitHubNoNoYesHugging Facehttps://github.com/InternLM/AlchemistCoderCodeGeeXGitHubNoNoYesHugging Facehttps://github.com/InternLM/AlchemistCoderCodeGeeXGitHubNoNoYesNA.CodeGeexGitHubNoNoYesNA.CodeGeaxGitHubYesYesYesCodeGeaxGitHubYesYesYesCodeSageGitHubYesYesYesCodeSageGitHubYesYesYesDeepSeek-Coder-V2GitHubNoNoNoDolphCoderGitHubNoYesYesDolphCoderGitHubNoNoNoCoLSBERTGitHubYesYesYesGitHubNoYesYesHugging FaceDLOOMHugging FaceYesYesNa.Hugsing FaceYesYesNa.InverseCoderGitHubYesYesGitHubYesYesYesNeNeYesYesHugging FaceHugging FaceHugging FaceInverseCoderGitHubYesYesHugging FaceNoYesYesInverseCoderGitHubYes <td>SantaCoder</td> <td>Hugging Face</td> <td>No</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://huggingface.co/bigcode/santacoder</td>	SantaCoder	Hugging Face	No	Yes	Yes	Hugging Face	https://huggingface.co/bigcode/santacoder
AlchemistCoderGitHubYesYesYesHugging Facehttps://github.com/lifernLM/AlchemistCoderAST-T5GitHubNoYesYesHugging Facehttps://github.com/lifernLM/AlchemistCoderAutoCoderGitHubNoNoYesHugging Facehttps://github.com/lifernLM/AlchemistCoderCodeQeex1GitHubNoNoYesN.A.https://github.com/lifernLM/AlchemistCoderCodeQeen1.5GitHubNoNoYesHugging Facehttps://github.com/QvenLM/CodeQven1.5CodeSageGitHubYesYesYesHugging Facehttps://github.com/deepseek-ai/CodeSageCodeSageGitHubYesYesYesHugging Facehttps://github.com/stanford-futuredata/ColBERTDeepSeek-CoderGitHubYesYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-Coder-V2DolphCoderGitHubNoNoNoNoNohttps://github.com/stanford-futuredata/ColBERTDolphCoderGitHubYesYesYesNA.https://github.com/stanford-futuredata/ColBERTGraniteGitHubYesYesYesNA.https://github.com/pis-nlp.ophchoderGraniteGitHubYesYesYesYesNa.GraniteGitHubYesYesYesYesGraniteGitHubYesYesYesYesHugging FaceYesYesYesYesMagicoderGitHubYesYes </td <td>StarCoder</td> <td>GitHub</td> <td>No</td> <td>No</td> <td>No</td> <td>N.A.</td> <td>https://github.com/bigcode-project/starcoder</td>	StarCoder	GitHub	No	No	No	N.A.	https://github.com/bigcode-project/starcoder
AST-T5GitHubYesYesYesHugging Facehttps://github.com/gonglinyuan/ast_t5AutoCoderGitHubNoNoYesHugging Facehttps://github.com/Bullow/CodeGeeXCodeGeexXGitHubNoNoYesNA.https://github.com/THUDM/CodeGeeXCodeGemmaHugging FaceNoNoYesHugging Facehttps://github.com/THUDM/CodeGeeXCodeGemmaGitHubYesYesHugging Facehttps://github.com/THUDM/CodeQwen1.5CodeSageGitHubYesYesYesHugging FaceCoLSBERTGitHubYesYesYesHugging FaceDeepSeek-CoderGitHubNoNoNoNoDeepSeek-Coder-V2GitHubNoNoNoDolphCoderGitHubYesYesYesHugging FaceCLSBERTGitHubYesYesYesHugging FaceBLOOMHugging FaceYesYesYesHugging FaceCoLSBERTGitHubYesYesYesHugging FaceGitHubNoNoYesYesHugging FaceCoLSBERTGitHubNoYesYesHugging FaceGitHubNoYesYesHugging FaceIverseCoderGitHubYesYesHugging FaceIverseCoderGitHubYesYesYesHugging FaceNeYesYesMagicoderGitHubYesYesNT-Java	AlchemistCoder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/InternLM/AlchemistCoder
AutoCoderGitHubNoNoYesHugging Facehttps://github.com/bin123apple/AutoCoderCodeGeeXGitHubNoNoYesN.A.https://github.com/IHUDM/CodeGeeXCodeGemmaGitHubNoNoYesHugging Facehttps://github.com/QwenLM/CodeGeeXCodeGewaGitHubYesYesYesHugging Facehttps://github.com/QwenLM/CodeGeeXCodeSageGitHubYesYesYesHugging Facehttps://github.com/Amazon-science/CodeSageCoLSEERTGitHubYesYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoNoNoNA.https://github.com/deepseek-ai/DeepSeek-CoderDolphCoderGitHubNoNoNoNA.https://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesHugging FaceCoLSBERTGitHubYesYesYesHugging FaceGitHubYesYesYesHugging Facehttps://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesHugging FaceCoLSBERTGitHubNoYesYesHugging FaceGitHubYesYesYesHugging Facehttps://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesHugging FaceColSBERTGitHubNoYesYesHugging FaceGitHubYesYesYesHugging Fa	AST-T5	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/gonglinyuan/ast_t5
CodeGeeXGitHubNoNoYesN.A.https://github.com/THUDM/CodeGeeXCodeGeemmaHugging FaceNoNoNoHugging Facehttps://github.com/QwenLM/CodeQwenL5CodeGeemmaGitHubYesYesYesHugging Facehttps://github.com/amazon-science/CodeSageCoLSBERTGitHubYesYesYesHugging Facehttps://github.com/stanford-futuredata/ColBERTDeepSeek-CoderGitHubYesYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoNoNoNoNA.DolphCoderGitHubYesYesYesHugging FaceCCT5GitHubYesYesYesHugging FaceBLOOMHugging FaceYesYesYesHugging FaceCalSBERTGitHubYesYesYesHugging FaceGranuarT5GitHubYesYesYesHugging FaceGranuarT5GitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceYesYesYesHugging FaceOctoCoderHugging FaceYesYesYesHugging FaceStarCoder2GitHubYesYesYesHugging FaceStarCoder2GitHubYesYesYesHugging FaceOctoCoderHugging FaceYesYesYesHugging	AutoCoder	GitHub	No	No	Yes	Hugging Face	https://github.com/bin123apple/AutoCoder
CodeGemmaHugging FaceNoNoNoHugging Facehttps://ihuggingface.co/blog/codegemmaCodeQuen1.5GitHubNoNoYesHugging Facehttps://github.com/QuenLM/CodeQuen1.5CodeSageGitHubYesYesYesNA.https://github.com/deepseek.ai/DeepSeek-CoderDeepSeek-CoderGitHubYesYesYesHugging Facehttps://github.com/deepseek.ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoYesYesHugging Facehttps://github.com/pris-nlp/DolphCoderCoT5GitHubYesYesYesYesHugging Facehttps://github.com/pris-nlp/DolphCoderCoT5GitHubYesYesYesYesHugging Facehttps://github.com/pris-nlp/DolphCoderGitHubYesYesYesYesYesHugging Facehttps://github.com/pris-nlp/DolphCoderGitHubYesYesYesYesYesHugging Facehttps://github.com/pkace.co/bigscience/bloomGrammarT5GitHubYesYesYesHugging Facehttps://github.com/pkuzqh/GrammarT5GraniteGitHubYesYesYesHugging Facehttps://github.com/openLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/openLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/lise-uiuc/magicoderOctoGeeXHugging FaceYesYesYesYesHugging F	CodeGeeX	GitHub	No	No	Yes	N.A.	https://github.com/THUDM/CodeGeeX
CodeQwen1.5GitfTubNoNoYesHugging Facehttps://github.com/QwenLM/CodeQwen1.5CodeSageGitHubYesYesYesHugging Facehttps://github.com/amazon-science/CodeSageCoLSBERTGitHubYesYesYesNA.https://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderDolphCoderGitHubNoYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderCCT5GitHubYesYesYesHugging Facehttps://github.com/leepseek-ai/DeepSeek-CoderCLSBERTGitHubYesYesYesYeshttps://github.com/leepseek-ai/DeepSeek-CoderGrammarT5GitHubYesYesYesNA.https://github.com/leepseek-ai/DeepSeek-coderInverseCoderGitHubYesYesYesNA.https://github.com/leepseek-ai/DeepSeek-coderInverseCoderGitHubYesYesYesHugging Facehttps://github.com/leepseek-ai/DeepSeek-CoderInverseCoderGitHubYesYesYesHugging Facehttps://github.com/leepseek-ai/DeepSeek-CoderMagicoderGitHubYesYesYesHugging Facehttps://github.com/leenmar/LeondeNT-JavaHugging FaceYesYesYesHugging FaceOctoCoderHugging FaceYesYesYesHugging FaceSterCoder2GitHubYes	CodeGemma	Hugging Face	No	No	No	Hugging Face	https://huggingface.co/blog/codegemma
CodeSageGitHubYesYesYesHugging Facehttps://github.com/amazon-science/CodeSageCoLSBERTGitHubYesYesYesN.A.https://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-CoderGitHubNoYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-Coder-V2DolphCoderGitHubNoNoNoNoNoNoCCT5GitHubYesYesYesHugging Facehttps://github.com/kingbo/CCT5BLOOMHugging FaceYesYesYesNeCoLSBERTGitHubYesYesYesNa.GranmarT5GitHubYesYesYesNa.GraniteGitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceHugging Facehttps://github.com/buz.qh/GrammarT5NT-JavaHugging FaceNoYesYesNT-JavaHugging FaceNoYesYesVarOcOderGitHubYesYesYesVarOcOderHugging FaceHugging Facehttps://github.com/bigc.co/ibigcode/octocoderNT-JavaHugging FaceYesYesYesNtD-SocOderGitHubYesYesYesVarCoderGitHubYesYesYesVarOcderGitHubYesYesYesNtD-SocOderHugging FaceHutps://github.com/bigcode/octocode	CodeQwen1.5	GitHub	No	No	Yes	Hugging Face	https://github.com/QwenLM/CodeQwen1.5
CoLSBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTDeepSeek-CoderGitHubYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoYesYesHugging FaceDolphCoderGitHubYesNoNoNo.CCT5GitHubYesYesYesHugging FaceBLOOMHugging FaceYesYesYesHugging FaceCoLSBERTGitHubYesYesYesHugging FaceGranmarT5GitHubYesYesYesHugging FaceGranmarT5GitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceMajcoderGitHubYesYesYesHugging FaceMajcoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceNoYesYesHugging FaceOctoGeeXHugging FaceYesYesYesHugging FaceStarCoder2GitHubNoYesYesYesHugging FaceStarCoder2GitHubNoYesYesHugging FaceStarCoder2GitHubNoYesYesHugging FaceStarCoder2GitHubNoYesYesHugging FaceStarCoder2GitHubNoYesYesHugging FaceStarCoder2GitHubYes	CodeSage	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/amazon-science/CodeSage
DeepSeek-CoderGitHubYesYesYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-CoderDeepSeek-Coder-V2GitHubNoYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-Coder-V2DolphCoderGitHubNoNoNoNA.https://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesNA.CoLSBERTGitHubYesYesYesNA.GrammarT5GitHubYesYesYesNA.GrantiteGitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceMagicoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceNoYesYesHugging FaceOctoGeeXHugging FaceYesYesYesHugging FaceStarCoder2GitHubYesYesYesYesGitHubYesYesYesHugging Facehttps://luggingface.co/bigcode/octocoderOctoGeeXHugging FaceYesYesYesYesStarCoder2GitHubYesYesYesYesGitHubYesYesYesYesYesUniCoderGitHubYesYesYesHugging FaceStarCoder2GitHubYesYesYesHugging FaceGit	ColSBERT	GitHub	Yes	Yes	Yes	N.A.	https://github.com/stanford-futuredata/ColBERT
DeepSeek-Coder-V2GitHubNoYesYesHugging Facehttps://github.com/deepseek-ai/DeepSeek-Coder-V2DolphCoderGitHubNoNoNoN.A.https://github.com/pris-nlp/DolphCoderCCT5GitHubYesNoYesYeshttps://github.com/pris-nlp/DolphCoderBLOOMHugging FaceYesYesYesHugging FaceCoLSBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGranmarT5GitHubYesYesYesHugging Facehttps://github.com/pkuzqh/GrammarT5GraniteGitHubNoYesYesHugging Facehttps://github.com/openLemur/LemurMagicoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceNoYesYesHugging FaceOctoCoderHugging FaceNoYesYesOtaCder2GitHubYesYesYesGitHubNoYesYesYesYesYesYesYesOtaCoderHugging FaceYesYesOtaCoderGitHubYesYesStarCoder2GitHubNoYesYesGitHubYesYesYesHugging FaceHugging FaceKithusNoYesYesUniCoderGitHubYesYesYesGitHubYesYesYesHugging FaceHugging FaceKesYesYes </td <td>DeepSeek-Coder</td> <td>GitHub</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td>Hugging Face</td> <td>https://github.com/deepseek-ai/DeepSeek-Coder</td>	DeepSeek-Coder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/deepseek-ai/DeepSeek-Coder
DolphCoderGitHubNoNoNoN.A.https://github.com/pris-nlp/DolphCoderCCT5GitHubYesNoYesZenodohttps://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesHugging Facehttps://github.com/stanford-futuredata/ColBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGranmarT5GitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceInverseCoderGitHubYesYesYesHugging FaceMagicoderGitHubYesYesYesHugging FaceNT-JavaHugging FaceYesYesYesHugging FaceOctoCoderHugging FaceYesYesYesHugging FaceOctoGeeXHugging FaceYesYesYesHugging FaceStarCoder2GitHubYesYesYesHugging FaceStarCoder2GitHubYesYesYesHugging FaceStepCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHug	DeepSeek-Coder-V2	GitHub	No	Yes	Yes	Hugging Face	https://github.com/deepseek-ai/DeepSeek-Coder-V2
CCT5GitHubYesNoYesZenodohttps://github.com/Ringbo/CCT5BLOOMHugging FaceYesYesYesHugging Facehttps://github.com/Ringbo/CCT5CoLSBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGrammarT5GitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGraniteGitHubNoYesYesHugging Facehttps://github.com/stanford-futuredata/ColBERTInverseCoderGitHubYesYesYesHugging Facehttps://github.com/jbm-granite/granite-code-modelsInverseCoderGitHubYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-rLemurGitHubYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-rMagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://luggingface.co/bigcode/octocoderOctoCoderHugging FaceYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StarCoder2GitHubNoYesYesYesHugging Facehttps://github.com/albustrund/APPS_PlusUniCoderGitHubYesYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesYesHuggi	DolphCoder	GitHub	No	No	No	N.A.	https://github.com/pris-nlp/DolphCoder
BLOOMHugging FaceYesYesYesYesHugging Facehttps://huggingface.co/bigscience/bloomCoLSBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGranmarT5GitHubYesYesYesN.A.https://github.com/pkuzqh/GrammarT5GraniteGitHubNoYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsInverseCoderGitHubYesYesYesHugging Facehttps://github.com/wyt2000/InverseCoderLemurGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://huggingface.co/infosys/NT-Java-1.1BOctoCoderHugging FaceYesYesYesHugging Facehttps://github.com/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderStepCoderGitHubNoYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging Face	CCT5	GitHub	Yes	No	Yes	Zenodo	https://github.com/Ringbo/CCT5
CoLSBERTGitHubYesYesYesN.A.https://github.com/stanford-futuredata/ColBERTGrammarT5GitHubYesYesYesN.A.https://github.com/pkuzqh/GrammarT5GraniteGitHubNoYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsInverseCoderGitHubYesYesYesHugging Facehttps://github.com/wt2000/InverseCoderLemurGitHubYesYesYesHugging Facehttps://github.com/openLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://huggingface.co/infosys/NT-Java-1.1BOctoCoderHugging FaceYesYesYesHugging Facehttps://github.com/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://github.com/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StepCoderGitHubYesYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesYesHugging Facehttps://github.com/nipxucan/WizardLMWaveCoderGitHubYesYesYesYesHugging Facehttps://github.com/nipxucan/WizardLMWizardCoderGitHubYesYesYesYesYes<	BLOOM	Hugging Face	Yes	Yes	Yes	Hugging Face	https://huggingface.co/bigscience/bloom
GrammarT5GitHubYesYesYesN.A.https://github.com/pkuzqh/GrammarT5GraniteGitHubNoYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsInverseCoderGitHubYesYesYesHugging Facehttps://github.com/wyt2000/InverseCoderLemurGitHubYesYesYesHugging Facehttps://github.com/openLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://huggingface.co/bigcode/octocoderOctoCoderHugging FaceYesYesYesHugging Facehttps://github.com/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://github.com/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StepCoderGitHubYesYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceKithubYesYesYesYesHugging FaceKithubYesYesYesYesHugging FaceKithub	ColSBERT	GitHub	Yes	Yes	Yes	N.A.	https://github.com/stanford-futuredata/ColBERT
GraniteGitHubNoYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsInverseCoderGitHubYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsLemurGitHubYesYesYesHugging Facehttps://github.com/OpenLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsNT-JavaHugging FaceNoYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsOctoCoderHugging FaceYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsOctoGeeXHugging FaceYesYesYesHugging Facehttps://github.com/ibm-granite/granite-code-modelsStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderStepCoderGitHubNoYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWaveCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceKTTGitHubYesYesYesNA.KTTGitHubYesYesYesKTTGitHubYesYesYesKTTGitHubYesYesYesKTTGitHubYesYesKTTGitH	GrammarT5	GitHub	Yes	Yes	Yes	N.A.	https://github.com/pkuzqh/GrammarT5
InverseCoderGitHubYesYesYesHugging Facehttps://github.com/wyt2000/InverseCoderLemurGitHubYesYesYesHugging Facehttps://github.com/OpenLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesYesHugging Facehttps://lighub.com/ise-uiuc/magicoderOctoCoderHugging FaceYesYesYesHugging Facehttps://lighub.com/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StepCoderGitHubYesYesYesGoogle Drivehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/nlpxucan/WizardLMXFTGitHubYesYesYesN.A.https://github.com/ise-uiuc/xft	Granite	GitHub	No	Yes	Yes	Hugging Face	https://github.com/ibm-granite/granite-code-models
LemurGitHubYesYesYesHugging Facehttps://github.com/OpenLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/OpenLemur/LemurMagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://huggingface.co/infosys/NT-Java-1.1BOctoCoderHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderOctoGeeXHugging FaceYesYesHugging Facehttps://jthub.com/bigcode-project/starcoder2StepCoderGitHubYesYesNoN.A.https://github.com/Ablustrund/APPS_PlusUniCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/nicrosoft/WaveCoderKFTGitHubYesYesYesNo.A.https://github.com/nipsucan/WizardLM	InverseCoder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/wyt2000/InverseCoder
MagicoderGitHubYesYesYesHugging Facehttps://github.com/ise-uiuc/magicoderNT-JavaHugging FaceNoYesYesHugging Facehttps://github.com/ise-uiuc/magicoderOctoCoderHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StepCoderGitHubYesYesNoN.A.https://github.com/microsoft/UnicoderUniCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderXFTGitHubYesYesYesNA.https://github.com/ise-uiuc/xft	Lemur	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/OpenLemur/Lemur
NT-JavaHugging FaceNoYesYesHugging Facehttps://huggingface.co/infosys/NT-Java-1.1BOctoCoderHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderStepCoderGitHubYesYesNoNA.https://github.com/bigcode/octocoderUniCoderGitHubYesYesYesGoogle Drivehttps://github.com/bigcode/octocoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderXFTGitHubYesYesYesNeshttps://github.com/ilpxucan/WizardLMXFTGitHubYesYesYesN.A.https://github.com/ile-uuic/xft	Magicoder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/ise-uiuc/magicoder
OctoCoderHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderOctoGeeXHugging FaceYesYesYesHugging Facehttps://huggingface.co/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderStepCoderGitHubNoYesNoN.A.https://github.com/Ablustrund/APPS_PlusUniCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/nlpxucan/WizardLMXFTGitHubYesYesYesN.A.https://github.com/ise-uiuc/xft	NT-Java	Hugging Face	No	Yes	Yes	Hugging Face	https://huggingface.co/infosys/NT-Java-1.1B
OctoGeeXHugging FaceYesYesYesHugging Facehttps://buggingface.co/bigcode/octocoderStarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode/octocoderStepCoderGitHubNoYesNoN.A.https://github.com/Ablustrund/APPS_PlusUniCoderGitHubYesYesYesGogle Drivehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderXFTGitHubYesYesYesN.A.https://github.com/ilpxucan/WizardLM	OctoCoder	Hugging Face	Yes	Yes	Yes	Hugging Face	https://huggingface.co/bigcode/octocoder
StarCoder2GitHubYesYesYesHugging Facehttps://github.com/bigcode-project/starcoder2StepCoderGitHubNoYesNoN.A.https://github.com/Ablustrund/APPS_PlusUniCoderGitHubYesYesYesGoogle Drivehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/UnicoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderXFTGitHubYesYesYesN.A.https://github.com/ilpxucan/WizardLM	OctoGeeX	Hugging Face	Yes	Yes	Yes	Hugging Face	https://huggingface.co/bigcode/octocoder
StepCoderGitHubNoYesNoN.A.https://github.com/Ablustrund/APPS_PlusUniCoderGitHubYesYesGoogle Drivehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging FaceWizardCoderGitHubYesYesYesHugging FaceXFTGitHubYesYesYesN.A.	StarCoder2	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/bigcode-project/starcoder2
UniCoderGitHubYesYesYesGoogle Drivehttps://github.com/microsoft/UnicoderWaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderXFTGitHubYesYesYesN.A.https://github.com/nise-uiuc/xft	StepCoder	GitHub	No	Yes	No	N.A.	https://github.com/Ablustrund/APPS_Plus
WaveCoderGitHubYesYesYesHugging Facehttps://github.com/microsoft/WaveCoderWizardCoderGitHubYesYesYesHugging Facehttps://github.com/nlpxucan/WizardLMXFTGitHubYesYesYesN.A.https://github.com/ise-uiuc/xft	UniCoder	GitHub	Yes	Yes	Yes	Google Drive	https://github.com/microsoft/Unicoder
WizardCoderGitHubYesYesYesHugging Facehttps://github.com/nlpxucan/WizardLMXFTGitHubYesYesN.A.https://github.com/ise-uiuc/xft	WaveCoder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/microsoft/WaveCoder
XFT GitHub Yes Yes Yes N.A. https://github.com/ise-uiuc/xft	WizardCoder	GitHub	Yes	Yes	Yes	Hugging Face	https://github.com/nlpxucan/WizardLM
	XFT	GitHub	Yes	Yes	Yes	N.A.	https://github.com/ise-uiuc/xft

#### 4.1.1 Software Specifications Generation

Software specifications generation refers to the automated process of deriving formal descriptions and requirements for software systems from unstructured data sources such as comments or documentation within the software's source code. Traditional techniques for extracting software specifications usually involve rule-based or machine learningbased methods that necessitate manual effort and domain knowledge, and have limited the ability to generalize across various domains.

LLMs provide a promising avenue for automating the process of software specifications generation. LLMs, which have been utilized successfully in numerous software engineering tasks, offer the potential in automatically extracting software specifications from textual information. For example, Xie *et al.* [88] conduct the first empirical study to assess the capabilities of LLMs for generating software specifications from software comments or documentation. They employ few-shot learning techniques to enable LLMs to generalize from a limited number of examples and explore various prompt construction strategies. This work also conducts a comparative diagnosis of failure cases between LLMs and traditional methods to identify their respective strengths and weaknesses. Considering traditional methods relying on pre-defined templates or grammar rules, SpecGen [89] leverages the code comprehension capabilities of LLMs to generate formal program specifications. SpecSyn [90] is a specification synthesis approach that treats this task as a sequence-to-sequence learning problem, directly translating natural language input into formal specifications.

SE Activity	SE Task		Total
Software Requirements & Design (Section 4.1)	Ambiguity Detection (5) Class Diagram Derivation (2) GUI Layouts (2) Requirement Classification (7) Requirement Completeness Detection (1) Requirement Elicitation (7) Requirement Engineering (1) Use Case Generation (1)	Requirement Prioritization (1) Requirement Summarization (1) Requirement Traceability (2) Requirements Quality Assurance (4) Software Modeling (5) Specification Generation (3) Specifications Repair (1)	43
Software Development (Section 4.2)	API Documentation Smells (1) API Inference (4) API Recommendation (6) Code Comment Completion (1) Code Completion (34) Code Compression (2) Code Editing (5) Code Generation (155) Code Representation (6) Code Search (19) Code Summarization (41) Code Translation (24) Code Understanding (12) Continuous Development (1)	Identifier Normalization (1) Microservice Recommendation (1) Neural Architecture Search (1) Program Synthesis (13) SO Post Title Generation (2) Type Inference (1) Unified Development (1) Code Recommendation (1) Control Flow Graph Generation (2) Data Analysis (1) Method Name Generation (1) Project Planning (1) SO Question Answering (2) Data Augmentation (2)	341
Software Testing (Section 4.3)	Invariant Prediction (1) Proof Generation (1) Resource Leak Detection (1) Taint Analysis (1) Vulnerability Detection (76) Actionable Warning Identification (1) Adversarial Attack (3) API Misuse Detection (1) API Testing (1) Assertion Generation (10) Binary Code Similarity Detection (4) Code Execution (1) Decompilation (8) Failure-Inducing Testing (1) Fault Localization (17) Fuzzing (18)	GUI Testing (6) Indirect Call Analysis (1) Mutation Testing (12) NLP Testing (7) Penetration Testing (4) Program Analysis (1) Program Reduction (1) Property-based Testing (1) Simulation Testing (1) Static Analysis (6) Static Warning Validating (2) Test Generation (46) Test Suite Minimization (1) Dependency Alert Detection (1) Theorem Proving (1) Formal Verification (4)	240
Software Maintenance (Section 4.4)	Android Permissions (1) Bug Report Detection (5) Bug Reproduction (4) Bug Triaging (3) Code Review (24) Code Smells (1) Compiler Optimization (8) Exception Handling Recommendation (1) Incident Management (2) Issue Labeling (2) Log Anomaly Detection (13) Malware Tracker (1) Patch Correctness Assessment (6) Privacy Policy (1) Program Repair (66) Report Severity Prediction (3) Vulnerability Repair (12)	APP Review Analysis (2) Code Clone Detection (10) Code Coverage Prediction (1) Code Evolution (1) Code Refactoring (4) Commit Message Generation (5) Debugging (1) Flaky Test Prediction (1) Log Analysis (20) Mobile App Crash Detection (1) Outage Understanding (1) Sentiment Analysis (4) Tag Recommendation (1) Technical Debt Management (1) Test Update (3) Traceability Link Recovery (1)	211
Software Management (Section 4.5)	Developers' Behavior Analysis (1) Effort Estimation (2)	Software Tool Configuration (1) Software Repository Mining (1)	5

#### 4.1.2 Software Requirements Classification

Requirement classification refers to the process of categorizing software requirements into different classes or types, such as functional and non-functional requirements. Functional requirements outline the functionalities and behaviors the software should achieve, while non-functional requirements cover broader system attributes such as performance, security, reliability, and maintainability. As early as 2020, Hey *et al.* [91] propose NoRBERT, a BERT-based requirement classification approach for both functional and non-functional classes by transfer learning. Khan *et al.* [92] discuss the performance of LLMs in identifying and categorizing non-functional requirements. To address the issue of limited annotated data in non-functional requirements classification, Rahman *et al.* [93] propose to classify nonfunctional requirements by extracting features from pretrained word embedding models. Considering that previous work utilizing LLMs in a black-box manner, Han *et al.* [94] propose a requirement classification approach based on BERT and an explainable AI framework. They train a concern extraction model to extract concerns from requirement texts, and utilize explainability to generate explanations for the predictions of the requirement classification model, which is then used to fine-tune BERT for requirement classification.

#### 4.1.3 Requirement Quality Assurance

High-quality requirements are fundamental to the success of software development, providing a clear and detailed specification of what the software system should achieve. To assess the quality of requirements, Lubos et al. [95] empirically explores the effectiveness of LLMs (like Llama 2) to enhance the quality assurance process in the requirements engineering phase. Preda et al. [96] present an initial study to automate the review of coverage between highlevel and low-level software requirements by GPT-3.5 and GPT-4. Poudel et al. [97] utilize several BERT-style LLMs to assess whether design elements adequately satisfy software requirements. Ronanki et al. [98] utilizes ChatGPT to evaluate the quality of user stories, which are crucial to capture end-user needs and express requirements in agile software development projects. These studies suggest that LLMs can play a crucial role in automating and enhancing the quality assurance processes across various aspects of requirements engineering.

#### 4.1.4 Software Specifications Repair

Software Specifications Repair refers to the process of fixing errors in software specifications, which are formal declarations of software system requirements or behaviors. This repair process has become increasingly significant with the growing complexity and usage of declarative languages like Alloy. The recent integration of LLMs like ChatGPT in this domain aims to automate and enhance the effectiveness of repair techniques. These LLMs are evaluated for their ability to correct inaccuracies in specifications and compared against existing automated program repair methods. The process involves identifying and rectifying various types of errors in software specifications, including logical inconsistencies, type errors, and misuse of programming constructs. In 2023, Hasan et al. [99] evaluate the potential of ChatGPT for repairing software specifications in the Alloy declarative language. It aims to assess ChatGPT's capabilities in correcting errors and identifies challenges in making it a viable solution. This work demonstrates that ChatGPT successfully addresses unique errors that other tools fail to rectify, although it does not consistently surpass them in total repair count.

#### 4.1.5 Requirement Ambiguity Detection

Ambiguities refer to terms or phrases in requirements that can be interpreted in multiple ways, thus leading to misunderstandings and inconsistencies during the development process. Ambiguity detection attempts to identify such unclear, vague, or imprecise statements early in the requirements engineering phase. Moharil *et al.* [100], [101] introduce TABASCO to detect ambiguities by leveraging BERT to capture the different meanings a word can have depending on its context within a requirement. Further, Ezzini *et al.* [102] explore multiple approaches (such as SpanBERT) to handle anaphoric ambiguity by ambiguity detection and anaphora interpretation. Sridhara [103] conduct a preliminary empirical study to explore the potential of ChatGPT in anaphora ambiguity resolution.

#### 4.1.6 GUI Layouts

GUI layouts refer to the arrangement and organization of various elements, such as widgets, images, banners, and icons, within the design of a GUI. The purpose of GUI layouts is to provide a user-friendly interface and ensure a positive user experience. This encompasses how various interface components are effectively positioned and displayed to facilitate user understanding and interaction with the application. Designing layouts involves considerations of spatial relationships between elements, overall page structure, usability, aesthetics, and other factors to create an intuitive, user-friendly, and visually pleasing user interface. Kolthoff et al. [104] fine-tune BERT to retrieve reusable GUIs from a large-scale GUI repository, which can be adapted to facilitate GUI prototyping. Besides, Wu et al. [105] explore the application of LLMs in GUI layout and introduce Instigator, which utilizes LLMs to search and suggest GUI layouts based on textual instructions. Instigator aims to enhance creativity and efficiency in the GUI design process by providing designers with relevant and diverse layout options. This work highlights the potential of LLMs in supporting GUI design tasks, particularly by automating parts of the creative process.

In addition to the above-mentioned tasks detailed above, researchers also integrate LLMs into software requirements and design from other aspects, including class diagram derivation [106], requirement completeness detection [107], requirement elicitation [108], requirement prioritization [109], [110], requirement traceability [111], [112], software modeling [113], [114] and use case generation [115].

## 4.2 Software Development

Software Development is a creative process involving the use of computer programming languages, tools, and techniques to transform user requirements, functionality, and performance requirements into computer programs.

#### 4.2.1 Code Generation

Code generation plays a pivotal role during software development and has always been the primary focus in the application of LLMs, such as AlphaCode [40] and Code-Gen [54]. In general, recent advancements in LLM-based code generation focus on requirement-guided generation, execution-guided, and empirical studies. Below, we will introduce these studies in detail.

**Requirement-guided code generation.** In the early stages of development, LLMs commonly take a natural language description as the input and return the correct code snippet, which is evaluated by corresponding unit tests [116], [117], [118]. For example, ArchCode [119] leverages in-context learning to interpret software requirements from textual descriptions for LLM-based code generation. ClarifyGPT [120] attempts to detect ambiguous requirements, and prompt LLMs to specific clarifying questions, which are used to refine the requirements and generate

more accurate code solutions. Besides, AceCoder [121] directs LLMs to analyze the given requirement and generate intermediate artifacts for better code generation, such as test cases, that help clarify the requirement. Inspired by the way humans typically use planning to break down complex problems, Jiang *et al.* [117] introduce a self-planning code generation approach to help LLMs understand complex intents and simplify problem-solving.

Execution-guided Code Generation. Inspired by the process of human programming, developers utilize the execution results to guide LLMs in refining generated code iteratively [122], [123], [124]. For example, Self-Edit [125] validates generated code with available test cases, and the results are fed into LLMs as supplementary comments for further improvements and corrections. Besides, Dong et al. [126] introduce a self-collaboration code generation framework, which assembles a team consisting of three ChaGPT roles (*i.e.*, analyst, coder and tester). Given a requirement, the analyst decomposes it into several manageable subtasks and develops a high-level plan. The coder generates code according to the plan provided by the analyst, and refines code according to the test reports provided by the tester. The tester receives the code generated by the coder and subsequently produces a test report.

**Empirical Evaluation of LLMs.** A mass of empirical studies are conducted to investigate the actual code generation capabilities of LLMs from different aspects, such as robustness [127], [128], efficiency [129], human study [130], [131], [132], ChatGPT [133], [134], prompt engineering [135], benchmarks [136], [137], domain-specific generation [138] For example, Mastropaolo *et al.* [127] conduct an empirical study to investigate how robust GitHub Copilot is in generating consistent code when provided with semantically equivalent natural language descriptions. Kou *et al.* [139] empirically explore the attention alignment of LLMs and human programmers during code generation.

**Others.** Recently, In addition to the above-mentioned studies, there has been an exploration in cutting-edge areas such as repository-level generation [140], [141], [142], retrieval-augmented generation [143] and agent-based generation [144], [145], [146]

#### 4.2.2 Code Search

Code search is an essential practice in software development where developers search for specific pieces of source code within extensive codebases. Given a given query, this activity is undertaken to find code snippets, functions, classes, or entire files for potential reuse. Overall, existing studies utilizing LLMs for code search can be classified into two categories. First, researchers utilize training objectiveness to help LLMs learn more effective encoding representation, primarily focusing on contrastive learning [147], [148], [149], [150]. For example, CodeRetriever [151] learns semantic representations for function-level code search with unimodal and bimodal contrastive learning. Unimodal contrastive learning encourages similar functional code to cluster closely in the representation space, while bimodal contrastive learning assists in understanding the correlation between code and text. Similarly, CoCoSoDa [152] helps LLMs better align code snippets and natural language queries for code search based on multimodal contrastive learning and

data augmentation. Second, some empirical studies are conducted to investigate the potential of LLMs in code search. For example, Salza *et al.* [153] explore how transfer learning can be applied to code search tasks by pre-training and finetuning BERT. Chi *et al.* [154] evaluate exiting code search LLMs in industry requirements based on their adaptability, scalability, robustness, and semantic sensitivity.

#### 4.2.3 Code Translation

Code translation refers to the process of converting code from a source language into a target language while preserving the original functionality and behavior of the program. This task is crucial in software development, especially when developers want to migrate software systems to a different platform. Yang *et al.* [155] introduce UniTrans, which introduces test case generation to enhance the accuracy of code translation and provides mechanisms for iterative repair of translation errors. TransMap [156] attempts to detect semantic mistakes in code translated by models like Codex and ChatGPT. Regarding empirical studies, Pan *et al.* [157] propose a taxonomy of translation bugs introduced by LLMs, while Jiao *et al.* [158] provide a detailed analysis of code translation across four levels: token level, syntactic level, library level, and algorithm level.

#### 4.2.4 Code Co-Evolution

Code co-evolution attempts to update code snippets in a target programming language by reflecting the changes made in the source programming language. Different from code translation that directly generates code snippets from a source programming language to a target language, code co-evolution learns an edit sequence to update existing code snippets. Zhang *et al.* [159] propose Codeditor, which finetunes CoditT5 to align the code edits for two programming languages (Java and C#) from eight open-source projects.

#### 4.2.5 Code Comment Completion

Code comment completion refers to the process by which a computer program or model automatically writes code comments for programmers. In this process, based on the code that has already been written, the program or model automatically generates corresponding comments to explain the function and purpose of the code. It aims to provide real-time suggestions and assistance to programmers while writing code comments, similar to the concept of code auto-completion. This process does not create comments from scratch but rather assists programmers in completing comments more quickly based on the partial comments or code snippets they input. In 2021, Mastropaolo et al. [160] address the issue of code comments using T5 and n-gram models. The study compares a simple n-gram model and the T5 model in supporting code comment completion. The findings indicate that the T5 model performs better, although the n-gram model remains competitive. The research experiments with a dataset containing a large number of Java methods and their associated comments. Results show that the T5 model outperforms the n-gram model in all the tested code comment completion scenarios.

Code summarization takes as input a code snippet provided by the developer and automatically generates a higher-level summary in natural language form. These summaries are usually utilized to enhance the comprehension of software systems, thereby facilitating their maintenance. Integrating LLMs into code summarization can provide more accurate and natural summaries of source code, as LLMs can leverage their general knowledge on vast amounts of textual data to more accurately infer and generate natural language summaries of source code.

Existing LLM-based studies mainly fall into three areas: training optimizations, prompt engineering, and empirical studies. First, for open-source LLMs, researchers utilize pretraining or fine-tuning methods to enhance LLMs' capabilities of the alignment between code and natural language [161]. For example, ESALE [162] introduce three three code summarization-specific pre-training tasks (including two general tasks ULM and MLM, and one domain-specific task AWP) to help LLMs learn the code-summary alignment. Other training strategies include adapter tuning [163] and joint training [161]. Second, for commercial LLMs, prompt engineering is usually utilized to provide relevant information in a zero-shot or few-shot manner [164], [165]. For example, Ahmed et al. [166] explores enhancing the code summarization performance of LLMs by explicitly adding semantic information to the prompts, such as parameter names, return types, and simple control flows. Rukmono et al. [167] integrate static code analysis into the chain-ofthought prompting to generate component-level summaries of software systems. Third, empirical studies are conducted to explore the potential of LLMs from different aspects, such as explainability [168], metrics [169], binary code summarization [170] For example, Sun et al. [171] evaluate the performance of ChatGPT on code summarization, and Li et al. [168] utilize eye-tracking metrics from human participants to measure whether they concentrate the same parts of code as LLMs when generating summaries.

#### 4.2.7 Code Completion

Code completion aims at speeding up code writing by predicting the next code token the developer is likely to write. Researchers usually focus on improving the accuracy of the generated predictions. For example, TeCo [172] attempts to generate the next statement in a test method by fine-tuning CodeT5 with code semantic information. CCTEST [173] focuses on improving the performance of off-the-shelf code completion systems (such as Copilot and CodeGen) by utilizing a mutation strategy to detect erroneous outputs and a repair mechanism to fix these outputs, Besides, repositorylevel code completion has always been challenging due to complicated contexts from multiple files in the repository. LLMs demonstrate the potential in this task by integrating advanced strategies, such as information retrieval [174], [175], [176], [177], static analysis [178], and reinforcement learning [179]. There are also many empirical studies analyzing the actual performance of LLMs in code completion. For example, Ciniselli et al. [180], [181] investigates the effectiveness of T5 and RoBERTa for code completion at different granularity levels, from single tokens to entire code blocks.

Similarly, Van *et al.* [182]explores the impact of contextual information on three LLMs (UniXcoder, CodeGPT, and In-Coder) for both token-level and line-level code completion.

#### 4.2.8 Program Synthesis

Program synthesis refers to the automated process of generating computer programs based on high-level specifications or requirements. The objective of this process is to automate typically complex and time-consuming manual software development tasks by allowing machines to generate code based on specifications provided by users. The emphasis of program synthesis is to enhance the capabilities of LLMs, such as GPT-3 and Codex, enabling them to generate code from natural language specifications of programmer intent. For example, Jain et al. [183] from Microsoft explore the integration of LLMs such as GPT-3, Codex, and Google's LLM in generating code from natural language descriptions of programmer intent. Liventsev et al. [184] introduce SED, a framework to enhance the program synthesis capabilities of LLMs like OpenAI Codex. In SEIDR, a draft program is first synthesized based on a high-level description and is then executed to validate its correctness. If the program fails, specific instructions are generated to guide LLMs in fixing the issues until it meets the required specifications. Besides, Vella *et al.* [185] explores the integration of multiple LLMs within evolutionary algorithms to enhance program synthesis tasks.

#### 4.2.9 Code Editing

Code editing refers to the task of predicting changes or modifications that need to be made to a piece of code to transition from one version to another. It involves predicting the edits a developer will make to refactor code from one version (e.g.,  $v_1$ ) to another version (e.g.,  $v_2$  or  $v_3$ ). This task is essential in software development, especially during code refactoring or feature additions.

For example, Li et al. [186] design a pre-training specialized for code editing by rewriting mutated versions of code snippets into their correct form. They then introduce CodeEditor initialized with CodeT5 and fine-tune it on two code editing scenarios, i.e., code-to-code editing and comment&code-to-code editing. Besides, Gupta et al. [187] propose Grace to address code editing by leveraging the generative capabilities of LLMs on previously related edits. By mirroring the behavior of developers, Li et al. [188] introduce a hybrid approach SARGAM for automated code editing, which consists of three steps. SARGAM first retrieves similar code patches from a large repository and uses it to guide LLMs (such as PLBART, CoditT5, and NatGen) to generate a new patch, which is further modified to fit the exact context. These studies demonstrate the potential of LLMs to automate complex editing tasks, offering developers an efficient way to handle repetitive and time-consuming code modifications.

In addition to the above-mentioned tasks detailed above, researchers also integrate LLMs into software development from other aspects, including API documentation smells [189], API Inference [190], [191], [192], API recommendation [193], [194], [195], [196], [197], [198], code compression [199], [200], code representation [201], [202], [203], [148], [204], [205], code understanding [206], [207],

[208], continuous development optimization [209], identifier normalization [210], microservice recommendation [211], neural architecture search [212], performance data synthesize [213], SO post title generation [214], type inference [215], and unified development [216].

#### 4.3 Software Testing

Software testing is the process of executing a program or system with the intent of finding errors or any activity aimed at evaluating an attribute or capability of a program or system to ensure it meets its required results.

#### 4.3.1 Fault Localization

Fault localization is a critical process in software engineering that involves identifying the specific locations or elements in a software system where faults or bugs are present. By pinpointing the exact location of a fault, developers can more quickly perform software debugging and bug-fixing, leading to more efficient software development and maintenance. In the literature, researchers have conducted several studies to explore the performance of LLMs in fault localization, where two types of LLMs are involved, *i.e.*, encoder-like and GPT-like models.

Regarding encoder-based localization, as early as 2021, Zhu et al. [217] propose TroBo, a CodeBERT-based crossproject bug localization approach by leveraging both bug reports and source code. In 2022, Ciborowska et al. [218] discuss how to optimize BERT for changeset-based bug localization. They explore various design choices for applying BERT, including how to encode code changes and match error reports to specific code changes to enhance accuracy. To support cross-language cross-project bug localization, Chandramohan et al. [219] fine-tune UniXcoder with a contrastive learning object to enhance the representation of both bug reports and source code. Regarding GPT-based localization, Wu et al. [220] conduct a comprehensive empirical study on the large-scale open-source program Defects4J, evaluating the potential of OpenAI GPT LLMs (i.e., ChatGPT-3.5 and ChatGPT-4) in fault localization research. Besides, to handle large codebases, Kang et al. [221] introduce AutoFL, to select parts of the project and apply a post-processing step to match ChatGPT's answers with actual code elements. Yang et al. [222] introduce LLMAO, the first CodeGenbased approach that locates buggy lines without relying on traditional test coverage information. FuseFL [223] leverages ChatGPT to provide explainable fault localization by integrating multiple sources of information, including test case outcomes and code descriptions.

#### 4.3.2 Code Decompilation

Decompilation is the reverse engineering process of extracting a binary executable's code into a form that closely resembles its original source code and is understandable to humans. This task has important applications in security fields, such as malware analysis and vulnerability detection, as well as in software fields, such as code reuse and software supply chain analysis.

There mainly exist two key challenges during the decompilation process, *i.e.*, recovering variable names within binary executable files and producing human-readable code. To address the first issue, Xu et al. [224] introduce LmPa to improve the recovery of variable names and other high-level information by combining LLMs with program analysis. LmPa utilizes LLMs to provide meaningful names for variables, which are then refined and validated with program analysis techniques, ensuring that the recovered names are contextually appropriate and semantically accurate. To address the second issue, Wong et al. [225] automatically refine the accuracy and quality of decompiled C code by combining LLMs with traditional decompilation techniques. LLMs are utilized to fix syntax, inference, and memory errors in decompiled output, making it compatible with standard C/C++ compilation. A similar work is DeGPT[226], which designs a three-role mechanism to maximize the optimization capabilities of LLMs on decompiler output. Researchers also make efforts to integrate LLMs into code decompilation from different perspectives, including domain LLMs [227], [228], [229], and WebAssembly [230], binary code understanding [231].

#### 4.3.3 Vulnerability Detection

Vulnerability detection, also known as vulnerability prediction, aims to identify potential security bugs in software systems. Vulnerability detection is critical for protecting security-critical software systems from malicious attacks, providing the foundation for timely patching reported security vulnerabilities before they may be exploited (discussed in Section 4.4.2). In the literature, learning-based vulnerability detection approaches [232], [233] have been proposed to detect security vulnerabilities by extracting meaningful features and performing predictions automatically. For example, Li *et al.* [233] propose IVDetect, to perform fine-grained vulnerability prediction based on a FA-GCN model and GNNExplainer. However, such learning-based approaches are limited by the amount of training data, resulting in capturing a suboptimal vector representation of source code.

Thus, a mass of vulnerability detection approaches empowered with LLMs have been proposed. For example, LineVul attempts to detect vulnerabilities at the line level by fine-tuning CodeBERT and utilizing its attention mechanism to pinpoint vulnerable lines. In parallel to LineVul, VulBERTa is an encoder-only Transformer-based vulnerability detection approach by pre-training and fine-tuning RoBERTa. Besides, VulLLM [234] utilizes multi-task instruction tuning to adapt LLMs in vulnerability detection, which includes two auxiliary tasks: vulnerability localization to pinpoint the specific vulnerable parts of the code, and vulnerability interpretation to understand the underlying issues. GPTScan [235] attempts to detect smart contract logic vulnerabilities by combining GPT and static analysis. In the literature, researchers also conduct some empirical studies. For example, Steenhoek et al. [236] conduct an empirical study to investigate the performance of DL models in detecting software vulnerabilities from three aspects, i.e., model capabilities, training data, and model interpretation. This study includes nine learning-based AVD approaches, including the above-mentioned two LLM-based approaches, *i.e.*, LineVul and VulBERTa, and two off-the-shelf LLMs, i.e., CodeBERT and PLBART. In 2023, Zhang et al. [237] explore the performance of ChatGPT in software vulnerability detection with different prompts. Meanwhile, Noever et

*al.* [238] evaluate the capabilities of LLMs, particularly GPT-4, in detecting software vulnerabilities, comparing their performance against traditional static code analysis tools.

#### 4.3.4 Unit Test Generation

Test generation is the process of creating a set of test data or test cases for testing the adequacy of new or revised software programs. Unit test generation is a specialized domain within test generation, focusing on creating test cases for individual code units. We summarize these advanced studies that employ LLMs as follows.

**Fine-tuning LLM-based Generation.** AthenaTest represents the first work to apply LLMs in the field of test generation. AthenaTest first pre-trains BART on a large corpus of English and Java datasets and fine-tunes it on a labeled Java dataset. A3Test [239] first pre-trains PLBART to learn assertion knowledge in a self-supervision manner and fine-tune it to support the test case generation task. Rao *et al.* [240] introduce CAT-LM, a GPT-style LLM that is specifically trained to learn the mapping between code and its corresponding test cases.

Prompt-based Generation. For example, Schafer et al. [241] introduce TestPilot, an LLM-based end-to-end adaptive test generation technique for JavaScript. TestPilot first constructs a prompt with the information of the function under test and its usage examples. TestPilot then queries LLMs to generate test cases, which are validated through dynamic execution, and refined with new prompts containing failure information. MuTAP [242] utilizes mutation testing to augment the prompts, guiding LLMs to generate test cases that can detect software bugs. SymPrompt [243] enhances the performance of LLMs in generating highcoverage test cases by utilizing code-aware prompts, which are dynamically constructed with the execution paths of the method under test. Pizzorno et al. [244] introduce CoverUp, which integrates coverage analysis into prompts to iteratively generate Python regression tests.

Conversation-driven Generation with ChatGPT. To address issues of invalid test cases and low coverage, Gu et al. [245] introduce ChatGPT-based TestART, which integrates test generation with an iterative template-based repair process. To mitigate common issues such as invalid or incomplete tests generated by LLMs, Karmarkar et al. [246] introduce TestRefineGen to generate tests based on textual descriptions while ensuring confidentiality is maintained. Xie et al. [247] propose ChatUniTest, an automated unit test generation tool based on ChatGPT under the generationvalidation-repair framework. Ni et al. [248] introduce Cas-ModaTest, an end-to-end LLM-based framework, by dividing the unit test generation task into two cascaded ones: test prefix generation and test oracle generation. To enhance test coverage and improve the efficiency and effectiveness of automated testing, Lemieux et al. [249] introduce CO-DAMOSA, which integrates Codex with SBST to generate Python test cases.

**Empirical Evaluations of LLM-based Test Generation.** Xiao *et al.* [250] empirically explore how LLMs can be integrated into traditional search-based unit test generation workflows, including the initial phase, the test generation period, and the test coverage plateaus. Tang *et al.* [251] provide a comprehensive comparison between ChatGPT and EvoSuite based on several factors: correctness, readability, code coverage, and bug detection capabilities. Similarly, Yang *et al.* [252] explore the impact of prompt designs, comparison of open-source and commercial LLMs, and in-context learning. Researchers also conduct more studies from different aspects, such as the investigation of ChatGPT [253], [254], prompt engineering [255], human study [256], GUI text Input [257], security tests [258]

#### 4.3.5 Assertion Generation

Assertion Generation refers to the process of automatically inferring or creating expected outcomes or conditions against which the output of a software system or program is validated. These oracles serve as a standard or benchmark against which the system's behavior is tested, allowing for the automatic detection of bugs, discrepancies, or unexpected behaviors within the software. It involves using various methods, ranging from hard-coded patterns, natural language processing, neural networks, and machine learning models to derive or predict the expected outcomes, assertions, or exceptional behaviors of a given code snippet, function, or method. The goal is to generate these oracles accurately to enable automated testing and the identification of potential flaws or issues within the software.

As early as in 2022, Tufano et al. [259] propose to leverage the BART model to generate accurate assert statements in unit test cases. They first perform semi-supervised pretraining on a large corpus of English text to help BART learn the semantic and statistical properties of natural language. They then pre-train BART on abundant Java source code crawled from GitHub with a similar pre-training strategy to English pre-training. Finally, they fine-tune it on a dataset mined from more than 9 thousand open-source GitHub projects containing unit test cases defined with JUnit. Despite promising, the previous approach [259] struggles to find real-world bugs. In 2022, Dinella et al. [260] propose a transformer-based approach TOGA to infer both exceptional and assertion test oracles based on the context of the focal method. TOGA fine-tunes CodeBERT to classify exceptional oracles and rank assertion oracles. Unlike previous studies fine-tuning LLMs for assertion generation, Nashid et al. [17] introduce Cedar, a few-shot learning method that utilizes a prompt-based approach for both test assertion generation and program repair. Cedar retrieves relevant demonstrations and conducts prompts to query Codex to generate assertions in a few-shot manner.

Regarding empirical studies and benchmarking, He *et al.* [261] investigate the effectiveness of seven test-to-code traceability techniques in assertion generation and enhance existing datasets for training and evaluating assertion generation models, such as T5. besides, Pulavarthi *et al.* [262] introduce AssertionBench, a benchmark to assess the effectiveness of LLMs in generating assertions for hardware verification. AssertionBench focuses on generating high-quality assertions, which are crucial for detecting and diagnosing design bugs, particularly in complex hardware systems. Endres *et al.* [263] explore the potential of LLMs, such as GPT-4, to convert informal natural language descriptions of program behavior into formal postconditions that can be used for software verification. Hossain *et al.* [264] conduct a large-scale investigation of the ability

of LLMs to automatically generate test oracles by finetuning LLMs (including CodeGPT-110M, CodeParrot-110M, CodeGen-350M, PolyCoder-4B, Phi-1-1.3B, CodeGen-2B and PolyCoder-2.7B) with six different prompts.

#### 4.3.6 Test Suite Minimization

Test suite minimization aims at improving the efficiency of software testing by removing redundant test cases, thus reducing testing time and resources while maintaining the effectiveness of the test suite. Since previous test suite minimization approaches that rely on test code (black-box) are rather time-consuming, Pan et al. [265] propose LTM, a black-box similarity-based approach that leverages LLM to address the scalability problem. They explore three off-theshelf pre-trained models for similarity measurements: Code-BERT, GraphCodeBERT and UniXcoder. These models take the source code of test cases as input to generate numeric vectors. Then, they employ two similarity measures for calculating the similarity between test method embeddings: Cosine Similarity and Euclidean Distance. Cosine similarity measures the angle between two vectors, whereas Euclidean distance calculates the straight-line distance between them. Results show that UniXcoder/Cosine is the best LTM configuration when considering both effectiveness and efficiency. Besides, LTM outperforms prior works by achieving a significantly higher fault detection rate and faster minimization time.

### 4.3.7 Fuzzing

Fuzzing is an automated software testing method that injects invalid, malformed, or unexpected inputs into a system to reveal software defects and vulnerabilities. A fuzzing tool injects these inputs into the system and then monitors for exceptions such as crashes or information leakage. In the following, we summarize and categorize existing fuzzing studies empowered with LLMs.

DL Library Fuzzing. DL libraries, such as TensorFlow and PyTorch, are foundational to the burgeoning field of DL, play a pivotal role in our daily lives due to the widespread adoption of DL systems. Traditional fuzzing techniques often struggle to satisfy both the input language semantics and the DL API input constraints for tensor computations. To address this, Deng et al. [266] introduce TitanFuzz in 2023, the first approach to leverage LLMs directly for generating input programs for fuzzing DL libraries. For any given target API, TitanFuzz initially uses an LLM to generate a list of high-quality seed programs for fuzzing by querying the Codex model with a step-by-step prompt and sampling multiple completions. However, due to the nature of LLMs, TitanFuzz tends to generate ordinary human-like DL programs, which can only cover a limited range of program patterns. Deng et al. [267] propose FuzzGPT, which utilizes LLMs to generate unusual programs based on historically bug-triggering programs. FuzzGPT features three variants: few-shot learning, zero-shot learning, and fine-tuning, leveraging different LLMs, including Codex and CodeGen. Additionally, FuzzGPT can utilize the directive-following capabilities of ChatGPT to generate atypical programs.

**Compiler Fuzzing** Compilers are the foundation of modern software systems by translating high-level source code written by programmers into machine code, a lower-level language that a computer can execute. Thus, the correctness of a compiler is crucial as it ensures the accurate and efficient execution of the intended functionality of the software. In 2023, Yang et al. [268] introduce WhiteFox, the first whitebox compiler fuzzing tool using LLMs in conjunction with source code information to test compiler optimizations. WhiteFox utilizes a dual-model framework, where one analysis LLM examines low-level optimization source code and generates high-level test program requirements that can trigger optimizations, while another generation LLM produces test programs based on the summarized requirements. Eom et al. [269] introduce CovRL, a novel approach for fuzzing JavaScript engines by integrating coverageguided reinforcement learning with LLMs. CovRL leverages coverage feedback to guide the mutation process, aiming to uncover vulnerabilities more efficiently while minimizing

**Protocol Fuzzing.** Protocol implementations are the practical realizations of communication protocols in software or hardware, where correctness is crucial to ensure reliable and secure data transmission across different systems and networks. In 2023, Meng *et al.* [270] explore the opportunity of interacting with LLMs, which have ingested millions of pages of human-readable protocol specifications, to extract machine-readable information about the protocol for use in protocol fuzz testing. They develop CHATAFL, an LLM-guided protocol implementation fuzzing engine, to achieve structure-aware mutations concerning the state machine and input structure of the protocol. To fuzz Internet of Things (IoT) devices, LLMIF [271] utilizes an LLM to analyze protocol specifications and generate relevant test cases.

syntax and semantic errors.

General-purpose Fuzzing. Different from previous studies targeting specific scenarios, general-purpose fuzzing (e.g., AFL) is unaware of the programs and focuses on byte-level transformations. In 2023, Xia et al. [272] introduce Fuzz4All, the first universal fuzzer to support various software systems based on the multi-lingual capabilities of LLMs. It utilizes auto-prompting techniques to generate effective LLM prompts for fuzzing and iteratively updates prompts to generate diversified fuzzy inputs. Fuzz4All has been evaluated on nine systems across six different languages (i.e., C, C++, SMT, Go, Java, and Python), demonstrating a significant improvement in code coverage compared to previous fuzzers. Besides, considering that traditional fuzzers (e.g., AFL) struggle to generate structured test inputs efficiently and at scale, in 2023, Hu et al. [273] introduce CHATFUZZ, a grey-box fuzzing tool leveraging ChatGPT to enhance test input quality and effectiveness. In parallel to CHATFUZZ, Dakhama et al. [274] introduce an innovative approach that combines LLM and searchbased fuzzing, specifically targeting the gem5 system. The technique leverages ChatGPT to parameterize C programs, compiles the resulting code snippets, and feeds them to the SearchGEM5 extension of the AFL++ fuzzer, utilizing custom mutation operators. Similarly, LLAMAFUZZ [275] attempts to enhance traditional greybox fuzzing by leveraging LLMs to generate structured data, which is often a challenge for traditional fuzzing methods that rely on random mutations.

Fuzz Driver Generation. A fuzz driver is a piece of code

written to accept inputs from fuzzers and execute the program accordingly. It is labor-intensive and time-consuming for human experts to manually write high-quality fuzz drivers. In 2023, Zhang *et al.* [276] conduct an empirical study to explore the fundamental issues of effective fuzz driver generation using LLMs. This framework includes a quiz with 86 driver generation questions collected from 30 popular C projects and a set of criteria for precise driver effectiveness validation. In total, 189,628 fuzz drivers using 0.22 billion tokens are generated and evaluated. The research results indicate that enhanced query strategies and iterative methods can significantly improve the accuracy and efficiency of generating fuzz drivers.

**Others.** Researchers also integrate LLMs into other fuzzing scenarios, including smart contracts [277], kernel fuzzing [278], and BusyBox [279]. For example, Oliinyk *et al.* [279] utilize LLMs to generate initial test seeds for fuzzing BusyBox, a widely-used open-source software suite for Linux-based embedded devices, aligning these seeds more closely with the expected inputs of BusyBox's various utilities.

#### 4.3.8 Penetration Testing

Penetration Testing refers to the systematic process of actively assessing an organization's, company's, or system's security defenses by simulating real-world cyberattacks. This method involves identifying potential vulnerabilities and testing the system's resilience against exploitation, thereby providing insights into the system's security gaps and weaknesses. PentestGPT [280] is an LLM-empowered automatic penetration testing tool that leverages the abundant domain knowledge inherent in LLMs. PentestGPT consists of three core modules: (1) the reasoning module maintains a high-level overview of the testing process; (2) the generation module translates specific sub-tasks from the reasoning module into concrete instructions; and (3)the parsing module operates as a supportive interface between the user and the other two core modules. PTGroup [281] automates complex penetration testing scenarios by utilizing LLMs to interpret multiple testing strategies simultaneously and designing multiple prompt chains for different penetration testing tasks. Meanwhile, Happe et al. [282] explores the use of LLMs like GPT-3.5 to enhance penetration testing, focusing on both high-level task planning and low-level attack execution.

#### 4.3.9 Property-based Testing

Property-based testing (PBT) aims to verify whether the program properties are satisfied by generating a large number of random input data. In comparison to traditional unit testing, PBT emphasizes the program's properties and behaviors rather than singular predefined test cases. This testing method was initially popularized by the QuickCheck library in the Haskell language. The main steps of PBT include property definition, random data generation, and property validation.

Traditional PBT methods are not widely applied in actual software development because crafting diverse random input generators and meaningful test properties poses a challenge. However, developers tend to be more inclined

towards documentation writing, and library API documentation contains valuable natural language specifications for PBT. Vikram et al. [283] propose PBT-GPT, utilizing LLM to generate random inputs and test properties from API documentation. This study explores three different LLM prompting strategies, revealing various failure modes in PBT-GPT and outlining an evaluation methodology for generator and property quality. Preliminary research reports the results of using PBT-GPT on three Python library APIs. The experimental findings demonstrate the design and evaluation framework of PBT-GPT. In the design phase, researchers introduce three distinct LLM prompting strategies to generate critical components of property-based tests. The evaluation section thoroughly analyzes the quality of the generated generators and properties, encompassing metrics such as validity, diversity, and strength. Additionally, strategies to address potential issues are presented, providing effective pathways for enhancing test quality. Overall, the experimental results offer valuable insights into synthesizing property-based tests using LLM, despite some quality issues. The proposed mitigation strategies and evaluation framework pave the way for subsequent enhancements and improvements.

#### 4.3.10 Failure-Inducing Testing

Failure-inducing testing (FIT) is a software testing approach aimed at identifying test cases that can trigger software errors or faults. This method employs test inputs to provoke specific behaviors or anomalies within a program, thereby detecting and addressing errors in software.

For example, Li et al. [284] propose Differential Prompting, a methodology that utilizes ChatGPT to infer program intentions, generate program versions, and conduct differential testing, effectively identifying test cases that trigger software errors. The research finds that ChatGPT's ability to infer program intentions enables it to bypass subtle differences in code, thus identifying the correct program intention. By leveraging this characteristic, Differential Prompting successfully identifies test cases that trigger software errors. Differential Prompting comprises three main steps: program intention inference, program generation, and differential testing. In experiments conducted on different program sets such as QuixBugs and Codeforces, Differential Prompting demonstrates significant advantages in identifying failure-inducing test cases, far surpassing existing baseline methods.

#### 4.3.11 Mutation Testing

Mutation testing represents an established fault-based testing technique. It introduces faults into the programs under examination and requires developers to write tests that uncover these faults. These tests possess the potential to reveal numerous faults, particularly those associated with the introduced faults.

In particular,  $\mu$ BERT [285] represents the first attempt to integrate LLMs into mutation testing by using CodeBERT to generate natural mutants. Unlike traditional mutation testing methods,  $\mu$ BERT does not rely on predefined syntactic transformation rules. Instead, it masks tokens in the input expression and utilizes CodeBERT to predict and generate mutants. Inspired by  $\mu$ BERT, Ibrahimzada *et al.* [286] propose BugFarm to transform arbitrary code into complex bugs by querying LLMs to mutate code in multiple locations. VULGEN [287] focuses on generating realistic software vulnerabilities by combining pattern mining with LLMs. It first collects vulnerability-fixing examples to mine the patterns for vulnerability injection, and then leverages CodeT5 to learn the localization of injection. Similarly, Garg[288] investigates the relationship between software vulnerabilities and mutants generated by CodeBERT.

Regarding empirical studies, Wan *et al.* [289] investigate the performance of LLMs in generating mutations based on various criteria, including usability, fault detection potential, and their relationship with real bugs. Geng *et al.* [164] empirically investigates the feasibility of utilizing LLMs to generate comments that can reflect multiple developer intents by in-context learning. Besides, Tian *et al.* [290] explore the the effectiveness and efficiency of LLMs in detecting equivalent mutants.

#### 4.3.12 GUI Testing

Graphical user interface (GUI) testing ensures the accuracy and reliability of a mobile application's visual interface. It involves verifying that interactions with components like buttons and text boxes yield expected outcomes. The aim is to confirm the correct information display and intended user interactions. GUI testing can be manual or automated, often using metrics like error detection and code coverage for assessing performance. Its primary goal is to guarantee the stability and reliability of an application's visual and interactive elements.

In 2022, to recognize the diverse and semantic requirements for valid inputs in GUI testing, Liu et al. [291] propose an approach named QTypist based on LLMs for intelligently generating semantic input text according to the GUI context. To boost the performance of LLMs on text input in mobile GUI, they develop a prompt-based data construction and tuning method to automatically extract the prompts and answers for model tuning. They leverage the pre-trained GPT-3 model and fine-tune it with the tuning method. For GUI testing, a context-aware input generation method generates the prompt and feeds it into the GPT-3 model. Unlike QTypist [291] focusing on text input generation, in 2023, Liu et al. [292] propose GPTDroid, framing the mobile GUI testing problem as a question-answering task, utilizing LLM as a human tester. GPTDroid facilitates the passing of the application's GUI information to LLM to initiate testing scripts and receive and iterate execution results. This framework incorporates a functionality-aware memory prompting mechanism, equipping the LLM to retain testing knowledge and engage in long-term, functionality-based reasoning to guide exploration. Besides, VisionDroid [293] is a vision-driven automated GUI testing approach that leverages multimodal LLMs that can understand both visual and textual information to detect non-crash functional bugs in mobile apps. DroidAgent [294] leverages LLMs to simulate user interactions by setting and executing tasks that mirror realistic user behaviors and intents.

#### 4.3.13 NLP Testing

NLP testing refers to the process of assessing and evaluating the performance, accuracy, and robustness of natural language processing systems, including but not limited to machine translation, text generation, language understanding, and other NLP-related tasks. As early as 2020, He et al. [295] introduce SIT, a metamorphic testing approach that leverages BERT to validate machine translation software. SIT uses BERT to generate a set of similar sentences by altering a single word in the source sentence, helping to assess the structural consistency of translations. Similarly, motivated by the idea that sentences with distinct meanings should yield different translations, Gupta et al. [296] propose PatInv, which generates syntactically similar but semantically different sentences using BERT. In 2022, Sun et al. [297] introduce CAT, a BERT-driven word-replacement method for enhancing machine translation. Beyond these studies on machine translation, researchers have also explored using LLMs, particularly BERT, in other NLP testing scenarios, including named entity recognition software [298], textual content moderation software [299], dialogue systems [300], and question answering systems [301].

In addition to the above-mentioned tasks detailed above, researchers also integrate LLMs into software testing from other aspects, including API testing [302], code execution [303], static analysis [304], [305], [306], [307], vulnerable dependency alert detection [308] theorem proving [309], DL adversarial attack [310] and program reduction [311].

#### 4.4 Software Maintenance

Software maintenance is one of the foundational aspects of software engineering and encompasses the ongoing process of post-delivery software modification, aiming to rectify errors and meet emerging requirements.

#### 4.4.1 Program Repair

Automated program repair aims to generate correct patches for a detected buggy code snippet automatically and plays a crucial role during software maintenance [312], [313], [314]. A typical repair technique usually contains three steps: (1) applying off-the-shelf fault localization techniques to recognize the suspicious code elements; (2) modifying these elements based on a set of transformation rules to generate candidate patches; (3) adopting test suites to verify all candidate patches.

Overall, we summarize the existing program repair work involving LLMs into five stages. Initially, program repair is directly used as a downstream task to evaluate the capability of LLMs when such LLMs are designed and proposed in their original paper, such as CodeT5 and CodeBERT. Subsequently, there exist explorations in the SE field using LLMs as a component in existing repair workflow, such as CURE. Then comes the fine-tuning of LLMs as repair models on historical bug-fixing datasets, which is also the most widely researched topic in the literature. Later, zeroshot learning is utilized to better leverage LLMs, which also indicates a shift in the repair paradigm, *i.e.*, from an NMT task to a close test task in a fill-in-the-blank format. Recently, there have been attempts to combine LLMs with traditional repair techniques to address inherent problems that are difficult for traditional techniques to solve. At the same time, there is a substantial amount of empirical research in the field exploring the actual performances of LLMs in program

repair. Now, we list and summarize the existing LLM-based repair techniques as follows.

**Repair as a downstream task of LLMs.** Since the inception of LLMs, some researchers usually employ program repair as a downstream task (also referred to as code refinement) to evaluate the models' capabilities. In this scenario, program repair is viewed as a general code-code generation task, which translates the buggy code snippet to a correct code snippet on top of natural machine translation. The preliminary evaluations demonstrate the remarkable performance of LLMs in understanding code semantics and learning bug-fixing code changes, as well as fostering subsequent, deeper work introducing such LLMs into the field of program repair.

TABLE 6: The comparison results of representative LLMs on program repair

	BFP	-Small	BFP-N	Medium
Model	BLEU	Accuracy	BLEU	Accuracy
CodeBERTER	78.26%	17.75%	N.A.	N.A.
CodeT5	77.43%	21.62%	87.64%	13.96%
CodeBERT	77.42%	16.40%	91.07%	5.16%
GraphCodeBERT	80.02%	17.30%	91.31%	0.09%
PLBART	77.02%	19.21%	88.50%	8.98%
RoBERTa	77.30%	15.90%	90.07%	4.10%

LLM as a Repair Component. In the SE domain, the earliest exploration is to use LLMs to enhance certain aspects of existing traditional repair techniques. For example, in 2021, on top of CoCoNut, Jiang et al. [315] propose a new NMTbased APR technique CURE empowered with GPT. First, CURE extracts millions of methods from open-source Java projects and use subword tokenization to tokenize these methods. Second, CURE pre-trains GPT on the extracted dataset and fine-tunes it on CoCoNuT's training dataset. Third, CURE applies a new code-aware beam-search strategy to improve patch ranking and generate more correct patches. Finally, CURE combines the fine-tuned GPT with CoCoNuT as the full APR pipeline and trains it for the patch generation task. Importantly, it demonstrates the unique capabilities of combining a GPT PL model and an NMT model to learn both developer-like code and fix patterns to fix more bugs. Besides, in 2022, Li et al. [316] propose DEAR, a learning-based APR for multi-hunk, multi-statement bugs empowered with BERT. DEAR fine-tunes BERT to learn the fixing-together relationships among statements, *i.e.*, whether two statements are needed to be fixed together.

**Fine-tuning LLMs as Repairers.** Inspired by the successful application of program repair as a downstream task for LLMs, more research has delved into exploring the performance of fine-tuning such models in the repair domain [317]. For example, DeepDebug [318] is an early-stage work that views program repair as a Seq2Seq learning task by fine-tuning BART on Java datasets. At the same time, Berabi *et al.* [319] present TFix, which fine-tunes T5 to fix JavaScript code errors. To support multilingual repair, in 2022, Yuan *et al.* [16] propose CIRCLE, a T5-based APR framework equipped with continual learning ability across multiple programming languages. Recently, some studies utilize parameter-efficient fine-tuning to reduce training costs [320], [321].

Zero-shot LLM-based Repair. Despite promising, the repair performance of fine-tuned LLMs is usually constrained by the quality and quantity of labeled bug-fixing pairs, similar to previous learning-based repair techniques. Therefore, some researchers attempt to transform the repair problem into a cloze test task under a zero-shot setting, where LLMs are queried to directly predict the correct code tokens based on context information (*i.e.*, buggy methods) without any fine-tuning on historical datasets. For example, Xia et al. [13] propose AlphaRepair as the first cloze-style APR approach that leverages LLMs without any fine-tuning. AlphaRepair replaces the entire buggy line with a line containing only mask tokens and queries CodeBERT to generate candidate patches. Repilot [322] utilizes a Java completion engine to offer real-time feedback during the auto-regressive token generation process, thus assisting LLMs in producing better patches. FitRepair seeks to enhance the performance of cloze-style APR by combining LLMs and domain repair knowledge.

**Combination of LLMs and traditional APR.** Most LLMbased repair techniques utilize LLMs as an end-to-end learning-based patch generator and are developed separately from mature traditional techniques. Inspired by the fact that learning-based APR is complementary to traditional repair, Zhang *et al.* [18] propose GAMMA to combine the advance of LLMs and well-known template-based repair. GAMMA summarizes a variety of fix templates, transforms them into mask patterns, and adopts LLMs to predict the correct code for masked code as a fill-in-the-blank task. Ruiz *et al.* [323] explore the potential of LLMs to repair bugs with a round-trip translation strategy. At the same time, Peng *et al.* [324] propose a domain-aware promptbased approach TypeFix to repair Python type errors with fix templates.

Empirical Evaluation of LLMs. In conjunction with the aforementioned repair strategies tackling certain technical obstacles, there has been a concurrent surge in empirical studies examining the development and nuances of these methodologies. These empirical studies systematically explore the actual performance of LLMs during the repair workflow, with the sim to furnish insights for forthcoming program repair endeavors [325], [326]. For example, in 2022, Xia et al. [11] conduct an extensive study on the application of LLMs in real-world bug-fixing, with nine LLMs of varying sizes. In 2023, Jiang et al. [327] evaluate ten code LLMs on four APR benchmarks, to discuss the impact of finetuning, model size, and repair costs. Unlike previous studies focusing on software bugs [11], [327], Fan et al. [328] conduct a systematic study to explore whether APR techniques can fix the incorrect solutions produced by language models in LeetCode contests Besides, with the rise of ChatGPT, a mass of research efforts have been made to explore the potential of ChatGPT in repair scenarios, such as QuixBugs [329] and DL prorgam [330].

**Domain Repair.** In the LLM-based APR field, researchers have paid considerable attention to semantic and syntax bugs, which represent the most common application of the repair techniques discussed above. Unlike traditional APR, LLMs are pre-trained from a wide range of datasets to learn general language knowledge and can be applied to a wider range of repair scenarios. For example, in 2023, Jin *et al.* [331] propose InferFix, a Transformerbased approach based on Codex, to automatically fix both critical security and performance bugs detected by the static analysis tool Infer. So far, researchers have utilized different strategies (*e.g.*, zero-shot learning, fine-tuning, and few-shot learning) to integrate LLMs into various repair domains, including real-world issues [332], static warning [331], [333], syntax error [334], benchmark [335], neural network implementation [336], integrated development environment [337], human study [338], programming problems [339], repair agent [340], [341], interactive repair[342], [343], multi-location repair [344], [345], repair costs [346], and formal proof [347].

#### 4.4.2 Security Vulnerability Repair

Software vulnerability predominantly pertains to the weaknesses or flaws found within the software's code or design, which can potentially be exploited to compromise the security or functionality of the hardware or network it operates on. Unlike common software bugs focused on by most repair work, securities are more damaging and require more urgent fixes, making it critical to automate vulnerability fixes. Security researchers have to spend a huge amount of effort to manually fix such vulnerable functions, resulting in delays in vulnerability remediation and providing opportunities for attacks. With the successful application of LLMs in program repair, researchers have begun to apply LLMs to help under-resourced security researchers fix software vulnerabilities automatically. We summarize existing vulnerability repair studies empowered with LLMs as follows.

**Fine-tuning LLM-based Vulnerability Repair.** VulRepair [348] is an early-stage LLM-based vulnerability repair approach by directly fine-tuning CodeT5. VQM [349] is a successor of VulRepair by leveraging a cross-attention mechanism to locate vulnerable code elements during patch generation. VulMaster [350] fine-tunes CodeT5 with information from diverse sources, including the structure of vulnerable code and expert knowledge.

**Zero-shot LLM-based Vulnerability Repair.** In 2023, Pearce *et al.* [351] examine a zero-shot vulnerability repair approach, assessing the potential of large language models such as OpenAI's Codex and AI21's Jurassic J-1. The primary research challenge lies in designing prompts that prompt LLMs to generate corrected versions of insecure code. The study emphasizes the use of commercially available black-box LLMs, as well as open-source models and locally trained models, for extensive research experiments on synthetic, handcrafted, and real-world security vulnerability scenarios.

**Empirical Study of LLM-based Vulnerability Repair.** In 2023, Zhang *et al.* [12] conduct the first extensive empirical study to investigate the actual performance of various LLMs on vulnerability repair, involving more than 100 fine-tuned LLMs. First, they demonstrate that through simple fine-tuning, LLMs are able to outperform state-of-the-art vulnerability repair techniques. Second, they delved into studying the impact of LLMs on the repair workflow, including data pre-processing, model training, and repair inference phrases. Third, they develop a straightforward vulnerability repair strategy, leveraging transfer learning from bug-fixing,

and demonstrate that such a simplified approach further enhances the prediction accuracy of LLMs. Furthermore, they offer additional insights by discussing various aspects, such as code representation and a preliminary study with ChatGPT, to illuminate the capabilities and limitations of LLM-based vulnerability repair approaches. Finally, they precisely identify several practical guidelines, such as enhancing fine-tuning, to advance LLM-based vulnerability repair in the imminent future. Besides, Wu *et al.* [15] compare the performance of LLMs with existing learning-based vulnerability repair techniques, including Codex, CodeGen, CodeT5, PLBART and InCoder. A similar study is conducted by Huang *et al.* [326]. In 2023, Tol *et al.* [352] empirically explore the potential of leveraging LLMs to automatically generate patches for side-channel vulnerabilities.

#### 4.4.3 Patch Correctness Assessment

It is a common practice for the majority of extant program repair methodologies to predominantly utilize developerconstructed test suites as the program specification, serving to evaluate the accuracy of the patches produced. Nevertheless, such an existing test suite represents an inherently partial specification, delineating only a segment of the program's behavioral domain. Thus, repair approaches may suffer from the patch overfitting issue (*i.e.*, patches passing the available test suites fail to generalize to other potential test suites), limiting the value and deployment of such repair approaches in real-world scenarios. Patch correctness is a crucial phase for developers to further filter out overfitting patches after patch generation (detailed in Section 4.4.1), so as to improve the quality of returned patches. The patch overfitting issue is a long-standing challenge in the program repair community and some independent studies have been conducted to address it. We summarize these works from three aspects, i.e., LLMs as feature extractor, fine-tuningbased APCA and zero-shot-based APCA. First, as early as 2020, Tian et al. [353], [354] investigate the effectiveness of representation learning for for patch correctness assessment. They select four embedding models, including re-trained (i.e., Doc2vec, code2vec and CC2vec) and pre-trained models (i.e., BERT), marking the first application of BERT in this field. In 2022, Tianet al. [355] propose Quatrain, which utilizes CodeTrans to generate patch descriptions, and BERT to embed bug reports and patch descriptions. Recently, Invalidator [356] identifies the correctness of patches via semantic and syntactic reasoning. Second, APPT [357] is the first approach that fine-tunes LLMs to predict patch correctness. APPT consists of three components: (1) BERT to extract features from source code tokens; (2) LSTM to capture dependency information between source and repaired code snippets; and (3) a DL classifier to predict whether a patch is overfitting or not. Third, PatchZero [358] attempts to predict patch correctness in a zero-shot manner. PatchZero reformats the format of the patch correctness assessment task to match the original pre-training objective of the LLMs. Molina *et al.* [359] introduce FixCheck to filter out incorrect patches by combining random testing and LLMs to generate fault-revealing test cases.

### 4.4.4 Commit Message Generation

Commit message generation attempts to create natural language descriptions for code commits. It begins with modified code snippets and employs template-based, retrievalbased, or learning-based models to generate commit messages. The key lies in understanding the context of code modifications and accurately describing these changes in the commit messages. For example, Jung et al. [360] introduce CommitBERT to generate messages by using CodeBERT as the initial weight during training. Wang et al. [361] introduce ExGroFi to fine-tune LLMs by incorporating the correlation between commits and issues during the training process. Li et al. [362] utilize the reasoning capabilities of LLMs to generate commit messages by framing it as a knowledge-intensive reasoning task. Regarding empirical studies, Xue et al. [363] explore the effectiveness of different LLMs in generating commit messages, and Lopes et al. [364] focus on the ChatGPT.

#### 4.4.5 Code Review

Code review is a critical process in the software development lifecycle, withe the aim of enhancing code quality by identifying and resolving issues before the code is merged into the main codebase. In code review practices, developers are tasked with thoroughly examining, understanding, and executing the code under review. This process involves evaluating various aspects of the code, such as its logic, functionality, performance, and style.

To reduce human review efforts, early work in this community primarily focuses on training domain LLMs based on T5 to automate the code review process [365], [366], [367]. For example, Li et al. [366] introduce AUGER to generate code review comments by pre-training T5 with a masked language modeling object. Tufano et al. [365] pretrain and fine-tune T5 to support different tasks, such as comment generation and code refinement. Initialized with CodeT5, CodeReviewer is pre-trained with four pre-training tasks specifically designed for the code review scenario: diff tag prediction, denoising code diff, denoising review comment, and review comment generation. Researchers also conduct some empirical studies from different aspects [368], [369] For example, Guo et al. [370] explore the potential of ChatGPT in code review tasks, with a specific focus on code refinement based on code reviews. This study involves various research aspects, including the impact of prompt and temperature settings, the comparison with CodeReviewer, the qualitative analysis, and the analysis of root causes.

#### 4.4.6 Bug Report Detection

Duplicate bug report detection attempts to automatically identify and label duplicate bug reports in issue tracking systems, enabling developers to avoid redundantly dealing with the same issues. In the report detection process, researchers utilize LLMs to compare and analyze the similarity between different bug reports to determine if they describe the same defect or problem. For example, in 2023, Zhang *et al.* [371] introduce Cupid, which integrates the traditional detection approach REP with ChatGPT. Cupid utilizes ChatGPT in a zero-shot setting to extract key information from bug reports, which is then used as input for REP to detect duplicate bug reports. Meanwhile, Plein *et al.* [372] conduct empirical research, as outlined in [372], on how to utilize ChatGPT to transform user-provided software defect reports into formal test case specifications. They employ ChatGPT to generate test cases and evaluate the executability and validity of these generated test cases. Experimental results demonstrate the significant potential of ChatGPT in converting informal defect reports into formal test cases, holding crucial implications for automated software testing and defect resolution tasks.

#### 4.4.7 Bug Reproduction

Bug reproduction, also known as bug replay, refers to the process of reproducing or recreating software defects or issues based on the information provided in a bug report. The process is crucial for software maintenance as it enables developers to understand, replicate, and fix the defects reported.

In 2023, Kang *et al.* [373] introduce a framework named LIBRO, which utilizes LLMs to generate potential test cases from bug reports and subsequently ranks and suggests these generated solutions through post-processing steps. Focusing on mobile application crashes, Huang *et al.* [374] presents CrashTranslator, which leverages LLMs to predict the necessary exploration steps required to reproduce a crash and uses reinforcement learning to improve the search process and mitigate inaccurate predictions. Furthermore, Feng *et al.* [375] propose a lightweight approach AdbGPT to automatically reproduce Andriod bugs from bug reports without any training.

#### 4.4.8 Test Update

Test update refers to the process of modifying existing test cases to align them with recent changes in the production code. This is a crucial aspect of maintaining the quality and relevance of software tests throughout the software lifecycle. CEPROT [376] represents the first attempt to fine-tune CodeT5 to automatically identify and update obsolete method-level test cases in response to changes in production code. SYNBCIATR [377] designs three target-oriented contexts (*i.e.*, class contexts, usage contexts, and environment contexts), which are used to construct prompts to query GPT-4 to generate repaired test cases. TaRGet [378] treats the test update process as a language translation task by fine-tuning LLMs with crucial context information.

#### 4.4.9 Log Analysis

Logs record events that occur within a system, including user actions, system activities, error messages, and security alerts. Log analysis involves automatically examining and interpreting this log data, which is essential for developers to understand system status and diagnose potential problems. Existing approaches can be categorized into finetuning [379], [380], few-shot [381], [382], [383], [384], [385], and zero-shot learning [386], [387], [388]. For example, Le *et al.* [381] explore using prompt-based few-shot learning for log parsing, leveraging the flexibility of prompts to adapt to various log formats with minimal training examples. Researchers also empirically explore the potential of LLMs in log analysis, including the impact of data resampling [389], structuring logs [390], detecting unusual behaviors [390], [391], log-based question-answering [392], interpreting and categorizing logs[393].

#### 4.4.10 Code Clone Detection

Code Clone Detection attempts to identify duplicate or similar code segments within a software codebase based on code similarity analysis. Zhang *et al.* [394] conduct the first empirical study to explore the potential of ChatGPT and GPT-4 in the task of code clone detection. Moumoula *et al.* [395] investigate the capabilities of four LLMs for detecting code clones across different programming languages with eight different prompt configurations. Dou *et al.* [396] explores different aspects of LLMs' capabilities by examining five different prompts, multi-step chain-of-thought prompts, code embeddings, and multiple programming languages.

In addition to the aforementioned studies, researchers also leverage LLMs to automate a variety of software maintenance tasks, including bug triaging [397], [398], code smell [399], emotion-cause extraction [400], exception handling recommendation [401], incident management [402], [403], issue labeling [404], privacy policy [405], code porting [406], compiler optimization [407], [408], and Android permission-related problems resolution [409].

#### 4.5 Software Management

Software management refers to the practice of overseeing the entire software lifecycle, ensuring that software products are delivered on time, within budget, and meet quality standards. To date, researchers mainly utilize LLMs to perform effort estimation, software tool configuration, developers' behavior analysis, and software repository mining. First, effort estimation attempts to predict the amount of time, resources, and effort required to complete a software project. Alhamed et al. [410] explores the potential of BERT with expert features to estimate the effort required for software maintenance tasks. Fine-SE [411] combines both semantic and expert features to develop an automatic integrated BERT-based approach for effort estimation. Second, software tool configuration attempts to ensure that the appropriate tools are selected and configured. Kannan et al. [412] discusses various prompting strategies for interacting with GPT-4 in configuring tools like machine learning frameworks and complex software systems. Third, analyzing developers' behavior is crucial for project managers to understand team dynamics, productivity, and collaboration patterns. Cai et al. [401] conduct the first attempt to utilize LLMs to detect the causes of emotions within developer communications. They focus on zero-shot LLMs, such as ChatGPT and GPT-4, to automatically recognize and extract the causes behind emotional expressions such as frustration, happiness, or anger in platforms such as GitHub and Stack Overflow. Imran et al. [413] conduct an empirical study for emotion classification by fine-tuning LLMs, such as BERT, RoBERTa, CodeBERT and GraphCodeBERT. Fourth, software repository mining involves analyzing and extracting useful information from software repositories, thus helping project managers gain insights into development trends, team productivity, code quality, and project health. Abedu et

*al.* [414] explore the performance of LLMs answering questions related to software repositories to lower the barrier for stakeholders by automating the extraction and analysis of repository data.

Answer to RQ2: Overall, LLMs have been employed across various stages of SE research, tackling a diverse array of 112 tasks. On the one hand, these tasks align with previous downstream ones (detailed in Section 3.3), yet they are explored more thoroughly, such as program repair. On the other hand, researchers have turned their attention to a greater number of more complex SE tasks. These tasks may (1) include complex processes that LLMs cannot fully handle, such as fuzzing; (2) include other inputs, such as test reports and GUI testing; and (3) include some unique areas of SE, such as fuzzing. Researchers need to devote more effort to addressing these more domain-specific issues, such as designing specific LLMs or embedding them into existing research workflow. Notably, software testing and development have seen more extensive applications of LLMs. This trend may stem from the fact that these areas often serve as foundational downstream tasks for LLMs, where they have shown considerable promise. Besides, these tasks can be addressed naturally by existing LLMs in the form of sequence-to-sequence code generation. However, the application of LLMs in software requirements & design and software management is still relatively unexplored, suggesting a potential area of focus for future research in this field.

## 5 RQ3: INTEGRATION PERSPECTIVE

In the rapidly evolving field of SE, LLMs have emerged as pivotal roles, offering unprecedented opportunities for various code-related tasks. However, the integration of LLMs in SE is not without challenges due to the inherent characteristics of LLMs, such as the record-breaking parameters making it difficult to deploy in practical scenarios. This section delves into four crucial aspects of integrating LLMs for SE, focusing on evaluation and benchmarking in Section 5.1, security and reliability in Section 5.2, domain tuning in Section 5.3, and compressing and distillation in Section 5.4.

#### 5.1 Evaluation and Benchmarking

Despite an emerging research area, a variety of LLMs have been proposed and have continuously achieved promising results across a variety of SE tasks. In addition to developing new techniques that address technical challenges, the LLMbased SE research field is benefiting from empirical studies and benchmarks.

#### 5.1.1 Empirical Study

In Section 4, when introducing specific SE tasks, we have discussed corresponding empirical studies, such as program repair [327] and vulnerability repair [12]. We also notice there exist some empirical studies that systematically explore the capabilities of LLMs from a more comprehensive perspective, such as human study and educational scenarios.

Exploration for Multiple Tasks. These studies explore LLMs across multiple LLMs or tasks, providing macroscopic insights into future LLM-based SE work. In 2022, Mastropaolo et al. [415] empirically evaluate the performance of transfer learning on four code-related tasks by pre-training and fine-tuning T5, including (1) automatic bug-fixing, (2) injection of code mutants, (3) generation of assert statements, and (4) code summarization. Lu *et al.* [51] conduct an empirical study to investigate the performance of three common LLMs in the CodeXGLUE benchmark (discussed in Section 5.1.2), including the BERT-style, GPTstyle, and Encoder-Decoder models. As a pioneering work, this study only reports some preliminary results on a limited set of models. In 2022, Zeng et al. [416] conduct a comprehensive study of eight LLMs across seven code-related tasks in the CodeXGLUE dataset. The study covers three types of LLMs, including three encoder-based models (i.e., CodeBERT, GraphCodeBERT, ContraCode), one decoderonly model (*i.e.*, CodeGPT), and four encoder-decoder LLMs (i.e., CodeT5, CodeTrans, CoTexT and PLBART). The selected LLMs are evaluated on three code understanding tasks (i.e., defect detection, clone detection, and code search) and four code generation tasks (i.e., code summarization, code repair, code translation, and code generation). In 2023, Niu et al. [417] perform a large systematic study of 19 LLMs on 13 SE tasks. Besides, researchers explore the performance of LLMs in SE tasks regarding different aspects, including in-context learning [418], prompt design [419], code distributions [420].

**Human Study and Empirical Replication**. Liang *et al.* [421] explore how LLMs can be utilized to support human participation tasks in empirical software engineering. This study involves four LLMs (including ChatGPT, ERNIE Bot, Gemini, and ChatGLM) and three types of prompts (including zero-shot, one-shot, and optimized one-shot prompts). Endres *et al.* [263] investigate the potential of GPT-4 to replicate empirical software engineering research. They query GPT-4 to generate assumptions, analysis plans, and code modules based on the methodologies described in seven papers and conduct a user study involving 14 participants to evaluate the quality of the outputs generated by GPT-4.

Empirical Exploration of SE Education. In the SE community, the current research on LLMs has primarily focused on various code-related tasks and has achieved notable results. Given the powerful NL capabilities (e.g., ChatGPT) and extensive programming knowledge inherent in LLMs, their interaction with students to complete programming tasks is becoming increasingly promising. The community has engaged in empirical discussions about the potential of LLMs in the SE education scenario from various dimensions. On the one hand, it is exciting for LLMs to introduce innovative methods for learning and teaching, facilitating a more interactive and dynamic educational environment. On the other hand, there exists a growing concern regarding the potential misuse of these LLMs by students, such as relying excessively on automated solutions without developing critical problem-solving skills.

Thus, researchers explore the potential and concerns of LLMs in the SE education scenario. For example, to explore ChatGPT's effectiveness in answering software testing questions from a textbook, in 2023, Jalil et al. [422] evaluate ChatGPT with 31 questions from five topics like software faults, test driven development, and coverage criteria. The study focuses on the accuracy of ChatGPT's answers and explanations under different prompting strategies. At the same time, to explore how well ChatGPT can perform in an introductory-level functional language programming course, Geng et al. [423] select a second-year undergraduate computer science course to test ChatGPT. When LLMs (e.g., ChatGPT) are used by students during their learning processes, despite their potential, there may arise some concerns. For example, students might directly employ LLMs to complete assignments without self-thinking, leading to ineffective learning and even plagiarism concerns. To address such concerns, in 2023, Nguyen et al. [424] present an empirical study to investigate the feasibility of automated identification of AI-generated code snippets. They propose a CodeBERT-based classifier called GPTSniffer to detect source code written by LLMs. Tian et al. [425] conduct an empirical analysis of ChatGPT's potential as a fully automated programming assistant. Xue et al. [426] investigate the performance of ChatGPT in assisting students in an introductory computer science course. This study is conducted in a classroom setting and includes both quantitative and qualitative analyses to understand the impact of using ChatGPT on students' learning outcomes and behaviors during programming assignments.

#### 5.1.2 Benchmarking

Benchmarking plays a crucial role in LLM-based SE research, helping to drive the advancement of this rapidly evolving field. Existing benchmarks in the community can be broadly classified into two categories. The first category consists of existing datasets created by traditional SE research, which are generally well-established and have been validated by the community over time. Details can be found in prior SE survey papers [427], [3]. The second category includes newly developed datasets tailored specifically for LLM-based SE research. These new datasets primarily focus on two aspects: addressing challenges unique to LLMs and exploring various SE domains, summarized as follows.

First, different from traditional SE studies, the pipeline of LLM-based SE techniques is three-fold, *i.e.*, (1) a pre-training process with unsupervised learning on large datasets; (2) a fine-tuning process with supervised learning with labeled datasets; and (3) an evaluation process with limited datasets. As a result, such LLMs are usually trained from all possible open-source projects in the wild, and it is difficult to ensure there exist no samples in the evaluation benchmark that appear in the pre-training dataset, *i.e.*, the data leakage problem. To address this issue, researchers conduct new benchmarks from artifacts that are released after the training cutoff date of ChatGPT. For example, Zhang et al. [428] extensively explore the data leakage issue of ChatGPT in the program domain and introduce EvalGPTFix, a new benchmark based on competitive programming problems collected after 2021. Several other benchmarks includes HumanEval-Java [327], ConDefects [429] and HITS [430]

Second, some benchmarks are tailored for different SE scenarios. HumanEval [52] is initially released by OpenAI to evaluate the code generation capabilities of Codex and

has been the most popular benchmark in LLM-based code generation. HumanEval-X [61] is an extended version of HumanEval, specifically designed to evaluate the multilingual code generation capabilities of LLMs. Unlike HumanEval only for Python code generation, HumanEval-X supports both code generation and code translation tasks, spanning Python, C++, Java, JavaScript, and Go. EvalPlus [431] enhances HumanEval by generating additional high-quality test inputs. CodeXGlUE [51] is constructed by Microsoft to support a collection of ten code understanding and generation tasks and six programming languages. Compared with CodeXGLUE, CrossCodeBench [432] provides a larger scale and more diverse code-related tasks, including 216 tasks and more than 54M data instances. Recently, LLMs have been applied in som SE scenarios that have not been previously investigated, resulting in a gap in relevant benchmarks. As a result, with the advent of LLM-based SE techniques, researchers have also developed corresponding new datasets, such as class-level code generation [433], projectlevel code generation [137], code decompilation [227], code retrieval [434].

#### 5.2 Security and Reliability

As LLMs have been widely utilized and achieved stateof-the-art performances in various code-related tasks, the security of these models deserves an increasing number of attention. Similar to conventional deep learning models, LLMs have been shown to be vulnerable to adversarial attacks [435], i.e., generating totally different results given two semantically-identical source code snippets. This is particularly alarming given that LLMs are deployed in some mission-critical applications, such as vulnerability detection and code search. For example, an attacker can manipulate LLMs to, (1) in vulnerability detection, output a non-vulnerable label for a piece of code that actually contains vulnerabilities, with the intention of preserving the vulnerabilities in a software system; and (2) in code search, rank the malicious code snippet high in the search results such that it can be adopted in real-world deployed software, such as autonomous driving systems. Such attacks on LLMs may cause serious incidents and have a negative societal impact. In the field of SE, there has been some preliminary exploration of the attacks on LLMs for different SE tasks.

In the following, we summarize existing studies on attacking LLMs for SE, which mainly fall into four categories according to attack strategies.

Adversarial Attack for Code LLMs. An adversarial attack refers to an attempt to deceive models into making incorrect decisions or predictions by inserting subtle, imperceptible alterations to input data. In 2022, Yang *et al.* [435] propose ALERT, an adversarial attack for Code LLMs to ensure that the generated adversarial examples must maintain naturalness while preserving operational semantics to cater to human reviewers' needs. ALERT employs both Greedy-Attack and GA-Attack to search for adversarial examples, followed by conducting a user study to assess whether the substitutes generated by ALERT can produce adversarial examples that appear natural to human evaluators. ALERT conducts adversarial attacks on CodeBERT and GraphCode-BERT across three downstream tasks,*i.e.*, vulnerability prediction, clone detection, and authorship attribution. Unlike

ALERT focuses on code understanding tasks, like vulnerability detection and clone detection, Jha *et al.* [436] propose CodeAttack, the first work to perform adversarial attacks on different code generation tasks. CodeAttack attempts to generate imperceptible, effective, and minimally perturbed adversarial code samples based on code structure. CodeAttack selects representative LLMs from different categories as victim models to attack, including CodeT5, CodeBERT, GraphCodeBERT, RoBERTa, and generates adversarial samples for different tasks, including code translation, code repair, and code summarization.

Backdoor Attack for Code LLMs. A backdoor attack involves secretly making poison samples embedded with triggers (e.g., a specific word) during training, so that the target model normally performs on inputs without triggers (i.e., clean inputs) from ordinary users, but yields targeted erroneous behaviors on inputs with triggers (i.e., poison inputs) from attackers. By using triggers to activate backdoors, attackers can manipulate the output of poisoned models and lead to severe consequences. Such attacks enable perpetrators to manipulate the output of compromised models, potentially leading to severe consequences. For example, attackers can attack vulnerability detection models to mislabel a vulnerable piece of code as non-vulnerable. As early in 2021, Schuster et al. [437] perform a backdoor attack against the code completion model, including GPT-2. In 2022, Wan et al. [438] perform the first backdoor attack for code search models, including an encoder-only Code LLM CodeBERT. The attack utilizes two types of a piece of dead code as the backdoor trigger, including a piece of fixed logging code and a grammar trigger generated by the probabilistic context-free grammar.

However, the previously designed triggers (i.e., dead code snippets) are very suspicious and can be easily identified by developers [438]. Thus, focusing on more stealthy attack, in 2023, Sun et al. [439] propose BADCODE, a backdoor attack approach targeting neural code search models by altering function and variable names, BADCODE mutates function and/or variable names in the original code snippet by adding extensions to existing function/variable names, such as changing "function()" to "function\_aux()". BAD-CODE utilizes LLMs CodeBERT and CodeT5, and fine-tunes them on the CodeSearchNet dataset, using both fixed triggers and grammar triggers (PCFG) as baselines. Recently, AFRAIDOOR [440] leverages adversarial perturbations to inject adaptive triggers into code LLMs. Unlike previous studies designed for specific tasks, Li et al. [441] propose CodePoisoner, a general backdoor attack approach for three code-related tasks (*i.e.*, defect detection, clone detection, and code repair) and three models, including an LLM-based one CodeBERT. In parallel to CodePoisoner, Li et al. [442] propose a task-agnostic attack approach to train backdoored models during pre-training, so as to support the multi-target downstream tasks. The attack is designed on two LLMs (i.e., PLBART and CodeT5) and two code understanding tasks (i.e., defect detection, clone detection) and three code generation tasks (i.e., code translation, code refinement, and code generation) from CodeXGLUE.

**Imitation Attack for Code LLMs.** An imitation attack refers to an attempt to create a local model (also known as an imitation model) that mimics the behavior of a tar-

get model without having access to the target's internal architecture or training data. In 2023, Li *et al.* [443] propose the first imitation attack work to explore the feasibility of extracting specialized code abilities from LLMs sing common medium-sized models. The attack employs OpenAI's text-davinci-003 as the target LLM, CodeBERT and CodeT5 as imitation LLMs for training, and considers three coderelated tasks, *i.e.*, code synthesis, code translation and code summarization. The attack pipeline is four-fold, including (1) generating queries from LLMs tailored to different coderelated tasks and query schemes; (2)designing a rule-based filter to select high-quality responses suitable for training; and (3) fine-tuning medium-sized backbone models with these filtered responses to train the imitation model.

**Others.** In addition to the studies detailed above, researchers also explore the security and reliability of LLMs from a mass of perspectives, including human study [444], [445], [446], [447], glitch token analysis [448], testing [449], [450], [451], memorization detection [452], auto-generated code quality assurance [453], [454], [455], auto-generated code detection [456], knowledge understanding [457], model analysis [458], and jailbreak vulnerability fuzzing [459].

#### 5.3 Domain Tuning

As mentioned in Section 4, the pre-training-and-fine-tuning paradigm has been a crucial means of adapting LLMs to special domains. Typically, LLMs are first pre-trained to learn the general purpose code representations on a large amount of data and then fine-tuned to targeted tasks. While fine-tuning LLMs has proven to be effective, it comes with significant computational and energy costs due to the record-breaking parameter scale. For example, it takes about 2 days to train CodeT5 with the parameter size of 220M on NVIDIA A100-40G GPUs for program repair [460], let alone more advanced LLMs with hundreds of millions or even billions of parameters. Besides, when fine-tuning LLMs on new datasets, it is inevitable to suffer from the catastrophic forgetting problem [16], *i.e.*, forgetting the knowledge learned from previous datasets. In the field of SE, there has been some preliminary exploration of the optimizations on LLMs during the fine-tuning phase. In the following, we summarize existing studies on fine-tuning LLMs for SE, which mainly fall into three categories according to previous issues.

Efficient Parameter Fine-tuning. Such studies involve efficient training strategies to reduce the time and resource costs during fine-tuning [461], [163], [462], [463], [464]. For example, Liu *et al.* [463] conduct an empirical study to explore the performance of parameter-efficient fine-tuning methods on two LLMs and four code-related tasks, including adapter tuning, prefix tuning and low-rank adaptation. In 2023, considering that fine-tuning LLMs incurs a high computational cost, Shi *et al.* [461] attempt to reduce the number of parameters that need to be updated by selectively freezing layers that encode code basic properties well and only fine-tuning the more dynamically changing upper layers. Wang *et al.* [163] utilize adapter tuning to improve performance in code search and summarization tasks across multiple programming languages.

Effective Continual Fine-tuning Such studies involve effective training strategies to address the catastrophic forgetting issue during fine-tuning [465], [16], [466], [466]. For example, As early as 2022, Yuan et al. [16] propose a T5based program repair CIRCLE equipped with continual learning ability across multiple programming languages. The experimental results demonstrate that CIRCLE not only effectively repairs multiple programming languages in continual learning settings, but also achieves state-of-theart performance on five benchmarks with a single repair model. Since LLMs can easily forget knowledge learned from previous datasets when learning from the new dataset, in 2023, Gao et al. [465] introduce REPEAT, a method to address forgetting issues in LLMs during continual learning. REPEAT incorporates representative exemplars replay, where selected diverse and informative samples from previous datasets are used to retrain the model, preventing memory loss. Besides, Weyssow et al. [466] investigate how to adapt PLMs to the dynamic nature of software development with continual learning, including replay-based and regularization-based strategies.

**Others.** In addition to the studies mentioned above, researchers utilize various tuning strategies to adapt LLMs for the SE domain, including noise-tolerant training [467], instruction tuning [234], [468], reinforcement learning [469], [179], and prompt learning [470].

#### 5.4 Compressing and Distillation

Once LLMs are well-trained and achieve impressive results in various SE tasks, they need to be further deployed in real-world scenarios, such as integrated development environments. However, such LLMs consume hundreds of megabytes of memory and run slowly on personal devices, which results in an impediment to the wide and fluent adoption of these powerful models in the daily workflow of software developers. To address these challenges, some optimization strategies have been utilized by SE researchers to enhance the usability and practicality of LLMs during deployment. For example, Shi et al. [471] propose Compressor to compress LLMs into extremely small models without compromising performance. Compressor utilizes a genetic algorithm-based strategy to guide the process of model simplification, and adopts knowledge distillation to obtain a well-performing small model. Compressor compresses two well-known LLMs (*i.e.*, CodeBERT and GraphCodeBERT) to a size of 3 MB on two important tasks (i.e., vulnerability prediction and clone detection). Besides, Su et al. [472] introduce a smaller, distilled model with outputs generated by GPT-3.5 to generate concise natural language descriptions of source code.

Answer to RQ3: Overall, although a large amount of research effort has been devoted to how LLMs can be adapted to automate SE tasks more effectively, the literature has also seen some orthogonal works discussing the unique challenges encountered during the process of adaption. First, benchmarks play a pivotal role in shaping the trajectory of research advancements. One typical trend is the construction of new benchmarks to address the data leakage issue, *e.g.*, HumanEval, and EvalGPT-

Fix. The other typical trend is the application of various SE tasks, e.g., CodeXGLUE and CrossCodeBench. Second, researchers have constructed a mass of empirical studies to explore the actual performance of LLMs from different aspects, including multiple tasks, human study and SE education. Third, LLMs can be attacked to generate vulnerable code snippets or return the wrong classifications with different attack strategies, such as adversarial attack, backdoor attack, and imitation attack. Fouth, considering the huge parameter scale of LLMs, it is crucial to design domain-tuning strategies to adapt such LLMs in SE tasks, such as parameter and continual fine-tuning. Fifth, after LLMs are welltrained, deploying such LLMs within the development workflow necessitates further consideration of factors such as inference time and resource expenditure.

#### 6 CHALLENGES AND OPPORTUNITIES

Our survey reveals that advances in LLMs for SE have a significant impact on both academia and industry. Despite achieving promising progress, there are still numerous challenges that need to be addressed, providing abundant opportunities for further research and applications. We discuss the following important practical guidelines for future LLM-based SE research.

Trade-off between Effectiveness and Model Size. As discussed in Section 3.1, the community tends to introduce the growing size of models, resulting in the recent emergence of LLMs with record-breaking parameters, e.g., from 117M parameters of GPT-1 to 175B parameters of GPT-3. This trend is reasonable, as existing studies have demonstrated that larger models usually yield better performance, e.g., code generation [22] and program repair [11], highlighting the significance of the number of model parameters in performance enhancement. However, models with such a large number of parameters may raise some concerns during training and deployment. First, it is extremely timeconsuming and resource-intensive to train such LLMs, especially since the GPU resources required are unaffordable for most researchers in academia and even in the corporate world. For example, e.g., it takes 12 days to train the medium-sized CodeT5-base model (220M parameters) with 16 NVIDIA A100 GPUs. Second, it is difficult to deploy such LLMs in real-world scenarios, as they consume hundreds of megabytes of memory and disk space, e.g., Code Llama-34B takes about 63GB of disk space<sup>4</sup>. Thus, LLMs may run slowly on personal devices and cannot be deployed on resource-constrained or real-time terminal devices, such as mobile devices and autonomous driving.

We recommend that future work can be conducted in the following three directions. First, it is promising to optimize the size of LLMs without significantly compromising their performance, such as model pruning, quantization, and knowledge distillation [471]. Second, researchers can develop lightweight models tailored for specific applications or techniques for distributed computing, enabling parts of a model to run on different devices.

Exploring Task-oriented Domain LLMs. As discussed in Section 3.3, although LLMs are increasingly being applied in the SE community, the majority of these models are designed with general-purpose training strategies to support multiple downstream tasks. However, there are some concerns with the adoption of such general LLMs. First, LLMs need to learn general knowledge about natural language and different programming languages from extremely large datasets, leading to the model's vast size. Second, LLMs contain a vast array of knowledge, much of which is irrelevant to specific tasks. Third, their pretraining tasks are universal, creating a certain gap with the downstream tasks. For example, existing LLMs are usually trained with a given code snippet and the corresponding description, which can hardly be exploited to learn the code change patterns for some code-editing tasks that involve two code snippets. Thus, employing existing LLMs for such editing tasks will inevitably lead to inconsistent inputs and objectives between pre-training and fine-tuning.

We recommend future work to explore domain LLMs for specific tasks. For example, researchers can design LLMs specifically for unit testing scenarios (*e.g.*, test generation and update), focusing solely on learning domain knowledge relevant to unit testing with specific pre-training objectives.

Clean Evaluation Datasets. LLMs have been gaining increasing attention and demonstrated promising performance across a variety of SE tasks, such as program repair and code generation. However, there exists a potential risk of data leakage since such LLMS are usually trained with all possible public repositories in the wild. As mentioned in Section 5.1.2, researchers [18] find that some code snippets in Defects4J, the widely-adopted benchmark in the program repair literature, are leaked in CodeSearchNet, which is the most popular dataset to train LLMs, e.g., CodeT5, CodeBERT, and UniXcoder. More importantly, the greater concern arises from the black-box LLMs developed by commercial companies, which often outperform open-source LLMs. It is difficult to ensure whether or not the evaluation dataset has been seen by such LLMs during training as these LLMs are usually closed-source with unknown specific training details, e.g., pre-training datasets. For example, ChatGPT, the latest black-box LLM, has been investigated by numerous recent research studies and has shown impressive performance in various code-related tasks. However, researchers find that ChatGPT can directly provide complete descriptions and the corresponding solution by simply providing it with the number of a programming problem in LeetCode. Considering the fact there exist a quite number of black-box LLMs for which no architecture or training data information has been released. The data leaking on such LLMs is a significant concern when it comes to evaluating their performance in some code-related tasks in the SE community.

We recommend that future work can be carried out from two perspectives. First, the construction of clean datasets is crucial to ensure they have not been contaminated by LLMs. Three potential sources can be utilized for this purpose, (1) The first source comes from manually written programs. Similar to HumanEval [52], researchers can create evaluation programs by hand so as to provide a unique and uncontaminated benchmark. (2) The second source is the most

<sup>4.</sup> The model size is according to Code Llama's checkpoint implemented by HuggingFace in https://huggingface.co/codellama/ CodeLlama-34b-hf

recently released programs. Similar to EvalGPTFix [428], researchers can seek out the latest programs, such as those from recent competitions or coding challenge websites, as they often contain fresh and diverse problems that are less likely to have been included in the training sets of current LLMs. (3) The third source is closed-source projects. Researchers can evaluate LLMs with some internal projects within the company, which are not previously exposed to public repositories, thereby providing a more authentic evaluation of the models' capabilities in real-world scenarios. In addition to clean dataset construction, it is essential to design some techniques to verify whether LLMs exhibit any form of data memorization for a given testing sample, such as detecting if a model is simply recalling information from its training data rather than genuinely understanding or solving a problem.

Application on More SE Tasks. As discussed in Section 4, we observe a pronounced emphasis on the application of LLMs in software development, testing, and maintenance. These areas have undoubtedly benefited from the capabilities of LLMs, leading to impressive performance in code completion [180], fault detection [473], program repair [18] and so on. Despite its success in these tasks, there are other tasks that have been popularly studied with traditional techniques or machine/deep learning techniques. For example, the current application of LLMs in requirements engineering, software design, and software management remains relatively sparse.

We suggest that future work should concentrate on two aspects to broaden the scope of LLM applications for more SE tasks. First, for complex tasks, integrating LLMs into existing research workflows as a component rather than developing end-to-end solutions appears more pragmatic. For example, existing regression test case prioritization approaches tend to calculate the similarity of selected test cases and candidates based on code coverage and may fail to consider the semantic similarity between different test cases. Researchers can boost existing similarity-based prioritization techniques via LLMs, which contain generic knowledge pre-trained with millions of code snippets from open-source projects, and provide accurate semantic information for test code. This integration strategy leverages the strengths of LLMs in augmenting and enhancing current approaches, particularly in areas where conventional approaches have reached a plateau in terms of performance. By combining LLMs with established techniques, we can achieve more robust and efficient outcomes in complex scenarios. Second, for rare SE tasks where LLMs may lack rich knowledge, it is promising to design domain-specific LLMs tailored to these underrepresented areas. For example, a variety of medium-sized LLMs are trained with CodeSearchNet without test cases, thus failing to benefit tasks such as unit test generation.

**Multi-task and Multi-dimensional Benchmarks**. As the development of LLMs progresses, it is crucial to acquire and prepare benchmarks that are more diverse, comprehensive, and realistic to reflect capabilities in real-world scenarios. However, existing datasets may face issues related to data bias, deficiency, quality, and credibility. First, most well-constructed benchmarks are concentrated on some widely-investigated SE tasks (*e.g.*, HumanEval and CoderEval in

code generation), while lacking in other less-explored tasks like unit test generation. Second, the majority of existing evaluation dimensions focus primarily on performance metrics (*e.g.*, Pass-1 in code generation), paying little attention to other critical attributes of LLMs, such as time efficiency and robustness.

We recommend that future work can be directed in the following two areas. First, to address the limitation in task scope, researchers can build diversified benchmarks to evaluate LLMs in emerging fields, such as unit test generation. Second, to address the limitations in evaluation dimensions, new metrics, and specialized benchmarks should be introduced to assess some crucial aspects, such as robustness and efficiency.

**Beyond Text-based LLMs for Vision-based SE**. In the realm of SE, a predominant focus has been observed on LLMs that process text-based inputs, *i.e.*, natural language and source code, significantly benefiting a multitude of code-related tasks. However, alternative forms of input play an equally crucial role in SE tasks, notably images in mobile applications. For example, the graphical user interface has emerged as a crucial component of mobile applications, attracting substantial research attention in the area of GUI testing. Recently, with advancements in computer vision technologies, vision-based GUI testing approaches have been developed and have shown promising progress.

We suggest that future works focus on the utilization of multi-modal LLMs in version-based SE tasks. For example, it is potential to combine both text and image understanding capabilities of multi-modal LLMs to better capture the syntax and semantic information about source code, test scripts, and test reports in GUI testing, so as to benefit several tasks, *e.g.*, GUI test generation, GUI test record, and replay.

**Explainable LLM-based Research**. Existing LLMs usually address SE tasks in a black-box manner due to the inherent limitations of DL and the vast parameters of LLMs. The developers are unaware of why LLMs generate the predictions, thus unsure about the reliability of these results, hindering the adoption of LLM in practice. In the literature, a majority of studies focus on improving the performance of pre-defined metrics (*e.g.*, accuracy and precision), while minor focus on improving the explainability of such LLMs. Traditional rule-based SE approaches rely on pre-defined rules and logic, which makes them more interpretable and offers more transparency.

In the future, advanced explainable techniques can be considered to make the predictions of LLMs more practical, explainable, and actionable. We suggest that future work should concentrate on two aspects to support the understanding of LLMs for SE research. First, it is possible to incorporate XAI techniques to elucidate the decisionmaking process of LLMs, such as designing strategies to trace back the decision process to specific data points or model components. Second, developing hybrid frameworks that combine the interpretability of traditional rule-based approaches with the predictive power of LLMs could help in bridging the gap between traditional SE approaches and advanced LLMs, providing a balance between transparency and performance.

## 7 CONCLUSION

Large language models (LLMs) are bringing significant changes to the software engineering (SE) field, with their ability to handle complex code-related tasks poised to fundamentally reshape numerous SE practices and approaches. In this paper, we provide a comprehensive survey of existing LLM-based SE studies from both the LLM and SE perspectives. We summarize 62 representative LLMs of Code and discuss their distinct architectures, pre-training objectives, downstream tasks, and open science. We illustrate the wide range of SE tasks where LLMs have been applied, involving 947 relevant studies for 112 code-related tasks across five crucial SE phases. We highlight several crucial aspects of the optimization and application for the LLM-based SE research, including empirical evaluation, security and reliability, domain tuning, and compressing and distillation. Finally, we point out several challenges (such as the data leakage issue) and provide possible directions for future study. Overall, our work serves as a roadmap for promising future research and is valuable to both researchers and practitioners, assisting them in leveraging LLMs to improve existing SE practices.

#### REFERENCES

- J. Biolchini, P. G. Mian, A. C. C. Natali, and G. H. Travassos, "Systematic review in software engineering," System engineering and computer science department COPPE/UFRJ, Technical Report ES, vol. 679, no. 05, p. 45, 2005.
- [2] M. V. Zelkowitz, "Perspectives in software engineering," ACM Computing Surveys (CSUR), vol. 10, no. 2, pp. 197–216, 1978.
- [3] Y. Yang, X. Xia, D. Lo, and J. Grundy, "A survey on deep learning for software engineering," ACM Computing Surveys (CSUR), vol. 54, no. 10s, pp. 1–73, 2022.
- [4] J. Wang, Y. Huang, C. Chen, Z. Liu, S. Wang, and Q. Wang, "Software testing with large language model: Survey, landscape, and vision," arXiv preprint arXiv:2307.07221, 2023.
- [5] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pretraining of deep bidirectional transformers for language understanding," arXiv preprint arXiv:1810.04805, 2018.
- [6] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *The Journal of Machine Learning Research*, vol. 21, no. 1, pp. 5485–5551, 2020.
- [7] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever et al., "Language models are unsupervised multitask learners," *OpenAI blog*, vol. 1, no. 8, p. 9, 2019.
- [8] Z. Feng, D. Guo, D. Tang, N. Duan, X. Feng, M. Gong, L. Shou, B. Qin, T. Liu, D. Jiang *et al.*, "Codebert: A pre-trained model for programming and natural languages," in *Findings of the Association for Computational Linguistics: EMNLP 2020*, 2020, pp. 1536–1547.
- [9] Y. Wang, W. Wang, S. Joty, and S. C. Hoi, "Codet5: Identifieraware unified pre-trained encoder-decoder models for code understanding and generation," in *Proceedings of the 2021 Conference* on Empirical Methods in Natural Language Processing (EMNLP'21), 2021, pp. 8696–8708.
- [10] OpenAI, "Chatgpt: Optimizing language models for dialogue," https://openai.com/blog/chatgpt, 2023.
- [11] C. S. Xia, Y. Wei, and L. Zhang, "Automated program repair in the era of large pre-trained language models," in *Proceedings of the* 45th International Conference on Software Engineering (ICSE 2023). Association for Computing Machinery, 2023.
- [12] Q. Zhang, C. Fang, B. Yu, W. Sun, T. Zhang, and Z. Chen, "Pretrained model-based automated software vulnerability repair: How far are we?" *IEEE Transactions on Dependable and Secure Computing*, 2023.

- [13] C. S. Xia and L. Zhang, "Less training, more repairing please: revisiting automated program repair via zero-shot learning," in Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2022, pp. 959–971.
- [14] D. Fried, A. Aghajanyan, J. Lin, S. Wang, E. Wallace, F. Shi, R. Zhong, W.-t. Yih, L. Zettlemoyer, and M. Lewis, "Incoder: A generative model for code infilling and synthesis," arXiv preprint arXiv:2204.05999, 2022.
- [15] Y. Wu, N. Jiang, H. V. Pham, T. Lutellier, J. Davis, L. Tan, P. Babkin, and S. Shah, "How effective are neural networks for fixing security vulnerabilities," in *Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis*, ser. ISSTA 2023. Association for Computing Machinery, 2023, pp. 1282–1294.
- [16] W. Yuan, Q. Zhang, T. He, C. Fang, N. Q. V. Hung, X. Hao, and H. Yin, "Circle: Continual repair across programming languages," in *Proceedings of the 31st ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2022, pp. 678–690.
- [17] N. Nashid, M. Sintaha, and A. Mesbah, "Retrieval-based prompt selection for code-related few-shot learning," in *Proceedings of* the 45th International Conference on Software Engineering (ICSE'23), 2023.
- [18] Q. Zhang, C. Fang, T. Zhang, B. Yu, W. Sun, and Z. Chen, "Gamma: Revisiting template-based automated program repair via mask prediction," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 535–547.
- [19] C. Watson, N. Cooper, D. N. Palacio, K. Moran, and D. Poshyvanyk, "A systematic literature review on the use of deep learning in software engineering research," ACM Transactions on Software Engineering and Methodology (TOSEM), vol. 31, no. 2, pp. 1–58, 2022.
- [20] S. Wang, L. Huang, A. Gao, J. Ge, T. Zhang, H. Feng, I. Satyarth, M. Li, H. Zhang, and V. Ng, "Machine/deep learning for software engineering: A systematic literature review," *IEEE Transactions on Software Engineering*, vol. 49, no. 3, pp. 1188–1231, 2022.
  [21] C. Niu, C. Li, B. Luo, and V. Ng, "Deep learning meets software
- [21] C. Niu, C. Li, B. Luo, and V. Ng, "Deep learning meets software engineering: A survey on pre-trained models of source code," in *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence*, 2022, pp. 5546–5555.
- [22] D. Zan, B. Chen, F. Zhang, D. Lu, B. Wu, B. Guan, W. Yongji, and J.-G. Lou, "Large language models meet nl2code: A survey," in Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2023, pp. 7443– 7464.
- [23] A. Fan, B. Gokkaya, M. Harman, M. Lyubarskiy, S. Sengupta, S. Yoo, and J. M. Zhang, "Large language models for software engineering: Survey and open problems," arXiv preprint arXiv:2310.03533, 2023.
- [24] X. Hou, Y. Zhao, Y. Liu, Z. Yang, K. Wang, L. Li, X. Luo, D. Lo, J. Grundy, and H. Wang, "Large language models for software engineering: A systematic literature review," arXiv preprint arXiv:2308.10620, 2023.
- [25] H. Zhang, M. A. Babar, and P. Tell, "Identifying relevant studies in software engineering," *Information and Software Technology* (*IST*), vol. 53, no. 6, pp. 625–637, 2011.
- [26] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," Advances in neural information processing systems, vol. 30, 2017.
- [27] Z. Wang, M. Yan, J. Chen, S. Liu, and D. Zhang, "Deep learning library testing via effective model generation," in *Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2020, pp. 788–799.
- [28] Q. Zhang, C. Fang, Y. Ma, W. Sun, and Z. Chen, "A survey of learning-based automated program repair," ACM Transactions on Software Engineering and Methodology, vol. 33, no. 2, pp. 1–69, 2023.
- [29] A. Kanade, P. Maniatis, G. Balakrishnan, and K. Shi, "Learning and evaluating contextual embedding of source code," in *International conference on machine learning*. PMLR, 2020, pp. 5110–5121.
- [30] D. Guo, S. Ren, S. Lu, Z. Feng, D. Tang, S. Liu, L. Zhou, N. Duan, A. Svyatkovskiy, S. Fu *et al.*, "Graphcodebert: Pre-training code representations with data flow," *arXiv preprint arXiv*:2009.08366, 2020.
- [31] M. Mukherjee and V. J. Hellendoorn, "Stack over-flowing with

results: the case for domain-specific pre-training over one-sizefits-all models," arXiv preprint arXiv:2306.03268, 2023.

- [32] J. Lin, H. Dong, Y. Xie, and L. Zhang, "Scaling laws behind code understanding model," arXiv preprint arXiv:2402.12813, 2024.
- [33] C. B. Clement, D. Drain, J. Timcheck, A. Svyatkovskiy, and N. Sundaresan, "Pymt5: multi-mode translation of natural language and python code with transformers," arXiv preprint arXiv:2010.03150, 2020.
- [34] A. Mastropaolo, S. Scalabrino, N. Cooper, D. N. Palacio, D. Poshyvanyk, R. Oliveto, and G. Bavota, "Studying the usage of text-to-text transfer transformer to support code-related tasks," in 2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE). IEEE, 2021, pp. 336–347.
- [35] W. U. Ahmad, S. Chakraborty, B. Ray, and K.-W. Chang, "Unified pre-training for program understanding and generation," arXiv preprint arXiv:2103.06333, 2021.
- [36] D. Guo, S. Lu, N. Duan, Y. Wang, M. Zhou, and J. Yin, "Unixcoder: Unified cross-modal pre-training for code representation," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022, pp. 7212– 7225.
- [37] C. Niu, C. Li, V. Ng, J. Ge, L. Huang, and B. Luo, "Spt-code: sequence-to-sequence pre-training for learning source code representations," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 2006–2018.
- [38] H. Le, Y. Wang, A. D. Gotmare, S. Savarese, and S. C. H. Hoi, "Coderl: Mastering code generation through pretrained models and deep reinforcement learning," *Advances in Neural Information Processing Systems*, vol. 35, pp. 21 314–21 328, 2022.
- [39] J. Zhang, S. Panthaplackel, P. Nie, J. J. Li, and M. Gligoric, "Coditt5: Pretraining for source code and natural language editing," in 37th IEEE/ACM International Conference on Automated Software Engineering, 2022, pp. 1–12.
- [40] Y. Li, D. Choi, J. Chung, N. Kushman, J. Schrittwieser, R. Leblond, T. Eccles, J. Keeling, F. Gimeno, A. Dal Lago *et al.*, "Competitionlevel code generation with alphacode," *Science*, vol. 378, no. 6624, pp. 1092–1097, 2022.
- [41] Y. Wang, H. Le, A. D. Gotmare, N. D. Bui, J. Li, and S. C. Hoi, "Codet5+: Open code large language models for code understanding and generation," arXiv preprint arXiv:2305.07922, 2023.
- [42] S. Chandel, C. B. Clement, G. Serrato, and N. Sundaresan, "Training and evaluating a jupyter notebook data science assistant," arXiv preprint arXiv:2201.12901, 2022.
- [43] Y. Chai, S. Wang, C. Pang, Y. Sun, H. Tian, and H. Wu, "Ernie-code: Beyond english-centric cross-lingual pretraining for programming languages," *arXiv preprint arXiv:2212.06742*, 2022.
  [44] P. Shojaee, A. Jain, S. Tipirneni, and C. K. Reddy, "Execution-
- [44] P. Shojaee, A. Jain, S. Tipirneni, and C. K. Reddy, "Executionbased code generation using deep reinforcement learning," arXiv preprint arXiv:2301.13816, 2023.
- [45] J. Liu, Y. Zhu, K. Xiao, Q. Fu, X. Han, W. Yang, and D. Ye, "Rltf: Reinforcement learning from unit test feedback," arXiv preprint arXiv:2307.04349, 2023.
- [46] B. Lin, S. Wang, Z. Liu, Y. Liu, X. Xia, and X. Mao, "Cct5: A code-change-oriented pre-trained model," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2023, pp. 1509–1521.
- [47] Z. Yu, Y. Tao, L. Chen, T. Sun, and H. Yang, "B-coder: Value-based deep reinforcement learning for program synthesis." CoRR, 2023.
- [48] L. Gong, M. Elhoushi, and A. Cheung, "Ast-t5: Structureaware pretraining for code generation and understanding," arXiv preprint arXiv:2401.03003, 2024.
- [49] Q. Zhu, Q. Liang, Z. Sun, Y. Xiong, L. Zhang, and S. Cheng, "Grammart5: Grammar-integrated pretrained encoder-decoder neural model for code," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [50] A. Svyatkovskiy, S. K. Deng, S. Fu, and N. Sundaresan, "Intellicode compose: Code generation using transformer," in *Proceed*ings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2020, pp. 1433–1443.
- [51] S. Lu, D. Guo, S. Ren, J. Huang, A. Svyatkovskiy, A. Blanco, C. B. Clement, D. Drain, D. Jiang, D. Tang, G. Li, L. Zhou, L. Shou, L. Zhou, M. Tufano, M. Gong, M. Zhou, N. Duan, N. Sundaresan, S. K. Deng, S. Fu, and S. Liu, "Codexglue: A machine learning benchmark dataset for code understanding and generation," in *Proceedings of the Neural Information Processing Systems Track on*

Datasets and Benchmarks 1, NeurIPS Datasets and Benchmarks 2021, December 2021, virtual, J. Vanschoren and S. Yeung, Eds., 2021.

- [52] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. d. O. Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman *et al.*, "Evaluating large language models trained on code," *arXiv preprint arXiv*:2107.03374, 2021.
- [53] F. F. Xu, U. Alon, G. Neubig, and V. J. Hellendoorn, "A systematic evaluation of large language models of code," in *Proceedings* of the 6th ACM SIGPLAN International Symposium on Machine Programming, 2022, pp. 1–10.
- [54] E. Nijkamp, B. Pang, H. Hayashi, L. Tu, H. Wang, Y. Zhou, S. Savarese, and C. Xiong, "Codegen: An open large language model for code with multi-turn program synthesis," arXiv preprint arXiv:2203.13474, 2022.
- [55] D. Zan, B. Chen, D. Yang, Z. Lin, M. Kim, B. Guan, Y. Wang, W. Chen, and J.-G. Lou, "Cert: Continual pre-training on sketches for library-oriented code generation," arXiv preprint arXiv:2206.06888, 2022.
- [56] L. B. Allal, R. Li, D. Kocetkov, C. Mou, C. Akiki, C. M. Ferrandis, N. Muennighoff, M. Mishra, A. Gu, M. Dey *et al.*, "Santacoder: don't reach for the stars!" *arXiv preprint arXiv:2301.03988*, 2023.
- [57] R. Li, L. B. Allal, Y. Zi, N. Muennighoff, D. Kocetkov, C. Mou, M. Marone, C. Akiki, J. Li, J. Chim *et al.*, "Starcoder: may the source be with you!" *arXiv preprint arXiv*:2305.06161, 2023.
- [58] F. Christopoulou, G. Lampouras, M. Gritta, G. Zhang, Y. Guo, Z. Li, Q. Zhang, M. Xiao, B. Shen, L. Li et al., "Pangu-coder: Program synthesis with function-level language modeling," arXiv preprint arXiv:2207.11280, 2022.
- [59] B. Shen, J. Zhang, T. Chen, D. Zan, B. Geng, A. Fu, M. Zeng, A. Yu, J. Ji, J. Zhao *et al.*, "Pangu-coder2: Boosting large language models for code with ranking feedback," *arXiv preprint arXiv*:2307.14936, 2023.
- [60] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann et al., "Palm: Scaling language modeling with pathways," arXiv preprint arXiv:2204.02311, 2022.
- [61] Q. Zheng, X. Xia, X. Zou, Y. Dong, S. Wang, Y. Xue, Z. Wang, L. Shen, A. Wang, Y. Li *et al.*, "Codegeex: A pre-trained model for code generation with multilingual evaluations on humaneval-x," *arXiv preprint arXiv*:2303.17568, 2023.
- [62] E. Nijkamp, H. Hayashi, C. Xiong, S. Savarese, and Y. Zhou, "Codegen2: Lessons for training llms on programming and natural languages," arXiv preprint arXiv:2305.02309, 2023.
- [63] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar et al., "Llama: Open and efficient foundation language models," arXiv preprint arXiv:2302.13971, 2023.
- [64] T. Le Scao, A. Fan, C. Akiki, E. Pavlick, S. Ilić, D. Hesslow, R. Castagné, A. S. Luccioni, F. Yvon, M. Gallé et al., "Bloom: A 176b-parameter open-access multilingual language model," 2023.
- [65] P. Di, J. Li, H. Yu, W. Jiang, W. Cai, Y. Cao, C. Chen, D. Chen, H. Chen, L. Chen et al., "Codefuse-13b: A pretrained multilingual code large language model," in Proceedings of the 46th International Conference on Software Engineering: Software Engineering in Practice, 2024, pp. 418–429.
- [66] R. Xie, Z. Zeng, Z. Yu, C. Gao, S. Zhang, and W. Ye, "Codeshell technical report," arXiv preprint arXiv:2403.15747, 2024.
- [67] Y. Xu, H. Su, C. Xing, B. Mi, Q. Liu, W. Shi, B. Hui, F. Zhou, Y. Liu, T. Xie et al., "Lemur: Harmonizing natural language and code for language agents," arXiv preprint arXiv:2310.06830, 2023.
- [68] Y. Wei, Z. Wang, J. Liu, Y. Ding, and L. Zhang, "Magicoder: Empowering code generation with oss-instruct," in *Forty-first International Conference on Machine Learning*, 2024.
- [69] N. Muennighoff, Q. Liu, A. Zebaze, Q. Zheng, B. Hui, T. Y. Zhuo, S. Singh, X. Tang, L. Von Werra, and S. Longpre, "Octopack: Instruction tuning code large language models," arXiv preprint arXiv:2308.07124, 2023.
- [70] Z. Luo, C. Xu, P. Zhao, Q. Sun, X. Geng, W. Hu, C. Tao, J. Ma, Q. Lin, and D. Jiang, "Wizardcoder: Empowering code large language models with evol-instruct," arXiv preprint arXiv:2306.08568, 2023.
- [71] Z. Song, Y. Wang, W. Zhang, K. Liu, C. Lyu, D. Song, Q. Guo, H. Yan, D. Lin, K. Chen *et al.*, "Alchemistcoder: Harmonizing and eliciting code capability by hindsight tuning on multi-source data," *arXiv preprint arXiv*:2405.19265, 2024.

- [72] B. Lei, Y. Li, and Q. Chen, "Autocoder: Enhancing code large language model with\textsc {AIEV-Instruct}," arXiv preprint arXiv:2405.14906, 2024.
- [73] C. Team, "Codegemma: Open code models based on gemma," arXiv preprint arXiv:2406.11409, 2024.
- [74] D. Guo, Q. Zhu, D. Yang, Z. Xie, K. Dong, W. Zhang, G. Chen, X. Bi, Y. Wu, Y. Li et al., "Deepseek-coder: When the large language model meets programming-the rise of code intelligence," arXiv preprint arXiv:2401.14196, 2024.
- [75] Q. Zhu, D. Guo, Z. Shao, D. Yang, P. Wang, R. Xu, Y. Wu, Y. Li, H. Gao, S. Ma *et al.*, "Deepseek-coder-v2: Breaking the barrier of closed-source models in code intelligence," *arXiv preprint arXiv:2406.11931*, 2024.
- [76] Y. Wang, K. He, G. Dong, P. Wang, W. Zeng, M. Diao, Y. Mou, M. Zhang, J. Wang, X. Cai *et al.*, "Dolphcoder: Echo-locating code large language models with diverse and multi-objective instruction tuning," *arXiv preprint arXiv:2402.09136*, 2024.
- [77] M. Mishra, M. Stallone, G. Zhang, Y. Shen, A. Prasad, A. M. Soria, M. Merler, P. Selvam, S. Surendran, S. Singh *et al.*, "Granite code models: A family of open foundation models for code intelligence," arXiv preprint arXiv:2405.04324, 2024.
- [78] Y. Ding, J. Liu, Y. Wei, T. Y. Zhuo, and L. Zhang, "Xft: Unlocking the power of code instruction tuning by simply merging upcycled mixture-of-experts," arXiv preprint arXiv:2404.15247, 2024.
- [79] Y. Wu, D. Huang, W. Shi, W. Wang, L. Gao, S. Liu, Z. Nan, K. Yuan, R. Zhang, X. Zhang *et al.*, "Inversecoder: Unleashing the power of instruction-tuned code llms with inverse-instruct," *arXiv preprint arXiv*:2407.05700, 2024.
- [80] K. Rathinasamy, A. Kumar, G. Gayari, R. A. Mondal, S. Singh et al., "Narrow transformer: Starcoder-based java-lm for desktop," arXiv preprint arXiv:2407.03941, 2024.
- [81] A. Lozhkov, R. Li, L. B. Allal, F. Cassano, J. Lamy-Poirier, N. Tazi, A. Tang, D. Pykhtar, J. Liu, Y. Wei *et al.*, "Starcoder 2 and the stack v2: The next generation," *arXiv preprint arXiv*:2402.19173, 2024.
- [82] T. Sun, L. Chai, J. Yang, Y. Yin, H. Guo, J. Liu, B. Wang, L. Yang, and Z. Li, "Unicoder: Scaling code large language model via universal code," arXiv preprint arXiv:2406.16441, 2024.
- [83] Z. Yu, X. Zhang, N. Shang, Y. Huang, C. Xu, Y. Zhao, W. Hu, and Q. Yin, "Wavecoder: Widespread and versatile enhancement for code large language models by instruction tuning," in *Proceedings* of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2024, pp. 5140–5153.
- [84] W. X. Zhao, K. Zhou, J. Li, T. Tang, X. Wang, Y. Hou, Y. Min, B. Zhang, J. Zhang, Z. Dong et al., "A survey of large language models," arXiv preprint arXiv:2303.18223, 2023.
- [85] S. Yin, C. Fu, S. Zhao, K. Li, X. Sun, T. Xu, and E. Chen, "A survey on multimodal large language models," arXiv preprint arXiv:2306.13549, 2023.
- [86] B. Roziere, J. Gehring, F. Gloeckle, S. Sootla, I. Gat, X. E. Tan, Y. Adi, J. Liu, T. Remez, J. Rapin *et al.*, "Code llama: Open foundation models for code," *arXiv preprint arXiv:2308.12950*, 2023.
- [87] K. Clark, M.-T. Luong, Q. V. Le, and C. D. Manning, "Electra: Pretraining text encoders as discriminators rather than generators," arXiv preprint arXiv:2003.10555, 2020.
- [88] D. Xie, B. Yoo, N. Jiang, M. Kim, L. Tan, X. Zhang, and J. S. Lee, "Impact of large language models on generating software specifications," arXiv preprint arXiv:2306.03324, 2023.
- [89] L. Ma, S. Liu, Y. Li, X. Xie, and L. Bu, "Specgen: Automated generation of formal program specifications via large language models," arXiv preprint arXiv:2401.08807, 2024.
- [90] S. Mandal, A. Chethan, V. Janfaza, S. Mahmud, T. A. Anderson, J. Turek, J. J. Tithi, and A. Muzahid, "Large language models based automatic synthesis of software specifications," arXiv preprint arXiv:2304.09181, 2023.
- [91] T. Hey, J. Keim, A. Koziolek, and W. F. Tichy, "Norbert: Transfer learning for requirements classification," in 2020 IEEE 28th International Requirements Engineering Conference (RE), 2020, pp. 169–179.
- [92] M. A. Khan, M. S. Khan, I. Khan, S. Ahmad, and S. Huda, "Non functional requirements identification and classification using transfer learning model," *IEEE Access*, 2023.
- [93] K. Rahman, A. Ghani, A. Alzahrani, M. U. Tariq, and A. U. Rahman, "Pre-trained model-based nfr classification: Overcoming limited data challenges," *IEEE Access*, 2023.
- [94] L. Han, Q. Zhou, and T. Li, "Improving requirements classification models based on explainable requirements concerns," in

2023 IEEE 31st International Requirements Engineering Conference Workshops (REW). IEEE, 2023, pp. 95–101.

- [95] S. Lubos, A. Felfernig, T. N. T. Tran, D. Garber, M. El Mansi, S. P. Erdeniz, and V.-M. Le, "Leveraging llms for the quality assurance of software requirements," in 2024 IEEE 32nd International Requirements Engineering Conference (RE). IEEE, 2024, pp. 389– 397.
- [96] A.-R. Preda, C. Mayr-Dorn, A. Mashkoor, and A. Egyed, "Supporting high-level to low-level requirements coverage reviewing with large language models," in *Proceedings of the 21st International Conference on Mining Software Repositories*, 2024, pp. 242– 253.
- [97] A. Poudel, J. Lin, and J. Cleland-Huang, "Leveraging transformer-based language models to automate requirements satisfaction assessment," arXiv preprint arXiv:2312.04463, 2023.
- [98] K. Ronanki, B. Cabrero-Daniel, and C. Berger, "Chatgpt as a tool for user story quality evaluation: Trustworthy out of the box?" in *International Conference on Agile Software Development*. Springer, 2022, pp. 173–181.
- [99] M. R. Hasan, J. Li, I. Ahmed, and H. Bagheri, "Automated repair of declarative software specifications in the era of large language models," arXiv preprint arXiv:2310.12425, 2023.
- [100] A. Moharil and A. Sharma, "Tabasco: A transformer based contextualization toolkit," *Science of Computer Programming*, vol. 230, p. 102994, 2023.
- [101] —, "Identification of intra-domain ambiguity using transformer-based machine learning," in *Proceedings of the* 1st International Workshop on Natural Language-based Software Engineering, 2022, pp. 51–58.
- [102] S. Ezzini, S. Abualhaija, C. Arora, and M. Sabetzadeh, "Automated handling of anaphoric ambiguity in requirements: a multisolution study," in *Proceedings of the 44th International Conference* on Software Engineering, 2022, pp. 187–199.
- [103] G. Sridhara, S. Mazumdar et al., "Chatgpt: A study on its utility for ubiquitous software engineering tasks," arXiv preprint arXiv:2305.16837, 2023.
- [104] K. Kolthoff, C. Bartelt, and S. P. Ponzetto, "Data-driven prototyping via natural-language-based gui retrieval," *Automated software engineering*, vol. 30, no. 1, p. 13, 2023.
- [105] P. Brie, N. Burny, A. Sluÿters, and J. Vanderdonckt, "Evaluating a large language model on searching for gui layouts," *Proceedings* of the ACM on Human-Computer Interaction, vol. 7, no. EICS, pp. 1–37, 2023.
- [106] Z. Li, S. Dutta, and M. Naik, "Llm-assisted static analysis for detecting security vulnerabilities," arXiv preprint arXiv:2405.17238, 2024.
- [107] D. Luitel, S. Hassani, and M. Sabetzadeh, "Improving requirements completeness: Automated assistance through large language models," *Requirements Engineering*, vol. 29, no. 1, pp. 73–95, 2024.
- [108] S. Ren, H. Nakagawa, and T. Tsuchiya, "Combining prompts with examples to enhance llm-based requirement elicitation," in 2024 IEEE 48th Annual Computers, Software, and Applications Conference (COMPSAC). IEEE, 2024, pp. 1376–1381.
- [109] M. A. Sami, Z. Rasheed, M. Waseem, Z. Zhang, T. Herda, and P. Abrahamsson, "Prioritizing software requirements using large language models," arXiv preprint arXiv:2405.01564, 2024.
- [110] C. Jain, P. R. Anish, A. Singh, and S. Ghaisas, "A transformerbased approach for abstractive summarization of requirements from obligations in software engineering contracts," in 2023 IEEE 31st International Requirements Engineering Conference (RE). IEEE, 2023, pp. 169–179.
- [111] J. L. Guo, J.-P. Steghöfer, A. Vogelsang, and J. Cleland-Huang, "Natural language processing for requirements traceability," arXiv preprint arXiv:2405.10845, 2024.
- [112] J. Lin, Y. Liu, Q. Zeng, M. Jiang, and J. Cleland-Huang, "Traceability transformed: Generating more accurate links with pre-trained bert models," in 2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE). IEEE, 2021, pp. 324–335.
- [113] M. B. Chaaben, L. Burgueño, and H. Sahraoui, "Towards using few-shot prompt learning for automating model completion," in 2023 IEEE/ACM 45th International Conference on Software Engineering: New Ideas and Emerging Results (ICSE-NIER). IEEE, 2023, pp. 7–12.
- [114] A. Ferrari, S. Abualhaija, and C. Arora, "Model generation from requirements with llms: an exploratory study," arXiv preprint arXiv:2404.06371, 2024.

- [115] S. Zhang, J. Wang, G. Dong, J. Sun, Y. Zhang, and G. Pu, "Experimenting a new programming practice with llms," arXiv preprint arXiv:2401.01062, 2024.
- [116] G. Yang, Y. Zhou, X. Chen, X. Zhang, Y. Xu, T. Han, and T. Chen, "A syntax-guided multi-task learning approach for turduckenstyle code generation," *Empirical Software Engineering*, vol. 28, no. 6, p. 141, 2023.
- [117] X. Jiang, Y. Dong, L. Wang, F. Zheng, Q. Shang, G. Li, Z. Jin, and W. Jiao, "Self-planning code generation with large language models," ACM Transactions on Software Engineering and Methodology.
- [118] S. Zhang, Z. Chen, Y. Shen, M. Ding, J. B. Tenenbaum, and C. Gan, "Planning with large language models for code generation," arXiv preprint arXiv:2303.05510, 2023.
- [119] H. Han, J. Kim, J. Yoo, Y. Lee, and S.-w. Hwang, "Archcode: Incorporating software requirements in code generation with large language models," arXiv preprint arXiv:2408.00994, 2024.
- [120] F. Mu, L. Shi, S. Wang, Z. Yu, B. Zhang, C. Wang, S. Liu, and Q. Wang, "Clarifygpt: Empowering llm-based code generation with intention clarification," arXiv preprint arXiv:2310.10996, 2023.
- [121] J. Li, Y. Zhao, Y. Li, G. Li, and Z. Jin, "Acecoder: An effective prompting technique specialized in code generation," ACM Transactions on Software Engineering and Methodology, 2024.
- [122] A. Ni, S. Iyer, D. Radev, V. Stoyanov, W.-t. Yih, S. Wang, and X. V. Lin, "Lever: Learning to verify language-to-code generation with execution," in *International Conference on Machine Learning*. PMLR, 2023, pp. 26106–26128.
- [123] X. Chen, M. Lin, N. Schärli, and D. Zhou, "Teaching large language models to self-debug," arXiv preprint arXiv:2304.05128, 2023.
- [124] A. Chen, J. Scheurer, T. Korbak, J. A. Campos, J. S. Chan, S. R. Bowman, K. Cho, and E. Perez, "Improving code generation by training with natural language feedback," *arXiv preprint arXiv*:2303.16749, 2023.
- [125] K. Zhang, Z. Li, J. Li, G. Li, and Z. Jin, "Self-edit: Fault-aware code editor for code generation," arXiv preprint arXiv:2305.04087, 2023.
- [126] Y. Dong, X. Jiang, Z. Jin, and G. Li, "Self-collaboration code generation via chatgpt," ACM Trans. Softw. Eng. Methodol., jun 2024, just Accepted. [Online]. Available: https: //doi.org/10.1145/3672459
- [127] A. Mastropaolo, L. Pascarella, E. Guglielmi, M. Ciniselli, S. Scalabrino, R. Oliveto, and G. Bavota, "On the robustness of code generation techniques: An empirical study on github copilot," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2149–2160.
- [128] L. Zhong and Z. Wang, "Can llm replace stack overflow? a study on robustness and reliability of large language model code generation," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 19, 2024, pp. 21841–21849.
- [129] T. Coignion, C. Quinton, and R. Rouvoy, "A performance study of llm-generated code on leetcode," in *Proceedings of the 28th International Conference on Evaluation and Assessment in Software Engineering*, 2024, pp. 79–89.
- [130] K. Jin, C.-Y. Wang, H. V. Pham, and H. Hemmati, "Can chatgpt support developers? an empirical evaluation of large language models for code generation," in 2024 IEEE/ACM 21st International Conference on Mining Software Repositories (MSR). IEEE, 2024, pp. 167–171.
- [131] Y. Feng, S. Vanam, M. Cherukupally, W. Zheng, M. Qiu, and H. Chen, "Investigating code generation performance of chatgpt with crowdsourcing social data," in 2023 IEEE 47th Annual Computers, Software, and Applications Conference (COMPSAC). IEEE, 2023, pp. 876–885.
- [132] B. Kou, S. Chen, Z. Wang, L. Ma, and T. Zhang, "Do large language models pay similar attention like human programmers when generating code?" *Proc. ACM Softw. Eng.*, vol. 1, no. FSE, 2024. [Online]. Available: https://doi.org/10.1145/3660807
- [133] C. Liu, X. Bao, H. Zhang, N. Zhang, H. Hu, X. Zhang, and M. Yan, "Guiding chatgpt for better code generation: An empirical study," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 102–113.
- [134] D. Yan, Z. Gao, and Z. Liu, "A closer look at different difficulty levels code generation abilities of chatgpt," in 2023 38th

IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 1887–1898.

- [135] C. Liu, X. Bao, H. Zhang, N. Zhang, H. Hu, X. Zhang, and M. Yan, "Improving chatgpt prompt for code generation," arXiv preprint arXiv:2305.08360, 2023.
- [136] F. Cassano, J. Gouwar, D. Nguyen, S. Nguyen, L. Phipps-Costin, D. Pinckney, M.-H. Yee, Y. Zi, C. J. Anderson, M. Q. Feldman *et al.*, "Multipl-e: a scalable and polyglot approach to benchmarking neural code generation," *IEEE Transactions on Software Engineering*, vol. 49, no. 7, pp. 3675–3691, 2023.
- [137] H. Yu, B. Shen, D. Ran, J. Zhang, Q. Zhang, Y. Ma, G. Liang, Y. Li, Q. Wang, and T. Xie, "Codereval: A benchmark of pragmatic code generation with generative pre-trained models," in *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, 2024, pp. 1–12.
- [138] M. Chen, H. Zhang, C. Wan, Z. Wei, Y. Xu, J. Wang, and X. Gu, "On the effectiveness of large language models in domainspecific code generation," arXiv preprint arXiv:2312.01639, 2023.
- [139] B. Kou, S. Chen, Z. Wang, L. Ma, and T. Zhang, "Do large language models pay similar attention like human programmers when generating code?" *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 2261–2284, 2024.
- [140] R. Bairi, A. Sonwane, A. Kanade, A. Iyer, S. Parthasarathy, S. Rajamani, B. Ashok, and S. Shet, "Codeplan: Repository-level coding using llms and planning," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 675–698, 2024.
- [141] Z. Ma, S. An, B. Xie, and Z. Lin, "Compositional api recommendation for library-oriented code generation," in *Proceedings of the* 32nd IEEE/ACM International Conference on Program Comprehension, 2024, pp. 87–98.
- [142] M. Liu, T. Yang, Y. Lou, X. Du, Y. Wang, and X. Peng, "Codegen4libs: A two-stage approach for library-oriented code generation," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 434–445.
- [143] J. Li, Y. Li, G. Li, Z. Jin, Y. Hao, and X. Hu, "Skcoder: A sketch-based approach for automatic code generation," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2124–2135.
- [144] F. Lin, D. J. Kim *et al.*, "When llm-based code generation meets the software development process," *arXiv preprint arXiv*:2403.15852, 2024.
- [145] D. Huang, Q. Bu, J. M. Zhang, M. Luck, and H. Cui, "Agentcoder: Multi-agent-based code generation with iterative testing and optimisation," arXiv preprint arXiv:2312.13010, 2023.
- [146] K. Zhang, J. Li, G. Li, X. Shi, and Z. Jin, "Codeagent: Enhancing code generation with tool-integrated agent systems for real-world repo-level coding challenges," arXiv preprint arXiv:2401.07339, 2024.
- [147] J. Li, F. Liu, J. Li, Y. Zhao, G. Li, and Z. Jin, "Mcodesearcher: Multi-view contrastive learning for code search," in *Proceedings* of the 14th Asia-Pacific Symposium on Internetware, 2023, pp. 270– 280.
- [148] S. Liu, B. Wu, X. Xie, G. Meng, and Y. Liu, "Contrabert: Enhancing code pre-trained models via contrastive learning," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE Computer Society, 2023, pp. 2476–2487.
- [149] Z. Shi, Y. Xiong, X. Zhang, Y. Zhang, S. Li, and Y. Zhu, "Crossmodal contrastive learning for code search," in 2022 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2022, pp. 94–105.
- [150] Z. Shi, Y. Xiong, Y. Zhang, Z. Jiang, J. Zhao, L. Wang, and S. Li, "Improving code search with multi-modal momentum contrastive learning," in 2023 IEEE/ACM 31st International Conference on Program Comprehension (ICPC). IEEE, 2023, pp. 280–291.
- [151] X. Li, Y. Gong, Y. Shen, X. Qiu, H. Zhang, B. Yao, W. Qi, D. Jiang, W. Chen, and N. Duan, "Coderetriever: A large scale contrastive pre-training method for code search," in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, 2022, pp. 2898–2910.
- [152] E. Shi, Y. Wang, W. Gu, L. Du, H. Zhang, S. Han, D. Zhang, and H. Sun, "Cocosoda: Effective contrastive learning for code search," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2198–2210.
- [153] P. Salza, C. Schwizer, J. Gu, and H. C. Gall, "On the effectiveness of transfer learning for code search," *IEEE Transactions on Software Engineering*, 2022.

- [154] K. Chi, C. Li, J. Ge, and B. Luo, "An empirical study on code search pre-trained models: Academic progresses vs. industry requirements," in *Proceedings of the 15th Asia-Pacific Symposium* on Internetware, 2024, pp. 41–50.
- [155] Z. Yang, F. Liu, Z. Yu, J. W. Keung, J. Li, S. Liu, Y. Hong, X. Ma, Z. Jin, and G. Li, "Exploring and unleashing the power of large language models in automated code translation," *arXiv preprint arXiv*:2404.14646, 2024.
- [156] B. Wang, R. Li, M. Li, and P. Saxena, "Transmap: Pinpointing mistakes in neural code translation," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on* the Foundations of Software Engineering, 2023, pp. 999–1011.
- [157] R. Pan, A. R. Ibrahimzada, R. Krishna, D. Sankar, L. P. Wassi, M. Merler, B. Sobolev, R. Pavuluri, S. Sinha, and R. Jabbarvand, "Lost in translation: A study of bugs introduced by large language models while translating code," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE, 2024, pp. 995–1007.
- [158] M. Jiao, T. Yu, X. Li, G. Qiu, X. Gu, and B. Shen, "On the evaluation of neural code translation: Taxonomy and benchmark," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 1529–1541.
- [159] J. Zhang, P. Nie, J. J. Li, and M. Gligoric, "Multilingual code co-evolution using large language models," in *Proceedings of* the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 695–707.
- [160] A. Mastropaolo, E. Aghajani, L. Pascarella, and G. Bavota, "An empirical study on code comment completion," in 2021 IEEE International Conference on Software Maintenance and Evolution (IC-SME). IEEE, 2021, pp. 159–170.
- [161] L. Li, B. Liang, L. Chen, and X. Zhang, "Cross-modal retrievalenhanced code summarization based on joint learning for retrieval and generation," *Information and Software Technology*, vol. 175, p. 107527, 2024.
- [162] C. Fang, W. Sun, Y. Chen, X. Chen, Z. Wei, Q. Zhang, Y. You, B. Luo, Y. Liu, and Z. Chen, "Esale: Enhancing code-summary alignment learning for source code summarization," *IEEE Transactions on Software Engineering*, 2024.
- [163] D. Wang, B. Chen, S. Li, W. Luo, S. Peng, W. Dong, and X. Liao, "One adapter for all programming languages? adapter tuning for code search and summarization," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 5–16.
- [164] M. Geng, S. Wang, D. Dong, H. Wang, G. Li, Z. Jin, X. Mao, and X. Liao, "Large language models are few-shot summarizers: Multi-intent comment generation via in-context learning," in *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, 2024, pp. 1–13.
- [165] C. Wang, Y. Lou, J. Liu, and X. Peng, "Generating variable explanations via zero-shot prompt learning," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 748–760.
- [166] T. Ahmed, K. S. Pai, P. Devanbu, and E. T. Barr, "Automatic semantic augmentation of language model prompts (for code summarization)," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE Computer Society, 2024, pp. 2720–2732.
- [167] S. A. Rukmono, L. Ochoa, and M. R. Chaudron, "Achieving highlevel software component summarization via hierarchical chainof-thought prompting and static code analysis," in 2023 IEEE International Conference on Data and Software Engineering (ICoDSE). IEEE, 2023, pp. 7–12.
- [168] J. Li, Y. Zhang, Z. Karas, C. McMillan, K. Leach, and Y. Huang, "Do machines and humans focus on similar code? exploring explainability of large language models in code summarization," in *Proceedings of the 32nd IEEE/ACM International Conference on Program Comprehension*, 2024, pp. 47–51.
- [169] X. Jin and Z. Lin, "Simllm: Calculating semantic similarity in code summaries using a large language model-based approach," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1376–1399, 2024.
- [170] X. Jin, J. Larson, W. Yang, and Z. Lin, "Binary code summarization: Benchmarking chatgpt/gpt-4 and other large language models," arXiv preprint arXiv:2312.09601, 2023.
- [171] W. Sun, C. Fang, Y. You, Y. Miao, Y. Liu, Y. Li, G. Deng, S. Huang,

Y. Chen, Q. Zhang *et al.*, "Automatic code summarization via chatgpt: How far are we?" *arXiv preprint arXiv:2305.12865*, 2023.

- [172] P. Nie, R. Banerjee, J. J. Li, R. J. Mooney, and M. Gligoric, "Learning deep semantics for test completion," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2111–2123.
- [173] Z. Li, C. Wang, Z. Liu, H. Wang, D. Chen, S. Wang, and C. Gao, "Cctest: Testing and repairing code completion systems," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 1238–1250.
- [174] W. Liu, A. Yu, D. Zan, B. Shen, W. Zhang, H. Zhao, Z. Jin, and Q. Wang, "Graphcoder: Enhancing repository-level code completion via code context graph-based retrieval and language model," arXiv preprint arXiv:2406.07003, 2024.
- [175] W. Cheng, Y. Wu, and W. Hu, "Dataflow-guided retrieval augmentation for repository-level code completion," arXiv preprint arXiv:2405.19782, 2024.
- [176] D. Wu, W. U. Ahmad, D. Zhang, M. K. Ramanathan, and X. Ma, "Repoformer: Selective retrieval for repository-level code completion," arXiv preprint arXiv:2403.10059, 2024.
- [177] H. N. Phan, H. N. Phan, T. N. Nguyen, and N. D. Bui, "Repohyper: Better context retrieval is all you need for repository-level code completion," arXiv preprint arXiv:2403.06095, 2024.
- [178] J. Liu, Y. Chen, M. Liu, X. Peng, and Y. Lou, "Stall+: Boosting llm-based repository-level code completion with static analysis," arXiv preprint arXiv:2406.10018, 2024.
- [179] Y. Wang, Y. Wang, D. Guo, J. Chen, R. Zhang, Y. Ma, and Z. Zheng, "Rlcoder: Reinforcement learning for repository-level code completion," arXiv preprint arXiv:2407.19487, 2024.
- [180] M. Ciniselli, N. Cooper, L. Pascarella, D. Poshyvanyk, M. Di Penta, and G. Bavota, "An empirical study on the usage of bert models for code completion," in 2021 IEEE/ACM 18th International Conference on Mining Software Repositories (MSR). IEEE, 2021, pp. 108–119.
- [181] M. Ciniselli, N. Cooper, L. Pascarella, A. Mastropaolo, E. Aghajani, D. Poshyvanyk, M. Di Penta, and G. Bavota, "An empirical study on the usage of transformer models for code completion," *IEEE Transactions on Software Engineering*, vol. 48, no. 12, pp. 4818– 4837, 2021.
- [182] T. van Dam, M. Izadi, and A. van Deursen, "Enriching source code with contextual data for code completion models: An empirical study," arXiv preprint arXiv:2304.12269, 2023.
- [183] N. Jain, S. Vaidyanath, A. Iyer, N. Natarajan, S. Parthasarathy, S. Rajamani, and R. Sharma, "Jigsaw: Large language models meet program synthesis," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 1219–1231.
- [184] V. Liventsev, A. Grishina, A. Härmä, and L. Moonen, "Fully autonomous programming with large language models," arXiv preprint arXiv:2304.10423, 2023.
- [185] D. Vella Zarb, G. Parks, and T. Kipouros, "Synergistic utilization of llms for program synthesis," in *Proceedings of the Genetic and Evolutionary Computation Conference Companion*, 2024, pp. 539– 542.
- [186] J. Li, G. Li, Z. Li, Z. Jin, X. Hu, K. Zhang, and Z. Fu, "Codeeditor: Learning to edit source code with pre-trained models," ACM Transactions on Software Engineering and Methodology, vol. 32, no. 6, pp. 1–22, 2023.
- [187] P. Gupta, A. Khare, Y. Bajpai, S. Chakraborty, S. Gulwani, A. Kanade, A. Radhakrishna, G. Soares, and A. Tiwari, "Grace: Generation using associated code edits," arXiv preprint arXiv:2305.14129, 2023.
- [188] C. Liu, P. Cetin, Y. Patodia, B. Ray, S. Chakraborty, and Y. Ding, "Automated code editing with search-generate-modify," in *Proceedings of the 2024 IEEE/ACM 46th International Conference on Software Engineering: Companion Proceedings*, 2024, pp. 398–399.
- [189] J. Y. Khan, M. T. I. Khondaker, G. Uddin, and A. Iqbal, "Automatic detection of five api documentation smells: Practitioners' perspectives," in 2021 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2021, pp. 318–329.
- [190] Q. Huang, Y. Wu, Z. Xing, H. Jiang, Y. Cheng, and H. Jin, "Adaptive intellect unleashed: The feasibility of knowledge transfer in large language models," arXiv preprint arXiv:2308.04788, 2023.
- [191] S. Wang, S. Jean, S. Sengupta, J. Gung, N. Pappas, and Y. Zhang, "Measuring and mitigating constraint violations of in-context learning for utterance-to-api semantic parsing," arXiv preprint arXiv:2305.15338, 2023.

- [192] T. Y. Zhuo, X. Du, Z. Xing, J. Sun, H. Quan, L. Li, and L. Zhu, "Pop quiz! do pre-trained code models possess knowledge of correct api names?" arXiv preprint arXiv:2309.07804, 2023.
- [193] Q. Huang, Z. Wan, Z. Xing, C. Wang, J. Chen, X. Xu, and Q. Lu, "Let's chat to find the apis: Connecting human, llm and knowledge graph through ai chain," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 471–483.
- [194] M. Wei, N. S. Harzevili, Y. Huang, J. Wang, and S. Wang, "Clear: contrastive learning for api recommendation," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 376–387.
- [195] Z. Li, C. Li, Z. Tang, W. Huang, J. Ge, B. Luo, V. Ng, T. Wang, Y. Hu, and X. Zhang, "Ptm-apirec: Leveraging pre-trained models of source code in api recommendation," *ACM Transactions on Software Engineering and Methodology*, vol. 33, no. 3, pp. 1–30, 2024.
  [196] K. Zhang, H. Zhang, G. Li, J. Li, Z. Li, and Z. Jin, "Toolcoder:
- [196] K. Zhang, H. Zhang, G. Li, J. Li, Z. Li, and Z. Jin, "Toolcoder: Teach code generation models to use api search tools," arXiv preprint arXiv:2305.04032, 2023.
- [197] Y. Chen, C. Gao, M. Zhu, Q. Liao, Y. Wang, and G. Xu, "Apigen: Generative api method recommendation," *arXiv preprint arXiv:2401.15843*, 2024.
- [198] D. Wu, Y. Feng, H. Zhang, and B. Xu, "Automatic recognizing relevant fragments of apis using api references," *Automated Software Engineering*, vol. 31, no. 1, p. 3, 2024.
- [199] H. Gilbert, M. Sandborn, D. C. Schmidt, J. Spencer-Smith, and J. White, "Semantic compression with large language models," *arXiv preprint arXiv:2304.12512*, 2023.
- [200] J. Von der Mosel, A. Trautsch, and S. Herbold, "On the validity of pre-trained transformers for natural language processing in the software engineering domain," *IEEE Transactions on Software Engineering*, vol. 49, no. 4, pp. 1487–1507, 2022.
- [201] Y. Lin, C. Wan, S. Bai, and X. Gu, "Vargan: Adversarial learning of variable semantic representations," *IEEE Transactions on Software Engineering*, 2024.
- [202] I. Saberi and F. H. Fard, "Model-agnostic syntactical information for pre-trained programming language models," in 2023 IEEE/ACM 20th International Conference on Mining Software Repositories (MSR). IEEE, 2023, pp. 183–193.
- [203] L. Cui, J. Yin, J. Cui, Y. Ji, P. Liu, Z. Hao, and X. Yun, "Api2vec++: Boosting api sequence representation for malware detection and classification," *IEEE Transactions on Software Engineering*, 2024.
- [204] M. Agarwal, Y. Shen, B. Wang, Y. Kim, and J. Chen, "Structured code representations enable data-efficient adaptation of code language models," arXiv preprint arXiv:2401.10716, 2024.
- [205] J. He, X. Zhou, B. Xu, T. Zhang, K. Kim, Z. Yang, F. Thung, I. C. Irsan, and D. Lo, "Representation learning for stack overflow posts: How far are we?" ACM Transactions on Software Engineering and Methodology, vol. 33, no. 3, pp. 1–24, 2024.
- [206] J. Zhao, Y. Rong, Y. Guo, Y. He, and H. Chen, "Understanding programs by exploiting (fuzzing) test cases," arXiv preprint arXiv:2305.13592, 2023.
- [207] D. Shen, X. Chen, C. Wang, K. Sen, and D. Song, "Benchmarking language models for code syntax understanding," arXiv preprint arXiv:2210.14473, 2022.
- [208] A. Khakhar, S. Mell, and O. Bastani, "Pac prediction sets for large language models of code," in *International Conference on Machine Learning*. PMLR, 2023, pp. 16237–16249.
- [209] T. Baral, S. Rahman, B. N. Chanumolu, B. Balcı, T. Tuncer, A. Shi, and W. Lam, "Optimizing continuous development by detecting and preventing unnecessary content generation," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 901–913.
- [210] J. Zhang, S. Liu, L. Gong, H. Zhang, Z. Huang, and H. Jiang, "Beqain: An effective and efficient identifier normalization approach with bert and the question answering system," *IEEE Transactions* on Software Engineering, vol. 49, no. 4, pp. 2597–2620, 2022.
- [211] A. S. Alsayed, H. K. Dam, and C. Nguyen, "Microrec: Leveraging large language models for microservice recommendation," in 2024 IEEE/ACM 21st International Conference on Mining Software Repositories (MSR). IEEE, 2024, pp. 419–430.
- [212] M. U. Nasir, S. Earle, J. Togelius, S. James, and C. Cleghorn, "Llmatic: Neural architecture search via large language models and quality diversity optimization," in *Proceedings of the Genetic* and Evolutionary Computation Conference, 2024, pp. 1110–1118.
- [213] B. H. Banday, T. Z. Islam, and A. Marathe, "Perfgen: A synthesis and evaluation framework for performance data using generative

ai," in 2024 IEEE 48th Annual Computers, Software, and Applications Conference (COMPSAC). IEEE, 2024, pp. 188–197.

- [214] D. A. Le, A. M. Bui, P. T. Nguyen, and D. Di Ruscio, "Good things come in three: Generating so post titles with pre-trained models, self improvement and post ranking," arXiv preprint arXiv:2406.15633, 2024.
- [215] K. Jesse, P. T. Devanbu, and A. Sawant, "Learning to predict userdefined types," *IEEE Transactions on Software Engineering*, vol. 49, no. 4, pp. 1508–1522, 2022.
- [216] C. Qian, W. Liu, H. Liu, N. Chen, Y. Dang, J. Li, C. Yang, W. Chen, Y. Su, X. Cong et al., "Chatdev: Communicative agents for software development," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024, pp. 15174–15186.
- [217] Z. Zhu, Y. Wang, and Y. Li, "Trobo: A novel deep transfer model for enhancing cross-project bug localization," in *Knowledge Science, Engineering and Management: 14th International Conference, KSEM 2021, Tokyo, Japan, August 14–16, 2021, Proceedings, Part I.* Springer, 2021, pp. 529–541.
- [218] A. Ciborowska and K. Damevski, "Fast changeset-based bug localization with bert," in *Proceedings of the 44th International Conference on Software Engineering (ICSE'22), 2022, pp. 946–957.*
- [219] M. Chandramohan, D. Q. Nguyen, P. Krishnan, and J. Jancic, "Supporting cross-language cross-project bug localization using pre-trained language models," arXiv preprint arXiv:2407.02732, 2024.
- [220] Y. Wu, Z. Li, J. M. Zhang, M. Papadakis, M. Harman, and Y. Liu, "Large language models in fault localisation," arXiv preprint arXiv:2308.15276, 2023.
- [221] S. Kang, G. An, and S. Yoo, "A quantitative and qualitative evaluation of llm-based explainable fault localization," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1424–1446, 2024.
- [222] A. Z. Yang, C. Le Goues, R. Martins, and V. J. Hellendoorn, "Large language models for test-free fault localization," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE, 2024, pp. 165–176.
- [223] R. Widyasari, J. W. Ang, T. G. Nguyen, N. Sharma, and D. Lo, "Demystifying faulty code: Step-by-step reasoning for explainable fault localization," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 568–579.
  [224] X. Xu, Z. Zhang, S. Feng, Y. Ye, Z. Su, N. Jiang, S. Cheng, L. Tan,
- [224] X. Xu, Z. Zhang, S. Feng, Y. Ye, Z. Su, N. Jiang, S. Cheng, L. Tan, and X. Zhang, "Lmpa: Improving decompilation by synergy of large language model and program analysis," arXiv preprint arXiv:2306.02546, 2023.
- [225] W. K. Wong, H. Wang, Z. Li, Z. Liu, S. Wang, Q. Tang, S. Nie, and S. Wu, "Refining decompiled c code with large language models," arXiv preprint arXiv:2310.06530, 2023.
- [226] P. Hu, R. Liang, and K. Chen, "Degpt: Optimizing decompiler output with llm," in Proceedings 2024 Network and Distributed System Security Symposium (2024). https://api. semanticscholar. org/-CorpusID, vol. 267622140, 2024.
- [227] H. Tan, Q. Luo, J. Li, and Y. Zhang, "Llm4decompile: Decompiling binary code with large language models," arXiv preprint arXiv:2403.05286, 2024.
- [228] N. Jiang, C. Wang, K. Liu, X. Xu, L. Tan, and X. Zhang, "Nova<sup>+</sup>: Generative language models for binaries," arXiv preprint arXiv:2311.13721, 2023.
- [229] J. Armengol-Estapé, J. Woodruff, C. Cummins, and M. F. O'Boyle, "Slade: A portable small language model decompiler for optimized assembly," in 2024 IEEE/ACM International Symposium on Code Generation and Optimization (CGO). IEEE, 2024, pp. 67–80.
- [230] X. She, Y. Zhao, and H. Wang, "Wadec: Decompile webassembly using large language model," arXiv preprint arXiv:2406.11346, 2024.
- [231] X. Shang, S. Cheng, G. Chen, Y. Zhang, L. Hu, X. Yu, G. Li, W. Zhang, and N. Yu, "How far have we gone in stripped binary code understanding using large language models," *arXiv preprint arXiv:2404.09836*, 2024.
- [232] S. Chakraborty, R. Krishna, Y. Ding, and B. Ray, "Deep learning based vulnerability detection: Are we there yet," *IEEE Transactions on Software Engineering*, 2021.
- [233] Y. Li, S. Wang, and T. N. Nguyen, "Vulnerability detection with fine-grained interpretations," in Proceedings of the 29th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2021, pp. 292–303.

- [234] X. Du, M. Wen, J. Zhu, Z. Xie, B. Ji, H. Liu, X. Shi, and H. Jin, "Generalization-enhanced code vulnerability detection via multitask instruction fine-tuning," arXiv preprint arXiv:2406.03718, 2024.
- [235] Y. Sun, D. Wu, Y. Xue, H. Liu, H. Wang, Z. Xu, X. Xie, and Y. Liu, "Gptscan: Detecting logic vulnerabilities in smart contracts by combining gpt with program analysis," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [236] B. Steenhoek, M. M. Rahman, R. Jiles, and W. Le, "An empirical study of deep learning models for vulnerability detection," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2237–2248.
- [237] C. Zhang, H. Liu, J. Zeng, K. Yang, Y. Li, and H. Li, "Promptenhanced software vulnerability detection using chatgpt," arXiv preprint arXiv:2308.12697, 2023.
- [238] D. Noever, "Can large language models find and fix vulnerable software?" arXiv preprint arXiv:2308.10345, 2023.
- [239] S. Alagarsamy, C. Tantithamthavorn, and A. Aleti, "A3test: Assertion-augmented automated test case generation," arXiv preprint arXiv:2302.10352, 2023.
- [240] N. Rao, K. Jain, U. Alon, C. Le Goues, and V. J. Hellendoorn, "Catlm training language models on aligned code and tests," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 409–420.
- [241] M. Schafer, S. Nadi, A. Eghbali, and F. Tip, "An empirical evaluation of using large language models for automated unit test generation," *IEEE Transactions on Software Engineering*, vol. 50, no. 1, pp. 85–105, 2024.
- [242] A. M. Dakhel, A. Nikanjam, V. Majdinasab, F. Khomh, and M. C. Desmarais, "Effective test generation using pre-trained large language models and mutation testing," arXiv preprint arXiv:2308.16557, 2023.
- [243] G. Ryan, S. Jain, M. Shang, S. Wang, X. Ma, M. K. Ramanathan, and B. Ray, "Code-aware prompting: A study of coverage guided test generation in regression setting using llm," arXiv preprint arXiv:2402.00097, 2024.
- [244] J. A. Pizzorno and E. D. Berger, "Coverup: Coverage-guided llmbased test generation," arXiv preprint arXiv:2403.16218, 2024.
- [245] S. Gu, C. Fang, Q. Zhang, F. Tian, and Z. Chen, "Testart: Improving llm-based unit test via co-evolution of automated generation and repair iteration," arXiv preprint arXiv:2408.03095, 2024.
- [246] H. Karmarkar, S. Agrawal, A. Chauhan, and P. Shete, "Navigating confidentiality in test automation: A case study in llm driven test data generation," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 337–348.
- [247] Z. Xie, Y. Chen, C. Zhi, S. Deng, and J. Yin, "Chatunitest: a chatgpt-based automated unit test generation tool," arXiv preprint arXiv:2305.04764, 2023.
- [248] C. Ni, X. Wang, L. Chen, D. Zhao, Z. Cai, S. Wang, and X. Yang, "Casmodatest: A cascaded and model-agnostic selfdirected framework for unit test generation," arXiv preprint arXiv:2406.15743, 2024.
- [249] C. Lemieux, J. P. Inala, S. K. Lahiri, and S. Sen, "Codamosa: Escaping coverage plateaus in test generation with pre-trained large language models," in *International conference on software engineering (ICSE)*, 2023.
- [250] D. Xiao, Y. Guo, Y. Li, and L. Chen, "Optimizing search-based unit test generation with large language models: An empirical study," in *Proceedings of the 15th Asia-Pacific Symposium on Internetware*, 2024, pp. 71–80.
- [251] Y. Tang, Z. Liu, Z. Zhou, and X. Luo, "Chatgpt vs sbst: A comparative assessment of unit test suite generation," *IEEE Transactions* on Software Engineering, 2024.
- [252] L. Yang, C. Yang, S. Gao, W. Wang, B. Wang, Q. Zhu, X. Chu, J. Zhou, G. Liang, Q. Wang *et al.*, "An empirical study of unit test generation with large language models," *arXiv preprint arXiv*:2406.18181, 2024.
- [253] V. Guilherme and A. Vincenzi, "An initial investigation of chatgpt unit test generation capability," in *Proceedings of the 8th Brazilian Symposium on Systematic and Automated Software Testing*, 2023, pp. 15–24.
- [254] Z. Yuan, M. Liu, S. Ding, K. Wang, Y. Chen, X. Peng, and Y. Lou, "Evaluating and improving chatgpt for unit test generation," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1703–1726, 2024.

- [255] W. C. Ouédraogo, K. Kaboré, H. Tian, Y. Song, A. Koyuncu, J. Klein, D. Lo, and T. F. Bissyandé, "Large-scale, independent and comprehensive study of the power of llms for test case generation," arXiv preprint arXiv:2407.00225, 2024.
- [256] A. Deljouyi, R. Koohestani, M. Izadi, and A. Zaidman, "Leveraging large language models for enhancing the understandability of generated unit tests," arXiv preprint arXiv:2408.11710, 2024.
- [257] C. Cui, T. Li, J. Wang, C. Chen, D. Towey, and R. Huang, "Large language models for mobile gui text input generation: An empirical study," arXiv preprint arXiv:2404.08948, 2024.
- [258] Y. Zhang, W. Song, Z. Ji, N. Meng et al., "How well does llm generate security tests?" arXiv preprint arXiv:2310.00710, 2023.
- [259] M. Tufano, D. Drain, A. Svyatkovskiy, and N. Sundaresan, "Generating accurate assert statements for unit test cases using pretrained transformers," in *Proceedings of the 3rd ACM/IEEE International Conference on Automation of Software Test*, 2022, pp. 54–64.
- [260] E. Dinella, G. Ryan, T. Mytkowicz, and S. K. Lahiri, "Toga: A neural method for test oracle generation," in *Proceedings of the* 44th International Conference on Software Engineering, 2022, pp. 2130–2141.
- [261] Y. He, J. Huang, H. Yu, and T. Xie, "An empirical study on focal methods in deep-learning-based approaches for assertion generation," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1750–1771, 2024.
- [262] V. Pulavarthi, D. Nandal, S. Dan, and D. Pal, "Assertionbench: A benchmark to evaluate large-language models for assertion generation," arXiv preprint arXiv:2406.18627, 2024.
- [263] M. Endres, S. Fakhoury, S. Chakraborty, and S. K. Lahiri, "Can large language models transform natural language intent into formal method postconditions?" *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1889–1912, 2024.
- [264] S. B. Hossain and M. Dwyer, "Togll: Correct and strong test oracle generation with llms," arXiv preprint arXiv:2405.03786, 2024.
- [265] R. Pan, T. A. Ghaleb, and L. Briand, "Ltm: Scalable and blackbox similarity-based test suite minimization based on language models," arXiv preprint arXiv:2304.01397, 2023.
- [266] Y. Deng, C. S. Xia, H. Peng, C. Yang, and L. Zhang, "Large language models are zero-shot fuzzers: Fuzzing deep-learning libraries via large language models," in *Proceedings of the 32nd* ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA 2023), 2023.
- [267] Y. Deng, C. S. Xia, C. Yang, S. D. Zhang, S. Yang, and L. Zhang, "Large language models are edge-case fuzzers: Testing deep learning libraries via fuzzgpt," arXiv preprint arXiv:2304.02014, 2023.
- [268] C. Yang, Y. Deng, R. Lu, J. Yao, J. Liu, R. Jabbarvand, and L. Zhang, "White-box compiler fuzzing empowered by large language models," arXiv preprint arXiv:2310.15991, 2023.
- [269] J. Eom, S. Jeong, and T. Kwon, "Covrl: Fuzzing javascript engines with coverage-guided reinforcement learning for llm-based mutation," arXiv preprint arXiv:2402.12222, 2024.
- [270] R. Meng, M. Mirchev, M. Böhme, and A. Roychoudhury, "Large language model guided protocol fuzzing." NDSS, 2024.
- [271] J. Wang, L. Yu, and X. Luo, "Llmif: Augmented large language model for fuzzing iot devices," in 2024 IEEE Symposium on Security and Privacy (SP). IEEE Computer Society, 2024, pp. 196– 196.
- [272] C. S. Xia, M. Paltenghi, J. Le Tian, M. Pradel, and L. Zhang, "Fuzz4all: Universal fuzzing with large language models," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE, 2024, pp. 1547–1559.
- [273] J. Hu, Q. Zhang, and H. Yin, "Augmenting greybox fuzzing with generative ai," arXiv preprint arXiv:2306.06782, 2023.
- [274] A. Dakhama, K. Even-Mendoza, W. B. Langdon, H. D. Menendez, and J. Petke, "Searchgem5: Towards reliable gem5 with search based software testing and large language models," in 15th Symposium on Search Based Software Engineering (SSBSE): Lecture Notes in Computer Science. Springer, 2023.
- [275] H. Zhang, Y. Rong, Y. He, and H. Chen, "Llamafuzz: Large language model enhanced greybox fuzzing," *arXiv preprint arXiv*:2406.07714, 2024.
- [276] C. Zhang, M. Bai, Y. Zheng, Y. Li, X. Xie, Y. Li, W. Ma, L. Sun, and Y. Liu, "Understanding large language model based fuzz driver generation," arXiv preprint arXiv:2307.12469, 2023.

- [277] C. Shou, J. Liu, D. Lu, and K. Sen, "Llm4fuzz: Guided fuzzing of smart contracts with large language models," arXiv preprint arXiv:2401.11108, 2024.
- [278] C. Yang, Z. Zhao, and L. Zhang, "Kernelgpt: Enhanced kernel fuzzing via large language models," arXiv preprint arXiv:2401.00563, 2023.
- [279] Asmita, Y. Oliinyk, M. Scott, R. Tsang, C. Fang, and H. Homayoun, "Fuzzing BusyBox: Leveraging LLM and crash reuse for embedded bug unearthing," in 33rd USENIX Security Symposium (USENIX Security 24). Philadelphia, PA: USENIX Association, Aug. 2024, pp. 883– 900. [Online]. Available: https://www.usenix.org/conference/ usenixsecurity24/presentation/asmita
- [280] G. Deng, Y. Liu, V. Mayoral-Vilches, P. Liu, Y. Li, Y. Xu, T. Zhang, Y. Liu, M. Pinzger, and S. Rass, "Pentestgpt: An Ilmempowered automatic penetration testing tool," arXiv preprint arXiv:2308.06782, 2023.
- [281] L. Wu, X. Zhong, J. Liu, and X. Wang, "Ptgroup: An automated penetration testing framework using llms and multiple prompt chains," in *International Conference on Intelligent Computing.* Springer, 2024, pp. 220–232.
- [282] A. Happe and J. Cito, "Getting pwn'd by ai: Penetration testing with large language models," arXiv preprint arXiv:2308.00121, 2023.
- [283] V. Vikram, C. Lemieux, and R. Padhye, "Can large language models write good property-based tests?" arXiv preprint arXiv:2307.04346, 2023.
- [284] T.-O. Li, W. Zong, Y. Wang, H. Tian, Y. Wang, and S.-C. Cheung, "Finding failure-inducing test cases with chatgpt," *arXiv preprint arXiv*:2304.11686, 2023.
- [285] A. Khanfir, R. Degiovanni, M. Papadakis, and Y. L. Traon, "Efficient mutation testing via pre-trained language models," arXiv preprint arXiv:2301.03543, 2023.
- [286] A. R. Ibrahimzada, Y. Chen, R. Rong, and R. Jabbarvand, "Automated bug generation in the era of large language models," arXiv preprint arXiv:2310.02407, 2023.
- [287] Y. Nong, Y. Ou, M. Pradel, F. Chen, and H. Cai, "Vulgen: Realistic vulnerability generation via pattern mining and deep learning," in IEEE/ACM 45th International Conference on Software Engineering(ICSE) https://www. software-lab. org/publications/icse2023\_VulGen. pdf, 2023.
- [288] A. Garg, R. Degiovanni, M. Papadakis, and Y. Le Traon, "On the coupling between vulnerabilities and llm-generated mutants: A study on vul4j dataset," in 2024 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2024, pp. 305– 316.
- [289] B. Wang, M. Chen, Y. Lin, M. Papadakis, and J. M. Zhang, "An exploratory study on using large language models for mutation testing," arXiv preprint arXiv:2406.09843, 2024.
- [290] Z. Tian, H. Shu, D. Wang, X. Cao, Y. Kamei, and J. Chen, "Large language models for equivalent mutant detection: How far are we?" arXiv preprint arXiv:2408.01760, 2024.
- [291] Z. Liu, C. Chen, J. Wang, X. Che, Y. Huang, J. Hu, and Q. Wang, "Fill in the blank: Context-aware automated text input generation for mobile gui testing," arXiv preprint arXiv:2212.04732, 2022.
- [292] Z. Liu, C. Chen, J. Wang, M. Chen, B. Wu, X. Che, D. Wang, and Q. Wang, "Make llm a testing expert: Bringing humanlike interaction to mobile gui testing via functionality-aware decisions," arXiv preprint arXiv:2310.15780, 2023.
- [293] Z. Liu, C. Li, C. Chen, J. Wang, B. Wu, Y. Wang, J. Hu, and Q. Wang, "Vision-driven automated mobile gui testing via multimodal large language model," arXiv preprint arXiv:2407.03037, 2024.
- [294] J. Yoon, R. Feldt, and S. Yoo, "Intent-driven mobile gui testing with autonomous large language model agents," in 2024 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2024, pp. 129–139.
- [295] P. He, C. Meister, and Z. Su, "Structure-invariant testing for machine translation," in *Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering*, 2020, pp. 961–973.
- [296] S. Gupta, P. He, C. Meister, and Z. Su, "Machine translation testing via pathological invariance," in Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2020, pp. 863–875.
- [297] Z. Sun, J. M. Zhang, Y. Xiong, M. Harman, M. Papadakis, and L. Zhang, "Improving machine translation systems via isotopic

replacement," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 1181–1192.

- [298] B. Yu, Y. Hu, Q. Mang, W. Hu, and P. He, "Automated testing and improvement of named entity recognition systems," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, ser. ES-EC/FSE 2023. New York, NY, USA: Association for Computing Machinery, 2023, pp. 883–894.
- [299] W. Wang, J.-t. Huang, W. Wu, J. Zhang, Y. Huang, S. Li, P. He, and M. R. Lyu, "Mttm: Metamorphic testing for textual content moderation software," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2387–2399.
- [300] Z. Liu, Y. Feng, and Z. Chen, "Dialtest: automated testing for recurrent-neural-network-driven dialogue systems," in *Proceedings of the 30th ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2021, pp. 115–126.
- [301] Z. Liu, Y. Feng, Y. Yin, J. Sun, Z. Chen, and B. Xu, "Qatest: A uniform fuzzing framework for question answering systems," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1–12.
- [302] T. Le, T. Tran, D. Cao, V. Le, T. N. Nguyen, and V. Nguyen, "Kat: Dependency-aware automated api testing with large language models," in 2024 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2024, pp. 82–92.
- [303] Z. Xue, Z. Gao, S. Wang, X. Hu, X. Xia, and S. Li, "Selfpico: Self-guided partial code execution with llms," arXiv preprint arXiv:2407.16974, 2024.
- [304] H. Li, Y. Hao, Y. Zhai, and Z. Qian, "Assisting static analysis with large language models: A chatgpt experiment," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2023, pp. 2107–2111.
- [305] Y. Hao, W. Chen, Z. Zhou, and W. Cui, "E&v: Prompting large language models to perform static analysis by pseudo-code execution and verification," arXiv preprint arXiv:2312.08477, 2023.
- [306] M. M. Mohajer, R. Aleithan, N. S. Harzevili, M. Wei, A. B. Belle, H. V. Pham, and S. Wang, "Skipanalyzer: An embodied agent for code analysis with large language models," arXiv preprint arXiv:2310.18532, 2023.
- [307] Y. Li, Y. Peng, Y. Huo, and M. R. Lyu, "Enhancing llm-based coding tools through native integration of ide-derived static context," arXiv preprint arXiv:2402.03630, 2024.
- [308] J. Sun, Z. Xing, Q. Lu, X. Xu, L. Zhu, T. Hoang, and D. Zhao, "Silent vulnerable dependency alert prediction with vulnerability key aspect explanation," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 970– 982.
- [309] K. Liu, Y. Liu, Z. Chen, J. M. Zhang, Y. Han, Y. Ma, G. Li, and G. Huang, "Llm-powered test case generation for detecting tricky bugs," arXiv preprint arXiv:2404.10304, 2024.
- [310] H. Zhang, S. Lu, Z. Li, Z. Jin, L. Ma, Y. Liu, and G. Li, "Codebertattack: Adversarial attack against source code deep learning models via pre-trained model," *Journal of Software: Evolution and Process*, vol. 36, no. 3, p. e2571, 2024.
- [311] M. Zhang, Y. Tian, Z. Xu, Y. Dong, S. H. Tan, and C. Sun, "Lpr: Large language models-aided program reduction," in Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis (Vienna, Austria)(ISSTA 2024). Association for Computing Machinery, New York, NY, USA. https://doi. org/10.1145/3650212.3652126, 2024.
- [312] F. Li, J. Jiang, J. Sun, and H. Zhang, "Hybrid automated program repair by combining large language models and program analysis," *arXiv preprint arXiv:2406.00992*, 2024.
- [313] J. Xu, Y. Fu, S. H. Tan, and P. He, "Aligning llms for fl-free program repair," arXiv preprint arXiv:2404.08877, 2024.
- [314] S. B. Hossain, N. Jiang, Q. Zhou, X. Li, W.-H. Chiang, Y. Lyu, H. Nguyen, and O. Tripp, "A deep dive into large language models for automated bug localization and repair," arXiv preprint arXiv:2404.11595, 2024.
- [315] N. Jiang, T. Lutellier, and L. Tan, "Cure: Code-aware neural machine translation for automatic program repair," in 2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE). IEEE, 2021, pp. 1161–1173.
- [316] Y. Li, S. Wang, and T. N. Nguyen, "Dear: A novel deep learningbased approach for automated program repair," in *Proceedings of* the 44th International Conference on Software Engineering, 2022, pp. 511–523.

- [317] B. Yang, H. Tian, J. Ren, H. Zhang, J. Klein, T. F. Bissyandé, C. L. Goues, and S. Jin, "Multi-objective fine-tuning for enhanced program repair with llms," arXiv preprint arXiv:2404.12636, 2024.
- [318] D. Drain, C. Wu, A. Svyatkovskiy, and N. Sundaresan, "Generating bug-fixes using pretrained transformers," in *Proceedings* of the 5th ACM SIGPLAN International Symposium on Machine Programming, 2021, pp. 1–8.
- [319] B. Berabi, J. He, V. Raychev, and M. Vechev, "Tfix: Learning to fix coding errors with a text-to-text transformer," in *International Conference on Machine Learning*. PMLR, 2021, pp. 780–791.
- [320] M. Dehghan, J. J. Wu, F. H. Fard, and A. Ouni, "Mergerepair: An exploratory study on merging task-specific adapters in code llms for automated program repair," arXiv preprint arXiv:2408.09568, 2024.
- [321] A. Silva, S. Fang, and M. Monperrus, "Repairllama: Efficient representations and fine-tuned adapters for program repair," arXiv preprint arXiv:2312.15698, 2023.
- [322] Y. Wei, C. S. Xia, and L. Zhang, "Copiloting the copilots: Fusing large language models with completion engines for automated program repair," *arXiv preprint arXiv:2309.00608*, 2023.
- [323] F. V. Ruiz, A. Grishina, M. Hort, and L. Moonen, "A novel approach for automatic program repair using round-trip translation with large language models," arXiv preprint arXiv:2401.07994, 2024.
- [324] Y. Peng, S. Gao, C. Gao, Y. Huo, and M. R. Lyu, "Domain knowledge matters: Improving prompts with fix templates for repairing python type errors," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE, 2024, pp. 12–24.
- [325] J. Xiang, X. Xu, F. Kong, M. Wu, H. Zhang, and Y. Zhang, "How far can we go with practical function-level program repair?" arXiv preprint arXiv:2404.12833, 2024.
- [326] K. Huang, X. Meng, J. Zhang, Y. Liu, W. Wang, S. Li, and Y. Zhang, "An empirical study on fine-tuning large language models of code for automated program repair," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 1162–1174.
- [327] N. Jiang, K. Liu, T. Lutellier, and L. Tan, "Impact of code language models on automated program repair," *arXiv preprint arXiv*:2302.05020, 2023.
- [328] Z. Fan, X. Gao, A. Roychoudhury, and S. H. Tan, "Automated repair of programs from large language models," arXiv preprint arXiv:2205.10583, 2022.
- [329] D. Sobania, M. Briesch, C. Hanna, and J. Petke, "An analysis of the automatic bug fixing performance of chatgpt," *arXiv preprint arXiv:2301.08653*, 2023.
- [330] J. Cao, M. Li, M. Wen, and S.-c. Cheung, "A study on prompt design, advantages and limitations of chatgpt for deep learning program repair," arXiv preprint arXiv:2304.08191, 2023.
- [331] M. Jin, S. Shahriar, M. Tufano, X. Shi, S. Lu, N. Sundaresan, and A. Svyatkovskiy, "Inferfix: End-to-end program repair with llms," arXiv preprint arXiv:2303.07263, 2023.
- [332] J. Zhao, D. Yang, L. Zhang, X. Lian, and Z. Yang, "Enhancing llmbased automated program repair with design rationales," arXiv preprint arXiv:2408.12056, 2024.
- [333] N. Wadhwa, J. Pradhan, A. Sonwane, S. P. Sahu, N. Natarajan, A. Kanade, S. Parthasarathy, and S. Rajamani, "Core: Resolving code quality issues using llms," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 789–811, 2024.
- [334] H. Joshi, J. C. Sanchez, S. Gulwani, V. Le, G. Verbruggen, and I. Radiček, "Repair is nearly generation: Multilingual program repair with llms," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 37, no. 4, 2023, pp. 5131–5140.
- [335] B. Yang, H. Tian, W. Pian, H. Yu, H. Wang, J. Klein, T. F. Bissyandé, and S. Jin, "Cref: An llm-based conversational software repair framework for programming tutors," arXiv preprint arXiv:2406.13972, 2024.
- [336] Y. Charalambous, E. Manino, and L. C. Cordeiro, "Automated repair of ai code with large language models and formal verification," arXiv preprint arXiv:2405.08848, 2024.
- [337] Q. Xin, H. Wu, S. P. Reiss, and J. Xuan, "Towards practical and useful automated program repair for debugging," *arXiv preprint arXiv:2407.08958*, 2024.
- [338] A. Z. Yang, S. Kolak, V. J. Hellendoorn, R. Martins, and C. L. Goues, "Revisiting unnaturalness for automated program repair in the era of large language models," *arXiv preprint arXiv:2404.15236*, 2024.

- [339] J. Zhang, J. P. Cambronero, S. Gulwani, V. Le, R. Piskac, G. Soares, and G. Verbruggen, "Pydex: Repairing bugs in introductory python assignments using llms," *Proceedings of the ACM on Pro*gramming Languages, vol. 8, no. OOPSLA1, pp. 1100–1124, 2024.
- [340] I. Bouzenia, P. Devanbu, and M. Pradel, "Repairagent: An autonomous, llm-based agent for program repair," *arXiv preprint arXiv:2403.17134*, 2024.
- [341] C. Lee, C. S. Xia, J.-t. Huang, Z. Zhu, L. Zhang, and M. R. Lyu, "A unified debugging approach via llm-based multi-agent synergy," arXiv preprint arXiv:2404.17153, 2024.
- [342] X. Yin, C. Ni, S. Wang, Z. Li, L. Zeng, and X. Yang, "Thinkrepair: Self-directed automated program repair," arXiv preprint arXiv:2407.20898, 2024.
- [343] C. S. Xia and L. Zhang, "Keep the conversation going: Fixing 162 out of 337 bugs for \$0.42 each using chatgpt," arXiv preprint arXiv:2304.00385, 2023.
- [344] Q. Xin, H. Wu, J. Tang, X. Liu, S. P. Reiss, and J. Xuan, "Detecting, creating, repairing, and understanding indivisible multi-hunk bugs," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 2747–2770, 2024.
- [345] Y. Wang, T. Guo, Z. Huang, and Y. Yuan, "Revisiting evolutionary program repair via code language model," *arXiv preprint arXiv:2408.10486*, 2024.
- [346] D. Hidvégi, K. Etemadi, S. Bobadilla, and M. Monperrus, "Cigar: Cost-efficient program repair with llms," arXiv preprint arXiv:2402.06598, 2024.
- [347] E. First, M. N. Rabe, T. Ringer, and Y. Brun, "Baldur: Whole-proof generation and repair with large language models," in *Proceed*ings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 1229–1241.
- [348] M. Fu, C. Tantithamthavorn, T. Le, V. Nguyen, and D. Phung, "Vulrepair: a t5-based automated software vulnerability repair," in Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2022, pp. 935–947.
- [349] M. Fu, V. Nguyen, C. Tantithamthavorn, D. Phung, and T. Le, "Vision transformer inspired automated vulnerability repair," ACM Transactions on Software Engineering and Methodology, vol. 33, no. 3, pp. 1–29, 2024.
- [350] X. Zhou, K. Kim, B. Xu, D. Han, and D. Lo, "Out of sight, out of mind: Better automatic vulnerability repair by broadening input ranges and sources," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [351] H. Pearce, B. Tan, B. Ahmad, R. Karri, and B. Dolan-Gavitt, "Examining zero-shot vulnerability repair with large language models," in 2023 IEEE Symposium on Security and Privacy (SP). IEEE, 2023, pp. 2339–2356.
- [352] M. C. Tol and B. Sunar, "Zeroleak: Using Ilms for scalable and cost effective side-channel patching," arXiv preprint arXiv:2308.13062, 2023.
- [353] H. Tian, K. Liu, A. K. Kaboré, A. Koyuncu, L. Li, J. Klein, and T. F. Bissyandé, "Evaluating representation learning of code changes for predicting patch correctness in program repair," in *Proceedings of the 35th IEEE/ACM International Conference on Automated Software Engineering*, 2020, pp. 981–992.
- [354] H. Tian, K. Liu, Y. Li, A. K. Kaboré, A. Koyuncu, A. Habib, L. Li, J. Wen, J. Klein, and T. F. Bissyandé, "The best of both worlds: Combining learned embeddings with engineered features for accurate prediction of correct patches," ACM Transactions on Software Engineering and Methodology, vol. 32, no. 4, pp. 1–34, 2023.
- [355] H. Tian, X. Tang, A. Habib, S. Wang, K. Liu, X. Xia, J. Klein, and T. F. Bissyandé, "Is this change the answer to that problem? correlating descriptions of bug and code changes for evaluating patch correctness," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1– 13.
- [356] T. Le-Cong, D.-M. Luong, X. B. D. Le, D. Lo, N.-H. Tran, B. Quang-Huy, and Q.-T. Huynh, "Invalidator: Automated patch correctness assessment via semantic and syntactic reasoning," *IEEE Transactions on Software Engineering*, vol. 49, no. 6, pp. 3411– 3429, 2023.
- [357] Q. Zhang, C. Fang, W. Sun, Y. Liu, T. He, X. Hao, and Z. Chen, "Appt: Boosting automated patch correctness prediction via finetuning pre-trained models," *IEEE Transactions on Software Engineering*, vol. 50, no. 03, pp. 474–494, 2024.

- [358] X. Zhou, B. Xu, K. Kim, D. Han, T. Le-Cong, J. He, B. Le, and D. Lo, "Patchzero: Zero-shot automatic patch correctness assessment," arXiv preprint arXiv:2303.00202, 2023.
- [359] F. Molina, J. M. Copia, and A. Gorla, "Improving patch correctness analysis via random testing and large language models," in 2024 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2024, pp. 317–328.
- [360] T. H. Jung, "Commithert: Commit message generation using pre-trained programming language model," in *Proceedings of the 1st Workshop on Natural Language Processing for Programming* (NLP4Prog 2021), 2021, pp. 26–33.
- [361] L. Wang, X. Tang, Y. He, C. Ren, S. Shi, C. Yan, and Z. Li, "Delving into commit-issue correlation to enhance commit message generation models," arXiv preprint arXiv:2308.00147, 2023.
- [362] J. Li, D. Faragó, C. Petrov, and I. Ahmed, "Only diff is not enough: Generating commit messages leveraging reasoning and action of large language model," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 745–766, 2024.
- [363] P. Xue, L. Wu, Z. Yu, Z. Jin, Z. Yang, X. Li, Z. Yang, and Y. Tan, "Automated commit message generation with large language models: An empirical study and beyond," arXiv preprint arXiv:2404.14824, 2024.
- [364] C. V. Lopes, V. I. Klotzman, I. Ma, and I. Ahmed, "Commit messages in the age of large language models," *arXiv preprint arXiv:2401.17622*, 2024.
- [365] R. Tufano, S. Masiero, A. Mastropaolo, L. Pascarella, D. Poshyvanyk, and G. Bavota, "Using pre-trained models to boost code review automation," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 2291–2302.
- [366] L. Li, L. Yang, H. Jiang, J. Yan, T. Luo, Z. Hua, G. Liang, and C. Zuo, "Auger: automatically generating review comments with pre-training models," in *Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2022, pp. 1009–1021.
- [367] Z. Li, S. Lu, D. Guo, N. Duan, S. Jannu, G. Jenks, D. Majumder, J. Green, A. Svyatkovskiy, S. Fu et al., "Automating code review activities by large-scale pre-training," in Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2022, pp. 1035– 1047.
- [368] R. Widyasari, T. Zhang, A. Bouraffa, and D. Lo, "Explaining explanation: An empirical study on explanation in code reviews," arXiv preprint arXiv:2311.09020, 2023.
- [369] R. Tufano, O. Dabić, A. Mastropaolo, M. Ciniselli, and G. Bavota, "Code review automation: strengths and weaknesses of the state of the art," *IEEE Transactions on Software Engineering*, 2024.
- [370] Q. Guo, J. Cao, X. Xie, S. Liu, X. Li, B. Chen, and X. Peng, "Exploring the potential of chatgpt in automated code refinement: An empirical study," arXiv preprint arXiv:2309.08221, 2023.
- [371] T. Zhang, I. C. Irsan, F. Thung, and D. Lo, "Cupid: Leveraging chatgpt for more accurate duplicate bug report detection," arXiv preprint arXiv:2308.10022, 2023.
- [372] L. Plein and T. F. Bissyandé, "Can llms demystify bug reports?" arXiv preprint arXiv:2310.06310, 2023.
- [373] S. Kang, J. Yoon, and S. Yoo, "Large language models are few-shot testers: Exploring llm-based general bug reproduction," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2312–2323.
- [374] Y. Huang, J. Wang, Z. Liu, Y. Wang, S. Wang, C. Chen, Y. Hu, and Q. Wang, "Crashtranslator: Automatically reproducing mobile application crashes directly from stack trace," in *Proceedings of the* 46th IEEE/ACM International Conference on Software Engineering, 2024, pp. 1–13.
- [375] S. Feng and C. Chen, "Prompting is all your need: Automated android bug replay with large language models," arXiv preprint arXiv:2306.01987, 2023.
- [376] X. Hu, Z. Liu, X. Xia, Z. Liu, T. Xu, and X. Yang, "Identify and update test cases when production code changes: A transformerbased approach," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE), 2023, pp. 1111–1122.
- [377] J. Liu, J. Yan, Y. Xie, J. Yan, and J. Zhang, "Augmenting llms to repair obsolete test cases with static collector and neural reranker," arXiv preprint arXiv:2407.03625, 2024.
- [378] A. S. Yaraghi, D. Holden, N. Kahani, and L. Briand, "Automated test case repair using language models," arXiv preprint arXiv:2401.06765, 2024.

- [379] S. Tao, W. Meng, Y. Cheng, Y. Zhu, Y. Liu, C. Du, T. Han, Y. Zhao, X. Wang, and H. Yang, "Logstamp: Automatic online log parsing based on sequence labelling," ACM SIGMETRICS Performance Evaluation Review, vol. 49, no. 4, pp. 93–98, 2022.
- [380] M. Mehrabi, A. Hamou-Lhadj, and H. Moosavi, "The effectiveness of compact fine-tuned llms in log parsing."
- [381] V.-H. Le and H. Zhang, "Log parsing with prompt-based fewshot learning," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2438–2449.
- [382] Z. Ma, A. R. Chen, D. J. Kim, T.-H. Chen, and S. Wang, "Llmparser: An exploratory study on using large language models for log parsing," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE Computer Society, 2024, pp. 1209–1221.
- [383] Z. Jiang, J. Liu, Z. Chen, Y. Li, J. Huang, Y. Huo, P. He, J. Gu, and M. R. Lyu, "Lilac: Log parsing using llms with adaptive parsing cache," arXiv preprint arXiv:2310.01796, 2023.
- [384] Y. Liu, S. Tao, W. Meng, J. Wang, W. Ma, Y. Chen, Y. Zhao, H. Yang, and Y. Jiang, "Interpretable online log analysis using large language models with prompt strategies," in *Proceedings of the 32nd IEEE/ACM International Conference on Program Comprehension*, 2024, pp. 35–46.
- [385] J. Xu, Z. Cui, Y. Zhao, X. Zhang, S. He, P. He, L. Li, Y. Kang, Q. Lin, Y. Dang et al., "Unilog: Automatic logging via llm and in-context learning," in Proceedings of the 46th IEEE/ACM International Conference on Software Engineering, 2024, pp. 1–12.
- [386] Y. Liu, S. Tao, W. Meng, F. Yao, X. Zhao, and H. Yang, "Logprompt: Prompt engineering towards zero-shot and interpretable log analysis," in *Proceedings of the 2024 IEEE/ACM 46th International Conference on Software Engineering: Companion Proceedings*, 2024, pp. 364–365.
- [387] Y. Xiao, V.-H. Le, and H. Zhang, "Stronger, faster, and cheaper log parsing with llms," arXiv preprint arXiv:2406.06156, 2024.
- [388] J. Huang, Z. Jiang, Z. Chen, and M. R. Lyu, "Ulog: Unsupervised log parsing with large language models through log contrastive units," arXiv preprint arXiv:2406.07174, 2024.
- [389] X. Ma, H. Zou, J. Keung, P. He, Y. Li, X. Yu, and F. Sarro, "On the influence of data resampling for deep learning-based log anomaly detection: Insights and recommendations," arXiv preprint arXiv:2405.03489, 2024.
- [390] V.-H. Le and H. Zhang, "Log parsing: How far can chatgpt go?" in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE Computer Society, 2023, pp. 1699–1704.
- [391] F. Hadadi, Q. Xu, D. Bianculli, and L. Briand, "Anomaly detection on unstable logs with gpt models," arXiv preprint arXiv:2406.07467, 2024.
- [392] S. Huang, Y. Liu, J. Qi, J. Shang, Z. Xiao, C. Fung, Z. Wu, H. Yang, Z. Luan, and D. Qian, "Gloss: Guiding large language models to answer questions from system logs," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 91–101.
- [393] P. Mudgal and R. Wouhaybi, "An assessment of chatgpt on log data," in *International Conference on AI-generated Content*. Springer, 2023, pp. 148–169.
- [394] Z. Zhang and T. Saber, "Assessing the code clone detection capability of large language models," in 2024 4th International Conference on Code Quality (ICCQ). IEEE, 2024, pp. 75–83.
- [395] M. B. Moumoula, A. K. Kabore, J. Klein, and T. Bissyande, "Large language models for cross-language code clone detection," arXiv preprint arXiv:2408.04430, 2024.
- [396] S. Dou, J. Shan, H. Jia, W. Deng, Z. Xi, W. He, Y. Wu, T. Gui, Y. Liu, and X. Huang, "Towards understanding the capability of large language models on code clone detection: a survey," arXiv preprint arXiv:2308.01191, 2023.
- [397] A. K. Dipongkor and K. Moran, "A comparative study of transformer-based neural text representation techniques on bug triaging," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 1012–1023.
- [398] J. Lee, K. Han, and H. Yu, "A light bug triage framework for applying large pre-trained language model," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1–11.
- [399] W. Ma, Y. Yu, X. Ruan, and B. Cai, "Pre-trained model based feature envy detection," in 2023 IEEE/ACM 20th International Conference on Mining Software Repositories (MSR). IEEE, 2023, pp. 430–440.

- [400] M. M. Imran, P. Chatterjee, and K. Damevski, "Uncovering the causes of emotions in software developer communication using zero-shot llms," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [401] Y. Cai, A. Yadavally, A. Mishra, G. Montejo, and T. Nguyen, "Programming assistant for exception handling with codebert," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [402] Y. Jiang, C. Zhang, S. He, Z. Yang, M. Ma, S. Qin, Y. Kang, Y. Dang, S. Rajmohan, Q. Lin *et al.*, "Xpert: Empowering incident management with query recommendations via large language models," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [403] T. Ahmed, S. Ghosh, C. Bansal, T. Zimmermann, X. Zhang, and S. Rajmohan, "Recommending root-cause and mitigation steps for cloud incidents using large language models," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 1737–1749.
- [404] G. Colavito, F. Lanubile, N. Novielli, and L. Quaranta, "Leveraging gpt-like llms to automate issue labeling," in 2024 IEEE/ACM 21st International Conference on Mining Software Repositories (MSR). IEEE, 2024, pp. 469–480.
- [405] G. Morales, K. Pragyan, S. Jahan, M. B. Hosseini, and R. Slavin, "A large language model approach to code and privacy policy alignment," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 79–90.
- [406] N. Mohammed, A. Lal, A. Rastogi, S. Roy, and R. Sharma, "Enabling memory safety of c programs using llms," arXiv preprint arXiv:2404.01096, 2024.
- [407] Z. Gao, H. Wang, Y. Wang, and C. Zhang, "Vic: Virtual compiler is all you need for assembly code search," arXiv preprint arXiv:2408.06385, 2024.
- [408] H. Tu, Z. Zhou, H. Jiang, I. N. B. Yusuf, Y. Li, and L. Jiang, "Isolating compiler bugs by generating effective witness programs with large language models," arXiv preprint arXiv:2307.00593, 2023.
- [409] S. J. Oishwee, N. Stakhanova, and Z. Codabux, "Large language model vs. stack overflow in addressing android permission related challenges," in 2024 IEEE/ACM 21st International Conference on Mining Software Repositories (MSR). IEEE, 2024, pp. 373–383.
- [410] M. Alhamed and T. Storer, "Evaluation of context-aware language models and experts for effort estimation of software maintenance issues," in 2022 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2022, pp. 129–138.
- [411] Y. Li, Z. Ren, Z. Wang, L. Yang, L. Dong, C. Zhong, and H. Zhang, "Fine-se: Integrating semantic features and expert features for software effort estimation," in *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, 2024, pp. 1–12.
- [412] J. Kannan, "Can llms configure software tools," arXiv preprint arXiv:2312.06121, 2023.
- [413] M. M. Imran, "Emotion classification in software engineering texts: A comparative analysis of pre-trained transformers language models," in *Proceedings of the Third ACM/IEEE International Workshop on NL-based Software Engineering*, 2024, pp. 73–80.
- [414] S. Abedu, A. Abdellatif, and E. Shihab, "Llm-based chatbots for mining software repositories: Challenges and opportunities," in Proceedings of the 28th International Conference on Evaluation and Assessment in Software Engineering, 2024, pp. 201–210.
- [415] A. Mastropaolo, N. Cooper, D. N. Palacio, S. Scalabrino, D. Poshyvanyk, R. Oliveto, and G. Bavota, "Using transfer learning for code-related tasks," *IEEE Transactions on Software Engineering*, vol. 49, no. 4, pp. 1580–1598, 2022.
- [416] Z. Zeng, H. Tan, H. Zhang, J. Li, Y. Zhang, and L. Zhang, "An extensive study on pre-trained models for program understanding and generation," in *Proceedings of the 31st ACM SIGSOFT international symposium on software testing and analysis*, 2022, pp. 39–51.
- [417] C. Niu, C. Li, V. Ng, D. Chen, J. Ge, and B. Luo, "An empirical comparison of pre-trained models of source code," arXiv preprint arXiv:2302.04026, 2023.
- [418] S. Gao, X.-C. Wen, C. Gao, W. Wang, H. Zhang, and M. R. Lyu, "What makes good in-context demonstrations for code intelligence tasks with llms?" in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 761–773.
- [419] J. White, S. Hays, Q. Fu, J. Spencer-Smith, and D. C. Schmidt, "Chatgpt prompt patterns for improving code quality, refactor-

ing, requirements elicitation, and software design," in *Generative* AI for Effective Software Development. Springer, 2024, pp. 71–108.

- [420] X. Zhou, K. Kim, B. Xu, J. Liu, D. Han, and D. Lo, "The devil is in the tails: How long-tailed code distributions impact large language models," arXiv preprint arXiv:2309.03567, 2023.
- [421] W. Liang and G. Xiao, "An exploratory evaluation of large language models using empirical software engineering tasks," in *Proceedings of the 15th Asia-Pacific Symposium on Internetware*, 2024, pp. 31–40.
- [422] S. Jalil, S. Rafi, T. D. LaToza, K. Moran, and W. Lam, "Chatgpt and software testing education: Promises & perils," in 2023 IEEE International Conference on Software Testing, Verification and Validation Workshops (ICSTW). IEEE, 2023, pp. 4130–4137.
- [423] C. Geng, Z. Yihan, B. Pientka, and X. Si, "Can chatgpt pass an introductory level functional language programming course?" arXiv preprint arXiv:2305.02230, 2023.
- [424] P. T. Nguyen, J. Di Rocco, C. Di Sipio, R. Rubei, D. Di Ruscio, and M. Di Penta, "Is this snippet written by chatgpt? an empirical study with a codebert-based classifier," arXiv preprint arXiv:2307.09381, 2023.
- [425] H. Tian, W. Lu, T. O. Li, X. Tang, S.-C. Cheung, J. Klein, and T. F. Bissyandé, "Is chatgpt the ultimate programming assistant-how far is it?" arXiv preprint arXiv:2304.11938, 2023.
- [426] Y. Xue, H. Chen, G. R. Bai, R. Tairas, and Y. Huang, "Does chatgpt help with introductory programming? an experiment of students using chatgpt in cs1," in *Proceedings of the 46th International Conference on Software Engineering: Software Engineering Education* and Training, 2024, pp. 331–341.
- [427] J. M. Zhang, M. Harman, L. Ma, and Y. Liu, "Machine learning testing: Survey, landscapes and horizons," *IEEE Transactions on Software Engineering*, vol. 48, no. 1, pp. 1–36, 2020.
- [428] Q. Zhang, T. Zhang, J. Zhai, C. Fang, B. Yu, W. Sun, and Z. Chen, "A critical review of large language model on software engineering: An example from chatgpt and automated program repair," 2023.
- [429] Y. Wu, Z. Li, J. M. Zhang, and Y. Liu, "Condefects: A new dataset to address the data leakage concern for llm-based fault localization and program repair," arXiv preprint arXiv:2310.16253, 2023.
- [430] Z. Wang, K. Liu, G. Li, and Z. Jin, "Hits: High-coverage llmbased unit test generation via method slicing," arXiv preprint arXiv:2408.11324, 2024.
- [431] J. Liu, C. S. Xia, Y. Wang, and L. Zhang, "Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation," arXiv preprint arXiv:2305.01210, 2023.
- [432] C. Niu, C. Li, V. Ng, and B. Luo, "Crosscodebench: Benchmarking cross-task generalization of source code models," arXiv preprint arXiv:2302.04030, 2023.
- [433] X. Du, M. Liu, K. Wang, H. Wang, J. Liu, Y. Chen, J. Feng, C. Sha, X. Peng, and Y. Lou, "Evaluating large language models in classlevel code generation," in 2024 IEEE/ACM 46th International Conference on Software Engineering (ICSE). IEEE Computer Society, 2024, pp. 982–994.
- [434] X. Li, K. Dong, Y. Q. Lee, W. Xia, Y. Yin, H. Zhang, Y. Liu, Y. Wang, and R. Tang, "Coir: A comprehensive benchmark for code information retrieval models," arXiv preprint arXiv:2407.02883, 2024.
- [435] Z. Yang, J. Shi, J. He, and D. Lo, "Natural attack for pre-trained models of code," in *Proceedings of the 44th International Conference* on Software Engineering, 2022, pp. 1482–1493.
- [436] A. Jha and C. K. Reddy, "Codeattack: Code-based adversarial attacks for pre-trained programming language models," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2023, pp. 14 892–14 900.
- [437] R. Schuster, C. Song, E. Tromer, and V. Shmatikov, "You autocomplete me: Poisoning vulnerabilities in neural code completion," in 30th USENIX Security Symposium (USENIX Security 21), 2021, pp. 1559–1575.
- [438] Y. Wan, S. Zhang, H. Zhang, Y. Sui, G. Xu, D. Yao, H. Jin, and L. Sun, "You see what i want you to see: poisoning vulnerabilities in neural code search," in *Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2022, pp. 1233–1245.
- [439] W. Sun, Y. Chen, G. Tao, C. Fang, X. Zhang, Q. Zhang, and B. Luo, "Backdooring neural code search," in *Proceedings of the* 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2023, pp. 9692–9708.

- [440] Z. Yang, B. Xu, J. M. Zhang, H. J. Kang, J. Shi, J. He, and D. Lo, "Stealthy backdoor attack for code models," *IEEE Transactions on Software Engineering*, 2024.
- [441] J. Li, Z. Li, H. Zhang, G. Li, Z. Jin, X. Hu, and X. Xia, "Poison attack and poison detection on deep source code processing models," ACM Transactions on Software Engineering and Methodology, 2023.
- [442] Y. Li, S. Liu, K. Chen, X. Xie, T. Zhang, and Y. Liu, "Multi-target backdoor attacks for code pre-trained models," in *Proceedings* of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9-14, 2023. Association for Computational Linguistics, 2023, pp. 7236–7254.
- [443] Z. Li, C. Wang, P. Ma, C. Liu, S. Wang, D. Wu, C. Gao, and Y. Liu, "On extracting specialized code abilities from large language models: A feasibility study," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [444] W. Wang, H. Ning, G. Zhang, L. Liu, and Y. Wang, "Rocks coding, not development: A human-centric, experimental evaluation of llm-supported se tasks," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 699–721, 2024.
- [445] D. Nam, A. Macvean, V. Hellendoorn, B. Vasilescu, and B. Myers, "Using an llm to help with code understanding," in *Proceedings of* the IEEE/ACM 46th International Conference on Software Engineering, 2024, pp. 1–13.
- [446] R. Serafini, C. Otto, S. A. Horstmann, and A. Naiakshina, "Chatgpt-resistant screening instrument for identifying nonprogrammers," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [447] M. H. Tanzil, J. Y. Khan, and G. Uddin, "Chatgpt incorrectness detection in software reviews," in *Proceedings of the IEEE/ACM* 46th International Conference on Software Engineering, 2024, pp. 1– 12.
- [448] Y. Li, Y. Liu, G. Deng, Y. Zhang, W. Song, L. Shi, K. Wang, Y. Li, Y. Liu, and H. Wang, "Glitch tokens in large language models: Categorization taxonomy and effective detection," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 2075–2097, 2024.
- [449] W. Jiang, J. Zhai, S. Ma, X. Zhang, and C. Shen, "Costello: Contrastive testing for embedding-based large language model as a service embeddings," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 906–928, 2024.
- [450] M. Yang, Y. Chen, Y. Liu, and L. Shi, "Distillseq: A framework for safety alignment testing in large language models using knowledge distillation," arXiv preprint arXiv:2407.10106, 2024.
- [451] S. Hyun, M. Guo, and M. A. Babar, "Metal: Metamorphic testing framework for analyzing large-language model qualities," in 2024 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2024, pp. 117–128.
- [452] A. Al-Kaswan, M. Izadi, and A. Van Deursen, "Traces of memorisation in large language models for code," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–12.
- [453] Y. Liu, T. Le-Cong, R. Widyasari, C. Tantithamthavorn, L. Li, X.-B. D. Le, and D. Lo, "Refining chatgpt-generated code: Characterizing and mitigating code quality issues," ACM Transactions on Software Engineering and Methodology, vol. 33, no. 5, pp. 1–26, 2024.
- [454] K. Jesse, T. Ahmed, P. T. Devanbu, and E. Morgan, "Large language models and simple, stupid bugs," in 2023 IEEE/ACM 20th International Conference on Mining Software Repositories (MSR). IEEE, 2023, pp. 563–575.
- [455] Z. Liu, Y. Tang, X. Luo, Y. Zhou, and L. F. Zhang, "No need to lift a finger anymore? assessing the quality of code generation by chatgpt," *IEEE Transactions on Software Engineering*, 2024.
- [456] O. J. Idialu, N. S. Mathews, R. Maipradit, J. M. Atlee, and M. Nagappan, "Whodunit: Classifying code as human authored or gpt-4 generated-a case study on codechef problems," in *Proceedings* of the 21st International Conference on Mining Software Repositories, 2024, pp. 394–406.
- [457] A. Karmakar and R. Robbes, "Inspect: Intrinsic and systematic probing evaluation for code transformers," *IEEE Transactions on Software Engineering*, 2023.
- [458] D. Song, X. Xie, J. Song, D. Zhu, Y. Huang, F. Juefei-Xu, and L. Ma, "Luna: A model-based universal analysis framework for large language models," *IEEE Transactions on Software Engineering*, 2024.

- [459] D. Yao, J. Zhang, I. G. Harris, and M. Carlsson, "Fuzzllm: A novel and universal fuzzing framework for proactively discovering jailbreak vulnerabilities in large language models," in *ICASSP* 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2024, pp. 4485–4489.
- [460] W. Wang, Y. Wang, S. Joty, and S. C. Hoi, "Rap-gen: Retrievalaugmented patch generation with codet5 for automatic program repair," *arXiv preprint arXiv:2309.06057*, 2023.
- [461] E. Shi, Y. Wang, H. Zhang, L. Du, S. Han, D. Zhang, and H. Sun, "Towards efficient fine-tuning of pre-trained code models: An experimental study and beyond," in *Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2023, pp. 39–51.
- [462] M. Weyssow, X. Zhou, K. Kim, D. Lo, and H. Sahraoui, "Exploring parameter-efficient fine-tuning techniques for code generation with large language models," arXiv preprint arXiv:2308.10462, 2023.
- [463] J. Liu, C. Sha, and X. Peng, "An empirical study of parameterefficient fine-tuning methods for pre-trained code models," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 397–408.
- [464] T. Y. Zhuo, A. Zebaze, N. Suppattarachai, L. von Werra, H. de Vries, Q. Liu, and N. Muennighoff, "Astraios: Parameterefficient instruction tuning code large language models," arXiv preprint arXiv:2401.00788, 2024.
- [465] S. Gao, H. Zhang, C. Gao, and C. Wang, "Keeping pace with everincreasing data: Towards continual learning of code intelligence models," arXiv preprint arXiv:2302.03482, 2023.
- [466] M. Weyssow, X. Zhou, K. Kim, D. Lo, and H. Sahraoui, "On the usage of continual learning for out-of-distribution generalization in pre-trained language models of code," arXiv preprint arXiv:2305.04106, 2023.
- [467] S. Gao, W. Mao, C. Gao, L. Li, X. Hu, X. Xia, and M. R. Lyu, "Learning in the wild: Towards leveraging unlabeled data for effectively tuning pre-trained code models," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [468] A. Z. Yang, H. Tian, H. Ye, R. Martins, and C. L. Goues, "Security vulnerability detection with multitask self-instructed fine-tuning of large language models," arXiv preprint arXiv:2406.05892, 2024.
- [469] P. Jana, P. Jha, H. Ju, G. Kishore, A. Mahajan, and V. Ganesh, "Cotran: An llm-based code translator using reinforcement learning with feedback from compiler and symbolic execution," arXiv preprint arXiv:2306.06755, 2023.
- [470] W. Sun, C. Fang, Y. You, Y. Chen, Y. Liu, C. Wang, J. Zhang, Q. Zhang, H. Qian, W. Zhao *et al.*, "A prompt learning framework for source code summarization," *arXiv preprint arXiv*:2312.16066, 2023.
- [471] J. Shi, Z. Yang, B. Xu, H. J. Kang, and D. Lo, "Compressing pre-trained models of code into 3 mb," in *Proceedings of the* 37th IEEE/ACM International Conference on Automated Software Engineering, 2022, pp. 1–12.
- [472] C.-Y. Su and C. McMillan, "Distilled gpt for source code summarization," Automated Software Engineering, vol. 31, no. 1, p. 22, 2024.
- [473] M. Fu and C. Tantithamthavorn, "Linevul: A transformer-based line-level vulnerability prediction," in *Proceedings of the 19th International Conference on Mining Software Repositories*, 2022, pp. 608–620.
- [474] A. E. Gärtner and D. Göhlich, "Automated requirement contradiction detection through formal logic and llms," Automated Software Engineering, vol. 31, no. 2, p. 49, 2024.
- [475] A. F. Subahi, "Bert-based approach for greening software requirements engineering through non-functional requirements," *IEEE Access*, 2023.
- [476] X. Luo, Y. Xue, Z. Xing, and J. Sun, "Probert: Prompt learning for requirement classification using bert-based pretrained language models," in *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering*, 2022, pp. 1–13.
- [477] A. El-Hajjami, N. Fafin, and C. Salinesi, "Which ai technique is better to classify requirements? an experiment with svm, lstm, and chatgpt," arXiv preprint arXiv:2311.11547, 2023.
- [478] C. Arora, J. Grundy, and M. Abdelrazek, "Advancing requirements engineering through generative ai: Assessing the role of llms," in *Generative AI for Effective Software Development*. Springer, 2024, pp. 129–148.

- [479] S. Hassani, "Enhancing legal compliance and regulation analysis with large language models," arXiv preprint arXiv:2404.17522, 2024.
- [480] A. Vogelsang, "From specifications to prompts: On the future of generative llms in requirements engineering," *arXiv preprint arXiv:2408.09127*, 2024.
- [481] M. Fazelnia, V. Koscinski, S. Herzog, and M. Mirakhorli, "Lessons from the use of natural language inference (nli) in requirements engineering tasks," *arXiv preprint arXiv:2405.05135*, 2024.
- [482] D. Jin, Z. Jin, X. Chen, and C. Wang, "Mare: Multi-agents collaboration framework for requirements engineering," arXiv preprint arXiv:2405.03256, 2024.
- [483] A. Pilone, P. Meirelles, F. Kon, and W. Maalej, "Multilingual crowd-based requirements engineering using large language models," arXiv preprint arXiv:2408.06505, 2024.
- [484] K. Ronanki, B. Cabrero-Daniel, J. Horkoff, and C. Berger, "Requirements engineering using generative ai: Prompts and prompting patterns," in *Generative AI for Effective Software De*velopment. Springer, 2024, pp. 109–127.
- [485] B. Wang, C. Wang, P. Liang, B. Li, and C. Zeng, "How llms aid in uml modeling: An exploratory study with novice analysts," arXiv preprint arXiv:2404.17739, 2024.
- [486] C. Tinnes, A. Welter, and S. Apel, "Leveraging large language models for software model completion: Results from industrial and public datasets," *arXiv preprint arXiv:2406.17651*, 2024.
- [487] J. Wei, X. Chen, H. Xiao, S. Tang, X. Xie, and Z. Li, "Natural language processing-based requirements modeling: A case study on problem frames," in 2023 30th Asia-Pacific Software Engineering Conference (APSEC). IEEE, 2023, pp. 191–200.
- [488] Y. Li, J. Keung, X. Ma, C. Y. Chong, J. Zhang, and Y. Liao, "Llmbased class diagram derivation from user stories with chainof-thought promptings," in 2024 IEEE 48th Annual Computers, Software, and Applications Conference (COMPSAC). IEEE, 2024, pp. 45–50.
- [489] R. Sanyal, B. Ghoshal *et al.*, "A hybrid approach to extract conceptual diagram from software requirements," *Science of Computer Programming*, p. 103186, 2024.
- [490] S. G. Patil, T. Zhang, X. Wang, and J. E. Gonzalez, "Gorilla: Large language model connected with massive apis," arXiv preprint arXiv:2305.15334, 2023.
- [491] H. Ding, V. Kumar, Y. Tian, Z. Wang, R. Kwiatkowski, X. Li, M. K. Ramanathan, B. Ray, P. Bhatia, S. Sengupta *et al.*, "A static evaluation of code completion by large language models," *arXiv* preprint arXiv:2306.03203, 2023.
- [492] J. Y. Khan and G. Uddin, "Automatic detection and analysis of technical debts in peer-review documentation of r packages," in 2022 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2022, pp. 765–776.
- [493] M. Izadi, R. Gismondi, and G. Gousios, "Codefill: Multi-token code completion by jointly learning from structure and naming sequences," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 401–412.
- [494] N. Nashid, T. Shabani, P. Alian, and A. Mesbah, "Contextual api completion for unseen repositories using llms," *arXiv preprint arXiv:2405.04600*, 2024.
- [495] Y. Ding, Z. Wang, W. Ahmad, H. Ding, M. Tan, N. Jain, M. K. Ramanathan, R. Nallapati, P. Bhatia, D. Roth *et al.*, "Crosscodeeval: A diverse and multilingual benchmark for cross-file code completion," *Advances in Neural Information Processing Systems*, vol. 36, 2024.
- [496] A. Eghbali and M. Pradel, "De-hallucinator: Iterative grounding for llm-based code completion," arXiv preprint arXiv:2401.01701, 2024.
- [497] Z. Tang, J. Ge, S. Liu, T. Zhu, T. Xu, L. Huang, and B. Luo, "Domain adaptive code completion via language models and decoupled domain databases," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 421–433.
- [498] M. Ochs, K. Narasimhan, and M. Mezini, "Evaluating and improving transformers pre-trained on asts for code completion," in 2023 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2023, pp. 834–844.
- [499] L. Gong, S. Wang, M. Elhoushi, and A. Cheung, "Evaluation of llms on syntax-aware code fill-in-the-middle tasks," arXiv preprint arXiv:2403.04814, 2024.

- [500] R. Pudari and N. A. Ernst, "From copilot to pilot: Towards ai supported software development," arXiv preprint arXiv:2303.04142, 2023.
- [501] L. Zhang, Y. Li, J. Li, X. Xia, J. Yang, R. Luo, M. Wang, L. Chen, J. Liu, and M. Yang, "Hierarchical context pruning: Optimizing real-world code completion with repository-level pretrained code llms," arXiv preprint arXiv:2406.18294, 2024.
- [502] T. Dinh, J. Zhao, S. Tan, R. Negrinho, L. Lausen, S. Zha, and G. Karypis, "Large language models of code fail at completing code with potential bugs," *Advances in Neural Information Processing Systems*, vol. 36, 2024.
- [503] M. Zhang, B. Yuan, H. Li, and K. Xu, "Llm-cloud complete: Leveraging cloud computing for efficient large language modelbased code completion," *Journal of Artificial Intelligence General science (JAIGS) ISSN: 3006-4023*, vol. 5, no. 1, pp. 295–326, 2024.
- [504] J. A. Prenner and R. Robbes, "Making the most of small software engineering datasets with modern machine learning," *IEEE Transactions on Software Engineering*, vol. 48, no. 12, pp. 5050–5067, 2021.
- [505] J.-B. Döderlein, M. Acher, D. E. Khelladi, and B. Combemale, "Piloting copilot and codex: Hot temperature, cold prompts, or black magic?" arXiv preprint arXiv:2210.14699, 2022.
- [506] H. Tan, Q. Luo, L. Jiang, Z. Zhan, J. Li, H. Zhang, and Y. Zhang, "Prompt-based code completion via multi-retrieval augmented generation," arXiv preprint arXiv:2405.07530, 2024.
- [507] K. Deng, J. Liu, H. Zhu, C. Liu, J. Li, J. Wang, P. Zhao, C. Zhang, Y. Wu, X. Yin *et al.*, "R2c2-coder: Enhancing and benchmarking real-world repository-level code completion abilities of code large language models," *arXiv preprint arXiv:2406.01359*, 2024.
- [508] T. Liu, C. Xu, and J. McAuley, "Repobench: Benchmarking repository-level code auto-completion systems," arXiv preprint arXiv:2306.03091, 2023.
- [509] J. Li, R. Huang, W. Li, K. Yao, and W. Tan, "Toward less hidden cost of code completion with acceptance and ranking models," in 2021 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2021, pp. 195–205.
- [510] Z. Sun, X. Du, F. Song, S. Wang, and L. Li, "When neural code completion models size up the situation: Attaining cheaper and faster completion through dynamic model inference," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–12.
- [511] A. Kabir, S. Wang, Y. Tian, M. Asaduzzaman, W. Zhang et al., "Zs4c: Zero-shot synthesis of compilable code for incomplete code snippets using chatgpt," arXiv preprint arXiv:2401.14279, 2024.
- [512] S. Moon, Y. Song, H. Chae, D. Kang, T. Kwon, K. T.-i. Ong, S.-w. Hwang, and J. Yeo, "Coffee: Boost your code llms by fixing bugs with feedback," arXiv preprint arXiv:2311.07215, 2023.
- [513] M. Dilhara, A. Bellur, T. Bryksin, and D. Dig, "Unprecedented code change automation: The fusion of llms and transformation by example," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 631–653, 2024.
- [514] S. Wang, B. Lin, Z. Sun, M. Wen, Y. Liu, Y. Lei, and X. Mao, "Two birds with one stone: Boosting code generation and code search via a generative adversarial network," *Proceedings of the ACM on Programming Languages*, vol. 7, no. OOPSLA2, pp. 486–515, 2023.
- [515] A. Buscemi, "A comparative study of code generation using chatgpt 3.5 across 10 programming languages," arXiv preprint arXiv:2308.04477, 2023.
- [516] W. Zhang, T. Fu, T. Yuan, G. Zhang, D. Chen, and J. Wang, "A lightweight framework for adaptive retrieval in code completion with critique model," arXiv preprint arXiv:2406.10263, 2024.
- [517] M. L. Siddiq, B. Casey, and J. Santos, "A lightweight framework for high-quality code generation," *arXiv preprint arXiv:2307.08220*, 2023.
- [518] Y. Li, J. Shi, and Z. Zhang, "A novel approach for rapiddevelopment based on chatgpt and prompt engineering," arXiv preprint arXiv:2312.13115, 2023.
- [519] M. T. R. Laskar, M. S. Bari, M. Rahman, M. A. H. Bhuiyan, S. Joty, and J. X. Huang, "A systematic study and comprehensive evaluation of chatgpt on benchmark datasets," *arXiv preprint arXiv:2305.18486*, 2023.
- [520] N. Rao, J. Tsay, K. Kate, V. Hellendoorn, and M. Hirzel, "Ai for low-code for ai," in *Proceedings of the 29th International Conference* on Intelligent User Interfaces, 2024, pp. 837–852.
- [521] V. Dibia, A. Fourney, G. Bansal, F. Poursabzi-Sangdeh, H. Liu, and S. Amershi, "Aligning offline metrics and human judgments

of value of ai-pair programmers," *arXiv preprint arXiv:2210.16494*, 2022.

- [522] D. Huang, Z. Nan, X. Hu, P. Jin, S. Peng, Y. Wen, R. Zhang, Z. Du, Q. Guo, Y. Pu *et al.*, "Anpl: Compiling natural programs with interactive decomposition." *CoRR*, 2023.
- [523] K. Okuda and S. Amarasinghe, "Askit: Unified programming interface for programming with large language models," in 2024 IEEE/ACM International Symposium on Code Generation and Optimization (CGO). IEEE, 2024, pp. 41–54.
- [524] G. Antal, R. Vozár, and R. Ferenc, "Assessing gpt-4-vision's capabilities in uml-based code generation," arXiv preprint arXiv:2404.14370, 2024.
- [525] F. Tambon, A. Nikanjam, F. Khomh, and G. Antoniol, "Assessing programming task difficulty for efficient evaluation of large language models," arXiv preprint arXiv:2407.21227, 2024.
- [526] M. F. A. Khan, M. Ramsdell, E. Falor, and H. Karimi, "Assessing the promise and pitfalls of chatgpt for automated code generation," arXiv preprint arXiv:2311.02640, 2023.
- [527] N. Alshahwan, M. Harman, I. Harper, A. Marginean, S. Sengupta, and E. Wang, "Assured llm-based software engineering," arXiv preprint arXiv:2402.04380, 2024.
- [528] Z. Ji, P. Ma, Z. Li, and S. Wang, "Benchmarking and explaining large language model-based code generation: A causality-centric approach," arXiv preprint arXiv:2310.06680, 2023.
- [529] D. Ghosh Paul, H. Zhu, and I. Bayley, "Benchmarks and metrics for evaluations of code generation: A critical review," arXiv eprints, pp. arXiv–2406, 2024.
- [530] D. Huang, Q. Bu, J. Zhang, X. Xie, J. Chen, and H. Cui, "Bias assessment and mitigation in llm-based code generation," arXiv preprint arXiv:2309.14345, 2023.
- [531] A. K. Singh, Y. Yang, K. Tirumala, M. Elhoushi, and A. S. Morcos, "Brevity is the soul of wit: Pruning long files for code generation," arXiv preprint arXiv:2407.00434, 2024.
- [532] M. Li, A. Mishra, and U. Mujumdar, "Bridging the language gap: Enhancing multilingual prompt-based code generation in llms via zero-shot cross-lingual transfer," arXiv preprint arXiv:2408.09701, 2024.
- [533] L. Zhong and Z. Wang, "Can chatgpt replace stackoverflow? a study on robustness and reliability of large language model code generation," arXiv preprint arXiv:2308.10335, 2023.
- [534] D. Nichols, J. H. Davis, Z. Xie, A. Rajaram, and A. Bhatele, "Can large language models write parallel code?" *arXiv preprint arXiv:2401.12554*, 2024.
- [535] E. Jones and J. Steinhardt, "Capturing failures of large language models via human cognitive biases," *Advances in Neural Information Processing Systems*, vol. 35, pp. 11785–11799, 2022.
  [536] Z. Wang, J. Li, G. Li, and Z. Jin, "Chatcoder: Chat-based re-
- [536] Z. Wang, J. Li, G. Li, and Z. Jin, "Chatcoder: Chat-based refine requirement improves llms' code generation," arXiv preprint arXiv:2311.00272, 2023.
- [537] C. Sun, Y. Sheng, O. Padon, and C. Barrett, "Clover: Clo sedloop ver ifiable code generation," in *International Symposium on AI Verification*. Springer, 2024, pp. 134–155.
- [538] A. Jain, C. Adiole, S. Chaudhuri, T. Reps, and C. Jermaine, "Coarse-tuning models of code with reinforcement learning feedback," arXiv preprint arXiv:2305.18341, 2023.
- [539] P. Bareiß, B. Souza, M. d'Amorim, and M. Pradel, "Code generation tools (almost) for free? a study of few-shot, pre-trained language models on code," arXiv preprint arXiv:2206.01335, 2022.
- [540] T. Řidnik, D. Kredo, and I. Friedman, "Code generation with alphacodium: From prompt engineering to flow engineering," arXiv preprint arXiv:2401.08500, 2024.
- [541] Y.-D. Tsai, M. Liu, and H. Ren, "Code less, align more: Efficient llm fine-tuning for code generation with data pruning," arXiv preprint arXiv:2407.05040, 2024.
- [542] J. Chen, X. Hu, Z. Li, C. Gao, X. Xia, and D. Lo, "Code search is all you need? improving code suggestions with code search," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [543] S. Zhou, U. Alon, S. Agarwal, and G. Neubig, "Codebertscore: Evaluating code generation with pretrained models of code," arXiv preprint arXiv:2302.05527, 2023.
- [544] H. Le, H. Chen, A. Saha, A. Gokul, D. Sahoo, and S. Joty, "Codechain: Towards modular code generation through chain of self-revisions with representative sub-modules," arXiv preprint arXiv:2310.08992, 2023.
- [545] V. Murali, C. Maddila, I. Ahmad, M. Bolin, D. Cheng, N. Ghorbani, R. Fernandez, and N. Nagappan, "Codecompose: A large-

scale industrial deployment of ai-assisted code authoring," arXiv preprint arXiv:2305.12050, 2023.

- [546] D. Huang, Q. Bu, and H. Cui, "Codecot and beyond: Learning to program and test like a developer," *arXiv preprint arXiv:2308.08784*, 2023.
- [547] K. Du, R. Rui, H. Chai, L. Fu, W. Xia, Y. Wang, R. Tang, Y. Yu, and W. Zhang, "Codegrag: Extracting composed syntax graphs for retrieval augmented cross-lingual code generation," arXiv preprint arXiv:2405.02355, 2024.
- [548] P. Li, T. Sun, Q. Tang, H. Yan, Y. Wu, X. Huang, and X. Qiu, "Codeie: Large code generation models are better few-shot information extractors," arXiv preprint arXiv:2305.05711, 2023.
- [549] T. Zhang, T. Yu, T. Hashimoto, M. Lewis, W.-t. Yih, D. Fried, and S. Wang, "Coder reviewer reranking for code generation," in *International Conference on Machine Learning*. PMLR, 2023, pp. 41 832–41 846.
- [550] Y. Dong, J. Ding, X. Jiang, G. Li, Z. Li, and Z. Jin, "Codescore: Evaluating code generation by learning code execution," arXiv preprint arXiv:2301.09043, 2023.
- [551] R. Yen, J. Zhu, S. Suh, H. Xia, and J. Zhao, "Coladder: Supporting programmers with hierarchical code generation in multi-level abstraction," arXiv preprint arXiv:2310.08699, 2023.
- [552] Y. Chen, Y. Liu, F. Meng, Y. Chen, J. Xu, and J. Zhou, "Comments as natural logic pivots: Improve code generation via comment perspective," arXiv preprint arXiv:2404.07549, 2024.
- [553] N. Nascimento, P. Alencar, and D. Cowan, "Comparing software developers with chatgpt: An empirical investigation," arXiv preprint arXiv:2305.11837, 2023.
- [554] C. W. Tan, S. Guo, M. F. Wong, and C. N. Hang, "Copilot for xcode: Exploring ai-assisted programming by prompting cloudbased large language models," arXiv preprint arXiv:2307.14349, 2023.
- [555] F. Wu, X. Liu, and C. Xiao, "Deceptprompt: Exploiting llm-driven code generation via adversarial natural language instructions," arXiv preprint arXiv:2312.04730, 2023.
- [556] T. X. Olausson, J. P. Inala, C. Wang, J. Gao, and A. Solar-Lezama, "Demystifying gpt self-repair for code generation," arXiv preprint arXiv:2306.09896, 2023.
- [557] J. Li, G. Li, Y. Zhao, Y. Li, Z. Jin, H. Zhu, H. Liu, K. Liu, L. Wang, Z. Fang *et al.*, "Deveval: Evaluating code generation in practical software projects," *arXiv preprint arXiv*:2401.06401, 2024.
- [558] K. Li, S. Hong, C. Fu, Y. Zhang, and M. Liu, "Discriminating human-authored from chatgpt-generated code via discernable feature analysis," in 2023 IEEE 34th International Symposium on Software Reliability Engineering Workshops (ISSREW). IEEE, 2023, pp. 120–127.
- [559] J. Li and R. Mooney, "Distilling algorithmic reasoning from llms via explaining solution programs," arXiv preprint arXiv:2404.08148, 2024.
- [560] Y. Lai, C. Li, Y. Wang, T. Zhang, R. Zhong, L. Zettlemoyer, W.-t. Yih, D. Fried, S. Wang, and T. Yu, "Ds-1000: A natural and reliable benchmark for data science code generation," in *International Conference on Machine Learning*. PMLR, 2023, pp. 18319–18345.
- [561] J. Li, G. Li, Y. Li, and Z. Jin, "Enabling programming thinking in large language models toward code generation," arXiv preprint arXiv:2305.06599, 2023.
- [562] K. Yang, X. Mao, S. Wang, T. Zhang, B. Lin, Y. Wang, Y. Qin, Z. Zhang, and X. Mao, "Enhancing code intelligence tasks with chatgpt," arXiv preprint arXiv:2312.15202, 2023.
- [563] B. Huang, S. Lu, W. Chen, X. Wan, and N. Duan, "Enhancing large language models in coding through multi-perspective selfconsistency," arXiv preprint arXiv:2309.17272, 2023.
- [564] A. Shapkin, D. Litvinov, and T. Bryksin, "Entity-augmented code generation," arXiv preprint arXiv:2312.08976, 2023.
- [565] A. Patel, S. Reddy, D. Bahdanau, and P. Dasigi, "Evaluating incontext learning of libraries for code generation," arXiv preprint arXiv:2311.09635, 2023.
- [566] Y. Assogba and D. Ren, "Evaluating long range dependency handling in code generation models using multi-step key retrieval," arXiv preprint arXiv:2407.21049, 2024.
- [567] B. Yetiştiren, I. Özsoy, M. Ayerdem, and E. Tüzün, "Evaluating the code quality of ai-assisted code generation tools: An empirical study on github copilot, amazon codewhisperer, and chatgpt," arXiv preprint arXiv:2304.10778, 2023.
- [568] D. Wang, J. Zhao, H. Pei, S. Tan, and S. Zha, "Fine-tuning language models for joint rewriting and completion of code with

potential bugs," in *Findings of the Association for Computational Linguistics ACL 2024*, 2024, pp. 15854–15868.

- [569] X. Ren, X. Ye, D. Zhao, Z. Xing, and X. Yang, "From misuse to mastery: Enhancing code generation with knowledge-driven ai chaining," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 976–987.
- [570] H. To, M. Nguyen, and N. Bui, "Functional overlap reranking for neural code generation," in *Findings of the Association for Computational Linguistics ACL 2024*, 2024, pp. 3686–3704.
- [571] M. Fu and C. Tantithamthavorn, "Gpt2sp: A transformer-based agile story point estimation approach," *IEEE Transactions on Software Engineering*, vol. 49, no. 2, pp. 611–625, 2022.
- [572] G. Dong, H. Yuan, K. Lu, C. Li, M. Xue, D. Liu, W. Wang, Z. Yuan, C. Zhou, and J. Zhou, "How abilities in large language models are affected by supervised fine-tuning data composition," arXiv preprint arXiv:2310.05492, 2023.
- [573] M. Kazemitabaar, X. Hou, A. Henley, B. J. Ericson, D. Weintrop, and T. Grossman, "How novices use llm-based code generators to solve cs1 coding tasks in a self-paced learning environment," in *Proceedings of the 23rd Koli Calling International Conference on Computing Education Research*, 2023, pp. 1–12.
- [574] A. Malkadi, A. Tayeb, and S. Haiduc, "Improving code extraction from coding screencasts using a code-aware encoder-decoder model," in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 1492–1504.
- [575] S. Ugare, T. Suresh, H. Kang, S. Misailovic, and G. Singh, "Improving llm code generation with grammar augmentation," arXiv preprint arXiv:2403.01632, 2024.
- [576] S. K. Lahiri, S. Fakhoury, A. Naik, G. Sakkas, S. Chakraborty, M. Musuvathi, P. Choudhury, C. von Veh, J. P. Inala, C. Wang et al., "Interactive code generation via test-driven user-intent formalization," arXiv preprint arXiv:2208.05950, 2022.
- [577] W.-D. Li and K. Ellis, "Is programming by example solved by llms?" arXiv preprint arXiv:2406.08316, 2024.
- [578] H. Koziolek, S. Grüner, R. Hark, V. Ashiwal, S. Linsbauer, and N. Eskandani, "Llm-based and retrieval-augmented control code generation," in *Proc. 1st Int. Workshop on Large Language Models* for Coffice (LLM4Code) at ICSE, vol. 2024, 2024.
- [579] M. Chen, H. Tian, Z. Liu, X. Ren, and J. Sun, "Jumpcoder: Go beyond autoregressive coder via online modification," arXiv preprint arXiv:2401.07870, 2024.
- [580] T. Huang, Z. Sun, Z. Jin, G. Li, and C. Lyu, "Knowledge-aware code generation with large language models," in *Proceedings of the 32nd IEEE/ACM International Conference on Program Comprehension*, 2024, pp. 52–63.
- [581] A. Ni, P. Yin, Y. Zhao, M. Riddell, T. Feng, R. Shen, S. Yin, Y. Liu, S. Yavuz, C. Xiong *et al.*, "L2ceval: Evaluating language-to-code generation capabilities of large language models," *arXiv preprint arXiv:2309.17446*, 2023.
- [582] J. Xu, Z. Liu, N. A. V. Suryanarayanan, and H. Iba, "Large language models synergize with automated machine learning," arXiv preprint arXiv:2405.03727, 2024.
- [583] X. Wang, H. Peng, R. Jabbarvand, and H. Ji, "Leti: Learning to generate from textual interactions," arXiv preprint arXiv:2305.10314, 2023.
- [584] X. Hu, K. Kuang, J. Sun, H. Yang, and F. Wu, "Leveraging print debugging to improve code generation in large language models," arXiv preprint arXiv:2401.05319, 2024.
- [585] S. Ouyang, J. M. Zhang, M. Harman, and M. Wang, "Llm is like a box of chocolates: the non-determinism of chatgpt in code generation," arXiv preprint arXiv:2308.02828, 2023.
- [586] N. Jain, T. Zhang, W.-L. Chiang, J. E. Gonzalez, K. Sen, and I. Stoica, "Llm-assisted code cleaning for training accurate code generators," arXiv preprint arXiv:2311.14904, 2023.
- [587] Q. Gu, "Llm-based code generation method for golang compiler testing," in Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 2201–2203.
- [588] D. Hendrycks, S. Basart, S. Kadavath, M. Mazeika, A. Arora, E. Guo, C. Burns, S. Puranik, H. He, D. Song *et al.*, "Measuring coding challenge competence with apps," *arXiv preprint arXiv*:2105.09938, 2021.
- [589] S. Hong, X. Zheng, J. Chen, Y. Cheng, J. Wang, C. Zhang, Z. Wang, S. K. S. Yau, Z. Lin, L. Zhou *et al.*, "Metagpt: Meta programming for multi-agent collaborative framework," *arXiv* preprint arXiv:2308.00352, 2023.

- [590] B. Chen, M. Zhu, B. Dolan-Gavitt, M. Shafique, and S. Garg, "Model cascading for code: Reducing inference costs with model cascading for llm based code generation," arXiv preprint arXiv:2405.15842, 2024.
- [591] J. Li, P. Chen, and J. Jia, "Motcoder: Elevating large language models with modular of thought for challenging programming tasks," arXiv preprint arXiv:2312.15960, 2023.
- [592] Z. Dai, C. Yao, W. Han, Y. Yuan, Z. Gao, and J. Chen, "Mpcoder: Multi-user personalized code generator with explicit and implicit style representation learning," arXiv preprint arXiv:2406.17255, 2024.
- [593] S. Wang, L. Ding, L. Shen, Y. Luo, B. Du, and D. Tao, "Oop: Object-oriented programming evaluation benchmark for large language models," arXiv preprint arXiv:2401.06628, 2024.
- [594] C. Arora, A. I. Sayeed, S. Licorish, F. Wang, and C. Treude, "Optimizing large language model hyperparameters for code generation," arXiv preprint arXiv:2408.10577, 2024.
- [595] Z. Fan, H. Ruan, S. Mechtaev, and A. Roychoudhury, "Oracleguided program selection from large language models," 2018.
- [596] W. Zheng, S. Sharan, A. K. Jaiswal, K. Wang, Y. Xi, D. Xu, and Z. Wang, "Outline, then details: Syntactically guided coarseto-fine code generation," in *International Conference on Machine Learning*. PMLR, 2023, pp. 42 403–42 419.
- [597] D. Nichols, P. Polasam, H. Menon, A. Marathe, T. Gamblin, and A. Bhatele, "Performance-aligned llms for generating fast code," arXiv preprint arXiv:2404.18864, 2024.
- [598] D. Zan, B. Chen, Y. Gong, J. Cao, F. Zhang, B. Wu, B. Guan, Y. Yin, and Y. Wang, "Private-library-oriented code generation with large language models," arXiv preprint arXiv:2307.15370, 2023.
- [599] T. Pegolotti, E. Frantar, D. Alistarh, and M. Püschel, "Qigen: Generating efficient kernels for quantized inference on large language models," arXiv preprint arXiv:2307.03738, 2023.
- [600] M. L. Siddiq, S. Dristi, J. Saha, and J. Santos, "Quality assessment of prompts used in code generation," arXiv preprint arXiv:2404.10155, 2024.
- [601] M. Riddell, A. Ni, and A. Cohan, "Quantifying contamination in evaluating code generation capabilities of language models," arXiv preprint arXiv:2403.04811, 2024.
- [602] S. Wang, Z. Li, H. Qian, C. Yang, Z. Wang, M. Shang, V. Kumar, S. Tan, B. Ray, P. Bhatia *et al.*, "Recode: Robustness evaluation of code generation models," *arXiv preprint arXiv:2212.10264*, 2022.
- [603] D. Kang, K. J. Seo, and T. Kim, "Revisiting the impact of pursuing modularity for code generation," arXiv preprint arXiv:2407.11406, 2024.
- [604] X. Wu, N. Cheriere, C. Zhang, and D. Narayanan, "Rustgen: An augmentation approach for generating compilable rust code with large language models."
- [605] H. Su, J. Kasai, C. H. Wu, W. Shi, T. Wang, J. Xin, R. Zhang, M. Ostendorf, L. Zettlemoyer, N. A. Smith *et al.*, "Selective annotation makes language models better few-shot learners," *arXiv preprint arXiv*:2209.01975, 2022.
- [606] Y. Tian and T. Zhang, "Selective prompt anchoring for code generation," arXiv preprint arXiv:2408.09121, 2024.
- [607] L. Zheng, J. Yuan, Z. Zhang, H. Yang, and L. Kong, "Self-infilling code generation," in *Forty-first International Conference on Machine Learning*, 2023.
- [608] E. Zelikman, E. Lorch, L. Mackey, and A. T. Kalai, "Self-taught optimizer (stop): Recursively self-improving code generation," arXiv preprint arXiv:2310.02304, 2023.
- [609] S. Jiang, Y. Wang, and Y. Wang, "Selfevolve: A code evolution framework via large language models," arXiv preprint arXiv:2306.02907, 2023.
- [610] C. Zhu-Tian, Z. Xiong, X. Yao, and E. Glassman, "Sketch then generate: Providing incremental user feedback and guiding llm code generation through language-oriented code sketches," arXiv preprint arXiv:2405.03998, 2024.
- [611] J. Li, G. Li, Y. Li, and Z. Jin, "Structured chain-of-thought prompting for code generation," ACM Transactions on Software Engineering and Methodology, 2023.
- [612] C. E. Jimenez, J. Yang, A. Wettig, S. Yao, K. Pei, O. Press, and K. Narasimhan, "Swe-bench: Can language models resolve realworld github issues?" arXiv preprint arXiv:2310.06770, 2023.
- [613] L. Sarker, M. Downing, A. Desai, and T. Bultan, "Syntactic robustness for llm-based code generation," arXiv preprint arXiv:2404.01535, 2024.

- [614] C. Wang, J. Zhang, Y. Feng, T. Li, W. Sun, Y. Liu, and X. Peng, "Teaching code llms to use autocompletion tools in repositorylevel code generation," arXiv preprint arXiv:2401.06391, 2024.
- [615] Z. Tian and J. Chen, "Test-case-driven programming understanding in large language models for better code generation," arXiv preprint arXiv:2309.16120, 2023.
- [616] M. Hassid, T. Remez, J. Gehring, R. Schwartz, and Y. Adi, "The larger the better? improved llm code-generation via budget reallocation," arXiv preprint arXiv:2404.00725, 2024.
- [617] A. Tarassow, "The potential of llms for coding with low-resource and domain-specific programming languages," *arXiv preprint arXiv:2307.13018*, 2023.
- [618] X.-Y. Li, J.-T. Xue, Z. Xie, and M. Li, "Think outside the code: Brainstorming boosts large language models in code generation," arXiv preprint arXiv:2305.10679, 2023.
- [619] Z.-C. Lyu, X.-Y. Li, Z. Xie, and M. Li, "Top pass: Improve code generation by pass@ k-maximized code ranking," arXiv preprint arXiv:2408.05715, 2024.
- [620] S. Fakhoury, S. Chakraborty, M. Musuvathi, and S. K. Lahiri, "Towards generating functionally correct code edits from natural language issue descriptions," arXiv preprint arXiv:2304.03816, 2023.
- [621] D. Busch, A. Bainczyk, and B. Steffen, "Towards llm-based system migration in language-driven engineering," in *International Conference on Engineering of Computer-Based Systems*. Springer, 2023, pp. 191–200.
- [622] J. Wu, E. Schoop, A. Leung, T. Barik, J. P. Bigham, and J. Nichols, "Uicoder: Finetuning large language models to generate user interface code through automated feedback," *arXiv preprint arXiv:2406.07739*, 2024.
- [623] M. Allamanis, S. Panthaplackel, and P. Yin, "Unsupervised evaluation of code llms with round-trip correctness," *arXiv preprint arXiv:2402.08699*, 2024.
- [624] S. Thakur, B. Ahmad, H. Pearce, B. Tan, B. Dolan-Gavitt, R. Karri, and S. Garg, "Verigen: A large language model for verilog code generation," ACM Transactions on Design Automation of Electronic Systems, vol. 29, no. 3, pp. 1–31, 2024.
- [625] L. Gong, J. Zhang, M. Wei, H. Zhang, and Z. Huang, "What is the intended usage context of this model? an exploratory study of pre-trained models on various model repositories," ACM *Transactions on Software Engineering and Methodology*, vol. 32, no. 3, pp. 1–57, 2023.
- [626] D. Zan, B. Chen, Z. Lin, B. Guan, Y. Wang, and J.-G. Lou, "When language model meets private library," *arXiv preprint arXiv:2210.17236*, 2022.
- [627] L. Guo, Y. Wang, E. Shi, W. Zhong, H. Zhang, J. Chen, R. Zhang, Y. Ma, and Z. Zheng, "When to stop? towards efficient code generation in llms with excess token prevention," arXiv preprint arXiv:2407.20042, 2024.
- [628] J. Liu, X. Tang, L. Li, P. Chen, and Y. Liu, "Which is a better programming assistant? a comparative study between chatgpt and stack overflow," arXiv preprint arXiv:2308.13851, 2023.
- [629] M. A. M. Khan, M. S. Bari, X. L. Do, W. Wang, M. R. Parvez, and S. Joty, "xcodeeval: A large scale multilingual multitask benchmark for code understanding, generation, translation and retrieval," arXiv preprint arXiv:2303.03004, 2023.
- [630] G. Yang, Y. Zhou, X. Chen, X. Zhang, T. Han, and T. Chen, "Exploitgen: Template-augmented exploit code generation based on codebert," *Journal of Systems and Software*, vol. 197, p. 111577, 2023.
- [631] Y. Zhu, J. Li, G. Li, Y. Zhao, Z. Jin, and H. Mei, "Hot or cold? adaptive temperature sampling for code generation with large language models," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 1, 2024, pp. 437–445.
- [632] A. Varkey, S. Jiang, and W. Huang, "Codecse: A simple multilingual model for code and comment sentence embeddings," arXiv preprint arXiv:2407.06360, 2024.
- [633] Y. Li, T. Zhang, X. Luo, H. Cai, S. Fang, and D. Yuan, "Do pretrained language models indeed understand software engineering tasks?" *IEEE Transactions on Software Engineering*, 2023.
- [634] D. Li, Y. Shen, R. Jin, Y. Mao, K. Wang, and W. Chen, "Generationaugmented query expansion for code retrieval," arXiv preprint arXiv:2212.10692, 2022.
- [635] S. Jain, A. Dora, K. S. Sam, and P. Singh, "Llm agents improve semantic code search," arXiv preprint arXiv:2408.11058, 2024.

- [636] A. Saieva, S. Chakraborty, and G. Kaiser, "On contrastive learning of semantic similarity forcode to code search," *arXiv preprint arXiv:2305.03843*, 2023.
- [637] G. Fan, S. Chen, C. Gao, J. Xiao, T. Zhang, and Z. Feng, "Rapid: Zero-shot domain adaptation for code search with pre-trained models," ACM Transactions on Software Engineering and Methodology, vol. 33, no. 5, pp. 1–35, 2024.
- [638] H. Li, X. Zhou, and Z. Shen, "Rewriting the code: A simple method for large language model augmented code search," arXiv preprint arXiv:2401.04514, 2024.
- [639] Y. Mao, C. Wan, Y. Jiang, and X. Gu, "Self-supervised query reformulation for code search," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on* the Foundations of Software Engineering, 2023, pp. 363–374.
- [640] Y. Wang, L. Guo, E. Shi, W. Chen, J. Chen, W. Zhong, M. Wang, H. Li, H. Zhang, Z. Lyu et al., "You augment me: Exploring chatgpt-based data augmentation for semantic code search," in 2023 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2023, pp. 14–25.
- [641] S. Wang, M. Geng, B. Lin, Z. Sun, M. Wen, Y. Liu, L. Li, T. F. Bissyandé, and X. Mao, "Natural language to code: How far are we?" in Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 375–387.
- [642] S. S. Dvivedi, V. Vijay, S. L. R. Pujari, S. Lodh, and D. Kumar, "A comparative analysis of large language models for code documentation generation," arXiv preprint arXiv:2312.10349, 2023.
- [643] A. R. Sadik, A. Ceravola, F. Joublin, and J. Patra, "Analysis of chatgpt on source code," arXiv preprint arXiv:2306.00597, 2023.
- [644] R. Haldar and J. Hockenmaier, "Analyzing the performance of large language models on code summarization," *arXiv preprint arXiv:2404.08018*, 2024.
- [645] J. Gu, P. Salza, and H. C. Gall, "Assemble foundation models for automatic code summarization," in 2022 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2022, pp. 935–946.
- [646] J. Zhao, X. Chen, G. Yang, and Y. Shen, "Automatic smart contract comment generation via large language models and in-context learning," *Information and Software Technology*, vol. 168, p. 107405, 2024.
- [647] J. Kumar and S. Chimalakonda, "Code summarization without direct access to code-towards exploring federated llms for software engineering," in *Proceedings of the 28th International Conference on Evaluation and Assessment in Software Engineering*, 2024, pp. 100–109.
- [648] S. Gao, X.-C. Wen, C. Gao, W. Wang, and M. R. Lyu, "Constructing effective in-context demonstration for code intelligence tasks: An empirical study," arXiv preprint arXiv:2304.07575, p. 17, 2023.
- [649] C.-Y. Šu, A. Bansal, Y. Huang, T. J.-J. Li, and C. McMillan, "Context-aware code summary generation," *arXiv preprint arXiv:2408.09006*, 2024.
- [650] S. Oh and S. Yoo, "Csa-trans: Code structure aware transformer for ast," arXiv preprint arXiv:2404.05767, 2024.
- [651] B. Poudel, A. Cook, S. Traore, and S. Ameli, "Documint: Docstring generation for python using small language models," arXiv preprint arXiv:2405.10243, 2024.
- [652] Y. Virk, P. Devanbu, and T. Ahmed, "Enhancing trust in llmgenerated code summaries with calibrated confidence scores," arXiv preprint arXiv:2404.19318, 2024.
- [653] S. Arakelyan, R. Das, Y. Mao, and X. Ren, "Exploring distributional shifts in large language models for code analysis," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023, pp. 16298–16314.
- [654] S. Pordanesh and B. Tan, "Exploring the efficacy of large language models (gpt-4) in binary reverse engineering," arXiv preprint arXiv:2406.06637, 2024.
- [655] A. Al-Kaswan, T. Ahmed, M. Izadi, A. A. Sawant, P. Devanbu, and A. van Deursen, "Extending source code pre-trained language models to summarise decompiled binaries," in 2023 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2023, pp. 260–271.
- [656] S. Kang, L. Milliken, and S. Yoo, "Identifying inaccurate descriptions in llm-generated code comments via test execution," arXiv preprint arXiv:2406.14836, 2024.
- [657] B. Szalontai, G. Szalay, T. Márton, A. Sike, B. Pintér, and T. Gregorics, "Large language models for code summarization," 2024. [Online]. Available: https://arxiv.org/abs/2405.19032

- [658] H. Lu, H. Peng, G. Nan, J. Cui, C. Wang, and W. Jin, "Malsight: Exploring malicious source code and benign pseudocode for iterative binary malware summarization," arXiv preprint arXiv:2406.18379, 2024.
- [659] I. Saberi, F. Fard, and F. Chen, "Multilingual adapter-based knowledge aggregation on code summarization for low-resource languages," arXiv preprint arXiv:2307.07854, 2023.
- [660] Y. Wang, X. Li, T. Nguyen, S. Wang, C. Ni, and L. Ding, "Natural is the best: Model-agnostic code simplification for pre-trained large language models," arXiv preprint arXiv:2405.11196, 2024.
- [661] K. Shi, D. Altınbüken, S. Anand, M. Christodorescu, K. Grünwedel, A. Koenings, S. Naidu, A. Pathak, M. Rasi, F. Ribeiro *et al.*, "Natural language outlines for code: Literate programming in the llm era," *arXiv preprint arXiv:2408.04820*, 2024.
- [662] F. Chen, F. H. Fard, D. Lo, and T. Bryksin, "On the transferability of pre-trained language models for low-resource programming languages," in *Proceedings of the 30th IEEE/ACM International Conference on Program Comprehension*, 2022, pp. 401–412.
- [663] C.-Y. Su and C. McMillan, "Semantic similarity loss for neural source code summarization," *Journal of Software: Evolution and Process*, p. e2706, 2023.
- [664] E. Shi, F. Zhang, Y. Wang, B. Chen, L. Du, H. Zhang, S. Han, D. Zhang, and H. Sun, "Sotana: The open-source software development assistant," arXiv preprint arXiv:2308.13416, 2023.
- [665] W. Sun, Y. Miao, Y. Li, H. Zhang, C. Fang, Y. Liu, G. Deng, Y. Liu, and Z. Chen, "Source code summarization in the era of large language models," arXiv preprint arXiv:2407.07959, 2024.
- [666] Y. Wang, Y. Huang, D. Guo, H. Zhang, and Z. Zheng, "Sparsecoder: Identifier-aware sparse transformer for file-level code summarization," arXiv preprint arXiv:2401.14727, 2024.
- [667] G. Fan, S. Chen, H. Wu, C. Gao, J. Xiao, X. Xue, and Z. Feng, "Dialog summarization for software collaborative platform via tuning pre-trained models," *Journal of Systems and Software*, vol. 204, p. 111763, 2023.
- [668] Y. Shen, X. Ju, X. Chen, and G. Yang, "Bash comment generation via data augmentation and semantic-aware codebert," *Automated Software Engineering*, vol. 31, no. 1, p. 30, 2024.
- [669] J. Shin, C. Tang, T. Mohati, M. Nayebi, S. Wang, and H. Hemmati, "Prompt engineering or fine tuning: An empirical assessment of large language models in automated software engineering tasks," arXiv preprint arXiv:2310.10508, 2023.
- [670] M. Xue, A. Andrzejak, and M. Leuther, "An interpretable error correction method for enhancing code-to-code translation," in *The Twelfth International Conference on Learning Representations*.
- [671] G. Yang, Y. Zhou, X. Zhang, X. Chen, T. Han, and T. Chen, "Assessing and improving syntactic adversarial robustness of pre-trained models for code translation," *arXiv preprint arXiv:2310.18587*, 2023.
- [672] N. D. Bui, H. Le, Y. Wang, J. Li, A. D. Gotmare, and S. C. Hoi, "Codetf: One-stop transformer library for state-of-the-art code llm," arXiv preprint arXiv:2306.00029, 2023.
- [673] W. Yan, Y. Tian, Y. Li, Q. Chen, and W. Wang, "Codetransocean: A comprehensive multilingual benchmark for code translation," arXiv preprint arXiv:2310.04951, 2023.
- [674] M. Bhattarai, J. E. Santos, S. Jones, A. Biswas, B. Alexandrov, and D. O'Malley, "Enhancing code translation in language models with few-shot learning via retrieval-augmented generation," arXiv preprint arXiv:2407.19619, 2024.
- [675] Z. Tang, M. Agarwal, A. Shypula, B. Wang, D. Wijaya, J. Chen, and Y. Kim, "Explain-then-translate: an analysis on improving program translation with self-generated explanations," arXiv preprint arXiv:2311.07070, 2023.
- [676] M. Macedo, Y. Tian, F. Cogo, and B. Adams, "Exploring the impact of the output format on the evaluation of large language models for code translation," in *Proceedings of the 2024 IEEE/ACM First International Conference on AI Foundation Models and Software Engineering*, 2024, pp. 57–68.
- [677] M. T. Dearing, Y. Tao, X. Wu, Z. Lan, and V. Taylor, "Lassi: An Ilmbased automated self-correcting pipeline for translating parallel scientific codes," arXiv preprint arXiv:2407.01638, 2024.
- [678] R. Baltaji, S. Pujar, L. Mandel, M. Hirzel, L. Buratti, and L. Varshney, "Learning transfers over several programming languages," arXiv preprint arXiv:2310.16937, 2023.
- [679] Y. Huang, M. Qi, Y. Yao, M. Wang, B. Gu, C. Clement, and N. Sundaresan, "Program translation via code distillation," arXiv preprint arXiv:2310.11476, 2023.

- [680] X. Yin, C. Ni, T. N. Nguyen, S. Wang, and X. Yang, "Rectifier: Code translation with corrector via llms," *arXiv preprint arXiv*:2407.07472, 2024.
- [681] V. Nitin and B. Ray, "Spectra: Enhancing the code translation ability of language models by generating multi-modal specifications," arXiv preprint arXiv:2405.18574, 2024.
- [682] J. Pan, A. Sadé, J. Kim, E. Soriano, G. Sole, and S. Flamant, "Stelocoder: a decoder-only llm for multi-language to python code translation," arXiv preprint arXiv:2310.15539, 2023.
- [683] M. Qi, Y. Huang, M. Wang, Y. Yao, Z. Liu, B. Gu, C. Clement, and N. Sundaresan, "Sut: Active defects probing for transcompiler models," arXiv preprint arXiv:2310.14209, 2023.
- [684] H. F. Eniser, H. Zhang, C. David, M. Wang, B. Paulsen, J. Dodds, and D. Kroening, "Towards translating real-world code with llms: A study of translating to rust," arXiv preprint arXiv:2405.11514, 2024.
- [685] R. Pan, A. Ibrahimzada, R. Krishna, D. Sankar, L. Wassi, M. Merler, B. Sobolev, R. Pavuluri, S. Sinha, and R. Jabbarvand, "Understanding the effectiveness of large language models in code translation. preprint (2023)," arXiv preprint arXiv:2308.03109.
- [686] A. Z. Yang, Y. Takashima, B. Paulsen, J. Dodds, and D. Kroening, "Vert: Verified equivalent rust transpilation with few-shot learning," arXiv preprint arXiv:2404.18852, 2024.
- [687] X. Li, S. Yuan, X. Gu, Y. Chen, and B. Shen, "Few-shot code translation via task-adapted prompt learning," *Journal of Systems* and Software, vol. 212, p. 112002, 2024.
- [688] M. Zhu, K. Suresh, and C. K. Reddy, "Multilingual code snippets training for program translation," in *Proceedings of the AAAI* conference on artificial intelligence, vol. 36, no. 10, 2022, pp. 11783– 11790.
- [689] B. Paranjape, S. Lundberg, S. Singh, H. Hajishirzi, L. Zettlemoyer, and M. T. Ribeiro, "Art: Automatic multi-step reasoning and tooluse for large language models," arXiv preprint arXiv:2303.09014, 2023.
- [690] Y. Ding, J. Peng, M. J. Min, G. Kaiser, J. Yang, and B. Ray, "Semcoder: Training code language models with comprehensive semantics," arXiv preprint arXiv:2406.01006, 2024.
- [691] W. Ma, S. Liu, W. Wang, Q. Hu, Y. Liu, C. Zhang, L. Nie, and Y. Liu, "The scope of chatgpt in software engineering: A thorough investigation," arXiv preprint arXiv:2305.12138, 2023.
- [692] F. Artuso, M. Mormando, G. A. Di Luna, and L. Querzoni, "Binbert: Binary code understanding with a fine-tunable and execution-aware transformer," *IEEE Transactions on Dependable and Secure Computing*, 2024.
- [693] S. Utpala, A. Gu, and P. Y. Chen, "Language agnostic code embeddings," arXiv preprint arXiv:2310.16803, 2023.
- [694] H. Pei, J. Zhao, L. Lausen, S. Zha, and G. Karypis, "Better context makes better code language models: A case study on function call argument completion," in *Proceedings of the AAAI Conference* on Artificial Intelligence, vol. 37, no. 4, 2023, pp. 5230–5238.
- [695] J. Shi, S. Jiang, B. Xu, J. Liang, Y. Xiao, and W. Wang, "Shellgpt: Generative pre-trained transformer model for shell language understanding," in 2023 IEEE 34th International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2023, pp. 671–682.
- [696] I. Abdelaziz, J. Dolby, J. McCusker, and K. Srinivas, "Can machines read coding manuals yet?-a benchmark for building better language models for code understanding," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 36, no. 4, 2022, pp. 4415-4423.
- [697] D. Nam, A. Macvean, V. Hellendoorn, B. Vasilescu, and B. Myers, "In-ide generation-based information support with a large language model," arXiv preprint arXiv:2307.08177, 2023.
- [698] N. Tao, A. Ventresque, V. Nallur, and T. Saber, "Enhancing program synthesis with large language models using manyobjective grammar-guided genetic programming," *Algorithms*, vol. 17, no. 7, p. 287, 2024.
- [699] A. Singla, "Evaluating chatgpt and gpt-4 for visual programming," in Proceedings of the 2023 ACM Conference on International Computing Education Research-Volume 2, 2023, pp. 14–15.
- [700] A. Shirafuji, Y. Watanobe, T. Ito, M. Morishita, Y. Nakamura, Y. Oda, and J. Suzuki, "Exploring the robustness of large language models for solving programming problems," arXiv preprint arXiv:2306.14583, 2023.
- [701] P. Hajali and I. Budvytis, "Function-constrained program synthesis," arXiv preprint arXiv:2311.15500, 2023.
- [702] J. Ye, C. Li, L. Kong, and T. Yu, "Generating data for symbolic language with large language models," in *Proceedings of the 2023*

Conference on Empirical Methods in Natural Language Processing, 2023, pp. 8418–8443.

- [703] Y. Li, J. Parsert, and E. Polgreen, "Guiding enumerative program synthesis with large language models," in *International Conference* on Computer Aided Verification. Springer, 2024, pp. 280–301.
- [704] S. Barke, E. A. Gonzalez, S. R. Kasibatla, T. Berg-Kirkpatrick, and N. Polikarpova, "Hysynth: Context-free llm approximation for guiding program synthesis," arXiv preprint arXiv:2405.15880, 2024.
- [705] K. Kuznia, S. Mishra, M. Parmar, and C. Baral, "Less is more: Summary of long instructions is better for program synthesis," arXiv preprint arXiv:2203.08597, 2022.
- [706] A. Gandhi, T. Q. Nguyen, H. Jiao, R. Steen, and A. Bhatawdekar, "Natural language commanding via program synthesis," arXiv preprint arXiv:2306.03460, 2023.
- [707] J. Austin, A. Odena, M. Nye, M. Bosma, H. Michalewski, D. Dohan, E. Jiang, C. Cai, M. Terry, Q. Le *et al.*, "Program synthesis with large language models," *arXiv preprint arXiv:2108.07732*, 2021.
- [708] S. Yang, X. Chen, K. Liu, G. Yang, and C. Yu, "Automatic bimodal question title generation for stack overflow with prompt learning," *Empirical Software Engineering*, vol. 29, no. 3, p. 63, 2024.
- [709] S. Rahmani, A. Naghshzan, and L. Guerrouj, "Improving code example recommendations on informal documentation using bert and query-aware lsh: A comparative study," arXiv preprint arXiv:2305.03017, 2023.
- [710] X. Zong, S. Zheng, H. Zou, H. Yu, and S. Gao, "Graphpyrec: A novel graph-based approach for fine-grained python code recommendation," *Science of Computer Programming*, p. 103166, 2024.
- [711] Q. Huang, Z. Zou, Z. Xing, Z. Zuo, X. Xu, and Q. Lu, "Ai chain on large language model for unsupervised control flow graph generation for statically-typed partial code," *arXiv preprint arXiv:2306.00757*, 2023.
- [712] L. Cheng, X. Li, and L. Bing, "Is gpt-4 a good data analyst?" arXiv preprint arXiv:2305.15038, 2023.
- [713] J. Zhu, L. Li, L. Yang, X. Ma, and C. Zuo, "Automating method naming with context-aware prompt-tuning," in 2023 IEEE/ACM 31st International Conference on Program Comprehension (ICPC). IEEE, 2023, pp. 203–214.
- [714] M. Schroder, "Autoscrum: Automating project planning using large language models," arXiv preprint arXiv:2306.03197, 2023.
- [715] S. Kabir, D. N. Udo-Imeh, B. Kou, and T. Zhang, "Is stack overflow obsolete? an empirical study of the characteristics of chatgpt answers to stack overflow questions," in *Proceedings of the CHI Conference on Human Factors in Computing Systems*, 2024, pp. 1–17.
- [716] E. Firouzi and M. Ghafari, "Time to separate from stackoverflow and match with chatgpt for encryption," *Journal of Systems and Software*, p. 112135, 2024.
- [717] A. Abdellatif, K. Badran, D. E. Costa, and E. Shihab, "A transformer-based approach for augmenting software engineering chatbots datasets," arXiv preprint arXiv:2407.11955, 2024.
- [718] K. Pei, D. Bieber, K. Shi, C. Sutton, and P. Yin, "Can large language models reason about program invariants?" in *International Conference on Machine Learning*. PMLR, 2023, pp. 27 496–27 520.
- [719] J. Yoon, R. Feldt, and S. Yoo, "Autonomous large language model agents enabling intent-driven mobile gui testing," arXiv preprint arXiv:2311.08649, 2023.
- [720] L. Zhang, S. Lu, and N. Duan, "Selene: Pioneering automated proof in software verification," arXiv preprint arXiv:2401.07663, 2024.
- [721] B. Cheng, C. Zhang, K. Wang, L. Shi, Y. Liu, H. Wang, Y. Guo, and X. Chen, "Semantic-enhanced indirect call analysis with large language models," arXiv preprint arXiv:2408.04344, 2024.
- [722] C. Wang, J. Liu, X. Peng, Y. Liu, and Y. Lou, "Boosting static resource leak detection via llm-based resource-oriented intention inference," arXiv preprint arXiv:2311.04448, 2023.
- [723] K. Jain, U. Alon, A. Groce, and C. Le Goues, "Contextual predictive mutation testing," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2023, pp. 250–261.
- [724] C. Richter and H. Wehrheim, "Learning realistic mutations: Bug creation for neural bug detectors," in 2022 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2022, pp. 162–173.

- [725] M. Hassan, S. Ahmadi-Pour, K. Qayyum, C. K. Jha, and R. Drechsler, "Llm-guided formal verification coupled with mutation testing," in 2024 Design, Automation & Test in Europe Conference & Exhibition (DATE). IEEE, 2024, pp. 1–2.
- [726] F. Tip, J. Bell, and M. Schäfer, "Llmorpheus: Mutation testing using large language models," arXiv preprint arXiv:2404.09952, 2024.
- [727] Z. Li and D. Shin, "Mutation-based consistency testing for evaluating the code understanding capability of llms," in *Proceedings* of the IEEE/ACM 3rd International Conference on AI Engineering-Software Engineering for AI, 2024, pp. 150–159.
- [728] R. Degiovanni and M. Papadakis, "µbert: Mutation testing using pre-trained language models," in 2022 IEEE International Conference on Software Testing, Verification and Validation Workshops (ICSTW). IEEE, 2022, pp. 160–169.
- [729] P. Liu, C. Sun, Y. Zheng, X. Feng, C. Qin, Y. Wang, Z. Li, and L. Sun, "Harnessing the power of llm to support binary taint analysis," arXiv preprint arXiv:2310.08275, 2023.
- [730] B. Steenhoek, M. M. Rahman, M. K. Roy, M. S. Alam, E. T. Barr, and W. Le, "A comprehensive study of the capabilities of large language models for vulnerability detection," arXiv preprint arXiv:2403.17218, 2024.
- [731] M. M. Kholoosi, M. A. Babar, and R. Croft, "A qualitative study on using chatgpt for software security: Perception vs. practicality," arXiv preprint arXiv:2408.00435, 2024.
- [732] B. Ju, J. Yang, T. Yu, T. Abdullayev, Y. Wu, D. Wang, and Y. Zhao, "A study of using multimodal llms for non-crash functional bug detection in android apps," arXiv preprint arXiv:2407.19053, 2024.
- [733] M. Saad, J. A. H. López, B. Chen, D. Varró, and T. Sharma, "Alpine: An adaptive language-agnostic pruning method for language models for code," arXiv preprint arXiv:2407.04147, 2024.
- [734] E. Pelofske, V. Urias, and L. M. Liebrock, "Automated software vulnerability static code analysis using generative pre-trained transformer models," arXiv preprint arXiv:2408.00197, 2024.
- [735] L. Gomes, R. da Silva Torres, and M. L. Côrtes, "Bert-and tf-idfbased feature extraction for long-lived bug prediction in floss: a comparative study," *Information and Software Technology*, vol. 160, p. 107217, 2023.
- [736] Y. Chen, C. Gao, Z. Yang, H. Zhang, and Q. Liao, "Bridge and hint: Extending pre-trained language models for long-range code," arXiv preprint arXiv:2405.11233, 2024.
- [737] S. Wan, J. Saxe, C. Gomes, S. Chennabasappa, A. Rath, K. Sun, and X. Wang, "Bridging the gap: A study of ai-based vulnerability management between industry and academia," arXiv preprint arXiv:2405.02435, 2024.
- [738] H. Lee, S. Sharma, and B. Hu, "Bug in the code stack: Can llms find bugs in large python code stacks," *arXiv preprint arXiv:2406.15325*, 2024.
- [739] S. Ullah, M. Han, S. Pujar, H. Pearce, A. Coskun, and G. Stringhini, "Can large language models identify and reason about security vulnerabilities? not yet," arXiv preprint arXiv:2312.12575, 2023.
- [740] Y. Nong, M. Aldeen, L. Cheng, H. Hu, F. Chen, and H. Cai, "Chain-of-thought prompting of large language models for discovering and fixing software vulnerabilities," arXiv preprint arXiv:2402.17230, 2024.
- [741] Z. Wang, G. Li, J. Li, Y. Dong, Y. Xiong, and Z. Jin, "Code structure-aware through line-level semantic learning for code vulnerability detection," arXiv preprint arXiv:2407.18877, 2024.
- [742] Y. Zhao, L. Gong, Z. Huang, Y. Wang, M. Wei, and F. Wu, "Coding-ptms: How to find optimal code pre-trained models for code embedding in vulnerability detection?" arXiv preprint arXiv:2408.04863, 2024.
- [743] X. Zhou, D.-M. Tran, T. Le-Cong, T. Zhang, I. C. Irsan, J. Sumarlin, B. Le, and D. Lo, "Comparison of static application security testing tools and large language models for repo-level vulnerability detection," arXiv preprint arXiv:2407.16235, 2024.
- [744] W. Tang, M. Tang, M. Ban, Z. Zhao, and M. Feng, "Csgvd: A deep learning approach combining sequence and graph embedding for source code vulnerability detection," *Journal of Systems and Software*, vol. 199, p. 111623, 2023.
- [745] B. Steenhoek, H. Gao, and W. Le, "Dataflow analysis-inspired deep learning for efficient vulnerability detection," in *Proceedings* of the 46th IEEE/ACM International Conference on Software Engineering, 2024, pp. 1–13.

- [746] T. Koide, N. Fukushi, H. Nakano, and D. Chiba, "Detecting phishing sites using chatgpt," arXiv preprint arXiv:2306.05816, 2023.
- [747] T. Sun, K. Allix, K. Kim, X. Zhou, D. Kim, D. Lo, T. F. Bissyandé, and J. Klein, "Dexbert: Effective, task-agnostic and fine-grained representation learning of android bytecode," *IEEE Transactions* on Software Engineering, 2023.
- [748] Y. Chen, Z. Ding, L. Alowain, X. Chen, and D. Wagner, "Diversevul: A new vulnerable source code dataset for deep learning based vulnerability detection," in *Proceedings of the 26th International Symposium on Research in Attacks, Intrusions and Defenses*, 2023, pp. 654–668.
- [749] Y. Yang, X. Zhou, R. Mao, J. Xu, L. Yang, Y. Zhangm, H. Shen, and H. Zhang, "Dlap: A deep learning augmented large language model prompting framework for software vulnerability detection," arXiv preprint arXiv:2405.01202, 2024.
- [750] S. Liu, D. Cao, J. Kim, T. Abraham, P. Montague, S. Camtepe, J. Zhang, and Y. Xiang, "Eatvul: Chatgpt-based evasion attack against software vulnerability detection."
- [751] B. Yuan, Y. Lu, Y. Fang, Y. Wu, D. Zou, Z. Li, Z. Li, and H. Jin, "Enhancing deep learning-based vulnerability detection by building behavior graph model," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 2262–2274.
- [752] K. Lucas, R. Gheyi, E. Soares, M. Ribeiro, and I. Machado, "Evaluating large language models in detecting test smells," arXiv preprint arXiv:2407.19261, 2024.
- [753] S. S. Daneshvar, Y. Nong, X. Yang, S. Wang, and H. Cai, "Exploring rag-based vulnerability augmentation with llms," arXiv preprint arXiv:2408.04125, 2024.
- [754] A. Shestov, A. Cheshkov, R. Levichev, R. Mussabayev, P. Zadorozhny, E. Maslov, C. Vadim, and E. Bulychev, "Finetuning large language models for vulnerability detection," arXiv preprint arXiv:2401.17010, 2024.
- [755] B. Ahmad, B. Tan, R. Karri, and H. Pearce, "Flag: Finding line anomalies (in code) with generative ai," arXiv preprint arXiv:2306.12643, 2023.
- [756] G. Lu, X. Ju, X. Chen, W. Pei, and Z. Cai, "Grace: Empowering llm-based software vulnerability detection with graph structure and in-context learning," *Journal of Systems and Software*, vol. 212, p. 112031, 2024.
- [757] K. Tamberg and H. Bahsi, "Harnessing large language models for software vulnerability detection: A comprehensive benchmarking study," arXiv preprint arXiv:2405.15614, 2024.
- [758] A. A. Mahyari, "Harnessing the power of llms in source code vulnerability detection," arXiv preprint arXiv:2408.03489, 2024.
- [759] Z. Gao, H. Wang, Y. Zhou, W. Zhu, and C. Zhang, "How far have we gone in vulnerability detection using large language models," *arXiv preprint arXiv*:2311.12420, 2023.
- [760] X. Tang, Z. Chen, K. Kim, H. Tian, S. Ezzini, and J. Klein, "Just-in-time security patch detection–llm at the rescue for data augmentation," arXiv preprint arXiv:2312.01241, 2023.
- [761] X. Zhou, S. Cao, X. Sun, and D. Lo, "Large language model for vulnerability detection and repair: Literature review and roadmap," arXiv preprint arXiv:2404.02525, 2024.
- [762] K. Dozono, T. E. Gasiba, and A. Stocco, "Large language models for secure code assessment: A multi-language empirical study," arXiv preprint arXiv:2408.06428, 2024.
- [763] N. S. Mathews, Y. Brus, Y. Aafer, M. Nagappan, and S. McIntosh, "Llbezpeky: Leveraging large language models for vulnerability detection," arXiv preprint arXiv:2401.01269, 2024.
- [764] V. Ashiwal, S. Finster, and A. Dawoud, "Llm-based vulnerability sourcing from unstructured data," in 2024 IEEE European Symposium on Security and Privacy Workshops (EuroS&PW). IEEE, 2024, pp. 634–641.
- [765] Y. Cheng, L. K. Shar, T. Zhang, S. Yang, C. Dong, D. Lo, S. Lv, Z. Shi, and L. Sun, "Llm-enhanced static analysis for precise identification of vulnerable oss versions," arXiv preprint arXiv:2408.07321, 2024.
- [766] Y. Sun, D. Wu, Y. Xue, H. Liu, W. Ma, L. Zhang, M. Shi, and Y. Liu, "Llm4vuln: A unified evaluation framework for decoupling and enhancing llms' vulnerability reasoning," arXiv preprint arXiv:2401.16185, 2024.
- [767] M. Alqarni and A. Azim, "Low level source code vulnerability detection using advanced bert language model," in *Proceedings* of the Canadian Conference on Artificial Intelligence-Https://caiac. pubpub. org/pub/gdhb8oq4 (may 27 2022), 2022.

- [768] Z. Wang, G. Li, J. Li, Y. Xiong, and Z. Jin, "M2cvd: Multi-model collaboration for code vulnerability detection," arXiv preprint arXiv:2406.05940, 2024.
- [769] Z. Mao, J. Li, M. Li, and K. Tei, "Multi-role consensus through llms discussions for vulnerability detection," arXiv preprint arXiv:2403.14274, 2024.
- [770] X. Yin and C. Ni, "Multitask-based evaluation of open-source llm on software vulnerability," arXiv preprint arXiv:2404.02056, 2024.
- [771] M.-F. Wong, S. Guo, C.-N. Hang, S.-W. Ho, and C.-W. Tan, "Natural language generation and understanding of big code for ai-assisted programming: A review," *Entropy*, vol. 25, no. 6, p. 888, 2023.
- [772] C. X. Do, N. T. Luu, and P. T. L. Nguyen, "Optimizing software vulnerability detection using roberta and machine learning," *Automated Software Engineering*, vol. 31, no. 2, p. 40, 2024.
- [773] X. Yin, "Pros and cons! evaluating chatgpt on software vulnerability," arXiv preprint arXiv:2404.03994, 2024.
- [774] J. Gonçalves, T. Dias, E. Maia, and I. Praça, "Scope: Evaluating llms for software vulnerability detection," arXiv preprint arXiv:2407.14372, 2024.
- [775] J. Yu, P. Liang, Y. Fu, A. Tahir, M. Shahin, C. Wang, and Y. Cai, "Security code review by llms: A deep dive into responses," arXiv preprint arXiv:2401.16310, 2024.
- [776] A. Grishina, M. Hort, and L. Moonen, "The earlybird catches the bug: On exploiting early layers of encoder models for more efficient code classification," in *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2023, pp. 895–907.
- [777] Q. Mao, Z. Li, X. Hu, K. Liu, X. Xia, and J. Sun, "Towards effectively detecting and explaining vulnerabilities using large language models," *arXiv preprint arXiv:2406.09701*, 2024.
- [778] C. Thapa, S. I. Jang, M. E. Ahmed, S. Camtepe, J. Pieprzyk, and S. Nepal, "Transformer-based language models for software vulnerability detection," in *Proceedings of the 38th Annual Computer Security Applications Conference*, 2022, pp. 481–496.
- [779] A. Chan, A. Kharkar, R. Z. Moghaddam, Y. Mohylevskyy, A. Helyar, E. Kamal, M. Elkamhawy, and N. Sundaresan, "Transformerbased vulnerability detection in code at edittime: Zero-shot, fewshot, or fine-tuning?" arXiv preprint arXiv:2306.01754, 2023.
- [780] A. Khare, S. Dutta, Z. Li, A. Solko-Breslin, R. Alur, and M. Naik, "Understanding the effectiveness of large language models in detecting security vulnerabilities," arXiv preprint arXiv:2311.16169, 2023.
- [781] S. M. Taghavi and F. Feyzi, "Using large language models to better detect and handle software vulnerabilities and cyber security threats," 2024.
- [782] X. Du, G. Zheng, K. Wang, J. Feng, W. Deng, M. Liu, B. Chen, X. Peng, T. Ma, and Y. Lou, "Vul-rag: Enhancing llm-based vulnerability detection via knowledge-level rag," arXiv preprint arXiv:2406.11147, 2024.
- [783] H. Hanif and S. Maffeis, "Vulberta: Simplified source code pretraining for vulnerability detection," in 2022 International joint conference on neural networks (IJCNN). IEEE, 2022, pp. 1–8.
- [784] A. H. A. Chukkol, S. Luo, K. Sharif, Y. Haruna, and M. M. Abdullahi, "Vulcatch: Enhancing binary vulnerability detection through codet5 decompilation and kan advanced feature extraction," arXiv preprint arXiv:2408.07181, 2024.
- [785] Y. Liu, L. Gao, M. Yang, Y. Xie, P. Chen, X. Zhang, and W. Chen, "Vuldetectbench: Evaluating the deep capability of vulnerability detection with large language models," arXiv preprint arXiv:2406.07595, 2024.
- [786] X.-C. Wen, X. Wang, Y. Chen, R. Hu, D. Lo, and C. Gao, "Vuleval: Towards repository-level evaluation of software vulnerability detection," arXiv preprint arXiv:2404.15596, 2024.
- [787] V. Akuthota, R. Kasula, S. T. Sumona, M. Mohiuddin, M. T. Reza, and M. M. Rahman, "Vulnerability detection and monitoring using llm," in 2023 IEEE 9th International Women in Engineering (WIE) Conference on Electrical and Computer Engineering (WIECON-ECE). IEEE, 2023, pp. 309–314.
- [788] Y. Ding, Y. Fu, O. Ibrahim, C. Sitawarin, X. Chen, B. Alomair, D. Wagner, B. Ray, and Y. Chen, "Vulnerability detection with code language models: How far are we?" arXiv preprint arXiv:2403.18624, 2024.
- [789] V. L. A. Quan, C. T. Phat, K. Van Nguyen, P. T. Duy, and V.-H. Pham, "Xgv-bert: Leveraging contextualized language model and graph neural network for efficient software vulnerability detection," arXiv preprint arXiv:2309.14677, 2023.

- [790] H. Wu, Z. Zhang, S. Wang, Y. Lei, B. Lin, Y. Qin, H. Zhang, and X. Mao, "Peculiar: Smart contract vulnerability detection based on crucial data flow graph and pre-training techniques," in 2021 IEEE 32nd International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2021, pp. 378–389.
- [791] Z. Jiang, W. Sun, X. Gu, J. Wu, T. Wen, H. Hu, and M. Yan, "Dfept: Data flow embedding for enhancing pre-trained model based vulnerability detection," in *Proceedings of the 15th Asia-Pacific Symposium on Internetware*, 2024, pp. 95–104.
- [792] D. Pratama, N. Suryanto, A. A. Adiputra, T.-T.-H. Le, A. Y. Kadiptya, M. Iqbal, and H. Kim, "Cipher: Cybersecurity intelligent penetration-testing helper for ethical researcher," arXiv preprint arXiv:2408.11650, 2024.
- [793] J. Su, L. Deng, C. Wen, S. Qin, and C. Tian, "cfstra: Enhancing configurable program analysis through llm-driven strategy selection based on code features," in *International Symposium on Theoretical Aspects of Software Engineering*. Springer, 2024, pp. 374–391.
- [794] S. Yan, S. Wang, Y. Duan, H. Hong, K. Lee, D. Kim, and Y. Hong, "An llm-assisted easy-to-trigger backdoor attack on code completion models: Injecting disguised vulnerabilities against strong detection," arXiv preprint arXiv:2406.06822, 2024.
- [795] Y. Xia, Z. Xie, P. Liu, K. Lu, Y. Liu, W. Wang, and S. Ji, "Exploring automatic cryptographic api misuse detection in the era of llms," arXiv preprint arXiv:2407.16576, 2024.
- [796] F. He, J. Zhai, and M. Pan, "Beyond code generation: Assessing code llm maturity with postconditions," arXiv preprint arXiv:2407.14118, 2024.
- [797] H. Wang, H. Hu, C. Chen, and B. Turhan, "Chat-like asserts prediction with the support of large language model," arXiv preprint arXiv:2407.21429, 2024.
- [798] B. Mali, K. Maddala, S. Reddy, V. Gupta, C. Karfa, and R. Karri, "Chiraag: Chatgpt informed rapid and automated assertion generation," arXiv preprint arXiv:2402.00093, 2024.
- [799] Y. Feng, H. Li, Y. Cao, Y. Wang, and H. Feng, "Crabs-former: Cross-architecture binary code similarity detection based on transformer," in *Proceedings of the 15th Asia-Pacific Symposium on Internetware*, 2024, pp. 11–20.
- [800] H. Wang, W. Qu, G. Katz, W. Zhu, Z. Gao, H. Qiu, J. Zhuge, and C. Zhang, "Jtrans: Jump-aware transformer for binary code similarity detection," in *Proceedings of the 31st ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2022, pp. 1–13.
- [801] S. Ahn, S. Ahn, H. Koo, and Y. Paek, "Practical binary code similarity detection with bert-based transferable similarity learning," in *Proceedings of the 38th Annual Computer Security Applications Conference*, 2022, pp. 361–374.
- [802] Z. Yu, R. Cao, Q. Tang, S. Nie, J. Huang, and S. Wu, "Order matters: Semantic-aware neural networks for binary code similarity detection," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 34, no. 01, 2020, pp. 1145–1152.
- [803] Y. Qin, S. Wang, Y. Lou, J. Dong, K. Wang, X. Li, and X. Mao, "Agentfl: Scaling llm-based fault localization to project-level context," arXiv preprint arXiv:2403.16362, 2024.
- [804] J. Yan, J. Huang, C. Fang, J. Yan, and J. Zhang, "Better debugging: Combining static analysis and llms for explainable crashing fault localization," arXiv preprint arXiv:2408.12070, 2024.
- [805] A. M. Mohsen, H. Hassan, K. Wassif, R. Moawad, and S. Makady, "Enhancing bug localization using phase-based approach," *IEEE Access*, 2023.
- [806] S. Shan, Y. Huo, Y. Su, Y. Li, D. Li, and Z. Zheng, "Face it yourselves: An llm-based two-stage strategy to localize configuration errors via logs," *arXiv preprint arXiv:2404.00640*, 2024.
- [807] S. Ji, S. Lee, C. Lee, H. Im, and Y.-S. Han, "Impact of large language models of code on fault localization," arXiv preprint arXiv:2408.09657, 2024.
- [808] S. Bin Murtaza, A. Mccoy, Z. Ren, A. Murphy, and W. Banzhaf, "Llm fault localisation within evolutionary computation based automated program repair," in *Proceedings of the Genetic and Evolutionary Computation Conference Companion*, 2024, pp. 1824– 1829.
- [809] Y. Du and Z. Yu, "Pre-training code representation with semantic flow graph for effective bug localization," in *Proceedings of* the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 579–591.
- [810] A. Ciborowska and K. Damevski, "Too few bug reports? ex-

ploring data augmentation for improved changeset-based bug localization," arXiv preprint arXiv:2305.16430, 2023.

- [811] Y. Wu, Z. Li, J. M. Zhang, and Y. Liu, "Condefects: A complementary dataset to address the data leakage concern for llm-based fault localization and program repair," in *Companion Proceedings* of the 32nd ACM International Conference on the Foundations of Software Engineering, 2024, pp. 642–646.
- [812] Y. Charalambous, N. Tihanyi, R. Jain, Y. Sun, M. A. Ferrag, and L. C. Cordeiro, "A new era in software security: Towards selfhealing software via large language models and formal verification," arXiv preprint arXiv:2305.14752, 2023.
- [813] Y. Liu, Y. Xue, D. Wu, Y. Sun, Y. Li, M. Shi, and Y. Liu, "Propertygpt: Llm-driven formal verification of smart contracts through retrieval-augmented property generation," arXiv preprint arXiv:2405.02580, 2024.
- [814] N. Tihanyi, T. Bisztray, R. Jain, M. A. Ferrag, L. C. Cordeiro, and V. Mavroeidis, "The formai dataset: Generative ai in software security through the lens of formal verification," in *Proceedings* of the 19th International Conference on Predictive Models and Data Analytics in Software Engineering, 2023, pp. 33–43.
- [815] C. Wen, J. Cao, J. Su, Z. Xu, S. Qin, M. He, H. Li, S.-C. Cheung, and C. Tian, "Enchanting program specification synthesis by large language models using static analysis and program verification," in *International Conference on Computer Aided Verification*. Springer, 2024, pp. 302–328.
- [816] P. J. Chapman, C. Rubio-González, and A. V. Thakur, "Interleaving static analysis and llm prompting," in *Proceedings of the 13th* ACM SIGPLAN International Workshop on the State Of the Art in Program Analysis, 2024, pp. 9–17.
- [817] C. Fang, N. Miao, S. Srivastav, J. Liu, R. Zhang, R. Fang, R. Tsang, N. Nazari, H. Wang, H. Homayoun *et al.*, "Large language models for code analysis: Do {LLMs} really do their job?" in 33rd USENIX Security Symposium (USENIX Security 24), 2024, pp. 829– 846.
- [818] C. Wen, Y. Cai, B. Zhang, J. Su, Z. Xu, D. Liu, S. Qin, Z. Ming, and T. Cong, "Automatically inspecting thousands of static bug warnings with large language model: How far are we?" ACM *Transactions on Knowledge Discovery from Data*, vol. 18, no. 7, pp. 1–34, 2024.
- [819] A. Lops, F. Narducci, A. Ragone, M. Trizio, and C. Bartolini, "A system for automated unit test generation using large language models and assessment of generated test suites," arXiv preprint arXiv:2408.07846, 2024.
- [820] X. Yuan, J. Li, D. Wang, Y. Chen, X. Mao, L. Huang, H. Xue, W. Wang, K. Ren, and J. Wang, "S-eval: Automatic and adaptive test generation for benchmarking safety evaluation of large language models," arXiv preprint arXiv:2405.14191, 2024.
- [821] K. Zhang, D. Wang, J. Xia, W. Y. Wang, and L. Li, "Algo: Synthesizing algorithmic programs with generated oracle verifiers," *Advances in Neural Information Processing Systems*, vol. 36, pp. 54769–54784, 2023.
- [822] M. Schäfer, S. Nadi, A. Eghbali, and F. Tip, "An empirical evaluation of using large language models for automated unit test generation," *IEEE Transactions on Software Engineering*, 2023.
- [823] Z. Zhou, Y. Tang, Y. Lin, and J. He, "An Ilm-based readability measurement for unit tests' context-aware inputs," arXiv preprint arXiv:2407.21369, 2024.
- [824] L. Plein, W. C. Ouédraogo, J. Klein, and T. F. Bissyandé, "Automatic generation of test cases based on bug reports: a feasibility study with large language models," in *Proceedings of the 2024 IEEE/ACM 46th International Conference on Software Engineering: Companion Proceedings*, 2024, pp. 360–361.
- [825] H. Kirinuki and H. Tanno, "Chatgpt and human synergy in black-box testing: A comparative analysis," arXiv preprint arXiv:2401.13924, 2024.
- [826] A. Azaria, R. Azoulay, and S. Reches, "Chatgpt is a remarkable tool—for experts," *Data Intelligence*, vol. 6, no. 1, pp. 240–296, 2024.
- [827] N. Mündler, M. N. Müller, J. He, and M. Vechev, "Code agents are state of the art software testers," arXiv preprint arXiv:2406.12952, 2024.
- [828] M. Li, D. Li, J. Liu, J. Cao, Y. Tian, and S.-C. Cheung, "Dllens: Testing deep learning libraries via llm-aided synthesis," arXiv preprint arXiv:2406.07944, 2024.
- [829] J. Shin, S. Hashtroudi, H. Hemmati, and S. Wang, "Domain adaptation for deep unit test case generation," arXiv e-prints, pp. arXiv–2308, 2023.

- [830] C. Yang, J. Chen, B. Lin, J. Zhou, and Z. Wang, "Enhancing llmbased test generation for hard-to-cover branches via program analysis," arXiv preprint arXiv:2404.04966, 2024.
- [831] Y. He, J. Wang, Y. Rong, and H. Chen, "Exploring fuzzing as data augmentation for neural test generation," *arXiv preprint arXiv:2406.08665*, 2024.
- [832] M. L. Siddiq, J. Santos, R. H. Tanvir, N. Ulfat, F. Rifat, and V. C. Lopes, "Exploring the effectiveness of large language models in generating unit tests," arXiv preprint arXiv:2305.00418, 2023.
- [833] C. Arora, T. Herda, and V. Homm, "Generating test scenarios from nl requirements using retrieval-augmented llms: An industrial study," arXiv preprint arXiv:2404.12772, 2024.
- [834] R. Karanjai, A. Hussain, M. R. I. Rabin, L. Xu, W. Shi, and M. A. Alipour, "Harnessing the power of llms: Automating unit test generation for high-performance computing," arXiv preprint arXiv:2407.05202, 2024.
- [835] K. Li and Y. Yuan, "Large language models as test case generators: Performance evaluation and enhancement," arXiv preprint arXiv:2404.13340, 2024.
- [836] T. Li, C. Cui, L. Ma, D. Towey, Y. Xie, and R. Huang, "Leveraging large language models for automated web-form-test generation: An empirical study," arXiv preprint arXiv:2405.09965, 2024.
- [837] K. Etemadi, B. Mohammadi, Z. Su, and M. Monperrus, "Mokav: Execution-driven differential testing with llms," *arXiv preprint arXiv*:2406.10375, 2024.
- [838] Z. Yuan, Y. Lou, M. Liu, S. Ding, K. Wang, Y. Chen, and X. Peng, "No more manual tests? evaluating and improving chatgpt for unit test generation," arXiv preprint arXiv:2305.04207, 2023.
- [839] B. Steenhoek, M. Tufano, N. Sundaresan, and A. Svyatkovskiy, "Reinforcement learning from automatic feedback for highquality unit test generation," arXiv preprint arXiv:2310.02368, 2023.
- [840] M. Nabeel, D. D. Nimara, and T. Zanouda, "Test code generation for telecom software systems using two-stage generative model," arXiv preprint arXiv:2404.09249, 2024.
- [841] W. Xiong, Y. Guo, and H. Chen, "The program testing ability of large language models for code," arXiv preprint arXiv:2310.05727, 2023.
- [842] M. Tufano, D. Drain, A. Svyatkovskiy, S. K. Deng, and N. Sundaresan, "Unit test case generation with transformers and focal context," arXiv preprint arXiv:2009.05617, 2020.
- [843] Q. Motger, A. Miaschi, F. Dell'Orletta, X. Franch, and J. Marco, "Tfrex: A transformer-based feature extraction method from mobile app reviews," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 227–238.
- [844] Y. Wang, J. Wang, H. Zhang, X. Ming, L. Shi, and Q. Wang, "Where is your app frustrating users?" in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 2427– 2439.
- [845] H. Isotani, H. Washizaki, Y. Fukazawa, T. Nomoto, S. Ouji, and S. Saito, "Duplicate bug report detection by using sentence embedding and fine-tuning," in 2021 IEEE international conference on software maintenance and evolution (ICSME). IEEE, 2021, pp. 535–544.
- [846] X. Wu, H. Li, N. Yoshioka, H. Washizaki, and F. Khomh, "Refining gpt-3 embeddings with a siamese structure for technical post duplicate detection," in 2024 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2024, pp. 114–125.
- [847] R. K. Helmeczi, M. Cevik, and S. Yıldırım, "Few-shot learning for sentence pair classification and its applications in software engineering," arXiv preprint arXiv:2306.08058, 2023.
- [848] R. Sharma, F. Chen, F. Fard, and D. Lo, "An exploratory study on code attention in bert," in *Proceedings of the 30th IEEE/ACM International Conference on Program Comprehension*, 2022, pp. 437– 448.
- [849] A. I. Alam, P. R. Roy, F. Al-Omari, C. K. Roy, B. Roy, and K. A. Schneider, "Gptclonebench: A comprehensive benchmark of semantic clones and cross-language clones using gpt-3 model and semanticclonebench," in 2023 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2023, pp. 1–13.
- [850] N. T. Islam, J. Khoury, A. Seong, G. D. L. T. Parra, E. Bou-Harb, and P. Najafirad, "Llm-powered code vulnerability repair with reinforcement learning and semantic reward," *arXiv preprint arXiv:2401.03374*, 2024.

- [851] M. Chochlov, G. A. Ahmed, J. V. Patten, G. Lu, W. Hou, D. Gregg, and J. Buckley, "Using a nearest-neighbour, bert-based approach for scalable clone detection," in 2022 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2022, pp. 582–591.
- [852] I. Saberi, F. Fard, and F. Chen, "Utilization of pre-trained language models for adapter-based knowledge transfer in software engineering," *Empirical Software Engineering*, vol. 29, no. 4, p. 94, 2024.
- [853] Y. Du, T. Ma, L. Wu, X. Zhang, and S. Ji, "Adaccd: Adaptive semantic contrasts discovery based cross lingual adaptation for code clone detection," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 16, 2024, pp. 17942–17950.
- [854] S. Kang, J. Yoon, N. Askarbekkyzy, and S. Yoo, "Evaluating diverse large language models for automatic and general bug reproduction," arXiv preprint arXiv:2311.04532, 2023.
- [855] M. Tufano, S. Chandel, A. Agarwal, N. Sundaresan, and C. Clement, "Predicting code coverage without execution," arXiv preprint arXiv:2307.13383, 2023.
- [856] G. Colavito, F. Lanubile, N. Novielli, and L. Quaranta, "Impact of data quality for automatic issue classification using pre-trained language models," *Journal of Systems and Software*, vol. 210, p. 111838, 2024.
- [857] J. Lu, Z. Tang, and Z. Liu, "Improving code refinement for code review via input reconstruction and ensemble learning," in 2023 30th Asia-Pacific Software Engineering Conference (APSEC). IEEE, 2023, pp. 161–170.
- [858] L. Dong-Kyu, "A gpt-based code review system for programming language learning," arXiv preprint arXiv:2407.04722, 2024.
- [859] O. B. Sghaier and H. Sahraoui, "A multi-step learning approach to assist code review," in 2023 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2023, pp. 450–460.
- [860] M. Vijayvergiya, M. Salawa, I. Budiselić, D. Zheng, P. Lamblin, M. Ivanković, J. Carin, M. Lewko, J. Andonov, G. Petrović *et al.*, "Ai-assisted assessment of coding practices in modern code review," *arXiv preprint arXiv:2405.13565*, 2024.
- [861] Z. Rasheed, M. A. Sami, M. Waseem, K.-K. Kemell, X. Wang, A. Nguyen, K. Systä, and P. Abrahamsson, "Ai-powered code review with llms: Early results," arXiv preprint arXiv:2404.18496, 2024.
- [862] C. Yang, B. Xu, J. Y. Khan, G. Uddin, D. Han, Z. Yang, and D. Lo, "Aspect-based api review classification: How far can pre-trained transformer model go?" in 2022 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, 2022, pp. 385–395.
- [863] L. Ghadhab, I. Jenhani, M. W. Mkaouer, and M. B. Messaoud, "Augmenting commit classification by using fine-grained source code changes and a pre-trained deep neural language model," *Information and Software Technology*, vol. 135, p. 106566, 2021.
- [864] B. Kou, M. Chen, and T. Zhang, "Automated summarization of stack overflow posts," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 2023, pp. 1853– 1865.
- [865] Y. Yin, Y. Zhao, Y. Sun, and C. Chen, "Automatic code review by learning the structure information of code graph," *Sensors*, vol. 23, no. 5, p. 2551, 2023.
- [866] T. Ahmed, P. Devanbu, C. Treude, and M. Pradel, "Can llms replace manual annotation of software engineering artifacts?" arXiv preprint arXiv:2408.05534, 2024.
- [867] C. Koutcheme, N. Dainese, A. Hellas, S. Sarsa, J. Leinonen, S. Ashraf, and P. Denny, "Evaluating language models for generating and judging programming feedback," arXiv preprint arXiv:2407.04873, 2024.
- [868] L. Fan, J. Liu, Z. Liu, D. Lo, X. Xia, and S. Li, "Exploring the capabilities of llms for code change related tasks," *arXiv preprint arXiv*:2407.02824, 2024.
- [869] C. Pornprasit and C. Tantithamthavorn, "Fine-tuning and prompt engineering for large language models-based code review automation," *Information and Software Technology*, vol. 175, p. 107523, 2024.
- [870] O. Ben Sghaier and H. Sahraoui, "Improving the learning of code review successive tasks with cross-task knowledge distillation," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1086–1106, 2024.
- [871] I. Ferreira, A. Rafiq, and J. Cheng, "Incivility detection in open

source code review and issue discussions," Journal of Systems and Software, vol. 209, p. 111935, 2024.

- [872] J. Lu, L. Yu, X. Li, L. Yang, and C. Zuo, "Llama-reviewer: Advancing code review automation with large language models through parameter-efficient fine-tuning," in 2023 IEEE 34th International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2023, pp. 647–658.
- [873] N. McAleese, R. M. Pokorny, J. F. C. Uribe, E. Nitishinskaya, M. Trebacz, and J. Leike, "Llm critics help catch llm bugs," arXiv preprint arXiv:2407.00215, 2024.
- [874] Z. Zhao, Z. Xu, J. Zhu, P. Di, Y. Yao, and X. Ma, "The right prompts for the job: Repair code-review defects with large language model," arXiv preprint arXiv:2312.17485, 2023.
- [875] D. Pomian, A. Bellur, M. Dilhara, Z. Kurbatova, E. Bogomolov, T. Bryksin, and D. Dig, "Next-generation refactoring: Combining llm insights and ide capabilities for extract method."
- [876] A. Shirafuji, Y. Oda, J. Suzuki, M. Morishita, and Y. Watanobe, "Refactoring programs using large language models with fewshot examples," in 2023 30th Asia-Pacific Software Engineering Conference (APSEC). IEEE, 2023, pp. 151–160.
- [877] Z. Zhang, Z. Xing, X. Ren, Q. Lu, and X. Xu, "Refactoring to pythonic idioms: A hybrid knowledge-driven approach leveraging large language models," *Proceedings of the ACM on Software Engineering*, vol. 1, no. FSE, pp. 1107–1128, 2024.
- [878] H. Liu, Y. Wang, Z. Wei, Y. Xu, J. Wang, H. Li, and R. Ji, "Refbert: A two-stage pre-trained framework for automatic rename refactoring," in *Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis*, 2023, pp. 740–752.
- [879] Y. Zhang, Z. Qiu, K.-J. Stol, W. Zhu, J. Zhu, Y. Tian, and H. Liu, "Automatic commit message generation: A critical review and directions for future work," *IEEE Transactions on Software Engineering*, 2024.
- [880] T. Ye, T. Ma, L. Wu, X. Zhang, S. Ji, and W. Wang, "Iterative or innovative? a problem-oriented perspective for code optimization," arXiv preprint arXiv:2406.11935, 2024.
- [881] C. Cummins, V. Seeker, D. Grubisic, M. Elhoushi, Y. Liang, B. Roziere, J. Gehring, F. Gloeckle, K. Hazelwood, G. Synnaeve et al., "Large language models for compiler optimization," arXiv preprint arXiv:2309.07062, 2023.
- [882] A. Shypula, A. Madaan, Y. Zeng, U. Alon, J. Gardner, M. Hashemi, G. Neubig, P. Ranganathan, O. Bastani, and A. Yazdanbakhsh, "Learning performance-improving code edits," arXiv preprint arXiv:2302.07867, 2023.
- [883] C. Cummins, V. Seeker, D. Grubisic, B. Roziere, J. Gehring, G. Synnaeve, and H. Leather, "Meta large language model compiler: Foundation models of compiler optimization," arXiv preprint arXiv:2407.02524, 2024.
- [884] D. Grubisic, V. Seeker, G. Synnaeve, H. Leather, J. Mellor-Crummey, and C. Cummins, "Priority sampling of large language models for compilers," in *Proceedings of the 4th Workshop* on Machine Learning and Systems, 2024, pp. 91–97.
- [885] M. Romero Rosas, M. Torres Sanchez, and R. Eigenmann, "Should ai optimize your code? a comparative study of current large language models versus classical optimizing compilers," arXiv e-prints, pp. arXiv-2406, 2024.
- [886] S. Kang, B. Chen, S. Yoo, and J.-G. Lou, "Explainable automated debugging via large language model-driven scientific debugging," arXiv preprint arXiv:2304.02195, 2023.
- [887] S. Fatima, T. A. Ghaleb, and L. Briand, "Flakify: A black-box, language model-based predictor for flaky tests," *IEEE Transactions* on Software Engineering, vol. 49, no. 4, pp. 1912–1927, 2022.
- [888] Y. Li, Y. Huo, Z. Jiang, R. Zhong, P. He, Y. Su, and M. R. Lyu, "Exploring the effectiveness of llms in automated logging generation: An empirical study," arXiv preprint arXiv:2307.05950, 2023.
- [889] L. Ma, W. Yang, B. Xu, S. Jiang, B. Fei, J. Liang, M. Zhou, and Y. Xiao, "Knowlog: Knowledge enhanced pre-trained language model for log understanding," in *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, 2024, pp. 1–13.
- [890] S. Yu, Y. Wu, Z. Li, P. He, N. Chen, and C. Liu, "Log parsing with generalization ability under new log types," in *Proceedings* of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 425–437.
- [891] Y. Wu, S. Yu, and Y. Li, "Log parsing with self-

generated in-context learning and self-correction," arXiv preprint arXiv:2406.03376, 2024.

- [892] A. Mastropaolo, L. Pascarella, and G. Bavota, "Using deep learning to generate complete log statements," in *Proceedings of the 44th International Conference on Software Engineering*, 2022, pp. 2279– 2290.
- [893] A. Mastropaolo, V. Ferrari, L. Pascarella, and G. Bavota, "Log statements generation via deep learning: Widening the support provided to developers," *Journal of Systems and Software*, vol. 210, p. 111947, 2024.
- [894] Z. Liu, C. Chen, J. Wang, M. Chen, B. Wu, Z. Tian, Y. Huang, J. Hu, and Q. Wang, "Testing the limits: Unusual text inputs generation for mobile app crash detection with large language model," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–12.
- [895] S. He, Y. Lei, Y. Zhang, K. Xie, and P. K. Sharma, "Parameterefficient log anomaly detection based on pre-training model and lora," in 2023 IEEE 34th International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2023, pp. 207–217.
- [896] P. Jin, S. Zhang, M. Ma, H. Li, Y. Kang, L. Li, Y. Liu, B. Qiao, C. Zhang, P. Zhao et al., "Assess and summarize: Improve outage understanding with large language models," in Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023, pp. 1657–1668.
- [897] E. Biswas, M. E. Karabulut, L. Pollock, and K. Vijay-Shanker, "Achieving reliable sentiment analysis in the software engineering domain using bert," in 2020 IEEE International conference on software maintenance and evolution (ICSME). IEEE, 2020, pp. 162– 173.
- [898] M. Shafikuzzaman, M. R. Islam, A. C. Rolli, S. Akhter, and N. Seliya, "An empirical evaluation of the zero-shot, few-shot, and traditional fine-tuning based pretrained language models for sentiment analysis in software engineering," *IEEE Access*, 2024.
  [899] T. Zhang, I. C. Irsan, F. Thung, and D. Lo, "Revisiting sentiment
- [899] T. Zhang, I. C. Irsan, F. Thung, and D. Lo, "Revisiting sentiment analysis for software engineering in the era of large language models," arXiv preprint arXiv:2310.11113, 2023.
- [900] T. Zhang, B. Xu, F. Thung, S. A. Haryono, D. Lo, and L. Jiang, "Sentiment analysis for software engineering: How far can pretrained transformer models go?" in 2020 IEEE International Conference on Software Maintenance and Evolution (ICSME). IEEE, 2020, pp. 70–80.
- [901] J. He, B. Xu, Z. Yang, D. Han, C. Yang, and D. Lo, "Ptm4tag: sharpening tag recommendation of stack overflow posts with pre-trained models," in *Proceedings of the 30th IEEE/ACM International Conference on Program Comprehension*, 2022, pp. 1–11.
- [902] A. Mastropaolo, M. Di Penta, and G. Bavota, "Towards automatically addressing self-admitted technical debt: How far are we?" in 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 2023, pp. 585–597.
- [903] Q. Huang, J. Zhu, Z. Xing, H. Jin, C. Wang, and X. Xu, "A chain of ai-based solutions for resolving fqns and fixing syntax errors in partial code," arXiv preprint arXiv:2306.11981, 2023.
- [904] J. White, Q. Fu, S. Hays, M. Sandborn, C. Olea, H. Gilbert, A. Elnashar, J. Spencer-Smith, and D. C. Schmidt, "A prompt pattern catalog to enhance prompt engineering with chatgpt," arXiv preprint arXiv:2302.11382, 2023.
- [905] P. Widjojo and C. Treude, "Addressing compiler errors: Stack overflow or large language models?" arXiv preprint arXiv:2307.10793, 2023.
- [906] M. Kim, Y. Kim, H. Jeong, J. Heo, S. Kim, H. Chung, and E. Lee, "An empirical study of deep transfer learning-based program repair for kotlin projects," in *Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, 2022, pp. 1441–1452.
- [907] N. T. Islam and P. Najafirad, "Code security vulnerability repair using reinforcement learning with large language models," arXiv preprint arXiv:2401.07031, 2024.
- [908] C. S. Xia and L. Zhang, "Conversational automated program repair," arXiv preprint arXiv:2301.13246, 2023.
- [909] R. Paul, M. M. Hossain, M. L. Siddiq, M. Hasan, A. Iqbal, and J. Santos, "Enhancing automated program repair through finetuning and prompt engineering," arXiv preprint arXiv:2304.07840, 2023.
- [910] P. Deligiannis, A. Lal, N. Mehrotra, and A. Rastogi, "Fixing rust compilation errors using llms," arXiv preprint arXiv:2308.05177, 2023.

- [911] N. Wadhwa, J. Pradhan, A. Sonwane, S. P. Sahu, N. Natarajan, A. Kanade, S. Parthasarathy, and S. Rajamani, "Frustrated with code quality issues? llms can help!" *arXiv preprint arXiv:2309.12938*, 2023.
- [912] Z. Xu, Y. Lin, Q. Li, and S. H. Tan, "Guiding chatgpt to fix web ui tests via explanation-consistency checking," arXiv preprint arXiv:2312.05778, 2023.
- [913] Z. Sun, H. Zhu, B. Xu, X. Du, L. Li, and D. Lo, "Llm as runtime error handler: A promising pathway to adaptive self-healing of software systems," arXiv preprint arXiv:2408.01055, 2024.
- [914] Y. Zhang, G. Li, Z. Jin, and Y. Xing, "Neural program repair with program dependence analysis and effective filter mechanism," arXiv preprint arXiv:2305.09315, 2023.
- [915] Y. Liu, C. Tantithamthavorn, Y. Liu, and L. Li, "On the reliability and explainability of language models for program generation," *ACM Transactions on Software Engineering and Methodology*, vol. 33, no. 5, pp. 1–26, 2024.
- [916] C. S. Xia, Y. Wei, and L. Zhang, "Practical program repair in the era of large pre-trained language models," *arXiv preprint arXiv:2210.14179*, 2022.
- [917] Y. W. Chow, L. Di Grazia, and M. Pradel, "Pyty: Repairing static type errors in python," in *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, 2024, pp. 1–13.
- [918] Y. Zhao, Z. Huang, Y. Ma, R. Li, K. Zhang, H. Jiang, Q. Liu, L. Zhu, and Y. Su, "Repair: Automated program repair with process-based feedback," arXiv preprint arXiv:2408.11296, 2024.
- [919] X. Du, M. Liu, J. Li, H. Wang, X. Peng, and Y. Lou, "Resolving crash bugs via large language models: An empirical study," arXiv preprint arXiv:2312.10448, 2023.
- [920] J. Henkel, D. Silva, L. Teixeira, M. d'Amorim, and T. Reps, "Shipwright: A human-in-the-loop system for dockerfile repair," in 2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE). IEEE, 2021, pp. 1148–1160.
- [921] Y. Zhang, Z. Jin, Y. Xing, and G. Li, "Steam: simulating the interactive behavior of programmers for automatic bug fixing," arXiv preprint arXiv:2308.14460, 2023.
- [922] C. S. Xia, Y. Ding, and L. Zhang, "Revisiting the plastic surgery hypothesis via large language models," arXiv preprint arXiv:2303.10494, 2023.
- [923] M. Lajkó, V. Csuvik, and L. Vidács, "Towards javascript program repair with generative pre-trained transformer (gpt-2)," in Proceedings of the Third International Workshop on Automated Program Repair, 2022, pp. 61–68.
- [924] J. Zhang, T. Mytkowicz, M. Kaufman, R. Piskac, and S. K. Lahiri, "Using pre-trained language models to resolve textual and semantic merge conflicts (experience paper)," in *Proceedings of the* 31st ACM SIGSOFT International Symposium on Software Testing and Analysis, 2022, pp. 77–88.
- [925] R. Gharibi, M. H. Sadreddini, and S. M. Fakhrahmad, "T5apr: Empowering automated program repair across languages through checkpoint ensemble," *Journal of Systems and Software*, vol. 214, p. 112083, 2024.
- [926] A. Ali, Y. Xia, Q. Umer, and M. Osman, "Bert based severity prediction of bug reports for the maintenance of mobile applications," *Journal of Systems and Software*, vol. 208, p. 111898, 2024.
- [927] J. Acharya and G. Ginde, "Graph neural network vs. large language model: A comparative analysis for bug report priority and severity prediction," in *Proceedings of the 20th International Conference on Predictive Models and Data Analytics in Software Engineering*, 2024, pp. 2–11.
- [928] E. Mashhadi, H. Ahmadvand, and H. Hemmati, "Method-level bug severity prediction using source code metrics and llms," in 2023 IEEE 34th International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2023, pp. 635–646.
- [929] J. Zhu, G. Xiao, Z. Zheng, and Y. Sui, "Enhancing traceability link recovery with unlabeled data," in 2022 IEEE 33rd International Symposium on Software Reliability Engineering (ISSRE). IEEE, 2022, pp. 446–457.
- [930] U. Kulsum, H. Zhu, B. Xu, and M. d'Amorim, "A case study of llm for automated vulnerability repair: Assessing impact of reasoning and patch validation feedback," *arXiv preprint arXiv:2405.15690*, 2024.
- [931] T. Zhang, I. C. Irsan, F. Thung, D. Lo, A. Sharma, and L. Jiang, "Evaluating pre-trained language models for repairing api misuses," arXiv preprint arXiv:2310.16390, 2023.

- [932] F. Wu, Q. Zhang, A. P. Bajaj, T. Bao, N. Zhang, R. Wang, C. Xiao et al., "Exploring the limits of chatgpt in software security applications," arXiv preprint arXiv:2312.05275, 2023.
- [933] R. Wang, Z. Li, C. Wang, Y. Xiao, and C. Gao, "Navrepair: Node-type aware c/c++ code vulnerability repair," arXiv preprint arXiv:2405.04994, 2024.
- [934] Z. Ságodi, G. Antal, B. Bogenfürst, M. Isztin, P. Hegedűs, and R. Ferenc, "Reality check: Assessing gpt-4 in fixing real-world software vulnerabilities," in *Proceedings of the 28th International Conference on Evaluation and Assessment in Software Engineering*, 2024, pp. 252–261.

## APPENDIX A: SUMMARIZATION OF EXISTING LLMS OF CODE

In the following, we summarize some representative LLMs of code.

#### 0.1 Encoder-only LLMs

**CuBERT.** CuBERT [29] is the first attempt to apply BERT to source code by replicating the training procedure of BERT on a code corpus. In particular, Kanade *et al.* [29] construct a massive corpus of 7.4M Python files from GitHub and pretrain CuBERT with masked language modeling and next sentence prediction as the objectives. CuBERT is fine-tuned on six downstream tasks, including five classification tasks and one program repair task, demonstrating its superior performance over LSTM and vanilla Transformer models.

CodeBERT. CodeBERT [8] represents a successful adaption of BERT from NLP to the source code domain. CodeBERT follows the BERT architecture (*i.e.*, a multi-layer bidirectional Transformer model), but unlike BERT, which only considers natural language (NL), CodeBERT takes into account both NL and programming language (PL). Regarding input representation, CodeBERT's input is divided into two parts: NL and PL, forming the format  $[CLS], w_1, w_2, ..., w_n, [SEP], c_1, c_2, ..., c_m, [EOS],$ where the special marker [CLS] is positioned before these two segments. CodeBERT's output comprises contextual representations for each token and the representation of [*CLS*]. In the pre-training phase, CodeBERT employs two training objectives: masked language modeling and replaced token detection. The first objective aims to predict the original tokens that are masked, a goal established by Devlin et al. [5], where only bimodal data (NL-PL pairs) are utilized for training. The second objective is optimized to train on both unimodal and multimodal data, implying that the generator uses both NL and PL data.

Compared with CuBERT [29], CodeBERT is more powerful due to several improvements during pre-training. First, CuBERT is pre-trained with code snippets, while Code-BERT is pre-trained with both bimodal NL-PL data and unimodal PL/NL data. Second, CuBERT is only pre-trained with Python, while CodeBERT is pre-trained with six programming languages. Third, CuEBRT follows the objectives of BERT, while CodeBERT is trained with a new learning objective based on replaced token detection.

GraphCodeBERT: Structure-aware Pre-training for Source Code. Although CodeBERT introduces code snippets during pre-training, its training paradigm is still derived from NLP by regarding a code snippet as a sequence of tokens while overlooking the inherent structure of source code. In 2020, Guo et al. [30] introduce GraphCodeBERT, a graph-based LLM built upon the BERT architecture designed for code-related applications. GraphCodeBERT employs a representation approach rooted in data flow learning for code. It involves extracting ASTs through tree-sitter and capturing variables from the ASTs to form a sequence of variables. The relationships between extracted variables, such as data source connections, are used to construct a data flow graph. During the model's pre-training phase, GraphCodeBERT introduces two innovative training tasks alongside the inherited MLM task from CodeBERT, i.e.,

edge prediction and node alignment. The edge prediction task aims to learn code structural information by predicting edges within the data flow graph, while the node alignment task aims to learn which specific node in the data flow graph corresponds to which code token in the input code. Besides, to accommodate the structure of AST graphs, GraphCode-BERT employs graph-guided masked attention.

#### 0.2 Encoder-decoder LLMs

**PYMT5:** First Attempt of Encoder-decoder LLM. Similar to CuBERT [29] in the encoder-only LLM domain, as early as 2020, PYMT5 [33] is the first attempt to apply encoder-decoder LLMs to source code by replicating the pre-training process of T5 on a code corpus. PYMT5 is pre-trained with a similar span masking objective from T5 on 26 million Python code snippets and built on an encode-decoder Transformer with 374 million parameters. PYMT5 is fine-tuned with two tasks, *i.e.*, method and comment generation, demonstrating superior performance against GPT-2.

**T5-Learning:** Adaption of **T5** for Source Code. In parallel with PYMT5 [33], Mastropaolo *et al.* [34] propose T5-learning, to empirically investigate how the T5 model performs when pre-trained and fine-tuned to support code-related tasks. T5-learning is first pre-trained in a self-supervised way from T5 on CodeSearchNet with both natural language text and programming language code, *i.e.*, masking tokens in code and asking the model to guess the masked tokens. T5-learning is then fine-tuned to support four downstream tasks, *i.e.*, program repair, mutant injection, assertion generation, and code summarization. The results demonstrate that T5-learning outperforms previous baselines, showcasing the potential of T5 in code-related tasks.

PLBART: BART-based LLM for Code. Unlike PYMT5 [33] only focusing on Python code generation, in 2021, Ahmad et al. [35] propose PLBART, an encoderdecoder LLM capable of performing a broad spectrum of code understanding and generation tasks. PLABRT is pre-trained with the denoising objective and built on the BART architecture. During the pre-training, PLABRT learns to reconstruct an original text that is corrupted using an arbitrary noise function, including three noise strategies in this work, i.e., token masking, token deletion, and token infilling. PLBART is fine-tuned for two categories of four downstream tasks (i.e., code generation, translation, summarization, and classification) across seven programming languages. The experimental results demonstrate that PLBART outperforms previous LLMs, such as CodeBERT and GraphCodeBERT, demonstrating its promise in both code understanding and generation.

**CodeT5: Code-aware T5-based LLM.** Despite introducing source code, PLBART simply processes code snippets as natural language and ignores the code-specific characteristics. CodeT5 [8] represents a successful adaption of encoderdecoder LLMs from NLP to the source code domain and has been widely used in SE research. In 2021, Wang *et al.* [9] introduce CodeT5, a unified encoder-decoder LLM based on the T5 architecture by leveraging the code semantics from the developer-assigned identifiers. CodeT5 considers two types of input representations based on whether a code snippet has a corresponding NL description: unimodal (i.e., PL) and bimodal (i.e., PL-NL pairs) data. To encode the input data, CodeT5 concatenates PL and NL into a whole sequence X with a delimiter token [SEP], *i.e.*, X = $(w_1, \cdots, w_n, [SEP], c_1, \cdots, c_m, [SEP]])$ , where n and m denote the number of NL word tokens and PL code tokens, respectively. CodeT5 employs three identifier-aware pretraining tasks (*i.e.*, masked span prediction, masked identifier prediction, and identifier tagging) to consider the crucial token type information and a bimodal dual generation pretraining task to learn a better NL-PL alignment between the code and its accompanying comment. CodeT5 is then finetuned with the CodeXGLUE benchmark to perform both code generation and understanding tasks, *i.e.*, code summarization, code generation, code translation, code refinement, defect detection, and clone detection. The results demonstrate that CodeT5 significantly outperforms previous LLMs in most downstream tasks, such as RoBERTa, CodeBERT, GraphCodeBERT, GPT2, CodeGPT, and PLBART.

SPT-Code. However, previous LLMs simply reuse the pre-training tasks designed for NL, while failing to learn the the connection between a piece of code and the associated NL for code-related tasks. In May 2022, Niu et al. [37] introduce SPT-Code, which is a sequence-to-sequence LLM designed for source code. When given a complete method, SPT-Code aims to acquire general knowledge from the method's source code, its underlying code structure, and the corresponding natural language description. The input is represented as  $\{c_1, \dots, c_l, [SEP], a_1, \dots, a_m, [SEP], n_1, \dots, n_p\}$ , where l represents the number of code tokens, m denotes the length of the linearized Abstract Syntax Tree (AST) sequence, and p signifies the number of tokens in the natural language description. SPT-Code introduces three specialized codespecific pre-training tasks, *i.e.*, Code-AST Prediction (CAP), Masked Sequence to Sequence (MASS), and Method Name Generation (MNG). Each of these tasks enables SPT-Code to capture a distinct aspect of the data instance. Specifically, CAP focuses on understanding the source code by masking a random fragment of the code tokens. MNG aims to predict whether a given AST accurately represents a particular code fragment, thereby gaining insights into the syntactic structure. Finally, MNG's objective is to generate subtokens corresponding to the method name, a concise natural language description of the method. These three pre-training tasks are meticulously designed to enable SPT-Code to learn about source code, its underlying structure, and the natural language descriptions associated with it. Importantly, SPT-Code does not rely on any bilingual corpora. This knowledge is leveraged when SPT-Code is applied to downstream tasks, making use of these three informational sources.

**CodeRL: CodeT5-derived LLM for program synthesis.** Unlike previous general-propose LLMs, in 2022, Le *et al.* [38] propose CodeRL, a successor of CodeT5, for the program synthesis task based on deep reinforcement learning. CodeRL is built on top of CodeT5-large architecture with (1) an enlarged pre-training dataset, which has 10.5B tokens and is 10x larger than the CodeSearchNet corpus used in the original CodeT5; and (2) enhanced learning objectives, *i.e.*, masked span prediction and next-token prediction. In particular, CodeRL considers program synthesis as a reinforcement learning problem and applies the actorcritic reinforcement learning method, enhancing CodeT5's performance by leveraging unit test signals during model optimization and generation.

**CoditT5: CodeT5-derived LLM for Code Editing.** Despite achieving impressive performance in numerous coderelated generation tasks, previous LLMs are not well-suited for editing tasks. In 2022, Zhang *et al.* [39] propose CoditT5, an encoder-decoder LLM for code-related editing tasks based on CodeT5. Initialized from the CodeT5-base model, CoditT5 is pre-trained with an edit-aware pre-training objective on the CodeSearchNet dataset, *i.e.*, generating the editbased output sequence given the corrupted input sequence. CoditT5 is fine-tuned on three downstream tasks, including comment updating, bug fixing, and automated code review, demonstrating superior performance against previous generation-based LLMs (*e.g.*, PLBART and CodeT5) in tackling code editing tasks, such as program repair.

AlphaCode: Competition-level Code Generation LLM. Despite demonstrating remarkable abilities in code generation, previous LLMs have shown limited success when confronted with competition-level programming problems that require problem-solving skills beyond simply translating instructions into code. In 2022, Li et al. [40] from DeepMind propose AlphaCode, an encoder-decoder LLM specifically designed to generate solutions for competitive programming solutions problems that require deep reasoning. AlphaCode is built on top of an encoder-decoder transformer-based architecture and is pre-trained with 86.31 million files across 13 programming languages from public GitHub repositories. The encoder and decoder are pretrained with masked language modeling and next-token prediction objectives, respectively. AlphaCode takes the problem description as input to the encoder and generates a code autoregressively from the decoder one token at a time until an end-of-code token is produced. AlphaCode is then fine-tuned with the CodeContests dataset and the results show that AlphaCode performs roughly at the level of the median competitor, *i.e.*, achieving on average a ranking of top 54.3% in competitions with more than 5,000 participants.

CodeT5+: successor LLM of CodeT5. Although existing LLMs are adept at learning rich contextual representations applicable to a variety of code-related tasks, they often rely on a limited set of pre-training objectives. Such objectives might result in substantial performance degradation in certain downstream tasks due to the discrepancy between the pre-training and fine-tuning stages. In 2023, Wang et al. [41] present CodeT5+, a successor of CodeT5 where component modules can be flexibly combined to accommodate a wide range of downstream code tasks. CodeT5+ is pre-trained with two objectives (*i.e.*, span denoising and causal language modeling) on unimodal code corpora and two objectives(*i.e.*, text-code contrastive learning and text-code matching) on bimodal text-code corpora. Codet5+ is built on top of the encoder-decoder Transformer architecture and is classified into two groups according to mode size. CodeT5+ 220M and 770M are trained from scratch following T5's architecture and CodeT5+ 2B, 6B, 16B are initialized from off-the-shelf CodeGen checkpoints [54]. The evaluation experiments are conducted on 20 code-related benchmarks under different settings, including zero-shot, fine-tuning, and instructiontuning. The experimental results demonstrate that CodeT5+ achieves substantial performance on various code-related tasks, such as code generation and completion, math programming, and text-to-code retrieval tasks

JuPyT5: PyMT5-derived LLM for Jupyter Notebook. Unlike existing LLMs generating code from descriptions, in 2022, Chandel et al. [42] propose JuPyT5, an encoderdecoder LLM designed as a data science assistant for the Jupyter Notebook. JuPyT5 is built on the BART architecture and initialized from a pre-trained PyMT5 checkpoint with the same training hyperparameters. JuPyT5 is then pretrained with a cell-infilling objective on a Data Science Problems (DSP) dataset, which is constructed from almost all publicly available Jupyter Notebook GitHub repositories. DSP consists of 1119 problems curated from 306 pedagogical notebooks with 92 dataset dependencies, natural language and Markdown problem descriptions, and assert-based unit tests. These problems are designed to assess university students' mastery of various Python implementations in Math and Data Science. The experimental results demonstrate that JuPyT5 achieves a 77.5% success rate in solving DSP problems based on 100 sampling attempts, proving the potential of using LLMs as data science assistants.

ERNIE-Code: Multilingual-NL-and-PL LLM. Despite achieving impressive performance in various SE tasks, existing LLMs has been essentially connecting English texts (e.g., comments or docstring) and multilingual code snippets (e.g., Python and Java). Such an English-centricity issue dramatically limits the application of such LLMs in practice, given that 95% of the world's population are non-native English speakers. In 2023, Chai et al. [43] from Baidu propose ERNIE-Code, which is a unified LLM designed to bridge the gap between multilingual natural languages (NLs) and multilingual programming languages (PLs). The crosslingual NL-PL ability of ERNIE-Code is learned from two pre-training tasks, i.e., span-corruption language modeling and Pivot-based translation language modeling. The former learns intra-modal patterns from PL or NL only, while the latter learns cross-modal alignment from many NLs and PLs. ERNIE-Code is built on the T5 encoder-decoder architecture and trained on PL corpus (i.e., CodeSearchNe with six PLs), monolingual NL corpus (i.e., CC100 with monolingual NLs), and parallel NL corpus (i.e., OPUS with 105 bilingual pairs). ERNIE-Code is capable of understanding and generating code and text in 116 different NLs and 6 PLs, and outperforms previous LLMs such as PLBART and CodeT5 in various code tasks, such as code-to-text, text-tocode, code-to-code, and text-to-text generation. Importantly, ERNIE-Code demonstrates superior performance in zeroshot prompting for multilingual code summarization and text-to-text translation.

#### 0.3 Decoder-only LLMs

**GPT-C:** first attempt LLM for Code Generation. As early as 2020, Svyatkovskiy *et al.* [50] from Microsoft propose GPT-C, a variant of the GPT-2 trained from scratch on a large unsupervised multilingual source code dataset. GPT-C is a multi-layer generative transformer model trained to predict sequences of code tokens of arbitrary types, generating up to entire lines of syntactically correct code. The pre-training dataset contains 1.2 billion lines of code in Python,

C#, JavaScript, and TypeScript. The experimental results demonstrate that GPT-C achieves an average edit similarity of 86.7% on code completion tasks for Python programming language. Importantly, GPT-C is implemented as a cloud-based web service, offering real-time code completion suggestions in Visual Studio Code IDE and Azure Notebook environments.

CodeGPT: a variant of GPT-2 for Source Code In 2021, similar to GPT-C, Lu et al. [51] from Microsoft propose CodeGPT, a decoder-only Transformer-based LLM, following the model architecture and training objectives of GPT-2. As one of the baseline LLMs in CodeXGLUE, CodeGPT is designed to support code completion and textto-code generation tasks. CodeGPT undergoes pre-training on the CodeSearchNet dataset, particularly focusing on the Python and Java corpora. There exist two versions of CodeGPT, *i.e.*, the original CodeGPT, which is pre-trained from scratch with randomly initialized parameters; and CodeGPT-adapted, which is re-trained from the checkpoint of GPT-2 on the code corpus. The experimental results show that in code completion tasks on the PY150 and Github Java Corpus datasets, CodeGPT achieves a performance of 70.65%, while its enhanced version, CodeGPT-adapted, reaches 71.28%. In the text-to-code generation task on the CONCODE dataset, CodeGPT attains a CodeBLEU performance of 32.71%, and CodeGPT-adapted achieves 35.98%.

Codex: A descendant of GPT-3 for Code Tasks Inspired by the considerable success of LLMs (such as GPT-3) in NLP and the abundance of publicly available code, Chen et al. [52] from OpenAI propose Codex, a descendant of GPT-3 model fine-tuned with publicly available code corpus from GitHub. Codex is primarily trained for the task of generating independent Python functions from docstrings. The HumanEval benchmark is constructed to evaluate the functional correctness of generated code with 164 handwritten programming problems, each accompanied by a function signature, docstring, body, and several unit tests. The experimental results demonstrate that Codex exhibits remarkable performance, with its model solving more problems on the HumanEval dataset than GPT-3 and GPT-J, achieving a success rate of 28.8%. Furthermore, Codex can solve 70.2% of the questions using a repeated sampling strategy, with 100 samples per question. This suggests that generating multiple samples from the model and selecting the optimal solution is a highly effective approach for challenging prompts. Importantly, Codex and descendants are deployed in GitHub Copilot, indicating the power of LLMs in transforming the landscape of code-related tasks.

**PolyCoder: open-sourced LLM comparable to Codex.** Despite the impressive success of LLMs of code, some powerful LLMs (such as Codex) are not publicly available, preventing the research community from studying and improving such LLMs. In 2022, Xu *et al.* [53] propose Poly-Coder, a decoder-only LLM based on GPT-2 architecture. PolyCoder is trained with 249GB of code from 12 programming languages and contains three sizes, 160M, 400M, and 2.7B parameters. The results demonstrate that despite Codex's primary focus on Python, it still performs well on other programming languages, even outperforming GPT-J and GPT-NeoX. However, for the C programming language, PolyCoder outperforms all LLMs including Codex. Importantly, unlike Codex, three PolyCoder models of different sizes are made available for the research community.

CodeGen: LLM for program synthesis. To investigate program synthesis with LLMs, in 2023, Nijkamp et al. [54] from Salesforce introduce CodeGen, which employs a selfregressive Transformer architecture and is trained sequentially on natural language and programming language datasets (THEPILE, BIGQUERY, and BIGPYTHON). It is designed for multi-round program synthesis. CodeGen undergoes evaluation for both single-round and multi-round program synthesis. In single-round evaluation, the synthetic benchmark HumanEval is utilized, and it is observed that CodeGen performance improves with data sizes. Experimental results demonstrate that the performance of the CodeGen NL model either surpasses or is comparable to that of GPT-NEO and GPT-J. CodeGen-Multi demonstrates a significant performance advantage over GPT-NEO, GPT-J, and CodeGen-NL. Furthermore, CodeGen-Mono, finetuned on a pure Python dataset, exhibits remarkable enhancements in program synthesis.

InCoder: LLM for Code Infilling and Synthesis. Existing LLMs generate code in a left-to-right manner, which may be unsuitable to many many ubiquitous code editing tasks, such as bug fixing. In 2022, Fried et al. [14] from Facebook propose InCoder, a decoder-only LLM designed for program synthesis and editing. InCoder is pre-trained by a causal masking objective, *i.e.*, learning through the random replacement of code segments with sentinel tokens, moving them to the end of the sequence. InCoder's training data consists solely of open-licensed code (Apache 2.0, MIT, BSD-2, and BSD-3 licenses) from online sources such as GitHub, GitLab, and StackOverflow. It primarily focuses on Python and JavaScript but encompasses a total of 28 languages, amounting to approximately 200GB of data in total. There are two versions of the publicly released pre-trained models: one with 6.7 billion parameters and another with 1.3 billion parameters. The experimental results demonstrate that InCoder is able to infill arbitrary regions of code under a zero-shot setting for several tasks, such as type inference and comment generation ,InCoder achieves performance roughly equivalent to CodeGen-Multi on the HumanEval benchmark.

**PyCodeGPT: LLM for library-oriented code generation.** Previous state-of-the-art LLMs are not publicly available, hindering the progress of related research topics and applications. Similar to PolyCoder [53], in 2022, Zan *et al.* [55] propose PyCodeGPT, a publicly available LLM particular designed for Python. PyCodeGPT is derived from GPT-Neo 125M with a vocabulary size of 32K and incorporates a novel byte-level BPE tokenizer tailored for Python source code. The training dataset consists of 13 million Python files with 96GB crawled from GitHub. The experimental results demonstrate that PyCodeGPT achieves a pass@1 score of 8.33% and pass@10 of 13.53% on the HumanEval benchmark, surpassing other LLMs with similar parameters, such as AlphaCode, CodeClippy, and CodeParrot.

**SantaCoder.** Regarding the removal of personally identifiable information, the BigCode community [56] propose SantaCoder, a decoder-only LLM with 1.1 billion parameters. SantaCoder's architecture is based on GPT-2 with multi-query attention and Fill-in-the-Middle objective. Its training dataset consists of Python, Java, and JavaScript files from The Stack v1.1. The dataset has undergone several preprocessing steps, including partial data removal, nearduplication removal, de-identification of personally identifiable information, and filtering based on line length and the percentage of alphanumeric characters. Files containing test samples from benchmarks such as HumanEval, APPS, MBPP, and MultiPL-E have also been excluded. The experimental results on the MultiPL-E benchmark demonstrate that SantaCoder outperforms InCoder-6.7B and CodeGen-2.7B in code generation and filling tasks.

**StarCoder**. Committed to developing responsible LLMs, Li *et al.* [57] from Hugging Face present StarCoder and StarCoderBase, which are LLMs for code. StarCoder is trained on Stack v1.2, and to ensure the secure release of opensource LLMs, it has improved the personally identifiable information editing pipeline and introduced innovative attribution tracking tools. StarCoder undergoes evaluations on HumanEval and MBPP, the experimental results show that StarCoder outperforms PaLM, LaMDA, LLaMA, CodeGen-16B-Mono, and OpenAI's code-cushman-001 (12B) on HumanEval.

PanGu-Coder: LLM for text-to-code generation. To address the specific task of text-to-code generation, adapt to more specific language domains, and handle signals beyond natural language, In 2022, Christopoulou1 et al. [58] from Huawei propose PanGu-Coder, a decoder-only LLM for text-to-code generation, *i.e.*, generating stand-alone Python functions from docstrings and evaluating the correctness of code examples through unit tests. PanGu-Coder is built on top of the PanGu-Alpha architecture, a uni-directional decoder-only transformer with an extra query layer stacked on top. PanGu-Coder is trained with two objectives, i.e., a causal language modeling on raw programming language data, and a combination of causal language modeling and masked language modeling for the downstream task of textto-code generation. The results under a zero-shot manner show that PanGu-Coder outperforms industry LLMs such as Codex and AlphaCode on the HumanEval and MBPP datasets.

**PanGu-Coder2: LLM with Reinforcement Learning.** Inspired by the success of Reinforcement Learning from Human Feedback in LLMs, in 2023, Shen *et al.* [59] propose PanGu-Coder2, a successor of PanGu-Coder with more powerful code generation capability. PanGu-Coder2 is trained with a new training paradigm, *i.e.*, Rank Responses to align Test&Teacher Feedback and built on top of the advanced StarCoder 15B model. The experimental results demonstrate that PanGu-Coder2 is able to outperform previous LLMs, such as StarCoder, CodeT5+, and AlphaCode on HumanEval, CodeEval, and LeetCode benchmarks.

**PaLM-Coder: a variant of PaLM for source code.** To investigate the captivity of PaLM for source code, in 2022, Chowdhery *et al.* [60] from Google propose PaLM-Coder, a variant of PaLM by code-specific fine-tuning. The based model PaLM is pre-trained with a high-quality corpus of 780 billion tokens, including 196GB of source code from open-source repositories on GitHub. PaLM-Coder is further derived from PaLM with a two-stage fine-tuning process, *i.e.*, (1) an initial fine-tuning over 6.5 billion tokens, consisting of a blend with 60% Python code, 30% multi-language

code and 10% natural language; and (2) an extended finetuning with 1.9 billion Python code tokens. The experimental results show that PaLM-Coder is able to achieve 88.4% pass@100 on HumanEval and 80.8% pass@80 on MBPP. Besides, PaLM-Coder demonstrates impressive performance on the DeepFix code repair task with a compile rate of 82.1%, opening up opportunities for fixing complex errors that arise during software development.

CodeGeeX: LLM for Multilingual Code Generation. Despite demonstrating impressive performance, previous LLMs (such as Codex) mainly focus on code generation and are closed-source. In 2023, Zheng et al. [61] introduce CodeGeeX, a multilingual decoder-only open-sourced LLM with 13 billion parameters for both code generation and translation tasks. CodeGeeX is implemented with the Huawei MindSpore framework and pre-trained on 850 billion tokens from 23 programming languages, including C++, Java, JavaScript, and Go. Besides, on top of the wellknown HumanEval benchmark, a multilingual code generation benchmark HumanEval-X is constructed to evaluate CodeGeeX by hand-writing the solutions in C++, Java, JavaScript, and Go. The experimental results demonstrate that CodeGeeX performs exceptionally well in code generation and translation tasks on the HumanEval-X benchmark. Importantly, CodeGeeX has been integrated with Visual Studio Code, JetBrains, and Cloud Studio. It generates 4.7 billion tokens weekly for tens of thousands of active developers, enhancing the coding efficiency of 83.4% of its users. Besides, CodeGeeX is open-sourced, as well as its code, model weights, API, and HumanEval-X, facilitating the understanding and advances in the community.

**CodeGen2:** A Successor of CodeGen. Considering the high computational cost of training LLMs, in 2023, Nijkamp *et al.* [62] propose CodeGen2, an successor of Code-Gen, aimed at addressing the challenge of more efficiently training LLMs for program synthesis and understanding tasks. CodeGen2 provide a training framework along with open-source CodeGen2 models in four variations, including 1B, 3.7B, 7B, and 16B parameters in size. CodeGen2 is trained on the BigPython dataset and evaluated on the Stack dataset to assess its learning performance in HumanEval and HumanEval-Infill tasks. The experimental results demonstrate that CodeGen2 performs well across various model sizes and program synthesis and understanding tasks, outperforming InCoder in the evaluation on HumanEval.

**Code Llama: Llama-based LLM for Source Code.** On top of the powerful Llama 2 model in NLP, in 2023, Roziere *et al.* [86] from Meta AI propose Code Llama, a series of LLMs specialized in handling code-related tasks. Code Llama exhibits capabilities such as infilling, support for large input contexts, and zero-shot instruction-following abilities. The dataset of Code Llama primarily comprises an extensive collection of programming language content, with a special emphasis on Python language, trained through a code-heavy dataset containing 500B tokens and an additional Python-intensive data mix of 100B tokens. It comprises multiple versions, covering Code Llama, Code Llama - Python, and Code Llama - Instruct with 7B, 13B and 34B parameters each. Code Llama undergoes evaluation on HumanEval and MBPP, the experimental results indicate

that Code Llama outperforms LLama and Llama 2 in terms of performance.



Fig. 3: Taxonomy of the application of LLMs in different domains within software engineering

## APPENDIX B: DETAILED SUMMARIZATION OF EX-ISTING LLM-BASED SE STUDIES



Fig. 3: Taxonomy of the application of LLMs in different domains within software engineering (Continue)

			_	
		(Invariant Prediction		-[718]
		GUI Testing	$\supset$	[719] [291] [294] [292] [293]
	-	Proof Generation	$\supset$	-[720]
	-	Indirect Call Analysis	$\supset$	[[721]
	-	Resource Leak Detection	$\supset$	[[722]
	-	Mutation Testing	$\supset$	[289] [286] [723] [285] [290] [724] [725] [726] [727] [288] [287] [728]
	_	Taint Analysis	$\supset$	[[729]
		NLP Testing	$\supset$	[298] [300] [297] [296] [299] [301] [295]
		Vulnerability Detection	⊃–	[730]       [731]       [733]       [236]       [734]       [735]       [736]       [737]       [738]       [238]       [739]       [740]       [741]       [742]       [743]       [744]         [745]       [746]       [747]       [748]       [740]       [751]       [752]       [757]       [758]       [759]       [740]       [741]       [742]       [743]       [744]         [746]       [747]       [748]       [740]       [751]       [752]       [758]       [759]       [757]       [758]       [759]       [750]       [751]       [752]       [751]       [752]       [752]       [756]       [757]       [758]       [757]       [756]       [757]       [758]       [759]       [750]       [751]       [752]       [753]       [751]       [752]       [752]       [756]       [757]       [758]       [756]       [757]       [758]       [756]       [757]       [758]       [756]       [757]       [751]       [752]       [752]       [756]       [757]       [758]       [758]       [756]       [757]       [758]       [758]       [756]       [757]       [758]       [756]       [757]       [756]       [757]       [756]       [757]       [75
	_	Penetration Testing	$\supset$	[792] [282] [280] [281]
	-	Program Analysis	$\supset$	[[793]
	_	Adversarial Attack	$\supset$	[310] [794]
	$\cap$	Program Reduction	$\supset$	[311]
	உ	API Misuse Detection	$\supset$	[[795]
8	re Testir	API Testing	$\supset$	-[1302]
X		Assertion Generation	$\supset$	[261] [262] [796] [263] [797] [798] [259] [17] [260] [264]
	oftwa	Binary Code Similarity Detection	$\rightarrow$	-[[799] [800] [801] [802]
	S	Code Execution	5–	-[303]
	_	Decompilation	$\supset$	[226] [231] [224] [228] [225] [229] [230] [227]
	_	Failure-Inducing Testing	$\supset$	-[[284]
	_	Fault Localization		[221] [803] [804] [223] [223] [805] [806] [218] [807] [222] [220] [808] [809] [219] [810] [217] [811]
	_	Fuzzing	$\supset$	[273] [269] [272] [279] [278] [270] [267] [267] [266] [351] [275] [277] [271] [274] [276] [268]
	_	Formal Verification		-[[812] [813] [814] [815]
	_	Static Analysis	$\supset$	-[304] [305] [307] [306] [816] [817]
	_	Static Warning Validating		_[[518]
	_	Test Generation		[819] [820] [821] [822] [252] [253] [823] [824] [248] [240] [825] [826] [251] [247] [249] [827] [243] [244] [828] [829] [242] [830] [254] [831] [832] [833] [834] [430] [258] [835] [257] [255] [836] [256] [309] [837] [246] [838] [250] [839] [840] [245] [841] [842]
	⊢	Test Suite Minimization	$\supset$	[[265]
	┝	Vulnerable Dependency Alert Detection	$\supset$	-[1308]
	F	Theorem Proving	5–	-[[309]
	L	Property-based Testing	$\supset$	_[283]

Fig. 3: Taxonomy of the application of LLMs in different domains within software engineering (Continue)

	Г	Android Permissions	[409]	
	-	APP Review Analysis	(843) [844]	
	_	Bug Report Detection	(372] [371] [845] [846] [847]	
	_	Code Clone Detection	(848) [394] [849] [850] [395] [396] [851] [852] [853]	
	_	Bug Reproduction	(374] [854] [373] [375]	
	_	Code Coverage Prediction	[855]	
	_	Bug Triaging	([397] [398] [856]	
	_	Code Evolution	[159]	
	_	Code Review	[857] [858] [859] [860] [861] [862] [366] [863] [864] [865] [367] [866] [369] [867] [368] [868] [370] [869] [870] [871] [872] [873] [874] [365]	
	_	Code Refactoring	[875] [876] [877] [878]	
		Code Smells	(399)	
	-	Commit Message Generation	(363] [879] [364] [360] [362]	
		Compiler Optimization	(408) [880] [881] [882] [883] [884] [885] [407]	
		Debugging	([886]	
	8	Exception Handling Recommendation	(401)	
	nanc	Flaky Test Prediction	[887]	
_	ainte	Incident Management	(403] [402]	
	re Ma	Log Analysis	[393] [888] [392] [384] [889] [383] [382] [890] [381] [891] [390] [386] [379] [387] [380] [388] [385] [892] [893]	
	ftwa	(Issue Labeling	(404) [856]	
	S	Mobile App Crash Detection	[[894]	
	_	Log Anomaly Detection	[895]	
		Outage Understanding	(896)	
	_	Sentiment Analysis	[897] [898] [899] [900]	
	_	Patch Correctness Assessment	(357] [353] [359] [358] [354]	
		Tag Recommendation	[901]	
	_	Privacy Policy	(405]	
12H	_	Technical Debt Management	[902]	
	_	(Program Repair	[903] [314] [323] [904] [330] [341] [905] [313] [329] [906] [326] [11] [336] [328] [347] [346] [16] [907] [908] [322] [333] [335] [315] [316] [344] [324] [909] [332] [910] [911] [11] [318] [912] [325] [312] [327] [331] [365] [434] [13] [131] [312] [317] [141] [151] [161] [339] [917] [460] [334] [918] [340] [321] [919] [345] [338] [920] [921] [319] [922] [342] [923] [337] [924] [925]	
	_	Test Update	[377] [378] [376]	
	-	Report Severity Prediction	[926] [927] [928]	
	-	Traceability Link Recovery	[929]	
		Vulnerability Repair	(930] [931] [351] [932] [15] [850] [933] [12] [934] [349] [348] [352]	
		Developers' Behavior Analysis		
	ager	Effort Estimation	([410] [411]	
L	- Man	Software Tool Configuration	[412]	
	tware	Software Repository Mining		
	Sof		-	

Fig. 3: Taxonomy of the application of LLMs in different domains within software engineering (Continue)