

---

# EpilepsyLLM: Domain-Specific Large Language Model Fine-tuned with Epilepsy Medical Knowledge

---

Xuyang Zhao<sup>1,2</sup>, Qibin Zhao<sup>2</sup> and Toshihisa Tanaka<sup>1</sup>

1. Department of Electrical Engineering and Computer Science,  
Tokyo University of Agriculture and Technology, Tokyo, Japan

2. Tensor Learning Team,  
RIKEN Center for Advanced Intelligence Project, Tokyo, Japan

## Abstract

With large training datasets and massive amounts of computing sources, large language models (LLMs) achieve remarkable performance in comprehensive and generative ability. Based on those powerful LLMs, the model fine-tuned with domain-specific datasets possesses more specialized knowledge and thus is more practical like medical LLMs. However, the existing fine-tuned medical LLMs are limited to general medical knowledge with English language. For disease-specific problems, the model's response is inaccurate and sometimes even completely irrelevant, especially when using a language other than English. In this work, we focus on the particular disease of Epilepsy with Japanese language and introduce a customized LLM termed as EpilepsyLLM. Our model is trained from the pre-trained LLM by fine-tuning technique using datasets from the epilepsy domain. The datasets contain knowledge of basic information about disease, common treatment methods and drugs, and important notes in life and work. The experimental results demonstrate that EpilepsyLLM can provide more reliable and specialized medical knowledge responses.

## 1 Introduction

In recent years, large language models (LLMs) have demonstrated impressive performance, especially success in instruction understanding and human-like response generation. In the natural language processing (NLP) benchmark, LLMs continuously refreshed records. Most LLMs are built based on Transformer structure Vaswani et al. [2017], and with the help of large training data and massive computing resource. OpenAI has released a series models of GPT-3 Brown et al. [2020], InstructGPT Ouyang et al. [2022] and GPT-4 OpenAI [2023], and the performance of the models is constantly updated. However, the details of the model such as architecture, training strategies, training data and other information have not been released. LLaMA Touvron et al. [2023] is released by the Meta which is open-source in the research field, containing four different parameter models of 7, 13, 30 and 65 billions. At the same time, the model also achieved good performance on most benchmarks. LLaMA (13B) outperforms GPT-3 and is ten times smaller. For the largest 65B parameter model, the performance is similar to some well-known models such as Chinchilla and PaLM-540B.

In order to further improve the performance of the LLMs, Stanford Alpaca Taori et al. [2023] has proposed an efficient and low-cost fine-tuning method. The Alpaca method just uses 52K instruction-following demonstrations to fine-tune the pre-trained LLaMA (7B) model and the Alpaca behaves qualitatively similarly to OpenAI's GPT-3.5 (text-davinci-003). The instruction-following demonstrations are built from 175 human-written instruction-output pairs and use GPT-3.5 (text-davinci-003) to generate more instructions. In this mode, the performance of the basic model (LLaMA 7B) is

efficient (8 80GB A100s with 3 hours) and low cost (<600\$) improved to the GPT-3.5 (text-davinci-003) level.

Usually, LLMs focus on general tasks, and while these LLMs achieve amazing performance, in subdivided professional fields, the performance of the LLMs is often not professional and accurate enough. In order to improve the professional performance of LLMs in a specific field, it is often possible to fine-tune the model using specific field knowledge. In the medical field, there have been some works such as PubMedBERT Gu et al. [2021], BioLinkBert Yasunaga et al. [2022], BioMedLM Venigalla et al. [2022], BioGPT Luo et al. [2022], Med-PLaM Tu et al. [2023], and ChatDoctor Yunxiang et al. [2023]. Among them, the medical knowledge includes patient-physician conversations, PubMed abstracts & PubMed Central full text articles, and e-identified clinical notes. With the help of medical knowledge, fine-tuned LLMs achieves better performance on medical tasks. In the United States Medical Licensing Examination (USMLE), MedPaLM 2 achieved the highest score of 86.5.

LLMs fine-tuned by the medical knowledge achieve better performance in medical general tasks in English language. Unlike the common medical LLMs, this work presents a model of EpilepsyLLM that focuses on a particular disease of epilepsy and uses Japanese language. When using LLMs in the medical field, it is of more importance that the professionalism of the model output results. Our dataset for fine-tuning is professional knowledge about epilepsy collected from the Internet and is prepared as instruction-following demonstrations. Furthermore, the fine-tuning dataset uses the Japanese language. We adopt the pre-trained LLaMA (7B) and LLM-JP<sup>1</sup> as the base model. The experimental results show that LLMs fine-tuned with epilepsy knowledge achieves the highest performance in testing. Compared with LLaMA and LLM-JP for general tasks or medical LLMs that have been fine-tuned with medical knowledge, EpilepsyLLM shows more professional and reliable answers when faced with epilepsy knowledge. The experimental results also confirmed that by using more specific domain knowledge to fine-tune the LLMs, the performance of the model in this domain can be greatly improved.

The rest of the article is organized as follows. Section 2 describes the fine-tuning dataset and EpilepsyLLM model. Section 3 explains the experimental results. The discussion and conclusion are presented in Sections 4 and 5, respectively.

## 2 Approach

In this work, we use epilepsy knowledge to fine-tune the LLMs to improve the epilepsy-specific domain performance. The model shows the more reliable medical knowledge responses and better support in Japanese.

### 2.1 Epilepsy Knowledge

Epilepsy is a common brain neurological disorder disease that affects 50 million people around the world World Health Organization (WHO) Organization et al. [2019]. To improve patients' quality of life, there are some institutions that provide basic knowledge about epilepsy, including basic information about the disease, treatment methods, life precautions, school work, etc. In this work, the epilepsy dataset is collected from the Japan Epilepsy Association<sup>2</sup>, Epilepsy Information Center<sup>3</sup> and Tenkan Net<sup>4</sup>. Referring to Alpaca Taori et al. [2023], the dataset is prepared as instruction-following demonstrations, some examples in the dataset are shown in Table 1. There are more than two hundred samples used for fine-tuning the model and 24 samples used for model testing.

### 2.2 Base Model

Two open-source models of LLaMA and LLM-JP are used as base models. LLaMA Touvron et al. [2023] is a collection of foundation language models ranging from 7B to 65B parameters (four different parameters of 7, 13, 30, and 65 billion). The LLaMA is trained on trillions of tokens, and

---

<sup>1</sup><https://github.com/llm-jp>

<sup>2</sup><https://www.jea-net.jp/>

<sup>3</sup><https://shizuokamind.hosp.go.jp/epilepsy-info/>

<sup>4</sup><https://www.alfresa-pharma.co.jp/general/tenkan/faq/index.html>

all the training data is publicly available. The training data used in LLaMA is shown in Table 2. As a medium-size model, the LLaMA (13B) reaches the performance of GPT-3. By using Alpaca fine-tuning method, the LLaMA (7B) behaves qualitatively similarly to OpenAI’s GPT-3.5 (text-davinci-003).

Another base model is LLM-JP, which is trained by Japanese and English language data. LLM-JP has two different model size with the number of parameters of 1.3 and 13 billion. In multiple Japanese benchmark, LLM-JP achieved promising performance.

Table 1: Examples of epilepsy dataset.

Question	Answer
てんかんはどんな病気ですか	てんかん発作は大脳神経細胞の過剰な亢奮（てんかん発射）によって生じます。てんかん発作を繰り返し、慢性に経過する大脳の病気がてんかんです。ただ1回だけの発作や高熱のときだけに起こる発作はてんかんとは区別されます。また、脳炎の急性期や頭部外傷の直後に起こったけいれん発作も、それだけであれば、てんかんとは区別されます。慢性に経過することがてんかんの特徴です。てんかん発作は大脳の機能が種々の形で表出されるので、発作症状はきわめて多彩です。しかし、ひとりの患者の発作症状はほぼ一定しています。なぜてんかんになるのか、なぜてんかん発作が起こるかは十分にはわかっていません。大脳の神経細胞ネットワークの亢奮と抑制の微妙なバランスの破綻に求める学説が有力です。てんかん発作を起こしやすい下地（素因）と大脳の機能を不安定にする脳損傷（外因）とが複雑に絡み合っていててんかんが発病すると推測されています。
てんかん発作が起こることで、脳にダメージを受けませんか	てんかん重積状態という特別な状態をのぞけば、通常、一度の発作で脳がダメージを受けることはありません。てんかん重積状態とは、30分以上発作がとまらなかつたり、ひとつの発作が終わった後、意識が完全に回復する前に次の発作が起こることを30分以上繰り返す状態を指し、注射など薬物で発作をとめる必要のある緊急事態です。ただし、長い経過を見ますと、記憶障害、知能低下や行動障害、精神医学的問題を合併することがあります。これらは発作を繰り返した影響や、過ぎた薬物の服用、心理的要因、てんかんの原因となっているものと病気の影響など種々の要因が関与しています。てんかんが難治に経過する場合は多種類の抗てんかん薬による治療はできるだけ避け、場合によってはてんかん外科手術を早めに検討したほうが良いことがあります。また、てんかんではありませんが、乳幼児期に熱性けいれんなどのけいれんが長時間持続すると、側頭葉の内側にある海馬などの萎縮が起こり、それが数年から10年後に側頭葉てんかんの原因になることが知られています。
高齢で発病するてんかんの特徴を教えてください	てんかんの多くは小児期に発病します。2008年2月～11月に当院（静岡てんかん・神経医療センター）でてんかんと診断された928名のうち、751名（80.9%）が20歳までに発病していました。20歳を過ぎるとてんかんの発病率は次第に低下していきますが、60歳を越えると再び増加に転ずるといわれています。脳血管障害など、高齢になって新たに生ずる脳の器質的な障害を背景に、てんかんが発病しやすくなると考えられています。当院の統計でも高齢になるとわずかに発病率が増え、15名（1.6%）が60歳以降に発病していました。推定病因は脳梗塞2、脳腫瘍2、脳腫瘍1、脳外傷1、長年の大酒1名で、他は不明でした。このように器質性の病因が約半数に認められるのは、てんかん全体から見れば多い数字です。一方、熱性けいれんの既往や、てんかんまたは熱性けいれんの家族歴をもつ例は1名もありませんでした。診断は15名全例が症候性部分てんかんで、うち4名は側頭葉に焦点を認めました。発作型は全般性強直間代発作が10、複雑部分発作が7、単純部分発作が5、非けいれん性てんかん重積状態の疑いが2名でした（重複あり）。発作頻度は年単位5、月単位7、週単位2、日単位1名でした。ほぼ全例が結婚してお子さんもあり、お仕事もしてこられた方々です。一般に、高齢発病のてんかんは薬物治療で比較的容易に発作がコントロールされることが多いといわれています。高齢者では血中濃度が上昇しやすいので、服用量を決定する際には注意が必要です。
外科治療は誰でも受けられますか	手術という侵襲を考慮すると、外科治療の対象は、薬物治療で発作が抑制されない難治症例に限られます。薬が効かないと判定するには、1) 正しく診断されたてんかんに対して、2) 適切な薬が2種類以上使われたにもかかわらず、3) 2年以上発作が抑制されていない状態がめやすとなります。ただし、子どもの場合、病状によっては発育への影響を考慮して、2年を待たずに積極的に外科治療を検討することもあります。根治手術は、切除可能な病変が原因で、大脳の一部から発作が始まるてんかんを対象とします。一方、緩和手術は、根治手術の対象とはならないが、転倒する発作で外傷が絶えない症例などに検討されます。手術適応を検討する際に最も大切なことは、術前の病状だけではなく、術後の生活への期待まで視野に入れて、手術の意義について患者さんやそのご家族とよく話し合い、理解を共有することです。
発作が起きると、子どもの成長に影響がありますか	てんかんのある患者さんの身長や体重の変化をさす「成長」に関しての研究は、認知・知能・運動などの「発達」に関する研究に比べ多くなく、はっきりしたことはわかっていません。両者ともにさまざまな因子に影響されると思われます。「発達」については例えば、症候性ウエスト症候群、レンノックス症候群などの症候性全般てんかんは、てんかんの発病とともに知的退行（それまでできていたことが徐々にできなくなる）を起こす悪性のてんかんです。いわばてんかんの緊急事態であり、早急な診断と治療が知能の保護につながります。てんかんの種類、基礎疾患の有無や種類、てんかん発作が抑制されているかどうかによっても、発達への影響は異なります。また、抗てんかん薬の種類によっては鎮静効果の強いものや落ち着きをなくすなどの行動や認知に影響するもの、食欲に影響を与えるものもありますし、単剤か多剤併用かによっても違います。これらは患者さん一人ひとり違ってきますから、詳しいことは主治医あるいはてんかん専門の先生に尋ねてください。

### 3 Experiments

In this section, we evaluate the performance of the proposed method through a series of experiments. Since we have limited computing resources (4 80GB A100s), for LLaMA experiments, LLaMA (7B) is used as base model for fine-tuning and the larger models of LLaMA (13B) and LLaMA (30B) are used directly for inference. The Alpaca dataset is also used for fine-tuning. Since the

Table 2: Training and fine-tuning dataset.

Dataset	Content	Language
LLaMA Training	CommonCrawl	English
	C4	English
	Github	English
	Wikipedia	20 languages
	Books	English
	ArXiv Stack Exchange	English English
Alpaca	Instruction-following	English
Japanese Alpaca	Instruction-following	Japanese (Translate from Alpaca)
LLM-JP Training	mC4	Japanese
	Wikipedia	Japanese
	Pile	English
	Wikipedia Stack (code)	English English
Jaster	Instruction-following	Japanese
Japanese Dolly	Instruction-following	Japanese (Translate from Dolly)
Japanese Oasst	Instruction-following	Japanese (Translate from Oasst)
Epilepsy Dataset	Epilepsy knowledge	Japanese

epilepsy dataset is collected in Japanese, to verify the impact of language on LLMs performance, a translated version of the Alpaca dataset is also used for fine-tuning. The Alpaca is translated using ChatGPT, the Japanese-Alpaca data is provided from Github <sup>5</sup>. For the LLM-JP experiments, the LLM-JP (1.3B) is used as base model for fine-tuning, and the LLM-JP (13B) is used directly for inference. Three different fine-tuned models of LLM-jp-13B-instruct-full-jaster, LLM-jp-13B-instruct-full-jaster-dolly-oasst and LLM-jp-13B-instruct-full-dolly-oasst provided by LLM-JP are also used for inferences.

In the evaluation, four metrics of BLEU, METEOR, ROUGE-L, and SPICE are used to evaluate the performance of the LLMs. The experimental results are shown in Table 3. By fine-tuning the base LLMs using epilepsy knowledge data, the model’s performance is greatly improved. Although the LLM-JP (1.3B) has the fewest parameters, it achieves the highest performance in the epilepsy task due to the large amount of Japanese text included in the training data.

Table 3: LLMs performance on epilepsy tasks.

Model	Fine-tuning 1	Fine-tuning 2	BLEU	METEOR	ROUGE-L	SPICE	Mean
BioMedLM	–	–	0.0058	0.0091	0.0092	0.0000	0.0060
LLaMA (7B)	–	–	0.0173	0.0237	0.0234	0.0069	0.0178
LLaMA (7B)	Epilepsy Data	–	<b>0.2256</b>	<b>0.1836</b>	<b>0.2820</b>	0.1045	<b>0.1989</b>
LLaMA (7B)	Alpaca	–	0.0273	0.0418	0.0639	0.0439	0.0442
LLaMA (7B)	Alpaca	Epilepsy Data	0.1701	0.1705	0.2347	0.1070	0.1706
LLaMA (7B)	Japanese Alpaca	–	0.1637	0.1380	0.2217	0.0876	0.1528
LLaMA (7B)	Japanese Alpaca	Epilepsy Data	0.2037	0.1678	0.2668	<b>0.1308</b>	0.1923
LLaMA (13B)	–	–	0.0281	0.0559	0.0417	0.0057	0.0328
LLaMA (30B)	–	–	0.0281	0.0572	0.0417	0.0057	0.0332
LLM-JP (1.3B)	–	–	0.1418	0.1793	0.1805	0.0144	0.1290
LLM-JP (1.3B)	Epilepsy Data	–	<b>0.2351</b>	<b>0.2314</b>	<b>0.2631</b>	<b>0.0727</b>	<b>0.2006</b>
LLM-JP (13B)	–	–	0.1673	0.2102	0.2010	0.0198	0.1496
LLM-JP (13B)	Jaster	–	0.0004	0.0192	0.0174	0.0160	0.0132
LLM-JP (13B)	Japanese Dolly	–	0.0880	0.0891	0.1421	0.0647	0.0960
LLM-JP (13B)	Jaster & Japanese Dolly	–	0.0712	0.0889	0.1295	0.0712	0.0902

<sup>5</sup><https://github.com/masa3141/japanese-alpaca-lora/tree/main>

## 4 Discussion

Although the LLMs exhibit strong performance on general tasks. However, in some professional domains, the model’s response sometimes lacks professionalism and is not accurate enough. In order to make the response generated by the LLMs more professional and reliable, some works use the knowledge of specific domains to fine-tune the pre-trained model. In this work, we try to use more granular epilepsy knowledge to fine-tune the pre-trained model using non-English languages.

In the experiments, two different open-source LLMs are used as base models, and the fine-tuning data is collected from public websites. From the experimental results, the Japanese model of LLM-JP (1.3B) achieved the highest performance after being fine-tuned with epilepsy knowledge. Due to the lack of Japanese language support, the medical model of BioMedLM also do not show strong performance.

For the LLaMA that has not been fine-tuned, more parameters (from 7B to 30B) do not bring about a significant performance improvement. Due to the lack of professional epilepsy medical knowledge in the model’s training data, and the very low proportion of Japanese data, for Japanese epilepsy test questions, the model lacks the ability to understand and respond to the Epilepsy questions. For LLaMA (7B), the performance of the model is significantly improved by fine-tuning using Japanese epilepsy data. The Alpaca data effectively improved the LLaMA performance in general tasks Taori et al. [2023], in the epilepsy task, the model performance has also been slightly improved. However, based on the alpaca model, using the second fine-tuning of epilepsy data, the model performance did not reach the strongest performance. By using the translated Japanese Alpaca and the epilepsy data, the performance of the two-times fine-tuned model is improved.

Since the LLM-JP uses a large amount of Japanese data in the training process, the model shows a strong performance on Japanese tasks. The performance of LLM-JP (1.3B) fine-tuned based on epilepsy data has been greatly improved from 0.129 to 0.2006. For tasks in specific domains, using specific data for fine-tuning can achieve significant performance improvements.

## 5 Conclusion

In this work, to improve the professionalism and reliability of LLMs in epilepsy tasks, we try to use epilepsy knowledge to fine-tune the model. Different from common medical LLMs, we use the more specific disease knowledge to fine-tune the model. From the experimental results, by narrowing the scope of the domain, smaller data can also improve the performance of the model in a specific domain.

### Statement

EpilepsyLLM is dedicated to the research of LLMs in the medical field. The medical knowledge used in model training and testing is obtained from publicly accessible websites. The response content generated by the model cannot be guaranteed and cannot be used as a substitute for professional medical treatment.

## References

- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 1877–1901, 2020.
- Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. Domain-specific language model pretraining for biomedical natural language processing. *ACM Transactions on Computing for Healthcare*, 3(1):1–23, 2021.
- Renqian Luo, Liai Sun, Yingce Xia, Tao Qin, Sheng Zhang, Hoifung Poon, and Tie-Yan Liu. BioGPT: Generative pre-trained transformer for biomedical text generation and mining. *Briefings in Bioinformatics*, 23(6):bbac409, 2022.
- OpenAI. GPT-4 technical report. *arXiv 2303.08774*, 2023.
- World Health Organization et al. Epilepsy: a public health imperative. 2019.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. In *Proceedings of Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, pages 27730–27744, 2022.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpaca: A strong, replicable instruction-following model. *Stanford Center for Research on Foundation Models*. <https://crfm.stanford.edu/2023/03/13/alpaca.html>, 3(6):7, 2023.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. LLaMA: Open and efficient foundation language models. *arXiv:2302.13971*, 2023.
- Tao Tu, Shekoofeh Azizi, Danny Driess, Mike Schaekermann, Mohamed Amin, Pi-Chuan Chang, Andrew Carroll, Chuck Lau, Ryutaro Tanno, Ira Ktena, Basil Mustafa, Aakanksha Chowdhery, Yun Liu, Simon Kornblith, David Fleet, Philip Mansfield, Sushant Prakash, Renee Wong, Sunny Virmani, Christopher Sementurs, S Sara Mahdavi, Bradley Green, Ewa Dominowska, Blaise Aguerre y Arcas, Joelle Barral, Dale Webster, Greg S. Corrado, Yossi Matias, Karan Singhal, Pete Florence, Alan Karthikesalingam, and Vivek Natarajan. Towards generalist biomedical ai. *arXiv:2307.14334*, 2023.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems (NIPS)*, volume 30, 2017.
- A Venigalla, J Frankle, and M Carbin. BioMedLM: a domain-specific large language model for biomedical text. *MosaicML*. Accessed: Dec, 23(3):2, 2022.
- Michihiro Yasunaga, Jure Leskovec, and Percy Liang. LinkBERT: Pretraining language models with document links. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 8003–8016, 2022.
- Li Yunxiang, Li Zihan, Zhang Kai, Dan Ruilong, and Zhang You. ChatDoctor: A medical chat model fine-tuned on llama model using medical domain knowledge. *arXiv:2303.14070*, 2023.