CAS-DIFFCOM: CASCADED DIFFUSION MODEL FOR INFANT LONGITUDINAL SUPER-RESOLUTION 3D MEDICAL IMAGE COMPLETION

Lianghu Guo^{1,†} Tianli Tao^{1,†} Xinyi Cai^{1,†} Zihao Zhu^{1,†} Jiawei Huang¹ Lixuan Zhu¹ Zhuoyang Gu¹ Haifeng Tang¹ Rui Zhou¹ Siyan Han¹ Yan Liang¹ Qing Yang¹ Dinggang Shen^{1,2,3} Han Zhang^{1,3,*}

¹ School of Biomedical Engineering, ShanghaiTech University, Shanghai, China
 ² Shanghai United Imaging Intelligence Co., Ltd, Shanghai, China
 ³ Shanghai Clinical Research and Trial Center, Shanghai, 201210, China

ABSTRACT

Early infancy is a rapid and dynamic neurodevelopmental period for behavior and neurocognition. Longitudinal magnetic resonance imaging (MRI) is an effective tool to investigate such a crucial stage by capturing the developmental trajectories of the brain structures. However, longitudinal MRI acquisition always meets a serious data-missing problem due to participant dropout and failed scans, making longitudinal infant brain atlas construction and developmental trajectory delineation quite challenging. Thanks to the development of an AI-based generative model, neuroimage completion has become a powerful technique to retain as much available data as possible. However, current image completion methods usually suffer from inconsistency within each individual subject in the time dimension, compromising the overall quality. To solve this problem, our paper proposed a two-stage cascaded diffusion model, Cas-DiffCom, for dense and longitudinal 3D infant brain MRI completion and superresolution. We applied our proposed method to the Baby Connectome Project (BCP) dataset. The experiment results validate that Cas-DiffCom achieves both individual consistency and high fidelity in longitudinal infant brain image completion. We further applied the generated infant brain images to two downstream tasks, brain tissue segmentation and developmental trajectory delineation, to declare its taskoriented potential in the neuroscience field.

Index Terms— Medical imaging completion, Diffusion model, Super-resolution, Infant development, MRI

1. INTRODUCTION

During the initial two years after birth, the human brain undergoes a swift development in its structure and morphology [1]. Longitudinal studies have unique advantages in accounting for infant brain anatomical development and disease progression variations. Densely collecting brain images to construct a longitudinal medical image dataset has drawn extensive attention due to its profound applications in the neuroscience field, such as developmental brain atlas construction, growth charting, brain age and developmental outcome prediction.

However, research on early brain development faces challenges in both image acquisition and analysis due to the low scanning success rate for infants [1]. Moreover, factors like early termination and significant head motion contribute to failed scans, causing the absence of valid data in the longitudinal dataset. Therefore, completing the images of the missing time points in the longitudinal dataset is crucial as it enhances the reliability of neurodevelopmental analyses. Traditional methods involve fitting the structural or morphological information from incomplete data through a simple linear mixed-effect model. This approach often overlooks highly non-linear developmental patterns and degrades with more missing data.

Thus, a complex model that can learn the nonlinear brain developmental relationships is required for the collaborative completion of longitudinal neuroimage data. Many deep learning-based methods have been proposed to establish the mapping between existing and missing images, such as CNN and GAN-based models. However, such models always drive the result to an average of several possible missing predictions (e.g., model collapse), generating population average-like images without sufficient individual diversity. Such diversity is considered essential for development studies.

Recently, the denoising diffusion probabilistic model (DDPM) [2] has shown remarkable success in various tasks, such as conditioned image generation [3,4] and video synthesis [5]. Inspired by the DDPM, this paper proposes a novel

[†] indicates co-first authors and * indicates corresponding authors. This work is partially supported by the STI 2030-Major Projects (No. 2022ZD0209000), National Natural Science Foundation of China (No. 62203355), Shanghai Pilot Program for Basic Research - Chinese Academy of Science, Shanghai Branch (No. JCYJ-SHFY-2022-014), Shenzhen Science and Technology Program (No. KCXFZ20211020163408012), and Shanghai Pujiang Program (No. 21PJ1421400).



Fig. 1: The denoising module in generate and fine stages. a) The cascaded diffusion pipeline for image completion consists of an image generation model and a super-resolution model. b) The asynchronous multimodal (AsMM) block. c) The super-resolution block with transposed convolution.

cascaded diffusion model to effectively assure the generated images have the desired semantics. Specifically, our model firstly generates a structured image with multimodal guidance and then refines the synthesized image by a super-resolution diffusion model. An asynchronous 3D multimodal denoising block (AsMM Block) is designed to disentangle multimodal guidance and more effective use of multimodal information to generate the brain in the reverse denoising process.

2. METHODS

DDPM is still challenging to infer a high-quality 3D brain image with huge details and neuroscientific fidelity efficiently. Hence, we develop a cascaded two-stage diffusion-based pipeline [6] for generating high-quality infant brain MRI at missing time points, shown in Fig 1a. Suppose x_0 is the highresolution data and z_0 is its low-resolution data. Under low resolution, we have a diffusion model to generate structured longitudinal images $P_c(z_0|X_{mo})$; under high resolution, we have a fine super-resolution diffusion model to refine the lowresolution image to the high-resolution image $P_f(x_0|z_0)$. The cascaded pipeline forms a latent variable model of the high-resolution data, that is, $P_c(z_0) = \int P_f(x_0|z_0) dz_0$.

2.1. Generate Stage: Diffusion-based 3D Medical Image Completion

The first stage shown in Fig 1b is to generate a structured image with subject-specific guidance using diffusion model. The mathematical description of the conditional diffusion model is shown in formula (1).

$$p_{\theta}(x_{0:T}|c) = p(x_T) \prod_{t=1}^{T} p_{\theta}(x_{t-1}|x_t, c)$$

$$p_{\theta}(x_{t-1}|x_t, c) = \mathcal{N}(x_{t-1}; \mu_{\theta}(x_t, t, c), \Sigma_{\theta}(x_t, t, c))$$
(1)

We consider a set of paired images and age text as the multimodal guidance $c = (X_{im}, X_{mo})$ for both desired image and age information. The model training phase consists of two processes: the diffusion process and the reverse process. In the diffusion process, the low-resolution data z_0 sampling t time steps becomes a hidden variable in the Gaussian distribution x_t . In reverse denoising process, x_t and X_{im} are encoded by independent encoders including 4 residual blocks which consist of 3D convolution layers and average pooling layer. X_{mo} and t are embedded by 3D convolution and MLP respectively. The structure of the decoder is similar to the encoder, except that the up-sampling uses transposed convolution. Specifically, age information X_{mo} is applied to attention mechanisms, and denoising time step t is applied to the

residual block. In practice, since we take sample quality as the main purpose, we train with a simplified loss function in formula (2).

$$L^{simple} \triangleq E[||\epsilon - \epsilon_{\theta}(x_t; t, \tau(X_{mo}), X_{im})||^2]$$
(2)

In addressing the entanglement issue in the multimodal guidance during the reverse denoising process, we have developed an asynchronous 3D multimodal denoising block (AsMM block) architecture. Specifically, we have employed two distinct methods to guide the denoising process with both images and age. The subject-specific image is conditioned using a skip-connection by concatenating with the denoising images. An independent encoder is used for the denoising image and conditioning image in the reverse process. The subject's age is added to the information bottleneck using attention mechanism. Then age information is summed up with the image feature via the embedding layer.

2.2. Refine stage: Conditional 3D super-resolution

After getting the low-resolution generated image $P_c(z_0|X_{mo})$, we further refine high-resolution generated images using a super-resolution model to add more detailed information. Fig 1c illustrates the refined super-resolution diffusion model consisting of diffusion process and reverse process. The diffusion process gradually adds Gaussian noise to the original high-resolution image x_0 and becomes a hidden variable x_t in the Gaussian distribution. In the reverse process, $P_c(z_0|X_{mo})$ is up-sampled by transposed convolution and used as conditions to concatenate with x_t as model inputs and reconstructed to be high-resolution image $P_f(x_0|z_0)$ via denoising block. To efficiently condition the model on the low-resolution guided image, we adopt transposed convolution blocks instead of bilinear interpolation. After training, at inference stage, the low-resolution image $P_c(z_0|X_{mo})$ is upsampled and concatenated with randomly sampled Gaussian noise to input into model to transform itself into a highresolution image. We adopt DDIM [2] with a fine-tuning 3D U-net architecture that is trained with an objective function $E[||\epsilon - \epsilon_{\theta}(x_t; t, X_{im})||^2]$ to iterative denoising at various pixel levels.

3. EXPERIMENTS AND RESULTS

3.1. Dataset and Image Processing

We used large-scale longitudinal brain imaging data from the Baby Connectome Project (BCP) [7]. 654 T1w MRI scans from 340 subjects aged 2 weeks to 26 months were kept for the following experiments. We selected 30 MRI scans as a test set and ensured that the test cases covered the entire age range (i.e., 2 weeks to 26 months). All T1w MRI scans were acquired using the 3T Siemens Prisma MRI scanner with the following parameters: TR/TE = 2400/2.24ms, resolution = $0.8 \times 0.8 \times 0.8 \text{ mm}^3$, with an image size of $256 \times 320 \times 256$.

All structural MRIs were processed using a standard procedure followed by [8], including skull stripping, rigid alignment to the brain atlas, and segmentation. For data augmentation, the multimodal guidance images were rotated randomly along the x, y, and z axis with a randomly selected rotation degree between 0 and 5 degrees. This augmentation was only applied to guidance images to improve the robustness of the generation model. Considering the computational cost, the input data of the first stage generation model were down-sampled to the resolution of $2 \times 2 \times 2 \ mm^3$ and cropped into the size of $80 \times 96 \times 80$. During the second refine stage, the training data model was re-sampled to the resolution of $1 \times 1 \times 1 \ mm^3$ and resized to $160 \times 192 \times 160$.

3.2. Implementation Details

Our model was implemented using PyTorch. Network was constructed based on DDIM [2] with the noise level set from 1e-4 to 5e-3 by linearly scheduling with 4000 steps in the generation model, and 1e-4 to 2e-2 with 1000 steps for the super-resolution stage. Adam optimization was used with a learning rate of 2e-4. The generation model was trained on two Nvidia A100 GPUs with 80 GB memory each for 5 days. The super-resolution model was trained on four Nvidia A100 GPUs for 5 days.

3.3. Results

After Cas-DiffCom was trained, the model could use guidance images and age information to generate all the MRIs for the subject at missing time points. The final results of the generated images are shown in Fig 2. Segmentation is completed by the image analysis tool, uAI Research Portal [9] [10] [11]. It can be seen that the details were well preserved in the generated images by our method. The volume of the brain is increasing, and the contrast between white and grey matter in the brain has significantly improved from 3 to 9 months.

We evaluate the visual quality and similarity between the real and generated images qualitatively with two widely used metrics: peak signal-to-noise ratio (PSNR) and structural similarity index measure (SSIM). First, we chose conditional GAN as the baseline. The results illustrated that the GAN model faced difficulty on infant longitudinal brain image completion. In addition, we compared the results generated by different conditional diffusion-based networks to validate the effectiveness of the AsMM module. Model 1 is a conditional DDIM without an independent guidance image encoder. Model 2 is a conditional DDIM with the AsMM block. Table 1 shows the results of the comparison between the four models. The PSNR and SSIM of our proposed Cas-DiffCom are 24.15 and 0.81, respectively, which illustrate that our method performs better than all other compared models.



Fig. 2: Showcase of the generated longitudinal infant brain images by our proposed Cas-DiffCom from the same subject. The top row displays the generated T1w MRI scans. The bottom row shows the corresponding brain segmentation results. The age time points are 3, 6, 9, 12, 20, and 26 months old. The image on the right at 24 months old is the real image from the same subject.



Fig. 3: Comparison of brain tissue growth characterization between the generated data (red) and the ground truth (grey). The ground truth total volumes of the grey matter, white matter and cerebrospinal fluid fitted very well with the development trajectories estimated from the generated images.

	cGAN	Model 1	Model 2	Our Method
PSNR	17.76	22.33	23.22	24.15
SSIM	0.72	0.73	0.78	0.81

Table 1: Our method using an asynchronous block with an independent guided image encoder has the best SSIM of 0.81 and PSNR of 24.15.

data and generated data. The results show that the generated data closely approximates the real distribution, and the calculated trajectory from the completed data exhibits a similar trend to the real data.

4. CONCLUSION

To better evaluate our proposed model, we also validated its ability to complete missing data from the neuroscience perspective. Specifically, the development trajectories characterizing longitudinal growth of infant brain tissue volume were fitted with the completion data using the linear mixed-effect model with the log-linear function. In Figure 3, the volume of brain white matter, grey matter and cerebrospinal fluid from the real data was shown with a grey scatter plot, while the generated data was shown with a pink scatter, with the fitted trajectories calculated from the complete data, including real

In this work, we present a novel cascaded diffusion model (Cas-DiffCom) with multimodal guidance for longitudinal infant brain image completion. We propose an asynchronous multimodal block for multimodal guidance disentanglement. Our refinement approach for 3D brain image super-resolution further improves the image realism and sharpness of the generated images. Our approach provides a promising solution to employ the generated missing data for downstream neuroscience tasks with high fidelity and implications.

5. REFERENCES

- John H Gilmore, Rebecca C Knickmeyer, and Wei Gao, "Imaging structural and functional brain development in early childhood," *Nature Reviews Neuroscience*, vol. 19, no. 3, pp. 123–137, 2018.
- [2] Jiaming Song, Chenlin Meng, and Stefano Ermon, "Denoising diffusion implicit models," arXiv preprint arXiv:2010.02502, 2020. 1, 3
- [3] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer, "High-resolution image synthesis with latent diffusion models," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 10684–10695. 1
- [4] Xiangxi Meng, Yuning Gu, Yongsheng Pan, Nizhuan Wang, Peng Xue, Mengkang Lu, Xuming He, Yiqiang Zhan, and Dinggang Shen, "A novel unified conditional score-based generative framework for multimodal medical image completion," *arXiv preprint arXiv:2207.03430*, 2022. 1
- [5] Ludan Ruan, Yiyang Ma, Huan Yang, Huiguo He, Bei Liu, Jianlong Fu, Nicholas Jing Yuan, Qin Jin, and Baining Guo, "Mm-diffusion: Learning multi-modal diffusion models for joint audio and video generation," *arXiv preprint arXiv:2212.09478*, 2022. 1
- [6] Jonathan Ho, Chitwan Saharia, William Chan, David J Fleet, Mohammad Norouzi, and Tim Salimans, "Cascaded diffusion models for high fidelity image generation.," *J. Mach. Learn. Res.*, vol. 23, no. 47, pp. 1–33, 2022. 2
- [7] Brittany R Howell, Martin A Styner, Wei Gao, Pew-Thian Yap, Li Wang, Kristine Baluyot, Essa Yacoub, Geng Chen, Taylor Potts, Andrew Salzwedel, et al., "The unc/umn baby connectome project (bcp): An overview of the study design and protocol development," *NeuroImage*, vol. 185, pp. 891–905, 2019. 3
- [8] Gang Li, Jingxin Nie, Li Wang, Feng Shi, Weili Lin, John H Gilmore, and Dinggang Shen, "Mapping regionspecific longitudinal cortical surface expansion from birth to 2 years of age," *Cerebral cortex*, vol. 23, no. 11, pp. 2724–2733, 2013. 3
- [9] Feng Shi, Weigang Hu, Jiaojiao Wu, Miaofei Han, Jiazhou Wang, Wei Zhang, Qing Zhou, Jingjie Zhou, Ying Wei, Ying Shao, et al., "Deep learning empowered volume delineation of whole-body organs-at-risk for accelerated radiotherapy," *Nature Communications*, vol. 13, no. 1, pp. 6566, 2022. 3

- [10] Yongqin Zhang, Feng Shi, Jian Cheng, Li Wang, Pew-Thian Yap, and Dinggang Shen, "Longitudinally guided super-resolution of neonatal brain magnetic resonance images," *IEEE transactions on cybernetics*, vol. 49, no. 2, pp. 662–674, 2018. 3
- [11] Feng Shi, Yong Fan, Songyuan Tang, John H Gilmore, Weili Lin, and Dinggang Shen, "Neonatal brain image segmentation in longitudinal mri studies," *Neuroimage*, vol. 49, no. 1, pp. 391–400, 2010. 3