

Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2017.Doi Number

MetaStates: An Approach for Representing Human Workers Psychophysiological States in the Industrial Metaverse

AITOR TOICHOA EYAM1, JOSE L. MARTÍNEZ LASTRA1, Member, IEEE

¹ FAST-Laboratory, Faculty of Engineering and Natural Sciences, Tampere University, 3320 Tampere, Finland

Corresponding author: Aitor Toichoa Eyam (e-mail: aitor.toichoaeyam@tuni.fi).

This research was supported by AI Powered human-centred Robot Interactions for Smart Manufacturing (AI-PRISM) project. The AI-PRISM project has received funding from the European Union's Horizon Europe research and innovation program under grant agreement No. 101058589.

ABSTRACT Photo-realistic avatar is a modern term referring to the digital asset that represents a human in computer graphic advance systems such as video games and simulation tools. These avatars utilize the advances in graphic technologies on both software and hardware aspects. While photo-realistic avatars are increasingly used in industrial simulations, representing human factors such as human workers' internal states, remains a challenge. This article addresses this issue by introducing the concept of MetaStates which are the digitization and representation of the psychophysiological states of a human worker in the digital world. The MetaStates influence the physical representation and performance of a digital human worker while performing a task. To demonstrate this concept the study presents a development of a photo-realistic avatar which is integrated into a simulated environment and enhanced with a multi-level graphical representation of different psychophysiological states. This approach represents a major step forward in the use of digital humans for industrial simulations, allowing companies to better leverage the benefits of the Industrial Metaverse in their daily operations and simulations while keeping human workers at the center of the system.

INDEX TERMS Avatars, digital humans, emotions, human factors, industrial applications, industrial metaverse, industry 5.0, metaverse, psychophysiological states, simulations.

I. INTRODUCTION

Industry 4.0 combines technologies such as Industrial Cyber-Physical Systems (CPS), and the Industrial Internet of Things (IIoT) to improve the efficiency and productivity of the manufacture industry by combining physical and digital worlds [1]. Employing this context as foundation, Industry 5.0 complements Industry 4.0 by enhancing the focus on developing more human-centric and sustainable solutions [2].

Among a broad spectrum of technologies that have experienced a huge advance during last twenty years, simulations play a crucial role in the development of applications in Industry 5.0. Simulations allow the development of digital twins, which are digital replicas of physical systems. By utilizing digital twins, it is possible to apply real-time monitoring, run better analysis, and optimize processes, being able to enhance sustainability of the processes [3]. At the same time, simulations enable the possibility of tailoring processes to the human needs and

provide safe spaces for workers to upskill and reskill their abilities [4].

The physical-digital dyad that enables the integration of both realms finds its conception in the Metaverse. Introduced by Neal Stephenson in his book Snow Crash, the Metaverse represents a virtual interconnected space where physical and digital entities merge interacting between each other and exchanging information [5]. Even though the creation of the Metaverse still in its early stages, companies such as Nokia or Microsoft, have already seen three potential subdivisions [6], [7]. A Consumer Metaverse (CM) focused on socially immersive experiences based on entertainment and leisure. An Enterprise (or Commercial) Metaverse (EC) which intends to apply immersive technologies into the business environment to design products, improve communications and collaboration. And finally, the Industrial Metaverse (IM) which aligns its goals with Industry 5.0 aiming to blend physical and digital realities and make humans and artificial



intelligence (AI) collaborate to improve productivity, safety, and sustainability.

While physical systems such as machines or robots are being integrated into IM applications, it is also essential to introduce human workers in simulations. Although several industrial applications contemplate human workers in their simulations, they mainly considering their physical appearance and range of motion. These simulations rarely consider key aspects that shapes human behavior and performance such as their psychophysiological states [8]. This study proposes an approach to contemplate and represent psychophysiological states complementing the photo-realistic representation of a human worker in the digital world.

II. PREVIOUS WORK AND STATE OF THE ART

Introducing realistic representations of human operators in the Metaverse requires research on the concepts and methods in the domain. Such groundwork is presented as follows: subsection A focuses on the Metaverse and its future in industrial applications, subsection B. shows the current applications of avatars in the industry, and subsection C presents the current state of representing human states in digital applications.

A. INDUSTRIAL METAVERSE: THE FUTURE OF INDUSTRIAL APPLICATIONS

The IM rises as a subsection of the Metaverse which focuses industrial applications such as manufacturing, constructions, or logistics [7], [9]. The IM aims to make humans and AI entities work together to design, build, operate, and optimize physical systems using digital technologies [9], [10]. To achieve these goals different technologies are combined, including the internet of things (IoT), big data, digital twins, extended reality (XR), and AI models [11], [12]. The development of an IM that facilitates human-AI interactions allows the AI models to learn from the human, and the human to learn from the AI models [7]. As far as simulations are concerned, they play a major role in the IM by enabling the integration of data from multiple sources with a common goal. In the IM, is possible to improve aspects such as production efficiency or sustainability footprints by adjusting simulation variables of the industrial process [9]. Apart from production simulations, other key features of the IM include remote monitoring, real-time data visualization, or training and maintenance in simulated environments [13], [14]. The IM is evolving and being applied to several fields such as smart factories or supply chain. As regards to smart factories, XR interfaces are used to assist human workers to visualize production processes, provide them guidance, or training them in realistic virtual environments [14]. In the case of supply chain, the IM enhances its optimization through digital twins, real-time tracking, and predictive analytics [13]. One of the emerging platforms that allows the integration of technologies to develop IM applications is the NVIDIA

Omniverse [15]. Employed by several companies such as BMW or Siemens [16], [17], NVDIA Omniverse facilitates the development of 3D workflows and applications. Overall, companies such as, Amazon, Mercedes-Benz, Nokia, Boeing, Volkswagen Group supports the relevance of employing IM solutions in their systems for improving their results on the fields of factory simulation, mobile networks, training, construction planning, and project management [6], [18], [19], [20].

B. AVATARS: DIGITAL HUMANS IN INDUSTRIAL SIMULATION ENVIRONMENTS

One of the most critical aspects of simulated environments is providing an optimal immersion. A particular aspect for achieving the sense of immersion is the realism that the simulation provides [21]. Consequently, to improve the subjective experience of humans in simulated environments, it is relevant to have realistic digital humans, or avatars, in them [22]. An avatar is the representation of the self in a digital world [5], [23]. As avatars, the users can interact with digital entities and explore the digital world in which they are immersed. Depending on the characteristics and target of the digital world, the appearance and features of the avatars may vary. In the gaming industry, avatars may differ completely from the self, even with the possibility of having a non-human avatar [24]. On one hand, in social platforms, users might select avatars that reflect their personal interests, creativity, or desired persona, which can extend beyond human representation [25]. On the other hand, when talking about the IM, it becomes relevant having a more realistic representation of oneself in the digital world to enhance the user-avatar relationship [26]. The rise of the gaming industry, social platforms, and other simulation environments has incentivized the development of platforms to generate photo-realistic characters. Among these applications are Autodesk Maya [27], Blender [28], Unreal Engine's (UE) MetaHuman tool [29], [30], Reallusion's Character Creator [31], and DazStudio [32]. The use of photo-realistic avatars in digital worlds enhances the user experience by evoking deeper immersion levels and facilitating the connection with the application [33]. Commonly, industrial simulations have focused on the characteristics of the machinery, robots, or production allocation factors [34]. These elements are represented in a realistic way, respecting their dimensions, colors, and other visual features. Also, industrial simulations enable the user to view and update internal features of machinery elements, such as speed, range of motions, and production time. In this type of applications, digital humans tend to be introduced for visualization or design purposes, focusing on their external appearance, range of motion, or ergonomics, putting little attention towards the internal states and traits of the human workers [8]. With regards to the appearance of avatars, companies such as Meta, and Apple are investing resources on generating photo-realistic digital humans of users to provide a deeper sense of realism and immersion in Metaverse



applications [35], [36]. Even though the advances in digital human appearance have significantly improved over the years, eluding falling into the Uncanny Valley [37], few progress has been achieved in representing human internal and physical states in the IM.

C. HUMAN STATES IN DIGITAL APPLICATIONS

As introduced in the previous section, human beings are mainly represented in digital applications by their physical capacities [8]. Depending on the application, digital humans could have other qualities that allow them to interact and exchange information with the digital environment in metaverse different manners. As an example, in the gaming industry, avatars have a set of attributes which represent their statistics, states, or capabilities. For example, in role-playing games (RPGs), a character could have physical attributes such as strength, stamina, or speed, and mental attributes such as intelligence, wisdom, or charisma [38], [39]. These attributes enable the option of generating avatars with similar appearance but with different capacities. A great example of how attributes or states can influence how an avatar interacts with the surrounding digital world is depicted in The Sims videogame [40], [41]. The Sims presents a "real-life" simulation in which the digital humans have multiple physical and mental needs that influence their actions and behavior. Depending on the level of those physical and mental states that the character is experiencing, they will build skills faster or slower, or their interactions with other characters might be more successful. In videogames such as The Sims 4 the representation of physical and mental states has been performed employing color patterns and displaying information in the user interface (UI). For example, emotional states such as happy, sad, angry, or tense, were represented by displaying the colors green, dark blue, red, and peach, respectively, in the UI [42], [43]. Another example of representing human physical and mental states in the digital environments was presented in the work undertaken in [44]. The authors in [44] proposed an approach for representing emotional states in avatars by growing or contracting their fur or by adjusting the brightness of a particle system. Similarly, the authors in [45] represented in avatars physiological signals related to emotional and cognitive states with skeuomorphic, particles, creature, and environmental visualizations. Even though the abovementioned examples are focused on the gaming industry, more research should be performed in the field of representing emotions and cognitive states in the digital world. The findings of this research should also be applied into the IM as it can influence positively virtual trainings, simulation algorithms, or real-time monitoring.

III. METAHUMANS & METASTATES: HUMAN WORKERS INSIDE THE INDUSTRIAL METAVERSE

The aim of this research is to represent the psychophysiological state of human workers in the IM. To achieve an optimal representation of a human worker in the

digital world, it is crucial to define which main aspects are needed to represent a human worker in the workplace. This research work stands out as main characteristics for a digital representation a human worker: physical appearance, psychophysiological states, and task-oriented skills. The following subsections discuss how to meaningfully represent human workers' physical appearance and psychophysiological states in the context of the IM.

A. METAHUMAN

The aim of this study is to enhance the representation of a human worker in simulations by including psychophysiological states. Consequently, this research presents the concept of MetaHuman as digital representation of a human worker in the IM. A MetaHuman is the avatar of a human worker, therefore it provides a photo-realistic representation of the person it portrays. The photorealism includes their main physical features (facial, skin, body proportions), as it is crucial that visually the operators can be recognized as themselves. Furthermore, a MetaHuman goes beyond the visual representation, including internal traits of the person it represents, such as their emotions and cognitive states. As the context of this approach is inside the IM, the psychophysiological characteristics of a MetaHuman are mainly targeting the response of the human worker while performing specific tasks. By combining external and internal aspects of a human worker, a MetaHuman transforms the role a digital operator from an illustrative entity to another variable to be considered when running simulations of industrial process. As a result, three main goals are achieved, increasing the user experience, the realism of the simulation, and the possibility of having better algorithms which introduce psychophysiological factors.

B. METASTATES

The psychophysiological states are internal processes which may influence how human workers perform operations and tasks [46]. To perceive how a human worker might be feeling while performing a task in a simulation, it is important to generate a method of illustrating those internal states. Similar to the concept of MetaHuman for referring to the digital representation of a human worker, this study introduces the concept of MetaStates. The word MetaStates comes from the union of two words, meta and states. Meta, a Greek prefix meaning "beyond", is used to indicate an abstraction of a concept and to complete it. States, on the other hand, refers to the multiple ways of being of a person that can result in physical, emotional, cognitive, and other conditions. Thus, this work defines the MetaStates as the representation of the psychophysiological states of a human worker in the digital world.

Taking into consideration the context of manufacture in Industry 5.0, some of the most relevant human factors to consider are *stress*, *attention*, *cognitive workload*, and *physical fatigue* [46]. Thus, these states find their depiction



and computation in a simulation environment as MetaStates. A human has psychophysiological states and a MetaHuman has MetaStates. The MetaStates quantify and represent the psychophysiological states that a human operator experience while performing a task. This allows to understand the status of an operator while performing a task in a simulation environment.

The concept of MetaStates introduce a new layer of communication, allowing the expression of inner sensations, and enabling the possibility of making adaptations to the process, tasks or performed operations to improve workers' state. A MetaState can be depicted in multiple levels of detail. These levels of detail take into consideration the characteristics of a MetaHuman and what their role in a simulation is. Inside a simulation environment, a MetaHuman performs the same activities that the analog human worker would perform in the real world. Therefore, majority of the activities concerning MetaHumans are movements and actions. Thus, MetaStates are heavily influencing a MetaHuman's appearance, mobility, and performance. As it happens with humans, each person expresses differently an internal state. On one hand, some individuals experiencing physical fatigue might have an exhausted look, or even require more time for making certain operations. On the other hand, there might be some individuals who might not express fatigue in their look but with their body language and have a difference influence on their task performance. To express the variations in the manners of expressing internal states, in a simulation environment this leads to the need of developing a MetaState Reaction Model (MRM) for each MetaHuman. The MRM is based on the reactions of each human worker to the different psychophysiological states experienced during the task performance. At the start of the definition of a MetaHuman, a basic MRM is associated to it. Following, the more data is feed into the system, and more information is known about the worker the MRM becomes more complete having a MetaHuman more accurate to the real person.

As mentioned earlier, the MetaStates aim to recreate the internal states of a human worker while performing a task, influencing on the mobility, and appearance of the MetaHuman. Considering that the aim of these applications is to enhance user experience, improve real-time feedback, and perform better simulations, it should be generated a visual clue for the workers running the simulation, or users experiencing the digital world in XR, which indicates the overall status of the MetaHuman. In this work, this status is presented as the MetaState Performance Index (MPI). The MPI represents the overall status of the MetaHuman to perform a particular task, taking into consideration all the different MetaStates and task status. Inside the simulation environment, the MPI is represented by two main aspects, the MetaState aura, a circle generated in the base of the MetaHuman, and the MestaState sphere, a sphere located in the top of a MetaHuman's head. The idea behind using two elements to represent the MPI is improving the visual perception. This is because in a 3D

simulation depending on the perspective, one of the elements can be hidden behind a third object (e.g., working table, robot, cell). With two ways of visualizing the MPI it is improved the feedback to understand the status of the human worker.

The MPI provide extensive information of the overall condition of the MetaStates in a simplified way. With respect to providing visual information to the worker running the simulation, the MPI updates its color as indicated in TABLE 1. MetaState Performance Index color description...

TABLE 1. MetaState Performance Index color description.

Color	Description		
Green	The human worker is in an optimal status to perform the task		
	up to their skill level. At this status the worker is usually		
	performing correctly or is exceeding performance.		
Amber	The status of the human worker is a thread for performing the		
	task up to their skill level. At this status the person overall		
	performance decreases from their optimal.		
Red	The human worker is experiencing a suboptimal status to		
	perform the task up to their skill level. Under this situation the		
	worker is not in a good condition, thus it might need a break.		

Depending on the human worker, the values of the MetaStates and their corresponding thresholds would be different. Therefore, to normalize the values of each worker, three different ranges have been defined high, mid, and low. As it can be seen in TABLE 2, for MetaStates such as stress, cognitive workload, or physical fatigue, a lower value in these metrics relates with a better internal state of the human. Whereas, for the same MetaStates, higher values are related to a suboptimal internal condition. On the other hand, MetaStates such as attention, follows an inverse relationship. In this case, a higher value of attention corresponds to a more optimal state. But a lower attention value relates with suboptimal performance conditions. For this research, it has been considered that if all the MetaStates are in an optimal range, the MPI color should be green; in case that one or more MetaStates are threading the performance, the MPI color should be amber; lastly if at least one MetaState is in a suboptimal range the MPI color will be red.

TABLE 2. MetaStates range levels.

MetaState	Optimal	Thread	Suboptimal
Stress	Low	Mid	High
Attention	High	Mid	Low
Cognitive Workload	Low	Mid	High
Physical Fatigue	Low	Mid	High

In addition, apart from providing information about the performance, the MPI serves as an indicator in Metaverse applications to differentiate between a MetaHuman and a digital avatar not based on a real person, or with non-playable characters (NPCs).

To finalize this section, FIGURE 1 illustrates how the concepts of MetaHuman and MetaStates enhance the current



state of the art of digital humans on industrial applications. The schema presents the concept of MetaHuman being composed of two main aspects, a photo-realistic digital human (grey), and their MetaStates (purple). The current state of the art is mainly focused on the creation of a photo-realistic digital human, whereas this study provides a new realm, the MetaStates. The MetaStates provide information about the psychophysiological states of a human worker. Visual feedback about these states is given with the MPI and also influencing the animations of the digital human with the MRM.




FIGURE 1. MetaStates influence in the state of the art.

IV. IMPLEMENTATION

The previous section introduced the concept of MetaHuman as the digital depiction of a human worker, and its MetaStates, which representations of their psychophysiological states. This section exposes an approach for generating the main necessary inputs for creating a MetaHuman. As proposed in the previous section, a MetaHuman is composed out of two main aspects, a photo-realistic representation of a digital human, and the MetaStates of the digital human. In FIGURE 1 it is presented a schema of the core elements that compose the concept of MetaHuman in this research work.

A MetaHuman is composed out of a photo-realistic digital human and MetaStates. On the one hand, the photo-realistic digital human is nourished with facial and body animations to make the external representation of the human worker precise. On the other hand, the MetaStates are represented with the MPI and the MRM. Starting with the MPI, it takes into consideration all the MetaStates to determine if the worker is in an optimal condition to perform the task. To show that, the MPI updates the colours of the MetaState aura and sphere are attached to the MetaHuman. Next, the MRM serves as a bridge between the MetaStates metrics and the animations that should be triggered to represent them.

Taking the schema presented in FIGURE 1 into consideration, the first input to develop a MetaHuman is generating a photorealistic digital human. Several platforms and software can be used to generate the appearance of a MetaHuman. Some these

platforms were mentioned in Section II such as, Reallusion Character Creator [31], or UE's MetaHuman tool [29]. This research work utilises UE's MetaHuman Animator and Creator for the generation of digital human workers. UE's MetaHuman Animator allows the generation of photo-realistic digital humans from a digital mesh of a human's face, or a face recording coming from a depth camera (head-mounted, or iPhone 12 or newer). The first approach employed in this research to create the digital human was developing a face mesh composed of multiple pictures. Pictures of the human worker were taken from different angles, after that they were combined into a generic head mesh using Blender. Even though the results of the facial mesh were considered uncanny, (FIGURE 2) the mesh was utilised to generate the digital human with UE MetaHuman tool (FIGURE 2b). As the mesh generated in the first iteration had some irregularities, a second approach for generating the digital human was done. In this case, instead of creating the mesh as a compilation of individual pictures, it was conceived by using a 3D scan of the human worker (FIGURE 2). As the mesh contained certain irregularities which could influence the final rendering of the avatar, certain parts of the mesh were smoothed using *Blender*. Once the mesh was ready, it was introduced into UE's MetaHuman to generate the digital human. The comparison between 3D scan mesh and the digital human conceived with it are shown in FIGURE 2 and FIGURE 2 respectively.










FIGURE 2. a) Mesh generated with pictures; b) Digital human from pictures' mesh; c) Mesh generated with 3D scan; d) Digital human from 3D mesh.

Finally, the last approach was performed using a depth camera from an *iPhone 12 Pro Max* to capture the facial expression of the human worker. Four main frames of his face were captured; frontal, right, and left frames with a relaxed neutral



expression, and a frontal frame showing the teeth to register the bite (FIGURE 3).




FIGURE 3. a) Frontal frame. b) Right frame. c) Left frame. d) Teeth frame.

Once the frames were extracted, and the features' trackers adjusted it was generated the first version of the digital human FIGURE 4.



FIGURE 4. Human worker vs Digital worker mesh

In order to make adjustments to the mesh for a better resemblance in the features, skin tone, eye colours, hair, body type and other characteristics, the mesh was modified using *UE's MetaHuman Creator*. The result of the digital human can be seen in FIGURE 5, where it can be appreciated a greater resemblance to the human worker in this approach in comparison to the digital humans created in the previous iterations.





FIGURE 5. Human Worker vs Digital Human worker: a) Human Worker, b) Digital Human Worker.

Once the facial features of the digital human are generated, there should be also created animations that complement the external appearance. For this input, it was also employed UE's MetaHuman Animator. In this work, the animations generated were focused on the facial expression of the human worker. Similar to the creation of the digital human's mesh, the human worker was recorded performing the target facial expressions. As it was necessary a depth sensor camara, the recording was also done with an iPhone 12 Pro Max. Once the footage of the performance was defined, it was processed and mapped to the digital human mesh created in the previous step. The results of the processed animation can be seen in FIGURE 6. Regarding body animations, for this research it has been only integrated three main animations, idle, walking, and physical fatigue. Other animations targeting working posture, and multiple MetaStates will be integrated in future research.





FIGURE 6. Stress performance vs Stress animation.

After finishing the creation of the photo-realistic digital human and its animations, the next step for creating a MetaHuman is integrating the representation of the MetaStates. To achieve this goal, it was developed a scene on UE staging a workstation composed by a MetaHuman, a cobot, and the product. To develop the MPI, two dynamic elements were created, the MetaState aura, and sphere, which accompany the MetaHuman in all its actions. As indicated in the previous section, both elements, aura, and sphere, update their colour in relation to the values of the MetaStates that the MetaHuman is experiencing. The representation of the abovementioned elements is shown in FIGURE 7.










FIGURE 7. MetaState Performance Index: a) Green, b) Amber, c) Red.

With the purpose of showing the metrics of the MetaStates in real-time it was developed a UI shown in FIGURE 8. This UI

includes the metrics of *stress, attention, cognitive workload,* and *physical fatigue*. As the aim of this development is focused on the representation of the MetaStates, the values shown in the UI could be increased and decreased at ease by giving inputs to the simulation. This way it is possible to trigger directly certain reactions from the MetaHuman.

MetaStates See Detail				
Name: Aitor MetaState	Metric			
` Stress	33%			
Attention	85%			
⊚ Cog. Workload	62%			
7 ⁵ Fatigue	41%			


FIGURE 8. MetaState User Interface

For this paper, the threshold values for the different MetaStates have been extracted from the psychophysiological signals measured in the experiment conducted in [47]. Regarding *stress* and *attention*, this MetaStates take the value ranges from *stress* and *focus* of the mentioned experiment. On the other hand, *cognitive workload* and *physical fatigue* have been estimated employing *cognitive workload* and *stress* metrics.

Finally, the MRM serves as a bridge between the MetaStates values, and the animations performed by the MetaHuman. In this scenario, two MetaStates were selected to trigger animations when they arrive to a certain value. The selected MetaStates are *stress*, which triggers a facial animation, and physical fatigue that triggers a body animation. On one hand, the facial animation is triggered when stress values are a thread for the task performance FIGURE 9. In this case the MetaHuman recreates the facial expression of the human worker when he experiences a stressful situation. On the other hand, the body posture animation is activated when physical fatigue is suboptimal for performing the task FIGURE 9. In this animation the MetaHuman has a less upright posture than in the idle position, showing signs of fatigue. Following, FIGURE 9 presents a scenario in which multiple MetaStates are triggering reactions, in this case the stress level is a thread and physical fatigue is suboptimal for fulfilling the task.







b)






FIGURE 9. MetaState Reaction Model: a) idle, b) stress, c) physical fatigue, d) stress and physical fatigue

V. CONCLUSIONS AND FURTHER RESEARCH

Creating simulations is a complex process which relies heavily in the accuracy of the introduced data. IM applications should take into consideration the premises of *Industry 5.0*, developing sustainable and human-centric solutions. To achieve this goal, it is crucial to properly introduce humans into the simulations considering how they can influence the process and how the process can affect them. This consideration will increase realism of the simulations, their algorithms, and thus improving the outputs.

With the idea of generating human-centric IM applications, this study aims to provide a new approach for representing psychophysiological states of human workers in the IM. To achieve this goal two concepts were presented, MetaHuman, and MetaStates. A MetaHuman was defined as the representation of a human worker in the IM, including a photorealistic digital human and their MetaStates. Being the MetaStates the digital representation of psychophysiological states of the human worker. The definition of these two concepts introduces a novelty in the field of industrial simulations expanding the state of the art, which was mainly focused on developing photo-realistic representations of persons, with few research done in how to include psychophysiological states in digital humans.

Even though the implementation of this study has been limited to exemplify how to represent MetaStates by employing the MPI, and animations triggered by the MRM, it serves as a foundation for further research on this topic. This research work opens a new era of IM applications which will be able to apply the concepts from this study to contemplate psychophysiological signal in their simulations. Consequently, future studies should focus on gathering human workers data regarding their psychophysiological states to improve the ranges and algorithms of the MPI. Additionally, more research should be done to capture human workers expressions and body language to generate better animations correlated with the MRM.

In conclusion, introducing MetaStates into IM applications can lead towards more realistic simulations. These simulations can generate more sustainable and human-centric solutions by assessing how a situation can influence positively or negatively the wellbeing and performance of a human worker.

REFERENCES

- [1] B. R. Ferrer, W. M. Mohammed, E. Chen, and J. L. M. Lastra, 'Connecting web-based IoT devices to a cloud-based manufacturing platform', in *IECON 2017 - 43rd Annual Conference of the IEEE Industrial Electronics Society*, Oct. 2017, pp. 8628–8633. doi: 10.1109/IECON.2017.8217516.
- [2] 'Industry 5.0 European Commission'. Accessed: Feb. 18, 2024.
 [Online]. Available: https://research-and-innovation.ec.europa.eu/research-area/industrial-research-and-innovation/industry-50_en
- [3] A. Lago Alvarez, W. M. Mohammed, T. Vu, S. Ahmadi, and J. L. Martinez Lastra, 'Enhancing Digital Twins of Semi-Automatic Production Lines by Digitizing Operator Skills', *Appl. Sci.*, vol. 13, no. 3, Art. no. 3, Jan. 2023, doi: 10.3390/app13031637.
- [4] L. A. Hormaza, W. M. Mohammed, B. R. Ferrer, R. Bejarano, and J. L. Martinez Lastra, 'On-line Training and Monitoring of Robot



- Tasks through Virtual Reality', in 2019 IEEE 17th International Conference on Industrial Informatics (INDIN), Jul. 2019, pp. 841–846. doi: 10.1109/INDIN41052.2019.8971967.
- N. Stephenson, Snow Crash. 2022. Accessed: Feb. 14, 2024.
 [Online]. Available: https://www.penguin.co.uk/books/20868/snow-crash-by-stephenson-neal/9780241629833
- [6] 'Powering the industrial metaverse | Nokia'. Accessed: Feb. 14, 2024. [Online]. Available: https://www.nokia.com/metaverse/industrial-metaverse/
- [7] J. King, 'Microsoft Touts Industrial Metaverse as Innovation, Sustainability Tool', SDxCentral. Accessed: Feb. 13, 2024. [Online]. Available: https://www.sdxcentral.com/articles/news/microsoft-touts-industrial-metaverse-as-innovation-sustainability-tool/2022/10/
- [8] W. Zhu, X. Fan, and Y. Zhang, 'Applications and research trends of digital human models in the manufacturing industry', Virtual Real. Intell. Hardw., vol. 1, no. 6, pp. 558–579, Dec. 2019, doi: 10.1016/j.vrih.2019.09.005.
- [9] N. Kshetri, 'The Economics of the Industrial Metaverse', *IT Prof.*, vol. 25, no. 1, pp. 84–88, Jan. 2023, doi: 10.1109/MITP.2023.3236494.
- [10] 'What is the Industrial Metaverse and why should I care?', siemens.com Global Website. Accessed: Feb. 13, 2024. [Online]. Available: https://www.siemens.com/global/en/company/digital-transformation/industrial-metaverse/what-is-the-industrial-metaverse-and-why-should-i-care.html
- [11] X. Yao, N. Ma, J. Zhang, K. Wang, E. Yang, and M. Faccio, 'Enhancing wisdom manufacturing as industrial metaverse for industry and society 5.0', *J. Intell. Manuf.*, vol. 35, no. 1, pp. 235– 255, Jan. 2024, doi: 10.1007/s10845-022-02027-7.
- [12] S.-M. Park and Y.-G. Kim, 'A Metaverse: Taxonomy, Components, Applications, and Open Challenges', *IEEE Access*, vol. 10, pp. 4209–4251, 2022, doi: 10.1109/ACCESS.2021.3140175.
- [13] S. K. Jagatheesaperumal and M. Rahouti, 'Building Digital Twins of Cyber Physical Systems With Metaverse for Industry 5.0 and Beyond', IT Prof., vol. 24, no. 6, pp. 34–40, Nov. 2022, doi: 10.1109/MITP.2022.3225064.
- [14] M. Bordegoni and F. Ferrise, 'Exploring the Intersection of Metaverse, Digital Twins, and Artificial Intelligence in Training and Maintenance', J. Comput. Inf. Sci. Eng., vol. 23, no. 060806, May 2023, doi: 10.1115/1.4062455.
- [15] 'NVIDIA Omniverse', NVIDIA. Accessed: Feb. 14, 2024. [Online]. Available: https://www.nvidia.com/en-us/omniverse/
- [16] 'NVIDIA and BMW Partnership', NVIDIA. Accessed: Feb. 14, 2024. [Online]. Available: https://www.nvidia.com/enus/industries/automotive/partners/
- [17] 'Siemens and NVIDIA to enable industrial metaverse'. Accessed: Feb. 13, 2024. [Online]. Available: https://press.siemens.com/global/en/pressrelease/siemens-and-nvidia-partner-enable-industrial-metaverse
- [18] 'Amazon Robotics Builds Digital Twins of Warehouses with NVIDIA Omniverse and Isaac Sim', NVIDIA. Accessed: Feb. 14, 2024. [Online]. Available: https://resources.nvidia.com/en-usomniverse-enterprise/amazon-robotics
- [19] 'NVIDIA & Mercedes Benz Automotive Partner', NVIDIA. Accessed: Feb. 14, 2024. [Online]. Available: https://www.nvidia.com/en-us/self-driving-cars/partners/mercedes/
- [20] 'How the industrial metaverse will transform manufacturing', SiliconANGLE. Accessed: Feb. 13, 2024. [Online]. Available: https://siliconangle.com/2022/12/24/industrial-metaverse-will-transform-manufacturing/
- [21] D. A. Bowman and R. P. McMahan, 'Virtual Reality: How Much Immersion Is Enough?', *Computer*, vol. 40, no. 7, pp. 36–43, Jul. 2007, doi: 10.1109/MC.2007.257.
- [22] A. Steed, Y. Pan, F. Zisch, and W. Steptoe, 'The impact of a self-avatar on cognitive load in immersive virtual reality', in 2016 IEEE Virtual Reality (VR), Mar. 2016, pp. 67–76. doi: 10.1109/VR.2016.7504689.
- [23] E. Castronova, 'Theory of the Avatar'. Rochester, NY, Feb. 01, 2003. doi: 10.2139/ssrn.385103.
- [24] S. Lakhmani and C. Bowers, 'Reflected in a Liquid Crystal Display: Personalization and the Use of Avatars in Serious Games', in Virtual and Mixed Reality - Systems and Applications, R. Shumaker, Ed., in

- Lecture Notes in Computer Science. Berlin, Heidelberg: Springer, 2011, pp. 237–242. doi: 10.1007/978-3-642-22024-1_26.
- [25] K. Szolin, D. Kuss, F. Nuyens, and M. Griffiths, 'Gaming Disorder: A systematic review exploring the user-avatar relationship in videogames', *Comput. Hum. Behav.*, vol. 128, p. 107124, Mar. 2022, doi: 10.1016/j.chb.2021.107124.
- [26] D. Y. Kim, H. K. Lee, and K. Chung, 'Avatar-mediated experience in the metaverse: The impact of avatar realism on user-avatar relationship', *J. Retail. Consum. Serv.*, vol. 73, p. 103382, Jul. 2023, doi: 10.1016/j.jretconser.2023.103382.
- [27] '3D Animation And Modeling Software | Maya | Autodesk'. Accessed: Feb. 15, 2024. [Online]. Available: https://www.autodesk.com/za/products/maya/overview-dts
- [28] B. Foundation, 'blender.org Home of the Blender project Free and Open 3D Creation Software', blender.org. Accessed: Feb. 15, 2024. [Online]. Available: https://www.blender.org/
- [29] 'MetaHuman | Realistic Person Creator', Unreal Engine. Accessed: Feb. 15, 2024. [Online]. Available: https://www.unrealengine.com/en-US/metahuman
- [30] Z. Fang, L. Cai, and G. Wang, 'MetaHuman Creator The starting point of the metaverse', in 2021 International Symposium on Computer Technology and Information Science (ISCTIS), Jun. 2021, pp. 154–157. doi: 10.1109/ISCTIS51085.2021.00040.
- [31] 'Character Creator: 3D Character Design Software', 3D Character Maker | Character Creator | Reallusion. Accessed: Feb. 15, 2024. [Online]. Available: https://www.reallusion.com/character-creator/default.html
- [32] 'Daz 3D 3D Models and 3D Software | Daz 3D'. Accessed: Feb. 15, 2024. [Online]. Available: https://www.daz3d.com/
- [33] T. Waltemate, D. Gall, D. Roth, M. Botsch, and M. E. Latoschik, 'The Impact of Avatar Personalization and Immersion on Virtual Body Ownership, Presence, and Emotional Response', *IEEE Trans.* Vis. Comput. Graph., vol. 24, no. 4, pp. 1643–1652, Apr. 2018, doi: 10.1109/TVCG.2018.2794629.
- [34] X. Li and C. Zhang, 'Some new trends of intelligent simulation optimization and scheduling in intelligent manufacturing', Serv. Oriented Comput. Appl., vol. 14, no. 3, pp. 149–151, Sep. 2020, doi: 10.1007/s11761-020-00299-6.
- [35] S. Ma et al., 'Pixel Codec Avatars', presented at the Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2021, pp. 64–73. Accessed: Feb. 13, 2024. [Online]. Available: https://openaccess.thecvf.com/content/CVPR2021/html/Ma_Pixel_C odec_Avatars_CVPR_2021_paper.html
- [36] M. Kocabas, J.-H. R. Chang, J. Gabriel, O. Tuzel, and A. Ranjan, 'HUGS: Human Gaussian Splats'. arXiv, Nov. 29, 2023. doi: 10.48550/arXiv.2311.17910.
- [37] M. Mori, K. F. MacDorman, and N. Kageki, 'The Uncanny Valley [From the Field]', *IEEE Robot. Autom. Mag.*, vol. 19, no. 2, pp. 98–100, Jun. 2012, doi: 10.1109/MRA.2012.2192811.
- [38] 'Automatic Mapping between Gameplay and Aesthetics RPG Character Attributes through Fuzzy System | IEEE Conference Publication | IEEE Xplore'. Accessed: Feb. 15, 2024. [Online]. Available: https://ieeexplore.ieee.org/document/7000051
- [39] N. R. Widiyanto, S. M. S. Nugroho, and M. H. Purnomo, 'The Calculation of Player's and Non-Player Character's Gameplay Attribute Growth in Role-Playing Game with K-NN and Naive Bayes', in 2020 International Conference on Computer Engineering, Network, and Intelligent Multimedia (CENIM), Nov. 2020, pp. 103– 110. doi: 10.1109/CENIM51130.2020.9297945.
- [40] E. Arts, 'Videojuegos de Los Sims: sitio oficial de EA', Electronic Arts Inc. Accessed: Feb. 15, 2024. [Online]. Available: https://www.ea.com/games/the-sims
- [41] D. Nutt and D. Railton, 'The Sims: Real Life as Genre', *Inf. Commun. Soc.*, vol. 6, no. 4, pp. 577–592, Dec. 2003, doi: 10.1080/1369118032000163268.
- [42] 'The Sims™ 4 Download free Electronic Arts'. Accessed: Feb. 15, 2024. [Online]. Available: https://www.ea.com/games/the-sims/the-sims-4
- [43] 'Emotion', The Sims Wiki. Accessed: Feb. 15, 2024. [Online]. Available: https://sims.fandom.com/wiki/Emotion



- [44] G. Bernal and P. Maes, 'Emotional Beasts: Visually Expressing Emotions through Avatars in VR', in *Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems*, in CHI EA '17. New York, NY, USA: Association for Computing Machinery, May 2017, pp. 2395–2402. doi: 10.1145/3027063.3053207.
- [45] A. E. Ali, S. Lee, and P. Cesar, 'Social Virtual Reality Avatar Biosignal Animations as Availability Status Indicators', arXiv, Feb. 10, 2023. Accessed: Nov. 16, 2023. [Online]. Available: http://arxiv.org/abs/2302.05172
- [46] E. Loizaga, A. T. Eyam, L. Bastida, and J. I. M. Lastra, 'A Comprehensive Study of Human Factors, Sensory Principles, and Commercial Solutions for Future Human-Centered Working Operations in Industry 5.0', *IEEE Access*, vol. 11, pp. 53806–53829, 2023, doi: 10.1109/ACCESS.2023.3280071.
- [47] A. Toichoa Eyam, W. M. Mohammed, and J. L. Martinez Lastra, 'Emotion-Driven Analysis and Control of Human-Robot Interactions in Collaborative Applications', *Sensors*, vol. 21, no. 14, Art. no. 14, Jan. 2021, doi: 10.3390/s21144626.



AITOR TOICHOA EYAM was born in Spain, in 1994. He received a B.Sc in Industrial Engineering from the Polytechnic University of Valencia, Spain in 2017. He made the M.Sc. specialisation in MS Automation Engineering at Tampere University, Finland in 2019, and received a M.Sc. in Industrial Engineering with a specialisation in Process Control, Automation and Robotics from the Polytechnic University of Valencia, Spain in 2020. Previously, he worked as an intern for the

Engineering Department of Grupo Antolin Autotrim in Spain. During 2018-2019 he worked as a Research Assistant in the FAST-Lab research group, at Tampere University. Later in 2020, he worked as a software engineer in Cappemini's ADCenter in Valencia, Spain. Then, in 2021, he worked as Researcher at the FAST-Lab research group at Tampere University Currently, he is a Doctoral Researcher at Tampere University working on the project AI-PRISM from the Horizon Europe funding program. His main research interests include Human-AI Interactions, Robotics, Emotion-Driven technology, and Factory Automation.



JOSE L. MARTÍNEZ LASTRA (Member, IEEE) received the Ingeniero Técnico Industrial degree in electrical engineering from the Universidad de Cantabria, Santander, Spain, and the M.Sc. degree (Hons.) and the Dr.Tech. degree (with Commendation) in automation engineering from the Tampere University of Technology, Tampere, Finland. He carried out research at the Departamento de Ingenieria Elctrica y Energtica, Santander, the Institute of Hydraulics and

Automation, Tampere, and the Mechatronics Research Laboratory, Massachusetts Institute of Technology, Cambridge. In 1999, he joined the Tampere University of Technology and became a Full Professor of factory automation in 2006. He has published over 250 original articles in international journals and conference proceedings. His research interest includes the applications of information and communication technologies in the field of factory automation and robotics. He is a member of the IEEE Industrial Electronics Society. He is a member of several editorial boards. He was the Deputy Chair of the IEEE/ES Technical Committee on Industrial Cyberphysical Systems from 2019 to 2022. He served as an Associate Editor for IEEE TRANSACTIONS ON INDUSTRIAL INFORMATICS in 2006 and from 2012 to 2022 and a Technical Editor for IEEE/ASME TRANSACTIONS ON MECHATRONICS from 2015 to 2016.