Reaching Consensus in Cooperative Multi-Agent Reinforcement Learning with Goal Imagination

*Liangzhou Wang,¹ *Kaiwen Zhu,¹ *Fengming Zhu,¹ Xinghu Yao,¹ Shujie Zhang,¹ Deheng Ye,¹ Haobo Fu,¹ Qiang Fu,¹ Wei Yang¹

¹ Tencent AI Lab, Shenzhen, China

{allanlzwang, kevinltzhu, fridazhu, xinghuyao, shujiezhang, dericye, haobofu, leonfu, willyang}@tencent.com

Abstract

Reaching consensus is key to multi-agent coordination. To accomplish a cooperative task, agents need to coherently select optimal joint actions to maximize the team reward. However, current cooperative multi-agent reinforcement learning (MARL) methods usually do not explicitly take consensus into consideration, which may cause miscoordination problem. In this paper, we propose a model-based consensus mechanism to explicitly coordinate multiple agents. The proposed Multi-agent Goal Imagination (MAGI) framework guides agents to reach consensus with an imagined common goal. The common goal is an achievable state with high value, which is obtained by sampling from the distribution of future states. We directly model this distribution with a self-supervised generative model, thus alleviating the "curse of dimensinality" problem induced by multi-agent multi-step policy rollout commonly used in model-based methods. We show that such efficient consensus mechanism can guide all agents cooperatively reaching valuable future states. Results on Multi-agent Particle-Environments and Google Research Football environment demonstrate the superiority of MAGI in both sample efficiency and performance.

Introduction

Cooperative multi-agent reinforcement learning has demonstrated its promising ability to deal with many complicated real-world problems, such as coordination of autonomous vehicles (Cao et al. 2012), control of multiple robots (Hüttenrauch, Šošić, and Neumann 2017), and management of network routing (Ye, Zhang, and Yang 2015). In cooperative multi-agent systems, consensus among agents is important to successful coordination (Ren, Beard, and Atkins 2005). Particularly, agents need to choose action coherently to reach the optimal joint decision. For example, in bidirectional traffic, keeping to one side (left or right) of the road when driving is an important consensus to traffic flow, and agents have to reach a consensus in terms of which side to conform to.

Early methods addressing the cooperative MARL problems consider other agents as part of environment and learn policy for each agent individually (Matignon, Laurent, and Le Fort-Piat 2012; Tampuu et al. 2017). However, as the environment dynamics becomes non-stationary, it is hard for agents to reach consensus and jointly make optimal decision (Gronauer and Diepold 2022).

Recent approaches adopt the centralized training with decentralized execution (CTDE) framework to handle the nonstationary issue, such as MADDPG (Lowe et al. 2017) and a series of value decomposition methods (Sunehag et al. 2018; Rashid et al. 2018; Son et al. 2019; Peng et al. 2021). In the training phase, the centralized structure in these CTDE methods provides an implicit consensus mechanism for agents' policy learning. However, in the execution phase, agents still make decisions independently. Hence, miscoordination may arise due to lack of consensus and sub-optimal solutions are found as a result (Gronauer and Diepold 2022).

Hierarchical reinforcement learning methods introduce a high-level policy to guide low-level policy. This architecture can be used to construct a consensus mechanism to coordinate multi-agent policies. Representative methods like feudal network (Vezhnevets et al. 2017; Ahilan and Dayan 2019) generate a hidden state goal with high-level policy, while the low-level policies of agents are supposed to reach the goal state. The high-level state goal can provide a consensus mechanism that helps multiple agents behave coherently towards the state with potential high value. However, in multi-agent environments, how to generate the goal and use it to coordinate agents to reach consensus effectively and efficiently still remains an open challenge.

To address above challenges, we propose *Multi-agent Goal Imagination (MAGI)*, a cooperative MARL framework that generates goals to achieve multi-agent consensus in an effective and efficient way.

MAGI constructs an explicit consensus mechanism for multi-agent coordination. This consensus is an achievable and valuable future state, which is used as a common goal to guide multi-agent policies. Agents make decisions conditioned not only on their local observation, but also on the common goal. This goal encourages agents to cooperatively explore towards a common target state with potential high reward. To generate such a common goal, MAGI adopts a model-based way. Specifically, MAGI uses a self-supervised conditional variational auto-encoder (CVAE) (Sohn, Lee, and Yan 2015) to model the distribution of future states. The agents' behavior will be implicitly embedded in the self-

^{*}These authors contributed equally.

Copyright © 2023, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

supervised CVAE, and therefore possible future states can be sampled while alleviating the "curse of dimensionality" problem introduced by policy rollout. After that, a valuable future state from the distribution will be selected as the common goal, and we call this process goal imagination.

In summary, our main contributions are listed as follows:

- We propose a novel consensus mechanism for cooperative MARL. This consensus mechanism provides an explicit goal to coordinate multiple agents effectively.
- We introduce an efficient model-based goal generation method, which avoids the multi-step rollout procedure commonly used in model-based methods.
- Empirical results on Multi-agent Particle-Environments and challenging Google Research Football environments demonstrate the superiority of MAGI in terms of both performance and sample efficiency.

Related Work

Cooperative MARL: Based on the development of single agent reinforcement learning, early methods handle the multi-agent reinforcement problem by regarding each agent individually and training independent learners (Matignon, Laurent, and Le Fort-Piat 2012; Tampuu et al. 2017). However, treating other agents as part of environment will cause the non-stationary dynamics problem (Omidshafiei et al. 2017), and many popular MARL methods adopt a centralized training with decentralized execution (CTDE) framework to attenuate this problem. Representative CTDE methods include value decomposition networks (VDN) (Sunehag et al. 2018), QMIX (Rashid et al. 2018), MADDPG (Lowe et al. 2017) and FACMAC (Peng et al. 2021).

The CTDE methods adopt a centralized structure during training, which can be regarded as an implicit consensus mechanism for multi-agent coordination. However, during execution agents make decisions independently without such centralized guidance, which may result in sub-optimal solutions due to mis-coordination (Gronauer and Diepold 2022). Goal conditioned methods can be used to enhance multi-agent learning. Cooperative multi-agent exploration (CMAE) (Liu et al. 2021) selects unexplored states as the goal to improve exploration. Feudal network (Vezhnevets et al. 2017; Ahilan and Dayan 2019) adopts a high-level policy generating the hidden state goal to guide the low-level policies.

Compared with these methods, MAGI builds an explicit consensus mechanism by generating a model-based common-goal to guide multi-agent policies, which coordinates multiple agents effectively and efficiently.

Model-based RL: Model-based reinforcement learning provides a more sample efficient framework by learning an environment model first and then planning optimal control upon it (Sutton 1991). Representative model-based methods such as MPC (Nagabandi et al. 2018) are based on the stepby-step prediction that predicts the next observation given the current state and action. However, the multi-step compounding error limits the performance of model-based methods(Talvitie 2014). Some recent approaches directly model the long-term dynamics to alleviate this problem (Mishra, Abbeel, and Mordatch 2017; Ke et al. 2019; Krupnik, Mordatch, and Tamar 2020). However, the growing joint action space still makes their action-dependent planning hard to scale with agent numbers in multi-agent environments.

Compared with above mentioned model-based methods, the goal generation procedure of MAGI is more efficient since the common goal generation and action selection is disentangled in MAGI. The multi-agent behavior is implicitly embedded in the generative model, so MAGI can directly model long-horizon future state distribution.

Preliminary

A single agent reinforcement learning problem can be described as a Markov Decision Process (MDP) (Sutton and Barto 2018). A MDP is defined by the tuple $(S, A, P, r, \rho_0, \gamma)$, where S is a finite set of states, A is a finite set of actions, $P : S \times A \times S \mapsto [0, 1]$ is the transition probability distribution, $r : S \times A \mapsto \mathbb{R}$ is the reward function, ρ_0 is the distribution of the initial state s_0 , and $\gamma \in (0, 1)$ is the discount factor. The agent aims to maximize its total expected reward $R = \sum_{t=0}^{T} \gamma^t r^t$, where T is the time horizon.

A multi-agent extension of MDP calls Markov games (Littman 2001). A Markov game for N agents is defined by a set of global states S, and a set of actions A_1, \dots, A_N for each agent. To choose actions, each agent *i* uses a stochastic policy $\pi_{\theta^i} : S \times A_i \mapsto [0, 1]$ parameterized by θ^i , and produces the next state according to the state transition function $\mathcal{T} : S \times A_1 \times \dots \times A_N \mapsto S$. Each agent *i* obtains rewards based on function $r_i : S \times A_i \mapsto \mathbb{R}$. The initial states are determined by a distribution $\rho_0 : S \mapsto [0, 1]$. Each agent *i* aims to maximize its total discounted reward $R_i = \sum_{t=0}^{T} \gamma^t r_i^t$ where γ is a discount factor and T is the time horizon. In this paper, we consider a fully-cooperative Markov game where the reward is identical for all agents. To simplify notation, we omit θ from the subscript of π when there is no ambiguity in the following sections.

Methods

The proposed MAGI framework consists of a model-based goal imagination module and a model-free policy. Figure 1 illustrates the overall architecture.

In the next, we first introduce our model-based longhorizon goal imagination mechanism. We then explain how the generated goal helps agents reach consensus and coordinate model-free multi-agent learning. Finally, we present the whole training procedure of the proposed MAGI framework.

Long-horizon Goal Imagination

The long-horizon goal imagination module is a model-based structure that aims to establish a common goal as multiagent consensus. Specifically, this structure consists of two parts: a generative network for modeling future state distribution and an actor-critic-style (Konda and Tsitsiklis 2000) goal generator to produce a valuable long-horizon goal.

Future State Distribution Modeling We use CVAE to model the future state distribution, which is suitable for



Figure 1: Overview of MAGI. (a) The multi-agent goal imagination module. CVAE models the future state distribution, from which the goal actor and goal critic sample the common goal. (b) Agent network structure coordinated by imagined goal-based consensus mechanism with intrinsic reward and hypernetwork policy. (c) Policy network with goal-based hypernetwork.

modeling long-term environment dynamics and easy for sampling possible states (Mishra, Abbeel, and Mordatch 2017; Krupnik, Mordatch, and Tamar 2020). Furthermore, we decouple action selection from dynamics modeling, allowing our architecture to have better scalability in multiagent environments.

Specifically, at time step t, we want to model a future state $s_{t+c} \in S$ after a horizon length c. Our CVAE consists of a posterior distribution (encoder) $q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t)$, a generative distribution (decoder) $p_{\theta^{\text{dec}}}(s_{t+c}|s_t, z_t)$ and a prior distribution $p_{\theta^{\text{prior}}}(z_t|s_t)$ regularized by the posterior distribution $q_{\theta^{\text{enc}}}$.

As shown in Figure 1(a), the CVAE encoder maps s_{t+c} and s_t to a posterior distribution $q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t)$. Then, we sample a z_t from $q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t)$ and feed it into decoder together with s_t to model the distribution $p_{\theta^{\text{dec}}}(s_{t+c}|s_t, z_t)$. The sampling process during training is differentiable using the reparameterization trick $z_t = \mu^{\text{post}} + \sigma^{\text{post}} \cdot \epsilon$, where $\epsilon \sim \mathcal{N}(0, I)$ is the sample noise (Kingma and Welling 2014).

Goal Actor and Goal Critic After the future state distribution modeling, the goal state will be sampled and evaluated through an actor-critic-style process.

The goal actor aims to find the hidden state from the prior distribution $p_{\theta^{\text{prior}}}(z_t|s_t)$ that can be decoded to the future state with the highest value. We propose two types of goal actor with different sampling strategies:

- Uniform sampling ${}^{1} \epsilon$ within range [-D, D], where D is a hyperparameter specifying sampling region.
- Training a deterministic sampling policy $\pi_{\psi}^{g}(s_t, \mu, \sigma)$ that outputs the reparameterization coefficient ϵ directly.

As a nonparametric method, the uniform sampling is more flexible, but each sample needs to be evaluated to compare values. On the other hand, the parameterized deterministic policy $\pi_{\psi}^{g}(s_{t}, \mu, \sigma)$ has a lower computation cost during goal generation but requires training. Our experimental results show that both strategies are effective.

The goal critic V^g aims to evaluate the value of the imagined future state \hat{s}_{t+c} which is decoded by the CVAE. It can be trained using temporal-difference learning as the standard actor-critic method.

In summary, the general process of goal generation can be described as follows.

• For the uniformly sampling strategy, the CVAE decoder takes M uniformly sampled hidden state $[z_t^1, z_t^2, \cdots, z_t^M]$ as input and outputs a series of goal candidates $[\hat{s}_{t+c}^1, \hat{s}_{t+c}^2, \cdots, \hat{s}_{t+c}^M]$. Then, all goal candidates are fed into the goal critic to get the goal with highest state value $s_t^g = \arg \max_{\hat{s}_{t+c}^i} V^g(\hat{s}_{t+c}^i)$, for $i \in \{1, 2, \cdots, M\}$.

¹We use uniform sampling instead of widely used normal sampling to increase the probability of unexplored states.

For the deterministic sampling policy π^g_ψ, π^g_ψ takes state s_t, μ and σ as inputs and outputs a continuous action ε ∈ [-D, D]. Then the hidden state z_t = μ + σ ⋅ ε is fed into the CVAE decoder to obtain the goal s^g_t.

Consensus Coordinated Policy Learning

After the long-horizon goal s_t^g is generated, MAGI uses it to build consensus among agents. MAGI provides two mechanisms for coordinating multi-agent policy learning with the goal-based consensus, as shown in Figure 1(b).

Firstly, the parameters of agents' policy network are generated by hypernetwork (David Ha 2017) taking the goal s_t^g as input. This makes it possible to condition the weights of each agent's policy network on s_t^g in arbitrary ways, thus integrating the goal imagination s_t^g into each agent's policy as flexibly as possible. Then, we can perform standard actorcritic-based methods for policy learning.

To further guide all agents to reach the consensus described by the goal state s_t^g , we design an intrinsic reward function that encourages agents to take actions leading to the goal state. Specifically, at time step t, we assign each agent an intrinsic reward based on whether the current action contributes to the goal state. Formally, the intrinsic reward for agent i has the following form:

$$r_t^{i-\mathrm{in}} = d(u_i(s_t^g); v_i(s_t)) - d(u_i(s_t^g); v_i(s_{t+1})), \quad (1)$$

 $u_i(\cdot)$ and $v_i(\cdot)$ map s_t^g and s_t to the same metric space for agent *i*, and $d(\cdot)$ is the corresponding distance function. Then, each agent *i*'s policy can be guided by a proxy reward function $r_t^{i\text{-proxy}}$ which combines the external environment's reward r_t^{ex} and intrinsic reward r_t^{in} :

$$r_t^{i\text{-proxy}} = r_t^{\text{ex}} + \lambda r_t^{i\text{-in}},\tag{2}$$

where λ is a parameter balancing the external and intrinsic rewards. In the following training procedure, this proxy reward function $r_t^{i-\text{proxy}}$ is default reward setting for all agents.

Training Procedure

The long-horizon goal imagination module can be trained end-to-end together with the policy network. The training of CVAE is self-supervised, which takes state pairs $\{s_t, s_{t+c}\}$ from the agents' trajectory as training data. Since the prior $p_{\theta^{\text{prior}}}(z_t|s_t)$ is regularized by $q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t)$, which is a Gaussian distribution with parameter μ and σ , the KL divergence in the evidence lower bound (ELBO) could be computed in closed form. Besides, the expected reconstruction error $\mathbb{E}_{q_{\theta^{\text{prior}}}(z_t|s_{t+c},s_t)}[\log p_{\theta^{\text{dec}}}(s_{t+c}|z_t,s_t)]$ can be estimated by sampling. Thus, maxing ELBO in CVAE is equivalent to minimizing the following loss function:

$$\mathcal{L}_{\text{CVAE}}(\theta) = \mathbb{KL}[q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t) \| p_{\theta^{\text{prior}}}(z_t|s_t)] \\ - \mathbb{E}_{q_{\theta^{\text{enc}}}(z_t|s_{t+c}, s_t)}[\log p_{\theta^{\text{dec}}}(s_{t+c}|z_t, s_t)].$$
(3)

For the goal critic, it can be trained together with agent *i*'s centralized critic Q^i for all $i \in \{1, 2, \dots, N\}$. Formally, the goal critic loss has the following form:

$$\mathcal{L}_{t}^{\text{gc}}(\zeta) = \frac{1}{N} \sum_{i=1}^{N} \left[V_{\zeta}^{g}(s_{t}) - Q^{i}(s_{t}, a_{t}^{i}) \right]^{2}.$$
 (4)

Whether to train the goal actor depends on the sampling method of z_t . The strategy of uniformly sampling z_t in a neighborhood of mean vector μ does not require training since it is nonparametric. For deterministic sampling policy π_{ψ}^{g} , we adopt a DDPG-style training and solve the following optimization problem using gradient ascent:

$$\max_{\psi} V^g(f_{\text{dec}}(s_t, \mu + \sigma \cdot \pi^g_{\psi}(s_t, \mu, \sigma))), \tag{5}$$

where the action of the goal actor π_{ψ}^{g} is predicting the reparameterization coefficient ϵ , and its objective is to maximize the value future state s_{t}^{g} which is decoded by CVAE decoder $f_{\text{dec}}(z_{t})$ with $z_{t} = \mu + \sigma \cdot \pi_{\psi}^{g}(s_{t}, \mu, \sigma)$. Specifically, we can use the following sampled policy gradient to optimize (5):

$$\nabla_{\psi} J(\psi) \approx \frac{1}{N_b} \sum_{j=1}^{N_b} \left[\nabla_{\psi} \pi_{\psi}^g(s_j, \mu, \sigma) \nabla_{\epsilon_j} V^g(f_{\text{dec}}(s_j, \mu + \sigma \cdot \epsilon_j)) \right]$$
(6)

where N_b is mini-batch size.

Each agent's policy optimization process follows the standard actor-critic paradigm such as DDPG and PPO (Schulman et al. 2017). Figure1(b) shows the policy optimization procedure using DDPG. When using DDPG, agent *i*'s Q function can be optimized by minimizing the following loss:

$$\mathcal{L}(\theta^{i}) = \frac{1}{N_{b}} \sum_{j=1}^{N_{b}} \left(y_{j}^{i} - Q^{i}(s_{j}, a_{j}^{i}; \theta^{i}) \right)^{2},$$
(7)

where $y_j^i = r_j^{i\text{-proxy}} + \gamma Q'^i(s'_j, a'_j{}^i; \theta'{}^i)|_{a'_j{}^i = \pi^i(s'_j)}$ is the one step temporal difference target, N_b is the batch size, and Q'^i is the target network. Each agent *i*'s policy π^i can be updated with the sampled policy gradient:

$$\nabla_{\phi^i} J(\phi^i) \approx \frac{1}{N_b} \sum_{j=1}^{N_b} \nabla_{\phi^i} \pi^i(s_j; \phi^i) \nabla_{a^i_j} Q^i(s_j, a^i_j), \quad (8)$$

It is worth noting that the DDPG structure mentioned above for agent's policy training can be replaced by other actor-critic-based algorithms, such as PPO (Schulman et al. 2017). See the experiment section for more details.

Experiments

We evaluate MAGI on two multi-agent environments: the multi-agent particle-environments (MPEs) and challenging Google Research Football (GRF). In this section, we present experimental results and answer the following three questions: 1) Can MAGI achieve better performance on MPEs and challenging GRF environments? 2) How does the consensus modeling improve the performance? 3) Does the generated goal actually influence the agents' policy?

Environments

Multi-agent Particle-Environments The MPEs is a physics-based 2D environment, which provides continuous action space, including stay and move. We consider the following four tasks as shown in Figure 2:

Navigation N = 3 agents need to cooperatively cover 3 landmarks while avoiding collision.



Figure 2: Illustrations of the Multi-agent Particle-Environments.

Treasure Collection (Iqbal and Sha 2019) N = 3 agents aim to cooperatively collect 6 randomly placed treasures.

Ten-Agents Treasure Collection N = 10 agents to collect 20 treasures. This is an extension of Treasure Collection.

Predator-Prey N = 3 slower predators aim to catch one faster prey which is controlled by a fixed pretrained policy.

Keep Away N = 3 slower guards agents need to safeguard three treasures. Another faster theft agent controlled by a fixed pretrained policy tries to steal treasures.

In Predator-Prey and Keep Away tasks, the fixed opponent agent is pretrained by self-play using DDPG. For detailed reward designs, please refer to Appendix B.

Google Research Football The GRF is a challenging physics-based 3D football simulation environment. It provides large discrete action space, including moving, shooting, and passing. Agents need complex cooperation to get more scores than opponents. In N vs N scenario, there are N - 1 players and one goalkeeper on each team. We consider scenarios 3 vs 3, 4 vs 4 and 5 vs 5, in which the opponent team is controlled by built-in AI.

Baselines and Settings

For MPEs, we build MAGI based on DDPG (Lillicrap et al. 2016). We compare MAGI with the following approaches: centralized DDPG; CTDE methods MADDPG (Lowe et al. 2017) and FACMAC (Peng et al. 2021) (an extension of QMIX under actor-critic framework); modelbased planning RL methods Conditional-TSM (Krupnik, Mordatch, and Tamar 2020) and MPC (Nagabandi et al. 2018); an imagination-augmented method I2A (Racanière et al. 2017); a goal-conditioned hierarchical method Feudal Network (FuN) (Vezhnevets et al. 2017). The implementations of DDPG, MADDPG, FACMAC, I2A, and FuN adopt the same policy network structure as MAGI. During the evaluation of model-based planning methods, we use the same planning horizon length as MAGI and only choose the Navigation task considering the heavy computation complexity of learning dynamics model in other scenarios. We list the comparison of parameter and training complexity in Table 1.

Methods	Parameter Number	Inference Time	Training Time
DDPG	$1 \times$	$1 \times$	$1 \times$
MADDPG	$1 \times$	$1 \times$	$1.05 \times$
FACMAC	$1 \times$	$1 \times$	$0.78 \times$
Central	$1.03 \times$	$0.47 \times$	$0.50 \times$
FuN	$1.59 \times$	$1.23 \times$	$1.40 \times$
I2A	$4.42 \times$	$285.70 \times$	$15.23 \times$
MAGI	1.54 ×	1.22 ×	1.54 ×

Table 1: Parameter number, inference and training time comparison of different methods (DDPG is normalized to 1x).

For the Google Research Football environment, we choose PPO as the baseline since its performance in complex environments has been verified before (Berner et al. 2019; Ye et al. 2020). We build MAGI upon PPO to verify its effectiveness in complex environments. 2 Nvidia V100 GPUs and 800 AMD EPYC 7K62 CPU cores are used for GRF experiments.

The imagination module takes c = 4 and c = 16 as the horizon length in MPEs and GRF. Unless specified, we use uniform sampling in experiments. When implementing intrinsic reward in Equation 1, u_i and v_i output the coordinates of the agent *i*'s goal position and current position, *d* is set as Euclidean distance, and the goal reward weight is set as $\lambda = 0.001$. For environments where the distance is hard to measure directly, we provide a generalized implementation of intrinsic reward. Please refer to Appendix A for details.

Main Results

For tasks in MPEs, we repeated each experiment 32 times, and the average results are displayed in Figure 3 and Table 2. Results show that MAGI outperforms all baselines in every task regarding sample efficiency and final performance.

Compared with baseline methods DDPG and Centralized-DDPG, MAGI achieves better performance and sample efficiency. This is likely because the common goal in MAGI improves agents' exploration and coordination.

MAGI yields better and more stable results than MAD-DPG and FACMAC, two representatives of CTDE methods that implicitly take consensus into consideration during training. This result demonstrates the importance of an explicit consensus mechanism for multi-agent coordination.

MAGI significantly outperforms model-based methods Conditional-TSM and MPC. Its performance can likely be



Figure 3: The average results in four MPEs tasks. MAGI outperforms all other methods in sample efficiency and performance. The legend in (a) applies across all plots.



Figure 4: Demonstration of the GRF environment and average goal difference results in three GRF scenarios.

Methods	Rewards	
Conditional-TSM	-20.3	
MPC	-17.6	
MAGI	-11.1	

Table 2: Results of Conditional-TSM and MPC in Navigation task.

attributed to that MAGI directly models long-term dynamics, which decouples high-level state planning and low-level action decision. Therefore it can suffer less from dynamics prediction compounding error and produce better goals to guide agents cooperation.

MAGI performs better than the goal-conditioned method FuN, which uses hidden state as the goal. We assume that the goal generated by self-supervised generative method in MAGI can provide more direct and useful instructions for agents than the hidden state goal of FuN.

Compared with I2A, an imagination-augmented method reaches significantly better performance. The result can be attributed to that our imagination module can generate better future states and consensus mechanism can coordinate agents more efficiently.

Average results in GRF are shown in Figure 4. MAGI yields better results than PPO in all scenarios, including the challenging 5 vs 5, showing that MAGI has the ability to solve complex multi-agent tasks and has the adaptability to be built upon different learning algorithms.

To further demonstrate the scalability of MAGI, we expand agent number to 10 in Treasure Collection task and the results are shown in Figure 5. MAGI achieves better per-



Figure 5: Demonstration of scalability. MAGI improves performance in Ten-Agents Treasure Collection task.

formance in comparison of baseline DDPG and MADDPG methods. This result shows that MAGI can be scaled to scenarios with large number of agents.

Consensus Analysis

To verify how the learned consensus in MAGI affect policies of agents, we conduct several visualization analyses.

The visualization of the imagined future state distributions are presented in Figure 6(a) and (b). Imagined states at training step 20M are concentrated in regions closer to target landmarks than training step 1M, demonstrating that MAGI can provide better imagination about future states after training, which helps to sample valuable goals more efficiently. From multi-agent coordination perspective, the difference in the distribution of each agent's future goal makes it possible for all agents as a team to get more rewards, thus achieving consensus among all agents.

Another question is whether agents can perform actions



Figure 6: (a) and (b): distribution of imagined positions of agents. Green circles and blue arrows are agents' current positions and velocities, and black crosses are target land-marks. (c) and (d): illustration of trajectories and imagined goals. The green curves are trajectories of agents, and red circles are positions of goals.

according to the common goal (or team consensus). We further provide a case study to visualize the agents' trajectories and goals in Figure 6(c) and (d). At training step 1M, goals are far away from targets, and agents fail to reach the goals. When the training step comes to 20M, goals can provide more useful instructions, and agents follow the goals well.

The above analysis indicates that MAGI can learn to generate achievable and valuable common goals for all agents, which achieves a consensus mechanism and further improves multi-agent coordination.

Ablation Study

We conducted two ablation experiments in Navigation task to evaluate the effectiveness of the goal generated by MAGI.

We first analyze the influence of sample size and sampling strategy. Figure 7(a) shows that when the sample size is 1, MAGI degrades to naive DDPG. As the sample size increases, the quality of generated goals becomes better, and the performance of MAGI improves monotonically. The deterministic sampling also achieves comparable performance with the uniformly sampling strategy.

Then, we test MAGI with different planning horizon lengths. As shown in Figure 7(b), horizon length that is too short or too long both degrade the performance. We attribute it to that short horizon length goal provide little useful instructions. While excessive long horizon goals are hard for agents to achieve, thus failing to guide agents effectively.



Figure 7: Ablation results of sample size and horizon length.

These results prove the goal generated by MAGI actually coordinates the policies of agents and a valuable and achievable goal is of vital importance for the superiority of MAGI.

Conclusion

In this paper, we present MAGI, a cooperative MARL framework which introduces an explicit consensus mechanism for multi-agent coordination. Firstly, a distribution of future states is modeled with a novel CVAE-based selfsupervised generative model. Then, a common goal with high potential value is sampled as multi-agent consensus to guide all agents' policies. Experimental results on Multiagent Particle Environment and Google Research Football demonstrate the proposed consensus mechanism can effectively enhance the cooperation among agents and improve sample-efficiency.

References

Ahilan, S.; and Dayan, P. 2019. Feudal multi-agent hierarchies for cooperative reinforcement learning. *arXiv preprint arXiv:1901.08492*.

Berner, C.; Brockman, G.; Chan, B.; Cheung, V.; Debiak, P.; Dennison, C.; Farhi, D.; Fischer, Q.; Hashme, S.; Hesse, C.; et al. 2019. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*.

Cao, Y.; Yu, W.; Ren, W.; and Chen, G. 2012. An overview of recent progress in the study of distributed multi-agent co-ordination. *IEEE Transactions on Industrial informatics*, 9(1): 427–438.

David Ha, Q. V. L., Andrew M. Dai. 2017. HyperNetworks. In 5th International Conference on Learning Representations, ICLR 2017.

Gronauer, S.; and Diepold, K. 2022. Multi-agent deep reinforcement learning: a survey. *Artificial Intelligence Review*, 55(2): 895–943.

Hüttenrauch, M.; Šošić, A.; and Neumann, G. 2017. Guided deep reinforcement learning for swarm systems. *arXiv* preprint arXiv:1709.06011.

Iqbal, S.; and Sha, F. 2019. Actor-attention-critic for multiagent reinforcement learning. In *International Conference on Machine Learning*, 2961–2970.

Ke, N. R.; Singh, A.; Touati, A.; Goyal, A.; Bengio, Y.; Parikh, D.; and Batra, D. 2019. Learning dynamics model in reinforcement learning by incorporating the long term future. *stat*, 1050: 16.

Kingma, D. P.; and Welling, M. 2014. Auto-Encoding Variational Bayes. *stat*, 1050: 1.

Konda, V. R.; and Tsitsiklis, J. N. 2000. Actor-critic algorithms. In *Advances in neural information processing systems*, 1008–1014.

Krupnik, O.; Mordatch, I.; and Tamar, A. 2020. Multi-agent reinforcement learning with multi-step generative models. In *Conference on Robot Learning*, 776–790.

Lillicrap, T. P.; Hunt, J. J.; Pritzel, A.; Heess, N.; Erez, T.; Tassa, Y.; Silver, D.; and Wierstra, D. 2016. Continuous control with deep reinforcement learning. *4th International Conference on Learning Representations, ICLR 2016 - Conference Track Proceedings.*

Littman, M. L. 2001. Value-function reinforcement learning in Markov games. *Cognitive systems research*, 2(1): 55–66.

Liu, I.-J.; Jain, U.; Yeh, R. A.; and Schwing, A. 2021. Cooperative exploration for multi-agent deep reinforcement learning. In *International Conference on Machine Learning*, 6826–6836. PMLR.

Lowe, R.; Wu, Y. I.; Tamar, A.; Harb, J.; Abbeel, O. P.; and Mordatch, I. 2017. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in neural information processing systems*, 6379–6390.

Matignon, L.; Laurent, G. J.; and Le Fort-Piat, N. 2012. Independent reinforcement learners in cooperative markov games: a survey regarding coordination problems. *The Knowledge Engineering Review*, 27(1): 1–31.

Mishra, N.; Abbeel, P.; and Mordatch, I. 2017. Prediction and control with temporal segment models. In *International Conference on Machine Learning*, 2459–2468. PMLR.

Nagabandi, A.; Kahn, G.; Fearing, R. S.; and Levine, S. 2018. Neural network dynamics for model-based deep reinforcement learning with model-free fine-tuning. In *IEEE International Conference on Robotics and Automation*, 7559–7566. IEEE.

Omidshafiei, S.; Pazis, J.; Amato, C.; How, J. P.; and Vian, J. 2017. Deep decentralized multi-task multi-agent reinforcement learning under partial observability. In *International Conference on Machine Learning*, 2681–2690. PMLR.

Peng, B.; Rashid, T.; Schroeder de Witt, C.; Kamienny, P.-A.; Torr, P.; Böhmer, W.; and Whiteson, S. 2021. Facmac: Factored multi-agent centralised policy gradients. *Advances in Neural Information Processing Systems*, 34: 12208– 12221.

Racanière, S.; Weber, T.; Reichert, D. P.; Buesing, L.; Guez, A.; Rezende, D.; Badia, A. P.; Vinyals, O.; Heess, N.; Li, Y.; et al. 2017. Imagination-augmented agents for deep reinforcement learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, 5694–5705.

Rashid, T.; Samvelyan, M.; Schroeder, C.; Farquhar, G.; Foerster, J.; and Whiteson, S. 2018. QMIX: Monotonic Value Function Factorisation for Deep Multi-Agent Reinforcement Learning. In *International Conference on Machine Learning*, 4295–4304.

Ren, W.; Beard, R. W.; and Atkins, E. M. 2005. A survey of consensus problems in multi-agent coordination. In *Proceedings of the 2005, American Control Conference, 2005.*, 1859–1864. IEEE.

Schulman, J.; Wolski, F.; Dhariwal, P.; Radford, A.; and Klimov, O. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Sohn, K.; Lee, H.; and Yan, X. 2015. Learning structured output representation using deep conditional generative models. *Advances in neural information processing systems*, 28: 3483–3491.

Son, K.; Kim, D.; Kang, W. J.; Hostallero, D. E.; and Yi, Y. 2019. QTRAN: Learning to Factorize with Transformation for Cooperative Multi-Agent Reinforcement Learning. In *International Conference on Machine Learning*, 5887– 5896.

Sunehag, P.; Lever, G.; Gruslys, A.; Czarnecki, W. M.; Zambaldi, V. F.; Jaderberg, M.; Lanctot, M.; Sonnerat, N.; Leibo, J. Z.; Tuyls, K.; et al. 2018. Value-Decomposition Networks For Cooperative Multi-Agent Learning Based On Team Reward. In *International Conference On Autonomous Agents and Multi-Agent Systems*, 2085–2087.

Sutton, R. S. 1991. Dyna, an integrated architecture for learning, planning, and reacting. *ACM Sigart Bulletin*, 2(4): 160–163.

Sutton, R. S.; and Barto, A. G. 2018. *Reinforcement learn-ing: An introduction*. MIT press.

Talvitie, E. 2014. Model regularization for stable sample rollouts. In *Proceedings of the Thirtieth Conference on Uncertainty in Artificial Intelligence*, 780–789.

Tampuu, A.; Matiisen, T.; Kodelja, D.; Kuzovkin, I.; Korjus, K.; Aru, J.; Aru, J.; and Vicente, R. 2017. Multiagent cooperation and competition with deep reinforcement learning. *PloS one*, 12(4): e0172395.

Vezhnevets, A. S.; Osindero, S.; Schaul, T.; Heess, N.; Jaderberg, M.; Silver, D.; and Kavukcuoglu, K. 2017. Feudal networks for hierarchical reinforcement learning. In *International Conference on Machine Learning*, 3540–3549.

Ye, D.; Chen, G.; Zhang, W.; Chen, S.; Yuan, B.; Liu, B.; Chen, J.; Liu, Z.; Qiu, F.; Yu, H.; et al. 2020. Towards Playing Full MOBA Games with Deep Reinforcement Learning. *arXiv e-prints*, arXiv–2011.

Ye, D.; Zhang, M.; and Yang, Y. 2015. A multi-agent framework for packet routing in wireless sensor networks. *sensors*, 15(5): 10026–10047.

Appendix A. Generalized Intrinsic Reward

In Section 5, we implement intrinsic reward in Equation 1 by calculating the Euclidean distance between agent and goal positions. In fact, the intrinsic reward can be calculated without any domain knowledge. Here we provide a generalized implementation of intrinsic reward, which makes MAGI can be used in any complex environment.



Figure 8: Results of MAGI with generalized intrinsic reward.

In this generalized version, the agent state and the goal state are mapped to CVAE latent space to calculate the difference. Specifically, in Equation 1, $f(\cdot)$ and $g(\cdot)$ are implemented with the posterior distribution in CVAE $h_{\theta^{enc}}(\cdot) = q_{\theta^{enc}}(z|\cdot, s_t)$, and their distance is calculated with KL divergence. Thus the intrinsic reward becomes:

 $r_t^{i-\text{in}} = \mathbb{KL}[h_{\theta^{\text{enc}}}(s_t^g) \| h_{\theta^{\text{enc}}}(s_t)] - \mathbb{KL}[h_{\theta^{\text{enc}}}(s_t^g) \| h_{\theta^{\text{enc}}}(s_{t+1})]$ This distance metric contains high-dimensional information about the difference between s_t^g and s_t and can be used in any environment without domain knowledge.

We implemented MAGI with the above variant r^{i-in} in the MPEs Navigation scenario. As shown in Figure 8, MAGI can achieve competitive performance compared to the version presented in Section 5.

B. Reward Designs in Multi-agent Particle-Environments

All agents share the same reward.

Navigation Agents are rewarded using sum of minimum distance to any agents for each landmark at each time step. Agents get -1 when they collide with each other. Total time steps for one episode game is 25.

Treasure Collection Agents get +1 when they collect any treasure and get -1 when they collide with each other. Total time steps for one episode game is 25.

Predator-Prey Agents get +10 they collide with the prey. Total time steps for one episode game is 100.

Keep Away Agents get +1 when they collide with the theft agent and get -1 when they collide with each other. Total time steps for one episode game is 100.