HeteroMILE: a Multi-Level Graph Representation Learning Framework for Heterogeneous Graphs

Yue Zhang * Yuntian He[†]

Saket Gurukar[‡]

Srinivasan Parthasarathy[§]

Abstract

Heterogeneous graphs are ubiquitous in real-world applications because they can represent various relationships between different types of entities. Therefore, learning embeddings in such graphs is a critical problem in graph machine learning. However, existing solutions for this problem fail to scale to large heterogeneous graphs due to their high computational complexity. To address this issue, we propose a Multi-Level Embedding framework of nodes on a heterogeneous graph (HeteroMILE) - a generic methodology that allows contemporary graph embedding methods to scale to large graphs. HeteroMILE repeatedly coarsens the largesized graph into a smaller size while preserving the backbone structure of the graph before embedding it, effectively reducing the computational cost by avoiding time-consuming processing operations. It then refines the coarsened embedding to the original graph using a heterogeneous graph convolution neural network. We evaluate our approach using several popular heterogeneous graph datasets. The experimental results show that HeteroMILE can substantially reduce computational time (approximately 20x speedup) and generate an embedding of better quality for link prediction and node classification.

1 Introduction

Graphs serve as a versatile representation for capturing relationships across diverse domains, including social networks, biological systems, and information networks. In these applications, entities and their relationships are often in different types, leading to the concept of heterogeneous graphs. Heterogeneous graphs, characterized by nodes and edges with diverse types and attributes, offer a more comprehensive representation of complex systems [1]. Recently, graph embedding has gained significant attention as a means to capture both the structural and content-related aspects of graphs in a lower-dimensional vector space. This representation effectively preserves essential graph properties and information. Graph embedding finds applicability

[†]The Ohio State University (he.1773@osu.edu).

across various types of graphs, including homogeneous and heterogeneous graphs, and has been leveraged in diverse domains like social network analysis, bioinformatics, and natural language processing [6]. However, existing graph embedding techniques face challenges when it comes to scalability. Particularly, the embedding techniques that rely on random walks, such as metapath2vec [2] demand considerable CPU time to generate a sufficient number of walks for training the embedding model. This computationally intensive process hinders their scalability, restricting their applicability to largescale graphs.

In recent years, improvements in the scalability of homogeneous graph embedding have been extensively studied. A popular methodology adopted by several prior studies [3, 4, 5] is the multi-level framework. The core concept of their approach involves iteratively reducing the complexity of the original graph through coarsening, followed by the application of a pre-existing embedding method to the simplified graph. The resulting embeddings are further refined using graph neural networks (GNN). Through extensive experimentation, they have shown that this approach enhances scalability without sacrificing the performance of the embeddings.

However, these approaches are not trivial to extend to heterogeneous graphs, as one must carefully account for node heterogeneity in both the coarsening and refinement procedures. To our understanding, this is the initial endeavor to tackle this issue. Specifically, we propose a Multi-Level Embedding framework on a Heterogeneous graph (HeteroMILE). HeteroMILE consists of three major steps: Firstly, we employ various matching strategies to iteratively reduce the size of the large graph, resulting in a smaller coarsened graph. Secondly, we apply well-established heterogeneous graph embedding techniques [2, 31] to compute embeddings on this coarsened graph. Lastly, we introduce a refinement model that utilizes a heterogeneous graph convolution network to enhance the embeddings, refining them from the smaller-sized graph back to the originalsized graph. We demonstrated the viability of the HeteroMILE framework on several popular datasets: AcademicII, DBLP, IMDB, and OGB_MAG. Our current

^{*}The Ohio State University (zhang.8016@osu.edu).

[‡]The Ohio State University (gurukar.10osu.edu).

[§]The Ohio State University (srini@cse.ohio-state.edu).

results show that HeteroMILE can significantly reduce the computational time and improve link prediction and node classification accuracy. The primary contributions of this research can be outlined as follows:

- In order to address the scalability issue in heterogeneous graph embedding, we propose HeteroMILE which is a generalizable multi-level framework improving the efficiency of well-established heterogeneous graph embedding methods. Unlike existing approaches, HeteroMILE is not simply reliant on advanced computing resources. We demonstrate the effectiveness and efficiency of HeteroMILE using Metapath2Vec and GATNE[2, 31], popular heterogeneous graph embedding strategies, as a proofof-concept base embedding strategy.
- We propose two novel coarsening algorithms that adapt to the heterogeneous context - an exact Jaccard Similarity based approach and a more efficient approximate approach based on Locality-Sensitive Hashing (LSH) for node matching. We explored different experimental designs for the two algorithms to improve the performance and speed up the coarsening process.
- Our proposed approach involves utilizing a Heterogeneous Graph Convolutional Network [12] as a refinement model to enhance the embeddings obtained from the smaller-size graph, refining them to align with the initial graph.
- We perform our experiments on diverse and realworld datasets of heterogeneous graphs. We used four heterogeneous graph datasets, including academic graphs and Internet movie databases. On the largest dataset, OGB_MAG, which reflects the relationship between authors and institutions, papers, and fields, HeteroMILE is more than 20x faster than the baseline and offers improved performance to boot (up to a certain coarsening level).
- We evaluate different parameters on HeteroMILE. The experimental results show a tradeoff between performance and computation cost, but also prove that HeteroMILE can work well in different parameter settings.

2 Background and Motivation

2.1 Heterogeneous Graph Embedding Several algorithms have been proposed for learning node representations in homogeneous networks [15, 16]. However, applying these methods to heterogeneous graphs directly is not feasible due to the inherent heterogeneity present in the graph data. Specifically, heterogeneous

graphs have different relationships between nodes and may require specific efforts for information fusion across different node and edge spaces.

Recent studies have focused on heterogeneous graph embeddings. Several methods learn node representations by leveraging heterogeneous substructures and semantics. A representative work using this idea is metapath2vec [2], which generates the embeddings by performing random walks using predefined *meta-paths* and training a skip-gram model [7] with these sequences. Meta-path is a defined sampling scheme to capture a specific semantic between different node and edge types (e.g., "author-paper-author" denotes a co-authorship in a citation network). Another representative embedding method is GATNE [31] which also performs random works based on *meta-paths* but considers both graph structure and temporal information. It employs graph attention networks and attention mechanisms to capture the structure dependencies and temporal dynamics of the network. Other studies learn heterogeneous embeddings by preserving other substructures, such as links [18, 20, 19] and subgraphs [21, 22]. In addition, another group of studies leveraged the rich attributes and built heterogeneous graph neural networks (HGNNs) [24, 23] for performance improvement.

Despite the promising performance of these methods, their applicability is limited to large-scale heterogeneous graphs, owing to their complexity. For example, they require exceptional time for sampling (randomwalk-based methods) or training (HGNN-based methods). This motivates our study of HeteroMILE, which aims to help contemporary heterogeneous graph embedding techniques scale up to large networks.

2.2 Scalable Graph Embedding Recently, several approaches have been put forth to enhance the scalability of graph embedding techniques. Several studies have adopted a multi-level framework to improve scalability [3, 32, 4, 28].

A multi-level embedding framework is an effective way to address the challenges of large graph embedding. The process begins with graph coarsening to decrease the size of the input graph, followed by learning the embeddings of the fine-grained graph based on the coarsened versions. By decreasing the graph size, this framework not only can improve the efficiency of the embedding process but also maintain high-order structural features for enhanced quality.

One recent work is MILE [3], which is a framework for homogeneous graphs. It first merges groups of nodes into supernodes and then combines the edges. MILE uses a combination of two methods to match nodes: Structural Equivalence Matching (SEM) and Normal-

Sysmbol	Definition	
G_i	the graph resulting from i iterations of the coarsening process	
V_i, E_i	node set and edge set of G_i	
O_i, R_i	node types, edge types of G_i	
A_i, D_i	the adjacency and degree matrix of G_i	
d	dimensionality of the embeddings	
m	the total number of coarsening levels	
f_e	e the base embedding method applicable on G_i	
E_i	the embeddings of nodes in G_i	
$M_{i,i+1}$	the matching matrix from G_i to G_{i+1}	

Table 1: The table of notations

ized Heavy Edge Matching (NHEM). SEM matches nodes with the same neighbors, whereas NHEM matches unmatched nodes u with their unmatched neighbor vwith the highest normalized weight edge (u, v). In addition, NHEM prioritizes nodes with more neighbors to collapse first to merge more nodes. Then, MILE generates the embeddings on the shrunk graph and projects the embeddings to the original graph.

Another representative work is Graphzoom[17], which partitions the graph into multiple subgraphs using a spectral clustering algorithm and combines node attributes and the structure information to construct a fused graph. It then performs the embedding and maps it to the original graph.

In addition to the multi-level framework, some studies [25, 27, 33] used high-performance computing techniques, such as parallel computing, distributed computing, and GPU training, to resolve the scalability issue. Unfortunately, all of these studies were strictly designed for homogeneous graphs due to differences in the graph structure and the properties of nodes and edges. In homogeneous graphs, nodes, and edges typically have similar characteristics, making it easier to combine and merge the nodes. In contrast, heterogeneous graphs often contain nodes and edges with diverse properties, such as different types, attributes, or semantics. General matching methods of different node types would lead to a loss of contextual information, which causes less accurate results. Additionally, heterogeneous graphs often exhibit complex connectivity patterns between different types of nodes. The general merging approach might lose the patterns and ignore the intricate relationships and connections in the original graph. While existing studies fail to leverage heterogeneous data, our proposed HeteroMILE considers the specific node and edge types which is able to learn node embeddings on such networks while improving scalability.

3 Problem Statement

We use the notation G = (V, E) to represent a graph, where V is the set of nodes and E is the set of edges



Figure 1: Overview of HeteroMILE framework



Figure 2: Example of matching and merging the nodes

in graph G. The graph is associated with a node type mapping function $\Phi: V \to O$ and an edge type mapping function $\Psi: E \to R$. Here, O represents the set of all node types, and R represents the set of all edge types. It is important to note that for a heterogenous graph, the sum of the cardinalities of O and R must exceed 2, i.e., |O| + |R| > 2. Let A denote the adjacency matrix of the graph. The notations used in this paper are summarized in Table 1. Graph embedding can be defined as follows:

Scalable Heterogeneous Graph Embedding In the context of a heterogeneous graph G = (V, E), where the dimensionality is denoted as $d \ (d \ll |V|)$, our objective is to effectively acquire an embedding model $f : V \to \mathbb{R}^d$ that successfully captures the semantic aspects of the diverse relationships present within the heterogeneous graph.

4 Methodology

The HeteroMILE framework is divided into three stages: graph coarsening, base embedding, and refinement, as illustrated in Figure 1. Each stage will be explained in further detail.

4.1 Graph Coarsening During this phase, the initial graph (referred to as G or G_0) undergoes a repetitive



Figure 3: Refinement Process of HeteroMILE

coarsening process, resulting in a sequence of smaller graphs $(G_1, G_2, ..., G_m)$ with a decreasing number of nodes. The coarsening operation involves merging multiple nodes from G_i to create larger nodes known as supernodes within G_{i+1} . The edges connected to a supernode consist of the combined edges from the original nodes in G_i . The process of merging nodes to form a supernode is referred to as matching, where nodes of the same type are grouped together. To ensure efficient size reduction of the graph while preserving its overall structure, we propose two matching strategies. Figure 2 provides an illustrative example of this coarsening process.

Jaccard Similarity Matching Strategy: Jaccard Similarity[30] measures the similarity between two sets of data, which is calculated as the size of the intersection divided by the size of the union of two sets. In the context of graphs, Jaccard Similarity can be applied to the sets of 1-hop and 2-hop neighbors of two nodes. By calculating the Jaccard Similarity between each neighbor pair, we merged the nodes in two ways:

• Jaccard Max: For each unmatched node u in the graph, we find a node v from its 1-hop and 2-hop neighbors (denoted as $N_{(u)}$) which has the maximum Jaccard Similarity. We then collapsed nodes u and v in the same type into one supernode and marked them as matched. This matching process continues until all nodes have been matched or all unmatched nodes do not have unmatched neighbors. In this study, we calculated Jaccard Similarity using the following formula:

$$J(u, v) = \frac{|N_{(u)} \cap N_{(v)}|}{|N_{(u)} \cup N_{(v)}|}$$

• Jaccard weighted random sampling (WRS): We propose a variant of Jaccard-similarity-based matching by leveraging weighted random sampling (WRS). The difference is that here we randomly pick a neighbor v from $N_{(u)}$ with a probability proportional to the Jaccard similarity instead of selecting the one with maximum similarity. Formally, given a node u, we match it with its neighbor

 $v \in N_{(u)}$ with probability:

$$p(u, v_j) = \frac{J(u, v_j)}{\sum_{i \in N_{(u)}} J(u, v_i)}$$

Locality Sensitive Hashing (LSH) Matching Strategy: To further improve the efficiency of graph coarsening, we propose an approximate solution based on locality-sensitive hashing (LSH) [8]. LSH is an algorithm technique for efficiently finding approximate nearest neighbors in high-dimensional data. It works using hash functions that are designed to produce hash values of those similar nodes. Similar nodes that have common neighbors are highly likely to be grouped together in the same bucket. This greatly reduces the dimensionality of high-dimensional data because the high-dimension input is converted into lower dimensions while preserving the structure, which makes the computation much more efficient.

Formally, for nodes u and v in the same type, we estimate the similarity between $N_{(u)}$ and $N_{(v)}$ as follows:

$$im(N_{(u)}, N_{(v)}) = p_{f_i \in F}[f_i(N_{(u)}) = f_i(N_{(v)})]$$

s

In HeteroMILE, a set of k hash functions denoted as F, is randomly sampled for the purpose of hashing. Each individual hash function, $f_i \in F$, is defined as $f_i(u) = \min \pi(u)$, where $u \in U$ and π represents a permutation. Consequently, for a pair of nodes u and vwith a Jaccard similarity of J(u, v), the probability of them having the same hash value can be expressed as $Pr[f_i(u) = f_i(v)] = J(u, v)$. To capture and represent this information, a k-dimensional vector is assigned as the signature for each node. When two nodes exhibit identical signatures, it indicates that they are likely to possess structural equivalence, which enables their merging. This technique reduces the time complexity from $O(|V|^2)$ to O(|V|).

Choice for Coarsening Level: The coarsening level is a key parameter that can affect both utility and efficiency. Later we empirically show that using a small number of coarsening levels (typically between 2 and 4) results in high-quality embeddings with a good balance of speedup for medium-sized graphs (with less than 1,000,000 nodes). For larger graphs, the embeddings maintain their high quality even with higher coarsening levels (i.e., between 4 and 6), which leads to an even greater speedup.

4.2 Base Embedding The coarsening process significantly decreased the size of the graph, with the potential to halve it at each iteration. We perform this process for a fixed number of iterations m and then use a graph embedding technique f_e on the final coarsest

Datasets	Nodes	Edges
AcademicII	# author (A): 28,646 # paper (P): 21,044 # venue (V): 18	# A-P: 69,311 # P-P: 46,931 # P-V: 21,044
DBLP	# author (A): 4,057 # paper (P): 14,328 # term (T): 7,723 # venue (V): 20	# A-P: 19,645 # P-T: 85,810 # P-V: 14,328
IMDB	# movie (M): 4,278 # director (D): 2,081 # actor (A): 5,257	# M-D: 4,278 # M-A: 12,828
OGB_MAG	<pre># paper (P): 736,389 # author (A): 1,134,649 # institution (I): 8,740 # field (F): 59,965</pre>	# P-A: 7,145,660 # P-F: 7,505,078 # P-P: 5,416,271 # A-I: 1,043,998

Table 2: Dataset Information

graph G_m . The embeddings produced in G_m are referred to as E_m . Because the graph size is dramatically reduced, the computational time decreases dramatically.

Refinement The HeteroMILE framework's final 4.3stage focuses on refining the embeddings to derive the node embeddings of the original graph G_0 from the coarsened graph G_m . We start by addressing the simpler task of inferring the embeddings E_i for a graph G_i using its coarsened version G_{i+1} , the node embeddings E_{i+1} from G_{i+1} and the matching matrix $M_{i,i+1}$ as shown in Figure 3. Once this step is completed, we can systematically apply this approach to consecutive pairs of graphs, starting with G_m and progressing towards G_0 . As a result, we gradually obtain the node embeddings for G_0 . To accomplish this, we utilize a Heterogeneous Graph Convolutional Network model, which aids in refining the embeddings and improving their quality.

Heterogeneous Graph Convolutional Network for Refinement Learning: By leveraging the matching information between two consecutive graphs, specifically G_i and G_{i+1} , we can utilize a projection technique to transfer the node embeddings from the coarser graph G_{i+1} to the finer graph G_i . This process involves mapping the embeddings from G_{i+1} to the corresponding nodes in G_i .

$$E_i^p = M_{i,i+1}E_{i+1}$$

In this case, the embedding of a supernode is duplicated across its corresponding original node(s). The duplicated embeddings, denoted as E_i^p , correspond to the projected embeddings from G_{i+1} to G_i , or simply referred to as projected embeddings. These embeddings capture the structure information transferred from the coarser graph to the finer graph and serve as a repre**Algorithm 1** HeteroMILE Algorithm for Graph Embedding

Input: Given an input graph denoted as $G_0 = (V_0, E_0)$, a specified number of coarsening levels m, and a base embedding method represented as f_e . **Output:** Graph embeddings, denoted as E_0 , generated on graph G_0 .

- 1: The input graph G_0 is coarsened into a sequence of coarsened graphs $G_1, G_2, ..., G_m$ using either the Jaccard Similarity matching or LSH matching method
- 2: Apply the base embedding method f_e on the coarsest graph G_m to obtain the graph embeddings E_m .
- 3: Learn the weights W by optimizing the loss function.
- 4: for i = (m 1)...0 do
- 5: Compute the projected embeddings E_i^p for each graph G_i .
- 6: Compute the refined embeddings E_i using refinement models equations.
- 7: end for
- 8: Return the graph embeddings E_0 on G_0 .

sentation of the nodes in the refined embedding space. The simple projection method preserves some information from the node embeddings; however, it has a clear drawback in that if nodes are grouped and collapsed into a supernode during the coarsening stage, they will have identical embeddings. This issue becomes increasingly severe as the embedding refinement process is repeated multiple times, starting from G_m and working down to G_0 . To address this constraint, we introduce a refinement model that leverages the capabilities of a Heterogeneous Graph Convolutional Network (HGCN) [12].The proposed model enables the refinement of the embeddings by taking advantage of the projected embeddings E_i^p , which are derived from the initial embedding method, and the adjacency matrix A_i , which is obtained from the input graph. These components serve as input to the refinement process, enhancing the quality and accuracy of the embeddings. Using these inputs, the refinement model generates embeddings E_i for the graph G_i .

Consider O_N refers to a neighbor node type of O_i . V_i^O as the set comprising nodes of type O_i , while N_{O_i} represents the set of all neighbor node types of O_i (i.e. the set comprising nodes of type O_N). The relationship linking O_N and O_i is denoted as $\langle O_N, O_i \rangle$ or $O_N \to O_i$.

When considering the graph G, we take into account

the expedited approximation of heterogeneous graph convolution proposed in [12]. In this neural network model, the subsequent layer is

$$H_i^{O_i'} = \sigma(a_i^{Self-O_i} \cdot Z_{i,:}^{Self-O_i} + \sum_{O_N \in N_{O_i}} a_i^{O_N \to O_i} \cdot Z_{i,:}^{O_N \to O_i})$$

Here, σ represents the nonlinearity, and the subscript i(i, :) refers to the *i*-th node in V^{O_i} . The terms $a_i^{Self-O_i}$ and $a_i^{O_N \to O_i}$ denote the normalized attention coefficients for V^{O_i} and V^{O_N} , respectively. Z^{Self-O_i} denotes the projected representation of V^{O_i} , while $Z^{O_N \to O_i}$ represents the aggregated representations from V^{O_N} to V^{O_i} . The projection is computed as follows:

$$Z^{Self-O_i} = H^{O_i} \cdot W^{Self-O_i}$$
$$Z^{O_N \to O_i} = \hat{A}^{O_i - O_N} \cdot H^{O_N} \cdot W^{O_N \to O_i}, O_N \in N_{O_i}$$

In this context, H_i^O refers to the hidden representation of V_i^O in the preceding layer, \hat{A} indicates the adjacency matrix that has been row-normalized, and Wdenotes a weight matrix. In the initial scenario, specifically when layer n = 1, $H^{O_i}[1]$ is assigned as E^{O_i} , representing the node embedding.

Loss Function: The aim of the refinement model is to acquire the weights W for each layer and different node types through the utilization of a heterogeneous graph convolution model. The objective of this model is to generate predictions for the embeddings E_i of a given graph G_i . The "ground-truth" embeddings are obtained by applying a projected embedding E_i^p , and the loss function is formulated as the mean square error between the predicted embeddings and the groundtruth embeddings. In our approach, the weights Ware initially learned on the coarsest graph and then shared across all levels during the refinement process. This sharing of weights allows for efficient learning and promotes consistency in the embeddings across different levels. The loss function used in our approach is the mean square error, which quantifies the discrepancy between the predicted embeddings and the ground-truth embeddings. The loss is defined as follow:

$$L = \frac{1}{V_m} |E_m - H|^2$$

The detailed pipeline for HeteroMILE is presented in Algorithm 1.

5 Experiment

5.1 Experiment Setup :

Datasets: Experiments were performed on four real-world datasets, evaluating their performance by

link prediction and node classification. We used four datasets including AcademicII, DBLP, IMDB, OGB_MAG. OGB_MAG contains around 2M nodes and 20M edges. The dataset statistics are presented in Table 2

Baselines: We select metapath2vec [2] and GATNE [31] as baseline methods of heterogeneous graph embedding. To evaluate our HeteroMILE, we let it run in conjunction with all four coarsening policies (Jacc_max, Jacc_WRS, LSH (k=128), and LSH (k=256)) on top of metapath2vec and GATNE as the base models.

HeteroMILE-specific Settings: In our implementation of the HeteroMILE framework, we used an embedding dimensionality of 128 for the baseembedding method. We also experimented by varying the coarsening level, m, from 1 to 6 when applicable. For the heterogeneous graph convolution network model, we used four hidden layers and employed the ELU activation function [13]. The Adam Optimizer [14] was employed for training the model, with a learning rate of 0.01. The training process was carried out for 200 epochs.

Evaluation Metrics: The quality of the embeddings was assessed using multi-label node classification [16, 15] with F1-score and link prediction [29] with AU-ROC. A 10-fold cross-validation was conducted, where the embeddings were utilized as features for node classification. For link prediction, 10% of the edges were randomly selected to construct the test dataset, which were then removed from the training data. An equal number of negative samples were added to both the training and test sets. The efficiency of the methods was evaluated by measuring the end-to-end wallclock time in seconds for all the baselines. To ensure the accuracy of the results, five runs were generated for each coarsening level, and the average Micro-F1 and average AUROC were reported.

System Specifications: The experiments were performed on a Linux machine equipped with an Intel Xeon E5-2680 CPU (28 cores, 2.40GHz) and 128 GB RAM. The HeteroMILE framework was implemented in Python, adapting the original code from the authors [2, 31, 12] for the base embedding methods and utilizing the heterogeneous graph convolutional network model for the refinement phase. The refinement learning component was embedded using the PyTorch package.

5.2 HeteroMILE Framework Performance Figure 4 and Figure 5 show the performance of HeteroMILE on various datasets and coarsening levels for link prediction and node classification using different embedding approaches of metapath2vec and GATNE. In addition,



Figure 4: The performance of HeteroMILE using metapath2vec as the base embedding method varies as the number of coarsening levels increases, as depicted by the color scheme. The results for node classification, measured by the Micro-F1 score, and link prediction, measured by AUROC, are presented in the first and second rows, respectively. The running time, displayed in the third row, is plotted on a logarithmic scale. Notably, the running time lines of Jacc_WRS and Jacc_max overlap, similar to LSH (k=128) and LSH (k=256). "level = 0" represents the original embedding method without HeteroMILE.

we examined various coarsening strategies and design choices for HeteroMILE for link prediction and node classification. We observed the following when considering the coarsening level of m=0:

The scalability of HeteroMILE HeteroMILE presents a significant improvement in the efficiency of the base embedding method. This can be observed in both Figure 4 and Figure 5, where the utilization of one level of coarsening (m=1) results in an approximate 2x increase in speed compared to the original base embedding method, while maintaining comparable performance in terms of quality.

By further increasing the coarsening level to m=6, HeteroMILE achieves an impressive speedup of approximately 20 times compared to the original base embedding method. This efficiency gain becomes particularly evident in the case of the largest dataset, OGB_MAG. While the base embedding method would require over 7 days to complete, HeteroMILE accomplishes the execution in approximately 8 hours, exemplifying its ability to significantly expedite the graph embedding process.

Impact of HeteroMILE on embedding quality: From Figure 4 and 5 we can see that HeteroMILE can preserve and even improve link prediction and node classification performance across all datasets. On OGB_MAG and AcademicII with metapath2vec, it achieves an even better quality for coarsening levels m= 1 and m = 2. From m = 0 to m = 1, the Micro-F1



Figure 5: The performance of HeteroMILE using GATNE as the base embedding method varies as the number of coarsening levels increases, as depicted by the color scheme. The results for node classification, measured by the Micro-F1 score, and link prediction, measured by AUROC, are presented in the first and second rows, respectively. The running time, displayed in the third row, is plotted on a logarithmic scale. Notably, the running time lines of Jacc_WRS and Jacc_max overlap, similar to LSH (k=128) and LSH (k=256). "level = 0" represents the original embedding method without HeteroMILE.

score increases by more than 4%, and for m = 2, Micro-F1 remains the same as the original embedding. For link prediction on the AcademicII and DBLP datasets, we can find an obvious jump over m = 1 by around 5%. In addition, we achieved 1% to 2% increment on AUROC after coarsening to level m = 3. The better performance is even more obvious on GATNE embedding approach in Figure 5. As we can see on most of the datasets, HeteroMILE achieves better performance on both link prediction and node classification. On the AcamdeicII dataset, HeteroMILE improves the link prediction performance by 3% with coarsening level m = 1and achieves the same performance as GATNE at coarsening level m = 3. HeteroMILE also accelerates among all datasets compared to the original embedding methods.

Impact of varying coarsening levels on HeteroMILE: As shown in Figure 4 and 5, when coarsening level m is small (m = 1 and 2), HeteroMILE can preserve the performance and even improve the quality of embeddings on some datasets with a considerable reduction in time. In our experiments on the OGB-MAG and AcademicII datasets, we observe about 3% to 4% improvement in the Micro-F1 score when using HeteroMILE with m = 1 or m = 2 compared to the original embeddings. Specifically, on the AcademicII dataset, employing HeteroMILE with m = 1 leads to a remarkable 4.3% increase in the Micro-F1 score. No-

Datasets	Coarsening Method	F 1	AUROC	Coarsening Time
AcademicII	Jacc_WRS	0.8482	0.5984	464.21078
	Jacc_MAX	0.8503	0.5974	465.16261
	LSH(k=128)	0.8378	0.5817	38.884464
	LSH(k=256)	0.8422	0.5917	39.323140
DBLP	Jacc_WRS	0.9514	0.7121	355.23242
	Jacc_MAX	0.9526	0.7404	356.32588
	LSH(k=128)	0.9456	0.6914	22.213039
	LSH(k=256)	0.9488	0.7061	23.034396
IMDB	Jacc_WRS	0.5666	0.7313	9.2708401
	Jacc_MAX	0.5668	0.7317	9.2509674
	LSH(k=128)	0.5628	0.7177	2.6778357
	LSH(k=256)	0.5642	0.7235	2.7453285
OGB_MAG	Jacc_WRS	0.3700	0.5551	11235.346
	Jacc_MAX	0.3701	0.5612	11214.024
	LSH(k=128)	0.3588	0.5373	1338.1838
	LSH(k=256)	0.3640	0.5484	1379.7852

Table 3: The performance and coarsening time in seconds using different coarsening strategies



Figure 6: As the number of coarsening levels increases, the coarsening time of different coarsening strategies (LSH vs Jaccard Similarity) exhibits variations, which are measured on a logarithmic scale. "level = 0" represents the original embedding method without HeteroMILE.

Μ	LSH (sec)	Jacc (sec)	speedup
1	1084.419547	8721.358899	8.0424
2	1204.901603	9991.356486	8.2923
3	1338.183869	11214.02438	8.3801
4	1429.028702	12040.22179	8.4255
5	1509.925771	12869.49342	8.5233
6	1562.473834	13524.23359	8.6557

Table 4:Coarsening Time comparison between LSHand Jaccard Similarity on OGB_MAG dataset

tably, this improvement is achieved while reducing the computational time by half compared to the original embeddings. Furthermore, HeteroMILE demonstrates impressive efficiency gains, achieving more than 20x speedup while only experiencing a slight decrease in per-

formance. These findings highlight the effectiveness of HeteroMILE in significantly enhancing both the quality and efficiency of graph embedding tasks on heterogeneous graphs.

Overall, the experiments show that HeteroMILE not only significantly reduces the time consumption of embedding generation, but also preserves and even improves the performance of link prediction and node classification.

Impact of different coarsening strategies on HeteroMILE: HeteroMILE uses both Jaccard similarity matching and locality-sensitive hashing (LSH) matching. For the Jaccard similarity, we compared the two methods. One is to merge with the node that has maximum Jaccard similarity (Jacc_Max), and the other is to use Jaccard-weighted random sampling (WRS),



Figure 7: Running time comparison of HGT versus HeteroMILE with different coarsening level m



Figure 8: F_1 score comparison of Base Embedding versus HeteroMILE with different coarsening level m

which selects the node based on its relative Jaccard similarity weight. Table 3 shows that the Jaccard Max strategy achieves a better average Micro-F1 score compared to other coarsening approaches, whereas the result of WRS varies, but sometimes can achieve even better performance.

To further minimize the computational cost, we explore another coarsening strategy, locality-sensitive hashing (LSH), which significantly reduces the coarsening time. From Table 4, we can see that for the largest OGB_MAG dataset, the coarsening time of LSH is approximately 8 times faster than Jaccard similarity, but with a slight decrease in performance. Therefore, we tuned the number of hashing functions, which had little influence on time but improved the performance based on Figure 6. From Table 3, we can see that using the LSH strategy with a number of hashing functions k = 256 increased the performance by 3% than using k =

128, so that the performance of LSH is close to Jaccard Similarity.

Support of multiple embedding methods on HeteroMILE: HeteroMILE is a generic framework allowing different embedding methods on various realworld datasets. Using metapath2vec, we can see that HeteroMILE achieves the same performance on coarsening level m = 1 or m = 2 on node classification and improves the performance on link prediction. On GATNE, HeteroMILE achieves even better results on most of the datasets. On both link prediction and node classification, HeteroMILE with coarsening level m = 1 improves more than 3%. On both embedding approaches, HeteroMILE significantly speeds up while preserving the high-quality embedding performance.

Comparing HeteroMILE with HGT: Heterogenous Graph Transformer(HGT)[34] integrated a transformer architecture that relies on the inherent structure of the neural architecture to naturally include complex, multi-level connections between different types of nodes in the graph. This approach enables the model to autonomously discern the significance of these intricate patterns, even those that are not explicitly defined. Even though HGT improves the efficiency and efficacy of training compared to the regular GNN networks. However, it still requires a lot of memory usage to generate a promising result. Figure 7 shows the running time comparison between HeteroMILE and HGT on the OGB_MAG dataset. HeteroMILE using metapath2vec (M2V) as the base embedding approach with coarsening level m = 1 reduces the running time to half. Setting the coarsening level m = 6 achieves more than 20x speedup compared to HGT. Figure 8 shows that HeteroMILE improves the performance compared to the base embedding approaches of setting the coarsening level between 1 and 3. With coarsening level m = 6 within only 2% performance loss, while significantly speeding up the process.

6 Conclusion

In this work, we introduce HeteroMILE, a framework designed to enhance the efficiency of graph embedding methods in heterogeneous graphs. HeteroMILE achieves this by seamlessly integrating existing embedding techniques, thereby improving the scalability of the methods without requiring any modifications. By leveraging the properties of the graph and the chosen embedding method, HeteroMILE effectively reduces both the runtime and memory usage associated with the embedding process. Notably, HeteroMILE not only enhances efficiency but also often improves the quality of node embeddings. This framework's key contribution lies in its ability to reduce computational costs while preserving the graph structure, making it a valuable tool for graph embedding in heterogeneous settings.

References

- Sun, Y., Han, J., Yan, X., Yu, P. & Wu, T. Pathsim: Meta path-based top-k similarity search in heterogeneous information networks. *Proceedings Of The VLDB Endowment.* 4, 992-1003 (2011)
- [2] Dong, Y., Chawla, N. & Swami, A. metapath2vec: Scalable representation learning for heterogeneous networks. Proceedings Of The 23rd ACM SIGKDD International Conference On Knowledge Discovery And Data Mining. pp. 135-144 (2017)
- [3] Liang, J., Gurukar, S. & Parthasarathy, S. Mile: A multi-level framework for scalable graph embedding. *Proceedings Of The International AAAI Conference* On Web And Social Media. **15** pp. 361-372 (2021)
- [4] Chen, H., Perozzi, B., Hu, Y. & Skiena, S. Harp: Hierarchical representation learning for networks. Proceedings Of The AAAI Conference On Artificial Intelligence. 32 (2018)
- [5] Fu, G., Hou, C. & Yao, X. Learning topological representation for networks via hierarchical sampling. 2019 International Joint Conference On Neural Networks (IJCNN). pp. 1-8 (2019)
- [6] Maruhashi, K., Guo, F. & Faloutsos, C. Multiaspectforensics: Pattern mining on large-scale heterogeneous networks with tensor analysis. 2011 International Conference On Advances In Social Networks Analysis And Mining. pp. 203-210 (2011)
- [7] Guthrie, D., Allison, B., Liu, W., Guthrie, L. & Wilks, Y. A closer look at skip-gram modelling. *LREC.* 6 pp. 1222-1225 (2006)
- [8] Jafari, O., Maurya, P., Nagarkar, P., Islam, K. & Crushev, C. A survey on locality sensitive hashing algorithms and their applications. *ArXiv Preprint* arXiv:2102.08942. (2021)
- Karypis, G. & Kumar, V. Multilevelk-way partitioning scheme for irregular graphs. *Journal Of Parallel And Distributed Computing*. 48, 96-129 (1998)
- [10] Karypis, G. & Kumar, V. Parallel multilevel k-way partitioning scheme for irregular graphs. Proceedings Of The 1996 ACM/IEEE Conference On Supercomputing. pp. 35-es (1996)
- [11] LaSalle, D. & Karypis, G. Multi-threaded graph partitioning. 2013 IEEE 27th International Symposium On Parallel And Distributed Processing. pp. 225-236 (2013)
- [12] Yang, Y., Guan, Z., Li, J., Zhao, W., Cui, J. & Wang, Q. Interpretable and efficient heterogeneous graph convolutional network. *IEEE Transactions On Knowledge And Data Engineering*. (2021)
- [13] Rasamoelina, A., Adjailia, F. & Sinčák, P. A review of activation function for artificial neural network. 2020 IEEE 18th World Symposium On Applied Machine Intelligence And Informatics (SAMI). pp. 281-286 (2020)

- [14] Haji, S. & Abdulazeez, A. Comparison of optimization techniques based on gradient descent algorithm: A review. *PalArch's Journal Of Archaeology Of Egypt/Egyptology.* 18, 2715-2743 (2021)
- [15] Grover, A. & Leskovec, J. node2vec: Scalable feature learning for networks. Proceedings Of The 22nd ACM SIGKDD International Conference On Knowledge Discovery And Data Mining. pp. 855-864 (2016)
- [16] Perozzi, B., Al-Rfou, R. & Skiena, S. Deepwalk: Online learning of social representations. Proceedings Of The 20th ACM SIGKDD International Conference On Knowledge Discovery And Data Mining. pp. 701-710 (2014)
- [17] Deng, C., Zhao, Z., Wang, Y., Zhang, Z. & Feng, Z. Graphzoom: A multi-level spectral approach for accurate and scalable graph embedding. ArXiv Preprint arXiv:1910.02370. (2019)
- [18] Chen, H., Yin, H., Wang, W., Wang, H., Nguyen, Q. & Li, X. PME: projected metric embedding on heterogeneous networks for link prediction. *Proceedings* Of The 24th ACM SIGKDD International Conference On Knowledge Discovery & Data Mining. pp. 1177-1186 (2018)
- [19] Zhang, H., Qiu, L., Yi, L. & Song, Y. Scalable multiplex network embedding.. *IJCAI*. 18 pp. 3082-3088 (2018)
- [20] Tang, J., Qu, M. & Mei, Q. Pte: Predictive text embedding through large-scale heterogeneous text networks. *Proceedings Of The 21th ACM SIGKDD International Conference On Knowledge Discovery And Data Mining.* pp. 1165-1174 (2015)
- [21] Zhang, D., Yin, J., Zhu, X. & Zhang, C. Metagraph2vec: Complex semantic path augmented heterogeneous network embedding. Advances In Knowledge Discovery And Data Mining: 22nd Pacific-Asia Conference, PAKDD 2018, Melbourne, VIC, Australia, June 3-6, 2018, Proceedings, Part II 22. pp. 196-208 (2018)
- [22] Tu, K., Cui, P., Wang, X., Wang, F. & Zhu, W. Structural deep embedding for hyper-networks. *Proceedings* Of The AAAI Conference On Artificial Intelligence. **32** (2018)
- [23] Zhang, C., Song, D., Huang, C., Swami, A. & Chawla, N. Heterogeneous graph neural network. Proceedings Of The 25th ACM SIGKDD International Conference On Knowledge Discovery and Data Mining. pp. 793-803 (2019)
- Wang, X., Ji, H., Shi, C., Wang, B., Ye, Y., Cui, P. & Yu, P. Heterogeneous graph attention network. *The World Wide Web Conference*. pp. 2022-2032 (2019)
- [25] Zhu, Z., Xu, S., Tang, J. & Qu, M. Graphvite: A high-performance CPU-GPU hybrid system for node embedding. *The World Wide Web Conference*. pp. 2494-2504 (2019)
- [26] Qiu, J., Dhulipala, L., Tang, J., Peng, R. & Wang, C. LightNE: A Lightweight Graph Processing System for Network Embedding. SIGMOD. (2021)
- [27] Lerer, A., Wu, L., Shen, J., Lacroix, T., Wehrstedt,

L., Bose, A. & Peysakhovich, A. Pytorch-biggraph: A large scale graph embedding system. *Proceedings Of Machine Learning And Systems*. **1** pp. 120-131 (2019)

- [28] Akyildiz, T., Aljundi, A. & Kaya, K. GOSH: Embedding big graphs on small hardware. *ICPP*. pp. 1-11 (2020)
- [29] Kumar, A., Singh, S., Singh, K. & Biswas, B. Link prediction techniques, applications, and performance: A survey. *Physica A: Statistical Mechanics And Its Applications.* 553 pp. 124289 (2020)
- [30] Sathre, P., Gondhalekar, A. & Feng, W. Edge-Connected Jaccard Similarity for Graph Link Prediction on FPGA. 2022 IEEE High Performance Extreme Computing Conference (HPEC). pp. 1-10 (2022)
- [31] Cen, Y., Zou, X., Zhang, J., Yang, H., Zhou, J. & Tang, J. Representation learning for attributed multiplex heterogeneous network. Proceedings Of The 25th ACM SIGKDD International Conference On Knowledge Discovery & Data Mining. pp. 1358-1368 (2019)
- [32] He, Y., Zhang, Y., Gurukar, S. & Parthasarathy, S. WebMILE: democratizing network representation learning at scale. *Proceedings Of The VLDB Endowment.* **15** (2022)
- [33] Zhang, Y. & Stewart, C. Poster: Configuration management for internet services at the edge: A datadriven approach. 2020 IEEE/ACM Symposium On Edge Computing (SEC). pp. 155-157 (2020)
- [34] Hu, Z., Dong, Y., Wang, K. & Sun, Y. Heterogeneous graph transformer. *Proceedings Of The Web Confer*ence 2020. pp. 2704-2710 (2020)