

# Techniques for Measuring the Inferential Strength of Forgetting Policies

Patrick Doherty<sup>1</sup>, Andrzej Szalas<sup>1,2</sup>

<sup>1</sup>Department of Computer and Information Science, Linköping University, Sweden

<sup>2</sup>Institute of Informatics, University of Warsaw, Poland

patrick.doherty@liu.se, andrzej.szalas@{mimuw.edu.pl, liu.se}

## Abstract

The technique of *forgetting* in knowledge representation has been shown to be a powerful and useful knowledge engineering tool with widespread application. Yet, very little research has been done on how different policies of forgetting, or use of different forgetting operators, affects the inferential strength of the original theory. The goal of this paper is to define loss functions for measuring changes in inferential strength based on intuitions from model counting and probability theory. Properties of such loss measures are studied and a pragmatic knowledge engineering tool is proposed for computing loss measures using PROBLG. The paper includes a working methodology for studying and determining the strength of different forgetting policies, in addition to concrete examples showing how to apply the theoretical results using PROBLG. Although the focus is on forgetting, the results are much more general and should have wider application to other areas.

## 1 Introduction

The technique of forgetting (Lin and Reiter 1994) in knowledge representation has been shown to be a powerful and useful knowledge engineering tool with many applications (see Section 9 on related work).

Recently, it has been shown (Doherty and Szalas 2024) that two symmetric and well-behaved forgetting operators can be defined that provide a qualitative *best* upper and lower bound on forgetting in the following sense: it has been shown that strong or standard forgetting (Lin and Reiter 1994) provides a strongest necessary condition on a theory with a specific forgetting policy, while weak forgetting (Doherty and Szalas 2024) provides a weakest sufficient condition on a theory with a specific forgetting policy. In the former, one loses inferential strength relative to the original theory wrt necessary conditions, while in the latter one loses inferential strength wrt sufficient conditions. That is, some necessary (respectively, sufficient) conditions that can be expressed in the language of the original theory may be lost when the language becomes restricted after forgetting. A question then arises as to how these losses can be measured, both individually relative to each operator and comparatively relative to each other. The loss function used should be well-behaved and also quantitative, so as to ensure fine-grained measurement.

The goal of this paper is to define such measures in terms of loss functions, show useful properties associated with them, show how they can be applied, and also show how they can be computed efficiently. The basis for doing this will be to use intuitions from the area of model counting, both classical and approximate (Gomes, Sabharwal, and Selman 2021) and probability theory. In doing this, a pragmatic knowledge engineering tool based on the use of PROBLG (De Raedt and Kimmig 2015) will be described that allows for succinctly specifying the inferential strength of arbitrary theories, in themselves, and their associated losses using the dual forgetting operators. Initial focus is placed on propositional theories for clarity, but the techniques are then shown to generalize naturally to 1st-order theories, with some restrictions. Although the focus in this paper is on measuring inferential strength relative to forgetting operators, the techniques are much more general than this and should be applicable to other application areas including traditional model counting and approximate model counting through sampling.

Let's begin with describing an approach to measuring inferential strength using intuitions from model counting and then show how this measurement technique can be used in the context of forgetting. Consider the following simple theory,  $\mathcal{T}_c$ , extracted from an example considered in (Nayak and Levy 1995), where  $jcar$  stands for “Japanese car”,  $ecar$  – for “European car”, and  $fcars$  – for “foreign car”:

$$jcar \rightarrow (car \wedge reliable \wedge fcars) \quad (1)$$

$$ecar \rightarrow (car \wedge fast \wedge fcars) \quad (2)$$

$$fcars \rightarrow (ecar \vee jcar). \quad (3)$$

The theory partitions the set of all assignments of truth values to propositional variables occurring in a theory (*worlds*) into two sets: (i) the worlds satisfying  $\mathcal{T}_c$  (*models*), and (ii) the worlds not satisfying  $\mathcal{T}_c$ .

This suggests loss measures based on model counting to reflect theory strength. In such a case, the entailment strength can be measured by the number of models: the more models a theory  $\mathcal{T}$  has, the less conclusions it may entail, and the less models  $\mathcal{T}$  has, the more conclusions it possibly entails.

Though model counting enjoys quite successful implementations (Fichte, Hecher, and Hamiti 2021), it is generally complex (Gomes, Sabharwal, and Selman 2021) with challenging scalability issues.

In a more general case, the proportion between (i) and (ii) can be represented by the *probability of  $\mathcal{T}_c$* , another useful measure of inferential strength. Here we shall deal with probability spaces, where samples are worlds, events are sets of worlds specified by formulas (given as models of formulas), and the probability function is given by:

$$\mathcal{P}(\mathcal{T}) \stackrel{\text{def}}{=} \frac{|\{w \in \mathcal{W} : w \models \mathcal{T}\}|}{|\mathcal{W}|}, \quad (4)$$

where  $\mathcal{T}$  is a theory,  $\mathcal{W}$  is the set of worlds,  $\models$  is the satisfiability relation, and  $|\cdot|$  denotes the cardinality of a set. That is,  $\mathcal{P}(\mathcal{T})$  is the fraction between the number of models of  $\mathcal{T}$  and the number of all worlds.

For example, there are  $2^6 = 64$  assignments of truth values to propositional variables occurring in  $\mathcal{T}_c$  (worlds) and 13 such assignments satisfying  $\mathcal{T}_c$  (models of  $\mathcal{T}_c$ ), so  $\mathcal{P}(\mathcal{T}_c) = \frac{13}{64} = 0.203125$ . Since evaluating probabilities can, in many cases, be very efficient (at least when approximated by sampling), we focus on probabilities rather than model counting directly.<sup>1</sup> We will also define more general probabilistic-based loss measures, where one does not just count models with uniform distributions, but also pay attention to arbitrary probability distributions. This provides a much more flexible and general inferential measurement technique. These intuitions provide the basis for the specification of loss functions for forgetting operators, based on probabilistic measures on worlds, that measure the inferential strength of the original theory and the loss in inferential strength after applying a specific forgetting policy and operator.

Two forgetting operators considered in (Doherty and Szałas 2024), strong (standard) and weak forgetting, are shown to have very nice intrinsic properties in the following sense. Given a specific policy of forgetting, when applying that policy to a theory using the weak forgetting operator, the resultant models of the revised theory are a subset of models of the original theory. Similarly, when applying the strong forgetting operator to the same theory using the same forgetting policy, the resultant models of the revised theory are a superset of the models of the original theory. As mentioned previously, the revised theories characterize the weakest sufficient and strongest necessary theories relative to a specific forgetting policy. One can therefore measure the gap between the original theory and the theories resulting from forgetting in terms of the size of gaps between the mentioned sets of models associated with the revised theories. Intuitively, the larger the gaps are, the more one loses in terms of reasoning strength.

The motivations for desiring such measures include the following:

- no measures have yet been provided in the literature that indicate how reasoning strength changes when the technique of forgetting is used;
- such measures are useful indicators for belief base engineers when determining proper policies of forgetting for various applications;
- such measures are generally needed as one of the criteria that can be used for automated selection of symbols to forget, e.g., for optimizing a selected class of queries, when forgetting a particular choice of symbols can substantially increase the system’s performance without seriously affecting its inferential capabilities.

The working methodology for the approach is as follows, where details are provided in the paper:

1. Given a propositional theory  $\mathcal{T}$ , transform it into a stratified logic program using the transformation rules in Section 4.
2. Specify a probability distribution on worlds using the propositional facts (variables in  $\mathcal{T}$ ) as probabilistic variables in PROLOG, as described in Section 2.2.
3. Using PROLOG’s query mechanism, described in Section 2.2, query for the probability  $\mathcal{P}(\mathcal{T})$  of theory  $\mathcal{T}$ .

For forgetting, given a propositional theory  $Th(\bar{p}, \bar{q})$  and a forgetting policy  $\bar{p}$ :

4. Specify the 2nd-order theories,  $F^{NC}(Th(\bar{p}, \bar{q}); \bar{p})$  and  $F^{SC}(Th(\bar{p}, \bar{q}); \bar{p})$ , representing strong and weak forgetting, respectively, relative to the forgetting policy  $\bar{p}$ , as described in Section 2.1.
5. Apply quantifier elimination techniques to both theories as exemplified in Section 7, resulting in propositional theories without  $\bar{p}$ .
6. Apply steps 1 to 3 above to each of the theories.
7. The resulting probabilities  $\mathcal{P}(\mathcal{T})$ ,  $\mathcal{P}(F^{NC}(\mathcal{T}, \bar{p}))$ , and  $\mathcal{P}(F^{SC}(\mathcal{T}, \bar{p}))$ , for each of the three theories, can then be used to compute *loss* values for the respective losses of inferential strength associated with strong and weak forgetting relative to the original theory, as described in Section 3 and Section 6.

Generalization of this approach to the 1st-order case is described in Section 8.

The original results of this paper include:

- formal specification of model counting-based and probability-based loss measures for forgetting with an analysis of their properties;
- an equivalence preserving technique for transforming any formula of propositional or 1st-order logic into a set of stratified logic programming rules in time linear wrt the size of the input formula;
- algorithms for computing these loss measures implemented using PROLOG, a well-known probabilistic logic programming language.

PROLOG is chosen as a basis for this research since it provides a straightforward means of computing probabilistic

<sup>1</sup>Note that given the probability of a theory  $\mathcal{T}$  and the number of variables in the theory, the model count can easily be derived.

measures in general, and it also has built in mechanisms for doing approximate Inference by Sampling (constant time by fixing the number of samples). Consequently, both classical and approximation-based model counting techniques can be leveraged in defining loss measures.

The paper is structured as follows. In Section 2 we describe the essentials of strong and weak forgetting and the PROBLOG constructs used in the paper. In Section 3 we define model counting-based loss measures for forgetting and show their properties. Section 4 is devoted to how one computes model-counting-based loss measures using PROBLOG. In Section 5, probabilistic-based loss measures are defined which allow for arbitrary probability distributions over worlds rather than uniform distributions. Section 6 focuses on how one computes probabilistic-based loss measures using PROBLOG. In Section 7, we consider an example showing how both types of loss measures are used to describe loss of inferential strength relative to forgetting policies. Section 8 provides a generalization of the techniques to the 1st-order case. Section 9 is devoted to a discussion of related work. Section 10 concludes the paper with summary and final remarks. Finally, PROBLOG sources of all programs discussed in the paper are listed in the Appendix in ready to validate form using an online PROBLOG interpreter referenced in Section 10.

## 2 Preliminaries

### 2.1 Forgetting

For the sake of simplicity, we start with presenting ideas focusing on classical propositional logic with truth values  $\mathbb{T}$  (true) and  $\mathbb{F}$  (false), an enumerable set of propositional variables,  $\mathcal{V}^0$ , and standard connectives  $\neg, \wedge, \vee, \rightarrow, \equiv$ . We assume the classical two-valued semantics with truth values  $\mathbb{T}$  (true) and  $\mathbb{F}$  (false). To define forgetting operators, we shall also use 2nd-order quantifiers  $\exists p, \forall p$ , where  $p$  is a propositional variable. The meaning of quantifiers in the propositional context is:

$$\exists p(A(p)) \stackrel{\text{def}}{=} A(p = \mathbb{F}) \vee A(p = \mathbb{T}); \quad (5)$$

$$\forall p(A(p)) \stackrel{\text{def}}{=} A(p = \mathbb{F}) \wedge A(p = \mathbb{T}), \quad (6)$$

where  $A(p = expr)$  denotes a formula obtained from  $A$  by substituting all occurrences of  $p$  in  $A$  by expression  $expr$ .

A *theory* is a finite set of propositional formulas.<sup>2</sup> As usually, we identify propositional theories with conjunctions of their formulas. By a *vocabulary* (a *signature*) of  $\mathcal{T}$ , denoted by  $\mathcal{V}_{\mathcal{T}}^0$ , we mean all propositional variables occurring in  $\mathcal{T}$ .

By a *world for a theory (formula)*  $\mathcal{T}$  we mean any assignment of truth values to propositional variables in  $\mathcal{V}_{\mathcal{T}}^0$ :

$$w : \mathcal{V}_{\mathcal{T}}^0 \longrightarrow \{\mathbb{T}, \mathbb{F}\}. \quad (7)$$

The set of worlds of  $\mathcal{T}$  is denoted by  $\mathcal{W}_{\mathcal{T}}$ .

The rest of this subsection is based on (Doherty and Szałas 2024). Let  $\mathcal{T}(\bar{p}, \bar{q})$  be a propositional theory over a vocabulary consisting of propositional

variables in tuples  $\bar{p}, \bar{q}$ .<sup>3</sup> When forgetting  $\bar{p}$  in the theory  $\mathcal{T}h(\bar{p}, \bar{q})$ , one can delineate two alternative views, with both resulting in a theory expressed in the vocabulary containing  $\bar{q}$  only:

- *strong (standard) forgetting*  $F^{NC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p})$ : a theory that preserves the entailment of necessary conditions over vocabulary  $\bar{q}$ ;
- *weak forgetting*  $F^{SC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p})$ : a theory that preserves the entailment by sufficient conditions over  $\bar{q}$ .

As shown in (Doherty and Szałas 2024) (with Point 1 proved earlier, in (Lin and Reiter 1994)), we have the following theorem.

**Theorem 2.1.** *For arbitrary tuples of propositional variables  $\bar{p}, \bar{q}$  and  $\mathcal{T}h(\bar{p}, \bar{q})$ ,*

1.  $F^{NC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p}) \equiv \exists \bar{p}(\mathcal{T}h(\bar{p}, \bar{q}))$ .
2.  $F^{NC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p})$  is the strongest (wrt  $\rightarrow$ ) formula over vocabulary  $\bar{q}$ , preserving the entailment of necessary conditions over a vocabulary disjoint with  $\bar{p}$ .
3.  $F^{SC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p}) \equiv \forall \bar{p}(\mathcal{T}h(\bar{p}, \bar{q}))$ .
4.  $F^{SC}(\mathcal{T}h(\bar{p}, \bar{q}); \bar{p})$  is the weakest (wrt  $\rightarrow$ ) formula over vocabulary  $\bar{q}$ , preserving the entailment by sufficient conditions over a vocabulary disjoint with  $\bar{p}$ .  $\square$

From the Theorem 2.1 it easily follows that:

$$\begin{aligned} & \models F^{SC}(\mathcal{T}, \bar{p}) \rightarrow \mathcal{T}; \\ & \models \mathcal{T} \rightarrow F^{NC}(\mathcal{T}, \bar{p}). \end{aligned} \quad (8)$$

### 2.2 ProbLog

To compute the probability of  $\mathcal{T}$ , one can use the well-known probabilistic programming language PROBLOG (De Raedt and Kimmig 2015).

PROBLOG extends classical PROLOG with constructs specific for defining probability distributions as well as with stratified negation. It uses the symbol  $\setminus+$  for negation, where ‘ $\setminus$ ’ stands for ‘not’ and ‘+’ stands for ‘provable’. That is,  $\setminus+$  represents *negation as failure*. Stratification in logic programs and rule-based query languages is a well-known idea (see (Abiteboul, Hull, and Vianu 1995) and references there), so we will not discuss it here.

The PROBLOG constructs specific for defining probabilistic distributions used in the paper are listed below. For simplicity, we restrict the presentation to propositional logic, since we mainly focus on that in the paper. For additional features, the reader is referred to related literature, including (De Raedt et al. 2016; De Raedt and Kimmig 2015), in addition to other references there.

- To specify *probabilistic variables*, an operator ‘ $::$ ’ is used. The specification  $u :: p$  states that  $p$  is true with probability  $u$  and false with probability  $(1 - u)$ .

Probabilistic variables can be used to specify probabilistic facts and heads of probabilistic rules.

<sup>3</sup>When we refer to tuples of variables as arguments, like in  $\mathcal{T}h(\bar{p}, \bar{q})$ , we always assume that  $\bar{p}$  and  $\bar{q}$  are disjoint.

<sup>2</sup>Such finite sets of formulas are frequently called *belief bases*.

- *Queries* are used to compute probabilities. The probability of  $p$  is returned as the result of the query  $query(p)$  or  $subquery(p, P)$ , where  $P$  obtains the probability of  $p$ .
- *Annotated disjunctions* support choices. If  $u_1, \dots, u_k \in [0.0, 1.0]$  such that  $0.0 \leq u_1 + \dots + u_k \leq 1.0$ , and  $p_1, \dots, p_k$  are propositional variables, then an *annotated disjunction* is an expression of the form:

$$u_1 :: p_1; \dots; u_k :: p_k. \quad (9)$$

It states that at most one of  $u_1 :: p_1, \dots, u_k :: p_k$  is chosen as a probabilistic fact.

Let  $\mathcal{W}$  denote the set of all worlds assigning truth values to variables occurring in a given PROBLOG program. *Distribution semantics* assumes that probabilistic variables are independent. Probabilities of queried propositional variables are defined as the sum of probabilities of worlds, where they are true,

$$\mathcal{P}(p) \stackrel{\text{def}}{=} \sum_{w \in \mathcal{W}: w \models p} \mathcal{P}(w),$$

where probabilities of worlds,  $\mathcal{P}(w)$ , are evaluated as the product of probabilities  $u_i$  of probabilistic facts being true in these worlds and  $(1 - u_i)$  of those being false:

$$\mathcal{P}(w) \stackrel{\text{def}}{=} \prod_{1 \leq i \leq k, w \models p_i} u_i \quad * \quad \prod_{1 \leq i \leq k, w \not\models p_i} (1 - u_i).$$

Approximate evaluation of probabilities, with sampling, is available through PROBLOG’s interpreter using the command: `problog sample model.txt --estimate -N n` where ‘model.txt’ is a text file with a PROBLOG source, and ‘n’ is a positive integer fixing the number of samples.

### 3 Model-Counting-Based Loss Measures of Forgetting

Let  $mod(\mathcal{T})$  and  $\#\mathcal{T}$  denote the set of, and the number of models of  $\mathcal{T}$ , respectively.<sup>4</sup> As an immediate corollary of (8) we have:

$$mod(F^{SC}(\mathcal{T}, \bar{p})) \subseteq mod(\mathcal{T}) \subseteq mod(F^{NC}(\mathcal{T}, \bar{p})), \quad (10)$$

so also:

$$\#F^{SC}(\mathcal{T}, \bar{p}) \leq \#\mathcal{T} \leq \#F^{NC}(\mathcal{T}, \bar{p}). \quad (11)$$

For any propositional theory  $\mathcal{T}$ , the probability of  $\mathcal{T}$ ,  $\mathcal{P}(\mathcal{T})$ , is defined by Equation (4).

Model counting-based measures of forgetting can now be defined as follows.

**Definition 3.1.** *By model counting-based loss measures of forgetting we understand:*

$$loss_m^{NC}(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}(F^{NC}(\mathcal{T}, \bar{p})) - \mathcal{P}(\mathcal{T}); \quad (12)$$

$$loss_m^{SC}(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}(\mathcal{T}) - \mathcal{P}(F^{SC}(\mathcal{T}, \bar{p})); \quad (13)$$

$$loss_m^T(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}(F^{NC}(\mathcal{T}, \bar{p})) - \mathcal{P}(F^{SC}(\mathcal{T}, \bar{p})), \quad (14)$$

where the underlying distribution on worlds is assumed to be uniform.  $\square$

<sup>4</sup>Though the vocabulary after applying forgetting operators is a subset of the vocabulary of the original theory  $\mathcal{T}$ , for the sake of uniformity of presentation we assume that the considered worlds, thus models, too, are built over the vocabulary of  $\mathcal{T}$ .

Obviously,  $loss_m^T(\mathcal{T}, \bar{p}) = loss_m^{NC}(\mathcal{T}, \bar{p}) + loss_m^{SC}(\mathcal{T}, \bar{p})$ .

The intuition behind the  $loss_m$  measures is the following:

- (12) indicates how much, in terms of the number of models, strong forgetting differs from the original theory. In this case, the new theory is inferentially weaker than the original theory, and certain necessary conditions that were previously entailed by the original theory are no longer entailed by the resultant theory.
- (13) indicates how much, in terms of the number of models, weak forgetting differs from the original theory. In this case, the new theory is inferentially stronger than the original theory, although certain sufficient conditions that previously entailed the original theory no longer entail the resultant theory;
- (14) indicates what the total loss is measured as the size of the gap between strong and weak forgetting.

We have the following interesting properties of the defined loss measures.

**Proposition 3.2.** *Let  $*$   $\in \{NC, SC, T\}$ . Then for every propositional theory  $\mathcal{T}$ ,*

1.  $loss_m^*(\mathcal{T}, \bar{p}) \in [0.0, 1.0]$ ;
2.  $loss_m^*(\mathcal{T}, \bar{p}) = 0.0$ , when variables from  $\bar{p}$  do not occur in  $\mathcal{T}$ ; in particular:
  - (a)  $loss_m^*(\mathbb{F}, \bar{p}) = 0.0$ ;
  - (b)  $loss_m^*(\mathbb{T}, \bar{p}) = 0.0$ ;
3.  $loss_m^*(\bigvee_{1 \leq i} \mathcal{T}_i) = \sum_{1 \leq i} loss_m^*(\mathcal{T}_i, \bar{p})$ , when for all  $1 \leq i \neq j$ ,  $\mathcal{T}_i \wedge \mathcal{T}_j \equiv \mathbb{F}$ , i.e.,  $\mathcal{T}_i, \mathcal{T}_j$  represent mutually disjoint sets (countable additivity);
4.  $loss_m^*(\mathcal{T}, \bar{\epsilon}) = 0.0$ , where  $\bar{\epsilon}$  stands for the empty tuple;
5.  $loss_m^*(\mathcal{T}, \bar{p}) \leq loss_m^*(\mathcal{T}, \bar{q})$  when all propositional variables occurring in  $\bar{p}$  also occur in  $\bar{q}$  ( $loss_m^*(\ )$  is monotonic wrt forgotten vocabulary).  $\square$

Points 1, 2(a), 3 show that  $loss_m^*(\ )$  is a measure (with 3 being a well-known property of probability). Point 2 shows that nothing is lost when one forgets redundant variables (not occurring in the theory), in particular from  $\mathbb{F}$  or  $\mathbb{T}$ . Point 4 shows that  $loss_m^*(\ )$  is 0.0 when nothing is forgotten, and Point 5 shows that the more propositional variables are forgotten, the greater  $loss_m^*(\ )$  is.

### 4 Computing Model Counting-Based Loss Measures Using PROBLOG

To compute the probability of  $\mathcal{T}$ , we use PROBLOG. Though many #SAT solvers, counting the number of satisfying assignments exist – see (Fichte, Hecher, and Hamiti 2021; Chakraborty, Meel, and Vardi 2021; Gomes, Sabharwal, and Selman 2021; Soos and Meel 2019) and references there, we have chosen PROBLOG, since:

- it allows for computing exact probability as well as probability based on approximate (sampling based) evaluation;

- the resulting probability and loss measures can be used within a probabilistic logic programming framework in a uniform manner.

Let us start with an example of a PROBLOG program computing the probability of theory  $\mathcal{T}_c$  discussed in Section 1. We encode  $\mathcal{T}_c$  as Program 1. Indeed,  $r$  is equivalent to  $\neg jcar \vee (car \wedge reliable \wedge fcar)$ , i.e., to (1),  $s$  is equivalent to  $\neg ecar \vee (car \wedge fast \wedge fcar)$ , i.e., to (2), and  $u$  is equivalent to  $\neg fcar \vee jcar \veve ecar$ , i.e., to (3). Since  $t$  is the conjunction of  $r$ ,  $s$  and  $u$ , it is equivalent to  $\mathcal{T}_c$ . Therefore, the probability of  $t$ , computed by PROBLOG's interpreter, is equal to  $\mathcal{P}(\mathcal{T}_c)$ . Indeed, there are 6 propositional variables and each possible world encodes an assignment of truth values to these propositions with the probability 0.5. So there are  $2^6$  possible worlds, each having the probability  $\frac{1}{2^6}$ , and  $t$  is true in 13 of them (in those satisfying  $\mathcal{T}_c$ ). Accordingly, the PROBLOG interpreter answers that the probability of  $t$  (i.e., of  $\mathcal{T}_c$ ), is 0.203125.

---

Program 1: PROBLOG program for computing the probability of  $\mathcal{T}_c$ .

---

```

1 0.5 :: car. 0.5 :: reliable. 0.5 :: fast.
2 0.5 :: fcar. 0.5 :: jcar. 0.5 :: ecar.
3 r :- car, reliable, fcar.
4 r :- \+ jcar. % r represents (1)
5 s :- car, fast, fcar.
6 s :- \+ ecar. % s represents (2)
7 u :- jcar.
8 u :- ecar.
9 u :- \+ fcar. % u represents (3)
10 t :- r, s, u. % t represents (1) \wedge (2) \wedge (3)

```

---

Let us show how this approach works in general.

First, one has to define a transformation of an arbitrary propositional formula into a set of rules. Let  $A$  be a propositional formula. The rules of a *program*  $\pi_A^0$  encoding  $A$ , are constructed as shown in Table 1, where the  $r$  indexed with formulas are auxiliary propositional variables. The intended meaning of each auxiliary variable  $r_B$  is that it is equivalent to formula  $B$ . It is assumed that whenever a subformula occurs more than once, a single auxiliary variable is used to substitute all of its occurrences.

As an example of a transformation defined in Table 1, consider Program 2 transforming formula  $(q \equiv (p \wedge \neg q \wedge s))$  into a set of rules. Note that the number of auxiliary variables are often optimized while encoding longer expressions consisting of the same commutative connectives, such as a conjunction with more than two arguments,  $A_1 \wedge \dots \wedge A_k$ , with  $k > 2$ . In this case, one usually uses a single variable together with the rule  $r_{A_1 \wedge \dots \wedge A_k} :- r_{A_1}, \dots, r_{A_k}$ . An example of such an optimization is demonstrated in Line 3 of Program 2 which contains a conjunction of three literals. Similarly, one optimizes auxiliary variables in disjunctions with more than two arguments.

**Proposition 4.1.** *For every propositional formula  $A$ , the size of  $\pi_A^0$  is liner in the size of  $A$ .*

**Proof:** By construction of  $\pi_A^0$ , for each connective occurring in  $A$  at most 5 additional rules are added. If there are  $n$

Table 1: Transformation of an arbitrary propositional formula to a stratified logic program.

---

$\pi_A^0 \stackrel{\text{def}}{=} \left\{ \begin{array}{l} \emptyset; r_A \stackrel{\text{def}}{=} A \quad \text{when } A \text{ is a propositional variable;} \\ \pi_B^0. \\ r_A :- \backslash+ r_B. \\ \pi_C^0. \pi_D^0. \\ r_A :- \backslash+ r_C, r_D. \\ \pi_C^0. \pi_D^0. \\ r_A :- r_C. \\ \pi_C^0. \pi_D^0. \\ r_A :- r_D. \\ \pi_C^0. \pi_D^0. \\ r_A :- \backslash+ r_C. \\ r_A :- r_D. \\ \pi_C^0. \pi_D^0. \\ r_{A'} :- \backslash+ r_C. \\ r_{A''} :- r_D. \\ r_{A''} :- \backslash+ r_D. \\ r_{A''} :- r_C. \\ r_A :- r_{A'}, r_{A''}. \end{array} \right.$	<p>when <math>A = \neg B</math>;</p> <p>when <math>A = C \wedge D</math>;</p> <p>when <math>A = C \vee D</math>;</p> <p>when <math>A = C \rightarrow D</math>;</p> <p>when <math>A = C \equiv D</math>.</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

---

Program 2: A program  $\pi_{q \equiv (p \wedge \neg q \wedge s)}^0$  encoding the formula  $(q \equiv (p \wedge \neg q \wedge s))$ .

---

```

1 %  $\pi_p^0, \pi_q^0, \pi_s^0$  are empty;  $r_p \stackrel{\text{def}}{=} p, r_q \stackrel{\text{def}}{=} q, r_s \stackrel{\text{def}}{=} s$ 
2  $r_{\neg q} :- \backslash+ q.$ 
3  $r_{p \wedge \neg q \wedge s} :- p, r_{\neg q}, s.$ 
4  $r_{A'} :- \backslash+ q.$ 
5  $r_{A'} :- r_{p \wedge \neg q \wedge s}.$ 
6  $r_{A''} :- \backslash+ r_{p \wedge \neg q \wedge s}.$ 
7  $r_{A''} :- q.$ 
8  $r_{q \equiv (p \wedge \neg q \wedge s)} :- r_{A'}, r_{A''}.$ 

```

---

connectives then  $\pi_A^0$  contains at most  $5n$  rules.  $\square$

Similarly, it is easily seen that the following proposition also holds.

**Proposition 4.2.**

1. Let  $A$  be a propositional formula. Then each world  $w \in \mathcal{W}_A$  determines the values of auxiliary variables in  $\pi_A^0$ .
2. Given a world  $w \in \mathcal{W}_A$ , the truth values of auxiliary variables in  $\pi_A^0$  can be determined in time linear in the size of  $A$ .  $\square$

The following lemmas are used to show Theorem 4.5.

**Lemma 4.3.** *For every propositional formula  $A$ ,  $\pi_A^0$  is a stratified program.*

**Proof:** By construction of  $\pi_A^0$ : whenever a variable, say  $r_F$ , is negated by  $\backslash+$ , it appears in a body of a rule with variable  $r_E$  in its head such that  $F$  is a subformula of  $E$ . This provides a natural stratification reflecting the subformula nesting.  $\square$

One can now define a PROBLOG program,  $\Pi_A^m$ , computing the probability of a formula  $A$ .  $\Pi_A^m$  is specified by the following probabilistic facts and rules:

$$\Pi_A^m \stackrel{\text{def}}{=} \left| \begin{array}{l} 0.5 :: p_1. \dots 0.5 :: p_k. \\ \pi_A^0. \end{array} \right. \quad (15)$$

In this case,  $p_1, \dots, p_k$  are all variables occurring in  $A$  and the probability of  $A$  is given by querying for the probability of the auxiliary variable  $r_A$  representing the formula  $A$  in the transformation defined in Table 1.  $r_A$  is included in  $\pi_A^0$ , the stratified logic program associated with  $A$ .

Note that:

- $\Pi_A^m$  as specified by (15) is a PROLOG program since, by Lemma 4.3,  $\pi_A^0$  is a stratified logic program;
- the probabilities 0.5, assigned to propositional variables together with artificially assuming them independent, are used as a technical fix that ensures a uniform distribution on worlds and that guarantees the program specifies the number of models where  $A$  is true.

**Lemma 4.4.** *Let  $\pi_A^0$  occur in the program  $\Pi_A^m$ . Then for every subformula  $B$  of  $A$  occurring in the construction of  $\pi_A^0$ , we have that  $r_B$  is equivalent to  $B$ .*

**Proof** By Lemma 4.3,  $\pi_A^0$  specifies a stratified logic program. The semantics of stratified logic programs can be defined in terms of least models of rules expressed by implications. In a manner similar to the well-known completion technique (Clark 1977),

each  $r_B$  appearing in  $\pi_A^m$  in a head of a rule (or heads of two rules, as in the case of  $\vee$ ,  $\rightarrow$  and  $\equiv$ ), is actually equivalent to the rule's body (respectively, disjunction of bodies) due to the completion. This observation is used below when claiming equivalences, rather than implications, directly reflecting rules. (16)

We proceed by structural induction on  $B$ .

- When  $B$  is a propositional variable, say  $p$ , then  $\pi_B^0$ , being  $\pi_p^0$ , is  $\emptyset$ , and  $r_B \stackrel{\text{def}}{=} p$ , so the induction hypothesis is trivially true.
- When  $B$  is a negated formula, say  $\neg E$ , then  $r_B$ , being  $r_{\neg E}$ , is defined by  $r_{\neg E} := \neg r_E$ , where  $\neg$  stands for negation as failure. By observation (16),  $r_{\neg E} \equiv \neg r_E$ . Note that probabilistic clauses in  $\Pi_A^m$ , given in the first line of (15), assign truth values to all propositional variables occurring in  $A$ . Therefore, truth values of all subformulas of  $A$  are uniquely determined, in which case the only reason for a failure to prove an  $A$ 's subformula, say  $E$ , is the falsity of  $E$ . Therefore, in  $\Pi_A^m$ , negation as failure becomes classical negation. Thus  $r_B = r_{\neg E} \equiv \neg r_E \equiv \neg r_E$ . By the inductive assumption,  $r_E$  is equivalent to  $E$ , so  $\neg r_E$  is equivalent to  $\neg E$ , which shows the equivalence of  $r_B$  and  $B$ .
- When  $B$  is a non-negated subformula of  $A$  occurring in the construction of  $\pi_A^0$ , one uses the inductive assumption together with observation (16) and obvious tautologies of propositional logic to show that the auxiliary variable  $r_B$  is equivalent to  $B$ .  $\square$

The following theorem can now be shown, stating that programs  $\Pi_A^m$  can be used to calculate the probability measures for a formula (theory) which are then used as a basis for computing the values of the considered model counting-based measures.

**Theorem 4.5.** *For every propositional formula  $A$ , the probability of  $A$  is equal to the probability of  $r_A$  given by the PROLOG program  $\Pi_A^m$ , defined by (15).*

**Proof:** By Lemma 4.4,  $r_A$  is equivalent to  $A$ , so in every possible world,  $r_A$  is true iff  $A$  is true. Assume  $p_1, \dots, p_k$  are all propositional variables occurring in  $A$ . There are  $2^k$  possible worlds, so if  $A$  is true in  $n$  worlds, its probability is  $\frac{n}{2^k}$ . Each propositional variable is assigned the probability 0.5 in  $\Pi_A^m$ , so the probability of each possible world is  $\frac{1}{2^k}$ . Since  $r_A$  is true exactly in worlds where  $A$  is true and, by the distribution semantics (Sato 1995) used in PROLOG, the probability of  $r_A$  is the sum of probabilities of possible worlds where  $r_A$  is true, the value of  $r_A$  is:

$$r_A = \sum_{w \in \mathcal{W}: w \models r_A} \frac{1}{2^k} = \frac{n}{2^k} = \mathcal{P}(A). \quad \square$$

In order to compute measures  $loss_m^{NC}(\mathcal{T}, \bar{p})$ ,  $loss_m^{SC}(\mathcal{T}, \bar{p})$  and  $loss_m^T(\mathcal{T}, \bar{p})$ , it now suffices to run programs  $\Pi_{F^{NC}(\mathcal{T}, \bar{p})}^m$ ,  $\Pi_{F^{SC}(\mathcal{T}, \bar{p})}^m$  and  $\Pi_{\mathcal{T}}^m$ . The probabilities  $\mathcal{P}(F^{NC}(\mathcal{T}, \bar{p}))$ ,  $\mathcal{P}(F^{SC}(\mathcal{T}, \bar{p}))$  and  $\mathcal{P}(\mathcal{T})$  required in Definition 3.1 are given respectively as the probabilities of  $r_{F^{NC}(\mathcal{T}, \bar{p})}$ ,  $r_{F^{SC}(\mathcal{T}, \bar{p})}$  and  $r_{\mathcal{T}}$ .

## 5 Probabilistic-based Loss Measures of Forgetting

Model counting-based loss measures are defined using a uniform probability distribution on worlds. Probabilistic-based loss measures generalize this idea to allow arbitrary probability distributions on worlds. In general, it is assumed that an arbitrary probability distribution over worlds is provided, and one is then interested in probabilities of formulas wrt this distribution. Let us then assume that a probability distribution on worlds is given,  $\mathcal{P}_{\mathcal{W}} : \mathcal{W} \rightarrow [0.0, 1.0]$ . Let  $\mathcal{T}$  be a propositional theory. The probability of  $\mathcal{T}$  wrt  $\mathcal{P}_{\mathcal{W}}$  is then defined by:

$$\mathcal{P}_0(\mathcal{T}) \stackrel{\text{def}}{=} \sum_{w \in \mathcal{W}, w \models \mathcal{T}} \mathcal{P}_{\mathcal{W}}(w). \quad (17)$$

Probabilistic-based loss measures of forgetting are defined as follows.

**Definition 5.1.** *By probabilistic-based loss measures of forgetting wrt probability distribution  $\mathcal{P}_0(\cdot)$ , we understand:*

$$loss_p^{NC}(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}_0(F^{NC}(\mathcal{T}, \bar{p})) - \mathcal{P}_0(\mathcal{T}); \quad (18)$$

$$loss_p^{SC}(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}_0(\mathcal{T}) - \mathcal{P}_0(F^{SC}(\mathcal{T}, \bar{p})); \quad (19)$$

$$loss_p^T(\mathcal{T}, \bar{p}) \stackrel{\text{def}}{=} \mathcal{P}_0(F^{NC}(\mathcal{T}, \bar{p})) - \mathcal{P}_0(F^{SC}(\mathcal{T}, \bar{p})), \quad (20)$$

where the underlying distribution on worlds is assumed to be arbitrary.  $\square$

As in the case of model counting-based loss measures,  $loss_p^T(\mathcal{T}, \bar{p}) = loss_p^{NC}(\mathcal{T}, \bar{p}) + loss_p^{SC}(\mathcal{T}, \bar{p})$ . The following proposition also applies.

**Proposition 5.2.** For  $*$  in  $\{NC, SC, T\}$  and every propositional theory  $\mathcal{T}$ , the measures  $loss_p^*(\mathcal{T}, \bar{p})$  enjoy properties analogous to those stated in Points 1–5 of Proposition 3.2, where  $loss_m^*$  is substituted by  $loss_p^*$ .  $\square$

## 6 Computing Probabilistic-Based Loss Measures Using PROBLOG

As shown through research with probabilistic logic programming and applications of distribution semantics, the probability  $\mathcal{P}_{\mathcal{W}}$  can be specified by using PROBLOG probabilistic facts and rules (see, e.g., (De Raedt et al. 2016; Pfeffer 2016; Riguzzi 2023; Sato and Kameya 1997) and references there).

Assuming that  $\mathcal{P}_{\mathcal{W}}$  can be specified in PROBLOG, a PROBLOG program,  $\Pi_A^p$ , can be defined that computes the probability of  $A$  wrt probability distribution  $\mathcal{P}_{\mathcal{W}}$ :

$$\Pi_A^p \stackrel{\text{def}}{=} \left| \begin{array}{l} \text{PROBLOG specification of } \mathcal{P}_{\mathcal{W}} \\ \text{over } p_1, \dots, p_k. \\ 0.5 :: q_1. \dots 0.5 :: q_n. \\ \pi_A^0. \end{array} \right. \quad (21)$$

In this case,  $p_1, \dots, p_k$  are all probabilistic variables used to define the probability distribution  $\mathcal{P}_{\mathcal{W}}$  over worlds,  $p_1, \dots, p_k$  are pairwise independent,  $q_1, \dots, q_n$  are all variables occurring in  $A$  other than  $p_1, \dots, p_k$ , and the probability of  $A$  is given by querying for the probability of  $r_A$  which is included in  $\pi_A^0$ , the stratified logic program associated with  $A$ .

Computing probabilistic-based loss measures  $loss_p^{NC}(\mathcal{T}, \bar{p})$ ,  $loss_p^{SC}(\mathcal{T}, \bar{p})$  and  $loss_m^T(\mathcal{T}, \bar{p})$ , can now be done by analogy with the method described in the last paragraph of Section 4.

As an example, consider theory  $\mathcal{T}_c$  from Section 1, and assume that in a district of interest, the probability of *ecar* is 0.2 and the probability of *jcar* is 0.3. Assume further that the choices of *jcar* and *ecar* are independent and both exclude each other. Program 3 below can then be used, where an annotated disjunction (Line 1) is used to ensure a suitable probability distribution together with the mutual exclusion of *ecar*, *jcar*. In this case  $\mathcal{P}_0(\mathcal{T}_c)$  is 0.3125.

---

Program 3: PROBLOG program for computing the probability of  $\mathcal{T}_c$  when  $\mathcal{P}(\textit{ecar}) = 0.2$  and  $\mathcal{P}(\textit{jcar}) = 0.3$ .

---

1 0.2 :: *ecar*; 0.3 :: *jcar*.  
2 0.5 :: *car*. 0.5 :: *reliable*. 0.5 :: *fast*. 0.5 :: *fcar*.  
3 Lines 3–10 of Program 1

---

In summary, PROBLOG is used to specify a given probability on worlds and then rules of  $\pi$  are used for computing probabilistic-based loss measures.

Notice that, as in Section 4, the probabilistic facts  $0.5 :: q_i$  ( $1 \leq i \leq n$ ) serve as technical fix that enables generation of all possible worlds, where propositional variables whose probabilities are not given explicitly are also included (Line 2 in Program 3). The following proposition shows that adding these additional probabilistic facts  $0.5 :: q_i$ , does not

affect the probability distribution on formulas over a vocabulary consisting of only  $p_1, \dots, p_k$ .

In the following proposition,  $\mathcal{W}_{\bar{s}}$  denotes the set of worlds assigning truth values to propositional variables in  $\bar{s}$ .

**Proposition 6.1.** Let  $\mathcal{P}_{\bar{p}} : \mathcal{W}_{\bar{p}} \rightarrow [0.0, 1.0]$  be a probability distribution on  $\mathcal{W}_{\bar{p}}$ , specified by the first line in (21),  $\mathcal{P}_{\bar{p}, \bar{q}} : \mathcal{W}_{\bar{p}, \bar{q}} \rightarrow [0.0, 1.0]$  be the whole probability distribution specified in the first two lines of (21), and let  $\mathcal{T}$  be an arbitrary theory over vocabulary  $\bar{p}$ . Then  $\mathcal{P}_{\bar{p}}(\mathcal{T}) = \mathcal{P}_{\bar{p}, \bar{q}}(\mathcal{T})$ , where the probability of  $\mathcal{T}$  is defined by (17).

**Proof:** According to (17),

$$\mathcal{P}_{\bar{p}, \bar{q}}(\mathcal{T}) \stackrel{\text{def}}{=} \sum_{w \in \mathcal{W}_{\bar{p}, \bar{q}}, w \models \mathcal{T}} \mathcal{P}_{\bar{p}, \bar{q}}(w).$$

By (21), the probability of each  $q_i \in \bar{q}$  is  $\frac{1}{2}$ . There are  $n$  variables in  $\bar{q}$ , so  $\mathcal{P}_{\bar{p}, \bar{q}}(w) = \mathcal{P}_{\bar{p}}(w) * \frac{1}{2^n}$ . Therefore,

$$\mathcal{P}_{\bar{p}, \bar{q}}(\mathcal{T}) = \sum_{w \in \mathcal{W}_{\bar{p}, \bar{q}}, w \models \mathcal{T}} \mathcal{P}_{\bar{p}}(w) * \frac{1}{2^n}.$$

Every world  $w \in \mathcal{W}_{\bar{p}, \bar{q}}$  extends the corresponding world  $w' \in \mathcal{W}_{\bar{p}}$  by assigning truth values to each variable in  $\bar{q}$ . Each such world  $w'$  has then  $2^n$  copies in  $\mathcal{W}_{\bar{p}, \bar{q}}$  (each copy accompanied by a different assignment of truth values to variables in  $\bar{q}$ ). Therefore,

$$\begin{aligned} \mathcal{P}_{\bar{p}, \bar{q}}(\mathcal{T}) &= 2^n * \sum_{w \in \mathcal{W}_{\bar{p}}, w \models \mathcal{T}} \mathcal{P}_{\bar{p}}(w) * \frac{1}{2^n} \\ &= \sum_{w \in \mathcal{W}_{\bar{p}}, w \models \mathcal{T}} \mathcal{P}_{\bar{p}}(w) = \mathcal{P}_{\bar{p}}(\mathcal{T}). \end{aligned} \quad \square$$

## 7 Generating Loss Measures: an Example

In this example, we will use the theory  $\mathcal{T}_c$  and generate both model-counting-based and probabilistic-based loss measures for a forgetting policy  $\bar{p} = \{\textit{ecar}, \textit{jcar}\}$ .

In Section 4, it was shown how  $\mathcal{T}_c$  could be transformed into a stratified logic program where its probability variables were all assigned the value 0.5, reflecting a uniform probability on worlds. In this case,  $\mathcal{P}_0(\mathcal{T}_c) = 0.203125$ . In Section 6, a probability distribution where *ecar* and *jcar* were assigned probabilities, 0.2 and 0.3, respectively, resulted in  $\mathcal{P}_0(\mathcal{T}_c) = 0.3125$ .

In the next step,  $F^{NC}(\mathcal{T}_c; \textit{ecar}, \textit{jcar})$  and  $F^{SC}(\mathcal{T}_c; \textit{ecar}, \textit{jcar})$  need to be reduced to propositional theories using quantifier elimination. Using results in Section 2.1, forgetting *ecar* and *jcar* in theory  $\mathcal{T}_c$ , given by formulas (1)–(3) in Section 1, is defined by:

$$F^{NC}(\mathcal{T}_c; \textit{ecar}, \textit{jcar}) \equiv \exists \textit{ecar} \exists \textit{jcar} (\mathcal{T}_c); \quad (22)$$

$$F^{SC}(\mathcal{T}_c; \textit{ecar}, \textit{jcar}) \equiv \forall \textit{ecar} \forall \textit{jcar} (\mathcal{T}_c). \quad (23)$$

Using formulas (1)–(3) together with (22) and (23), it can be shown that:

- $F^{NC}(\mathcal{T}_c; ecar, jcar)$  is equivalent to:

$$\begin{aligned} \exists ecar \exists jcar ( & jcar \rightarrow (car \wedge reliable \wedge fcar) \wedge \\ & ecar \rightarrow (car \wedge fast \wedge fcar) \wedge \\ & fcar \rightarrow (ecar \vee jcar) ). \end{aligned} \quad (24)$$

Using (5) and some equivalence preserving transformations, one can show that (24) is equivalent to the propositional formula:<sup>5</sup>

$$fcar \rightarrow ((car \wedge fast) \vee (car \wedge reliable)). \quad (25)$$

- $F^{SC}(\mathcal{T}_c; ecar, jcar)$  is equivalent to:

$$\begin{aligned} \forall ecar \forall jcar ( & jcar \rightarrow (car \wedge reliable \wedge fcar) ) \wedge \\ \forall ecar \forall jcar ( & ecar \rightarrow (car \wedge fast \wedge fcar) \wedge \\ \forall ecar \forall jcar ( & fcar \rightarrow (ecar \vee jcar) ), \end{aligned} \quad (26)$$

i.e, to:

$$\begin{aligned} (car \wedge reliable \wedge fcar) \wedge \\ (car \wedge fast \wedge fcar) \wedge \neg fcar, \end{aligned} \quad (27)$$

which simplifies to  $\mathbb{F}$ .

The next step in the working methodology is to encode  $F^{NC}(\mathcal{T}_c; ecar, jcar)$  as a stratified logic program in PROBLOG. There is no need to encode  $F^{SC}(\mathcal{T}_c; ecar, jcar)$ , since it is equivalent to  $\mathbb{F}$  and its probability  $\mathcal{P}(F^{SC}(\mathcal{T}_c; ecar, fcar)) = 0.0$ .<sup>6</sup>

Program 4 below, contains rules encoding formula (25) which is equivalent to  $F^{NC}(\mathcal{T}_c; ecar, jcar)$ . In order to compute model-counting-based loss measures, probabilistic facts of the form  $0.5 :: p$  for each propositional variable  $p$  occurring in  $F^{NC}(\mathcal{T}_c; ecar, jcar)$ , i.e.,

$$0.5 :: car. 0.5 :: reliable. 0.5 :: fast. 0.5 :: fcar. , \quad (28)$$

are added to Program 4. To determine the probability  $\mathcal{P}(F^{NC}(\mathcal{T}_c; ecar, fcar))$ , one sets up a PROBLOG query about the probability of the auxiliary variable  $r_{fcar \rightarrow ((car \wedge fast) \vee (car \wedge reliable))}$ , defined in Lines 6–7 of Program 4. The query returns  $\mathcal{P}(F^{NC}(\mathcal{T}_c; ecar, fcar)) = 0.6875$ .

In order to compute the probabilistic-based loss measures, the probability distribution is the same as in Program 3. That is, rather than adding specification (28) to Program 4, one should instead add Lines 1–2 of Program 3. As before, the probability of  $F^{NC}(\mathcal{T}_c; ecar, jcar)$  is given by the probability of its encoding specified by the auxiliary variable  $r_{fcar \rightarrow ((car \wedge fast) \vee (car \wedge reliable))}$ . But in fact, this would not change the probability  $\mathcal{P}(F^{NC}(\mathcal{T}_c; ecar, jcar))$ . Since formula  $F^{NC}(\mathcal{T}_c; ecar, jcar)$  does not contain the variables

<sup>5</sup>Here we have actually used the DLS algorithm (Doherty, Łukaszewicz, and Szalas 1997) together with obvious simplifications of the resulting formula.

<sup>6</sup>Note that this is a limiting case for  $F^{SC}(\mathcal{T}_c; \bar{p})$ , where the resultant theory is inconsistent. Similarly, but not in this example, the limiting case for  $F^{NC}(\mathcal{T}_c; \bar{p})$  would be where the resultant theory is a tautology. In the former case, the forgetting policy is simply too strong, whereas in the latter, it would be too weak. What is important to observe is that the computational techniques proposed can identify these limiting cases, where probabilities of the resultant theories would be 0.0 and 1.0, respectively.

---

Program 4: PROBLOG program  $\pi_{(25)}^0$  encoding formula (25) equivalent to  $F^{NC}(\mathcal{T}_c; ecar, jcar)$

---

```

1  $r_{\neg fcar} :- \neg fcar.$ 
2  $r_{car \wedge fast} :- car, fast.$ 
3  $r_{car \wedge reliable} :- car, reliable.$ 
4  $r_{(car \wedge fast) \vee (car \wedge reliable)} :- r_{car \wedge fast}.$ 
5  $r_{(car \wedge fast) \vee (car \wedge reliable)} :- r_{car \wedge reliable}.$ 
6  $r_{fcar \rightarrow ((car \wedge fast) \vee (car \wedge reliable))} :- r_{\neg fcar}.$ 
7  $r_{fcar \rightarrow ((car \wedge fast) \vee (car \wedge reliable))} :- r_{(car \wedge fast) \vee (car \wedge reliable)}.$ 

```

---

$ecar, jcar$ , its probability is 0.6875 when computing both  $loss_m^T$  and  $loss_p^T$ .

The values of model counting-based as well probabilistic-based measures of forgetting for  $\mathcal{T}_c$  with forgetting policy  $\bar{p} = \{ecar, jcar\}$  are shown in Table 2.

Notice that, in this particular case,  $loss_m^{NC}$  is greater than  $loss_p^{NC}$ . That indicates that the reasoning strength wrt necessary conditions is lost to a greater extent when we count equally probable models, compared to the case when models get nonequal probabilities. At the same time, as regards reasoning with sufficient conditions,  $loss_m^{SC}$  is smaller than  $loss_p^{SC}$ . In this case, though the same models result from forgetting, the probabilistic measures indicate how the reasoning strength changes when real-world probabilities of models are taken into account.

Table 2: The values of measures of forgetting  $ecar, jcar$  from  $\mathcal{T}_c$ .

$loss_m^{NC}$	$loss_m^{SC}$	$loss_m^T$	$loss_p^{NC}$	$loss_p^{SC}$	$loss_p^T$
0.484375	0.203125	0.6875	0.375	0.3125	0.6875

## 8 Extending Measures to the 1st-Order Case

In this section we deal with classical 1st-order logic. For the 1st-order language we assume finite sets of relation symbols,  $\mathcal{R}$ , (1st-order) variables,  $\mathcal{V}_I$  and constants,  $\mathcal{C}$ . We assume that  $\mathcal{C}$  is the domain of 1st-order interpretations (worlds) we consider.

In addition to propositional connectives we also allow quantifiers  $\forall, \exists$  ranging over the domain.<sup>7</sup> We assume the standard semantics for 1st-order logic. A variable occurrence  $x$  is *bound* in a formula  $A$  when it occurs in the scope of a quantifier  $\forall x$  or  $\exists x$ . A variable occurrence is *free* when the occurrence is not bound. In the rest of this section we write  $A(\bar{x})$  to indicate that  $\bar{x}$  are all variables that occur free in  $A$ . Formula  $A$  is *closed* when it contains no free variables. By an *atomic formula* (*atom*, for short) we mean any formula of the form  $r(\bar{z})$ , where  $r \in \mathcal{R}$ , each  $z$  in  $\bar{z}$  is a variable in  $\mathcal{V}_I$  or a constant in  $\mathcal{C}$ . We write  $r(\bar{x})$  to indicate that  $\bar{x}$  are all variables in  $\bar{z}$ . By a *ground atom* we mean an atom containing only constants, if any.

A *1st-order theory* (*beliefbase*) is a finite set of closed 1st-order formulas,  $\mathcal{T}$ , understood as a single formula being the

<sup>7</sup>We avoid function symbols, as standard in rule-based query languages and underlying belief bases – see, e.g., (Abiteboul, Hull, and Vianu 1995).



conjunction of formulas in  $\mathcal{T}$ .<sup>8</sup> In what follows we always assume that the set of constants (thus the domain) consists of all and only constants occurring in the considered theory.<sup>9</sup>

The extension of definitions of model counting-based and probabilistic measures is now straightforward when we assume that worlds assign truth values to ground atoms rather than to propositional variables, and that *models* are worlds where given theories (formulas) are true. We shall use the same symbols  $loss_m^*$ ,  $loss_p^*$  to denote these measures.

In order to use PROBLOG, we have to adjust transformation of formulas provided in Table 1 to cover the extended logical language, as shown in Table 3, where rather than auxiliary variables, we use auxiliary relation symbols.

Table 3: Transformation of an arbitrary 1st-order formula to a stratified logic program. We specify variables  $\bar{x}$  to indicate the arguments of rules' heads and all free variables occurring in formulas in rules' bodies.

$\pi_A^I \stackrel{\text{def}}{=} \left\{ \begin{array}{l} \end{array} \right.$	$\emptyset; r_A \stackrel{\text{def}}{=} A$	when $A$ is an atom;
	$\frac{\pi_B^I}{r_A(\bar{x})} := \neg r_B(\bar{x})$	when $A = \neg B(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := r_C(\bar{x}), r_D(\bar{x})$	when $A = (C \wedge D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := r_C(\bar{x}), r_D(\bar{x})$	when $A = (C \vee D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := \neg r_C(\bar{x}), \neg r_D(\bar{x})$	when $A = (C \rightarrow D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := \neg r_C(\bar{x}), r_D(\bar{x})$	when $A = (C \equiv D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := \neg r_C(\bar{x}), \neg r_D(\bar{x})$	when $A = (C \equiv D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := \neg r_C(\bar{x}), r_D(\bar{x})$	when $A = (C \equiv D)(\bar{x})$ ;
	$\frac{\pi_C^I \cdot \pi_D^I}{r_A(\bar{x})} := \neg r_C(\bar{x}), \neg r_D(\bar{x})$	when $A = (C \equiv D)(\bar{x})$ ;
	$\frac{\pi_B^I}{r_A(\bar{x})} := r_B(y, \bar{x})$	when $A(\bar{x}) = \exists y B(y, \bar{x})$ ;
	$\frac{\pi_B^I}{r_A(\bar{x})} := \neg r_B(y, \bar{x})$	when $A(\bar{x}) = \exists y B(y, \bar{x})$ ;
	$\frac{\pi_B^I}{r_A(\bar{x})} := \neg r_B(y, \bar{x}), r_{A'}(\bar{x})$	when $A(\bar{x}) = \forall y B(y, \bar{x})$ ;

As an example, consider a formula  $A$ , being  $\forall x \exists y (s(x, y, a) \wedge t(y, b))$ , where  $x, y$  are variables and  $a, b$  are constants. The set of rules is given as Program 5.

Similarly to the transformation given in Table 1, for the transformation given in Table 3, we have:

- propositions analogous to Proposition 4.1; Point 1 of Proposition 4.2 and Proposition 6.1; linear complexity claimed in Point 2 of Proposition 4.2 does not hold in general – here we have deterministic polynomial time wrt the number of constants occurring in  $A$ ;<sup>10</sup>

<sup>8</sup>The assumption as to the closedness of formulas is used to simplify the presentation. It can be dropped in a standard manner by assuming an external assignment of constants to free variables.

<sup>9</sup>That, is, we assume the Domain Closure Axiom.

<sup>10</sup>The polynomial time complexity reflects the complexity of

Program 5: A program  $\pi_{\forall x \exists y (s(x, y, a) \wedge t(y, b))}^I$  encoding the formula  $\forall x \exists y (s(x, y, a) \wedge t(y, b))$ .

- 1 %  $\pi_{s(x, y, a)}^I, \pi_{t(y, b)}^I$  are empty;  $r_{s(x, y, a)} \stackrel{\text{def}}{=} s(x, y, a)$ ,  
 $r_{t(y, b)} \stackrel{\text{def}}{=} t(y, b)$
- 2  $r_{s(x, y, a) \wedge t(y, b)}(x, y) := s(x, y, a), t(y, b)$ .
- 3  $r_{\exists y (s(x, y, a) \wedge t(y, b))}(x) := r_{s(x, y, a) \wedge t(y, b)}(x, y)$ .
- 4  $r_{B'}(x) := \neg r_{\exists y (s(x, y, a) \wedge t(y, b))}(x)$ .
- 5  $r_{A'}() := r_{B'}(x)$ .
- 6  $r_{\forall x \exists y (s(x, y, a) \wedge t(y, b))}() := \neg r_{A'}()$ .

- lemmas analogous to Lemmas 4.3, 4.4;
- a theorem analogous to Theorem 4.5.

The construction of the PROBLOG program  $\Pi_A^m$  given in Equation (15) is adjusted to the 1st-order case by replacing probabilistic propositional variables by all ground atoms. That is, if  $A(\bar{x})$  is a 1st-order formula then  $\Pi_A^m$  becomes:

$$\Pi_A^m \stackrel{\text{def}}{=} \left\{ \begin{array}{l} 0.5 :: r_1(\bar{c}_{11}) \dots 0.5 :: r_l(\bar{c}_{1m_l}) \\ \dots \\ 0.5 :: r_l(\bar{c}_{l1}) \dots 0.5 :: r_l(\bar{c}_{lm_l}) \\ \pi_A^I(\bar{x}) \end{array} \right. \quad (29)$$

where  $r_1, \dots, r_l$  are all relation symbols in  $\mathcal{R}$ , for  $1 \leq i \leq l$ ,  $m_i$  is the arity of relation  $r_i$ , and  $r_1(\bar{c}_{11}), \dots, r_l(\bar{c}_{1m_l}), \dots, r_l(\bar{c}_{l1}), r_l(\bar{c}_{lm_l})$  are all ground atoms with constants occurring in  $A(\bar{x})$ .

The construction of the 1st-order version of  $\Pi_A^p$  adjusts the construction (21) as follows:

$$\Pi_A^p \stackrel{\text{def}}{=} \left\{ \begin{array}{l} \text{PROBLOG specification of } \mathcal{P}_{\mathcal{W}} \\ \text{over selected ground atoms specified} \\ \text{in (29)} \\ 0.5 :: a_1 \dots 0.5 :: a_n. \text{ where } a_1, \dots, a_n \\ \text{are all other ground atoms} \\ \pi_A^I \end{array} \right. \quad (30)$$

For the above construction we have a proposition analogous to Proposition 6.1.

Essentially, while extending our results to 1st-order logic, we simply switch from propositional variables to ground atoms, and then suitably deal with quantifiers. The resulting rules form stratified logic programs, so remain within the PROBLOG syntax. Though rules for quantifiers are similar to standard transformations like, e.g., in (Lloyd and Topor 1984), the use of auxiliary relation symbols allows us to properly deal with negation, by using it in a stratified manner.

Table 4 provides a comparison of transformations given in Tables 1 and 3 and the transformations of (Tseitin 1968) and (Lloyd and Topor 1984) from the point of view of properties needed in our paper. The rows ‘Sat’, ‘Equiv’, ‘#Models’ respectively indicate whether a given transformation preserves satisfiability, equivalence (in the sense of Lemma 4.4), and the number of models, ‘Size’ – the (worst case) size of the

1st-order queries (Abiteboul, Hull, and Vianu 1995): worlds can be seen as relational databases, and formulas – as queries to such databases.

Table 4: A comparison of properties of formula transformations considered in the paper.

	Tseitin	Lloyd-Topor	Table 1	Table 3
Sat	+	+	+	+
Equiv	-	-	+	+
#Models	+	-	+	+
Size	linear	exponential	linear	linear
1st-order	-	+	-	+
Stratified	-	-	+	+

resulting formula wrt the size of the input formula, ‘1st-order’ – whether the technique is applicable to 1st-order logic, and ‘Stratified’ – whether the result is stratified wrt negation.

## 9 Related Work

Strong (standard) forgetting,  $F^{NC}()$ , has been introduced in the foundational paper (Lin and Reiter 1994), where model theoretical definitions and analysis of properties of the standard  $forget()$  operator are provided. The paper (Lin and Reiter 1994) opened a research sub-area, summarized, e.g., in (van Ditmarsch et al. 2009) or more recently, e.g., in (Eiter and Kern-Isberner 2019; Doherty and Szałas 2024).

Numerous applications of forgetting include (van Ditmarsch et al. 2009; Beierle et al. 2019; Delgrande 2017; Del-Pinto and Schmidt 2019; Eiter and Kern-Isberner 2019; Zhao and Schmidt 2017; Zhao and Schmidt 2016; Gonçalves, Knorr, and Leite 2021; Wang, Wang, and Zhang 2013; Zhang and Foo 2006). In summary, while the topic of forgetting has gained considerable attention in knowledge representation, measures of forgetting have not been proposed in the literature. Notice that the weak forgetting operator  $F^{SC}()$ , introduced in (Doherty and Szałas 2024), plays a substantial role in definitions of measures  $loss_m^{SC}()$ ,  $loss_m^T()$ ,  $loss_p^{SC}()$  and  $loss_p^T()$ .

The model counting problem #SAT as well as #SAT-solvers have intensively been investigated (Fichte, Hecher, and Hamiti 2021; Chakraborty, Meel, and Vardi 2021; Gomes, Sabharwal, and Selman 2021; Soos and Meel 2019). The methods and algorithms for #SAT provide a solid alternative for implementing model counting-based measures. In particular projected model counting, such as that considered in (Lagniez and Marquis 2019; Lagniez, Lonca, and Marquis 2020; Gebser, Kaufmann, and Schaub 2009), could be used for computing the measures  $loss_m^{NC}()$  since variables are projected out using existential quantification which directly corresponds to standard forgetting (see Point 1 of Theorem 2.1).

We have chosen PROBLOG as a uniform framework for computing both model counting-based as well as probabilistic measures. This, in particular, has called for a new formula transformation, as shown in Table 1.

Our transformation is inspired by Tseitin’s transformation of arbitrary propositional formulas into the Conjunctive Normal Form (see, e.g., (Tseitin 1968; Kuitert et al. 2022; Lagniez, Lonca, and Marquis 2020)). Though Tseitin’s transformation preserves satisfiability, it does not preserve equivalence, nor does it lead to stratified clauses. On the other hand, our transformation preserves equivalence in the sense formulated in Lemma 4.4 and allows its use together with probabilistic logic programming languages that use stratified negation, including PROBLOG. For 1st-order quantifiers, the transformation shown in Table 3 uses a rather standard technique, similar to the well-known transformation of (Lloyd and Topor 1984). However, the use of auxiliary relation symbols again allows us to obtain stratified programs. On the other hand, the transformations of (Lloyd and Topor 1984) and alike could not be directly applied here as they generally do not ensure stratification. For a comparison of Tseitin’s, Lloyd-Topor and our transformations from the point of view of properties needed in our paper, see Table 4.

In the past decades there has been a fundamental interest in combining logic with probabilities, in particular in the form of probabilistic programming languages which could also be used for computing measures such as those proposed in our paper. Such languages include CLP(BN) (Costa et al. 2008), CP (Vennekens, Denecker, and Bruynooghe 2006), ICL (Poole 2008), LP<sup>MLN</sup> (Lee and Yang 2017), PRISM (Sato and Kameya 1997), PROPPR (Wang, Mazaitis, and Cohen 2013). For books surveying related approaches see (De Raedt et al. 2016; Pfeffer 2016; Riguzzi 2023). Our choice of PROBLOG is motivated by the rich and extensive research around it, both addressing theory and applications, as well as by its efficient implementation.

To deal with 2nd-order quantifiers, which are inevitably associated with forgetting, one can use a variety of techniques – see, e.g., (Gabbay, Schmidt, and Szałas 2008) and, for the context of forgetting, (Doherty and Szałas 2024). For eliminating 2nd-order quantifiers, in the paper we used the DLS algorithm (Doherty, Łukaszewicz, and Szałas 1997).

Measures considered in our paper are relatively independent of a particular formalism since we only require algorithms for counting models or probabilities over them. For example, forgetting is particularly useful in rule-based languages, when one simplifies a belief base to improve query-performance. This is especially useful for forgetting in Answer Set Programs (Gonçalves, Knorr, and Leite 2021; Wang, Wang, and Zhang 2013; Zhang and Foo 2006), where the corresponding entailment tasks, centering around necessary conditions, are typically intractable. Our approach can be adjusted to this framework using algorithms for counting ASP models, like those investigated in (Aziz et al. 2015).

## 10 Conclusions

Two types of loss measures have been proposed, one model counting-based and the other probabilistic-based, to measure the losses in inferential strength for theories where

different forgetting policies and operators are used. The model counting-based approach is based on an underlying uniform probability distribution for worlds, whereas the probabilistic-based approach is based on the use of arbitrary probability distributions on worlds. The former can be seen as a non-weighted approach and the latter as a weighted approach to measuring inferential strength and the losses ensued through the use of forgetting. A computational framework based on PROBLOG is proposed that allows analysis of any propositional or closed 1st-order theory with finite domains relative to different forgetting policies.

The framework proposed should have applications beyond forgetting. For instance, the example in Section 1 has been used in (Nayak and Levy 1995) as a means of modeling abstraction through the use of forgetting where one abstracts from  $ecar, jcar$ . The loss measures proposed in this paper should be useful as one criterion for determining degrees of abstraction. Earlier in the paper, it was pointed out that model counts can be derived directly from the model-counting-based approach to loss. It would be interesting to empirically compare the use of PROBLOG and the techniques proposed here with existing model counting approaches as mentioned in Section 9.

It should be mentioned that all PROBLOG programs specified in this paper are accessible for experimentation and verification using a special PROBLOG web interface.<sup>11</sup>

## Appendix A: PROBLOG Programs

### Program 1

The following program computes the probability of theory  $\mathcal{T}_c$  expressed by (1)–(3).

```
0.5::car. 0.5::reliable. 0.5::fast.
0.5::fcar. 0.5::jcar. 0.5::ecar.

r :- car, reliable, fcar.
r :- \+jcar. % r represents (1)
s :- car, fast, fcar.
s :- \+ecar. % s represents (2)
u:- jcar.
u:- ecar.
u:- \+ fcar. % u represents (3)
t :- r, s, u. % t represents (1)&(2)&(3)
query(t).
```

### Program 2

The following program computes the probability of the formula ( $q \equiv (p \wedge \neg q \wedge s)$ ).

```
0.5::p. 0.5::q. 0.5::s.

r_not_q :- \+ q.
r_p_and_not_q_and_s :- p, r_not_q, s.
r_A1 :- \+ q.
r_A1 :- r_p_and_not_q_and_s.
r_A2 :- \+ r_p_and_not_q_and_s.
```

<sup>11</sup>For the convenience of the reader, PROBLOG sources, in ready to copy and paste form are included in the appendix. They can be tested using the web interface accessible from <https://dtai.cs.kuleuven.be/problog/editor.html>.

```
r_A2 :- q.
r_q_equiv_p_and_not_q_and_s :- r_A1, r_A2.

query(r_q_equiv_p_and_not_q_and_s).
```

### Program 3

The following program computes the probability of theory  $\mathcal{T}_c$  expressed by (1)–(3) when  $\mathcal{P}(ecar) = 0.2$  and  $\mathcal{P}(jcar) = 0.3$ , and the choices of  $jcar$  and  $ecar$  exclude each other.

```
0.2::ecar; 0.3::jcar.
0.5::car. 0.5::reliable.
0.5::fast. 0.5::fcar.

r :- car, reliable, fcar.
r :- \+jcar. % r represents (1)
s :- car, fast, fcar.
s :- \+ecar. % s represents (2)
u:- jcar.
u:- ecar.
u:- \+ fcar. % u represents (3)
t :- r, s, u. % t represents (1)&(2)&(3)

query(t).
```

### Program 4

The following program computes the probability of the formula (25) equivalent to  $F^{NC}(\mathcal{T}_c; ecar, jcar)$ . To compute the probability of (25) when  $\mathcal{P}(ecar) = 0.2$ ,  $\mathcal{P}(jcar) = 0.3$ , and  $ecar, jcar$  exclude each other, it suffices to replace the first line by:  $0.2::ecar; 0.3::jcar$ .

```
0.5::ecar. 0.5::jcar.
0.5::car. 0.5::reliable.
0.5::fast. 0.5::fcar.

r_not_fcar :- \+ fcar.
r_car_and_fast :- car, fast.
r_car_and_reliable :- car, reliable.
r_car_and_fast_or_car_and_reliable
:- r_car_and_fast.
r_car_and_fast_or_car_and_reliable
:- r_car_and_reliable.
r_fcar_impl_car_and_fast_or_car_and_reliable
:- r_not_fcar.
r_fcar_impl_car_and_fast_or_car_and_reliable
:- r_car_and_fast_or_car_and_reliable.

query(r_fcar_impl_car_and_fast_or_car_and_reliable).
```

### Program 5

The following program computes the probability of formula  $\forall x \exists y (s(x, y, a) \wedge t(y, b))$ , assuming that the underlying domain consists of  $a, b$  (expressed by  $dom(a), dom(b)$ ).

```
0.5::s(X, Y, Z) :- dom(X), dom(Y), dom(Z).
0.5::t(X, Y) :- dom(X), dom(Y).

dom(a). dom(b).

r_sxya_and_tyb(X, Y) :- s(X, Y, a), t(Y, b).
r_exists_y_sxya_and_tyb(X)
:- r_sxya_and_tyb(X, Y).
```

```

r_B1(X) :- \+ r_exists_y_sxya_and_tyb(X).
r_A1 :- r_B1(X).
r_forall_x_exists_y_sxya_and_tyb :- \+ r_A1.

query(r_forall_x_exists_y_sxya_and_tyb).

```

## Acknowledgments

The research has been supported by a research grant from the ELLIIT Network Organization for Information and Communication Technology, Sweden.

## References

- Abiteboul, S.; Hull, R.; and Vianu, V. 1995. *Foundations of Databases*. Addison-Wesley.
- Aziz, R. A.; Chu, G.; Muise, C. J.; and Stuckey, P. J. 2015. Stable model counting and its application in probabilistic logic programming. In Bonet, B., and Koenig, S., eds., *Proc. 29th AAAI Conf. on AI*, 3468–3474. AAAI Press.
- Beierle, C.; Kern-Isberner, G.; Sauerwald, K.; Bock, T.; and Ragni, M. 2019. Towards a general framework for kinds of forgetting in common-sense belief management. *Künstliche Intell.* 33(1):57–68.
- Biere, A.; Heule, M.; van Maaren, H.; and Walsh, T., eds. 2021. *Handbook of Satisfiability*, volume 336 of *Frontiers in AI and Applications*. IOS Press.
- Chakraborty, S.; Meel, K. S.; and Vardi, M. Y. 2021. Approximate model counting. In Biere et al. (2021). 1015–1045.
- Clark, K. L. 1977. Negation as failure. In Gallaire, H., and Minker, J., eds., *Logic and Data Bases, Symposium on Logic and Data Bases*, Advances in Data Base Theory, 293–322. New York: Plenum Press.
- Costa, S. V.; Page, D.; Quazi, M.; and Cussens, J. 2008. CLP(BN): Constraint logic programming for probabilistic knowledge. In De Raedt et al. (2008), 156–188.
- De Raedt, L., and Kimmig, A. 2015. Probabilistic (logic) programming concepts. *Machine Learning* 100(1):5–47.
- De Raedt, L.; Frasconi, P.; Kersting, K.; and Muggleton, S., eds. 2008. *Probabilistic Inductive Logic Programming - Theory and Applications*, volume 4911 of *LNCS*. Springer.
- De Raedt, L.; Kersting, K.; Natarajan, S.; and Poole, D. 2016. *Statistical Relational Artificial Intelligence: Logic, Probability, and Computation*. Synthesis Lectures on AI and ML. Morgan & Claypool Pub.
- Del-Pinto, W., and Schmidt, R. A. 2019. Abox abduction via forgetting in ALC. In *The 33rd AAAI Conf. on AI*, 2768–2775.
- Delgrande, J. P. 2017. A knowledge level account of forgetting. *J. Artif. Intell. Res.* 60:1165–1213.
- Doherty, P., and Szałas, A. 2024. Dual forgetting operators in the context of weakest sufficient and strongest necessary conditions. *Artif. Intell.* 326:104036.
- Doherty, P.; Łukaszewicz, W.; and Szałas, A. 1997. Computing circumscription revisited. *J. Automated Reasoning* 18(3):297–336.
- Eiter, T., and Kern-Isberner, G. 2019. A brief survey on forgetting from a knowledge representation and reasoning perspective. *Künstliche Intell.* 33(1):9–33.
- Fichte, J. K.; Hecher, M.; and Hamiti, F. 2021. The model counting competition 2020. *ACM J. of Experimental Algorithmics* 26(13):1–26.
- Gabbay, D. M.; Schmidt, R. A.; and Szałas, A. 2008. *Second-Order Quantifier Elimination. Foundations, Computational Aspects and Applications*, volume 12 of *Studies in Logic*. College Publications.
- Gebser, M.; Kaufmann, B.; and Schaub, T. 2009. Solution enumeration for projected boolean search problems. In van Hove, W. J., and Hooker, J. N., eds., *6th Int. Conf. CPAIOR*, volume 5547 of *LNCS*, 71–86. Springer.
- Gomes, C. P.; Sabharwal, A.; and Selman, B. 2021. Model counting. In Biere et al. (2021). 993–1014.
- Gonçalves, R.; Knorr, M.; and Leite, J. 2021. Forgetting in Answer Set Programming - A survey. *Theory and Practice of Logic Programming* 1–43.
- Kuiter, E.; Krieter, S.; Sundermann, C.; Thüm, T.; and Saake, G. 2022. Tseitin or not Tseitin? The impact of CNF transformations on feature-model analyses. In *37th ASE, IEEE/ACM Int. Conf. on Automated Software Engineering*, 110:1–110:13.
- Lagniez, J.-M., and Marquis, P. 2019. A recursive algorithm for projected model counting. In *The 33rd AAAI Conf. on AI*, 1536–1543. AAAI Press.
- Lagniez, J.-M.; Lonca, E.; and Marquis, P. 2020. Definability for model counting. *Artif. Intell.* 281:103229.
- Lee, J., and Yang, Z. 2017.  $Lp^{min}$ , weak constraints, and P-log. In *Proc. 31st AAAI Conf.*, 1170–1177.
- Lin, F., and Reiter, R. 1994. Forget it! In *Proc. of the AAAI Fall Symp. on Relevance*, 154–159.
- Lloyd, J. W., and Topor, R. W. 1984. Making Prolog more expressive. *Journal of Logic Programming* 1(3):225–240.
- Nayak, P. P., and Levy, A. Y. 1995. A semantic theory of abstractions. In *Proc. 14th IJCAI 95*, 196–203. Morgan Kaufmann.
- Pfeffer, A. 2016. *Practical Probabilistic Programming*. Manning Pub. Co.
- Poole, D. 2008. The independent choice logic and beyond. In De Raedt et al. (2008), 222–243.
- Riguzzi, F. 2023. *Foundations of Probabilistic Logic Programming. Languages, Semantics, Inference and Learning*. Series in Software Engineering. River Publishers.
- Sato, T., and Kameya, Y. 1997. PRISM: A language for symbolic-statistical modeling. In *Proc. of the 15th IJCAI*, 1330–1339. Morgan Kaufmann.
- Sato, T. 1995. A statistical learning method for logic programs with distribution semantics. In *Proc. 12th Int. Conf. on Logic Programming ICLP*, 715–729.
- Soos, M., and Meel, K. S. 2019. BIRD: engineering an efficient CNF-XOR SAT solver and its applications to approximate model counting. In *33rd AAAI*, 1592–1599.

- Tseitin, G. S. 1968. On the complexity of derivation in propositional calculus. In *Structures in Constructive Mathematics and Mathematical Logic*, 115–125. Steklov Mathematical Institute.
- van Ditmarsch, H.; Herzig, A.; Lang, J.; and Marquis, P. 2009. Introspective forgetting. *Synth.* 169(2):405–423.
- Vennekens, J.; Denecker, M.; and Bruynooghe, M. 2006. Representing causal information about a probabilistic process. In Fisher, M.; van der Hoek, W.; Konev, B.; and Lisitsa, A., eds., *Proc. Logics in AI, 10th JELIA*, volume 4160 of *LNCS*, 452–464. Springer.
- Wang, W. Y.; Mazaitis, K.; and Cohen, W. W. 2013. Programming with personalized pagerank: a locally groundable first-order probabilistic logic. In He, Q.; Iyengar, A.; Nejdl, W.; Pei, J.; and Rastogi, R., eds., *22nd ACM Int. Conf. on Information and Knowledge Management*, 2129–2138.
- Wang, Y.; Wang, K.; and Zhang, M. 2013. Forgetting for Answer Set Programs revisited. In Rossi, F., ed., *Proc. IJCAI'2013*, 1162–1168.
- Zhang, Y., and Foo, N. Y. 2006. Solving logic program conflict through strong and weak forgettings. *Artif. Intell.* 170(8):739–778.
- Zhao, Y., and Schmidt, R. A. 2016. Forgetting concept and role symbols in  $\mathcal{ALCCOQH}\mu^+(\nabla, \sqcap)$ -ontologies. In Kambhampati, S., ed., *Proc. IJCAI'2016*, 1345–1352.
- Zhao, Y., and Schmidt, R. A. 2017. Role forgetting for  $\mathcal{ALCCOQH}$  (universal role)-ontologies using an Ackermann-based approach. In Sierra, C., ed., *Proc. IJCAI'17*, 1354–1361.