SEVENLLM : Benchmarking, Eliciting, and Enhancing Abilities of Large Language Models in Cyber Threat Intelligence

Hangyuan Ji¹, Jian Yang¹, Linzheng Chai¹, Chaoren Wei¹, Liqun Yang¹, Yunlong Duan¹, Yunli Wang¹, Tianzhen Sun¹, Hongcheng Guo¹, Tongliang Li¹, Changyu Ren¹, Zhoujun Li¹

¹State Key Laboratory of Complex & Critical Software Environment, Beihang University {jhy_1,jiaya, challenging, weichaoren, lqyang, tonyliangli, cyren, lizj}@buaa.edu.cn;

Abstract

To address the increasing complexity and frequency of cybersecurity incidents emphasized by the recent cybersecurity threat reports with over 10 billion instances, cyber threat intelligence (CTI) plays a critical role in the modern cybersecurity landscape by offering the insights required to understand and combat the constantly evolving nature of cyber threats. Inspired by the powerful capability of large language models (LLMs) in handling complex tasks, in this paper, we introduce a framework to benchmark, elicit, and improve cybersecurity incident analysis and response abilities in LLMs for Security Events (called SEVEN-LLM). Specifically, we create a high-quality bilingual instruction corpus by crawling cybersecurity raw text from cybersecurity websites to overcome the lack of effective data for information extraction. Then, we design a pipeline to auto-select tasks from the tasks pool and convert the raw text into supervised corpora comprised of question and response. The instruction dataset SEVENLLM-Instruct is used to train cybersecurity LLMs with the multitask learning objective (28 well-designed tasks) for augmenting the analysis of cybersecurity events. Extensive experiments in our curated benchmark (SEVENLLM-Bench) demonstrate that SEVENLLM performs more sophisticated threat analysis and fortifies defenses against the evolving landscape of cyber threats¹.

1 Introduction

In the rapidly evolving landscape of cyberspace, the intricate and diverse nature of cybersecurity postures is undergoing exponential growth in complexity (Zhao et al., 2020; Arp et al., 2022; Alam, 2022). The digital realm is witnessing an unprecedented surge in cybersecurity incidents, with over 10 billion events impacting networks globally, which




Figure 1: Comparison between GPT-3.5 and our proposed model SEVENLLM.

presents an immense challenge for cybersecurity professionals and analysts.

Cyber threat intelligence (CTI) (Liu and Zhan, 2023; Motlagh et al., 2024; Arazzi et al., 2023; Siracusano et al., 2023) is proposed to understand and anticipate cyber threats for cybersecurity defense. However, traditional approaches often lack the requisite background knowledge needed for effective investigation. Large language models (LLMs) (Touvron et al., 2023; Schick and Schütze, 2021; Achiam et al., 2023) present a groundbreaking shift in the capabilities of understanding and generating language-based content. Domain-specific LLMs by instruction tuning further improve the specific field, such as code and math. For CTI, there is still no comprehensive work to encompass all required parts comprised of instruction corpora, domainspecific LLMs, and the evaluation benchmark.

In this paper, we introduce a framework to benchmark, elicit, and improve cybersecurity incident analysis and response abilities in **LLMs** for **Security Events** (called **SEVENLLM**). In Figure 1, the fine-tuned SEVENLLM with fewer param-

^{*}Corresponding Author.

¹https://github.com/CSJianYang/ SEevenLLM

eters can get a more complete and professional response compared to the strong common LLM GPT-3.5, emphasizing the importance of domainspecific LLM for CTI. Specifically, we address the scarcity of high-quality, task-specific datasets for security event analysis by curating an extensive bilingual (English and Chinese) corpus of cybersecurity incident reports. To construct the supervised question-answer pair, we first use the LLM (GPT-4) to generate the candidate tasks, and then human experts correct the tasks based on threat intelligence analysis criteria and focal points proposed by security organizations and institutions, such as MITRE² and OASIS CTI TC³, to form a task pool. Given the cybersecurity raw text, we prompt the LLM to select the proper task from the task pool and then simultaneously generate the query and corresponding response of the chosen task, where we use Select-Instruct to generate the instruction corpus SEVENLLM-Instruct. Opensource LLMs tailored for cyber threat intelligence based on different base models are fine-tuned on the SEVENLLM-Instruct with multi-task learning. To effectively evaluate SEVENLLM for cyber threat intelligence, we construct an evaluation benchmark SEVENLLM-Bench to comprehensively evaluate the performance of LLMs for CTI, thereby bridging the gap between the common field and the cybersecurity field in understanding and generation.

The main contributions are summarized as:

- We create a high-quality bilingual multi-task instructional corpora SEVENLLM-Instruct by crawling cybersecurity texts and adopting the dataset construction method Select-Instruct to address the data scarcity of CTI, where the dataset ensures the practical utility and relevance of the dataset in real-world scenarios.
- Based on the open-source base LLMs, SEV-ENLLM tailored for cyber threat intelligence is fine-tuned on SEVENLLM-Instruct to assist in the automated and intelligent processing of security incidents. SEVENLLM aims to streamline the analysis process and reduce the reliance on human expertise, thus accelerating and enhancing the capabilities of analysts in threat identification and response.
- To fill in the gaps in the evaluation for cyber

threat intelligence, we construct an evaluation benchmark SEVENLLM-Bench comprised of multiple-choice questions and query-answer questions for assessing the performance of LLMs within the context of cybersecurity.

2 SEVENLLM

2.1 Model Overview

Figure 2, we propose a framework (SEVENLLM) for assessing and enhancing the capabilities of LLMs in analyzing and responding to cybersecurity incidents, specifically referred to as security events. First, we collect extensive bilingual (English and Chinese) collection of cybersecurity incident reports. To create supervised question-answer pairs, we initially employ LLMs to produce potential tasks, which are then refined by human experts to create a collection of tasks (a task pool). Using raw cybersecurity texts, we prompt the LLM to pick an appropriate task from this collection and then generate both the query and its answer for the selected task (Select-Instruct). This process involves using Select-Instruct to create an instruction corpus SEVENLLM-Instruct. The open-source LLMs (e.g. Llama and Qwen) are further fine-tuned on SEVENLLM-Instruct with multi-task learning objectives tailored for cyber threat intelligence (CTI). To accurately assess the effectiveness of SEVENLLM for CTI purposes, we establish a benchmark evaluation, SEVENLLM-Bench, designed to thoroughly evaluate the performance of LLMs in CTI, which aims to close the gap in understanding and generation capabilities between the general and cybersecurity domains.

2.2 Benchmark Construction

Data Collection and Preprocessing To construct the instruction corpora of the cyber threat intelligence (CTI), we amass a collection of over ten thousand cybersecurity incident websites from leading domestic and international cybersecurity vendors, ensuring the relevance and breadth of the cybersecurity incidents encompassed (from 2004 to now). The collection data includes official reports from the websites of security vendors and published media news by internet companies. We duplicate the gathered reports by title and extract text-based information from the different categories of security event reports after removing low-quality

²https://attack.mitre.org/
3https://oasis-open.github.io/
cti-documentation/




Figure 2: Overview of SEVENLLM. By crawling different formats of files from the Internet, we collect bilingual (English and Chinese) collection of cybersecurity incident reports. First, we adopt LLMs to produce potential tasks and refine them to create a task pool. Given raw cybersecurity texts, we use Select-Instruct select a proper task and generate the query and its answer. The open-source LLMs are further fine-tuned on SEVENLLM-Instruct with multi-task learning objectives tailored for CTI. A curated CTI evaluation benchmark SEVENLLM-Bench is created to compare SEVENLLM with other baselines.

data with heuristic rules. Finally, the curated collection contains 6,706 English and 1,779 Chinese high-quality reports as the seeds.

Select-Instruct To improve the quality and informational value of the generated instruction-answer datasets, we have improved the self-instruct(Wang et al., 2023a) method specifically for the task of cybersecurity incident analysis. Our approach involves two steps. In the first step, we input the raw corpus and use carefully designed prompts to enable the LLM to select a specified number and format of tasks from a task pool, producing task seeds. In the second step, we input both the task seeds and the raw corpus, requiring the LLM to extract valuable portions of the corpus based on the tasks to generate instructions and corresponding answers. During the generation of instructions and responses, we also require the LLM to provide its reasoning process and justification(Jin et al., 2024). Testing results demonstrate that, using our method, out of 44,240 generated data points, there were only 24 erroneous data points and 37 empty outputs. In contrast, the self-instruct method, when used to generate instructions and answers for all tasks, produced 41,296 data points, of which 78 were erroneous and 1,182 were empty outputs.

SEVENLLM-Instruct The analysis of cybersecurity incidents is categorized into understanding and generation tasks, encompassing 28 subcategories in Figure 2. The understanding task in cybersecurity incident analysis involves transforming unstructured data into structured data by extracting entities and relationships from cybersecurity incidents, aiming at acquiring well-defined knowledge such as identifying advanced persistent threat (APT) groups, attack techniques, and the relationships between APT groups and techniques. For cybersecurity professionals, the generation tasks (e.g. generating summaries and suggesting mitigation measures) provide straightforward knowledge for the general analyst and are used for data fusion and information compression of cybersecurity incident content. In Figure 2, we randomly select the raw text feed into the LLM to generate the task name and then correct them with the human experts to design 13 understanding tasks and 15 generation tasks. Given the cybersecurity-related raw text, we use Select-Instruct method to generate the supervised instruction corpora SEVENLLM-Instruct.

SEVENLLM-Bench We use multiple-choice questions and query-answer questions to evaluate the performance of SEVENLLM in CTI. In Table 1,

	Problem	,	Zh	En			
	Problem		Len	Size	Len		
Seed	Raw	1779	4798	6706	900		
Train	MCQ QA	3000 41218	347/1 384/196	3000 44183	121/1 184/90		
Test	MCQ QA	50 600	364/1 450/236	50 600	138/1 167/91		

Table 1: Statistics of SEVENLLM-Bench. The training data contains two types of questions: multiple-choice questions (MCQ) and query-answer questions(QA). The supervised data derives from high-quality raw texts (Seed) collected from the Internet. Here, we calculate the length of Chinese at the token level and the length of English by splitting space tokens.

SEVENLLM-Instruct contains nearly 90K samples and SEVENLLM-Bench has 1300 test samples. Especially, for the multiple-choice question (MCQ), 364/1 denotes that the length of the prompt is 364 and the length of the output is 1 (A, B, C, or D).

2.3 Large Language Model for CTI

Given a cybersecurity raw text $c \in L_{all}$ = $\{D_{L_i}^r\}_{i=1}^m$ (L_i is the language of c and L_{all} contains Chinese and English in our work), we prompt the LLM \mathcal{M} to select the proper task T_k , where $T_k \in T_{all} = \{T_j\}_{j=1}^n$ and the task pool T_{all} contains 13 understanding tasks and 15 generation tasks, as shown in Table 2. Conditioned on {Predefined tasks} and {Cybersecurity-related Raw Text, we use the prompt "Based on the content and tasks of cyber security events, please generate suitable task category and the reason" in Figure 2 to generate the target task T_k with the chosen reason. Then, we use the raw text c and the chosen task T_k to generate the query, the corresponding response, and the thought q_k, a_k, t_k to construct the supervised fine-tuned corpora $D_{all} = \{D_i\}_{i=1}^m$, where D_{all} is the supervised instruction corpus containing m tasks and $(q_k, a_k) \in D^s_{all}$. In Figure 2, we feed the prompt "{Cybersecurity-related Raw Text. {Task Definition}. Based on the content and the task of cyber security events, please generate structured data including input, instruction, thought, and output" into the LLM \mathcal{M} to generate the supervised pair q_k , a_k , t_k . The CoT generation process can be described as:

$$P(a_k, t_k | q_k) = \prod_{j=1}^{L} P(a_k^j | a_k^{< j}; q_k, t_k, \mathcal{M})$$
(1)

where t_k is the reasoning step (Wei et al., 2022; Jin et al., 2024) for the answer a_k . a_k^j is the j-th token of the answer a_k .

2.4 Multitask Instruction Tuning

Given the bilingual multitask instruction corpora $D_{all} = \{D_i\}_{i=1}^m$, where D contains m=2 languages and n=28 tasks. The base LLM is jointly trained on the multitask corpus D_{all} :

$$\mathcal{L}_{all} = -\sum_{i=1}^{m} \mathbb{E}_{q_k^{L_i}, a_k, t_k \in D_i} [\log P(a_k, t_k | q_{t_k}; \theta)]$$
 (2)

where q_k is the query, t_k is the thought, and a_k is the response.

3 Experiment Setting

3.1 Instruction Tuning

Backbone Models Based on the English and Chinese pre-trained model, we adopt Llama-2-7B/13B⁴ and Qwen-1.5-7B/14B⁵ as the foundation model to build SEVENLLM.

Implementation Details To fine-tune all models with different sizes, we set epochs to 3 and batch size to 128. We use a cosine scheduler with a learning rate of 2e-5 and 3% learning rate warmup.

Dataset Based on based model of Llama2 and Qwen-1.5, SEVENLLMs are trained on SEVEN-LLM-Instruct of nearly 85K samples generated by GPT-4.

3.2 Evaluation

Rouge-L Score We use Rouge-L to evaluate the output of the LLM, which is tokenized by space in English and jieba⁶ in Chinese.

Semantic Score Using the multilingual sentence-transformers model⁷ (Reimers and Gurevych, 2019), we map the text to a 384-dimensional dense vector space. This can be used for tasks such as clustering or semantic search, allowing for the evaluation of whether the values in a test dictionary can score from a semantic understanding perspective. This approach is more aligned with the open-ended nature of cyber security event analysis. Due to its support for various lengths and both Chinese and

⁴https://github.com/meta-llama/llama

⁵https://github.com/QwenLM/Qwen1.5

⁶https://github.com/fxsjy/jieba

⁷https://huggingface.

co/sentence-transformers/

paraphrase-multilingual-MiniLM-L12-v2

Task Name	Task Description							
	Understanding Task							
(1) Key Entity Recognition	Identify the main entity information in the text, such as attacker organization, victim type, main person, the common vulnerabilities and exposures (CVE), email address, virtual account, IP address, and the indicators of compromise (IOCs) Extract the relationships between major entities such as attacker, victim, attack method and so on. Through							
(2) Main Relation Extraction	relationship extraction, connections between entities can be established to help cybersecurity experts better understand the content and context of threat intelligence.							
(3) Important Event Extraction	Key information such as the type, time, location, and impact of the event can be identified through critical event extraction.							
(4) Malware Feature Extraction	Extract the malware features mentioned in the text, such as file characteristics, means of exploitation, and harm caused.							
(5) Cybersecurity Event Classification	The classification results or category characteristics such as event type, severity, etc. are extracted from the security event information and structurally labeled.							
(6) Attack Tool Identification	Tools and toolchains utilized in the attack are identified and extracted.							
(7) Domain Intelligence Acquisition	Domain names often involve information about phishing sites and locations, obtaining the domain name used by the attacker to look for potential relevance.							
(8) Time Element Acquisition	The timing of cybersecurity events is extracted and the timeline is scrutinized and parsed in detail.							
(9) Network Protocol Utilization	Extract the network protocols used in the attack, which may include some information containing the attacker's characteristics.							
(10) Enc-Dec Algorithm Identification	The process of identifying the encryption or decryption algorithm used in a text and determining the specific algorithm used for the encryption or decryption operation in the text.							
(11) Vulnerability Intelligence Extraction	Identify the main information of the vulnerability described in the text, the vulnerability number, and the way the vulnerability is exploited.							
(12) Attacker Information Extraction	Characterize the attacker's place of origin, ip, language, unique fingerprints during the attack, and attack behavior and confrontation ideas							
(13) Attack Target Intelligence Gathering	Analyze the main characteristics of the attacked target, such as operating system, software, and target industry, field, geographical location, etc.							
	Generation Task							
(1) Vulnerability Exploitation Analysis	Analyze and assess the exploitation of known vulnerabilities (also known as exploits).							
(2) Attack Means Analysis	Analyze the means and specific methods used in attacks during cybersecurity incidents.							
(3) Attack Strategy Analysis	Analyze the attacker's tactics, attack plan, or usual methods in a cybersecurity incident.							
(4) Correlation Analysis	Analyze the connections and correlated evidence between different threat intelligence reports and cybersecurity incidents.							
(5) Attack Intent Analysis	Analyze the attacker's potential motivation, intent, target industry, or target area.							
(6) Threat Analysis	Analyze potential threats and possible hazards in cybersecurity incidents.							
(7) Risk Assessment	Assess the risk and level of risk posed by the security incident or such attack.							
(8) Impact Scope	Analyze the scope and impact of security incidents.							
(9) Trend Prediction	Predicts future security trends based on historical and current data, or predicts likely development outcomes based on known information.							
(10) Behavioral Pattern Analysis	Research the behavioral pattern characteristics of attackers in cyber security incidents, including attack timing, target selection, etc.							
(11) Protection Strategy Research	Research and design strategies to protect against such security incidents or attacks.							
(12) Incident Response Planning	Develop an emergency response plan to deal with such incidents.							
(13) Security Policy Audit	Audit and evaluate the applicability and effectiveness of proposed security policies.							
(14) Summary Generation	A concise and complete summary of the text needs to be generated based on the content of the long text, highlighting the activities and characteristics associated with the main cybersecurity incidents.							
(15) Security Alert Generation	Automatically generate security alerts based on analysis of events.							

Table 2: List of the understanding and generation tasks.

Model	Base Model	Model Size	Understanding (En)	Generation (En)	Understanding (Zh)	Generation (Zh)	Understanding (Avg.)	Generation (Avg.)	Avg.
Llama2-Chat (Touvron et al., 2023)	Llama	7B	55.8	39.8	52.3	81.8	54.1	60.8	57.5
Llama2-Chat (Touvron et al., 2023)	Llama	13B	48.1	39.6	56.4	74.6	52.2	57.1	54.7
Qwen1.5-Chat (Bai et al., 2023)	Qwen	7B	76.3	45.6	81.4	84.8	78.8	65.2	72.0
Qwen1.5-Chat (Bai et al., 2023)	Qwen	14B	75.0	42.6	74.9	86.7	75.0	64.6	69.8
SEVENLLM	Llama	7B	78.7	68.9	84.5	88.4	81.6	78.7	80.1
SEVENLLM + CoT	Llama	7B	76.9	67.2	82.9	88.4	79.9	77.9	78.9
SEVENLLM	Llama	13B	77.5	68.2	84.5	90.0	81.0	79.1	80.1
SEVENLLM + CoT	Llama	13B	76.9	67.2	82.9	88.4	79.9	77.9	78.9
SEVENLLM	Qwen	7B	78.9	66.7	83.3	88.1	81.1	77.4	79.3
SEVENLLM	Qwen	14B	78.6	66.8	84.4	88.4	81.5	77.6	79.6

Table 3: Rouge-L scores of our method and previous baselines for downstream generation tasks.

Model	Base Model	Model Size	Understanding (En)	Generation (En)	Understanding (Zh)	Generation (Zh)	Understanding (Avg.)	Generation (Avg.)	Avg.
Llama2-Chat (Touvron et al., 2023)	Llama	7B	43.3	71.363	45.4	84.5	44.4	77.9	61.2
Llama2-Chat (Touvron et al., 2023)	Llama	13B	35.9	73.8	43.8	81.6	39.9	77.7	58.8
Qwen1.5-Chat (Bai et al., 2023)	Qwen	7B	66.6	77.2	74.9	86.6	70.8	81.9	76.4
Qwen1.5-Chat (Bai et al., 2023)	Qwen	14B	63.4	75.1	74.4	87.5	68.9	81.3	75.1
SEVENLLM	Llama	7B	71.9	84.6	80.4	87.3	76.2	85.9	81.1
SEVENLLM + CoT	Llama	7B	69.7	84.3	79.4	86.7	74.6	85.5	80.1
SEVENLLM	Llama	13B	71.0	84.5	81.4	89.3	76.2	86.9	81.6
SEVENLLM + CoT	Llama	13B	69.3	85.3	79.4	89.3	74.4	87.3	80.9
SEVENLLM	Qwen	7B	71.5	82.7	79.4	89.4	75.5	86.1	80.8
SEVENLLM	Qwen	14B	70.1	84.5	79.9	88.1	75.0	86.3	80.7

Table 4: Semantic similarity score of generation task.

English languages, this model is applied to both understanding and generation tasks.

GPT-4 Score To score the standard answers of the test set and the answers provided by the trained

model, we set the evaluation criteria as {very pool: 1, slightly poor: 2, neutral: 3, good: 4, very good: 5} to compute the score.

Model	Base Model	Model Size	Understanding (En)	Generation (En)	Understanding (Zh)	Generation (Zh)	Understanding (Avg.)	Generation (Avg.)	Avg.
Llama2-Chat (Touvron et al., 2023)	Llama	7B	70.4	78.9	65.2	67.7	67.8	73.3	70.6
Llama2-Chat (Touvron et al., 2023)	Llama	13B	69.2	79.9	69.4	73.3	69.3	76.6	73.0
Qwen1.5-Chat (Bai et al., 2023)	Qwen	7B	78.2	79.5	79.5	77.5	78.9	78.5	78.7
Qwen1.5-Chat (Bai et al., 2023)	Qwen	14B	82.1	79.6	79.7	77.7	80.9	78.6	79.8
SEVENLLM	Llama	7B	82.1	79.7	80.9	77.9	81.5	78.8	80.2
SEVENLLM + CoT	Llama	7B	82.3	79.7	79.6	77.5	81.0	78.6	79.8
SEVENLLM	Llama	13B	83.7	80.3	80.9	78.0	82.3	79.1	80.7
SEVENLLM + CoT	Llama	13B	82.7	80.1	80.3	78.3	81.5	79.2	80.4
SEVENLLM	Qwen	7B	84.1	80.7	81.3	78.7	82.7	79.7	81.2
SEVENLLM	Qwen	14B	82.6	79.7	80.6	77.9	81.6	78.8	80.2

Table 5: GPT-4 Evaluation of our method and previous baselines downstream generation tasks.

Model	Base Model	Model Size	Understanding (En)	Generation (En)	Understanding (Zh)	Generation (Zh)	Understanding (Avg.)	Generation (Avg.)	Avg.
Llama2-Chat (Touvron et al., 2023)	Llama	7B	11	18	13	11	24	29	53
Llama2-Chat (Touvron et al., 2023)	Llama	13B	20	21	14	15	34	36	70
Qwen1.5-Chat (Bai et al., 2023)	Qwen	7B	19	23	25	24	44	47	91
Qwen1.5-Chat (Bai et al., 2023)	Qwen	14B	22	24	22	24	44	48	92
SEVENLLM	Llama	7B	22	24	24	25	46	49	95
SEVENLLM + CoT	Llama	7B	20	24	23	25	43	49	92
SEVENLLM	Llama	13B	23	25	23	25	46	50	96
SEVENLLM + CoT	Llama	13B	22	25	24	25	46	50	96
SEVENLLM	Qwen	7B	23	23	23	24	46	47	93
SEVENLLM	Qwen	14B	22	25	24	25	46	50	96

Table 6: Results of multiple-choice question.

Multiple-choice Question Score We design 100 multiple-choice questions for two languages and two major types of tasks to comprehensively evaluate the model's capabilities. The output results were manually verified to ensure an effective assessment of the model's ability to handle objective questions.

4 Main Results

Rouge-L&Semantic Evaluation In Table 3 and Table 4, SEVENLLM based on the Llama2 and Qwen1.5 gets the best performance by fine-tuning on the instruction dataset SEVENLLM-Instruct. Further, we can observe that SEVENLLM based on the Qwen tends to get better performance in Table 3. Plus, SEVENLLM + CoT gains no improvement, since the evaluated tasks do not require the complex reason. But the reasoning text can be provided to cybersecurity staff as a reference.

GPT-4 Evaluation In Table 5, compared to the results of models that have not been trained with SEVENLLM-Instruct, it is evident that training with the datasets provided in this work significantly improves performance. Additionally, it is observed that while higher-capacity models show improvements in multiple-choice questions, they can occasionally perform worse in Rouge-L and semantic similarity matching. Considering that cybersecurity data is challenging to collect and highly specialized, this underscores the importance of enhancing training materials in this field with datasets like those

provided in this paper. It has also been observed that base models can perform correct analysis but still produce incorrect answers, indicating that the full potential of an AI model requires not only general training but also alignment with specialized corpora to yield more accurate outcomes.

Multiple-choice Question In Table 6, during a comparison of multiple-choice questions, it is observed that the Qwen performs less effectively than Llama2, particularly in scenarios requiring a degree of reasoning and where answers may be confusing. The LLMs with 13B and 14B parameters have been confirmed to perform better in multiple-choice question scenarios. This suggests that the enrichment of overall knowledge and reasoning capabilities with larger model sizes improves performance in multiple-choice questions.

5 Analysis

Training Data Size of Instruction Tuning To discuss the effect of the instruction tuning, we plot Rouge-L scores and Semantic similarity scores with different training data sizes in Figure 3. The performance is influenced by the size of the instruction data. We randomly sample $N = \{0K, 1K, 2K, \ldots, ALL\}$ sentences from the whole corpora to fine-tune the Qwen model. With the training data size increasing, the SEVENLLM gets better performance. Notably, only 1K supervised data sentences bring large improvement to the zero-shot cross-lingual NER, which benefits




Figure 3: Evaluation results of different instruction data sizes.

from knowledge transfer of the multilingual self-training. When the size of target annotated corpora is greater than 10K, our method gets exceptional performance. From the results obtained through Rouge-L score and Semantic similarity score, the model's performance appears to reach a level close to the testing set when it scales to around the 70,000 magnitude. However, overall it appears that the larger the training dataset, the better the accuracy of the model.

Quality Analysis of SEVENLLM-Bench To ensure the quality of the SEVENLLM-Bench, we employ three experts to evaluate the quality of the test set and calculate the error rate in Table 7. Manual revision includes corrections for accuracy and reasonableness, inspecting the result content to ensure it meets the requirements of the instructions, is based on prior knowledge from the input, and involves removing redundant information and hallucinations, as well as adding some undetected information. This includes proofreading 100 multiple-choice questions for the correctness and uniqueness of answers. We can that the total error rate of SEVENLLM-Bench is 17% generated by GPT-4 and then the experts fix these errors to ensure the correctness of the test set.

Human Evaluation To better evaluate the LLM Llama-2-Chat and SEVENLLM, we employ five volunteers to score the test set SEVENLLM-Bench of cyber threat intelligence {1: very poor; 2: poor; 3: neutral, 4: good; 5: very good} based on three criteria (1) Correctness: Correctness refers to the accuracy and reliability of the information provided or the actions performed. (2) Fluency: It's about how smoothly and coherently the system can produce or interpret language, making it comprehensi-




Figure 4: Comparison between SEVENLLM with Llama-2-Chat.

ble and pleasant for human users. (3) Instruction Following Capability: This component assesses how effectively a system or application can comprehend and execute commands or requests given by users.

6 Related Work

Cyber Threat Intelligence Cyber threat intelligence (Liu and Zhan, 2023; Motlagh et al., 2024; Arazzi et al., 2023; Siracusano et al., 2023; Camacho et al., 2024) has emerged as a pivotal aspect of cybersecurity practices, aimed at understanding and anticipating cyber threats for proactive defense. This field encompasses the collection, analysis, and dissemination of information regarding current or potential attacks threatening the security of information systems (Park et al., 2023; Guo et al., 2021, 2024). By leveraging CTI, organizations are equipped to identify specific threats and vulnerabilities, enabling them to tailor their security measures more effectively. This intelligence-gathering process draws from a wide array of sources, including historical cyber attack data, hacker forums, malware samples, and more, to provide a comprehensive view of the cyber threat landscape, which helps

Task	Zh	En	All	Zh (C)	En (C)	All (C)	Ratio (%)
Key Entity Recognition	3	25	28	2	1	3	0.11
Main Relation Extraction	0	0	0	0	0	0	0.00
Important Event Extraction	12	28	40	2	2	4	0.1
Malware Feature Extraction	227	41	268	99	9	108	0.40
Cybersecurity Event Classification	14	86	100	5	3	8	0.08
Attack Tool Identification	3	21	24	1	2	3	0.13
Domain Intelligence Acquisition	0	9	9	0	4	4	0.44
Time Element Acquisition	2	36	38	1	0	1	0.03
Network Protocol Utilization	0	0	0	0	0	0	0.00
Encryption-Decryption Algorithm Identification	0	11	11	0	0	0	0
Vulnerability Information Extraction	39	33	72	9	2	11	0.15
Attacker Information Extraction	20	15	35	12	0	12	0.34
Attack Target Intelligence Gathering	5	18	23	2	1	3	0.13
Vulnerability Exploitation Analysis	0	0	0	0	0	0	0.00
Attack Means Analysis	7	1	8	1	0	1	0.13
Attack Strategy Analysis	14	3	17	2	0	2	0.12
Correlation Analysis	7	0	7	0	0	0	0
Attack Intent Analysis	2	1	3	0	0	0	0
Threat Analysis	224	92	316	27	10	37	0.12
Risk Assessment	10	37	47	3	1	4	0.09
Impact Scope	8	20	28	0	2	2	0.07
Trend Prediction	2	9	11	1	1	2	0.18
Behavioral Pattern Analysis	0	0	0	0	0	0	0.00
Protection Strategy Research	39	50	89	0	3	3	0.03
Incident Response Planning	6	46	52	0	2	2	0.04
Security Policy Audit	0	1	1	0	0	0	0
Summary Generation	6	55	61	2	13	15	0.25
Security Alert Generation	0	12	12	0	2	2	0.17
Total	650	650	1300	168	54	222	0.17

Table 7: Correction of SEVENLLM-Instruct. |Zh| denotes the number of Chinese samples in SEVENLLM-Bench while |Zh(C)| denotes the number of samples need to be corrected.

in enhancing the security posture against known threats and aids in predicting and mitigating future cyber attacks. Consequently, CTI plays a critical role in the strategic, operational, and tactical levels of an organization's cybersecurity framework, ensuring resilience against the evolving nature of cyber threats.

Domain-specific Large Language Model The evolution of large language models (LLMs) (Touvron et al., 2023; Bai et al., 2023; Achiam et al., 2023) is a remarkable milestone while addressing concerns of reliability and safety. The development of the generative pre-trained Transformer (GPT) series by OpenAI progressively expands the frontiers of the field of natural language processing (NLP), such as named entity recognition (Mo et al., 2024a; Yang et al., 2022; Mo et al., 2024b), machine translation (Yang et al., 2020b, 2021, 2020a, 2023) and text style transfer (Wang et al., 2019, 2020; Wu et al., 2020). It even has an impact (Lin et al., 2023; Zhai et al., 2024) on some traditional recommendation and advertising methods (Wang et al., 2023b; Huang et al., 2022). To further enhance the adaptability of LLMs to various tasks, instruction-tuning has become a commonly

adopted method by utilizing instructions derived from human-curated prompts, feedback, and public benchmarks, which supports the fast development of the domain-specific LLMs, such as complex reasoning (Chai et al., 2024; Qin et al., 2024), coding (Roziere et al., 2023; Lozhkov et al., 2024), IT operation (Guo et al., 2023, 2024), and science (Xie et al., 2023). Instruction tuning (Wang et al., 2023a) is introduced to generate novel tasks and associated instructions from the ground up, offering advantages in terms of performance and cost efficiency. The breadth and variety of the instruction data correlate strongly with how well the models can generalize and handle tasks they have not encountered before.

7 Conclusion

In this work, we present SEVENLLM, which marks a significant advancement in the use of LLMs for benchmarking, eliciting, and improving cybersecurity incident analy- sis and response abilities in cybersecurity LLMs. By leveraging a meticulously curated bilingual instruction corpus from an extensive collection of cybersecurity texts, SEVENLLM bridges the gap in the availability of effective data for cybersecurity applications.

The instruction dataset SEVENLLM-Instruct encompassing 28 well-conceptualized tasks is used to fine-tune SEVENLLM based on the different foundation models (Llama and Qwen). The extensive main and analytic experiments performed on a specialized curated cybersecurity benchmark, SEVENLLM-Bench, further corroborate the efficacy of SEVENLLM in improving the analytical capabilities and providing a robust response mechanism against cyber threats.

Limitations

The primary data source collected focuses on English as the mainstream language for cybersecurity intelligence. Although it has been extended to include Chinese data, the analysis of cybersecurity incidents would benefit from a multilingual capability, which requires further collection and organization. In the future, we will expand SEV-ENLLM-Instruct to more languages.

Ethical Considerations

In this study, we analyze cyber threat intelligence exclusively derived from publicly available sources provided by security companies. Although some sensitive cybersecurity terminology was used, we strictly avoided involving any personal privacy, trade secrets, or activities that could constitute a threat. Moreover, we ensured that all data handling and usage complied with ethical standards and legal regulations to maintain transparency and integrity in our research.

References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. arXiv preprint arXiv:2303.08774.
- Shahid Alam. 2022. Cybersecurity: Past, present and future. *arXiv preprint arXiv:2207.01227*.
- Marco Arazzi, Dincy R Arikkat, Serena Nicolazzo, Antonino Nocera, Mauro Conti, et al. 2023. Nlp-based techniques for cyber threat intelligence. *arXiv* preprint arXiv:2311.08807.
- Daniel Arp, Erwin Quiring, Feargus Pendlebury, Alexander Warnecke, Fabio Pierazzi, Christian Wressnegger, Lorenzo Cavallaro, and Konrad Rieck. 2022. Dos and don'ts of machine learning in computer security. In 31st USENIX Security Symposium, USENIX Security 2022, Boston, MA, USA, August 10-12, 2022, pages 3971–3988. USENIX Association.

- Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. 2023. Qwen technical report. *arXiv* preprint arXiv:2309.16609.
- Jose Manuel Camacho, Aitor Couce-Vieira, David Arroyo, and David Rios Insua. 2024. A cybersecurity risk analysis framework for systems with artificial intelligence components. *arXiv preprint arXiv:2401.01630*.
- Linzheng Chai, Jian Yang, Tao Sun, Hongcheng Guo, Jiaheng Liu, Bing Wang, Xiannian Liang, Jiaqi Bai, Tongliang Li, Qiyao Peng, et al. 2024. xcot: Crosslingual instruction tuning for cross-lingual chain-of-thought reasoning. arXiv preprint arXiv:2401.07037.
- Hongcheng Guo, Xingyu Lin, Jian Yang, Yi Zhuang, Jiaqi Bai, Tieqiao Zheng, Bo Zhang, and Zhoujun Li. 2021. Translog: A unified transformer-based framework for log anomaly detection. *arXiv preprint arXiv:2201.00016*.
- Hongcheng Guo, Jian Yang, Jiaheng Liu, Liqun Yang, Linzheng Chai, Jiaqi Bai, Junran Peng, Xiaorong Hu, Chao Chen, Dongfeng Zhang, et al. 2023. Owl: A large language model for it operations. *arXiv preprint arXiv:2309.09298*.
- Hongcheng Guo, Wei Zhang, Anjie Le, Jian Yang, Jiaheng Liu, Zhoujun Li, Tieqiao Zheng, Shi Xu, Runqiang Zang, Liangfan Zheng, et al. 2024. Lemur: Log parsing with entropy sampling and chain-of-thought merging. arXiv preprint arXiv:2402.18205.
- Siguang Huang, Yunli Wang, Lili Mou, Huayue Zhang, Han Zhu, Chuan Yu, and Bo Zheng. 2022. Mbct: Tree-based feature-aware binning for individual uncertainty calibration. In *Proceedings of the ACM Web Conference* 2022, pages 2236–2246.
- Feihu Jin, Yifan Liu, and Ying Tan. 2024. Zero-shot chain-of-thought reasoning guided by evolutionary algorithms in large language models. *arXiv preprint arXiv:2402.05376*.
- Jianghao Lin, Xinyi Dai, Yunjia Xi, Weiwen Liu, Bo Chen, Xiangyang Li, Chenxu Zhu, Huifeng Guo, Yong Yu, Ruiming Tang, et al. 2023. How can recommender systems benefit from large language models: A survey. *arXiv preprint arXiv:2306.05817*.
- Jiehui Liu and Jieyu Zhan. 2023. Constructing knowledge graph from cyber threat intelligence using large language model. In *IEEE International Conference on Big Data, BigData 2023, Sorrento, Italy, December 15-18, 2023*, pages 516–521. IEEE.
- Anton Lozhkov, Raymond Li, Loubna Ben Allal, Federico Cassano, Joel Lamy-Poirier, Nouamane Tazi, Ao Tang, Dmytro Pykhtar, Jiawei Liu, Yuxiang Wei, et al. 2024. Starcoder 2 and the stack v2: The next generation. *arXiv preprint arXiv:2402.19173*.

- Ying Mo, Jian Yang, Jiahao Liu, Qifan Wang, Ruoyu Chen, Jingang Wang, and Zhoujun Li. 2024a. MCL-NER: cross-lingual named entity recognition via multi-view contrastive learning. In *Thirty-Eighth AAAI Conference on Artificial Intelligence, AAAI 2024, Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence, IAAI 2024, Fourteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2014, February 20-27, 2024, Vancouver, Canada*, pages 18789–18797.
- Ying Mo, Jian Yang, Jiahao Liu, Shun Zhang, Jingang Wang, and Zhoujun Li. 2024b. C-icl: Contrastive in-context learning for information extraction. *arXiv* preprint arXiv:2402.11254.
- Farzad Nourmohammadzadeh Motlagh, Mehrdad Hajizadeh, Mehryar Majd, Pejman Najafi, Feng Cheng, and Christoph Meinel. 2024. Large language models in cybersecurity: State-of-the-art. *arXiv preprint arXiv:2402.00891*.
- Kuchan Park, Junho Hong, Wencong Su, and HyoJong Lee. 2023. Machine learning based post event analysis for cybersecurity of cyber-physical system. *arXiv* preprint arXiv:2311.13488.
- Libo Qin, Qiguang Chen, Yuhang Zhou, Zhi Chen, Yinghui Li, Lizi Liao, Min Li, Wanxiang Che, and Philip S Yu. 2024. Multilingual large language model: A survey of resources, taxonomy and frontiers. *arXiv preprint arXiv:2404.04925*.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.
- Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, et al. 2023. Code llama: Open foundation models for code. *arXiv* preprint arXiv:2308.12950.
- Timo Schick and Hinrich Schütze. 2021. It's not just size that matters: Small language models are also fewshot learners. In *NAACL 2021*, pages 2339–2352.
- Giuseppe Siracusano, Davide Sanvito, Roberto Gonzalez, Manikantan Srinivasan, Sivakaman Kamatchi, Wataru Takahashi, Masaru Kawakita, Takahiro Kakumaru, and Roberto Bifulco. 2023. Time for action: Automated analysis of cyber threat intelligence in the wild. *arXiv preprint arXiv:2307.10214*.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023a. Self-instruct: Aligning language

- models with self-generated instructions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9-14, 2023*, pages 13484–13508.
- Yunli Wang, Zhiqiang Wang, Jian Yang, Shiyang Wen, Dongying Kong, Han Li, and Kun Gai. 2023b. Adaptive neural ranking framework: Toward maximized business goal for cascade ranking systems. *arXiv* preprint arXiv:2310.10462.
- Yunli Wang, Yu Wu, Lili Mou, Zhoujun Li, and Wenhan Chao. 2019. Harnessing pre-trained neural networks with rules for formality style transfer. In *Proceedings* of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 3573–3578.
- Yunli Wang, Yu Wu, Lili Mou, Zhoujun Li, and Wenhan Chao. 2020. Formality style transfer with shared latent space. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 2236–2249.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022.
- Yu Wu, Yunli Wang, and Shujie Liu. 2020. A dataset for low-resource stylized sequence-to-sequence generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 9290–9297.
- Tong Xie, Yuwei Wan, Wei Huang, Zhenyu Yin, Yixuan Liu, Shaozhou Wang, Qingyuan Linghu, Chunyu Kit, Clara Grazian, Wenjie Zhang, et al. 2023. Darwin series: Domain specific large language models for natural science. *arXiv preprint arXiv:2308.13565*.
- Jian Yang, Shaohan Huang, Shuming Ma, Yuwei Yin, Li Dong, Dongdong Zhang, Hongcheng Guo, Zhoujun Li, and Furu Wei. 2022. CROP: zero-shot crosslingual named entity recognition with multilingual labeled sequence translation. In *Findings of EMNLP* 2022, pages 486–496.
- Jian Yang, Shuming Ma, Li Dong, Shaohan Huang, Haoyang Huang, Yuwei Yin, Dongdong Zhang, Liqun Yang, Furu Wei, and Zhoujun Li. 2023. Ganlm: Encoder-decoder pre-training with an auxiliary discriminator. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, ACL 2023, Toronto, Canada, July 9-14, 2023, pages 9394–9412.
- Jian Yang, Shuming Ma, Haoyang Huang, Dongdong Zhang, Li Dong, Shaohan Huang, Alexandre Muzio, Saksham Singhal, Hany Hassan, Xia Song, and Furu

- Wei. 2021. Multilingual machine translation systems from microsoft for WMT21 shared task. In *Proceedings of the Sixth Conference on Machine Translation, WMT@EMNLP 2021, Online Event, November 10-11, 2021*, pages 446–455.
- Jian Yang, Shuming Ma, Dongdong Zhang, Zhoujun Li, and Ming Zhou. 2020a. Improving neural machine translation with soft template prediction. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pages 5979–5989. Association for Computational Linguistics.
- Jian Yang, Shuming Ma, Dongdong Zhang, Shuangzhi Wu, Zhoujun Li, and Ming Zhou. 2020b. Alternating language modeling for cross-lingual pre-training. In The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020, pages 9386–9393.
- Jiaqi Zhai, Lucy Liao, Xing Liu, Yueming Wang, Rui Li, Xuan Cao, Leon Gao, Zhaojie Gong, Fangda Gu, Michael He, et al. 2024. Actions speak louder than words: Trillion-parameter sequential transducers for generative recommendations. *arXiv* preprint *arXiv*:2402.17152.
- Jun Zhao, Qiben Yan, Xudong Liu, Bo Li, and Guangsheng Zuo. 2020. Cyber threat intelligence modeling based on heterogeneous graph convolutional network.
 In 23rd International Symposium on Research in Attacks, Intrusions and Defenses, RAID 2020, San Sebastian, Spain, October 14-15, 2020, pages 241–256. USENIX Association.