# A REVIEW ON TWO TYPES OF SONIC INTERFACES

MYOUNGJEAN BAE

ABSTRACT. In this paper, two examples of sonic interfaces ([2, 3, 4, 5, 6]) are presented. The first example shows the case of sonic interfaces as weak discontinuities in self-similar shock configurations of unsteady Euler system. The second example shows the case of sonic interfaces as regular interfaces in accelerating transonic flows governed by the steady Euler-Poisson system with self-generated electric forces. And, we discuss analytic differences of the two examples, and introduce an open problem on decelerating transonic solution to the steady Euler-Poisson system.

## 1. A SONIC INTERFACE AS A WEAK DISCONTINUITY

Fix a constant  $\varepsilon_0 > 0$ . Given a function  $f : [0, \varepsilon_0] \to \mathbb{R}_+$  with

(1.1) 
$$||f||_{C^{1,1}([0,\varepsilon_0])} < \infty, \quad f(0) > 0, \quad \text{and} \quad \frac{df}{dx} \ge \omega > 0 \,\forall 0 \le x \le \varepsilon_0,$$

 $\operatorname{set}$ 

$$P_0 := (0, f(0)),$$

and define a domain

(1.2) 
$$\mathcal{Q}^{f}_{\varepsilon_{0}} := \{ (x, y) : 0 < x < \varepsilon_{0}, \ 0 < y < f(x) \}.$$

For each  $t \in (0, f(0))$ , set

$$\mathcal{R}_t := (0, \frac{\varepsilon_0}{2}) \times (0, f(0) - t).$$

Given two constants a > 0 and b > 0, and functions  $\beta_k \in C(\partial \mathcal{Q}^f_{\varepsilon_0} \cap \{y = f(x)\})$ for k = 1, 2, 3, consider the equation

(1.3) 
$$(2x - a\psi_x + O_1)\psi_{xx} + O_2\psi_{xy} + (b + O_3)\psi_{yy} - (1 + O_4)\psi_x + O_5\psi_y = 0$$
 in  $\mathcal{Q}^f_{\varepsilon_0}$ 

and the boundary conditions

(1.4) 
$$\psi = 0 \quad \text{on } \partial \mathcal{Q}^f_{\varepsilon_0} \cap \{x = 0\}$$

(1.5) 
$$\partial_y \psi = 0 \text{ on } \partial \mathcal{Q}^f_{\varepsilon_0} \cap \{y = 0\}$$

(1.6) 
$$\beta_1(x,y)\psi_x + \beta_2(x,y)\psi_y + \psi = 0 \quad \text{on } \partial \mathcal{Q}^f_{\varepsilon_0} \cap \{y = f(x)\}.$$

In addition, assume that

(1.7) 
$$\beta_1(x,y) \ge \lambda, |\beta_2(x,y), \beta_3(x,y)| \le \frac{1}{\lambda} \text{ on } \partial \mathcal{Q}^f_{\varepsilon_0} \cap \{y = f(x)\}$$

for some constant  $\lambda > 0$ .

Date: May 10, 2024.

<sup>2010</sup> Mathematics Subject Classification. 35C06, 35M10, 35M30, 35Q31, 76H05, 76N10. Key words and phrases. Keldysh type, transonic, sonic interface, weak discontinuity, regular interface.

**Theorem 1** (Theorem 3.1 in [1]). Suppose that a function  $\psi : \overline{\mathcal{Q}_{\varepsilon_0}^f} \to \mathbb{R}$  satisfies the following conditions:

- (i)  $\psi \in C^2(\mathcal{Q}^f_{\varepsilon_0}) \cap C^{1,1}(\overline{\mathcal{Q}^f_{\varepsilon_0}});$ (ii)  $\psi > 0$  in  $\mathcal{Q}^f_{\varepsilon_0};$
- (iii) there exist constants  $\mu > 0$  and  $\delta \in (0, 1)$  such that

$$-\mu \leq \frac{\psi_x(x,y)}{x} \leq \frac{2-\delta}{a} \quad in \ \mathcal{Q}^f_{\varepsilon_0};$$

(iv)  $\psi$  satisfies (1.3)–(1.6).

In addition, assume that the terms  $O_i(x,y)$ ,  $i = 1, \dots, 5$  are continuously differentiable, and that there exists a constant N > 0 satisfying

(1.8) 
$$\frac{|O_1(x,y)|}{x^2}, \frac{|O_i(x,y)|}{x} \le N \quad \text{for } i = 2, \cdots, 5, \\ \frac{|DO_1(x,y)|}{x}, |DO_k(x,y)| \le N \quad \text{for } i = 2, \cdots, 5$$

in  $\{x > 0\}$ .

Then, the following properties hold:

- (a)  $\forall t \in (0, f(0)), \ \psi \in C^{2,\alpha}(\overline{\mathcal{R}_t}) \ \forall \alpha \in (0, 1);$ (b)  $\psi_{xx}(0, y) = \frac{1}{a}, \ \psi_{xy}(0, y) = \psi_{yy}(0, y) = 0 \text{ for all } 0 \le y < f(0);$ (c) there are two sequences  $\{(x_m^{(1)}, y_m^{(1)})\}$  and  $\{(x_m^{(2)}, y_m^{(2)})\}$  in  $\mathcal{Q}_{\varepsilon_0}^f$  such that

$$\lim_{m \to \infty} (x_m^{(1)}, y_m^{(1)}) = \lim_{m \to \infty} (x_m^{(2)}, y_m^{(2)}) = P_0 \quad \text{for } j = 1, 2,$$
$$\lim_{m \to \infty} \psi_{xx}(x_m^{(1)}, y_m^{(1)}) = \frac{1}{a}, \quad \lim_{m \to \infty} \psi_{xx}(x_m^{(2)}, y_m^{(2)}) = 0.$$

Now we demonstrate an application of Theorem 1.

An irrotational flow of inviscid compressible polytropic gas is governed by the Euler equation for potential flow:

(1.9) 
$$\partial_t \rho + \nabla_{\mathbf{x}} \cdot (\rho \nabla_{\mathbf{x}} \Phi) = 0,$$
$$\partial_t \Phi + \frac{1}{2} |\nabla_{\mathbf{x}} \Phi|^2 + \frac{\rho^{\gamma - 1} - 1}{\gamma - 1} = B_0$$

for an adiabatic exponent  $\gamma > 1$ . The density and the velocity potential of the flow are represented as  $\rho$  and  $\Phi$ , respectively. And, the term  $B_0 > 0$  represents the Bernoulli constant which is determined by the initial data. For  $\theta_w \in (0, \frac{\pi}{2})$ , define a symmetric wedge W in  $\mathbb{R}^2$  by

(1.10) 
$$W := \{ \mathbf{x} = (\mathbf{x}_1, \mathbf{x}_2) \in \mathbb{R}^2 : |\mathbf{x}_2| < \mathbf{x}_1 \tan \theta_{\mathbf{w}}, \ \mathbf{x}_1 > 0 \}$$

Suppose that  $(\rho, \Phi)$  solves (1.9) in  $\mathbb{R}^2 \setminus W$ , and satisfies the slip boundary condition

(1.11) 
$$\nabla_{\mathbf{x}} \Phi \cdot \mathbf{n}_w = 0 \quad \text{on } \partial W$$

for the exterior unit normal **n** to  $\partial W$ . Then, for any constant  $\alpha > 0$ , it can be directly checked that  $(\tilde{\rho}, \Phi)$  given by

$$(\tilde{\rho}, \tilde{\Phi})(\mathbf{x}, t) := (\rho, \frac{1}{\alpha} \Phi)(\alpha \mathbf{x}, \alpha t)$$

satisfies (1.9) in  $\mathbb{R}^2 \setminus W$ , and (1.11) on  $\partial W$ . Owing to the scaling invariance, one may seek for a self-similar solution in the form of

$$(\rho, \Phi)(\mathbf{x}, t) = (\varrho(\boldsymbol{\xi}), t\Psi(\boldsymbol{\xi})) \text{ for } \boldsymbol{\xi} = (\xi_1, \xi_2) \text{ with } (\xi_1, \xi_2) := \frac{1}{t}(x_1, x_2).$$

With a pseudo-potential function  $\varphi$  given by

$$arphi(oldsymbol{\xi}) := -rac{1}{2}|oldsymbol{\xi}|^2 + \Psi(oldsymbol{\xi}),$$

one can rewrite (1.9) as

(1.12) 
$$\nabla \cdot (\varrho \nabla \varphi) + 2\varrho = 0$$

with

(1.13) 
$$\varrho^{\gamma - 1} = (\gamma - 1)B_0 + 1 - (\gamma - 1)\left(\varphi + \frac{1}{2}|\nabla\varphi|^2\right).$$

With (1.12), the global-in-time existence of weak solutions to (1.9) of various shock structures are investigated in [2, 3, 5, 6, 7, 8]. When a plane shock hits the symmetric wedge W head-on, it is proved in [5, 6] that if  $\theta_w \in (\theta_d, \frac{\pi}{2})$  for the critical angle(=the detachment angle uniquely determined by a shock polar), then (1.9) has a weak solution of a self-similar regular shock reflection configuration (Fig.1).



FIGURE 1. Self-similar regular shock reflection  $(S_{\infty}:$  incoming plane shock,  $\overline{S_0 \cup \Gamma_{\text{shock}}}:$  reflected shock,  $\theta_w \in (\theta_{\text{sonic}}, \frac{\pi}{2}))$ 

When a supersonic flow with a constant density moves horizontally toward the symmetric wedge W at a constant speed, it is proved in [3, 8] that there exists a global-in-time weak solution of a self-similar weak shock configuration for  $\theta_w \in (0, \theta_d)$  (Fig.2). In Fig.1 and Fig.2, the straight shocks  $S_0$  and the corresponding downstream state in  $\Omega_0$  are given as the weak shock state on the shock polar (Fig.3). Considering that the incoming supersonic flow has a constant density and a constant velocity, the straight normal shock  $S_1$  and the corresponding downstream state in  $\Omega_1$  (see Fig.2) can be easily computed from the Rankine-Hugoniot jump conditions.

Since the density  $\rho$  in  $\Omega_0(\text{Fig.2})$  is a constant, it follows from (1.12) and (1.13) that the pseudo-potential function  $\varphi$  satisfies

$$\begin{cases} \Delta \varphi + 2 = 0 \\ \varphi + \frac{1}{2} |\nabla \varphi|^2 = \text{a constant} \end{cases} \quad \text{ in } \Omega_0$$



FIGURE 2. Self-similar weak shock configuration past a wedge (Left:  $\theta_w < \theta_{\text{sonic}}$ , Right:  $\theta_{\text{sonic}} \le \theta_w < \theta_d$ )



FIGURE 3. The shock polar for steady potential flow equation( $\mathbf{u}_0$ : the weak shock state in  $\Omega_0$  for  $0 < \theta_w < \theta_{\text{sonic}}$ )

and this yields

(1.14) 
$$\varphi(\boldsymbol{\xi}) = -\frac{1}{2}|\boldsymbol{\xi}|^2 + \mathbf{u}_0 \cdot \boldsymbol{\xi} + k \quad \text{in } \Omega_0$$

for the constant vector  $\mathbf{u}_0$  given on the shock polar (Fig.3), and for a constant k.

Take the representation of  $\rho$  in terms of  $(\varphi, \nabla \varphi)$ , directly given from (1.13). Substituting the representation  $\rho(\varphi, \nabla \varphi)$  into (1.12), we are given with a second order quasi-linear equation

(1.15) 
$$\nabla \cdot (\varrho(\varphi, \nabla \varphi) \nabla \varphi) + 2\varrho(\varphi, \nabla \varphi) = 0.$$

If  $\rho^{\gamma-1} - |\nabla \varphi|^2 < 0$ , the equation (1.15) is hyperbolic, and if  $\rho^{\gamma-1} - |\nabla \varphi|^2 > 0$ , it is elliptic.

Back to the uniform state in  $\Omega_0$  (Fig.1, Fig.2), let  $\rho_0 > 0$  represent the constant density in  $\Omega_0$ . Then, for the pseudo-potential function  $\varphi$  given by (1.14), we have

$$\mathcal{C}_0 := \{ \boldsymbol{\xi} : |\nabla \varphi|^2 = \varrho_0^{\gamma - 1} \} = \{ |\boldsymbol{\xi} - \mathbf{u}_0|^2 = \varrho_0^{\gamma - 1} \}.$$

The boundary portion  $\Gamma_0 := \partial \Omega_0 \cap C_0$  is called a *pseudo-sonic arc* associated with the state of the density  $\rho_0$ , and the velocity  $\mathbf{u}_0$ . In  $\Omega_0$ , the equation (1.15) is hyperbolic, and the hyperbolicity is degenerate on the pseudo-sonic arc  $\partial \Omega_0 \cap C_0$ . Note that the pseudo-supersonic region  $\Omega_0$  bounded by a straight oblique shock  $S_0$  is shown for  $\theta_w \in (\theta_{\text{sonic}}, \frac{\pi}{2}]$  in Fig.1, and for  $\theta_w \in (0, \theta_{\text{sonic}})$  in Fig.2. And, this region shrinks to a point as  $\theta_w$  approaches to the sonic angle  $\theta_{\text{sonic}}$ , which is uniquely determined by the shock polar associated with the incoming flow state.

The region in which the equation (1.15) is  $\text{elliptic}(\rho^{\gamma-1} - |\nabla_{\boldsymbol{\xi}}\varphi|^2 > 0)$  is indicated as  $\Omega$ . For the admissible solution  $\varphi$  constructed in [3, 5, 6], one of the essential properties is that there exists a constant  $\mu > 0$  satisfying

$$\frac{|\nabla \varphi(\boldsymbol{\xi})|}{\varrho^{\frac{\gamma-1}{2}}(\nabla \varphi(\boldsymbol{\xi}), \varphi(\boldsymbol{\xi}))} \leq 1 - \mu \operatorname{dist}(\boldsymbol{\xi}, \mathcal{C}_0) \quad \text{for } \boldsymbol{\xi} \in \Omega \text{ near } \Gamma_0$$

as long as the pseudo-supersonic region  $\Omega_0$  appears (Fig.1, Fig.2(left)).

Let  $\varphi_0$  be the pseudo-potential function given by (1.14). Define a polar coordinate system by

$$\boldsymbol{\xi} - \mathbf{u}_0 := r(\cos\theta, \sin\theta)$$

And, define a new coordinate system by

$$(x,y) := \begin{cases} (\varrho_0^{\frac{\gamma-1}{2}} - r, \theta - \theta_w) & \text{for } \boldsymbol{\xi} \text{ near } \Gamma_0 \text{ in Fig. 1} \\ (\varrho_0^{\frac{\gamma-1}{2}} - r, \pi + \theta_w - \theta) & \text{for } \boldsymbol{\xi} \text{ near } \Gamma_0 \text{ in Fig. 2} \end{cases}$$

Finally, define

(1.16) 
$$\psi(x,y) := \varphi(\boldsymbol{\xi}) - \varphi_0(\boldsymbol{\xi}) \quad \text{in } \Omega \text{ near } \Gamma_0.$$

The admissible solutions constructed in [3, 5, 6] have the following properties: if  $\theta_w \in (\theta_{\text{sonic}}, \frac{\pi}{2}]$  in Fig. 1, or if  $\theta_w \in (0, \theta_{\text{sonic}})$  in Fig. 2, then

(i)  $\exists$  a (small) constant  $\varepsilon_0 > 0$  and a function  $f : [0, \varepsilon_0] \to \mathbb{R}_+$  such that

$$\Omega \cap \{ \operatorname{dist}(\boldsymbol{\xi}, \Gamma_0) < \varepsilon_0 \} = \mathcal{Q}_{\varepsilon_0}^f$$

for the domain  $\mathcal{Q}_{\varepsilon_0}^f$  defined by (1.2);

- (ii) such a function f, representing the curved pseudo-transonic shock  $\Gamma_{\rm shock}$ (Fig. 1, Fig. 2), satisfies all the properties stated in (1.1);
- (iii) the equation (1.15) is rewritten as

$$(2x - (\gamma + 1) + O_1)\psi_{xx} + O_2\psi_{xy} + \left(\frac{1}{\frac{\gamma - 1}{\varrho_0^2}} + O_3\right)\psi_{yy} - (1 + O_4)\psi_x + O_5\psi_y = 0$$

for the terms  $O_i(x, \psi, \psi_x, \psi_y)$  satisfying all the properties stated in (1.8);

- (iv)  $\psi$  satisfies the boundary conditions (1.4)–(1.6) with (1.7) holding;
- (v)  $\psi \in C^2(\mathcal{Q}^f_{\varepsilon_0} \cap C^{1,1}(\overline{\mathcal{Q}^f_{\varepsilon_0}}));$ (vi)  $0 \le \psi(x,y) \le Lx^2$  in  $\mathcal{Q}^f_{\varepsilon_0}$  for some constant L > 0;
- (vii)  $0 \leq \frac{\psi_x}{x} \leq \frac{2-\delta}{\gamma+1}$  in  $\mathcal{Q}_{\varepsilon_0}^f$  for some constant  $\delta \in (0, \frac{1}{2})$ .

Then it directly follows from Theorem 1 that

(a)  $\forall y \in [0, f(0)),$ 

$$\lim_{x \to 0+} \psi_{xx}(x,y) = \frac{1}{\gamma+1};$$

(b)  $\psi|_{\overline{\mathcal{Q}_{\varepsilon_0}^f}}$  is not  $C^2$  at the point (0, f(0)).

According to the statement (a), the radial derivative of the flow velocity  $(= \nabla_{\mathbf{x}} \Phi)$ on the pseudo-sonic arc  $\Gamma_0(\text{Fig.1}, \text{Fig.2(left)})$  is nonzero. While the velocity field  $\nabla_{\mathbf{x}} \Phi$  is discontinuous on the shock  $\overline{S_0 \cup \Gamma_{\text{shock}}}$ , it is continuous on  $\Gamma_0$ . What the statement (a) indicates, however, is that the pseudo-sonic arc  $\Gamma_0$  is a weak discontinuity in the sense that a derivative of the velocity field is discontinuous on  $\Gamma_0$ . We also point out that another pseudo-sonic arc  $\Gamma_1$  in Fig.2 due to the presence of

### MYOUNGJEAN BAE

a normal shock state in  $\Omega_1$  is also a *a weak discontinuity*. Now, a question arises naturally:

Given a second order equation with a degeneracy of Keldysh type, does the degeneracy always result in a discontinuity in a second order derivative of its solutions on the degenerate interface?

Another example introduced in the next section indicates that the answer to the question is 'no'.

# 2. A sonic interface as a regular interface

Given a constant L > 0, define

$$\Omega_L := \{ \mathbf{x} = (x_1, x_2) \in \mathbb{R}^2 : 0 < x_1 < L, \ |x_2| < 1 \}.$$

The boundary  $\partial \Omega_L$  consists of the entrance  $\Gamma_0 = \{0\} \times [-1, 1], \Gamma_w := (0, L) \times \{\pm 1\}$ , and the exit  $\Gamma_L := \{L\} \times [-1, 1]$ .

For two fixed constants  $\gamma > 1$  and  $\bar{\rho}_I > 0$ , consider the steady Euler-Poisson system

(2.1)  

$$\begin{aligned} \nabla \cdot (\rho \mathbf{u}) &= 0 \\ \nabla \cdot (\rho \mathbf{u} \otimes \mathbf{u}) + \nabla p &= \rho \nabla \Phi \\ \nabla \cdot (\rho \mathcal{B} \mathbf{u}) &= \rho \mathbf{u} \cdot \nabla \Phi \\ \Delta \Phi &= \rho - \bar{\rho}_I \end{aligned}$$

with

$$\mathcal{B} = \frac{1}{2}|\mathbf{u}|^2 + \frac{\gamma p}{(\gamma - 1)\rho}$$

for a fixed adiabatic exponent  $\gamma > 1$ .

Any one-dimensional solution  $(\rho, \mathbf{u}, p, \Phi) = (\bar{\rho}, \bar{u}_1 \mathbf{e}_1, \bar{p}, \bar{\Phi})(x_1)$  with  $\bar{\rho} > 0$  and  $\bar{u}_1 > 0$  can be given as

$$\bar{\rho}(x_1) = \frac{J}{\bar{u}_1(x_1)}$$
$$\bar{p}(x_1) = S_0 \bar{\rho}^{\gamma}(x_1)$$
$$\bar{\Phi}(x_1) = \frac{u_0^2}{2} + \frac{\gamma S_0}{\gamma - 1} \left(\frac{J}{u_0}\right)^{\gamma - 1} + \int_0^{x_1} \bar{E}(t) dt$$

with  $(\bar{u}_1, \bar{E})$  solving

(2.2) 
$$\begin{cases} \bar{u}_1' = \frac{\bar{E}\bar{u}_1^{\gamma}}{\bar{u}_1^{\gamma+1} - u_s^{\gamma+1}} \\ \bar{E}' = \frac{\bar{I}}{\bar{u}_1} - \bar{\rho}_I \end{cases} \quad \text{for } x_1 > 0, \quad (\bar{u}_1, \bar{E})(0) = (u_0, E_0) \end{cases}$$

for constants  $S_0 > 0$ , J > 0,  $u_0 > 0$  and  $E_0 \in \mathbb{R}$ . Here, the constant  $u_s$  represents the speed at the sonic state, and is explicitly given by

$$u_s = (\gamma S_0 J^{\gamma - 1})^{\frac{1}{\gamma + 1}}.$$

Define  $(\bar{u}_I, \zeta_0) := (\frac{J}{\bar{\rho}_I}, \frac{\bar{u}_I}{u_s})$ , and assume that

$$\zeta_0 > 1.$$

For  $H: (0,\infty) \to \mathbb{R}$  given by

$$H(u) := \frac{J}{\bar{u}_I} \int_{u_s}^u \frac{1}{t^{\gamma+1}} (t^{\gamma+1} - u_s^{\gamma+1}) (\bar{u}_I - t) \, dt,$$

6

if  $(\bar{u}_1, \bar{E})(x_1)$  is a  $C^1$ -solution to (2.2), then it can be directly checked from (2.2) that

$$\frac{1}{2}\bar{E}^2 - H(\bar{u}_1) = \frac{1}{2}E_0^2 - H(u_0) \quad \text{for } x_1 > 0$$

as long as the solution exists.

We call a set

(2.3) 
$$\mathcal{T} := \{(u, E) : \frac{1}{2}E^2 - H(u) = 0\}$$

the critical trajectory on the uE-plane. Further, we call a set

$$\mathcal{T}_{\mathrm{acc}} := \{ (u, E) \in \mathcal{T} : (u - u_s)E \ge 0 \}$$

the critical trajectory with an acceleration(Fig.4).



FIGURE 4. The critical trajectory

For the initial data  $(u_0, E_0)$  in (2.2), suppose

$$(2.4) (u_0, E_0) \in \mathcal{T}_{\mathrm{acc}}, \quad u_0 < u_s.$$

**Lemma 2.1** (Lemma 1.1 in [4]). The initial value problem (2.2) with  $(u_0, E_0)$  satisfying (2.4) has a unique smooth solution  $(\bar{u}_1, \bar{E})$  with the following properties:

(i) there exists a finite constant  $l_{\text{max}} > 0$  such that

$$\bar{u}_1'(x_1) > 0 \quad for \ x_1 \in [0, l_{\max});$$

(ii) 
$$\lim_{x \to l_{\max}} \bar{u}_1'(x_1) = 0,$$

(iii)  $\mathcal{T}_{acc} \cap \{(\bar{u}_1, \bar{E})(x_1) : 0 \le x_1 \le l_{max}\} = \mathcal{T}_{acc} \cap \{(u, E) : u \ge u_0\}$  (Fig.4);

(iv) there exists a unique constant  $l_s \in (0, l_{max})$  (Fig.5) such that

$$\bar{u}_1(x_1) \begin{cases} < u_s & \text{for } x_1 < l_s \\ = u_s & \text{at } x_1 = l_s \\ > u_s & \text{for } x_1 > l_s \end{cases}$$



FIGURE 5.

For the solution  $(\bar{u}_1, \bar{E})$  given in Lemma 2.1, we can write as

(2.5) 
$$\bar{E} = \operatorname{sgn}(\bar{u}_1 - u_s)\sqrt{2H(\bar{u}_1)} \text{ for } x_1 \in [0, l_{\max}].$$

 $\operatorname{Set}$ 

$$\bar{\varphi}(x_1) := \int_0^{x_1} \bar{u}_1(t) \, dt.$$

It easily follows from (2.2) and (2.5) that

$$\left( (\partial_1 \bar{\varphi})^{\gamma+1} - u_s^{\gamma+1} \right) \partial_{11} \bar{\varphi} - \operatorname{sgn}(\partial_1 \bar{\varphi} - u_s) \sqrt{2H(\partial_1 \bar{\varphi})} (\partial_1 \bar{\varphi})^{\gamma} = 0 \quad \text{for } x_1 \in [0, l_{\max}].$$

Therefore,  $\bar{\varphi}$  can be regarded as a solution to a second order equation with a degeneracy of Keldysh type, and the smoothness of  $\bar{\varphi}$  indicates that the degenerate interface  $x_1 = l_s$  is not a weak discontinuity. So we are given with an example for a degenerate interface of a new type for a second order equation with a degeneracy of Keldysh type. Naturally, the following questions arise:

- Does there exist a multi-dimensional solution to (2.1) with a degenerate interface?

- If so, what is the regularity of the solution across the degenerate interface? Let us assume that

$$\mathcal{B}-\Phi=0,$$

which we call a pseudo Bernoulli's law, and let us write the pressure function p as

$$p = S \rho^{\gamma}.$$

For  $\rho > 0$  and  $\mathbf{u} \cdot \mathbf{e}_1(=: u_1) > 0$ , the system (2.1) can be rewritten as

(2.6)  
$$\begin{cases} \nabla \cdot (\rho \mathbf{u}) = 0\\ \nabla \times \mathbf{u} = \frac{\rho^{\gamma - 1} \partial_2 S}{(\gamma - 1)u_1}\\ \rho \mathbf{u} \cdot \nabla S = 0\\ \frac{1}{2} |\mathbf{u}|^2 + \frac{\gamma S \rho^{\gamma - 1}}{\gamma - 1} = \Phi\\ \Delta \Phi = \rho - \bar{\rho}_I. \end{cases}$$

Take the one-dimensional solution  $(\bar{\rho}, \bar{u}_1 \mathbf{e}_1, \bar{p} (= S_0 \bar{\rho}^{\gamma}), \bar{\Phi})$  with  $(\bar{u}_1, \bar{E})$  given from Lemma 2.1. For a two-dimensional velocity field  $\mathbf{u}$ , we represent as

$$\mathbf{u} = \nabla \varphi + \nabla^{\perp} \phi,$$

and define

$$(\psi, \Psi) := (\varphi, \Phi) - (\bar{\varphi}, \bar{\Phi}).$$

Then we can further rewrite (2.6) as a nonlinear system for  $(\psi, \Psi, \phi, S)$  as follows: (2.7)

$$\sum_{i,j=1}^{2} a_{ij}\partial_{ij}\psi + b_{1}\partial_{1}\psi + \bar{u}_{1}\partial_{1}\Psi + (\gamma - 1)\bar{u}_{1}'\Psi = f_{1}(S,\nabla\psi,\nabla^{\perp}\phi,D(\nabla^{\perp}\phi)\Psi,\nabla\Psi)$$

$$(2.8) \qquad \Delta\Psi - \frac{1}{\gamma S_{0}\bar{\rho}^{\gamma-2}}\Psi + \frac{\bar{u}_{1}}{\gamma S_{0}\bar{\rho}^{\gamma-2}}\partial_{1}\psi = f_{2}(S,\nabla\psi,\nabla^{\perp}\phi,\Psi,\nabla\Psi)$$

(2.9) 
$$-\Delta\phi = f_3(S, \nabla\psi, \nabla^{\perp}\phi, \Psi, \nabla\Psi)$$

(2.10) 
$$(\nabla \bar{\varphi} + \nabla \psi + \nabla^{\perp} \phi) \cdot \nabla S = 0$$

for

$$a_{ij} = (\gamma + 1) \left( \bar{\Phi} + \Psi - \frac{1}{2} |\mathbf{v}|^2 \right) \delta_{ij} - (\mathbf{v} \cdot \mathbf{e}_i) (\mathbf{v} \cdot \mathbf{e}_j) \text{ with } \mathbf{v} = \nabla \bar{\varphi} + \nabla \psi + \nabla^{\perp} \phi$$
$$b_1 = \bar{E} - (\gamma + 1) \bar{u}_1' \bar{u}_1.$$

To find a two-dimensional solution to (2.1) as a small perturbation of  $(\bar{\rho}, \bar{u}_1 \mathbf{e}_1, \bar{p}, \bar{\Phi})$ . we prescribe the following boundary conditions:

(2.11) 
$$\mathbf{u} \cdot \mathbf{e}_2 = w_{\text{en}}, \quad S = S_{\text{en}}, \quad \partial_1 \Phi = E_{\text{en}} \quad \text{on } \Gamma_0$$
$$\mathbf{u} \cdot \mathbf{e}_2 = 0, \quad \partial_2 \Phi = 0 \quad \text{on } \Gamma_w$$
$$\Phi = \bar{\Phi} \quad \text{on } \Gamma_L$$

for three functions  $w_{\text{en}}$ ,  $S_{\text{en}}$ ,  $E_{\text{en}}$ :  $[-1, 1] \rightarrow \mathbb{R}$  satisfying (2.12)  $\mathcal{P}(w_{\text{en}}, S_{\text{en}}, E_{\text{en}}) := \|w_{\text{en}}\|_{C}^{5}([-1, 1]) + \|(S_{\text{en}}, E_{\text{en}}) - (S_{0}, E_{0})\|_{C^{4}([-1, 1])} \leq \sigma$ for some small constant  $\sigma > 0$ , and satisfying the compatibility conditions

$$\left(\frac{d}{dx_2}\right)^k E_{\text{en}} = \left(\frac{d}{dx_2}\right)^k S_{\text{en}} = 0 \quad \text{at } |x_2| = 1 \text{ for } k = 1, 3,$$
$$\left(\frac{d}{dx_2}\right)^l w_{\text{en}} = 0 \quad \text{at } |x_2| = 1 \text{ for } l = 0, 2, 4.$$

In the framework of the Helmhotz decomposition, (2.11) becomes

(2.13) 
$$\begin{aligned} \partial_2 \psi &= \omega_{\text{en}}, \ \partial_1 \phi = 0, \ S = S_{\text{en}}, \ \partial_1 \Psi = E_{\text{en}} - E_0 \quad \text{on } \Gamma_0 \\ \partial_2 \psi &= 0, \ \phi = 0, \ \partial_2 \Psi = 0 \quad \text{on } \Gamma_w \\ \phi &= 0, \ \Psi = 0 \quad \text{on } \Gamma_L. \end{aligned}$$

The boundary condition  $\phi = 0$  on  $\Gamma_L$  is added in (2.13) for the well-posedness of the boundary value problem (2.7)–(2.10) with (2.13) for  $(\psi, \Psi, \phi, S)$ . As we seek for a solution  $(\psi, \Psi, \phi, S)$  with  $\|(\psi, \Psi, \phi)\|_{W^{1,\infty}}$  being small, we first investigate a modified equation of (2.7):

(2.14) 
$$\bar{a}_{11}\partial_{11}w + \bar{a}_{22}\partial_{22}w + b_1\partial_1w = f$$

for  $(\bar{a}_{11}, \bar{a}_{22}) = (a_{11}, a_{22})$  with  $\psi = \phi = \Psi = 0$ . For the normalized coefficients

(2.15) 
$$\alpha_{11} := \frac{\bar{a}_{11}}{\bar{a}_{22}} = 1 - \left(\frac{\bar{u}_1}{u_s}\right)^{\gamma+1}, \quad \beta_1 := \frac{b_1}{\bar{a}_{22}} = \frac{(\bar{E} - (\gamma+1)\bar{u}_1'\bar{u}_1)\bar{u}_1^{\gamma-1}}{u_s^{\gamma+1}},$$

define a linear differential operator

(2.16) 
$$\mathcal{L}w := \alpha_{11}\partial_{11}w + \partial_{22}w + \beta_1\partial_1w.$$

## MYOUNGJEAN BAE

According to Lemma 2.1(iv), the operator  $\mathcal{L}$  is elliptic in  $\Omega_L \cap \{x_1 < l_s\}$ , hyperbolic in  $\Omega_L \cap \{x_1 > l_s\}$ , and degenerate on  $\Omega_L \cap \{x_1 = l_s\}$ . Therefore, it is a mixed type operator with a degeneracy of Keldysh type if  $L > l_s$ . From this, it is easy to see that the equation (2.7), as a second order equation for  $\psi$ , is a mixed type with a degeneracy of Keldysh type.

One of differences between the two equations (1.3) and (2.7) (or (2.14)) is that the equation (1.3) is hyperbolic before (x < 0) the degenerate boundary (=sonic arc), and turns to be elliptic after (x > 0) the degenerate interface, while the equation (2.14) changes its type from being elliptic to being hyperbolic across the degenerate interface. Does this difference lead to a different result on the regularity of solutions to the boundary value problem (2.7)–(2.10) with (2.13)?

**Theorem 2** (Theorem 2 in [4]). Given constants  $(\gamma, \zeta_0, J, S_0, E_0)$  satisfying

 $\gamma > 1, \quad \zeta_0 > 1, \quad S_0 > 0, \quad E_0 < 0,$ 

suppose that  $(u_0, E_0) \in \mathcal{T}_{acc}$ , which is equivalent to  $0 < u_0 < u_s$ . Then one can fix two constants  $\overline{J}$  and  $\underline{J}$  depending only on  $(\gamma, \zeta_0, S_0)$  with  $0 < \overline{J} < 1 < \underline{J} < \infty$  so that whenever the background momentum density  $J(=\overline{\rho}\overline{u}_1)$  satisfies

either 
$$0 < J \leq \overline{J}$$
 or  $\underline{J} \leq J < \infty$ ,

there exists a constant  $d \in (0,1)$  depending on  $(\gamma, \zeta_0, S_0, J)$  so that if the two constants  $u_0$  and L are fixed to satisfy

(2.17) 
$$1 - d \le \frac{u_0}{u_s} < 1 < \frac{\bar{u}_1(L)}{u_s} \le 1 + d$$

and if the constant  $\sigma > 0$  in (2.12) is fixed sufficiently small depending only on  $(\gamma, \zeta_0, S_0, E_0, J, L)$ , then the boundary value problem (2.7)–(2.10) with (2.13) has a unique solution  $(\psi, \phi, \Psi, S)$  that satisfies the estimate

(2.18) 
$$\|(\psi, \phi, \Psi, S - S_0)\|_{H^4(\Omega_L)} \le C\mathcal{P}(S_{\text{en}}, E_{\text{en}}, w_{\text{en}})$$

for some constant C > 0 depending on  $(\gamma, \zeta_0, S_0, E_0, J, L)$ .

Furthermore, there exists a function  $f_{sn}: [-1,1] \to (0,L)$  such that

(2.19) 
$$\frac{|\mathbf{u}|}{\sqrt{\gamma S \rho^{\gamma-1}}} \begin{cases} <1 & \text{for } x_1 < \mathfrak{f}_{\mathrm{sn}}(x_2) \\ =1 & \text{for } x_1 = \mathfrak{f}_{\mathrm{sn}}(x_2) \\ >1 & \text{for } x_1 > \mathfrak{f}_{\mathrm{sn}}(x_2) \end{cases}$$

and the function  $\mathfrak{f}_{\mathrm{sn}}$  satisfies

(2.20) 
$$\|\mathbf{f}_{sn} - l_s\|_{H^2((-1,1))} + \|\mathbf{f}_{sn} - l_s\|_{C^1([-1,1])} \le C\mathcal{P}(S_{en}, E_{en}, w_{en})$$

for some constant C > 0 depending on  $(\gamma, \zeta_0, S_0, E_0, J, L)$ .

We are given from Theorem 2 with a classical solution  $(\rho, \mathbf{u}, p)$  of (2.1) with the sonic interface  $x_1 = \mathfrak{f}_{\mathrm{sn}}(x_2)$  across which the velocity field  $\mathbf{u}$  is not only continuous, but also its derivative is continuous. In other words,  $x_1 = \mathfrak{f}_{\mathrm{sn}}(x_2)$  is a degenerate interface but not a weak discontinuity. We call this sonic interface as a *regular interface* in the sense that the solution  $(\rho, \mathbf{u}, p)$  is a classical solution across the sonic interface.

#### 3. Discussion

In §1, we show an example of a (pseudo) sonic interface as a weak discontinuity in the sense that a velocity field is continuous but its derivative is discontinuous on the interface. Such an example is given from a solution to a mixed-type equation with a degeneracy of Keldysh type. More precisely, the type of the equation changes from being hyperbolic to being elliptic through a degenerate interface of codimension one. In §2, we show an example of a sonic interface as a regular interface on which a velocity field is  $C^1$ . This example is also given from a solution to a degenerate equation of Keldysh type, where the equation changes its type from being elliptic to being hyperbolic.

The interesting point is that the equations given in §1–2 are both Keldysh type, and that the lower order derivative terms  $(-1 + O_4)\psi_x$ ' from (1.3), and  $b_1\partial_1\psi'$ from (2.7) have significant contributions to Theorem 1 and Theorem 2, respectively. In spite of those similarities, the equations (1.3) and (2.7) give different regularity results. Why?

3.1. The existence of a special smooth solution. In §2, the classical solution of (2.1) with a sonic interface as a regular interface (Theorem 2) is constructed as a small perturbation of a smooth one-dimensional solution (Lemma 2.1). Therefore, one may suggest that the existence of a special smooth solution can be a clue to determine a destiny of a sonic interface in general.

It is true that a smooth one-dimensional solution comes in handy to reformulate (2.1) into (2.7)–(2.10) so that an iteration method can be applied. But still, it is another matter to establish the well-posedness of the boundary value problem (2.7)–(2.10) with (2.13). According to the work in [4], the essential ingredient used to prove Theorem 2 is the strictly increasing property of  $\bar{u}_1$  stated in Lemma 2.1(i). This monotonicity property combined with the method developed in [9] yields the well-posedness of a linearized boundary value problem derived from (2.7)–(2.10) with (2.11), and this yields Theorem 2.



FIGURE 6. Self-similar normal shock reflection (S<sub>0</sub>: reflected normal shock,  $\varphi = \varphi_0$  in  $\Omega_0 \cup \Gamma_0 \cup \Omega$ , see [5])

#### MYOUNGJEAN BAE

But, there is another example that shows that the existence of a special smooth solution does not necessarily tells the destiny of a sonic interface in general. As repeatedly pointed out, the sonic arc  $\Gamma_0$  in a self-similar regular shock reflection is a weak discontinuity for  $\theta_w \in (\theta_{\text{sonic}}, \frac{\pi}{2})$  (see §1). For the wedge-angle  $\theta_w = \frac{\pi}{2}$ , however, the sonic arc is not a weak discontinuity (Fig. 6) because the state behind the reflected normal shock  $S_0$  is simply given by  $\varphi = \varphi_0$  for a quadratic polynomial function  $\varphi_0$  of self-similar variables  $\boldsymbol{\xi} = (\xi_1, \xi_2)$  in the form of (1.14). In [5], a self-similar regular shock reflection solution for  $\theta_w \in (\frac{\pi}{2} - \sigma, \frac{\pi}{2})$  is constructed as a small perturbation of the normal shock reflection solution, but the nature of the sonic arc  $\Gamma_0$  for  $\theta_w < \frac{\pi}{2}$  is not determined by the arc  $\Gamma_0$  for  $\theta_w = \frac{\pi}{2}$ .

3.2. Acceleration VS. deceleration in a transonic transition. Notice that the self-similar flow (Fig.1 and Fig.2 (left)) introduced in §1 turns from being (pseudo) supersonic in  $\Omega_0$  to being (pseudo) subsonic in  $\Omega$  through the (pseudo) sonic arc  $\Gamma_0$ . This is a decelerating transition on  $\Gamma_0$ , and Theorem 1 implies that  $\Gamma_0$  is a weak discontinuity. On the other hand, the  $C^1$ -transonic solution of Euler-Poisson system (2.1) given by Theorem 2 in §2 has an accelerating transition on the sonic interface  $x_1 = \mathfrak{f}_{sn}(x_2)$ .

**Question.** Does a decelerating transonic transition always yield a sonic interface as a weak discontinuity, while accelerating transonic transition does not?

Here is another interesting example to investigate. For the set  $\mathcal{T}$  given by (2.3), define

$$\mathcal{T}_{dec} := \{ (u, E) \in \mathcal{T} : (u - u_s)E \le 0 \}.$$

We call the set  $\mathcal{T}_{dec}$  the critical trajectory with a deceleration. By modifying the proof of Lemma 2.1 given in [4], one obtains the following lemma:

**Lemma 3.1.** For the initial data  $(u_0, E_0)$  in (2.2), suppose

$$(u_0, E_0) \in \mathcal{T}_{dec}, \quad u_0 > u_s$$

Then, the initial value problem (2.2) has a unique smooth solution  $(\bar{u}_1, E)$  with the following properties:

(Case 1) For  $1 < \gamma < 2$ ,

(i) there exists a finite constant  $l_{\text{max}} > 0$  such that

$$\bar{u}_1'(x_1) < 0 \quad for \ x_1 \in [0, \tilde{l}_{\max});$$

- $\bar{u}'_1(x_1) < 0 \quad for \ x_1 \in [0, l_{\max});$ (ii)  $\lim_{x_1 \to \bar{l}_{\max} -} \bar{u}'_1(x_1) = 0 \ and \ \lim_{x_1 \to \bar{l}_{\max} -} \bar{E}(x_1) = \infty;$
- (iii)  $\mathcal{T}_{dec} \cap \{(\bar{u}_1, \bar{E})(x_1) : 0 \le x_1 \le \tilde{l}_{max}\} = \mathcal{T}_{dec} \cap \{(u, E) : u \le u_0\}$  (Fig.4);
- (iv) there exists a unique constant  $\tilde{l}_s \in (0, \tilde{l}_{\max})$  such that

$$\bar{u}_{1}(x_{1}) \begin{cases} > u_{s} & \text{for } x_{1} < l_{s} \\ = u_{s} & \text{at } x_{1} = \tilde{l}_{s} \\ < u_{s} & \text{for } x_{1} > \tilde{l}_{s} \end{cases}$$

(Case 2) For  $\gamma \geq 2$ , the statements given in (i)–(iv) hold with  $\tilde{l}_{\max} = \infty$ .

The smooth one-dimensional solution of the Euler-Poisson system (2.1) has a decelerating speed and a sonic interface at  $x_1 = l_s$ . Similarly to Theorem 2, would it be possible to establish the existence of a classical solution to (2.1) as a small perturbation of this one-dimensional decelerating smooth transonic solution? In proving Theorem 2, the key property used in [4] is that there exists a constant  $\lambda_L > 0$  satisfying

(3.1) 
$$-2\beta_1 - (2m-1)\partial_1\alpha_{11} \ge \lambda_L \text{ in } \Omega_L \text{ for } m = 0, 1, 2, 3$$

for the coefficients  $\alpha_{11}$  and  $\beta_1$  given by (2.15). This inequality enables to apply [9, Theorem 1.7] to achieve a priori  $H^{m+1}$  estimates of solutions obtained from Theorem 2 for m = 0, 1, 2, 3. More precisely, a direct computation yields the representation

$$-2\beta_1 - (2m-1)\partial_1\alpha_{11} = \frac{\bar{u}_1'}{u_s^{\gamma+1}} \left( 2m(\gamma+1)\bar{u}_1^{\gamma} + (\gamma-1)\bar{u}_1^{\gamma} + 2\frac{u_s^{\gamma+1}}{\bar{u}_1} \right).$$

And, the inequality (3.1) is obtained by Lemma 2.1.

For one-dimensional smooth transonic solution  $(\bar{u}_1, \bar{E})$  lying on the critical trajectory  $\mathcal{T}_{dec}$  with a deceleration, Lemma 3.1 implies that the inequality (3.1) does not hold because  $\bar{u}'_1 < 0$ . So one cannot apply [9, Theorem 1.7] to establish the existence of a classical solution to (2.1) as a small perturbation of  $(\bar{u}_1, \bar{E})$ . This opens to a possibility that a multi-dimensional solution to (2.1) given as a small perturbation of  $(\bar{u}_1, \bar{E})$  with  $\bar{u}'_1 < 0$  may contain a sonic interface as a weak discontinuity. This is an open problem to be investigated in the future.

Acknowledgements: The author shows her sincere respect to Prof. Gui-Qiang Chen's for his ambition and contribution to mathematics. The research of Myoungjean Bae was supported in part by Samsung Science and Technology Foundation under Project Number SSTF-BA1502-51.

# References

- BAE, M., CHEN, G.-Q., AND FELDMAN, M. Regularity of solutions to regular shock reflection for potential flow. *Invent. Math.* 175, 3 (2009), 505–543.
- [2] BAE, M., CHEN, G.-Q., AND FELDMAN, M. Prandtl-meyer reflection for supersonic flow past a solid ramp. Quarterly of Applied Mathematics 71, 3 (2013), 583–600.
- [3] BAE, M., CHEN, G.-Q. G., AND FELDMAN, M. Prandtl-meyer reflection configurations, transonic shocks, and free boundary problems. arXiv preprint arXiv:1901.05916 (2019).
- [4] BAE, M., DUAN, B., AND XIE, C. The steady euler-poisson system and accelerating flows with transonic c<sup>1</sup>-transitions. arXiv preprint arXiv:2308.04694 (2023).
- [5] CHEN, G.-Q., AND FELDMAN, M. Global solutions of shock reflection by large-angle wedges for potential flow. Annals of mathematics (2010), 1067–1182.
- [6] CHEN, G.-Q. G., AND FELDMAN, M. The Mathematics of Shock Reflection-diffraction and Von Neumann's Conjectures, vol. 359. Princeton University Press, 2018.
- [7] CHEN, S. Mach configuration in pseudo-stationary compressible flow. Journal of the American Mathematical Society 21, 1 (2008), 63–100.
- [8] ELLING, V., AND LIU, T.-P. Supersonic flow onto a solid wedge. Communications on Pure and Applied Mathematics: A Journal Issued by the Courant Institute of Mathematical Sciences 61, 10 (2008), 1347–1448.
- [9] KUZ'MIN, A. G. Boundary value problems for transonic flow. John Wiley & Sons, 2003.

DEPARTMENT OF MATHEMATICAL SCIENCES, KAIST, 291 DAEHAK-RO, YUSEONG-GU, DAEJEON, 43141, KOREA

Email address: mjbae@kaist.ac.kr



