Semantic Gesticulator: Semantics-Aware Co-Speech Gesture Synthesis

ZEYI ZHANG*, School of Electronics Engineering and Computer Science, Peking University, China

TENGLONG AO*, School of Computer Science, Peking University, China

YUYAO ZHANG*, Renmin University of China, China

QINGZHE GAO, Shandong University, China and Peking University, China

CHUAN LIN, Peking University, China

BAOQUAN CHEN, Peking University, China and State Key Lab of General AI, China

LIBIN LIU[†], Peking University, China and State Key Lab of General AI, China




Fig. 1. Our system can synthesize realistic co-speech gestures with strong rhythmic coherence and semantic correspondence.

In this work, we present *Semantic Gesticulator*, a novel framework designed to synthesize realistic gestures accompanying speech with strong semantic correspondence. Semantically meaningful gestures are crucial for effective non-verbal communication, but such gestures often fall within the long tail of the distribution of natural human motion. The sparsity of these movements makes it challenging for deep learning-based systems, trained on moderately sized datasets, to capture the relationship between the movements and the corresponding speech semantics. To address this challenge, we develop a generative retrieval framework based on a large language model. This framework efficiently retrieves suitable semantic gesture candidates from

Authors' addresses: Zeyi Zhang, illusence1@gmail.com, School of Electronics Engineering and Computer Science, Peking University, China; Tenglong Ao, aubrey, tenglong.ao@gmail.com, School of Computer Science, Peking University, China; Yuyao Zhang, 2020201710@ruc.edu.cn, Renmin University of China, China; Qingzhe Gao, gaoqingzhe97@gmail.com, Shandong University, China and Peking University, China; Chuan Lin, chuanlin2015@foxmail.com, Peking University, China; Baoquan Chen, baoquan@pku.edu.cn, Peking University, China and State Key Lab of General AI, China; Libin Liu, libin.liu@pku.edu.cn, Peking University, China and State Key Lab of General AI, China.

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in ACM Transactions on Graphics, https://doi.org/10.1145/3658134.

a motion library in response to the input speech. To construct this motion library, we summarize a comprehensive list of commonly used semantic gestures based on findings in linguistics, and we collect a high-quality motion dataset encompassing both body and hand movements. We also design a novel GPT-based model with strong generalization capabilities to audio, capable of generating high-quality gestures that match the rhythm of speech. Furthermore, we propose a semantic alignment mechanism to efficiently align the retrieved semantic gestures with the GPT's output, ensuring the naturalness of the final animation. Our system demonstrates robustness in generating gestures that are rhythmically coherent and semantically explicit, as evidenced by a comprehensive collection of examples. User studies confirm the quality and human-likeness of our results, and show that our system outperforms state-of-the-art systems in terms of semantic appropriateness by a clear margin. We will release the code and dataset for academic research.

CCS Concepts: • Computing methodologies \rightarrow Animation; Natural language processing; Neural networks.

Additional Key Words and Phrases: co-speech gesture synthesis, multi-modality, retrieval augmentation

ACM Reference Format:

Zeyi Zhang, Tenglong Ao, Yuyao Zhang, Qingzhe Gao, Chuan Lin, Baoquan Chen, and Libin Liu. 2024. Semantic Gesticulator: Semantics-Aware Co-Speech Gesture Synthesis. *ACM Trans. Graph.* 43, 4 (July 2024), 17 pages. https://doi.org/10.1145/3658134

^{*}these authors contributed equally to this research.

[†]corresponding author

1 INTRODUCTION

Gestures, which are hand and body movements that are non-verbal and non-manipulative, often accompany speech and play an important role in communication [McNeill 1992]. They not only enhance expression, making it more dynamic, especially through rhythmic movements known as *beat gestures*, but also increase communicative efficacy. This includes pointing or deictic gestures that convey specific references, metaphoric and iconic gestures that depict concepts, and emblems that symbolize specific words or phrases [Nyatsanga et al. 2023]. In this work, we refer to gestures with such communicative functions as *semantic gestures*. The occurrence of such gestures is much less frequent than that of beat gestures and falls within the long tail distribution of gestures. [Liu et al. 2022a,d].

Deep learning-based approaches have recently achieved significant success in synthesizing natural-looking gestures from speech input. These methods often excel at producing beat gestures that are in rhythmic harmony with the speech, but tend to stuggle with semantic gestures that reflect the meaning of the spoken words. Many previous deep learning-based systems adopt textual features extracted from transcripts as inputs to perceive semantics [Ao et al. 2022; Kucherenko et al. 2020; Pang et al. 2023; Yoon et al. 2020; Zhi et al. 2023]. However, since the majority of words in transcripts are not accompanied by semantically meaningful gestures, the learning process often tends to overlook these sparse semantic gestures and treat them as noises in the training data. There are methods attempting to refine the training procedure to address such issues. For example, Liu et al. [2022a] cluster gestures and resample within each cluster to improve data balance. Ao et al. [2023] attempt to discover implicit correspondence between semantic gestures and semantically salient words using contrastive learning. Meanwhile, Liang et al. [2022] train classifiers to classify gestures into a small number of labels and use these classifiers as extra perceptual objectives. Although these methods show effectiveness in certain scenarios, they still rely on sufficient coverage of semantic gesture-speech pairs within training data. Given the sparsity of such data, obtaining this coverage is challenging. Consequently, these methods struggle in practice to reliably produce appropriate semantic gestures at the correct moments, especially when dealing with a diverse range of semantic gesture categories.

A widely-used and robust strategy for enabling neural systems to perceive sparse and hard-to-mine data clues is retrieval augmentation, which has achieved great success in natural language processing [Izacard et al. 2022; Lewis et al. 2020; Ram et al. 2023]. The core idea involves retrieving useful items from an external database to enhance generation. When such retrieval is conducted by a powerful model, like a large language model, the external database effectively becomes augmented in return by the knowledge embedded in the retrieval model. This knowledge, originating from a much larger volume of data and potentially from different modalities, extends the limits of the data being retrieved.

Adapting this idea to semantic gestures is non-trivial, containing two challenges: 1) establishing a high-quality motion dataset with sufficient diversity to cover commonly used semantic gestures; 2) developing a retrieval model adept at choosing appropriate semantic gestures according to context and determining their timing.

To address the first challenge, we compile a comprehensive set of semantic gestures commonly used in human communication, drawing on relevant linguistic and human behavioral studies (e.g. [Kipp 2005; Morris 1994; Wagner and Armstrong 2003; World Federation of the Deaf 1975]). Based on this collection, we record a high-quality dataset of body, hand, and finger movement using motion capture. This dataset contains over 200 types of semantic gestures, each offering a variety of gestures. As for the second challenge, large language models like ChatGPT [OpenAI 2022] possess strong contextual understanding and generalization capabilities. We construct a generative retrieval model by fine-tuning a large language model, enabling it to efficiently retrieve appropriate semantic gestures based on input speech in an end-to-end manner and determine their timing.

We refer to this framework as *Semantic Gesticulator*, a co-speech gesture synthesis neural system designed to generate diverse and appropriate semantic gestures while ensuring rhythmic coherence with speech. We learn a GPT-based [Radford et al. 2018] gesture generative model to accommodate the retrieved gestures. This model is built upon discrete tokens extracted by a scalable, body partaware Residual VQ-VAE [Zeghidour et al. 2022]. It generalizes to a broad range of audio inputs, resulting in gestures that are both realistic and rhythmically in sync with the input speech. Moreover, we develop a semantics-aware gesture alignment mechanism. This mechanism fuses semantic and rhythmic gestures at the latent space level, ensuring that the generated gestures are not only meaningful but also exhibit rhythmic harmony.

In summary, the technical contributions of this work include:

- We introduce a novel semantics-aware co-speech gesture synthesis system that produces natural and semantically rich gestures. The GPT-based generator and the semantics-aware alignment mechanism effectively ensure motion quality and generalization across different audio inputs.
- We develop an LLM-based generative semantic gesture retrieval framework capable of efficiently retrieving semantic gestures from a gesture library.
- We compile a comprehensive list of commonly used semantic gestures and capture a high-quality dataset according to it.
 The list and the dataset will be released to the community for academic research.

2 RELATED WORK

2.1 Co-Speech Gesture Synthesis

Early methods for co-speech gesture synthesis is rule-based approaches, which primarily employ linguistic mapping rules to convert speech into sequences of pre-defined gesture clips [Cassell et al. 1994, 2001; Kipp 2004; Kopp et al. 2006]. A thorough review of these methods is presented by [Wagner et al. 2014]. Although rule-based methods yield interpretable and controllable outcomes, the construction of mapping rules and gesture databases is labor-intensive and movements generated by these methods are not realistic. To reduce the manual effort involved in creating rules and improve motion quality, data-driven approaches have increasingly become the dominant methodology in this field. A comprehensive survey of these methods is provided by [Nyatsanga et al. 2023]. Statistical models

are initially employed to extract mapping rules from data [Levine et al. 2010, 2009; Neff et al. 2008], but they still require a meticulously curated library of gesture units to generate the final motion. Subsequently, the advanced capabilities of deep neural networks enable the training of complex end-to-end models directly using raw gesture data. Deep learning-based systems can be categorized based on the randomness of their output. One choice is deterministic models, which are mainly based on MLPs [Kucherenko et al. 2020], CNNs [Habibie et al. 2021], RNNs [Bhattacharya et al. 2021a; Ghorbani et al. 2023; Liang et al. 2022; Liu et al. 2022a,a,c; Xu et al. 2023; Yoon et al. 2020, 2019], and Transformer [Bhattacharva et al. 2021b; Qi et al. 2023a,b; Voß and Kopp 2023]. Gestures generated by deterministic methods easily converge to "mean" poses due to the inherent many-to-many relationship between speech and gestures. Generative models are widely used to alleviate this problem, such as VAEs [Ghorbani et al. 2023; Li et al. 2021], VQ-VAEs [Ao et al. 2022; Liu et al. 2023, 2022b; Ng et al. 2024; Yazdian et al. 2022; Yi et al. 2022; Zhang et al. 2023d; Zhou et al. 2023], flow-based models [Alexanderson et al. 2020; Kucherenko et al. 2021; Ye et al. 2022], and diffusion-based models [Alexanderson et al. 2023; Ao et al. 2023; Chen et al. 2023; Chhatre et al. 2023; Deichler et al. 2023; Ji et al. 2023; Mehta et al. 2023; Xue et al. 2023; Yang et al. 2023b, 2024; Yin et al. 2023; Zhang et al. 2023a,b; Zhi et al. 2023; Zhu et al. 2023a]. Additionally, some hybrid systems integrate deep features with motion graphs [Zhou et al. 2022a] or motion matching [Ferstl et al. 2021; Habibie et al. 2022; Yang et al. 2023a] to enhance the controllability of the system. Generating meaningful gestures in sync with speech robustly is challenging for neural systems [Yoon et al. 2022]. Liang et al. [2022] design specific semantic gesture classifiers to explicitly guide the generator. Some systems opt to mine implicit content as a representation of semantics [Ao et al. 2023; Liu et al. 2022a]. Gao et al. [2023] define six general semantic gestures and employ a Large Language Model (LLM) as a simple classifier. Through prompt engineering, it identifies corresponding gestures for each sentence of text. Finally, the identified gestures are merged with gestures generated by the neural system through linear interpolation. There are there key differences between this work with our system: (a) our method enables generating over 200 types of semantic gestures, which covers commonly used scenarios; (b) we develop a generative retrieval framework through fine-tuning the LLM, capable of efficiently retrieving semantic gestures from a large gesture library; and (c) a semantics-aware gesture alignment mechanism is proposed to fuse semantic and rhythmic gestures at the latent space level, ensuring that the generated gestures are both meaningful and rhythm-coherent.

2.2 Speech-Gesture Dataset

Current co-speech gesture datasets could be divided into two types: pose-estimated and motion-captured. For the former, Ginosar et al. [2019] propose the Speech2Gesture Dataset, which employs Open-Pose [Cao et al. 2017] to extract 2D poses from News and Teaching videos. This dataset is then lifted to 3D pose [Habibie et al. 2021] and SMPL-X [Yi et al. 2022]. Similarly, Yoon et al. [2019] estimate 2D poses from TED videos and build the TED Dataset, which is also

extended to 3D pose [Liu et al. 2022c; Yoon et al. 2020] and SMPL-X [Lu et al. 2023]. Although pose-estimation methods facilitate the extraction of vast amounts of data from videos, their accuracy remains constrained. Motion-captured methods can yield high-quality motion datasets but are often costly. The Trinity Dataset [Ferstl and McDonnell 2018] showcases a male actor with 4 hours of data, and the TalkingWithHands Dataset [Lee et al. 2019] gathers data from conversational scenarios involving two speakers. The BEAT Dataset [Liu et al. 2022d] first incorporates both 3D pose and facial blendshapes. Liu et al. [2023] add mesh-level data to this dataset. ZEGGS [Ghorbani et al. 2023] focuses on a single speaker across 12 different styles. In this work, we collect a motion-captured gesture dataset encompassing commonly used semantic gestures, designed to augment and enrich existing datasets.

2.3 Generative Retrieval

Unlike the traditional index-retrieval-rank paradigm [Zhu et al. 2023b], generative retrieval involves storing knowledge in model parameters [Tay et al. 2022; Zhu et al. 2023b]. It focuses on generating index identifiers, such as numbers and titles, sequentially through an autoregressive fashion to achieve end-to-end retrieval [Cao et al. 2021]. This model-based information retrieval has recently gained significant attention in academia [Chen et al. 2022; Zhou et al. 2022b]. Methods like DSI [Tay et al. 2022] and NCI [Wang et al. 2023a] encode document content into vectors and use hierarchical clustering to generate numeric, semantically-based identifiers for retrieval. These number-based identifiers implicitly capture the document's hierarchical information and demonstrate efficient and effective performance. However, converting text to number-based identifiers can result in a loss of semantic detail, posing challenges for neural networks in learning this mapping function. To transfer the knowledge compressed in Pre-trained Language Models (PLMs), GENRE [Cao et al. 2021] focuses on retrieving entities by finetuning a T5 model [Raffel et al. 2020] to generate term-based identifiers such as each entity's unique title, progressing from left to right and token by token. Additionally, there are studies exploring the integration of multiple identifiers and how to use Large Language Models (LLMs) [Bevilacqua et al. 2022; Li et al. 2023; Ziems et al. 2023]. We can interpret our semantic gesture synthesis as a specific retrieval task. It uses speech text as a query to retrieve and decode appropriate semantic gesture identifiers at relevant locations using an autoregressive fashion, fulfilling the overall system's requirements. In contrast to sequence labeling tasks, this approach enables cross-encoding of context and considers semantics of gestures.

3 SYSTEM OVERVIEW

Our system processes audio and speech transcripts as inputs to generate realistic full-body gestures, including finger motion, that are both rhythmically and semantically aligned with the speech content. It is capable of robustly synthesizing sparse semantic gestures, vital for effective communication.

Our system is built upon a discrete latent motion space, learned through the use of a residual VQ-VAE [Zeghidour et al. 2022]. This approach tokenize a sequence of gestures into hierarchical and compact motion tokens, ensuring both motion quality and diversity.




Fig. 2. Our system is composed of three principal components: (a) an end-to-end neural generator, adept at handling a wide array of speech audio inputs to create gesture animations that are in rhythm with the speech; (b) a generative retrieval framework based on a large language model (LLM), adept at interpreting transcript context and selecting suitable semantic gestures from an extensive library covering commonly used gestures; and (c) a semantics-aware alignment mechanism, which amalgamates the chosen semantic gestures with the rhythmically produced motion, culminating in gestures that are semantically enriched.

As illustrated in Figure 2, our system comprises three key modules: (a) an end-to-end neural generator capable of processing a diverse range of speech audio inputs to produce rhythm-matched gesture animations utilizing the GPT architecture [Radford et al. 2019]; (b) a large language model (LLM)-based generative retrieval framework that comprehends the context of the transcript input and retrieves appropriate semantic gestures from a high-quality motion library covering commonly used semantic gestures; and (c) a semantics-aware alignment mechanism that integrates the retrieved semantic gestures with the rhythmic motion generated, resulting in semantically-enhanced gesture animation. In subsequent sections, we detail the components of our system and their respective training processes.

4 CO-SPEECH GESTURE GPT MODEL

We design a gesture generative model $\mathcal G$ enabling synthesizing rhythm-matched gestures as the foundation for the following semantic enhancement. The generator $\mathcal G$ predicts a sequence of discrete gesture tokens $\hat Z = [[\hat z_l^r]_{r=1}^R]_{l=1}^L$ conditioned on a speech, where the space of gesture tokens is pre-learned by a Residual VQ-VAE (RVQ) [Zeghidour et al. 2022], R is the number of the residual quantization layers, $\hat z_l^r \in \mathbb R^C$, and C is the dimension of the latent space. Then, the token sequence is decoded into gesture motion $\mathbf M = [\mathbf m_k]_{k=1}^K$ using the RVQ decoder $\mathcal D_{\text{VQ}}$, where the RVQ's downsampling rate is d = K/L. Each pose $\mathbf m_k \in \mathbb R^{3+6J}$ consists of the translation of the avatar and the rotations of its J joints. The rotations are parameterized as the exponential map. Next, we will discuss the details of the gesture tokenizer and the generator $\mathcal G$.

4.1 Gesture Tokenizer

Vanilla VQ-VAE [van den Oord et al. 2017] exhibits limited representational capacity, which hinders its ability to reconstruct complex motions, particularly in finger animation. To address this, as shown in Figure 3 (a), we enhance the standard VQ-VAE across three dimensions: 1) by dividing the motion representation into two parts, namely, body and hands, and compressing them independently; 2) by designing a more powerful encoder \mathcal{E}_{VQ} and decoder \mathcal{D}_{VQ} consisting of 1D convolutional layers and the Transformer layer [Vaswani

et al. 2017]; 3) by improving the capacity of the quantization module through the addition of multiple residual quantization layers.

Specifically, we divide the gesture sequence M into the body part $M_{\rm body}$ and the hand part $M_{\rm hand}$, utilizing two independent RVQ networks to model them respectively. The body part encompasses joints except for the fingers, while the hand part represents finger movements. Each network, acting as an expert, focuses on one specific part, thereby facilitating the handling of the complexity inherent in human movements. For simplicity, we next still use M to stand in for the general motion sequence. Formally, the RVQ encoder $\mathcal{E}_{\rm VQ}$ computes the gesture feature sequence $Z = [z_l]_{l=1}^L$ as

$$Z = \mathcal{E}_{VO}(M), \tag{1}$$

where $z_l \in \mathbb{R}^C$ and C is the dimension of the latent space.

Then, we should quantize Z into \hat{Z} . Due to the high diversity of motion data, the representational capacity of the quantization module needs to be extended. But simply increasing the size of the codebook C would lead to inefficient and unstable training, e.g., code collapse [Dhariwal et al. 2020]. To address it, inspired by [Zeghidour et al. 2022], we implement a hierarchical architecture with multiple residual vector quantization layers and corresponding independent codebooks $\{C_i\}_{i=1}^R$ to iteratively model the motion features, where the size of each codebook is N_{VQ} . As demonstrated in Figure 4, a RVQ layer, e.g., RVQ-i, processes the residue r_l^i from the quantization of the preceding RVQ layer and quantizes it into a discrete feature sequence \hat{z}_l^i by looking up the corresponding codebook C_i as

$$\hat{z}_{l}^{i} = \underset{\hat{z}' \in C_{i}}{\arg \min} \|\hat{z}' - r_{l}^{i}\|_{2}. \tag{2}$$

When i < R, the new residue r_i^{i+1} is calculated as

$$r_l^{i+1} = r_l^i - \hat{z}_l^i. {3}$$

This cycle continues sequentially for R times and finally the input motion feature z_l is quantized into a hierarchical discrete feature sequence $[\hat{z}_l^i]_{i=1}^R$. Notably, the first layer (RVQ-1) actually functions as the standard VQ layer. We treat it as a special RVQ layer, where the preceding residue is $r_l^1 = z_l$. As the number of layers increases, the Residual VQ-VAE demonstrates an exponential expansion in its capacity [Yao et al. 2023]. This enhancement significantly boosts the model's capability for expression.

Finally, we compute the reconstructed motion M^* as

$$M^* = \mathcal{D}_{VO}(\hat{Z}). \tag{4}$$

Following [van den Oord et al. 2017], the loss function is defined as $\frac{1}{2}$

$$\mathcal{L}_{\text{RVQ}} = w_1 \| \boldsymbol{M} - \boldsymbol{M}^* \|_1 + w_2 \| \dot{\boldsymbol{M}} - \dot{\boldsymbol{M}}^* \|_1 + w_2 \| \ddot{\boldsymbol{M}} - \ddot{\boldsymbol{M}}^* \|_1$$

$$+ w_{3} \|\mathcal{E}_{VQ}(\mathbf{M}) - \operatorname{sg}(\left[\sum_{i=1}^{R} \hat{z}_{l}^{i}\right]_{l=1}^{L})\|_{2}^{2}$$

$$+ w_{4} \|\operatorname{sg}(\mathcal{E}_{VQ}(\mathbf{M})) - \left[\sum_{i=1}^{R} \hat{z}_{l}^{i}\right]_{l=1}^{L}\|_{2}^{2},$$
(5)

where \dot{M} and \ddot{M} represent the first-order (velocity) and second-order (acceleration) derivatives of M on time. sg stands for the *stop gradient* operator that prevents the gradient from backpropagating through it. And $[w_i]_{i=1}^4$ corresponds to the weighted factors.




Fig. 3. The process of synthesizing a rhythm-coherent gesture segment consists of: (a) a residual VQ-VAE [Zeghidour et al. 2022] learns a hierarchical categorical space to represent motion as discrete tokens; (b) a powerful GPT-based [Radford et al. 2019] generator predicts the future gesture token conditioned on the preceding gesture tokens and synchronized audio features in an autoregressive manner.




Fig. 4. Residual quantization module. The motion features Z are iteratively quantized by a series of residual quantization layers. The first RVQ layer is a special RVQ layer, where the preceding residue is $\boldsymbol{r}_l^1 = \boldsymbol{z}_l$.

4.2 Gesture Generator

As shown in Figure 3 (b), the gesture generator \mathcal{G} is based on the GPT-2 [Radford et al. 2019], which predicts the future gesture tokens $(\hat{z}^*_{\mathrm{hand},L+1},\,\hat{z}^*_{\mathrm{body},L+1})$ in an autoregressive manner conditioned on preceding motion tokens $(\hat{Z}_{\text{hand}} = [\hat{z}_{\text{hand},l}]_{l=1}^{L}, \hat{Z}_{\text{body}} = [\hat{z}_{\text{body},l}]_{l=1}^{L})$ and the synchronized audio features $A = [a_l]_{l=1}^{L+1}$. The process is formalized as

$$\hat{z}_{\text{hand},L+1}^{*},\hat{z}_{\text{body},L+1}^{*} = \mathcal{G}(A, [\hat{z}_{\text{hand},l}]_{l=1}^{L}, [\hat{z}_{\text{body},l}]_{l=1}^{L}), \tag{6}$$

where the audio features A consist of mel frequency cepstral coefficients (MFCC), MFCC delta, constant-Q chromagram, onset, and tempogram, which are extracted by the famous audio processing toolbox Librosa [McFee et al. 2015]. Our approach incorporates the causal attention layer, as introduced by Vaswani et al. [2017], which is designed to facilitate communication exclusively between current and preceding data, thereby maintaining causality. Following [Radford et al. 2019], we minimize the standard categorical cross-entropy loss to train the generator.

GENERATIVE SEMANTIC GESTURE RETRIEVAL

In this section, we introduce Generative Semantic Gesture Retrieval. The traditional index-retrieval-rank paradigm [Zhu et al. 2023b] retrieves candidate items from a database based on the context of the input query and then ranks these items to determine the final item. Although this method thoroughly considers the semantic distribution of the database, it only supports whole-sentence retrieval and cannot automatically determine the specific occurrence timestamp of the retrieved item within the sentence. To solve it, we choose the generative retrieval architecture inspired by GENRE [Cao et al. 2021]. Specifically, as shown in Figure 5, the whole process is modeled as the standard prompt-based autoregressive generation. Given the input transcript as the prompt, the model will repeat the input and, based on the context, insert the retrieved semantic gesture, e.g., 1 ARM FLEX, at the appropriate position, where 1 represents the index of the gesture. The retrieval model is initialized by the Large Language Model (LLM), ensuring its generalizability. Then, it is finetuned with a small amount of annotated data for task alignment and to perceive the semantic distribution of the semantic gesture set, with specific details to be discussed in Section 5.2.

5.1 SeG: Semantic Gesture Dataset

Gestures are intrinsically linked with semantic information and form a fundamental aspect of human communication. This connection dates back to the use of body postures for expressing intentions, predating the use of written symbols. Meanwhile, the semantic information conveyed by gestures is significantly influenced by cultural backgrounds, leading to substantial differences in gesture meanings across various cultures. To cover such diversity and avoid the ambiguity inherent in semantic gestures, we reference and synthesize findings in the fields of linguistic and human behavioral studies pertaining to semantic gestures [Kipp 2005; Morris 1994;




Fig. 5. The overview of generative semantic gesture retrieval.

SeG Example	Tag	Content
	index	128
	label	PALMS REPEL
	description	The palms of both hands are parallel initially, then they are pushed sideways quickly, as if they are pushing something away.
	contextual meaning	Dismissal (indicating disapproval); pushing away (meeting annoying people)
3 8	example sentence	I'm not ready, please push it aside for the moment.

Fig. 6. The meta-information of a semantic gesture in the SeG Dataset.

Instruction

...Please mark the given transcripts with gestures. Here are the gestures you can use: 3100 ARM FLEX 0210 FOREHEAD SALUTE 3010 ARM RAISE HIGH-LEVEL ...

Input

I think it's safe to say there's never been a moment like this one in all of history.

Outpu

I (3332 TEMPLE TOUCH) think it's safe to say there's never been a moment like this one in all of (2030 ARMS DESCEND) history.

Fig. 7. An example of the instruction dataset for (Large Language Model) LLM fine-tuning.

Wagner and Armstrong 2003; World Federation of the Deaf 1975]. This effort leads to the compilation of a comprehensive semantic gesture dataset (SeG), denoted as $G = [g_i]_{i=1}^{N_{\rm sec}}$, which encompasses $N_{\rm sec}$ types of semantic gestures commonly utilized globally. Each record g in the dataset consists of a sequence of captured motion and its meta-information. Figure 6 shows an example of the meta-information of a semantic gesture in SeG, which includes an index, label, description, contextual meaning, and example sentence, facilitating a thorough organization and analysis of human gestures.

As for motion, we employ professional motion capture equipment to gather high-quality, finger-contained animation. The collection involves two performers, a male and a female. To ensure the diversity




Fig. 8. The process of building a semantics-aware identifier for the semantic gesture.

of motion, performers deliver multiple interpretations and styles for each semantic gesture in the dataset. In total, we capture 1.5 hours of semantic gesture motion data, with each gesture being interpreted in an average of 5.7 in different ways.

5.2 LLM-Based Retrieval Model

Concurrently, we collect twenty 10~20-minute speech transcripts from TED talks [TED Talks 2023] and enlist annotators for manual annotation, thereby creating an instruction dataset to fine-tune Large Language Models (LLMs) for semantic gesture retrieval. Figure 7 shows a case of the instruction dataset. Notably, we explicitly integrate the index information of each gesture into the Instruction part of the dataset and require the model to predict the name of the gesture as well as its index simultaneously. In practice, this trick could significantly alleviate the model to produce hallucinations, including the generation of non-existent gestures and the combination of different body parts and other actions. Intuitively, incorporating such logical information can help enhance the reasoning ability of LLMs, similar to how some studies opt to add some code data when training LLMs [Anil et al. 2023; Touvron et al. 2023]. We choose to fine-tune OpenAI's GPT-3.5-turbo [Ouyang et al. 2022] on the instruction dataset.

Meanwhile, the current instruction data does not take into account the meta-information of semantic gestures, thereby overlooking the rich semantic information it contains. In addition to using example sentence from the meta-information of each gesture to enrich the dataset, we also replace the current indexing identifier for each gesture, a simple combination of increasing numbers and gesture names, with a new semantics-aware indexing identifier. The core idea is to cluster the semantic gestures according to their textual description and index them based on the clusters, making the index implicitly indicate the relationship between different gestures. To be specific, as illustrated in Figure 8, we feed the gesture label, description, and contextual meaning into a sentence-T5-base model [Raffel et al. 2020] to generate a representational embedding vector. Each vector encapsulates the semantic information of a specific gesture within the SeG, and collectively, these vectors form a big gesture embedding set. Then, we apply hierarchical clustering with constrained K-means [Bennett et al. 2000] to these embedding vectors. The resultant index within each cluster is utilized as the final hierarchical semantic number identifiers. We conduct a related ablation study in Section 7.5.3.

Tag	Content	Content	
index	0100	0101	
label	FINGERS RUB	PALM UP	
description	Rubbing the fingertips with the thumb of the same hand.	Similar to the begging, but with the palm flatter and the thumb held stiffly out to the side.	
contextual meaning	Money (physical meaning); solicitation (requesting material gain)	Anticipation (awaiting receipt); solicitation (requesting)	
example sentence	Would you consider leaving a tip?	' l agreed on please take it	

Fig. 9. Comparison of the indexing results of two semantic gestures.




Fig. 10. (a) Determining when to merge each semantic gesture based on audio beats; and (b) how to merge these semantic gestures into the generated rhythmic gestures without affecting the naturalness of the original motion.

For example, as shown in Figure 9, the gestures FINGERS RUB and PALM UP share the same prefix "010" and differ in the 4-th position, indicating similar description or contextual meanings. With these indexes, the final semantic identifiers, e.g., 0100 FINGERS RUB, can capture hierarchical semantics of gestures while ensuring interpretability.

6 SEMANTICS GESTURE ALIGNMENT

We develop an alignment module to merge retrieved semantic gestures into rhythmic gestures synthesized by the generator G at the right timing. Specifically, we need to solve two problems: (a) determining when to merge each semantic gesture; and (b) how to merge these semantic gestures into the generated rhythmic gestures without affecting the naturalness of the original motion. Corresponding solutions are discussed in the following sections.

6.1 When to Merge

To determine when to merge retrieved semantic gestures, a straightforward method is to directly mark the timestamp of the trigger word (such as "opportunity" in Figure 10 (a)) identified by the retrieval model as the *merging timing l*. The trigger word timestamp refers to the midpoint of the time interval in which the word occurs. But this approach would disrupt the ongoing beat gestures or create gestures with unexpected strokes during the subdued parts of the audio, leading to rhythm incongruity. To solve it, as shown in Figure 10 (a), our approach begins with detecting beats of the audio, which likely correspond to the stroke phase of gestures. This phase is recognized as the most expressive and energetically concentrated phase within a gesture's progression [Ferstl et al. 2020]. Subsequently, we identify the beat closest to the timestamp of the trigger word as the final l. The positive impact of this approach on rhythm integrity will be discussed in an ablation study.

6.2 How to Merge

In this section, we aim at explicitly merging retrieved semantic gestures with generated rhythmic gestures at the merging timing *l*. For preparation, we first extract the stroke part of each semantic gesture from the SeG Dataset and crop it into a 1-second segment. Then, these gesture segments are encoded into discrete tokens using \mathcal{E}_{VO} , thereby constructing the SeG token library. Given the index and label of the retrieved semantic gesture, we could search the matched gesture tokens from the library. As illustrated in Figure 10 (b), the following merging process is executed in two phases: (a) we replace the original motion with matched semantic gesture tokens, while aligning the timing *l* with the three-quarters of the way through the matched token sequences. It allows semantic gestures to manifest slightly ahead of the corresponding semantic content in the speech, reflecting the typical 0.4-second planning phase observed in human gestures informed by the behavioral study findings by [Indefrey and Levelt 2004]. To mitigate abrupt and unnatural transitions often associated with hard replacements, inspired by TM2D [Gong et al. 2023], we employ a strategy involving a weighted merge operation at token positions around the replacement site. Explicitly, we increase the merging weight of the matched semantic gesture tokens w_s from 0.3 to 0.7 using a half cosine curve prior to replacement, and subsequently reduce it in the opposite manner after replacement. Meanwhile, the merging weight of the raw motion tokens w_r is set to 1- w_s to maintain the scale of the features. This technique ensures the final animation decoded by \mathcal{D}_{VO} results is not only smooth but also retains the intended semantic richness and rhythmic precision.

Additionally, the gesture generator \mathcal{G} , during pre-training, only utilizes paired speech-gesture data and has not encountered the semantic gesture tokens from the SeG dataset. Before merging, it is necessary to ensure the output motion distribution of \mathcal{G} covering the SeG dataset. Inspired by the Supervised Fine-Tuning (SFT) strategy for LLMs [Wang et al. 2023b], we utilize the speech transcripts with semantic annotation in Section 5.2 and the alignment timestamps of each semantic gestures to construct a new instruction dataset to fine-tune the pre-trained generator \mathcal{G} . The instruction dataset consists of the speech audio synthesized by a Text-to-Speech (TTS) tool [Murf.AI 2023], semantic gesture tokens encoded by \mathcal{E}_{VO} , and their

alignment timestamps. When fine-tuning, the generator takes the synthesized speech audio as input and generates the synchronized gestures, where we only optimize the cross-entropy loss at the merging interval for the target semantic gesture tokens. It could implicitly align the generator with the distribution of semantic gestures and make a preparation for the subsequent explicit merging.

7 EVALUATION

In this section, we initially outline our system's setup, followed by an evaluation of our results. We then compare these results with those from other systems, discuss potential applications, and validate our framework's various design choices through an ablation study.

7.1 System Setup

7.1.1 Speech-Gesture Datasets. As for the speech-gesture datasets, our system is trained and evaluated on two high-quality speech-gesture datasets: ZEGGS [Ghorbani et al. 2023] and BEAT [Liu et al. 2022d]. The ZEGGS Dataset comprises two hours of full-body motion capture and audio from monologues by an English-speaking female actor, performed in 19 distinct styles. Synchronized transcripts are obtained using an automatic speech recognition (ASR) tool [Alibaba 2009]. The BEAT dataset features about 76 hours of multimodal speech data, including audio, transcripts, and full-body motion capture from 30 speakers. These speakers performed in eight emotional styles across four languages. In alignment with the baseline setting in [Liu et al. 2022d], we selectively use the speech data of English speakers 2, 4, 6, and 8.

7.1.2 Instruction Dataset for LLM Fine-Tuning. To construct the annotation instruction dataset in Section 5.2, we collect twenty 10~20-minute speech transcripts and annotate them manually. For gestures not annotated in this process, we use examples from SeG dataset and employ few-shot strategy to prompt GPT-4 [OpenAI 2023a] in generating new annotated sentences containing them. This process mitigates the performance decline caused by the long-tail distribution of semantic gestures. When fine-tuning the LLM, there are a total of 5,410,940 training tokens for naive indexing identifier and 6,113,270 training tokens for semantics-aware indexing identifier, respectively.

7.1.3 Settings. Our system generates semantic-aware gestures at a rate of 60 fps. In configuring the RVQ (Section 4.1), we set the number of residual quantization layers to R = 4, the downsampling rate to d = 8, and the codebook size to C = 512. This system is trained on both the SeG dataset and the speech-gesture datasets (Section 7.1). The parameters w_1 , w_2 , w_3 , and w_4 in the loss function are assigned values of 1, 1, 0.02, and 1, respectively. Regarding the Gesture Generator G (Section 4.2), it is composed of a 12-layer transformer with a width of 768 features and is trained exclusively on speech-gesture datasets. During training, the RVQ is trained using standard motion clips of 2 seconds in length, whereas Gis trained with paired speech and motion clips of 4 seconds. All the models are trained using four NVIDIA 3090Ti GPUs, taking approximately two days for the ZEGGS dataset and five days for the BEAT dataset. For LLM fine-tuning, we train 5 epochs and set batch size to 2, taking approximately one hour.

7.2 Results

Figure 11 shows the visualization results of our system generating gestures conditioned on the semantic gesture retrieval outcomes and synchronized speech. The generator \mathcal{G} employs top-5 sampling methods for token generation during inference and we utilize a physical tracking approach from [Yao et al. 2023] to alleviate the issue of sliding foot in our results. Our system successfully creates realistic gestures that accurately convey the intended meanings, aligning with the respective retrieval results. The character performs a range of semantic gestures, including natural body movements, reasonable arm swings, and delicate finger gesticulations. For example, the character performs suitable pointing gestures when "elephant" and "you" are mentioned. In the meanwhile, "uproot" and "book" are expressively portrayed. For abstract concepts like "strength," the character vividly illustrates them by gesturing towards the biceps. In the supplementary video, when the word "two" is mentioned, the character naturally makes a "V-sign" gesture. This demonstrates that the retrieval model can accurately capture the specific meanings of each semantic gesture in the SeG dataset.

To illustrate the significance of the semantics-aware alignment module, Figure 12 presents the comparative visualization results of synthesis without semantics-aware alignment (the first row) against synthesis with such alignment (the second row). The communicative efficacy of the generated gestures is enhanced through the explicit integration of contextually appropriate, meaningful gestures based on the speech transcript.

7.3 Comparison

Evaluating gestures with objective metrics presents significant challenges. Many current objective metrics poorly correlate with subjective feedback outcomes [Kucherenko et al. 2023]. Echoing approaches in [Alexanderson et al. 2023; Ao et al. 2023; Ghorbani et al. 2023], this study emphasizes user study evaluations for generated results, with quantitative evaluations serving as supplementary references.

7.3.1 Baselines. We compare our system with GestureDiffuCLIP [Ao et al. 2023] on the ZEGGS dataset, using the code provided by its authors. This system learns an implicit shared space between transcripts and gestures, enhancing semantic perception. The BEAT dataset is released alongside a strong baseline, the Cascaded Motion Network (CaMN), which uses transcripts as inputs to generate semantic gestures based on a hierarchical architecture. The related codes for two semantics-aware systems [Gao et al. 2023; Zhi et al. 2023] are not available at the time of writing this work.

7.3.2 User Study. Following the method in [Alexanderson et al. 2023; Ao et al. 2023], we conduct user studies using pairwise comparisons. For each test, participants view two 10-second videos, each synthesized by different models (including the ground truth) for the same speech segment, played one after the other. Participants are required to choose the video they prefer, following the instructions given below the videos, and rate their choice on a scale from 0 to 2, where 0 signifies no preference. The unselected video in the pair is then assigned the inverse score (for instance, if the chosen video is rated 1, the other video is assigned —1). Participant recruitment




Fig. 11. Semantics-aware gestures synthesized by our system conditioned on results of the semantic gesture retrieval and the synchronized speech. The character performs a variety of semantic gestures, including significant body movements, reasonable arm swings, and delicate finger gesticulations.




Fig. 12. Qualitative comparison between synthesis without semantics-aware alignment (first row) and synthesis with alignment (second row).

Table 1. Average scores of user study with 95% confidence intervals. Our system without semantic alignment (w/o semantic alignment) excludes the semantics-aware alignment module for the pre-trained generator. Asterisks indicate the significant effects (*: p < 0.05, **: p < 0.01, **: p < 0.001).

Dataset	System	Human Likeness ↑	Beat Matching↑	Semantic Accuracy ↑
ZEGGS	GT	$0.07 \pm 0.02^*$	$0.15 \pm 0.03^*$	0.51 ± 0.08
	GestureDiffuCLIP	$-0.02 \pm 0.01^*$	-0.05 ± 0.01	$-0.15 \pm 0.10^{**}$
	Ours (w/o semantic alignment)	$-0.08 \pm 0.03^*$	-0.07 ± 0.02	$-0.94 \pm 0.12^{**}$
	Ours	0.02 ± 0.01	-0.05 ± 0.02	0.48 ± 0.07
BEAT	GT	0.43 ± 0.06	0.39 ± 0.06	0.37 ± 0.05
	CaMN	$-1.03 \pm 0.15^{**}$	$-0.91 \pm 0.13^{**}$	$-0.22 \pm 0.04^{**}$
	Ours (w/o semantic alignment)	0.29 ± 0.08	0.32 ± 0.07	$-0.58 \pm 0.07^{**}$
	Ours	0.35 ± 0.04	0.33 ± 0.05	0.41 ± 0.03



Fig. 13. Qualitative comparison between our system and baselines (GestureDiffuCLIP [Ao et al. 2023] and CaMN [Liu et al. 2022d]) using two test speech excerpts.

is conducted via the Credamo platform [Credamo 2017]. Details of the user study are described in Appendix A.

We conduct three distinct preference tests: human likeness, beat matching, and semantic accuracy, incorporating attention checks in each. During the human likeness test, participants determine if the generated motion closely mimics that of a real human. To avoid any speech-induced bias, these video clips are presented without sound. In the beat matching test, participants assess the synchronization of the generated motion with the speech's rhythm. For the semantic accuracy test, participants are required to evaluate whether the generated gestures based on the input speech accurately convey the appropriate semantics. The average scores from these tests are detailed in Table 1. We implement a one-way ANOVA and a post-hoc Tukey multiple comparison test for each user study. The assumptions of normality, homogeneity of variances, and independence for each ANOVA are all met for both the ZEGGS and BEAT datasets.

In the ZEGGS Dataset evaluation, we analyze four methods: the ground-truth gestures (GT), our system (Ours), our system without the semantic alignment module (w/o semantic alignment) for ablation, and GestureDiffuCLIP. After attention checks, we collect the valid answers of 98, 99, 101 participants for the human likeness, beat matching, and semantic accuracy tests, respectively.

Multiple one-way ANOVAs are conducted, one for each questionnaire item. The results reveal that different baselines have statistically significant effects on human likeness (F(3, 4700) = 142.91, p < .05, Partial Eta Squared = 0.083), beat matching (F(3, 4748) = 119.71, p < .05, Partial Eta Squared = 0.071), and semantic accuracy (F(3, 4844) = 250.87, p < .01, Partial Eta Squared = 0.134). Table 1 indicates that, in the human likeness and beat matching tests, the performance differences between Ours and the other methods are not significant. But in the semantic accuracy test, Ours notably excels over both GestureDiffuCLIP and Ours w/o semantic alignment, with a considerable margin (p < 0.001), emphasizing the vital role of the semantic alignment module in enhancing semantic perception. The left part of Figure 13 provides a visual demonstration, showing that the motions generated by GestureDiffuCLIP are less meaningful compared to those from Ours. These results confirm the efficiency of our system in semantic gesture synthesis.

On the BEAT Dataset, our evaluation encompasses four methods: the ground-truth gestures (GT), our system (Ours), our system without the semantic alignment module (w/o semantic alignment) for ablation, and CaMN, with its speaker ID input matched to the ground truth. In the user study, 99, 103, and 100 subjects pass the attention checks for the human likeness, beat matching, and semantic accuracy tests, respectively. Multiple one-way ANOVAs indicate

that different generation methods have main effects on human like $ness\ (F(3,4748)\ =\ 179.92,\ p\ <\ .01,\ Partial\ Eta\ Squared\ =\ 0.102),$ beat matching (F(3,4940) = 271.35, p < .01, Partial Eta Squared =0.141), and semantic accuracy (F(3, 4796) = 151.52, p < .01, PartialEta Squared = 0.087). As shown in Table 1, in the human likeness and beat matching tests, GT, Ours, and Ours w/o semantic alignment perform comparably and surpass CaMN (p < 0.001). For the semantic accuracy test, Ours outscore other baselines (p < 0.001), but the score of Ours (w/o semantic alignment) decreases significantly due to the lack of semantic alignment. It highlights the essential role of the semantic alignment module in maintaining semantic consistency between speech and gestures. The right part of Figure 13 illustrates that gestures generated by our system exhibit greater communicative efficacy compared to those produced by CaMN.

7.3.3 Quantitative Evaluation. We quantitatively evaluate the human likeness of generated motion and speech-gesture semantic matching using two metrics, i.e., Fréchet Gesture Distance (FGD) [Yoon et al. 2020] and Semantic Score (SC) [Ao et al. 2023], respectively. The Fréchet Gesture Distance (FGD) quantifies the disparity between the latent feature distributions of generated and real gestures. Commonly employed to evaluate gesture perceptual quality, a lower FGD indicates superior motion quality. The Semantic Score (SC) assesses the semantic coherence between speech and generated gestures. It computes the cosine similarity in the semantic space between generated motion and ground-truth transcripts, as defined in the gesture-transcript embedding framework by Ao et al. [2023]. SC ranges from -1 to 1, with a higher SC indicating more effective speech-gesture content alignment. Besides, the FGD and SC are computed using sentence-level motion segments. We compute the mean (± standard deviation) values for each metric by generating on the test data 10 times.

As shown in Table 2, our system surpasses all baseline comparisons in both metrics, FGD and SC. Notably, discarding the semantic alignment module leads to a substantial decrease in the SC value of our system, underscoring the module's critical role. Meanwhile, the FGD value remains relatively unchanged with the addition of the semantic alignment module. This suggests that the fusion operation within this module does not degrade the quality of the motion. The SC metric exhibits a decline in our system when semantic gestures are indexed with increasing numbers (w/ naive indexer). This trend suggests that the semantics-aware indexing identifier, as detailed in Section 5.2, can effectively enhance the performance of the gesture retrieval model.

7.4 **Gesture Editing**

Our SeG dataset (Section 5.1) faces two primary issues: a) the variations of each semantic gesture is restricted; and b) there is a discrepancy between the captured motion and the real, spontaneous speech gestures. To enrich the diversity and bridge the gap, we propose a data augmentation framework to retrieve the semantically similar gesture segment M' corresponding to the given semantic gesture g from other existing datasets, e.g., G'. G' is derived from 2D videos. We measure the semantic relevance between gesture sequences in two dimensions: (a) a high-level filtering based on the meta-information of g; and (b) a low-level movement matching




Fig. 14. The data augmentation consists of two stages: (a) a high-level filtering utilizes the GPT-4V [OpenAl 2023b] to filter out candidate gesture segments from the motion base according to the meta-information of the semantic gesture anchor; and (b) an example of finding joint-level similar motion in the latent space of RVQ. The red point represents the embedding of semantic gesture 3030 ARMS RAISE V-SHAPE. We can find similar motion within an appropriate threshold.

between M' and motion part M of g. Details of these methods are introduced in the following sections.

Based on the augmentation method, we are able to achieve flexible editing of the generated semantic gestures. For instance, as illustrated in Figure 15, we employ a large multi-modality model to select appropriate semantic gestures from in-the-wild 2D videos conditioned on the meta-information of the retrieved semantic gesture, and align the new semantic gestures with original motion sequence. Furthermore, users can flexibly control the style and appearance of the final generated gestures by customizing a 2D video library. Please refer to the supplementary video for more visualization results.

7.4.1 High-Level Filtering. We first utilize the GPT-4 with vision (GPT-4V) [OpenAI 2023b], which is a powerful multimodal model and supports both image and text inputs, to filter out candidate gesture segments from G' according to the meta-information of the anchor g. Specifically, as shown in Figure 14 (a), each segment in the motion set G' corresponds to a sequence of image frames. These image frames are about 1 second in duration, and we uniformly sample 5 images as the image prompt for GPT-4V. Meanwhile, the meta-information of the semantic gesture anchor is added as the text prompt. GPT-4V analyzes these prompts and selects the final candidate segments, matching them with the textual description of the anchor g. These selected segments are converted into 3D motion sequences using a pose estimation tool [DeepMotion 2024].

7.4.2 Low-Level Matching. To refine the results of GPT-4V and ensure motion plausibility, we further select gestures from candidate motion segments that are similar to the semantic gesture anchor at the movement level. Specifically, we use the RVQ encoder \mathcal{E}_{VO} to encode the motion part M of the anchor and one of the selected

Table 2. Quantitative evaluation on the ZEGGS and BEAT Datasets. This table reports the mean (± standard deviation) values for each metric by synthesizing on the test data 10 times.

Dataset	System	FGD ↓	SC↑
ZEGGS	GT	-	0.55
	GestureDiffuCLIP	81.73 ± 3.27	0.21 ± 0.07
	Ours (w/o semantic alignment)	82.02 ± 2.49	0.09 ± 0.02
	Ours (w/ naive indexer)	81.88 ± 2.23	0.30 ± 0.03
	Ours	81.22 ± 2.53	0.38 ± 0.05
BEAT	GT	-	0.65
	CaMN	105.42 ± 0.00	0.21 ± 0.00
	Ours (w/o semantic alignment)	89.73 ± 2.11	0.08 ± 0.02
	Ours (w/ naive indexer)	89.58 ± 2.23	0.38 ± 0.01
	Ours	89.15 ± 2.06	0.45 ± 0.09




Fig. 15. An example of gesture editing (Section 7.4). We use GPT-4V to filter appropriate semantic gestures from in-the-wild 2D videos to edit the original motion segment.

motion segment M' into corresponding latent sequences Z and Z', respectively. These sequences are then averaged along the temporal dimension into \overline{z} and \overline{z}' , respectively. We compute the Euclidean distance between these two embeddings as the similarity score. If the score falls below the predefined threshold, M' is selected. Finally, we obtain semantically relevant gestures from G', thereby enriching the diversity of the gesture library. Figure 14 (b) illustrates an example of this process.

7.5 Ablation Study

Our analysis focuses on the effects of various architectures of the gesture tokenizer, the semantics-aware indexing identifier, and differing configurations of the semantics-aware alignment module on our system's performance. These findings are detailed in Figure 12, Table 1, Table 2, Figure 16, and the supplementary video.

7.5.1 LLM-Based Retrieval Model. In this experiment, we compare three different strategies, zero-shot, few-shot and finetuned LLM, which have exactly the same instruction settings and simultaneously contain the index information of all semantic gestures. Zero-shot strategy only has instruction settings, few-shot strategy has some examples of output formats, and the finetuned LLM is trained on the instruction dataset. We select GPT-3.5-turbo-1106 as the base model. There are two commonly used evaluation methods for LLM:

automatic evaluation as quantitative analysis and human evaluation as qualitative analysis [Chang et al. 2023]. We conduct a qualitative analysis and present several examples in Figure 16. With the same instruction, the zero-shot LLM struggles to perform adequately, failing to generate valid gestures or comprehend semantic information effectively. For example, from Figure 16 we can see that zero-shot LLM can not always produce appropriate gesture labels. The few-shot LLM effectively performs the annotation task and produces valid gesture labels but falls short in fully understanding semantic information. The fine-tuned model addresses all these requirements robustly, and can understand the semantics of gestures.

It is challenging to design an effective quantitative pipeline to evaluate the outcomes of LLM because there is a lack of credible metrics to judge whether the response is aligned with human performance. As explored in the NLP field [Zhang et al. 2023c], a potential approach is to utilize the LLM itself for evaluation and stabilize the results through multiple independent evaluations. Details and results of the quantitative evaluation are described in Appendix B.

7.5.2 Architecture of Gesture Tokenizer. In this experiment, we train the gesture tokenizer (Section 4.1) with three different architectures, i.e., (1D-Conv+Transformer, RVQ), (1D-Conv, RVQ), and (1D-Conv+Transformer, VQ) to investigate the impact of the

zero-shot	few-shot	finetune	
[ARMS RAISE HIGH-LEVEL] Now five years later,	Now (0002 MOUTH BUGLE) five years later,	Now five (0332 FINGERS 'FIVE') years later,	
[ARMS WELCOME] There's an emptiness	There's an emptiness (0033 HANDS GAME)	There's an emptiness (0303 HANDS DRAW-OUTLINE)	
FAIL TO LABEL THE SENTENCE	Imagine for a second (0232 ARM GRATITUDE) that	Imagine for a second (2211 FOREFINGER RAISE) that	
[HEAD NOD] Sooner or later, I think we all wonder, is this all there is?	Sooner (3232 HEAD SHAKE) or later, I think we all wonder (1132 HEAD SCRATCH), is this all there is?	Sooner or later, I think we all wonder (1200 BEARD STROKE), is this all there is (1203 FINGERS STEEPLE)?	

Fig. 16. The comparison of three strategies.

Transformer layer and the residual quantization layer on motion encoding, respectively. "1D-Conv+Transformer" refers to a tokenizer whose encoder and decoder consist of 1D convolutional layers and the Transformer layer. We conduct comparisons by observing the quality of the reconstructed motion. As demonstrated in the supplementary video, motion reconstructed using RVQ based solely on 1D convolutional layers tend to exhibit jitter, while those using a vanilla quantization layer are prone to losing fine details, such as finger movements.

7.5.3 Semantics-Aware Indexing Identifier. In this experiment, we train and compare two generative retrieval models (Section 5.2) using the naive and semantics-aware indexing identifiers, respectively. The naive approach involves indexing semantic gestures with sequentially increasing numbers. Table 2 reveals that the semanticsaware metric, SC, experiences a decrease with the naive indexing approach. This observation confirms that the semantics-aware indexing identifier effectively improves the semantic consistency between speech and gestures.

7.5.4 Semantics-Aware Alignment. We conduct three experiments to study the semantics-aware alignment module (Section 6) from a holistic to a localized perspective. First, we discard the whole semantic alignment module, resulting in a significant drop in relevant semantic metrics, such as semantic accuracy (Table 1) and SC (Table 2). Figure 12 also demonstrates that gestures synthesized by Ours (w/o semantic alignment) perform low communicative efficacy. Then, we do not consider audio beats when determining the merging timing (Section 6.1) for each retrieved semantic gesture. As shown in the supplementary video, the rhythmic harmony of the generated gestures is disrupted. Lastly, we discard the weighted merge operation (Section 6.2) when replacing the original motion with retrieved semantic gestures. As demonstrated in the supplementary video, the generated motion exhibits unnatural transitions.

CONCLUSION

In this paper, we present Semantic Gesticulator, a semantics-aware co-speech gesture synthesis system that generates realistic and meaningful gestures while maintaining rhythmic coherence with speech. Initially, we develop a GPT-based gesture generative model, trained using hierarchical discrete tokens extracted by a scalable,

body part-aware residual VQ-VAE. This architecture effectively produces gestures that are rhythmically coherent and exhibit robust generalization across a wide range of audio inputs. Subsequently, we employ a powerful large language model (LLM) to establish a generative semantic gesture retrieval framework. This framework analyzes the context of speech transcripts and efficiently retrieves suitable semantic gestures from our self-collected, high-quality gesture library, namely the SeG Dataset. This dataset encompasses a comprehensive array of semantic gestures frequently utilized in human communication. Finally, we introduce a semantic alignment mechanism. This mechanism merges retrieved semantic gestures with generated rhythmic gestures at the latent space level, ensuring that the resulting gestures are both meaningful and rhythmically synchronized. We carry out a comprehensive series of experiments to assess our framework. Our system surpasses all baseline comparisons in terms of both qualitative and quantitative measures, demonstrated by the results of FGD and SC metrics, as well as user study outcomes. For applications, we devise an augmentation framework for identifying semantically similar gestures from an extensive collection of 2D videos, thereby enhancing the diversity of gestures. Moreover, through customizing a 2D video library, users can flexibly edit the style of final outcomes.

There is still room for improvement in our current research. First, the semantic gesture retrieval model only considers the textual information of each gesture and the input speech transcript, neglecting the inherent rhythm of speech audio. This may result in retrieving redundant gestures in areas lacking prominent prosody (moments when the speaker typically does not perform semantic gestures), or missing the corresponding semantic gestures in instances where prosody is significant. Employing a model to integrate multiple modalities, such as textual descriptions, gesture example images, and speech audio, can further enhance the accuracy of semantic gesture mining. Moreover, our retrieval model occasionally retrieves an excess of semantic gestures than necessary, failing to align with user preferences. We have observed that our annotators tend to label as many potential gestures as possible, which contributes to this issue. Our system currently supports users in manually revising the retrieval results. A potential way to achieve this automatically is to employ a LLM as a discriminator to refine the results of semantic gesture retrieval. A user may specify their preferences via prompting and let the LLM adjust the frequency of retrieved semantic gestures to a suitable degree.

Second, we employ a straightforward but effective merging strategy to align the retrieved semantic gestures with the generator's outcomes. However, we only align the stroke phase of semantic gestures to the audio beats to maintain the existing gesture sequence's phases. A more phase-informed strategy may better preserve motion details. Concurrently, augmenting the pool of semantic gesture samples with additional references and training a specialized generator could pave the way for the creation of a more varied range of semantic gestures. To further align the pre-trained generator \mathcal{G} with semantic preferences or even human values, methods like reinforcement learning with human feedback [Christiano et al. 2023; Ouyang et al. 2022] and Direct Preference Optimization (DPO) [Rafailov et al. 2023] can be explored to enhance the model's capabilities.

Third, the motion quality exhibits certain deficiencies, such as foot sliding and excessive upper-body movements. The former issue can be alleviated by employing additional constraints in training and by using IK-based post-processing. The latter is partially caused by exaggerated gesture performance in motion data. Constructing a more curated dataset may address this problem.

Finally, our system enhances the communicative efficacy of generated gestures by explicitly specifying appropriate semantic gestures. Expanding this system to two-party, and even multi-party conversational scenarios, is a direction worth exploring in the future.

ACKNOWLEDGMENTS

We thank the anonymous reviewers for their constructive comments. This work was supported in part by National Key R&D Program of China 2022ZD0160803.

REFERENCES

- Simon Alexanderson, Gustav Eje Henter, Taras Kucherenko, and Jonas Beskow. 2020. Style-Controllable Speech-Driven Gesture Synthesis Using Normalising Flows. Computer Graphics Forum 39, 2 (2020), 487–496. https://doi.org/10.1111/cgf.13946
- Simon Alexanderson, Rajmund Nagy, Jonas Beskow, and Gustav Eje Henter. 2023. Listen, denoise, action! audio-driven motion synthesis with diffusion models. *ACM Transactions on Graphics (TOG)* 42, 4 (2023), 1–20.
- Alibaba. 2009. Alibaba Cloud Automatic Speech Recognition. Accessed: 2023-12-15.
- Rohan Anil, Andrew M. Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, Eric Chu, Jonathan H. Clark, Laurent El Shafey, Yanping Huang, Kathy Meier-Hellstern, Gaurav Mishra, Erica Moreira, Mark Omernick, Kevin Robinson, Sebastian Ruder, Yi Tay, Kefan Xiao, Yuanzhong Xu, Yujing Zhang, Gustavo Hernandez Abrego, Junwhan Ahn, Jacob Austin, Paul Barham, Jan Botha, James Bradbury, Siddhartha Brahma, Kevin Brooks, Michele Catasta, Yong Cheng, Colin Cherry, Christopher A. Choquette-Choo, Aakanksha Chowdhery, Clément Crepy, Shachi Dave, Mostafa Dehghani, Sunipa Dev, Jacob Devlin, Mark Díaz, Nan Du, Ethan Dyer, Vlad Feinberg, Fangxiaoyu Feng, Vlad Fienber, Markus Freitag, Xavier Garcia, Sebastian Gehrmann, Lucas Gonzalez, Guy Gur-Ari, Steven Hand, Hadi Hashemi, Le Hou, Joshua Howland, Andrea Hu, Jeffrey Hui, Jeremy Hurwitz, Michael Isard, Abe Ittycheriah, Matthew Jagielski, Wenhao Jia, Kathleen Kenealy, Maxim Krikun, Sneha Kudugunta, Chang Lan, Katherine Lee, Benjamin Lee, Eric Li, Music Li, Wei Li, YaGuang Li, Jian Li, Hyeontaek Lim, Hanzhao Lin, Zhongtao Liu, Frederick Liu, Marcello Maggioni, Aroma Mahendru, Joshua Maynez, Vedant Misra, Maysam Moussalem, Zachary Nado, John Nham, Eric Ni, Andrew Nystrom, Alicia Parrish, Marie Pellat, Martin Polacek, Alex Polozov, Reiner Pope, Siyuan Qiao, Emily Reif, Bryan Richter, Parker Riley, Alex Castro Ros, Aurko Roy, Brennan Saeta, Rajkumar Samuel, Renee Shelby, Ambrose Slone, Daniel Smilkov, David R. So, Daniel Sohn, Simon Tokumine, Dasha Valter, Vijay Vasudevan, Kiran Vodrahalli, Xuezhi Wang, Pidong Wang, Zirui Wang, Tao Wang, John Wieting, Yuhuai Wu, Kelvin Xu, Yunhan Xu, Linting Xue, Pengcheng Yin, Jiahui Yu, Qiao Zhang, Steven Zheng, Ce Zheng, Weikang Zhou, Denny Zhou, Slav Petrov, and Yonghui Wu. 2023. PaLM 2 Technical Report. arXiv:2305.10403 [cs.CL]
- Tenglong Ao, Qingzhe Gao, Yuke Lou, Baoquan Chen, and Libin Liu. 2022. Rhythmic Gesticulator: Rhythm-Aware Co-Speech Gesture Synthesis with Hierarchical Neural Embeddings. ACM Trans. Graph. 41, 6, Article 209 (nov 2022), 19 pages. https://doi.org/10.1145/3550454.3555435
- Tenglong Ao, Zeyi Zhang, and Libin Liu. 2023. GestureDiffuCLIP: Gesture Diffusion Model with CLIP Latents. 42, 4, Article 42 (jul 2023), 18 pages. https://doi.org/10. 1145/3592097
- K.P. Bennett, P.S. Bradley, and A. Demiriz. 2000. Constrained K-Means Clustering. Technical Report MSR-TR-2000-65. 8 pages. https://www.microsoft.com/en-us/research/publication/constrained-k-means-clustering/
- Michele Bevilacqua, Giuseppe Ottaviano, Patrick Lewis, Wen tau Yih, Sebastian Riedel, and Fabio Petroni. 2022. Autoregressive Search Engines: Generating Substrings as Document Identifiers. arXiv:2204.10628 [cs.CL]
- Uttaran Bhattacharya, Elizabeth Childs, Nicholas Rewkowski, and Dinesh Manocha. 2021a. Speech2AffectiveGestures: Synthesizing Co-Speech Gestures with Generative Adversarial Affective Expression Learning. In Proceedings of the 29th ACM International Conference on Multimedia (Virtual Event, China) (MM '21). Association for Computing Machinery, New York, NY, USA, 2027–2036. https://doi.org/10.1145/3474085.3475223
- Uttaran Bhattacharya, Nicholas Rewkowski, Abhishek Banerjee, Pooja Guhan, Aniket Bera, and Dinesh Manocha. 2021b. Text2Gestures: A Transformer-Based Network

- for Generating Emotive Body Gestures for Virtual Agents. In 2021 IEEE Conference on Virtual Reality and 3D User Interfaces (IEEE VR). IEEE.
- Nicola De Cao, Gautier Izacard, Sebastian Riedel, and Fabio Petroni. 2021. Autoregressive Entity Retrieval. arXiv:2010.00904 [cs.CL]
- Zhe Cao, Tomas Simon, Shih-En Wei, and Yaser Sheikh. 2017. Realtime multi-person 2d pose estimation using part affinity fields. In Proceedings of the IEEE conference on computer vision and pattern recognition. 7291–7299.
- Justine Cassell, Catherine Pelachaud, Norman Badler, Mark Steedman, Brett Achorn, Tripp Becket, Brett Douville, Scott Prevost, and Matthew Stone. 1994. Animated Conversation: Rule-Based Generation of Facial Expression, Gesture & Spoken Intonation for Multiple Conversational Agents. In Proceedings of the 21st Annual Conference on Computer Graphics and Interactive Techniques (SIGGRAPH '94). Association for Computing Machinery, New York, NY, USA, 413–420. https: //doi.org/10.1145/192161.192272
- Justine Cassell, Hannes Högni Vilhjálmsson, and Timothy Bickmore. 2001. BEAT: The Behavior Expression Animation Toolkit. In Proceedings of the 28th Annual Conference on Computer Graphics and Interactive Techniques (SIGGRAPH '01). Association for Computing Machinery, New York, NY, USA, 477–486. https://doi.org/10.1145/ 383259.383315
- Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie. 2023. A Survey on Evaluation of Large Language Models. arXiv:2307.03109 [cs.CL]
- Junming Chen, Yunfei Liu, Jianan Wang, Ailing Zeng, Yu Li, and Qifeng Chen. 2023.
 DiffSHEG: A Diffusion-Based Approach for Real-Time Speech-driven Holistic 3D Expression and Gesture Generation. Preprint (2023).
- Jiangui Chen, Ruqing Zhang, Jiafeng Guo, Yiqun Liu, Yixing Fan, and Xueqi Cheng. 2022. CorpusBrain: Pre-train a Generative Retrieval Model for Knowledge-Intensive Language Tasks. In Proceedings of the 31st ACM International Conference on Information & Computer Management (CIKM '22). ACM. https://doi.org/10.1145/ 3511808.3557271
- Kiran Chhatre, Radek Daněček, Nikos Athanasiou, Giorgio Becherini, Christopher Peters, Michael J Black, and Timo Bolkart. 2023. Emotional Speech-driven 3D Body Animation via Disentangled Latent Diffusion. arXiv preprint arXiv:2312.04466 (2023).
- Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2023. Deep reinforcement learning from human preferences. arXiv:1706.03741 [stat.ML]
- Credamo. 2017. Credamo: an online data survey platform. Accessed: 2023-12-15.
- DeepMotion. 2024. DeepMotion AI Motion Capture & Body Tracking. Accessed: 2024-1-2.
- Anna Deichler, Shivam Mehta, Simon Alexanderson, and Jonas Beskow. 2023. Diffusion-based co-speech gesture generation using joint text and audio representation. In *Proceedings of the 25th International Conference on Multimodal Interaction*. 755–762.
- Prafulla Dhariwal, Heewoo Jun, Christine Payne, Jong Wook Kim, Alec Radford, and Ilya Sutskever. 2020. Jukebox: A generative model for music. arXiv preprint arXiv:2005.00341 (2020).
- Ylva Ferstl and Rachel McDonnell. 2018. IVA: Investigating the use of recurrent motion modelling for speech gesture generation. In IVA '18 Proceedings of the 18th International Conference on Intelligent Virtual Agents. https://trinityspeechgesture.scss.tcd. ie
- Ylva Ferstl, Michael Neff, and Rachel McDonnell. 2020. Adversarial gesture generation with realistic gesture phasing. *Computers & Graphics* 89 (2020), 117–130. https://doi.org/10.1016/j.cag.2020.04.007
- Ylva Ferstl, Michael Neff, and Rachel McDonnell. 2021. ExpressGesture: Expressive gesture generation from speech through database matching. Computer Animation and Virtual Worlds 32 (05 2021). https://doi.org/10.1002/cav.2016
- Nan Gao, Zeyu Zhao, Zhi Zeng, Shuwu Zhang, and Dongdong Weng. 2023. Ges-GPT: Speech Gesture Synthesis With Text Parsing from GPT. arXiv preprint arXiv:2303.13013 (2023).
- Saeed Ghorbani, Ylva Ferstl, Daniel Holden, Nikolaus F. Troje, and Marc-André Carbonneau. 2023. ZeroEGGS: Zero-shot Example-based Gesture Generation from Speech. Computer Graphics Forum 42, 1 (2023), 206–216. https://doi.org/10.1111/cgf.14734 arXiv:https://onlinelibrary.wiley.com/doi/pdf/10.1111/cgf.14734
- Shiry Ginosar, Amir Bar, Gefen Kohavi, Caroline Chan, Andrew Owens, and Jitendra Malik. 2019. Learning Individual Styles of Conversational Gesture. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).
- Kehong Gong, Dongze Lian, Heng Chang, Chuan Guo, Zihang Jiang, Xinxin Zuo, Michael Bi Mi, and Xinchao Wang. 2023. TM2D: Bimodality Driven 3D Dance Generation via Music-Text Integration. arXiv:2304.02419 [cs.CV]
- Ikhsanul Habibie, Mohamed Elgharib, Kripasindhu Sarkar, Ahsan Abdullah, Simbarashe Nyatsanga, Michael Neff, and Christian Theobalt. 2022. A Motion Matching-Based Framework for Controllable Gesture Synthesis from Speech. In ACM SIGGRAPH 2022 Conference Proceedings (Vancouver, BC, Canada) (SIGGRAPH '22). Association for Computing Machinery, New York, NY, USA, Article 46, 9 pages. https://doi.org/10.1145/3528233.3530750

- Ikhsanul Habibie, Weipeng Xu, Dushyant Mehta, Lingjie Liu, Hans-Peter Seidel, Gerard Pons-Moll, Mohamed Elgharib, and Christian Theobalt. 2021. Learning Speech-Driven 3D Conversational Gestures from Video. In Proceedings of the 21st ACM International Conference on Intelligent Virtual Agents (Virtual Event, Japan) (IVA '21). Association for Computing Machinery, New York, NY, USA, 101-108. https: //doi.org/10.1145/3472306.3478335
- P Indefrey and W.J.M Levelt. 2004. The spatial and temporal signatures of word production components. Cognition 92, 1 (2004), 101-144. https://doi.org/10.1016/j. cognition.2002.06.001 Towards a New Functional Anatomy of Language.
- Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. 2022. Few-shot learning with retrieval augmented language models. arXiv preprint arXiv:2208.03299 (2022).
- Longbin Ji, Pengfei Wei, Yi Ren, Jinglin Liu, Chen Zhang, and Xiang Yin. 2023. C2G2: Controllable Co-speech Gesture Generation with Latent Diffusion Model. arXiv preprint arXiv:2308.15016 (2023).
- Michael Kipp. 2004. Gesture Generation by Imitation: From Human Behavior to Computer Character Animation. Dissertation.com, Boca Raton.
- Michael Kipp. 2005. Gesture generation by imitation: from human behavior to computer character animation. https://api.semanticscholar.org/CorpusID:26271318
- Stefan Kopp, Brigitte Krenn, Stacy Marsella, Andrew N. Marshall, Catherine Pelachaud, Hannes Pirker, Kristinn R. Thórisson, and Hannes Vilhjálmsson. 2006. Towards a Common Framework for Multimodal Generation: The Behavior Markup Language. In Proceedings of the 6th International Conference on Intelligent Virtual Agents (Marina Del Rey, CA) (IVA'06). Springer-Verlag, Berlin, Heidelberg, 205-217. https://doi. org/10.1007/11821830 17
- Taras Kucherenko, Patrik Jonell, Sanne van Waveren, Gustav Eje Henter, Simon Alexandersson, Iolanda Leite, and Hedvig Kjellström. 2020. Gesticulator: A Framework for Semantically-Aware Speech-Driven Gesture Generation. In Proceedings of the 2020 International Conference on Multimodal Interaction (Virtual Event, Netherlands) (ICMI '20). Association for Computing Machinery, New York, NY, USA, 242-250. https://doi.org/10.1145/3382507.3418815
- Taras Kucherenko, Rajmund Nagy, Patrik Jonell, Michael Neff, Hedvig Kjellström, and Gustav Eie Henter, 2021. Speech2Properties2Gestures: Gesture-Property Prediction as a Tool for Generating Representational Gestures from Speech. In Proceedings of the 21th ACM International Conference on Intelligent Virtual Agents (Virtual Event, Japan) (IVA '21). Association for Computing Machinery, New York, NY, USA. https: //doi.org/10.1145/3472306.347833
- Taras Kucherenko, Pieter Wolfert, Youngwoo Yoon, Carla Viegas, Teodor Nikolov, Mihail Tsakov, and Gustav Eje Henter. 2023. Evaluating gesture-generation in a largescale open challenge: The GENEA Challenge 2022. arXiv preprint arXiv:2303.08737
- Gilwoo Lee, Zhiwei Deng, Shugao Ma, Takaaki Shiratori, Siddhartha S Srinivasa, and Yaser Sheikh. 2019. Talking with hands 16.2 m: A large-scale dataset of synchronized body-finger motion and audio for conversational motion analysis and synthesis. In $Proceedings\ of\ the\ IEEE/CVF\ International\ Conference\ on\ Computer\ Vision.\ 763-772.$
- Sergey Levine, Philipp Krähenbühl, Sebastian Thrun, and Vladlen Koltun. 2010. Gesture Controllers. ACM Trans. Graph. 29, 4, Article 124 (jul 2010), 11 pages. https: //doi.org/10.1145/1778765.1778861
- Sergey Levine, Christian Theobalt, and Vladlen Koltun. 2009. Real-Time Prosody-Driven Synthesis of Body Language. ACM Trans. Graph. 28, 5 (dec 2009), 1-10. https://doi.org/10.1145/1618452.1618518
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. Advances in Neural Information Processing Systems 33 (2020), 9459-9474.
- Jing Li, Di Kang, Wenjie Pei, Xuefei Zhe, Ying Zhang, Zhenyu He, and Linchao Bao. 2021. Audio2Gestures: Generating Diverse Gestures From Speech Audio With Conditional Variational Autoencoders. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV). 11293-11302.
- Yongqi Li, Nan Yang, Liang Wang, Furu Wei, and Wenjie Li. 2023. Multiview Identifiers Enhanced Generative Retrieval. arXiv:2305.16675 [cs.CL]
- Yuanzhi Liang, Qianyu Feng, Linchao Zhu, Li Hu, Pan Pan, and Yi Yang. 2022. SEEG: Semantic Energized Co-Speech Gesture Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). 10473-10482.
- Haiyang Liu, Naoya Iwamoto, Zihao Zhu, Zhengqing Li, You Zhou, Elif Bozkurt, and Bo Zheng. 2022a. DisCo: Disentangled Implicit Content and Rhythm Learning for Diverse Co-Speech Gestures Synthesis. In Proceedings of the 30th ACM International Conference on Multimedia (Lisboa, Portugal) (MM '22). Association for Computing Machinery, New York, NY, USA, 3764-3773. https://doi.org/10.1145/3503161.
- Haiyang Liu, Zihao Zhu, Giorgio Becherini, Yichen Peng, Mingyang Su, You Zhou, Xuefei Zhe, Naoya Iwamoto, Bo Zheng, and Michael J. Black. 2023. EMAGE: Towards Unified Holistic Co-Speech Gesture Generation via Masked Audio Gesture Modeling. arXiv:2401.00374 [cs.CV]

- Haiyang Liu, Zihao Zhu, Naoya Iwamoto, Yichen Peng, Zhengqing Li, You Zhou, Elif Bozkurt, and Bo Zheng. 2022d. BEAT: A Large-Scale Semantic and Emotional Multi-Modal Dataset for Conversational Gestures Synthesis. In European conference on computer vision
- Xian Liu, Qianyi Wu, Hang Zhou, Yuanqi Du, Wayne Wu, Dahua Lin, and Ziwei Liu. 2022b. Audio-Driven Co-Speech Gesture Video Generation. In Advances in Neural Information Processing Systems, Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (Eds.).
- Xian Liu, Qianyi Wu, Hang Zhou, Yinghao Xu, Rui Qian, Xinyi Lin, Xiaowei Zhou, Wayne Wu, Bo Dai, and Bolei Zhou. 2022c. Learning Hierarchical Cross-Modal Association for Co-Speech Gesture Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). 10462-10472.
- Shuhong Lu, Youngwoo Yoon, and Andrew Feng. 2023. Co-Speech Gesture Synthesis using Discrete Gesture Token Learning. arXiv preprint arXiv:2303.12822 (2023).
- Brian McFee, Colin Raffel, Dawen Liang, Daniel P Ellis, Matt McVicar, Eric Battenberg, and Oriol Nieto. 2015. librosa: Audio and music signal analysis in python. In Proceedings of the 14th python in science conference, Vol. 8. 18-25.
- David McNeill. 1992. Hand and Mind: What Gestures Reveal about Thought. University of Chicago Press.
- Shivam Mehta, Siyang Wang, Simon Alexanderson, Jonas Beskow, Éva Székely, and Gustav Eje Henter. 2023. Diff-TTSG: Denoising probabilistic integrated speech and gesture synthesis. arXiv preprint arXiv:2306.09417 (2023).
- Desmond Morris. 1994. Bodytalk: A World Guide to Gestures. semanticscholar.org/CorpusID:193353377
- Murf.AI. 2023. Murf.AI: An Online Text-to-Speech Tool. Accessed: 2023-12-15.
- Michael Neff, Michael Kipp, Irene Albrecht, and Hans-Peter Seidel. 2008. Gesture Modeling and Animation Based on a Probabilistic Re-Creation of Speaker Style. ACM Trans. Graph. 27, 1, Article 5 (mar 2008), 24 pages. https://doi.org/10.1145/ 1330511.1330516
- Evonne Ng, Javier Romero, Timur Bagautdinov, Shaojie Bai, Trevor Darrell, Angjoo Kanazawa, and Alexander Richard. 2024. From Audio to Photoreal Embodiment: Synthesizing Humans in Conversations. In ArXiv.
- Simbarashe Nyatsanga, Taras Kucherenko, Chaitanya Ahuja, Gustav Eje Henter, and Michael Neff. 2023. A Comprehensive Review of Data-Driven Co-Speech Gesture Generation. https://doi.org/10.48550/ARXIV.2301.05339
- OpenAI. 2022. ChatGPT: Optimizing Language Models for Dialogue. Accessed: 2023-05-
- OpenAI. 2023a. GPT-4 System Card. https://openai.com/research/gpt-4 Accessed: 2023-12-15.
- OpenAI. 2023b. GPT-4 Vision System Card. https://openai.com/research/gpt-4vsystem-card Accessed: 2023-12-15.
- Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. arXiv:2203.02155 [cs.CL]
- Kunkun Pang, Dafei Qin, Yingruo Fan, Julian Habekost, Takaaki Shiratori, Junichi Yamagishi, and Taku Komura. 2023. BodyFormer: Semantics-Guided 3D Body Gesture Synthesis with Transformer. ACM Trans. Graph. 42, 4, Article 43 (jul 2023), 12 pages. https://doi.org/10.1145/3592456
- Xingqun Qi, Chen Liu, Lincheng Li, Jie Hou, Haoran Xin, and Xin Yu. 2023a. EmotionGesture: Audio-Driven Diverse Emotional Co-Speech 3D Gesture Generation. arXiv preprint arXiv:2305.18891 (2023).
- Xingqun Qi, Jiahao Pan, Peng Li, Ruibin Yuan, Xiaowei Chi, Mengfei Li, Wenhan Luo, Wei Xue, Shanghang Zhang, Qifeng Liu, et al. 2023b. Weakly-Supervised Emotion Transition Learning for Diverse 3D Co-speech Gesture Generation. arXiv preprint arXiv:2311.17532 (2023)
- Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. 2018. Improving language understanding by generative pre-training. (2018).
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. OpenAI blog 1, 8 (2019), 9.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. arXiv:2305.18290 [cs.LG]
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. Journal of Machine Learning Research 21, 140 (2020), 1-67. http://jmlr.org/papers/v21/20-074.html
- Ori Ram, Yoav Levine, Itay Dalmedigos, Dor Muhlgay, Amnon Shashua, Kevin Leyton-Brown, and Yoav Shoham. 2023. In-context retrieval-augmented language models. arXiv preprint arXiv:2302.00083 (2023).
- Yi Tay, Vinh O. Tran, Mostafa Dehghani, Jianmo Ni, Dara Bahri, Harsh Mehta, Zhen Qin, Kai Hui, Zhe Zhao, Jai Gupta, Tal Schuster, William W. Cohen, and Donald Metzler. 2022. Transformer Memory as a Differentiable Search Index. arXiv:2202.06991 [cs.CL]

- TED Talks. 2023. TED: Ideas change everything. Accessed: 2023-12-15.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. LLaMA: Open and Efficient Foundation Language Models. arXiv:2302.13971 [cs.CL]
- Aaron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. 2017. Neural Discrete Representation Learning. In Proceedings of the 31st International Conference on Neural Information Processing Systems (Long Beach, California, USA) (NIPS'17). Curran Associates Inc., Red Hook, NY, USA, 6309–6318.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. 2017. Attention is All you Need. In Advances in Neural Information Processing Systems, I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (Eds.), Vol. 30. Curran Associates, Inc.
- Hendric Voß and Stefan Kopp. 2023. Augmented Co-Speech Gesture Generation: Including Form and Meaning Features to Guide Learning-Based Gesture Synthesis. In Proceedings of the 23rd ACM International Conference on Intelligent Virtual Agents. 1–8
- Melissa Wagner and Nancy Leonard Armstrong. 2003. Field Guide to Gestures: How to Identify and Interpret Virtually Every Gesture Known to Man. https://api.semanticscholar.org/CorpusID:141961447
- Petra Wagner, Zofia Malisz, and Stefan Kopp. 2014. Gesture and speech in interaction: An overview. *Speech Communication* 57 (2014), 209–232. https://doi.org/10.1016/j.specom.2013.09.008
- Yujing Wang, Yingyan Hou, Haonan Wang, Ziming Miao, Shibin Wu, Hao Sun, Qi Chen, Yuqing Xia, Chengmin Chi, Guoshuai Zhao, Zheng Liu, Xing Xie, Hao Allen Sun, Weiwei Deng, Qi Zhang, and Mao Yang. 2023a. A Neural Corpus Indexer for Document Retrieval. arXiv:2206.02743 [cs.IR]
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023b. Self-Instruct: Aligning Language Models with Self-Generated Instructions. arXiv:2212.10560 [cs.CL]
- World Federation of the Deaf. 1975. GESTUNO: International sign language of the deaf, language gestuel international Des sourds. British Deaf Association [for] the World Federation of the Deaf. Carlise.
- Zunnan Xu, Yachao Zhang, Sicheng Yang, Ronghui Li, and Xiu Li. 2023. Chain of Generation: Multi-Modal Gesture Synthesis via Cascaded Conditional Control. arXiv preprint arXiv:2312.15900 (2023).
- Haiwei Xue, Sicheng Yang, Zhensong Zhang, Zhiyong Wu, Minglei Li, Zonghong Dai, and Helen Meng. 2023. Conversational Co-Speech Gesture Generation via Modeling Dialog Intention, Emotion, and Context with Diffusion Models. arXiv preprint arXiv:2312.15567 (2023).
- Sicheng Yang, Zhiyong Wu, Minglei Li, Zhensong Zhang, Lei Hao, Weihong Bao, Ming Cheng, and Long Xiao. 2023b. DiffuseStyleGesture: Stylized Audio-Driven Co-Speech Gesture Generation with Diffusion Models. In Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence, IJCAI-23. International Joint Conferences on Artificial Intelligence Organization, 5860–5868. https://doi.org/10.24963/ijcai.2023/650
- Sicheng Yang, Zhiyong Wu, Minglei Li, Zhensong Zhang, Lei Hao, Weihong Bao, and Haolin Zhuang. 2023a. QPGesture: Quantization-Based and Phase-Guided Motion Matching for Natural Speech-Driven Gesture Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2321–2330.
- Sicheng Yang, Zunnan Xu, Haiwei Xue, Yongkang Cheng, Shaoli Huang, Mingming Gong, and Zhiyong Wu. 2024. Freetalker: Controllable Speech and Text-Driven Gesture Generation Based on Diffusion Models for Enhanced Speaker Naturalness. In ICASSP 2024 - 2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP).
- Heyuan Yao, Zhenhua Song, Yuyang Zhou, Tenglong Ao, Baoquan Chen, and Libin Liu. 2023. MoConVQ: Unified Physics-Based Motion Control via Scalable Discrete Representations. arXiv preprint arXiv:2310.10198 (2023).
- Payam Jome Yazdian, Mo Chen, and Angelica Lim. 2022. Gesture2Vec: Clustering Gestures using Representation Learning Methods for Co-speech Gesture Generation. In 2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS). 3100–3107. https://doi.org/10.1109/IROS47612.2022.9981117
- Sheng Ye, Yu-Hui Wen, Yanan Sun, Ying He, Ziyang Zhang, Yaoyuan Wang, Weihua He, and Yong-Jin Liu. 2022. Audio-Driven Stylized Gesture Generation with Flow-Based Model. In Computer Vision ECCV 2022, Shai Avidan, Gabriel Brostow, Moustapha Cissé, Giovanni Maria Farinella, and Tal Hassner (Eds.). Springer Nature Switzerland, Cham. 712–728.
- Hongwei Yi, Hualin Liang, Yifei Liu, Qiong Cao, Yandong Wen, Timo Bolkart, Dacheng Tao, and Michael J. Black. 2022. Generating Holistic 3D Human Motion from Speech.
- Lianying Yin, Yijun Wang, Tianyu He, Jinming Liu, Wei Zhao, Bohan Li, Xin Jin, and Jianxin Lin. 2023. EMoG: Synthesizing Emotive Co-speech 3D Gesture with Diffusion Model. arXiv preprint arXiv:2306.11496 (2023).
- Youngwoo Yoon, Bok Cha, Joo-Haeng Lee, Minsu Jang, Jaeyeon Lee, Jaehong Kim, and Geehyuk Lee. 2020. Speech Gesture Generation from the Trimodal Context of Text, Audio, and Speaker Identity. ACM Trans. Graph. 39, 6, Article 222 (nov 2020),

- 16 pages. https://doi.org/10.1145/3414685.3417838
- Youngwoo Yoon, Woo-Ri Ko, Minsu Jang, Jaeyeon Lee, Jaehong Kim, and Geehyuk Lee. 2019. Robots Learn Social Skills: End-to-End Learning of Co-Speech Gesture Generation for Humanoid Robots. In 2019 International Conference on Robotics and Automation (ICRA). 4303–4309. https://doi.org/10.1109/ICRA.2019.8793720
- Youngwoo Yoon, Pieter Wolfert, Taras Kucherenko, Carla Viegas, Teodor Nikolov, Mihail Tsakov, and Gustav Eje Henter. 2022. The GENEA Challenge 2022: A Large Evaluation of Data-Driven Co-Speech Gesture Generation. In Proceedings of the 2022 International Conference on Multimodal Interaction (Bengaluru, India) (ICMI '22). Association for Computing Machinery, New York, NY, USA, 736–747. https: //doi.org/10.1145/3536221.3558058
- Neil Zeghidour, Alejandro Luebs, Ahmed Omran, Jan Skoglund, and Marco Tagliasacchi. 2022. SoundStream: An End-to-End Neural Audio Codec. IEEE/ACM Transactions on Audio, Speech, and Language Processing 30 (2022), 495–507. https://doi.org/10. 1109/TASLP.2021.3129994
- Fan Zhang, Naye Ji, Fuxing Gao, and Yongping Li. 2023a. DiffMotion: Speech-Driven Gesture Synthesis Using Denoising Diffusion Model. In MultiMedia Modeling: 29th International Conference, MMM 2023, Bergen, Norway, January 9–12, 2023, Proceedings, Part I. Springer, 231–242.
- Fan Zhang, Naye Ji, Fuxing Gao, Siyuan Zhao, Zhaohan Wang, and Shunman Li. 2023b. Audio is all in one: speech-driven gesture synthetics using WavLM pre-trained model. arXiv:2308.05995 [cs.SD]
- Jinsong Zhang, Minjie Zhu, Yuxiang Zhang, Yebin Liu, and Kun Li. 2023d. SpeechAct: Towards Generating Whole-body Motion from Speech. arXiv preprint arXiv:2311.17425 (2023).
- Xinghua Zhang, Bowen Yu, Haiyang Yu, Yangyu Lv, Tingwen Liu, Fei Huang, Hongbo Xu, and Yongbin Li. 2023c. Wider and Deeper LLM Networks are Fairer LLM Evaluators. arXiv:2308.01862 [cs.CL]
- Yihao Zhi, Xiaodong Cun, Xuelin Chen, Xi Shen, Wen Guo, Shaoli Huang, and Shenghua Gao. 2023. LivelySpeaker: Towards Semantic-Aware Co-Speech Gesture Generation. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV). 20807–20817.
- Chi Zhou, Tengyue Bian, and Kang Chen. 2022a. GestureMaster: Graph-Based Speech-Driven Gesture Generation. In *Proceedings of the 2022 International Conference on Multimodal Interaction* (Bengaluru, India) (*ICMI '22*). Association for Computing Machinery, New York, NY, USA, 764–770. https://doi.org/10.1145/3536221.3558063
- Yujia Zhou, Jing Yao, Zhicheng Dou, Ledell Wu, and Ji-Rong Wen. 2022b. DynamicRetriever: A Pre-training Model-based IR System with Neither Sparse nor Dense Index. arXiv:2203.00537 [cs.IR]
- Zixiang Zhou, Yu Wan, and Baoyuan Wang. 2023. A Unified Framework for Multimodal, Multi-Part Human Motion Synthesis. arXiv preprint arXiv:2311.16471 (2023).
- Lingting Zhu, Xian Liu, Xuanyu Liu, Rui Qian, Ziwei Liu, and Lequan Yu. 2023a. Taming Diffusion Models for Audio-Driven Co-Speech Gesture Generation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 10544–10553.
- Yutao Zhu, Huaying Yuan, Shuting Wang, Jiongnan Liu, Wenhan Liu, Chenlong Deng, Zhicheng Dou, and Ji-Rong Wen. 2023b. Large Language Models for Information Retrieval: A Survey. arXiv:2308.07107 [cs.CL]
- Noah Ziems, Wenhao Yu, Zhihan Zhang, and Meng Jiang. 2023. Large Language Models are Built-in Autoregressive Search Engines. arXiv:2305.09612 [cs.CL]

DETAILS OF USER STUDY

A comparison set comprises two videos, each lasting 10 seconds, displayed sequentially from left to right. These pairs are generated using the same speech and character model. Questionnaires of the user study are built via the Human Behavior Online (HBO) tool provided by the Credamo platform [Credamo 2017]. Each test and questionnaire consist of 24 such video pairs. On average, an experiment is completed in 12 minutes. We have recruited 220 participants through Credamo, of which 117 are male and 103 are female. 77 participants are 18 - 25 years of age, 121 are between 25 - 35, and 22 are above 35. They are sourced from the United States (30%) and China (70%), and those involved in tests with audio must speak English fluently. In order to ensure that participants can clearly understand the detailed meaning of each metric and can distinguish between them effectively, We provide the participants with detailed instructions. For human likeness, participants are requested to assess the naturalness and fluidity of the movements, as well as their resemblance to actual human movements. For beat matching, we instruct the participants to focus on the rhythmic coherence between gestures and speech audio. For semantic accuracy, the participants first learn about "what are semantic gestures" by watching several examples of semantic gestures. They are asked to read the transcript of each speech before rating, ensuring a more informed judgment on the semantic performance of the results. Meanwhile, to ensure the validity of the responses, following [Ao et al. 2023], an attention check is incorporated randomly within the experiment. This check involves a text message, attention: please select the leftmost option, displayed continuously at the video pair's bottom throughout the question and embedded in the video during the transition between the two clips. Responses failing this attention check are excluded from the final results.

The settings for the human likeness, beat matching, and semantic accuracy tests on both the ZEGGS dataset and the BEAT dataset are identical. Specifically, We evaluate four methods for each dataset: GT, Ours, Ours (without semantic alignment), and either GestureDiffuCLIP for the ZEGGS dataset or CaMN for the BEAT dataset. This leads to 12 distinct side-by-side comparison combinations. We randomly select 24 speech segments from the test sets of the ZEGGS and BEAT datasets, respectively, and extract a 10-second clip from each segment starting at an arbitrary position. They are employed in the generation of gestures, yielding 24 video clips for each method. Consequently, there are 288 video pairs in total (24 speech segments × 12 combinations). Participants are tasked with evaluating 24 video pairs, covering all 24 speech segments. Each of the 12 comparison combinations is presented twice. The orders of both speech samples and the pairing of comparisons are randomized for each subject.

B QUANTITATIVE EVALUATION OF LLM-BASED RETRIEVAL MODEL

We evaluate the annotation results quantitatively using three methods by two metrics: a) Accuracy, which assesses whether the annotated gestures are in the SeG dataset, and b) Semantic Matching, which examines whether the annotated gestures at a specific point match the context and semantics of the situation.

In particular, we randomly select 49 different speech fragments from the BEAT dataset at first, extracting complete sentences from these fragments' first 20 seconds of transcript. Subsequently, we apply zero-shot, few-shot, and finetuned LLM strategies to perform semantic gesture retrieval on these sentences. For Accuracy, we employ word matching to detect whether each annotated semantic gesture appears in the SeG dataset we are given. We calculated this metric as the ratio of correctly annotated semantic gestures to the total number of annotated gestures. For Semantic Matching, we utilize the most powerful language model to date, GPT-4 Turbo [OpenAI 2023a]. By employing a prompt-based approach, we make it to play the role of scorer, with each metric rated on a scale from 1 to 10. The corresponding prompt is shown in fig 17. Finally, we calculate the mean values of the three different methods across the two metrics. The average scores are detailed in table 3:

Table 3. Quantitative evaluation on annotation results. This table reports the mean (± standard deviation) values for each metric by synthesizing on the test data 10 times.

Metric	zero-shot	few-shot	finetune
Accuracy	$56.7\% \pm 8.1\%$	$92.8\% \pm 3.8\%$	$97.8\% \pm 1.4\%$
Semantic Matching	4.35 ± 0.21	6.00 ± 0.30	7.38 ± 0.29

As indicated by the qualitative analysis in Section 7.5.1, the zeroshot strategy performs significantly worse, while the few-shot strategy shows marked improvement in both two metrics, particularly in Accurancy. The fine-tuned LLM exhibits a 23.0% enhancement in Semantic Matching beyond the few-shot strategy, reflecting significant advances in semantic comprehension. These results demonstrate the superiority of our fine-tuned LLM.

GPT4 Turbo-based Scorer's prompt

You are now a speaker proficient in semantic gestures. I will give you a table, which contains information on each gesture. Please fully understand the information in the table and score the gesture annotations for the given three sentences from 1 to 10. Here is the table of gestures:

{table}

You need to score based on one criteria:

Semantic Matching. To what extent does making this gesture at this position match the context and semantics.

Fig. 17. The prompt of GPT4-based Scorer for Semantic Matching.