# Training Compute Thresholds: Features and Functions in AI Regulation

Lennart Heim<sup>∗</sup>

Centre for the Governance of AI Oxford, United Kingdom

Leonie Koessler

Centre for the Governance of AI Oxford, United Kingdom & European New School of Digital Studies Frankfurt (Oder), Germany

#### Abstract

Regulators in the US and EU are using thresholds based on training compute—the number of computational operations used in training—to identify general-purpose artificial intelligence (GPAI) models that may pose risks of large-scale societal harm. We argue that training compute currently is the most suitable metric to identify GPAI models that deserve regulatory oversight and further scrutiny. Training compute correlates with model capabilities and risks, is quantifiable, can be measured early in the AI lifecycle, and can be verified by external actors, among other advantageous features. These features make compute thresholds considerably more suitable than other proposed metrics to serve as an initial filter to trigger additional regulatory requirements and scrutiny. However, training compute is an imperfect proxy for risk. As such, compute thresholds should not be used in isolation to determine appropriate mitigation measures. Instead, they should be used to detect potentially risky GPAI models that warrant regulatory oversight, such as through notification requirements, and further scrutiny, such as via model evaluations and risk assessments, the results of which may inform which mitigation measures are appropriate. In fact, this appears largely consistent with how compute thresholds are used today. As GPAI technology and market structures evolve, regulators should update compute thresholds and complement them with other metrics into regulatory review processes.

<sup>∗</sup>Correspondence to [lennart.heim@governance.ai](mailto:lennart.heim@governance.ai).

#### <span id="page-1-1"></span>Executive Summary

The development and deployment of advanced general-purpose artificial intelligence (GPAI) models, also referred to as "frontier AI models" or "dual-use foundation models", pose increasing risks of large-scale societal harm [\(Section 1\)](#page-5-0). Currently, these models develop ever higher capabilities through ever larger training runs, fuelled by ever more computational resources ("training compute"). But higher capabilities also mean higher risks to society, because many capabilities are dual-use (e.g., automated hacking capabilities) and because more capable models can be expected to be used more widely and relied upon more heavily, increasing the stakes if they fail or behave in undesired ways (e.g., producing biased outputs). As a result, regulators are increasingly using training compute thresholds to identify models of potential concern.

"Training compute" refers to the total number of operations a computer needs to perform to train an AI model [\(Section 2\)](#page-6-0). In recent years, the scale of AI training has grown significantly, with increases in the amount of training data, the number of model parameters, and corresponding increases in the amount of compute required for training [\(Figure 1\)](#page-1-0). "Compute" in this context refers to the total number of operations executed over the training process. While post-training enhancements like fine-tuning can significantly increase model capabilities, we recommend focusing on the compute used for the large training run ("pre-training"), as this aligns with empirical scaling laws and avoids impractical re-measurements for successive fine-tuning instances.



<span id="page-1-0"></span>

**Figure 1:** Training compute has been increasing at a fast rate, doubling roughly every 6 months ( $4 \times$ per year). The US AI EO introduces reporting requirements for models trained with more than  $10^{26}$ operations. The EU AI Act presumes a GPAI model poses systemic risk and imposes a variety of requirements for models trained with more than  $10^{25}$  operations.

#### Training compute has several features useful for GPAI regulation [\(Section 3\)](#page-8-0). In particular, it is:

• Risk-tracking: Training compute is indicative of a model's loss, capabilities, and risks. Empirical research has identified correlations, known as *scaling laws*, between a model's training compute and its training loss, test loss, or validation loss. Improvements in loss tend to correlate with improvements in capabilities. As models become more capable, they

may pose greater risks if they are misused or if they pursue misaligned objectives. The capabilities of a model also serve as a proxy for how widely it will be used and how heavily it will be relied upon and therefore the stakes if it fails or behaves in other undesired ways.

- Easily measurable: Training compute is a quantifiable metric that is relatively simple and cheap to calculate.
- Difficulty of circumvention: Training compute is relatively robust to circumvention attempts, as reducing the amount of compute used to train a model will generally decrease its capabilities and, consequently, lower its risks. This is because, for a given model architecture and training algorithm, the amount of compute used is directly related to the model's capabilities and potential risks. While algorithmic efficiency improvements gradually reduce the amount of training compute required for a certain level of performance over time, this represents an incremental progression of techniques rather than an active circumvention.
- Measurable before development and deployment: Training compute can be calculated before the model is deployed, and estimated before the model is trained.
- Externally verifiable: The possibility for external parties, such as compute providers, to verify compute usage, without disclosing proprietary details, enhances compliance.
- Cost-tracking: Training compute is proportionate to the cost of computational resources for training, allowing the regulatory burden on smaller actors to be minimized while focusing on the most well-resourced ones.

Notwithstanding the advantages discussed above, training compute also has relevant limitations [\(Section 4\)](#page-11-0). Fundamentally, it serves only as an imperfect proxy for risk. While high training compute generally indicates increased model capabilities and potential risks, some high-compute models may pose minimal concerns, whereas certain low-compute models could present significant risks (with the latter partially addressed through complementary non-GPAI regulations). Moreover, improvements in algorithmic efficiency are gradually reducing the amount of training compute required to achieve a given level of capability, potentially weakening the relationship between a specific compute threshold and the corresponding level of risk over time. However, this shift in the compute-risk correlation might occur gradually rather than abruptly as the field evolves.

Consequently, we suggest that compute thresholds should be used as an *initial filter* to identify GPAI models that warrant regulatory oversight and further scrutiny [\(Section 5.1\)](#page-12-0). We argue that compute thresholds can and should have two primary functions: ensuring that regulators obtain sufficient visibility into risks of large-scale societal harm from GPAI models and that companies invest appropriate resources in understanding these risks. Precautionary mitigation measures can be based on compute thresholds too, but it should be allowable to later remove those mitigations if they turn out to be unnecessary.

However, compute thresholds alone should generally *not* determine which mitigation measures are ultimately required, given that compute is only a crude proxy for model capabilities and an even cruder proxy for risks of large-scale societal harm. Instead, to determine which mitigation measures are required, compute thresholds can be complemented with more precise but harder to evaluate thresholds based on other metrics, such as capability thresholds based on model capability evaluations. We also highlight that in a full regulatory framework for AI, most requirements should not hinge on the amount of training compute [\(Figure 2\)](#page-3-0).

Both the US AI EO and the EU AI Act mostly use compute thresholds in line with our suggestions [\(Section 5.2](#page-14-0) and [Section 5.3\)](#page-15-0). The US Executive Order 14110 mandates companies to notify the government about any ongoing or planned activities concerning the development of models that cross a compute threshold of  $10^{26}$  operations, report on the measures taken to ensure the physical and cybersecurity of model weights, and share the results of red-teaming tests and mitigation measures taken based on those results. The *EU AI Act* requires providers of GPAI models that cross a compute threshold of  $10^{25}$  operations to notify the European Commission, perform model evaluations, assess and mitigate systemic risks, report serious incidents, and ensure cybersecurity of the model and its physical infrastructure.

Challenges remain in effectively leveraging compute thresholds for GPAI regulation [\(Section 6\)](#page-17-0). A key question is the appropriate threshold level. There is high uncertainty about the risk stemming from current and future GPAI models trained on different amounts of compute. As a result, a low threshold may be overinclusive, while a high threshold may be underinclusive. Moreover, the

<span id="page-3-0"></span>

Figure 2: Compute thresholds serve as an initial filter to identify GPAI models that warrant regulatory oversight and further scrutiny, and, for example, evaluation against capability thresholds to determine appropriate mitigation measures, complemented by other AI requirements.

direction in which a compute threshold should move over time is not obvious, and it can make sense to complement compute thresholds with other metrics. For example, increasing algorithmic efficiency allows more capable models to be trained with less compute. A reason to consider adjusting the compute threshold downwards over time.

However, there are also reasons to adjust the compute threshold upwards. If better understanding of GPAI models reveals that models that are in scope of a given compute threshold pose limited risks, the compute threshold should be raised to focus on potentially risky models. With improving algorithmic efficiency and computational price-performance, an increasing number of less well-resourced actors may fall within the scope of a given compute threshold, making the requirements increasingly burdensome and oversight increasingly costly. Other relevant factors include the threat landscape (i.e. the number, capacity, and willingness of malicious actors to use AI systems) and societal vulnerability or adaptation (i.e. the ability and capacity of society to deal with attacks, failures, and emergencies, e.g., through competent, well-resourced, and stable institutions).

Some other metrics, such as risk estimates, model capabilities, and effective compute, are better proxies for risk. However, these metrics are much harder to measure than training compute is. Complementing mere compute thresholds with other metrics becomes relevant to the extent that scaling laws cease to hold and training compute becomes a worse proxy for risk. Particularly relevant combinations may include training compute and model capability evaluations—to ensure catching the most capable models—and training compute and number of users—to ensure catching the most widely used models. However, any threshold that is supposed to serve as an initial filter to identify models of potential concern should be based on metrics that can be measured easily and early in the model lifecycle. This, at least currently, excludes risk estimates and model capability evaluations, and at least before deployment, the number of users.

Overall, while not perfect, compute thresholds are currently a key tool in GPAI regulation [\(Section 7\)](#page-27-0). In particular, compute thresholds are currently the best tool available for identifying potentially risky GPAI models and triggering regulatory oversight and further scrutiny. They are based on a risk-correlated, quantifiable metric that is difficult to circumvent and can be measured before model development and deployment, enabling proactive governance efforts. Compute thresholds can complement more targeted filters like model capability evaluations that ultimately determine which mitigation measures are required.

# **Contents**



# <span id="page-5-0"></span>1 Introduction

The development and deployment of advanced general-purpose artificial intelligence (GPAI) models<sup>[1](#page-5-1)</sup>, also referred to as "frontier AI models" or "dual-use foundation models", pose increasing risks of large-scale societal harm [\(Anderljung et al., 2023;](#page-28-0) [Bengio et al., 2024;](#page-28-1) [Hendrycks et al., 2023\)](#page-30-0). Currently, GPAI models develop ever higher capabilities through ever larger training runs, fuelled by ever more computational resources. The overall amount of computational resources used to train a model is referred to as *training compute*. But higher capabilities also mean higher risks to society, because many capabilities are dual-use (e.g., cyber capabilities) and because more capable models can be expected to be used more widely and relied upon more heavily, increasing the stakes if they fail or behave in undesired ways (e.g., producing biased outputs). As a result, regulators are increasingly imposing requirements on providers of GPAI models whose amount of training compute passes a certain limit. These limits are called *compute thresholds*. This paper discusses the key features of training compute and, accordingly, the functions compute thresholds should have in GPAI regulation.

GPAI regulation worldwide increasingly relies on training compute thresholds. Since October 2023, *US Executive Order 14110 on the Safe, Secure, and Trustworthy Development and Use of Artificial Intelligence (US AI EO)* requires companies developing and deploying GPAI models above a compute threshold of  $10^{26}$  operations to notify the government, conduct red-teaming, and secure the model weights (Section 4.2). From August 2024, the *EU Regulation 2024/1689 laying down harmonised rules on artificial intelligence (EU AI Act)* presumes that GPAI models that pass a compute threshold of  $10^{25}$  floating-point operations pose systemic risk (Article 51(2)). Providers of such models are required to notify the European Commission (Article 52(1)), conduct model evaluations, assess and mitigate systemic risks, ensure adequate cybersecurity, and report serious incidents (Article 55). Finally, an early draft of an *Artificial Intelligence Law of the People's Republic of China* references training compute as one of the criteria used to identify "critical AI" which would require heightened safety and security measures [\(Linghan et al., 2024\)](#page-31-0).<sup>[2](#page-5-2)</sup>

At the same time, the literature on compute thresholds is relatively scarce. While many papers analyze trends in training compute (e.g., [Lohn & Musser, 2022;](#page-31-1) [Pilz & Heim, 2023;](#page-33-0) [Sevilla et al., 2022a;](#page-34-0) [Villalobos et al., 2024\)](#page-34-1), only a few discuss using compute as a node for AI governance and suggest using training compute thresholds [\(Anderljung et al., 2023;](#page-28-0) [Heim et al., 2024;](#page-30-1) [Egan & Heim, 2023;](#page-29-0) [Sastry et al., 2024\)](#page-33-1). [Hooker](#page-30-2) [\(2024\)](#page-30-2) questions training compute as a proxy for risk and raises the issue that (training) compute thresholds may quickly become obsolete. While the paper points at some relevant challenges, as we argue in the following, it lacks nuance regarding the features of training compute, the function that compute thresholds *can* and *should* play in GPAI regulation, and an accurate representation of regulations that already incorporate such thresholds. The combination of increasing regulatory reliance on compute thresholds and scarce academic literature suggests an urgent need for more scholarly treatment of the topic.

This paper aims to answer the following two research questions: (1) What features of training compute are relevant for GPAI regulation? (2) What should be the function of (training) compute thresholds in GPAI regulation? The remainder of the paper is structured as follows: [Section 2](#page-6-0) clarifies the concept of training compute, [Section 3](#page-8-0) discusses its useful features, and [Section 4](#page-11-0) its limitations. [Section 5](#page-11-1) suggests which functions (training) compute thresholds should have in GPAI regulation, while [Section 6](#page-17-0) elaborates on challenges in that regard. [Section 7](#page-27-0) concludes with key claims and further research questions.

<span id="page-5-1"></span><sup>&</sup>lt;sup>1</sup>There is no common distinction between what still counts as a "model" and what already constitutes a "system." Regulators, such as the EU AI Office, need to provide clarification on this question. In this paper, we understand the term "model" to include model weights and source code, and the term "system" to encompass everything beyond (e.g., API, calls to other models, calls to other APIs) (similar to [Basdevant et al., 2024\)](#page-28-2).

<span id="page-5-2"></span><sup>&</sup>lt;sup>2</sup>Throughout this paper, we use the terms "(training) operations", "(training) compute", and "(training) compute threshold" to emphasize that our focus is on the computational resources used specifically during the training phase of a AI model's lifecycle. There are other types of "compute thresholds" that can be used for AI regulation. For example, the US AI EO also includes a reporting requirement for computing clusters above a certain computing capacity per second. This is another type of "compute threshold" that does not directly refer to the training process but rather to the mere possession of computing infrastructure that can be used not only for training but also for deploying AI models.

# <span id="page-6-0"></span>2 Training Compute

Training an AI model is an iterative process where a model—a large amount of numeric values (the so-called "parameters") arranged in a certain way (the so-called "architecture")—is exposed to a large amount of data, allowing the model to learn from the data by adapting the parameters. This learning can be supervised, where the model is provided with labeled examples, or unsupervised, where the model learns from unlabeled data [\(Goodfellow et al., 2016\)](#page-30-3).

"Training compute" or simply "compute" refers to the amount of computational resources or, more precisely, the total number of operations required to train an AI model. The training process runs on a computer that performs a vast number of mathematical operations. We are agnostic here as to whether these are integer operations, floating-point operations (FLOP), or other operations. Presently, most AI training predominantly uses floating-point operations, but this could change in the future. We therefore broadly refer to all types of operations as "(training) operations (OP)." The total number of operations used to train the model is a quantity we refer to as "(training) compute."[3](#page-6-1)

The term "compute" in this context refers to the number of operations executed in total over the whole training process, not to be confused with the computer's processing performance—the number of operations the computer is able to execute per second (FLOP/s or OP/s). For example, running an NVIDIA A100 processor (which has a processing performance of 312 TeraFLOP/s for FP16 tensor) for a week results in a total of  $1.9 \times 10^{20}$  FLOP being executed. Multiplied with the number of NVIDIA A100 processors used, this results in the total number of operations used to train the AI model.<sup>[4](#page-6-2)</sup>

In recent years, the scale of AI training has grown significantly, with increases in the amount of training data, the number of model parameters, and, therefore, the amount of compute required for training (growing by about  $4\times$  every year since 2010, [Figure 3\)](#page-7-0).

There is currently no standardized method for measuring a model's training compute. This introduces ambiguity that may be considered problematic in a regulatory context. We suggest measuring training compute by following the guidance of the Frontier Model Forum [\(Frontier Model Forum, 2024\)](#page-29-1). More precisely, we suggest using Method 1 described in [\(Sevilla et al., 2022b\)](#page-34-2). However, given that the amount of training compute used for the final large training run ("pre-training") currently increases by about four times per year [\(Epoch AI, 2024b;](#page-29-2) [Sevilla et al., 2022a\)](#page-34-0), the exact details of these methods are not critical.

By contrast, an important question is whether to focus on the compute used for pre-training alone or whether to also include the compute used for "fine-tuning", "reinforcement learning from human feedback" (RLHF), and other post-training enhancements [\(Figure 4\)](#page-8-1). Post-training enhancements can significantly improve model capabilities, up to an equivalent of a  $5\times$  to  $20\times$  increase in training compute [\(Davidson et al., 2023;](#page-29-3) Villalobos  $\&$  Atkinson, 2023). Presumably to account for this, Recital 111 of the EU AI Act suggests including compute used for post-training enhancements: "*The cumulative amount of computation used for training includes the computation used across the activities and methods that are intended to enhance the capabilities of the model prior to deployment, such as pre-training, synthetic data generation and fine-tuning.*"

We believe that including the compute used for post-training enhancements lacks an empirical basis, is unnecessary, and is impractical. First, the empirical basis for existing scaling laws describes model performance as a function of pre-training compute, not of compute used for fine-tuning or other post-training enhancements (for more on scaling laws, see [Section 3\)](#page-8-0). This means there is no empirical basis for imposing requirements based on the cumulative amount of compute. Second, fine-tuning compute is small compared to pre-training compute.[5](#page-6-3) Consequently, including fine-tuning compute would make only a small difference to the overall training compute measurement. Lastly, measuring fine-tuning compute is impractical because fine-tuning is repeated many times for a given pre-trained model and often performed by downstream developers. Re-measuring training compute

<span id="page-6-1"></span> $3$ When referring to the quantity of computational resources used during training, it is preferable to use the term "FLOP" rather than "FLOPs." For a longer elaboration, see [Heim](#page-30-4) [\(2023\)](#page-30-4).

<span id="page-6-3"></span><span id="page-6-2"></span><sup>&</sup>lt;sup>4</sup>Note that this is a simplified explanation. For more details, see [Pistillo et al.](#page-33-2) [\(forthcoming\)](#page-33-2).

<sup>&</sup>lt;sup>5</sup>Usually around 1%, or, in the largest case we are aware of, up to about 14% of the pre-training compute. A small robotics model (Swift) is an exception, using fine-tuning compute equivalent to about 200% of pre-training compute [\(Epoch AI, 2024a\)](#page-29-4).

# <span id="page-7-0"></span>Compute Used for AI Training Runs

Total compute used to train notable Al models, measured in total FLOP (floating-point operations) | Logarithmic



Figure 3: Amount of compute used to train AI models over time. In the pre-deep learning era, training compute followed Moore's Law, doubling approximately every two years. Since the emergence of the Deep Learning Era around 2010, training compute has been increasing at a much faster rate, doubling roughly every 6 months (increasing by about  $4\times$  per year). This rapid growth is largely driven by increased investments in computational resources for training larger models, which have demonstrated improved capabilities (figure from [Sastry et al. 2024;](#page-33-1) up-to-date as of end of 2023; underlying data and updates can be found at [Epoch AI 2024a\)](#page-29-4).

(and potentially re-reporting and re-conducting model evaluations) for every fine-tuned version would be extremely burdensome for individual regulatees and lead to a much larger number of regulatees.

Instead, we recommend only measuring pre-training compute. While post-training enhancements can significantly increase a model's capabilities, this should not be considered directly when designing a compute threshold, but only indirectly as discussed in [Section 6.1.](#page-17-1) Moreover, post-training enhancements can and should be taken into account when measuring a model's capabilities, as it is the enhanced model that will be deployed in the end. Indeed, comprehensive model evaluations should involve applying fine-tuning and other post-training enhancements to elicit the pre-trained model's full capabilities as much as possible. However, it is not necessary or practical to re-conduct model capability evaluations on every enhanced model version. Minor variations may not necessitate reconducting model capability evaluations, provided the pre-trained model has already been evaluated.

<span id="page-8-1"></span>

Figure 4: We recommend only measuring pre-training compute and not including compute used in further enhancement processes (figure adapted from [Pistillo et al.](#page-33-2) [\(forthcoming\)](#page-33-2)).

We suggest re-conducting model capability evaluations on enhanced model versions periodically and if they constitute a new model family.

# <span id="page-8-0"></span>3 Features of Training Compute Useful for GPAI Regulation

Training compute has several features that make it a valuable metric for GPAI regulation. Namely, training compute is indicative of a model's capabilities and therefore its risks, easily measurable, difficult to circumvent, measurable before development and deployment, externally verifiable, and indicative of the developer's resources and therefore its capacity to handle regulatory burdens. In the following, we discuss each of these features in more detail.

#### 1. Risk-tracking: Training compute is indicative of a model's loss, capabilities, and risks.

- For GPAI models, the amount of compute used to train a model correlates with the model's loss, capabilities, and risks it may present. Empirical research has identified correlations, known as *scaling laws*, between a model's training compute and its training loss, test loss, or validation loss [\(Hernandez et al., 2021;](#page-30-5) [Hoffmann et al., 2022;](#page-30-6) [Kaplan et al., 2020;](#page-31-2) [Sutton, 2019;](#page-34-4) [Villalobos,](#page-34-5) [2023\)](#page-34-5). Further, improvements in loss tend to correlate with improvements in capabilities on downstream tasks [\(Brown et al., 2020;](#page-29-5) [Ganguli et al., 2022;](#page-30-7) [Rae et al., 2022\)](#page-33-3). Finally, as models become more capable, they may pose greater risks if they are misused or if they pursue misaligned objectives. The capabilities of a model also serve as a proxy for how widely it will be used and how heavily it will be relied upon and therefore the stakes if it fails or behaves in other undesired ways.[6](#page-8-2) For example, this may include increases in the number and severity of people affected by biased outputs [\(Bommasani et al., 2022\)](#page-28-3).
- This feature of training compute—its correlation with a model's loss, capabilities, and risks—is the most important but also perhaps the most controversial (e.g., [Hooker, 2024\)](#page-30-2). While this feature is already disputed today, we highlight that to the extent that scaling laws cease to hold in the future—for example, because a training paradigm other than deep learning emerges training compute will become a less useful metric for GPAI regulation. We discuss this feature in some more depth in [Section 4.](#page-11-0)

#### 2. Easily measurable: Training compute is a quantifiable metric that is relatively simple and cheap to calculate.

<span id="page-8-2"></span><sup>6</sup>At the same time, the risks from failure and other undesired behaviors decrease with higher capabilities in terms of model accuracy, robustness, and not being susceptible to prompt injection attacks and jailbreaks. Which one of these two trends outweighs the other is currently impossible to say—empirical data is lacking to make statements about the past, let alone predict the future.

• Training compute is a metric that is easy to measure, as it can be directly calculated from model specifications or inferred from data about the use of hardware with minimal effort. Training compute also is unidimensional and durable, unlike other metrics, many of which are multidimensional (e.g., data quality and type) or may quickly become outdated (e.g., model capability benchmarks).

#### 3. Difficult to circumvent: Training compute is difficult to reduce without also decreasing a model's capabilities and risks.

- Training compute is relatively robust to circumvention attempts, as reducing the amount of compute used to train a model will generally decrease its capabilities and, consequently, lower its risks. This is because, for a given model architecture and training algorithm, the amount of compute used is directly related to the model's capabilities and potential risks. Therefore, a GPAI developer cannot simply decide to use less compute while maintaining the same level of capabilities. In contrast, a GPAI developer might be able to adjust other metrics, such as the score on a specific benchmark, to avoid regulation without substantially impacting the model's capabilities.
- However, improvements in algorithmic efficiency can reduce the amount of compute required for a given level of capabilities. Over time, this may allow less well-resourced actors to develop models that achieve a given level of capabilities [\(Pilz et al., 2023\)](#page-33-4). Indeed, improvements in algorithmic efficiency pose a challenge to using compute thresholds. However, while future algorithmic efficiency improvements may require less compute for the same level of capabilities, this represents natural progress rather than active circumvention attempts. Purposefully decreasing training compute for fixed algorithms would still come at the cost of lower capabilities and risks. We address the question of when to update compute thresholds to account for algorithmic efficiency improvements in [Section 6.3.](#page-20-0)

#### 4. Measurable before development and deployment: Training compute can be calculated before the model is deployed and even before it is trained.

• Training compute can be known ahead of deployment and estimated ahead of development. This is important because regulators may want to impose requirements for how a model is developed and deployed. Training compute can be calculated before model deployment because training will be completed at that time. Before model development, training compute can be estimated using the architectural details and the amount of training data, as outlined in Method 1 of [Sevilla et al.](#page-34-2) [\(2022b\)](#page-34-2). AI companies carefully plan their training runs, as training stateof-the-art models often requires tens of thousands of GPUs and costs on the order of millions of dollars. Given the significant computational resources and financial investment involved, companies have a strong incentive to accurately estimate training compute beforehand to ensure efficient resource allocation and budget planning. By estimating training compute before training begins, developers can implement compute-indexed precautions during the training process. For example, they can ensure that strong cybersecurity measures are in place for compute-intensive training runs, reducing the risk of model theft or unauthorized access.

#### 5. Externally verifiable: The possibility for external parties to verify compute usage, without disclosing proprietary details, enhances compliance.

• Ideally, measurements of training compute are verifiable by diverse external parties through protocols that maintain the confidentiality of proprietary information. This could also enable verifiable commitments across companies and even states [\(Brundage et al., 2020\)](#page-29-6). Compute providers can aid in the verification of requirements based on training compute. This is particularly desirable, as compute providers can monitor and verify compute usage without infringing on the confidentiality of developers, in contrast to model capabilities and other metrics that may require access to sensitive model details. This is because compute usage can be monitored and verified without the need to access specific details of the model architecture, training data, or other proprietary information [\(Heim et al., 2024\)](#page-30-1).

#### 6. Cost-tracking: Training compute is proportionately higher for models that cost more to develop, minimizing the regulatory burden on smaller actors while focusing on the most wellresourced ones.

• The amount of compute used to train a model directly corresponds to the amount of financial resources required to do so [\(Figure 5\)](#page-10-0). In other words, the cost of training a model scales with



# <span id="page-10-0"></span>Compute Used for AI Training Runs (Deep Learning Era)

Figure 5: Cost and compute used for training AI models. The amount of compute used to train a model directly corresponds to the amount of financial resources required to do so.[7](#page-10-1)This rapid growth is largely driven by increased investments in computational resources for training larger models, which have demonstrated improved capabilities (figure adapted from [Sastry et al. 2024;](#page-33-1) underlying data and updates can be found at [Epoch AI 2024a\)](#page-29-4).

the amount of training compute used. For example, training a model with  $10^{26}$  operations (\$70M) will cost approximately 10 times more than training one with 10<sup>25</sup> operations (\$7M).

- The large amounts of compute required to train state-of-the-art models are typically only available to well-resourced organizations. By setting compute thresholds at appropriate levels, regulators can focus on the most advanced and potentially risky models without imposing undue burdens on smaller actors in the AI ecosystem, such as startups, small businesses, or academic researchers.
- However, the cost of a given amount of compute decreases over time. Computational priceperformance (FLOP per \$) has been observed to double every 2.1 years for machine learning GPUs and 2.5 years for general GPUs [\(Hobbhahn et al., 2023\)](#page-30-8). As the cost of compute falls, more actors may be able to develop models that cross the compute threshold [\(Pilz et al., 2023\)](#page-33-4). This expansion in the regulatory scope would impose regulatory burdens on smaller actors and pose a challenge in terms of scaling oversight as the number of covered entities grows. In [Section 6.3,](#page-20-0) we discuss approaches to account for a regulatory scope that is potentially expanding due to improving computational price-performance.

<span id="page-10-1"></span><sup>&</sup>lt;sup>7</sup>While the exact cost calculations vary across different sources due to uncertainty about potential discounts and the achieved utilization or efficiency of leveraging the provided computing power (see [Hobbhahn et al.,](#page-30-8) [2023\)](#page-30-8), the rough estimates tend to fall within a similar range. For the purposes of this analysis, we assume a cost of \$1.8 per hour for renting an NVIDIA H100, which is a rather optimistic assumption. Also, note that this is only the cost of acquiring the computational resources for the final large training run. It does not include staff cost and compute usage beyond pre-training.

## <span id="page-11-0"></span>4 Limitations of Training Compute Relevant for GPAI Regulation

In this section, we discuss the main limitations of training compute relevant for frontier AI regulation. We argue that training compute is only a very crude proxy for risk and that, in the future, training compute may become a worse proxy for risk or even cease to be such a proxy altogether.

Scaling laws describe relationships between training compute and a model's loss [\(Section 3\)](#page-8-0). The subsequent relationship between loss and capabilities is not always "smooth." For example, inverse scaling has been observed for some tasks [\(Koralus & Wang-Mascianica, 2023;](#page-31-3) [McKenzie et al., 2024;](#page-32-0) ´ [Perez et al., 2022\)](#page-32-1), though for some of these tasks, the relationship has been re-established with further scaling [\(OpenAI et al., 2023;](#page-32-2) [Wei et al., 2022a\)](#page-34-6). Moreover, with gradual improvements in loss, there can be jumps in capabilities, or at least apparent jumps depending on how granular the capabilities are measured [\(Wei, 2023;](#page-34-7) [Wei et al., 2022b\)](#page-35-0).[8](#page-11-2)

The relationship between increases in capabilities and risks is also not "smooth." The higher a model's capabilities, the more risky the model will arguably be, because it can be misused for more dangerous purposes and it is likely to be employed in more and higher-stakes settings. However, risk is highly contextual. Factors other than model capabilities have a major impact on risk. Important factors include the offense-defense balance of AI systems, i.e. whether AI systems help more with beneficial or harmful uses<sup>[9](#page-11-3)</sup> [\(AI Policy Perspectives & Krier, 2024;](#page-28-4) [Buterin, 2023;](#page-29-7) [Lohn & Jackson, 2022\)](#page-31-4), the threat landscape, i.e. the number, capacity, and willingness of malicious actors to use AI systems [\(Koessler et al., 2024\)](#page-31-5), and societal vulnerability or adaptation, i.e. the ability and capacity of society to deal with attacks, failures, and emergencies, e.g., through competent, well-resourced, and stable institutions [\(Anderljung et al., 2023;](#page-28-0) [Bernardi et al., 2024;](#page-28-5) [Kapoor et al., 2024\)](#page-31-6).

Essentially, training compute correlates with loss, which correlates with capabilities, which in turn correlate with risk. Thus, training compute is a proxy for risk; however, as none of these three correlations are perfect, training compute can only be considered a very crude proxy for risk [\(Hooker,](#page-30-2)  $2024$ ).<sup>[10](#page-11-4)</sup>

Fundamentally, the notion of training compute as a proxy for risk hinges on the validity of scaling laws. While scaling laws are empirical observations derived from past data, they do not guarantee that these relationships will persist indefinitely. There is a prediction, referred to as the "scaling hypothesis", that these relationships will continue to hold true in the future [\(Branwen, 2020;](#page-29-8) [Sutton,](#page-34-4) [2019\)](#page-34-4). However, innovation in AI might gradually lead to a paradigm shift away from deep learning, or the pre-training phase might become less crucial for determining the final capabilities of AI models. As a result, training compute may become a less precise proxy for risk over time or could potentially cease to serve as an effective proxy for risk altogether. Nonetheless, we do not anticipate an abrupt disruption in the relationship between training compute and risk. Any potential shift is likely to occur gradually as the field evolves over an extended period. In [Section 6.3,](#page-20-0) we discuss approaches to account for changes in the relationship between training compute and risk due to improving algorithmic efficiency.

# <span id="page-11-1"></span>5 Functions of Training Compute Thresholds in GPAI Regulation

Building on the characteristics of training compute outlined in the previous sections, in this section we argue that compute thresholds can and should be used as an initial filter to identify models that warrant regulatory oversight, further scrutiny, and precautionary safety measures. However, given that compute is only a very crude proxy for capabilities and risk, compute thresholds should not be

<span id="page-11-2"></span><sup>&</sup>lt;sup>8</sup>These apparent discontinuities arise because we often care about discontinuous measures, such as getting the exact right answer in mathematics or avoiding crashes in autonomous vehicles, rather than just approximating the correct solution. While continuous surrogate measures could potentially be used to forecast when such discontinuous jumps in capability might occur, identifying the appropriate continuous measure is itself a complex problem. For a more comprehensive discussion of "emergent capabilities", see [Anderljung et al.](#page-28-0) [\(2023\)](#page-28-0), [Pistillo](#page-33-2) [et al.](#page-33-2) [\(forthcoming\)](#page-33-2), and [Woodside](#page-35-1) [\(2024\)](#page-35-1).

<span id="page-11-3"></span><sup>&</sup>lt;sup>9</sup>The offense-defense balance of AI systems could significantly impact how increased model capabilities translate to risks. If defensive AI applications can reduce AI risks, it may counterbalance risks from offensively used models.

<span id="page-11-4"></span><sup>&</sup>lt;sup>10</sup>For a discussion of the relationship between training compute, loss, capabilities, and risks, see [Anderljung](#page-28-0) [et al.](#page-28-0) [\(2023\)](#page-28-0), [Sastry et al.](#page-33-1) [\(2024\)](#page-33-1), and [Pistillo et al.](#page-33-2) [\(forthcoming\)](#page-33-2).

the final determinant for what safety measures to require. After compute thresholds, decision criteria based on more precise proxies for the risk a model poses, such as capability thresholds, should be applied [\(Section 5.1\)](#page-12-0). Both the US AI EO [\(Section 5.2\)](#page-14-0) and the EU AI Act [\(Section 5.3\)](#page-15-0) take this approach.

#### <span id="page-12-0"></span>5.1 Initial Filter

When imposing requirements on GPAI models, policymakers need to consider five interdependent questions:

- 1. Which *risks* should be countered? (E.g., large-scale societal harm.)
- 2. Which *models* could pose these risks? (E.g., advanced GPAI models.)
- 3. Which *metrics* correspond to features of these models? (E.g., training compute.)
- 4. Which *thresholds* are the values of those metrics at which models start to pose these risks?  $(E.g., 10^{26}$  operations of training compute.)
- 5. Which *requirements* should be imposed on models above those thresholds to counter these risks? (E.g., reporting, model evaluation, and risk assessment.)

Easily measurable metrics, such as training compute, are generally preferable to ensure legal certainty about which GPAI models are in scope of requirements. At the same time, metrics that are better proxies for the risk a GPAI model poses, such as model capabilities, are generally preferable to ensure requirements are targeted at risky GPAI models. There will often be a trade-off between ease of measurability and correlation with risk (more in [Section 6.4\)](#page-22-0). Taken together, metrics that are cruder proxies for the risk a GPAI model poses should be combined with less costly and less definitive requirements, while metrics that are better proxies for the risk a GPAI model poses may be linked to more costly and more definitive requirements. What is more, all else equal, the stricter the requirements, the higher and therefore more exclusive the threshold should be.

Building on these considerations, the function of compute thresholds should be to serve as an *initial filter* to identify models of potential concern. Training compute is an easily measurable and externally verifiable proxy for risk that allows focusing on the most risky models and the most well-resourced actors [\(Section 3\)](#page-8-0). Therefore, compute thresholds provide an easy way to identify those GPAI models that warrant heightened attention (both from companies and regulators), while filtering out the much larger fraction of GPAI models that are highly unlikely to pose risks of large-scale societal harm. As a result, using compute thresholds as an initial filter can help to reduce both compliance burdens for regulatees and enforcement costs for regulators, while focusing attention on those GPAI models that are most likely to pose risks of large-scale societal harm.

However, the function of compute thresholds should *only* be to serve as an initial filter to identify models that warrant regulatory oversight and further scrutiny. Already, training compute is a very crude proxy for risk, and this relationship may become worse in the future [\(Section 4\)](#page-11-0). Therefore, compute thresholds should be complemented by thresholds based on metrics that are more precise but that may be harder to evaluate, such as model capability evaluations. In particular, compute thresholds should not be used to ultimately determine which mitigation measures need to be taken (beyond a few key precautionary mitigation measures). For models that cross a compute threshold, more rigorous analyses of the risk they pose should be conducted through model evaluations and risk assessments. Based on the results of these analyses, specific mitigation measures can be required (and precautionary mitigation measures that have been taken but turn out unnecessary may be discontinued). Currently, a sensible approach would be to first apply compute thresholds (to identify GPAI models that warrant oversight and scrutiny) and to subsequently apply capability thresholds (to ultimately determine which mitigation measures need to be implemented) [\(Section 4\)](#page-11-0).

We also highlight that compute thresholds should not be used for all requirements aimed to counter risks from AI. First, many risks from AI stem from the context and way in which AI models are applied, instead of or in addition to the intrinsic properties of those AI models, necessitating requirements at the application layer. In particular, bias, discrimination, and fairness risks, for example, caused by AI models being applied in education, hiring, and public service provision, should be countered through requirements at the application layer in addition to the model layer, as done in the EU AI Act Chapter II (Prohibited AI Practices), Chapter III (High-Risk AI Systems), and

Chapter IV (Transparency Obligations). For requirements at the application layer, compute thresholds will usually not make sense but other criteria should be decisive, like the type of application. Second, some risks from GPAI models arise regardless of their amount of training compute, such as risks of copyright or privacy infringements. These risks should be countered through requirements imposed on all GPAI models, as done in the EU AI Act Article 53. Third, ex post regulation like tort law and criminal law should of course not hinge on compute thresholds. Overall, in a full regulatory framework for AI, most requirements should not hinge on the amount of training compute [\(Figure 6\)](#page-13-0).

<span id="page-13-0"></span>

Figure 6: A framework for the role of compute thresholds in GPAI regulation. Compute thresholds serve as an initial filter to identify GPAI models that warrant regulatory oversight and further scrutiny, and, for example, evaluation against capability thresholds to determine appropriate mitigation measures, complemented by other AI requirements.

Thresholds based on easily measurable metrics that serve as initial filters for regulatory oversight and further scrutiny are in place across various sectors. For example, in the US, the Environmental Protection Agency's (EPA) ecological risk assessments start by determining whether some concentration of contaminants has been crossed, only after which a more thorough risk assessment takes place [\(U.S. Environmental Protection Agency & Office of Emergency and Remedial Response, 1996\)](#page-34-8). In the EU, the Digital Services Act (DSA) identifies "very large online platforms" and "very large online search engines" that need to conduct systemic risk assessments based on whether they have a "number of average monthly active recipients of the service in the Union equal to or higher than 45 million" (Article 33(1) DSA). Similarly, the General Data Protection Regulation (GDPR) mandates data protection impact assessments for entities processing data "on a large scale" (Article 35(3) GDPR)— the concrete metric and threshold in this case is to be specified by member states, who have chosen different thresholds, most of which are based on the number of people whose data is concerned [\(Breitbarth, 2018\)](#page-29-9).

While we generally have reservations about using compute thresholds to ultimately determine which mitigation measures to require, this can be different if the threshold is set relatively high such that only a few well-resourced actors are affected. For example, we have suggested elsewhere to use compute thresholds to identify large compute providers on which to impose Know Your Customer (KYC) and other requirements [\(Egan & Heim, 2023\)](#page-29-0). We believe this approach can be justified, as it only targets a handful of companies (see [Heim et al., 2024;](#page-30-1) [Egan & Heim, 2023\)](#page-29-0).

#### <span id="page-14-0"></span>5.2 US AI Executive Order

The US AI EO covers a range of issues from AI. Section 4 leverages training compute thresholds as a criterion for classifying AI models that warrant regulatory oversight and further scrutiny due to potential safety and security concerns. Specifically, it targets:

"any model that was trained using a quantity of computing power greater than  $10^{26}$ *integer or floating-point operations, or using primarily biological sequence data and using a quantity of computing power greater than* 10<sup>23</sup> *integer or floating-point operations"* (Section 4.2(b)(i))

Note that these thresholds are designed to capture future models. As of July 2024, no model has been officially reported to meet the general compute threshold of  $10^{26}$  operations [\(Figure 7\)](#page-14-1). However, one model has been estimated to meet the lower bio-compute threshold [\(Maug et al., 2024\)](#page-31-7).

#### <span id="page-14-1"></span>Compute Thresholds as Specified in the US Executive Order 14110



Total compute used to train notable Al models, measured in total FLOP (floating-point operations) | Logarithmic

Figure 7: The US AI EO introduces reporting requirements for models trained with more than  $10^{26}$ operations and  $10^{23}$  operations if trained using primarily biological sequence data (figure adapted [Sastry et al. 2024;](#page-33-1) underlying data and updates can be found at [Epoch AI 2024a\)](#page-29-4).

The US AI EO mandates companies to notify the government about ongoing or planned activities concerning the development of models that cross the compute thresholds (Section 4.2(a)(i)(A)). It also requires these companies to report on the measures taken to ensure the physical and cybersecurity of model weights (Section  $4.2(a)(i)(B)$ ) and share the results of red-teaming tests and mitigation measures taken based on those results (Section  $4.2(a)(i)(C)$ ).

The US AI EO uses compute thresholds in line with what we have argued can and should be their role [\(Section 5.1\)](#page-12-0). Its requirements focus on reporting to increase regulatory oversight, which is one of the primary functions compute thresholds can fulfill. While the US AI EO does not mandate companies to implement security measures or conduct red-teaming tests, the corresponding reporting requirements strongly push companies to take such measures in order to not appear irresponsible to the regulator. In our view, the pressure to conduct red-teaming tests also makes sense, as increased scrutiny is another primary function of compute thresholds. The pressure to implement security measures can also be based on compute thresholds. However, we believe that companies should be given the option to relax their security measures again if they establish that their model does not exceed a specific level of capabilities or can otherwise be proven to be sufficiently safe. We discuss domain-specific compute thresholds in [Section 6.2.](#page-19-0)

### <span id="page-15-0"></span>5.3 EU AI Act

The EU AI Act is the most comprehensive regulatory framework on AI worldwide, prohibiting certain AI practices (Chapter II), imposing requirements on certain high-risk AI systems (Chapter III), requiring transparency about the use of AI in services and to produce content (Chapter IV), and imposing requirements on GPAI models (Chapter V). Regarding the latter, the EU AI Act leverages a compute threshold to distinguish between GPAI models with and without systemic risk. Concretely, it draws the line in the following way: $11$ 

*"A general-purpose AI model shall be presumed to have high impact capabilities pursuant to paragraph 1, point (a) [and thus be classified as posing systemic risk], when the cumulative amount of computation used for its training measured in floating point operations is greater than*  $10^{25}$ ." (Article 51(2))

In contrast to the general compute threshold in the US AI EO, this compute threshold has immediate relevance. As of July 2024, one model available in the EU has officially been reported to have crossed the  $10^{25}$  training compute threshold (Inflection-2), some additional models available have been estimated to have done so (e.g., Gemini Ultra, GPT-4, Inflection-2.5) [\(Epoch AI, 2024a\)](#page-29-4), and there may be a handful more of such models [\(Figure 8\)](#page-16-0).

In the EU AI Act, the compute threshold is only one of several ways to identify GPAI models with systemic risk, but it currently is the most concrete one. In more detail, Article 51(1) says that a GPAI model shall be classified as posing systemic risk if it has either "high impact capabilities" (Article 51(1)(a)) or "capabilities or an impact equivalent to those set out in point (a)" (Article 51(1)(b)). Regarding the first alternative, high-impact capabilities are defined as "capabilities that match or exceed the capabilities recorded in the most advanced general-purpose AI models" (Article 3(64)). A model is *presumed* to have high-impact capabilities, and thus pose systemic risk, if the compute threshold of  $10^{25}$  floating-point operations is crossed (Article 51(2)). Regarding the second alternative, it is not defined and remains somewhat unclear what "capabilities or an impact equivalent to those set out in point (a)" means. Instead, the European Commission decides whether these conditions are fulfilled "having regard to the criteria set out in Annex XIII" (Article  $51(1)(b)$ ). These criteria contain many of the metrics discussed in [Section 6.4,](#page-22-0) including the number of parameters, the quality and quantity of the training data, and the number of users (Annex XIII). Overall, the compute threshold currently seems to be the most concretely outlined way in which a GPAI model can be classified as posing systemic risk, and may therefore be the most relevant in the near term [\(Figure 9\)](#page-17-2).

Article 52(1) requires providers to notify the European Commission if a GPAI model crosses or will cross the threshold laid out in Article  $51(1)(a)$ , in particular by passing the compute thresholds in Article 51(2). This is to be done "without delay and in any event within two weeks." Furthermore, Article 55 requires providers of GPAI models with systemic risk to perform model evaluations, assess and mitigate systemic risks, report serious incidents, and ensure cybersecurity of the model and its

<span id="page-15-1"></span><sup>&</sup>lt;sup>11</sup>When establishing compute thresholds, it is advisable for the EU AI Act to use the term "operations" rather than specifying a particular type of operation (such as floating-point operations or FLOP). Using the broader term "operations" ensures that the threshold remains agnostic to the specific type of computational operations performed during training, making it more future-proof in light of possible technological changes. This approach also maintains consistency with the terminology used in the US AI EO, ensuring interoperability and enabling cooperation between EU and US regulators.



# <span id="page-16-0"></span>Compute Thresholds as Specified in the US Executive Order 14110 and EU AI Act

Estimated compute cost and total training compute used to train notable Al models, measured in total FLOP (floating-point operations) | Logarithmic

Figure 8: While the US AI EO introduces reporting requirements for models trained with more than  $10^{26}$  operations, the EU AI Act presumes a GPAI model poses systemic risk and imposes a variety of requirements for models trained with more than 10<sup>25</sup> operations (figure adapted from [Sastry et al.](#page-33-1) [2024;](#page-33-1) underlying data and updates can be found at [Epoch AI 2024a\)](#page-29-4).

physical infrastructure.<sup>[12](#page-16-1)</sup> These requirements are relatively vague but will be concretized by "codes" of practice" (Article 56). $^{13}$  $^{13}$  $^{13}$  [14](#page-16-3)

The EU AI Act uses compute thresholds mostly in line with what we have argued can and should be their role [\(Section 5.1\)](#page-12-0). It focuses on requirements of regulatory oversight (notification and serious incidents reporting) and further scrutiny (model evaluations and systemic risk assessments). The requirements to mitigate systemic risks and ensure adequate cybersecurity may appear to go beyond what we think compute thresholds should be used for—we have argued that they should not be used to determine which mitigation measures need to be implemented. But this is not necessarily how these requirements need to be interpreted. The codes of practice can and, in our view, should differentiate further which mitigation measures must be implemented under which circumstances (for example,

<span id="page-16-1"></span> $12$ These requirements apply in addition to the requirements for all GPAI models, which include documentation, transparency, and copyright policies (Article 53).

<span id="page-16-2"></span> $13$ It is very attractive, though not mandatory, for providers to comply with the codes of practice, because this provides a "presumption of conformity." If a provider complies with the codes of practice, the provider is presumed to also comply with the EU AI Act. But providers have the option to demonstrate compliance in other ways, too (Article 55(2)).

<span id="page-16-3"></span><sup>&</sup>lt;sup>14</sup>Ultimately, technical standards are supposed to provide the presumption of conformity (Article 40(1)). However, the European Commission has not yet issued the standardization request for GPAI models, and once this happens it will still take several months or years for the technical standard to be developed. Therefore, in the meantime, the codes of practice take on the equivalent role.

<span id="page-17-2"></span>

Figure 9: The EU AI Act outlines two main pathways for classifying general-purpose AI (GPAI) models as posing systemic risk. The first path deems models as high-risk if they possess "high-impact capabilities" that match or exceed the most advanced GPAI models, which is presumed if the training compute exceeds 10<sup>25</sup> floating-point operations (FLOP). Alternatively, the European Commission can classify models based on criteria outlined in Annex XIII. Models deemed high-risk through either pathway are subject to stringent regulations to mitigate systemic risks.

based on the results of model evaluations), such that this is not solely determined by the compute threshold.

Another important mechanism in the EU AI Act is the possibility for providers to demonstrate that their model does not pose systemic risk, despite fulfilling the conditions of Article  $51(1)(a)$ —such as passing the compute threshold (Article 52(2)). This exception especially makes sense if the conditions of Article 51(1)(a) are presumed to be fulfilled because the compute threshold is crossed, given that training compute is only a very crude proxy for risk [\(Section 4\)](#page-11-0). The provision is in line with how we have argued compute thresholds should be used [\(Section 5.1\)](#page-12-0). If it turns out that a model does not pose systemic risk despite passing the compute threshold—for example, based on model evaluations and risk assessments—providers will be allowed to refrain from further model evaluations, risk assessments, etc., and drop any precautionary security measures they have already taken. Overall, the EU AI Act can be understood to embed its compute threshold in a framework similar to what we have suggested in [Section 5.1](#page-12-0) [\(Figure 10\)](#page-18-0).

# <span id="page-17-0"></span>6 Challenges for Training Compute Thresholds in GPAI Regulation

The key question when using compute thresholds is at what level to place the threshold. In [Section 6.1,](#page-17-1) we discuss where a compute threshold should be set at a given point in time. In [Section 6.2,](#page-19-0) we briefly touch on whether domain-specific compute thresholds make sense. In [Section 6.3,](#page-20-0) we examine why, when, and how a compute threshold should be updated over time. In [Section 6.4,](#page-22-0) we discuss metrics other than training compute that may be useful to distinguish between more and less risky models, with a focus on but not limited to risk estimates, model capability evaluations, and effective compute.

#### <span id="page-17-1"></span>6.1 Where to Set Compute Thresholds

In this section, we discuss at what level a compute threshold should be set. Already, different regulators have chosen different values, with the US AI EO using  $10^{26}$  operations and the EU AI Act using  $10^{25}$  floating-point operations, one order of magnitude lower. This difference is relevant, as the EU threshold likely captures several existing models, while the US threshold probably does not capture any existing model [\(Section 5\)](#page-11-1).

In general, at any given point in time, a compute threshold can capture three tiers of models:

1. **Models above the frontier** (currently  $10^{26} - 10^{27}$  operations). At any given point in time, such models are the most important ones to include, as models above the frontier may

<span id="page-18-0"></span>

Figure 10: How the EU AI Act can be understood to implement the framework of [Figure 6.](#page-13-0) GPAI models exceeding the  $10^{25}$  FLOP training compute threshold (Article 51(1)(a)) are classified as posing systemic risk, triggering requirements such as notifying the Commission, undergoing model evaluations and risk assessments, reporting incidents, and implementing precautionary risk mitigation and cybersecurity measures. Subsequent model capability thresholds, outlined in Codes of Practice (CoP), further categorize these high-risk models into low or high systemic risk levels, informing increasingly stringent mitigation and cybersecurity requirements.

have unprecedented and hard-to-predict dangerous capabilities (see [Anderljung et al., 2023\)](#page-28-0). Better understanding of and government visibility into state-of-the-art models is key to identifying potential issues as early as possible, as well as for getting a sense for what may be coming down the pike. The advantage of this approach is that it focuses on the few models that are the most likely to be risky. On the other hand, it incurs some chance of being underinclusive, missing risky models.

- 2. Models at the frontier (currently  $10^{25} 10^{26}$  operations). Currently, including such models may be deemed warranted, as models at the current frontier may already be considered to show warning signs of some dangerous capabilities (see [Anthropic, 2024;](#page-28-6) [OpenAI](#page-32-2) [et al., 2023;](#page-32-2) [Phuong et al., 2024\)](#page-33-5). While some companies developing such models have reported that their models do not possess dangerous capabilities, governments may want to verify those claims and ensure that all companies developing such models conduct model evaluations and risk assessments. This seems to be the approach of the EU AI Act.
- 3. Models below the frontier (currently  $10^{24}$ – $10^{25}$  operations). Currently, including such models would be a very cautious approach. There still is some uncertainty about the full extent of the capabilities of models below the current frontier (see [Anderljung et al., 2023\)](#page-28-0). The advantage of this approach is that it creates a large "margin of safety." On the other hand, it has the biggest chance of being overinclusive, putting regulatory burdens on companies developing models that later turn out to be not risky. This is burdensome for regulators, if they want to properly verify company reports, and for companies themselves. However, in the future, if society does not keep pace in adapting to increasingly high model capabilities, maintaining a threshold below the frontier could be warranted [\(Section 6.3\)](#page-20-0).

Currently, the US AI EO, at least for now, has taken the first approach, only targeting models above the current frontier. Whether the US will uphold this approach by updating its compute thresholds with the moving frontier remains to be seen [\(Section 6.3\)](#page-20-0). The EU AI Act has explicitly taken the second approach, targeting models at and above the current frontier: A GPAI model poses systemic risk if it has "high impact capabilities" (Article  $51(1)(a)$ ), which in turn are defined as "capabilities" that match or exceed the capabilities recorded in the most advanced general-purpose AI models" (Article 3(64)). This arguably means the provision aims to refer to a moving set of models—those at and above the frontier *at any given point in time*. If the provision was referring to the models at and above the frontier *at a specific point in time*, such as the time of writing or entering into force of the EU AI Act, this point in time would have been specified for legal certainty. Based on this interpretation, the compute threshold in Article 51(2) would need to be updated with the moving frontier (see also [Section 6.3\)](#page-20-0).

#### Post-Training Enhancements

An important phenomenon that should affect where to set compute thresholds is the possibility of post-training enhancements [\(Section 2\)](#page-6-0). Compute thresholds should be based on the capabilities of enhanced *systems* like ChatGPT, rather than the capabilities of pre-trained models, because those are the capabilities the models will ultimately obtain. For example, if a regulator currently sets a threshold at  $10^{25}$  operations, this should be because they have concluded that models like GPT-4 or Gemini Ultra 1.0 and their superseeding application, such as ChatGPT or Gemini, should be subject to regulation. This assessment should not be based on the capabilities of the pre-trained model but rather on those achieved through post-training enhancements. By contrast, if a regulator currently sets a threshold at  $10^{26}$  operations, this should be because they believe that no current model possesses concerning capabilities, even after accounting for post-training enhancements.

Regulators could also add a safety buffer of an order of magnitude or so to account for potential future improvements in post-training enhancements. For pre-trained models trained on the same amount of compute, better post-training enhancements could be developed over time. Future improvements in post-training enhancements could lead to models trained on a given amount of pre-training compute being enhanced to display higher and more dangerous capabilities than current models trained on the same amount of pre-training compute but enhanced with current techniques only. To account for further unknown post-training enhancements, regulators could add a safety buffer in "equivalent pre-training compute" [\(Davidson et al., 2023\)](#page-29-3).

However, we expect that for the foreseeable future there is likely a limit to the increase in model capabilities that can be gained from post-training enhancements. The capabilities of the model determined by pre-training will likely remain critical. While post-training enhancements may continue to improve incrementally, they are unlikely to enable models to "leapfrog" or "skip multiple generations" of compute scaling and achieve capabilities comparable to those of models pre-trained with orders of magnitude more compute [\(Davidson et al., 2023\)](#page-29-3). Furthermore, certain post-training enhancements work better with larger models [\(Li et al., 2024\)](#page-31-8), suggesting their effectiveness may depend on leveraging the capabilities of models with significant pre-training compute. In other words, while post-training enhancements can potentially enhance the absolute capabilities of models, they are less likely to significantly alter the relative capabilities compared to models pre-trained with orders of magnitude more compute, especially for more advanced models.

#### <span id="page-19-0"></span>6.2 Domain-Specific Compute Thresholds

The focus of this paper up to this point has been on compute thresholds for GPAI models. This section briefly discusses domain-specific compute thresholds for narrower, more specialized models. Already, the US AI EO includes a compute threshold for models specialized in the domain of biology. The considerations for whether it makes sense to use domain-specific compute thresholds in general, and in the domain of biology in particular, are the same as the considerations for whether it makes sense to use compute thresholds for GPAI models.

Generally, the key consideration is whether scaling laws apply in the domain in question. Regulating models based on the amount of training compute only makes sense if there is a strong relationship between the amount of compute used to train a model and the level of risk the model poses. Another important consideration is how many actors will be in scope of a given compute threshold. If too many actors are in scope, i.e., the amount of computational power to surpass the threshold is available to a broad range of actors, a domain-specific compute threshold may not be practicable. Both of these considerations may differ from domain to domain.

We are uncertain whether compute thresholds in the domain of biology make sense and can only provide initial thoughts: In the domain of biology, a distinction can be made between AI-enabled biological tools (BTs) and large language models (LLMs) with a focus on biology [\(Sandbrink,](#page-33-6) [2023;](#page-33-6) [Smith et al., 2024\)](#page-34-9). AI-enabled BTs are AI models that are highly specialized on a particular biological task, such as predicting protein structures, like AlphaFold 2 [\(Jumper et al., 2021\)](#page-31-9). LLMs with a focus on biology are LLMs trained on a lot of biological sequence data, and can be used for a variety of applications, such as ESM3 [\(Hayes et al., 2024\)](#page-30-9). It is uncertain if compute thresholds are appropriate for AI-enabled BTs, as the literature on scaling laws is not well established for those. In contrast to GPAI models, other factors, such as the quality of data, are much more important for their capabilities. Moreover, AI-enabled BTs generally require about  $100\times$  less compute to train than GPAI models, such that a large number of actors would be in scope of requirements based on compute thresholds [\(Smith et al., 2024\)](#page-34-9). For LLMs with a focus on biology, compute thresholds could make sense, but the literature on scaling laws is similarly scarce (e.g., [Hesslow et al.](#page-30-10) [\(2022\)](#page-30-10); [Serrano et al.](#page-34-10) [\(2024\)](#page-34-10)).

#### <span id="page-20-0"></span>6.3 Why, When, and How to Update Compute Thresholds

Compute thresholds will very likely need to be updated over time. Generally, it is important to maintain flexibility in regulations for a poorly understood and rapidly evolving technology like GPAI. First and foremost, compute thresholds should be adjusted with better knowledge about what constitutes risky models. What is more, depending on improvements in algorithmic efficiency and computational price-performance, as well as changes in the offense-defense balance of AI systems, the threat landscape, and societal vulnerability or adaptation, compute thresholds will need to be adjusted downwards or upwards over time.

The US AI EO states that its thresholds for models in scope should regularly be updated:

*"The Secretary of Commerce, in consultation with the Secretary of State, the Secretary of Defense, the Secretary of Energy, and the Director of National Intelligence, shall define, and thereafter update as needed on a regular basis, the set of technical conditions for models and computing clusters that would be subject to the reporting requirements of subsection 4.2(a) of this section."* (Section 4.2(b))

The EU AI Act also states that its thresholds for GPAI models with systemic risk should be updated based on technological developments:

*"The Commission shall adopt delegated acts in accordance with Article 97 to amend the thresholds listed in paragraphs 1 and 2 of this Article, as well as to supplement benchmarks and indicators in light of evolving technological developments, such as algorithmic improvements or increased hardware efficiency, when necessary, for these thresholds to reflect the state of the art."* (Article 51(3))

Given that GPAI is a poorly understood and rapidly evolving technology, any GPAI regulation should have the ability to be updated. On a high level, there are two approaches to updating the level of compute thresholds over time: specifying a fixed value but tasking regulators with updating that value over time, or specifying a dynamic value that automatically moves according to certain rules over time. Both the US and the EU have specified fixed values but tasked regulators with updating those values over time. By contrast, for example, a compute threshold could specify a dynamic value that automatically moves over time by being tied to the highest-compute model at any given point in time, or, alternatively, by being set at an order of magnitude below the highest-compute model at any given point in time. But even a dynamic compute threshold should allow for updates by regulators to account for a better understanding of what constitutes risky models as well as for technological and other relevant developments.

The frequency and the direction of updates to training compute thresholds depend on several developments. First and foremost, over time, our understanding of what constitutes risky models may improve. Currently, uncertainty about model capabilities and societal risks is high. Regulators impose requirements on GPAI models not because they are sure those models pose a high level of risk, but because they might. As such, if the current approach is motivated by precaution and has the goal to detect when GPAI models reach some level of risk, the compute threshold can be expected to move up over time as our understanding of model capabilities and societal risks improves.

Moreover, compute thresholds may need to be adjusted downwards over time to account for algorithmic efficiency improvements. In the context of model training, algorithmic efficiency refers to the amount of compute required to run a given algorithm used to train a model. Over time, ongoing research yields improved model architectures and training algorithms, reducing the amount of compute needed to train models of a given level of capabilities [\(Pilz et al., 2023\)](#page-33-4). Adjusting the compute threshold downwards at the pace of algorithmic efficiency improvements would maintain its correspondence to a given level of capabilities. However, algorithmic efficiency improvements can also mean that more actors will be able to train models with a given amount of compute and thus obtain a given level of capabilities. This can lead to high regulatory burdens on a large number of less well-resourced actors like startups and academics, and, correspondingly, high oversight costs for regulators [\(Pistillo et al., forthcoming\)](#page-33-2). As a result, algorithmic efficiency improvements can also provide an argument to adjust the compute threshold upwards over time. Taken together, algorithmic efficiency improvements may pose a regulatory dilemma [\(Winter & Bullock, forthcoming\)](#page-35-2).

At the same time, algorithmic efficiency improvements merely define the upper limit for how quickly the compute threshold may need to be adjusted downwards to apply to models posing a given level of risk. Despite improvements in algorithmic efficiency, developments such as the offense-defense balance of AI systems, the threat landscape, and societal vulnerability or adaptation suggest the threshold may need slower downwards adjustments, remain unchanged, or even be adjusted upwards to catch models of a given level of risk. GPAI models may turn out to enable defensive uses less, as much as, or even more than offensive uses, for example, in the cyber domain [\(AI Policy Perspectives](#page-28-4) [& Krier, 2024;](#page-28-4) [Buterin, 2023;](#page-29-7) [Lohn & Jackson, 2022\)](#page-31-4). Malicious actors may for various reasons including such unrelated to GPAI models—become more or less numerous, able and willing to use GPAI models. Over time, society could become better at managing risks from models, meaning a model of a given level of capabilities may pose less risk [\(Anderljung et al., 2023;](#page-28-0) [Bernardi et al.,](#page-28-5) [2024;](#page-28-5) [Kapoor et al., 2024\)](#page-31-6). Under these circumstances, compute thresholds may be adjusted upwards over time to continue to focus on models posing a given level of risk.

Another development that can be relevant for adjusting compute thresholds is computational priceperformance improvements. In the context of model training, computational price-performance refers to the amount of compute that can be obtained for a given amount of money [\(Hobbhahn et al., 2023\)](#page-30-8). Over time, the amount of training compute available for a given amount of money increases due to innovations in hardware manufacturing and design [\(Pilz et al., 2023\)](#page-33-4). Importantly, such improvements in computational price-performance do not influence the amount of training compute necessary to achieve a given level of capabilities, meaning they do not influence the level of risk from models that cross a given compute threshold. However, improvements in computational price-performance may increase regulatory burdens and oversight costs: More actors may be able to afford the amount of compute required to train models that meet the regulatory threshold [\(Pilz et al., 2023\)](#page-33-4). Again, this does not influence the level of risk from models that cross a given compute threshold. But it might still be an argument to adjust the compute threshold upwards to reduce regulatory burdens and oversight costs. By doing so, however, regulators accept a higher level of risk for society.<sup>[15](#page-21-0)</sup>

The US AI EO tasks the Secretary of Commerce with updating its compute thresholds, without specifying further details on how to do so (Section 4.2(b)). We have provided what we believe to be the key substantive considerations. The Secretary of Commerce should monitor these developments and aim to increase understanding of risks from GPAI models. On the procedural side, the US AI EO specifies that updates should occur on a "regular basis." An examination of whether a compute threshold needs to be updated should happen at least every couple of months, and maybe more frequently if the pace of algorithmic efficiency or computational price-performance improvements increases.

The EU AI Act provides some guidance on how the European Commission should update its thresholds for identifying GPAI models with systemic risk, referring to "technological developments, such as algorithmic improvements or increased hardware efficiency" (Article 51(3)). As argued above, the mention of algorithmic (efficiency) improvements is important. However, the reference to "increased hardware efficiency" is ambiguous and might reflect a misunderstanding. To the extent that this term refers to innovations in hardware manufacturing and design that may lead to computational price-performance improvements, as explained above, corresponding developments do not influence the level of risk from a given compute threshold. Instead, they only affect the accessibility and

<span id="page-21-0"></span> $15$ For a more comprehensive discussion of this issue, see [Pilz et al.](#page-33-4) [\(2023\)](#page-33-4).

proliferation of models that meet a given compute threshold. As hardware becomes more efficient, the same amount of compute becomes available at a lower cost and therefore potentially to a broader range of actors. Consequently, hardware efficiency improvements should be considered when adjusting compute thresholds, not because they alter the relationship between training compute and model capabilities, but because they may increase the number of actors in scope of a given compute threshold. Furthermore, the EU AI Act guidance ignores two crucial factors: better understanding of what constitutes risky models, and societal developments that influence the level of risk posed by models with a given level of capabilities.

### <span id="page-22-0"></span>6.4 Alternative Metrics

Given the limitations of training compute, several other metrics may be useful to distinguish between more and less risky models. For example, the EU AI Act mentions a variety of metrics that should play a role in identifying GPAI models with systemic risk: the number of model parameters, the quantity and quality of training data, the amount of training compute, input and output modalities and type, model capabilities, a high impact on the internal market due to reach (presumed if at least 10 000 registered business users in the Union), and the number of registered end users (Annex XIII). Other metrics commonly discussed include risk estimates, model capability evaluations, effective compute, and some other metrics.

#### <span id="page-22-1"></span>6.4.1 Risk Estimates

The most straightforward way to distinguish between more and less risky models may be to directly measure, or rather estimate, the increase in risk from a model. On the one hand, risk estimates are directly focused on harm to individuals, groups, and society as a whole. Risk estimates do not face the issue of potentially focusing on wrong proxies, such as too little compute or harmless capabilities [\(Koessler et al., 2024\)](#page-31-5). On the other hand, risk estimates are extremely hard to do well for an emerging, general-purpose technology like GPAI. Little historical data and a tremendous amount of risk scenarios mean risk estimates have to rely on models and expert judgment, and they face the issue of missing important risk scenarios [\(Schuett et al., forthcoming\)](#page-33-7). Overall, risk estimates require a lot of effort to conduct, meaning they should not replace compute thresholds as an initial filter. After that filter has been applied, risk estimates are the ideal, but still highly immature, metric to decide whether mitigation measures are necessary. Risk thresholds defined in terms of risk estimates should thus not yet determine, but only inform decisions about whether mitigation measures are necessary [\(Koessler et al., 2024\)](#page-31-5).

### <span id="page-22-2"></span>6.4.2 Model Capability Evaluations

Another metric useful for distinguishing between more and less risky models is model capability evaluations. Currently, the two most common approaches to evaluations are "benchmarking" and "red-teaming." Benchmarking involves using standardized tests to evaluate model capabilities—these benchmarks allow comparisons between different models. Well-known benchmarks include BBQ (bias; [Parrish et al. 2022\)](#page-32-3), GLUE (natural language understanding; [Wang et al. 2019\)](#page-34-11), and MMLU (general knowledge; [Hendrycks et al. 2021\)](#page-30-11). Red-teaming involves less standardized and more in-depth testing, often by domain experts, for specific model capabilities and behaviors [\(Barrett et al.,](#page-28-7) [2024;](#page-28-7) [Jones et al., 2024\)](#page-31-10).

Risk-tracking: Model capabilities are attractive as a metric because they can be considered a proxy for risk and they are more closely related to risks than is training compute [\(Section 4\)](#page-11-0). However, model capabilities are an imperfect proxy, too. Other important factors include the offense-defense balance of AI systems, the threat landscape, and societal vulnerability or adaptation. Regulating consistent levels of capability over time may therefore not be warranted. At the same time, model capabilities may create a false sense of exhaustiveness, potentially leading to underestimating the need for risk assessments [\(Jones et al., 2024\)](#page-31-10).

Difficult to measure: Evaluating a model's capabilities is very challenging [\(Anwar et al., 2024;](#page-28-8) [Jones](#page-31-10) [et al., 2024;](#page-31-10) [Reuel et al., 2024\)](#page-33-8). In particular, proving the absence of a capability is difficult, implying a potentially large amount of false negatives [\(Casper et al., 2024\)](#page-29-10). Furthermore, models are highly prompt sensitive, meaning slight changes in inputs can lead to large differences in outputs [\(Mizrahi](#page-32-4) [et al., 2024;](#page-32-4) [Ramesh et al., 2023;](#page-33-9) [Sclar et al., 2024\)](#page-34-12). The appropriate point in a model's lifecycle to

evaluate capabilities can also lead to significant differences in results, as discussed in [Section 2.](#page-6-0) In general, there still is large disagreement in the research community about what constitutes adequate model capability evaluations, as evidenced by many competing benchmarks for similar capabilities (e.g., MATH, MGSM, and GSM8K for mathematical capabilities) [\(Anwar et al., 2024;](#page-28-8) [Jones et al.,](#page-31-10) [2024;](#page-31-10) [Reuel et al., 2024\)](#page-33-8). The field of dangerous model capability evaluations is especially nascent, with the first paper on the topic having been published about one year ago [\(Shevlane et al., 2023\)](#page-34-13). Finally, comprehensive model capability evaluations require significant effort [\(Anwar et al., 2024;](#page-28-8) [Jones et al., 2024;](#page-31-10) [Reuel et al., 2024\)](#page-33-8).

Easy to circumvent: Model capability evaluations may be circumvented. Related to the previous point, easy-to-run evaluations may be easy to game, allowing companies to design models that perform poorly on benchmarks while still excelling at the capabilities the benchmarks are meant to measure. The lack of standardization makes it particularly easy to inflate evaluation results [\(Leech](#page-31-11) [et al., 2024\)](#page-31-11). For example, companies may strategically choose which evaluations to conduct [\(Jones](#page-31-10) [et al., 2024\)](#page-31-10). Companies or deceptive AI models could also strategically underperform on a given set of evaluations, a phenomenon referred to as "sandbagging" [\(Järviniemi & Hubinger, 2024;](#page-31-12) [van der](#page-34-14) [Weij et al., 2024\)](#page-34-14).

Not measurable before development: Training compute is usually known prior to development, whereas model capability evaluations can only be conducted during and after development. There have been attempts to forecast model capabilities [\(Phuong et al., 2024\)](#page-33-5); however, such forecasting is likely still highly unreliable, as indicated by high disagreement between forecasters.

Difficult to verify externally: Model capabilities are also much harder to verify than training compute is. Since measuring model capabilities is more difficult, verifying these measurements is more difficult, too. Actors verifying model capabilities need more information and may even need to conduct model capability evaluations themselves. Regulators currently may not have the necessary expertise, and there is no mature third-party ecosystem, either. In the worst case, publishing model capability data might expose a company's algorithmic progress, potentially intensifying competitive dynamics in the AI industry.

Cost-tracking: Model capabilities are highly correlated with the cost of developing the model, since increases in capabilities largely stem from increases in training compute [\(Section 3\)](#page-8-0).

Overall, training compute and model capabilities should be viewed as complementary metrics. Training compute excels at providing a quick, easily measurable, and externally verifiable metric to identify potentially risky models and trigger regulatory oversight and further scrutiny. Model capabilities are more expensive and harder to measure but also provide more information about a model's risks. By using compute thresholds as a first-pass filter and then applying capability thresholds, regulators can create a more efficient and effective regulatory process [\(Section 5.1\)](#page-12-0).

#### <span id="page-23-0"></span>6.4.3 Effective Compute

Algorithmic efficiency improvements, including through advancements in model architecture and training methods, can over time reduce the amount of compute required to train models to similar levels of performance [\(Erdil & Besiroglu, 2023;](#page-29-11) [Hernandez & Brown, 2020;](#page-30-12) [Ho et al., 2024;](#page-30-13) [Sherry](#page-34-15) [& Thompson, 2021\)](#page-34-15). As a result, there is growing interest in using a metric called *effective compute*, which accounts for both increases in training compute and algorithmic efficiency improvements. Effective compute describes the equivalent increase in training compute that would be needed to match a given model performance absent algorithmic efficiency improvements [\(Ho et al., 2024\)](#page-30-13). Effective compute is a relative metric, as improvements in algorithmic efficiency are measured against a specific model performance. For example, effective compute may be expressed as how many times more compute would have been required to train a model to perform as well as a specific other model on a specific performance metric, had there been no algorithmic improvements (e.g.,  $4 \times$  effective compute relative to GPT-4 test loss).

Risk-tracking: Effective compute is as risk-tracking as the model performance metric it is tied to. For example, if this performance metric is a benchmark, then effective compute is a good of a proxy as the benchmark. If the performance metric is loss, then effective compute is as good as training compute. However, as with model capabilities, effective compute is only a proxy for risk. Regulating consistent levels of performance over time may therefore not be warranted. Depending on the performance metric, effective compute can even create a false sense of being a comprehensive

measure of risk—as it combines training compute and model capabilities—potentially leading to underestimating the need for risk assessments.

Difficult to measure: Effective compute is more difficult to measure than training compute is. Research on algorithmic efficiency improvements for AI models is sparse, with only a few papers published [\(Erdil & Besiroglu, 2023;](#page-29-11) [Hernandez & Brown, 2020;](#page-30-12) [Ho et al., 2024;](#page-30-13) [Sherry & Thompson,](#page-34-15) [2021\)](#page-34-15). There is also no agreement on two key questions: which performance metric to use and at what point during the model lifecycle to assess performance on that metric. Any definition of effective compute needs to choose a performance metric (e.g., test loss) as the reference point that the amount of compute required is "normalized" to. Technical metrics like test loss are easier to measure and scale more smoothly with compute, but they may not accurately represent real-world impact, which makes them similar to training compute as a metric while concealing this fact. Metrics like model capability evaluations are more relevant for risk but harder to measure and subject to sudden or unpredictable increases in performance, such as the emergence of new capabilities [\(Figure 11\)](#page-24-0). The appropriate point in the model's lifecycle to measure performance on a given metric also remains unclear. As discussed in [Section 2,](#page-6-0) performance gains can result from post-training enhancements like fine-tuning or prompting methods, often resulting in relatively larger increases in effective compute, primarily driven by the performance improvements achieved with a comparatively small additional compute investment. Furthermore, there is ambiguity regarding which prompting techniques (such zero-shot, few-shot, or chain-of-thought) should be allowed when measuring model capabilities, adding to the difficulty of making reliable statements about effective compute.

<span id="page-24-0"></span>



Technical performance metrics Capability evaluation benchmarks

Figure 11: Spectrum performance metrics effective compute can be tied to. Technical metrics like training loss, validation loss, and test loss scale more smoothly with compute, are easier to measure and verify, and are less context-dependent. In contrast, capability benchmarks may scale more suddenly with compute, are closer to real-world utility and impact, but can sometimes be more *reductive* to specific tests.

Easy to circumvent: The ease of circumventing effective compute depends on the chosen performance metric. Quantitative metrics like training loss or validation performance are more robust, but if based on evaluations or benchmarks, effective compute faces similar circumvention risks as those of model capability evaluations [\(Section 6.4.2\)](#page-22-2). Companies could game evaluations by designing models to underperform while still excelling at intended capabilities, strategically selecting evaluations, or intentionally underperforming ("sandbagging").

Not measurable before development: Training compute is usually known prior to development, whereas effective compute requires analysis of performance after development. As with model capabilities, performance can be forecasted, but such forecasts are still highly unreliable.

Difficult to verify externally: Verifying effective compute may require access to more proprietary information than does training compute. Publishing effective compute data alongside standard training compute data could expose a company's algorithmic progress, potentially intensifying competitive dynamics in the AI industry.

Cost-tracking: Effective compute is correlated with the cost of developing the model, since increases in performance largely stem from increases in training compute [\(Section 3\)](#page-8-0).

In conclusion, there currently are practical challenges to using effective compute as a metric. More research is needed to develop standardized ways to measure effective compute that address these challenges. If successful, an effective compute measure could become the "GDP per capita" of AI performance (e.g., by creating "a nominal basket of benchmarks"). Effective compute is currently most suitable for internal company use, where the necessary tools and insights for accurate assessment are readily available. For example, companies can use effective compute for selecting checkpoints for their safety policies [\(Anthropic, 2023;](#page-28-9) [Dragan et al., 2024;](#page-29-12) [OpenAI, 2023\)](#page-32-5). External entities, including regulatory bodies, may struggle to accurately assess effective compute due to the lack of standardized methods and limited access to models. Moreover, regulatory bodies may not yet possess the technical expertise required to accurately assess effective compute. Given these challenges, we currently recommend not using effective compute for regulatory purposes.

#### <span id="page-25-0"></span>6.4.4 Parameters, Data, and Other Metrics

This section provides an initial analysis and comparison of other metrics to the more extensively discussed ones above. The metrics in this section include most of the main variables in model development and deployment. In the discussion of each metric, we assume the values of all other variables remain fixed (e.g., when talking about the correlation between model architecture and risk we assume a fixed amount of training compute). We highlight that the discussion in this section is preliminary and many points we make need further work and empirical investigation.

*Model architecture and training algorithm*: The model's architecture and training algorithm influence its capabilities and thus risk, but empirically to a much lesser extent than the amount of training compute [\(Ho et al., 2024;](#page-30-13) [Kaplan et al., 2020;](#page-31-2) [Sutton, 2019\)](#page-34-4). Moreover, these metrics are hard to quantify, they often involve step changes, and they are multidimensional with complex synergies between different dimensions (e.g., a certain number of layers might work well with a certain learning rate but not another).

*Number of model parameters*: The number of model parameters tracks capabilities and thus risk [\(Kaplan et al., 2020\)](#page-31-2) and can simply be counted [\(Villalobos et al., 2022\)](#page-34-16). However, certain model architectures like Mixture of Experts (MoE) can significantly change the number of model parameters without necessarily increasing the model's capabilities and risk [\(Villalobos et al., 2022\)](#page-34-16), and the number of model parameters can be manipulated through post-training techniques like model pruning without necessarily decreasing the model's capabilities and risk [\(Cheng et al., 2023\)](#page-29-13). What is more, the number of model parameters affects the necessary amount of training compute and is thus captured by that metric. More training compute is required to handle more parameters trained on a given amount of data. Additionally, developers can be expected to aim for an optimal ratio between the number of model parameters and the amount of training data as described by scaling laws. Therefore, for a given architecture and assuming training compute allocation was optimal according to scaling laws, training compute implies the number of model parameters.

*Amount and quality of training data*: The amount of training data affects model capabilities and risk [\(Kaplan et al., 2020\)](#page-31-2) and can be quantified in tokens or bytes [\(Villalobos et al., 2024\)](#page-34-1). However, data quality is also crucial, influencing capabilities across dimensions like information density and diversity, yet lacking objective or standardized measurement methods [\(Mitchell et al., 2023\)](#page-32-6). Importantly, amount and quality are interrelated - more data does not guarantee better performance with poor quality, while high-quality data can compensate for smaller sizes [\(Evans et al., 2024;](#page-29-14) [Gunasekar et al., 2023\)](#page-30-14). Additionally, the number of epochs or passes over the training data during the training process also affects the total compute requirements, even with a fixed dataset size. Developers optimize the ratio of parameters, data size, data quality, and number of epochs per scaling laws. Thus, for a given architecture with optimal compute allocation, training compute serves as an indirect proxy for the amount of training data utilized, as well as the number of training epochs but not for the quality.

*Number of users*: The number of users correlates with risks from accidents and, to some extent, misuse (the larger the user base, the more likely misuse occurs). However, it may not correlate with risks from misalignment or risks that arise before deployment, such as malicious actors stealing and misusing the model. This metric is difficult to estimate before deployment and even more so before development.

*Applications*: While applications are often known before deployment (except if model weights are publicly released), many GPAI models are used in general-purpose tools, like GPT-4 powering ChatGPT. Before development, it often does not make sense to consider applications, as GPAI models, by definition, have broad capabilities and can be used for many downstream applications [\(Jones,](#page-31-13) [2023\)](#page-31-13).

*Harm*: This metric is the materialization of risk. However, it is not known in advance of development or deployment. The best we can do in advance of development and deployment is to estimate the likelihood and severity of harm, that is, estimate risk [\(Section 6.4.1\)](#page-22-1). Of course, such risk estimates should be updated with the data gathered through monitoring, and development or deployment should be discontinued at any time if a particular number or type of incidents occur. However, at that point, the harm from those incidents cannot be undone. Therefore, in particular for irreversible and large-scale harm, in addition to ex post metrics that measure risk in hindsight, we need ex ante metrics that measure risk in advance.



Table 1: First-pass ranking of potential metrics for GPAI regulation regarding the features discussed in [Section 3.](#page-8-0)

Complementing mere compute thresholds with other metrics becomes relevant to the extent that scaling laws cease to hold and training compute becomes a worse proxy for risk [\(Section 4\)](#page-11-0). Particularly relevant combinations may include training compute and model capability evaluations (to ensure catching the most capable models) and training compute and number of users (to ensure catching the most widely used models). However, any threshold that is supposed to serve as an initial filter to identify models of potential concern should be based on metrics that can be measured easily and early in the model lifecycle. This, at least currently, excludes model capability evaluations, and at least before deployment, the number of users.

# <span id="page-27-0"></span>7 Conclusion

While not perfect, compute thresholds are currently one of the key tools in GPAI regulation. They offer a risk-correlated, easily measurable, and externally verifiable metric that can inform regulatory decisions while minimizing circumvention and targeting the most well-resourced actors. They are currently the best tool for identifying potentially risky models and triggering regulatory oversight and further scrutiny.

Further research is necessary on many questions related to compute thresholds. In particular, the trends relevant for updating compute thresholds require further research—both empirical research on their current development and theoretical research on their future development [\(Section 6.3\)](#page-20-0). Moreover, the usefulness of metrics other than training compute should be studied further, especially effective compute, which we consider a highly promising metric [\(Section 6.4.3\)](#page-23-0), and how to combine training compute with other metrics such as model capability evaluations or the number of users [\(Section 6.4.4\)](#page-25-0). Another area of research we would like to highlight concerns the enforcement of compute thresholds. What information do regulators need? What process should regulators rely on to ensure they get that information (e.g., should they inspect companies)? What special considerations apply if companies are not physically located within the territory of the regulator's jurisdiction?

Finally, compute thresholds are not sufficient for GPAI regulation—they are one tool among many. Their effectiveness depends on the specific context and the design of the overall regulatory framework. In particular, the discussion of whether capability thresholds are better than compute thresholds is misguided. Capability thresholds are supplemental, and while they might play a more important role in the future, compute thresholds are likely to remain a valuable tool in GPAI regulation, too. By understanding the strengths and limitations of compute thresholds, policymakers can make informed decisions about when and how to use them as part of a comprehensive approach to GPAI regulation.

# <span id="page-27-1"></span>Acknowledgments

We are grateful for valuable input from the following individuals (in alphabetical order by surname): Neel Alex, Markus Anderljung, Mauricio Baker, Lukas Berglund, Benjamin Bucknall, Alan Chan, Stephen Clare, Connor Dunlop, Jimmy Farrell, James Gealy, John Halstead, Marius Hobbhahn, Nicolas Moës, James Petrie, Konstantin Pilz, Jonas Sandbrink, Risto Uuk, and many others. All views and remaining errors are our own.

#### References

- <span id="page-28-4"></span>AI Policy Perspectives and Krier, S. Models on the frontline: AI's defensive role, May 2024. URL [https://www.aipolicyperspectives.com/p/models-on-the-frontline](https://www.aipolicyperspectives.com/p/models-on-the-frontline-ais-defensive)[ais-defensive](https://www.aipolicyperspectives.com/p/models-on-the-frontline-ais-defensive).
- <span id="page-28-0"></span>Anderljung, M., Barnhart, J., Korinek, A., Leung, J., O'Keefe, C., Whittlestone, J., Avin, S., Brundage, M., Bullock, J., Cass-Beggs, D., Chang, B., Collins, T., Fist, T., Hadfield, G., Hayes, A., Ho, L., Hooker, S., Horvitz, E., Kolt, N., Schuett, J., Shavit, Y., Siddarth, D., Trager, R., and Wolf, K. Frontier AI Regulation: Managing Emerging Risks to Public Safety. arXiv preprint arXiv:2307.03718 [cs], November 2023. doi[:10.48550/arXiv.2307.03718.](https://doi.org/10.48550/arXiv.2307.03718)
- <span id="page-28-9"></span>Anthropic. Anthropic's responsible scaling policy, September 2023. URL [https://www.](https://www.anthropic.com/news/anthropics-responsible-scaling-policy) [anthropic.com/news/anthropics-responsible-scaling-policy](https://www.anthropic.com/news/anthropics-responsible-scaling-policy).
- <span id="page-28-6"></span>Anthropic. Claude 3.5 sonnet model card addendum, June 2024. URL [https://www](https://www-cdn.anthropic.com/fed9cc193a14b84131812372d8d5857f8f304c52/Model_Card_Claude_3_Addendum.pdf)[cdn.anthropic.com/fed9cc193a14b84131812372d8d5857f8f304c52/Model\\_Card\\_](https://www-cdn.anthropic.com/fed9cc193a14b84131812372d8d5857f8f304c52/Model_Card_Claude_3_Addendum.pdf) [Claude\\_3\\_Addendum.pdf](https://www-cdn.anthropic.com/fed9cc193a14b84131812372d8d5857f8f304c52/Model_Card_Claude_3_Addendum.pdf).
- <span id="page-28-8"></span>Anwar, U., Saparov, A., Rando, J., Paleka, D., Turpin, M., Hase, P., Lubana, E. S., Jenner, E., Casper, S., Sourbut, O., Edelman, B. L., Zhang, Z., Günther, M., Korinek, A., Hernandez-Orallo, J., Hammond, L., Bigelow, E., Pan, A., Langosco, L., Korbak, T., Zhang, H., Zhong, R., hÉigeartaigh, S. O., Recchia, G., Corsi, G., Chan, A., Anderljung, M., Edwards, L., Bengio, Y., Chen, D., Albanie, S., Maharaj, T., Foerster, J., Tramer, F., He, H., Kasirzadeh, A., Choi, Y., and Krueger, D. Foundational Challenges in Assuring Alignment and Safety of Large Language Models. arXiv preprint arXiv:2404.09932 [cs], April 2024. doi[:10.48550/arXiv.2404.09932.](https://doi.org/10.48550/arXiv.2404.09932)
- <span id="page-28-7"></span>Barrett, A. M., Jackson, K., Murphy, E. R., Madkour, N., and Newman, J. Benchmark Early and Red Team Often: A Framework for Assessing and Managing Dual-Use Hazards of AI Foundation Models. arXiv preprint arXiv:2405.10986 [cs], May 2024. doi[:10.48550/arXiv.2405.10986.](https://doi.org/10.48550/arXiv.2405.10986)
- <span id="page-28-2"></span>Basdevant, A., François, C., Storchan, V., Bankston, K., Bdeir, A., Behlendorf, B., Debbah, M., Kapoor, S., LeCun, Y., Surman, M., King-Turvey, H., Lambert, N., Maffulli, S., Marda, N., Shivkumar, G., and Tunney, J. Towards a Framework for Openness in Foundation Models: Proceedings from the Columbia Convening on Openness in Artificial Intelligence. arXiv preprint arXiv:2405.15802 [cs.SE], May 2024. URL <https://arxiv.org/abs/2405.15802v1>.
- <span id="page-28-1"></span>Bengio, Y., Hinton, G., Yao, A., Song, D., Abbeel, P., Darrell, T., Harari, Y. N., Zhang, Y.-Q., Xue, L., Shalev-Shwartz, S., Hadfield, G., Clune, J., Maharaj, T., Hutter, F., Baydin, A. G., McIlraith, S., Gao, Q., Acharya, A., Krueger, D., Dragan, A., Torr, P., Russell, S., Kahneman, D., Brauner, J., and Mindermann, S. Managing extreme AI risks amid rapid progress. *Science*, 384(6698): 842–845, May 2024. doi[:10.1126/science.adn0117.](https://doi.org/10.1126/science.adn0117)
- <span id="page-28-5"></span>Bernardi, J., Mukobi, G., Greaves, H., Heim, L., and Anderljung, M. Societal Adaptation to Advanced AI. arXiv preprint arXiv:2405.10295 [cs], May 2024. doi[:10.48550/arXiv.2405.10295.](https://doi.org/10.48550/arXiv.2405.10295)
- <span id="page-28-3"></span>Bommasani, R., Hudson, D. A., Adeli, E., Altman, R., Arora, S., von Arx, S., Bernstein, M. S., Bohg, J., Bosselut, A., Brunskill, E., Brynjolfsson, E., Buch, S., Card, D., Castellon, R., Chatterji, N., Chen, A., Creel, K., Davis, J. Q., Demszky, D., Donahue, C., Doumbouya, M., Durmus, E., Ermon, S., Etchemendy, J., Ethayarajh, K., Fei-Fei, L., Finn, C., Gale, T., Gillespie, L., Goel, K., Goodman, N., Grossman, S., Guha, N., Hashimoto, T., Henderson, P., Hewitt, J., Ho, D. E., Hong, J., Hsu, K., Huang, J., Icard, T., Jain, S., Jurafsky, D., Kalluri, P., Karamcheti, S., Keeling, G., Khani, F., Khattab, O., Koh, P. W., Krass, M., Krishna, R., Kuditipudi, R., Kumar, A., Ladhak, F., Lee, M., Lee, T., Leskovec, J., Levent, I., Li, X. L., Li, X., Ma, T., Malik, A., Manning, C. D., Mirchandani, S., Mitchell, E., Munyikwa, Z., Nair, S., Narayan, A., Narayanan, D., Newman, B., Nie, A., Niebles, J. C., Nilforoshan, H., Nyarko, J., Ogut, G., Orr, L., Papadimitriou, I., Park, J. S., Piech, C., Portelance, E., Potts, C., Raghunathan, A., Reich, R., Ren, H., Rong, F., Roohani, Y., Ruiz, C., Ryan, J., Ré, C., Sadigh, D., Sagawa, S., Santhanam, K., Shih, A., Srinivasan, K., Tamkin, A., Taori, R., Thomas, A. W., Tramèr, F., Wang, R. E., Wang, W., Wu, B., Wu, J., Wu, Y., Xie, S. M., Yasunaga, M., You, J., Zaharia, M., Zhang, M., Zhang, T., Zhang, X., Zhang, Y., Zheng, L., Zhou, K., and Liang, P. On the Opportunities and Risks of Foundation Models. arXiv preprint arXiv:2108.07258 [cs], July 2022. doi[:10.48550/arXiv.2108.07258.](https://doi.org/10.48550/arXiv.2108.07258)
- <span id="page-29-8"></span>Branwen, G. The Scaling Hypothesis, May 2020. URL [https://gwern.net/scaling](https://gwern.net/scaling-hypothesis)[hypothesis](https://gwern.net/scaling-hypothesis).
- <span id="page-29-9"></span>Breitbarth, P. On large-scale data processing and GDPR compliance, August 2018. URL [https:](https://iapp.org/news/a/on-large-scale-data-processing-and-gdpr-compliance) [//iapp.org/news/a/on-large-scale-data-processing-and-gdpr-compliance](https://iapp.org/news/a/on-large-scale-data-processing-and-gdpr-compliance).
- <span id="page-29-5"></span>Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., Litwin, M., Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., and Amodei, D. Language Models are Few-Shot Learners. arXiv preprint arXiv:2005.14165 [cs], July 2020. doi[:10.48550/arXiv.2005.14165.](https://doi.org/10.48550/arXiv.2005.14165)
- <span id="page-29-6"></span>Brundage, M., Avin, S., Wang, J., Belfield, H., Krueger, G., Hadfield, G., Khlaaf, H., Yang, J., Toner, H., Fong, R., Maharaj, T., Koh, P. W., Hooker, S., Leung, J., Trask, A., Bluemke, E., Lebensold, J., O'Keefe, C., Koren, M., Ryffel, T., Rubinovitz, J. B., Besiroglu, T., Carugati, F., Clark, J., Eckersley, P., de Haas, S., Johnson, M., Laurie, B., Ingerman, A., Krawczuk, I., Askell, A., Cammarota, R., Lohn, A., Krueger, D., Stix, C., Henderson, P., Graham, L., Prunkl, C., Martin, B., Seger, E., Zilberman, N., hÉigeartaigh, S. O., Kroeger, F., Sastry, G., Kagan, R., Weller, A., Tse, B., Barnes, E., Dafoe, A., Scharre, P., Herbert-Voss, A., Rasser, M., Sodhani, S., Flynn, C., Gilbert, T. K., Dyer, L., Khan, S., Bengio, Y., and Anderljung, M. Toward Trustworthy AI Development: Mechanisms for Supporting Verifiable Claims. arXiv preprint arXiv:2004.07213 [cs], April 2020. doi[:10.48550/arXiv.2004.07213.](https://doi.org/10.48550/arXiv.2004.07213)
- <span id="page-29-7"></span>Buterin, V. My techno-optimism, November 2023. URL [https://vitalik.eth.limo/general/](https://vitalik.eth.limo/general/2023/11/27/techno_optimism.html) [2023/11/27/techno\\_optimism.html](https://vitalik.eth.limo/general/2023/11/27/techno_optimism.html).
- <span id="page-29-10"></span>Casper, S., Ezell, C., Siegmann, C., Kolt, N., Curtis, T. L., Bucknall, B., Haupt, A., Wei, K., Scheurer, J., Hobbhahn, M., Sharkey, L., Krishna, S., Von Hagen, M., Alberti, S., Chan, A., Sun, Q., Gerovitch, M., Bau, D., Tegmark, M., Krueger, D., and Hadfield-Menell, D. Black-Box Access is Insufficient for Rigorous AI Audits. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '24, pp. 2254–2272, New York, NY, USA, June 2024. Association for Computing Machinery. ISBN 9798400704505. doi[:10.1145/3630106.3659037.](https://doi.org/10.1145/3630106.3659037)
- <span id="page-29-13"></span>Cheng, H., Zhang, M., and Shi, J. Q. A Survey on Deep Neural Network Pruning-Taxonomy, Comparison, Analysis, and Recommendations. arXiv preprint arXiv:2308.06767 [cs], August 2023. doi[:10.48550/arXiv.2308.06767.](https://doi.org/10.48550/arXiv.2308.06767)
- <span id="page-29-3"></span>Davidson, T., Denain, J.-S., Villalobos, P., and Bas, G. AI capabilities can be significantly improved without expensive retraining. arXiv preprint arXiv:2312.07413 [cs.AI], December 2023. URL <https://arxiv.org/abs/2312.07413v1>.
- <span id="page-29-12"></span>Dragan, A., King, H., and Dafoe, A. Introducing the frontier safety framework, May 2024. URL [https://deepmind.google/discover/blog/introducing-the-frontier](https://deepmind.google/discover/blog/introducing-the-frontier-safety-framework/)[safety-framework/](https://deepmind.google/discover/blog/introducing-the-frontier-safety-framework/).
- <span id="page-29-0"></span>Egan, J. and Heim, L. Oversight for Frontier AI through a Know-Your-Customer Scheme for Compute Providers. arXiv preprint arXiv:2310.13625 [cs], October 2023. doi[:10.48550/arXiv.2310.13625.](https://doi.org/10.48550/arXiv.2310.13625)
- <span id="page-29-4"></span>Epoch AI. Data on Notable AI Models, June 2024a. URL [https://epochai.org/data/notable](https://epochai.org/data/notable-ai-models)[ai-models](https://epochai.org/data/notable-ai-models).
- <span id="page-29-2"></span>Epoch AI. Machine Learning Trends, June 2024b. URL <https://epochai.org/trends>.
- <span id="page-29-11"></span>Erdil, E. and Besiroglu, T. Algorithmic progress in computer vision. arXiv preprint arXiv:2212.05153 [cs], August 2023. doi[:10.48550/arXiv.2212.05153.](https://doi.org/10.48550/arXiv.2212.05153)
- <span id="page-29-14"></span>Evans, T., Parthasarathy, N., Merzic, H., and Henaff, O. J. Data curation via joint example selection further accelerates multimodal learning. arXiv preprint arXiv:2406.17711 [cs], June 2024. doi[:10.48550/arXiv.2406.17711.](https://doi.org/10.48550/arXiv.2406.17711)
- <span id="page-29-1"></span>Frontier Model Forum. Issue brief: Measuring training compute, May 2024. URL [https://www.](https://www.frontiermodelforum.org/updates/issue-brief-measuring-training-compute/) [frontiermodelforum.org/updates/issue-brief-measuring-training-compute/](https://www.frontiermodelforum.org/updates/issue-brief-measuring-training-compute/).

<span id="page-30-7"></span>Ganguli, D., Hernandez, D., Lovitt, L., Askell, A., Bai, Y., Chen, A., Conerly, T., Dassarma, N., Drain, D., Elhage, N., El Showk, S., Fort, S., Hatfield-Dodds, Z., Henighan, T., Johnston, S., Jones, A., Joseph, N., Kernian, J., Kravec, S., Mann, B., Nanda, N., Ndousse, K., Olsson, C., Amodei, D., Brown, T., Kaplan, J., McCandlish, S., Olah, C., Amodei, D., and Clark, J. Predictability and surprise in large generative models. In *Proceedings of the 2022 ACM conference on fairness, accountability, and transparency (FAccT '22)*, pp. 1747–1764, New York, NY, USA, June 2022. Association for Computing Machinery. ISBN 978-1-4503-9352-2. doi[:10.1145/3531146.3533229.](https://doi.org/10.1145/3531146.3533229)

<span id="page-30-3"></span>Goodfellow, I., Bengio, Y., and Courville, A. *Deep learning*. MIT Press, 2016.

- <span id="page-30-14"></span>Gunasekar, S., Zhang, Y., Aneja, J., Mendes, C. C. T., Del Giorno, A., Gopi, S., Javaheripi, M., Kauffmann, P., de Rosa, G., Saarikivi, O., Salim, A., Shah, S., Behl, H. S., Wang, X., Bubeck, S., Eldan, R., Kalai, A. T., Lee, Y. T., and Li, Y. Textbooks Are All You Need. arXiv preprint arXiv:2306.11644 [cs], October 2023. doi[:10.48550/arXiv.2306.11644.](https://doi.org/10.48550/arXiv.2306.11644)
- <span id="page-30-9"></span>Hayes, T., Rao, R., Akin, H., Sofroniew, N. J., Oktay, D., Lin, Z., Verkuil, R., Tran, V. Q., Deaton, J., Wiggert, M., Badkundri, R., Shafkat, I., Gong, J., Derry, A., Molina, R. S., Thomas, N., Khan, Y., Mishra, C., Kim, C., Bartie, L. J., Nemeth, M., Hsu, P. D., Sercu, T., Candido, S., and Rives, A. Simulating 500 million years of evolution with a language model, July 2024.
- <span id="page-30-4"></span>Heim, L. FLOP for Quantity, FLOP/s for Performance, April 2023. URL [https://blog.heim.](https://blog.heim.xyz/flop-for-quantity-flop-s-for-performance/) [xyz/flop-for-quantity-flop-s-for-performance/](https://blog.heim.xyz/flop-for-quantity-flop-s-for-performance/).
- <span id="page-30-1"></span>Heim, L., Fist, T., Egan, J., Huang, S., Zekany, S., Trager, R., Osborne, M., and Zilberman, N. Governing through the cloud: The intermediary role of compute providers in AI regulation. Technical report, Oxford Martin AI Governance Initiative, March 2024. URL [https://cdn.governance.ai/Governing-Through-the-Cloud\\_The-](https://cdn.governance.ai/Governing-Through-the-Cloud_The-Intermediary-Role-of-Compute-Providers-in-AI-Regulation.pdf)[Intermediary-Role-of-Compute-Providers-in-AI-Regulation.pdf](https://cdn.governance.ai/Governing-Through-the-Cloud_The-Intermediary-Role-of-Compute-Providers-in-AI-Regulation.pdf).
- <span id="page-30-11"></span>Hendrycks, D., Burns, C., Basart, S., Zou, A., Mazeika, M., Song, D., and Steinhardt, J. Measuring Massive Multitask Language Understanding. arXiv preprint arXiv:2009.03300 [cs], January 2021. doi[:10.48550/arXiv.2009.03300.](https://doi.org/10.48550/arXiv.2009.03300)
- <span id="page-30-0"></span>Hendrycks, D., Mazeika, M., and Woodside, T. An Overview of Catastrophic AI Risks. arXiv preprint arXiv:2306.12001 [cs], October 2023. doi[:10.48550/arXiv.2306.12001.](https://doi.org/10.48550/arXiv.2306.12001)
- <span id="page-30-12"></span>Hernandez, D. and Brown, T. B. Measuring the Algorithmic Efficiency of Neural Networks. arXiv preprint arXiv:2005.04305 [cs, stat], May 2020. doi[:10.48550/arXiv.2005.04305.](https://doi.org/10.48550/arXiv.2005.04305)
- <span id="page-30-5"></span>Hernandez, D., Kaplan, J., Henighan, T., and McCandlish, S. Scaling Laws for Transfer. arXiv preprint arXiv:2102.01293 [cs], February 2021. doi[:10.48550/arXiv.2102.01293.](https://doi.org/10.48550/arXiv.2102.01293)
- <span id="page-30-10"></span>Hesslow, D., Zanichelli, N., Notin, P., Poli, I., and Marks, D. RITA: a Study on Scaling Up Generative Protein Sequence Models. arXiv preprint arXiv:2205.05789 [cs, q-bio], July 2022. doi[:10.48550/arXiv.2205.05789.](https://doi.org/10.48550/arXiv.2205.05789)
- <span id="page-30-13"></span>Ho, A., Besiroglu, T., Erdil, E., Owen, D., Rahman, R., Guo, Z. C., Atkinson, D., Thompson, N., and Sevilla, J. Algorithmic progress in language models. arXiv preprint arXiv:2403.05812 [cs], March 2024. doi[:10.48550/arXiv.2403.05812.](https://doi.org/10.48550/arXiv.2403.05812)
- <span id="page-30-8"></span>Hobbhahn, M., Heim, L., and Aydos, G. Trends in machine learning hardware. Technical report, Epoch AI, November 2023. URL [https://epochai.org/blog/trends-in-machine](https://epochai.org/blog/trends-in-machine-learning-hardware)[learning-hardware](https://epochai.org/blog/trends-in-machine-learning-hardware).
- <span id="page-30-6"></span>Hoffmann, J., Borgeaud, S., Mensch, A., Buchatskaya, E., Cai, T., Rutherford, E., Casas, D. d. L., Hendricks, L. A., Welbl, J., Clark, A., Hennigan, T., Noland, E., Millican, K., Driessche, G. v. d., Damoc, B., Guy, A., Osindero, S., Simonyan, K., Elsen, E., Rae, J. W., Vinyals, O., and Sifre, L. Training Compute-Optimal Large Language Models. arXiv preprint arXiv:2203.15556 [cs], March 2022. doi[:10.48550/arXiv.2203.15556.](https://doi.org/10.48550/arXiv.2203.15556)
- <span id="page-30-2"></span>Hooker, S. On the Limitations of Compute Thresholds as a Governance Strategy. arXiv preprint arXiv:2407.05694 [cs.AI], July 2024. URL <https://arxiv.org/abs/2407.05694v1>.
- <span id="page-31-13"></span>Jones, E. What is a foundation model? Technical report, Ada Lovelace Institute, July 2023. URL [https://www.adalovelaceinstitute.org/resource/foundation-models](https://www.adalovelaceinstitute.org/resource/foundation-models-explainer/)[explainer/](https://www.adalovelaceinstitute.org/resource/foundation-models-explainer/).
- <span id="page-31-10"></span>Jones, E., Hardalupas, M., and Agnew, W. Under the radar? Technical report, Ada Lovelace Institute, July 2024. URL <https://www.adalovelaceinstitute.org/report/under-the-radar/>.
- <span id="page-31-9"></span>Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K., Bates, R., Žídek, A., Potapenko, A., Bridgland, A., Meyer, C., Kohl, S. A. A., Ballard, A. J., Cowie, A., Romera-Paredes, B., Nikolov, S., Jain, R., Adler, J., Back, T., Petersen, S., Reiman, D., Clancy, E., Zielinski, M., Steinegger, M., Pacholska, M., Berghammer, T., Bodenstein, S., Silver, D., Vinyals, O., Senior, A. W., Kavukcuoglu, K., Kohli, P., and Hassabis, D. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873):583–589, August 2021. ISSN 1476-4687. doi[:10.1038/s41586-021-03819-2.](https://doi.org/10.1038/s41586-021-03819-2)
- <span id="page-31-12"></span>Järviniemi, O. and Hubinger, E. Uncovering Deceptive Tendencies in Language Models: A Simulated Company AI Assistant. arXiv preprint arXiv:2405.01576 [cs], April 2024. doi[:10.48550/arXiv.2405.01576.](https://doi.org/10.48550/arXiv.2405.01576)
- <span id="page-31-2"></span>Kaplan, J., McCandlish, S., Henighan, T., Brown, T. B., Chess, B., Child, R., Gray, S., Radford, A., Wu, J., and Amodei, D. Scaling Laws for Neural Language Models. arXiv preprint arXiv:2001.08361 [cs, stat], January 2020. doi[:10.48550/arXiv.2001.08361.](https://doi.org/10.48550/arXiv.2001.08361)
- <span id="page-31-6"></span>Kapoor, S., Bommasani, R., Klyman, K., Longpre, S., Ramaswami, A., Cihon, P., Hopkins, A., Bankston, K., Biderman, S., Bogen, M., Chowdhury, R., Engler, A., Henderson, P., Jernite, Y., Lazar, S., Maffulli, S., Nelson, A., Pineau, J., Skowron, A., Song, D., Storchan, V., Zhang, D., Ho, D. E., Liang, P., and Narayanan, A. On the Societal Impact of Open Foundation Models. arXiv preprint arXiv:2403.07918 [cs.CY], February 2024. URL [https://arxiv.org/abs/](https://arxiv.org/abs/2403.07918v1) [2403.07918v1](https://arxiv.org/abs/2403.07918v1).
- <span id="page-31-5"></span>Koessler, L., Schuett, J., and Anderljung, M. Risk thresholds for frontier AI. arXiv preprint arXiv:2406.14713 [cs.CY], June 2024. URL <https://arxiv.org/abs/2406.14713v1>.
- <span id="page-31-3"></span>Koralus, P. and Wang-Mascianica, V. Humans in Humans Out: On GPT Converging Toward ´ Common Sense in both Success and Failure. arXiv preprint arXiv:2303.17276 [cs], March 2023. doi[:10.48550/arXiv.2303.17276.](https://doi.org/10.48550/arXiv.2303.17276)
- <span id="page-31-11"></span>Leech, G., Vazquez, J. J., Yagudin, M., Kupper, N., and Aitchison, L. Questionable practices in machine learning. arXiv preprint arXiv:2407.12220 [cs], July 2024. doi[:10.48550/arXiv.2407.12220.](https://doi.org/10.48550/arXiv.2407.12220)
- <span id="page-31-8"></span>Li, L. H., Hessel, J., Yu, Y., Ren, X., Chang, K.-W., and Choi, Y. Symbolic Chain-of-Thought Distillation: Small Models Can Also "Think" Step-by-Step. arXiv preprint arXiv:2306.14050 [cs], April 2024. doi[:10.48550/arXiv.2306.14050.](https://doi.org/10.48550/arXiv.2306.14050)
- <span id="page-31-0"></span>Linghan, Z., Jianjun, Y., Ying, C., Jingwu, Z., Xuzhi, H., Zhifeng, Z., and Xiaoben, X. Artificial Intelligence Law of the People's Republic of China (Draft for Suggestions from Scholars). Technical report, Center for Security and Emerging Technologies, March 2024. URL <https://cset.georgetown.edu/publication/china-ai-law-draft/>.
- <span id="page-31-1"></span>Lohn, A. and Musser, M. AI and Compute: How Much Longer Can Computing Power Drive Artificial Intelligence Progress? Technical report, Center for Security and Emerging Technology, January 2022. URL <https://cset.georgetown.edu/publication/ai-and-compute/>.
- <span id="page-31-4"></span>Lohn, A. J. and Jackson, K. A. Will AI Make Cyber Swords or Shields: A few mathematical models of technological progress. arXiv preprint arXiv:2207.13825 [cs], July 2022. doi[:10.48550/arXiv.2207.13825.](https://doi.org/10.48550/arXiv.2207.13825)
- <span id="page-31-7"></span>Maug, N., O'Gara, A., and Besiroglu, T. Biological Sequence Models in the Context of the AI Directives. Technical report, Epoch AI, January 2024. URL [https://epochai.org/blog/](https://epochai.org/blog/biological-sequence-models-in-the-context-of-the-ai-directives) [biological-sequence-models-in-the-context-of-the-ai-directives](https://epochai.org/blog/biological-sequence-models-in-the-context-of-the-ai-directives).
- <span id="page-32-0"></span>McKenzie, I. R., Lyzhov, A., Pieler, M., Parrish, A., Mueller, A., Prabhu, A., McLean, E., Kirtland, A., Ross, A., Liu, A., Gritsevskiy, A., Wurgaft, D., Kauffman, D., Recchia, G., Liu, J., Cavanagh, J., Weiss, M., Huang, S., Droid, T. F., Tseng, T., Korbak, T., Shen, X., Zhang, Y., Zhou, Z., Kim, N., Bowman, S. R., and Perez, E. Inverse Scaling: When Bigger Isn't Better. arXiv preprint arXiv:2306.09479 [cs], May 2024. doi[:10.48550/arXiv.2306.09479.](https://doi.org/10.48550/arXiv.2306.09479)
- <span id="page-32-6"></span>Mitchell, M., Luccioni, A. S., Lambert, N., Gerchick, M., McMillan-Major, A., Ozoani, E., Rajani, N., Thrush, T., Jernite, Y., and Kiela, D. Measuring Data. arXiv preprint arXiv:2212.05129 [cs], February 2023. doi[:10.48550/arXiv.2212.05129.](https://doi.org/10.48550/arXiv.2212.05129)
- <span id="page-32-4"></span>Mizrahi, M., Kaplan, G., Malkin, D., Dror, R., Shahaf, D., and Stanovsky, G. State of What Art? A Call for Multi-Prompt LLM Evaluation. arXiv preprint arXiv:2401.00595 [cs], May 2024. doi[:10.48550/arXiv.2401.00595.](https://doi.org/10.48550/arXiv.2401.00595)
- <span id="page-32-5"></span>OpenAI. Preparedness framework (beta). Technical report, OpenAI, December 2023. URL [https:](https://cdn.openai.com/openai-preparedness-framework-beta.pdf) [//cdn.openai.com/openai-preparedness-framework-beta.pdf](https://cdn.openai.com/openai-preparedness-framework-beta.pdf).
- <span id="page-32-2"></span>OpenAI, Achiam, J., Adler, S., Agarwal, S., Ahmad, L., Akkaya, I., Aleman, F. L., Almeida, D., Altenschmidt, J., Altman, S., Anadkat, S., Avila, R., Babuschkin, I., Balaji, S., Balcom, V., Baltescu, P., Bao, H., Bavarian, M., Belgum, J., Bello, I., Berdine, J., Bernadett-Shapiro, G., Berner, C., Bogdonoff, L., Boiko, O., Boyd, M., Brakman, A.-L., Brockman, G., Brooks, T., Brundage, M., Button, K., Cai, T., Campbell, R., Cann, A., Carey, B., Carlson, C., Carmichael, R., Chan, B., Chang, C., Chantzis, F., Chen, D., Chen, S., Chen, R., Chen, J., Chen, M., Chess, B., Cho, C., Chu, C., Chung, H. W., Cummings, D., Currier, J., Dai, Y., Decareaux, C., Degry, T., Deutsch, N., Deville, D., Dhar, A., Dohan, D., Dowling, S., Dunning, S., Ecoffet, A., Eleti, A., Eloundou, T., Farhi, D., Fedus, L., Felix, N., Fishman, S. P., Forte, J., Fulford, I., Gao, L., Georges, E., Gibson, C., Goel, V., Gogineni, T., Goh, G., Gontijo-Lopes, R., Gordon, J., Grafstein, M., Gray, S., Greene, R., Gross, J., Gu, S. S., Guo, Y., Hallacy, C., Han, J., Harris, J., He, Y., Heaton, M., Heidecke, J., Hesse, C., Hickey, A., Hickey, W., Hoeschele, P., Houghton, B., Hsu, K., Hu, S., Hu, X., Huizinga, J., Jain, S., Jain, S., Jang, J., Jiang, A., Jiang, R., Jin, H., Jin, D., Jomoto, S., Jonn, B., Jun, H., Kaftan, T., Kaiser, L., Kamali, A., Kanitscheider, I., Keskar, N. S., Khan, T., Kilpatrick, L., Kim, J. W., Kim, C., Kim, Y., Kirchner, J. H., Kiros, J., Knight, M., Kokotajlo, D., Kondraciuk, L., Kondrich, A., Konstantinidis, A., Kosic, K., Krueger, G., Kuo, V., Lampe, M., Lan, I., Lee, T., Leike, J., Leung, J., Levy, D., Li, C. M., Lim, R., Lin, M., Lin, S., Litwin, M., Lopez, T., Lowe, R., Lue, P., Makanju, A., Malfacini, K., Manning, S., Markov, T., Markovski, Y., Martin, B., Mayer, K., Mayne, A., McGrew, B., McKinney, S. M., McLeavey, C., McMillan, P., McNeil, J., Medina, D., Mehta, A., Menick, J., Metz, L., Mishchenko, A., Mishkin, P., Monaco, V., Morikawa, E., Mossing, D., Mu, T., Murati, M., Murk, O., Mély, D., Nair, A., Nakano, R., Nayak, R., Neelakantan, A., Ngo, R., Noh, H., Ouyang, L., O'Keefe, C., Pachocki, J., Paino, A., Palermo, J., Pantuliano, A., Parascandolo, G., Parish, J., Parparita, E., Passos, A., Pavlov, M., Peng, A., Perelman, A., Peres, F. d. A. B., Petrov, M., Pinto, H. P. d. O., Michael, Pokorny, Pokrass, M., Pong, V. H., Powell, T., Power, A., Power, B., Proehl, E., Puri, R., Radford, A., Rae, J., Ramesh, A., Raymond, C., Real, F., Rimbach, K., Ross, C., Rotsted, B., Roussez, H., Ryder, N., Saltarelli, M., Sanders, T., Santurkar, S., Sastry, G., Schmidt, H., Schnurr, D., Schulman, J., Selsam, D., Sheppard, K., Sherbakov, T., Shieh, J., Shoker, S., Shyam, P., Sidor, S., Sigler, E., Simens, M., Sitkin, J., Slama, K., Sohl, I., Sokolowsky, B., Song, Y., Staudacher, N., Such, F. P., Summers, N., Sutskever, I., Tang, J., Tezak, N., Thompson, M. B., Tillet, P., Tootoonchian, A., Tseng, E., Tuggle, P., Turley, N., Tworek, J., Uribe, J. F. C., Vallone, A., Vijayvergiya, A., Voss, C., Wainwright, C., Wang, J. J., Wang, A., Wang, B., Ward, J., Wei, J., Weinmann, C. J., Welihinda, A., Welinder, P., Weng, J., Weng, L., Wiethoff, M., Willner, D., Winter, C., Wolrich, S., Wong, H., Workman, L., Wu, S., Wu, J., Wu, M., Xiao, K., Xu, T., Yoo, S., Yu, K., Yuan, Q., Zaremba, W., Zellers, R., Zhang, C., Zhang, M., Zhao, S., Zheng, T., Zhuang, J., Zhuk, W., and Zoph, B. GPT-4 Technical Report. arXiv preprint arXiv:2303.08774 [cs.CL], March 2023. URL <https://arxiv.org/abs/2303.08774v6>.
- <span id="page-32-3"></span>Parrish, A., Chen, A., Nangia, N., Padmakumar, V., Phang, J., Thompson, J., Htut, P. M., and Bowman, S. R. BBQ: A Hand-Built Bias Benchmark for Question Answering. arXiv preprint arXiv:2110.08193 [cs], March 2022. doi[:10.48550/arXiv.2110.08193.](https://doi.org/10.48550/arXiv.2110.08193)
- <span id="page-32-1"></span>Perez, E., Ringer, S., Lukošiūtė, K., Nguyen, K., Chen, E., Heiner, S., Pettit, C., Olsson, C., Kundu, S., Kadavath, S., Jones, A., Chen, A., Mann, B., Israel, B., Seethor, B., McKinnon, C., Olah, C., Yan, D., Amodei, D., Amodei, D., Drain, D., Li, D., Tran-Johnson, E., Khundadze, G., Kernion,

J., Landis, J., Kerr, J., Mueller, J., Hyun, J., Landau, J., Ndousse, K., Goldberg, L., Lovitt, L., Lucas, M., Sellitto, M., Zhang, M., Kingsland, N., Elhage, N., Joseph, N., Mercado, N., DasSarma, N., Rausch, O., Larson, R., McCandlish, S., Johnston, S., Kravec, S., Showk, S. E., Lanham, T., Telleen-Lawton, T., Brown, T., Henighan, T., Hume, T., Bai, Y., Hatfield-Dodds, Z., Clark, J., Bowman, S. R., Askell, A., Grosse, R., Hernandez, D., Ganguli, D., Hubinger, E., Schiefer, N., and Kaplan, J. Discovering Language Model Behaviors with Model-Written Evaluations. arXiv preprint arXiv:2212.09251 [cs], December 2022. doi[:10.48550/arXiv.2212.09251.](https://doi.org/10.48550/arXiv.2212.09251)

- <span id="page-33-5"></span>Phuong, M., Aitchison, M., Catt, E., Cogan, S., Kaskasoli, A., Krakovna, V., Lindner, D., Rahtz, M., Assael, Y., Hodkinson, S., Howard, H., Lieberum, T., Kumar, R., Raad, M. A., Webson, A., Ho, L., Lin, S., Farquhar, S., Hutter, M., Deletang, G., Ruoss, A., El-Sayed, S., Brown, S., Dragan, A., Shah, R., Dafoe, A., and Shevlane, T. Evaluating Frontier Models for Dangerous Capabilities. arXiv preprint arXiv:2403.13793 [cs], April 2024. doi[:10.48550/arXiv.2403.13793.](https://doi.org/10.48550/arXiv.2403.13793)
- <span id="page-33-0"></span>Pilz, K. and Heim, L. Compute at Scale: A Broad Investigation into the Data Center Industry. arXiv preprint arXiv:2311.02651 [cs], November 2023. doi[:10.48550/arXiv.2311.02651.](https://doi.org/10.48550/arXiv.2311.02651)
- <span id="page-33-4"></span>Pilz, K., Heim, L., and Brown, N. Increased Compute Efficiency and the Diffusion of AI Capabilities. arXiv preprint arXiv:2311.15377 [cs.CY], November 2023. URL [https://arxiv.org/abs/](https://arxiv.org/abs/2311.15377v2) [2311.15377v2](https://arxiv.org/abs/2311.15377v2).
- <span id="page-33-2"></span>Pistillo, M., Van Arsdale, S., Heim, L., and Winter, C. The Role of Compute Thresholds for AI Governance. *George Washington Journal of Law & Technology*, forthcoming.
- <span id="page-33-3"></span>Rae, J. W., Borgeaud, S., Cai, T., Millican, K., Hoffmann, J., Song, F., Aslanides, J., Henderson, S., Ring, R., Young, S., Rutherford, E., Hennigan, T., Menick, J., Cassirer, A., Powell, R., Driessche, G. v. d., Hendricks, L. A., Rauh, M., Huang, P.-S., Glaese, A., Welbl, J., Dathathri, S., Huang, S., Uesato, J., Mellor, J., Higgins, I., Creswell, A., McAleese, N., Wu, A., Elsen, E., Jayakumar, S., Buchatskaya, E., Budden, D., Sutherland, E., Simonyan, K., Paganini, M., Sifre, L., Martens, L., Li, X. L., Kuncoro, A., Nematzadeh, A., Gribovskaya, E., Donato, D., Lazaridou, A., Mensch, A., Lespiau, J.-B., Tsimpoukelli, M., Grigorev, N., Fritz, D., Sottiaux, T., Pajarskas, M., Pohlen, T., Gong, Z., Toyama, D., d'Autume, C. d. M., Li, Y., Terzi, T., Mikulik, V., Babuschkin, I., Clark, A., Casas, D. d. L., Guy, A., Jones, C., Bradbury, J., Johnson, M., Hechtman, B., Weidinger, L., Gabriel, I., Isaac, W., Lockhart, E., Osindero, S., Rimell, L., Dyer, C., Vinyals, O., Ayoub, K., Stanway, J., Bennett, L., Hassabis, D., Kavukcuoglu, K., and Irving, G. Scaling Language Models: Methods, Analysis & Insights from Training Gopher. arXiv preprint, January 2022. doi[:10.48550/arXiv.2112.11446.](https://doi.org/10.48550/arXiv.2112.11446)
- <span id="page-33-9"></span>Ramesh, R., Khona, M., Dick, R. P., Tanaka, H., and Lubana, E. S. How capable can a transformer become? A study on synthetic, interpretable tasks. In *R0-FoMo:robustness of few-shot and zeroshot learning in large foundation models*, November 2023. URL [https://openreview.net/](https://openreview.net/forum?id=KIhFggzePM) [forum?id=KIhFggzePM](https://openreview.net/forum?id=KIhFggzePM).
- <span id="page-33-8"></span>Reuel, A., Bucknall, B., Casper, S., Fist, T., Soder, L., Aarne, O., Hammond, L., Ibrahim, L., Chan, A., Wills, P., Anderljung, M., Garfinkel, B., Heim, L., Trask, A., Mukobi, G., Schaeffer, R., Baker, M., Hooker, S., Solaiman, I., Luccioni, A. S., Rajkumar, N., Moës, N., Ladish, J., Guha, N., Newman, J., Bengio, Y., South, T., Pentland, A., Koyejo, S., Kochenderfer, M. J., and Trager, R. Open Problems in Technical AI Governance. arXiv preprint arXiv:2407.14981 [cs], July 2024. doi[:10.48550/arXiv.2407.14981.](https://doi.org/10.48550/arXiv.2407.14981)
- <span id="page-33-6"></span>Sandbrink, J. B. Artificial intelligence and biological misuse: Differentiating risks of language models and biological design tools. arXiv preprint arXiv:2306.13952 [cs], December 2023. doi[:10.48550/arXiv.2306.13952.](https://doi.org/10.48550/arXiv.2306.13952)
- <span id="page-33-1"></span>Sastry, G., Heim, L., Belfield, H., Anderljung, M., Brundage, M., Hazell, J., O'Keefe, C., Hadfield, G. K., Ngo, R., Pilz, K., Gor, G., Bluemke, E., Shoker, S., Egan, J., Trager, R. F., Avin, S., Weller, A., Bengio, Y., and Coyle, D. Computing Power and the Governance of Artificial Intelligence. arXiv preprint arXiv:2402.08797 [cs], February 2024. doi[:10.48550/arXiv.2402.08797.](https://doi.org/10.48550/arXiv.2402.08797)
- <span id="page-33-7"></span>Schuett, J., Baumoehl, C., Murray, M., and Koessler, L. How to estimate the impact and likelihood of risks from AI, forthcoming.
- <span id="page-34-12"></span>Sclar, M., Choi, Y., Tsvetkov, Y., and Suhr, A. Quantifying Language Models' Sensitivity to Spurious Features in Prompt Design or: How I learned to start worrying about prompt formatting. arXiv preprint arXiv:2310.11324 [cs], July 2024. doi[:10.48550/arXiv.2310.11324.](https://doi.org/10.48550/arXiv.2310.11324)
- <span id="page-34-10"></span>Serrano, Y., Ciudad, A., and Molina, A. Are Protein Language Models Compute Optimal? arXiv preprint arXiv:2406.07249 [cs, q-bio], June 2024. doi[:10.48550/arXiv.2406.07249.](https://doi.org/10.48550/arXiv.2406.07249)
- <span id="page-34-0"></span>Sevilla, J., Heim, L., Ho, A., Besiroglu, T., Hobbhahn, M., and Villalobos, P. Compute Trends Across Three Eras of Machine Learning. In *2022 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8, July 2022a. doi[:10.1109/IJCNN55064.2022.9891914.](https://doi.org/10.1109/IJCNN55064.2022.9891914)
- <span id="page-34-2"></span>Sevilla, J., Heim, L., Hobbhahn, M., Besiroglu, T., Ho, A., and Villalobos, P. Estimating training compute of deep learning models. Technical report, Epoch AI, January 2022b.
- <span id="page-34-15"></span>Sherry, Y. and Thompson, N. C. How fast do algorithms improve? [Point of view]. *Proceedings of the IEEE*, 109(11):1768–1777, November 2021. doi[:10.1109/JPROC.2021.3107219.](https://doi.org/10.1109/JPROC.2021.3107219)
- <span id="page-34-13"></span>Shevlane, T., Farquhar, S., Garfinkel, B., Phuong, M., Whittlestone, J., Leung, J., Kokotajlo, D., Marchal, N., Anderljung, M., Kolt, N., Ho, L., Siddarth, D., Avin, S., Hawkins, W., Kim, B., Gabriel, I., Bolina, V., Clark, J., Bengio, Y., Christiano, P., and Dafoe, A. Model evaluation for extreme risks. arXiv preprint arXiv:2305.15324 [cs], September 2023. doi[:10.48550/arXiv.2305.15324.](https://doi.org/10.48550/arXiv.2305.15324)
- <span id="page-34-9"></span>Smith, J., Rose, S., Moulange, R., and Nelson, C. How the UK Government should address the misuse risk from AI-enabled biological tools. Technical report, The Centre for Long-Term Resilience, March 2024. URL [https://www.longtermresilience.org/post/how-the](https://www.longtermresilience.org/post/how-the-uk-government-should-address-the-misuse-risk-from-ai-enabled-biological-tools)[uk-government-should-address-the-misuse-risk-from-ai-enabled-biological](https://www.longtermresilience.org/post/how-the-uk-government-should-address-the-misuse-risk-from-ai-enabled-biological-tools)[tools](https://www.longtermresilience.org/post/how-the-uk-government-should-address-the-misuse-risk-from-ai-enabled-biological-tools).
- <span id="page-34-4"></span>Sutton, R. The Bitter Lesson, March 2019. URL [http://www.incompleteideas.net/IncIdeas/](http://www.incompleteideas.net/IncIdeas/BitterLesson.html) [BitterLesson.html](http://www.incompleteideas.net/IncIdeas/BitterLesson.html).
- <span id="page-34-8"></span>U.S. Environmental Protection Agency and Office of Emergency and Remedial Response. ECO Update Ecotox Thresholds. Technical Report 540F95038, U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response, January 1996. URL [https://www.epa.gov/](https://www.epa.gov/sites/default/files/2015-09/documents/v3no2.pdf) [sites/default/files/2015-09/documents/v3no2.pdf](https://www.epa.gov/sites/default/files/2015-09/documents/v3no2.pdf).
- <span id="page-34-14"></span>van der Weij, T., Hofstätter, F., Jaffe, O., Brown, S. F., and Ward, F. R. AI Sandbagging: Language Models can Strategically Underperform on Evaluations. arXiv preprint arXiv:2406.07358 [cs], June 2024. doi[:10.48550/arXiv.2406.07358.](https://doi.org/10.48550/arXiv.2406.07358)
- <span id="page-34-5"></span>Villalobos, P. Scaling laws literature review, 2023. URL [https://epochai.org/blog/scaling](https://epochai.org/blog/scaling-laws-literature-review)[laws-literature-review](https://epochai.org/blog/scaling-laws-literature-review).
- <span id="page-34-3"></span>Villalobos, P. and Atkinson, D. Trading off compute in training and inference. Technical report, Epoch AI, July 2023. URL [https://epochai.org/blog/trading-off-compute-in-training](https://epochai.org/blog/trading-off-compute-in-training-and-inference)[and-inference](https://epochai.org/blog/trading-off-compute-in-training-and-inference).
- <span id="page-34-16"></span>Villalobos, P., Sevilla, J., Besiroglu, T., Heim, L., Ho, A., and Hobbhahn, M. Machine Learning Model Sizes and the Parameter Gap. arXiv preprint arXiv:2207.02852 [cs], July 2022. doi[:10.48550/arXiv.2207.02852.](https://doi.org/10.48550/arXiv.2207.02852)
- <span id="page-34-1"></span>Villalobos, P., Ho, A., Sevilla, J., Besiroglu, T., Heim, L., and Hobbhahn, M. Will we run out of data? Limits of LLM scaling based on human-generated data. arXiv preprint arXiv:2211.04325 [cs], June 2024. doi[:10.48550/arXiv.2211.04325.](https://doi.org/10.48550/arXiv.2211.04325)
- <span id="page-34-11"></span>Wang, A., Singh, A., Michael, J., Hill, F., Levy, O., and Bowman, S. R. GLUE: A Multi-Task Benchmark and Analysis Platform for Natural Language Understanding. arXiv preprint arXiv:1804.07461 [cs], February 2019. doi[:10.48550/arXiv.1804.07461.](https://doi.org/10.48550/arXiv.1804.07461)
- <span id="page-34-7"></span>Wei, J. Common arguments regarding emergent abilities, May 2023. URL [https://www.jasonwei.](https://www.jasonwei.net/blog/common-arguments-regarding-emergent-abilities) [net/blog/common-arguments-regarding-emergent-abilities](https://www.jasonwei.net/blog/common-arguments-regarding-emergent-abilities).
- <span id="page-34-6"></span>Wei, J., Kim, N., Tay, Y., and Le, Q. V. Inverse scaling can become U-shaped. arXiv preprint arXiv:2211.02011 [cs.CL], November 2022a. URL <https://arxiv.org/abs/2211.02011v5>.

<span id="page-35-0"></span>Wei, J., Tay, Y., Bommasani, R., Raffel, C., Zoph, B., Borgeaud, S., Yogatama, D., Bosma, M., Zhou, D., Metzler, D., Chi, E. H., Hashimoto, T., Vinyals, O., Liang, P., Dean, J., and Fedus, W. Emergent Abilities of Large Language Models. arXiv preprint arXiv:2206.07682 [cs.CL], June 2022b. URL <https://arxiv.org/abs/2206.07682v2>.

<span id="page-35-2"></span>Winter, C. and Bullock, C. The Governance Misspecification Problem, forthcoming.

<span id="page-35-1"></span>Woodside, T. Emergent Abilities in Large Language Models: An Explainer. Technical report, Center for Security and Emerging Technology, April 2024. URL [https://cset.georgetown.edu/](https://cset.georgetown.edu/article/emergent-abilities-in-large-language-models-an-explainer/) [article/emergent-abilities-in-large-language-models-an-explainer/](https://cset.georgetown.edu/article/emergent-abilities-in-large-language-models-an-explainer/).