# An Opportunistically Parallel Lambda Calculus for Performant Composition of Large Language Models

STEPHEN MELL, University of Pennsylvania, USA STEVE ZDANCEWIC, University of Pennsylvania, USA OSBERT BASTANI, University of Pennsylvania, USA

Large language models (LLMs) have shown impressive results at a wide-range of tasks. However, they have limitations, such as hallucinating facts and struggling with arithmetic. Recent work has addressed these issues with sophisticated decoding techniques. However, performant decoding, particularly for sophisticated techniques, relies crucially on parallelization and batching, which are difficult for developers.

We make two observations: 1) existing approaches are high-level domain-specific languages for gluing expensive black-box calls, but are not general or compositional; 2) LLM programs are essentially pure (all effects commute). Guided by these observations, we develop a novel, general-purpose lambda calculus for automatically parallelizing a wide-range of LLM interactions, without user intervention. The key difference versus standard lambda calculus is a novel "opportunistic" evaluation strategy, which steps independent parts of a program in parallel, dispatching black-box external calls as eagerly as possible, even while data-independent parts of the program are waiting for their own external calls to return. To maintain the simplicity of the language and to ensure uniformity of opportunistic evaluation, control-flow and looping constructs are implemented in-language, via Church encodings.

We implement this approach in a framework called Epic, embedded in—and interoperating closely with—Python. We demonstrate its versatility and performance with three case studies drawn from the machine learning literature: Tree-of-Thoughts (LLMs embedded in classic search procedures), nested tool use, and constrained decoding. Our experiments show that opportunistic evaluation offers a  $1.5\times$  to  $4.8\times$  speedup over sequential evaluation, while still allowing practitioners to write straightforward and composable programs, without any manual parallelism or batching.

Additional Key Words and Phrases: lambda calculus, evaluation strategies, call-by-value, call-by-name, Church encodings, large language models, machine learning, tool use, constrained decoding

#### 1 INTRODUCTION

Large language models (LLMs) have shown remarkable success at a diverse range of tasks in natural language processing, from question answering to machine translation and have even made significant progress in other fields, such as code generation and theorem proving.

A significant reason for their success is that they are pretrained in an unsupervised way on large-scale text corpora gathered from the Internet. As a consequence, they have learned how to perform these diverse tasks from little or no supervision, a fundamental shift from the supervised learning paradigm that dominated machine learning over the past decade. Whereas in supervised learning, the predominant task for building machine learning systems was to gather and label a large dataset, it is now possible to develop a similar system simply by adapting pretrained LLMs. For example, simply adding instructions to an LLM prompt can elicit such diverse behaviors as question answering and translation [22], likely because fragments of the tasks occur naturally in the training data.

For many tasks, even if simple instructions are insufficient, LLMs can be adapted using more sophisticated techniques. Notable examples include chain-of-thought [26] (where the LLM is asked to provide an intuitive derivation of an answer), tool use [24] (where the LLM is provided with a tool it can use to solve a problem, such as a calculator or a Wikipedia search), and constrained decoding [21] (where the LLM decoding process is modified to ensure its output conforms to a

given formal specification). These techniques can enable complex applications, such as question answering systems that generate SQL queries [25] (constrained decoding) to be run against a knowledge base, or consult Wikipedia [16, 29] (tool use).

These techniques all require writing programs that compose LLM calls in complex ways (often called "chaining"). As a result, tools have emerged to help practitioners build these systems more effectively. For instance, LangChain [10] is a widely-used embedded Python domain-specific language (DSL) for chaining LLMs both with other LLMs and with programs (e.g., taking the output of one model, fetching related documents, and feeding the documents into another model; or feeding the output of a model into a theorem prover). Guidance [1] is a Python DSL for constrained decoding from a single LLM (e.g., requiring that it respond to a question with "yes" or "no"; or requiring that its output be valid JSON). Other frameworks include SGLang [31], LMQL [6], and DSPy [15].

While these frameworks make it easy to implement chaining, the resulting programs may not be performant. LLM performance depends crucially on parallelism (running multiple models or tools simultaneously) and batching (packing multiple data-parallel computations together for execution, e.g., on a GPU). However, these frameworks cannot provide parallelism unless the program fits into a predefined workflow for which parallelism is implemented. For example, Tree-of-Thoughts [28] involves an alternation between generation of claims and self-consistency checks. Different steps can be run in parallel once their dependencies have completed running. While LangChain supports parallelism at the level of an entire chain (i.e. run the same chain in parallel on multiple independent inputs), it cannot automatically provide this kind of granular parallelism. In these cases, programmers must manually parallelize their code to achieve good performance, which is difficult and error-prone. Thus, many practical implementations simply forgo parallelism; for instance, the reference implementation of Tree-of-Thoughts contains virtually no parallelism [2].

In this work, we develop a *general-purpose* language that allows programmers to write simple sequential implementations, which can then be automatically executed in a parallel and batched way. To motivate our language design choices, we make two key observations:

- (1) Existing approaches are all high-level DSLs for composing expensive, low-level primitives.
- (2) The behavior of these programs is *essentially* pure: most effects are parallelizable, being from pure external calls (e.g. network requests to remote LLMs) or nondeterminism (e.g. random sampling), rather than from intrinsically serial operations like mutation of state or IO. (Formally, most effects commute.)

Lambda calculus is a particularly general-purpose language for composing such opaque, primitive operations. Moreover, it is highly parallelizable, because it is *confluent*—the order of evaluation of different parts of a term does not affect the final result. This property opens the door to automatic parallel execution. While there has been work on evaluating lambda terms in parallel, such as Parallel Haskell, such systems typically require user annotations to expose parallelism, pushing the burden back onto the programmer, and furthermore require *truly* pure code. LLMs are often provided as services (e.g. OpenAI's ChatGPT), so programs must make network requests to call them. Using Haskell's IOMonad sequentializes all requests, destroying opportunities for parallelism.

In contrast, we need an evaluation order that allows these benign (commuting) effects (e.g., remote LLM inference) while preserving opportunities for parallelism. To accomplish this, we introduce the notion of *opportunistic evaluation*. At each step, opportunistic evaluation inlines all function calls at the top level of the program. Ongoing tasks, representing external calls (e.g. to a remote LLM), are treated opaquely, similar to free variables. When an external call is resolved (e.g. a network call returns), its result is substituted for the opaque task. Because of confluence, the order in which tasks are resolved does not affect the final result.

This achieves a large amount of parallelism, by quickly identifying LLM calls to be made and opportunistically dispatching them. For example, suppose we have a list of known length, but where some of the elements are unknown (e.g. they are the results of outstanding LLM calls), and the program needs to loop over the list. Conventionally, an interpreter would wait until the list is concrete, and then execute the loop iterations one at a time. However, using our opportunistic strategy, it can unroll the loop (since it knows the length), and opportunistically begin executing operations that do not depend on any unknown values. If the those operations are additional LLM calls, they can be dispatched immediately, without waiting for the entire list to be known or all previous iterations to complete. As more values in the list become concrete and as early loop iterations finish, more operations in the later loop iterations can be executed. This strategy automatically uncovers parallelism in a way that dramatically improves performance.

Because this opportunistic evaluation strategy relies on stepping independent parts of the term, it is helpful to have "let-bindings" to make dependencies explicit. However, lambda calculus does not have explicit let-bindings, making the formulation of opportunistic evaluation unnecessarily complicated. Instead, we use a novel calculus,  $\lambda^O$ . Like ANF [12] or SSA [11], in  $\lambda^O$  the result of every application and abstraction is bound to an explicit name; unlike them, the semantics of  $\lambda^O$  are based on our novel opportunistic evaluation strategy.

Notably,  $\lambda^O$  eschews the use of other traditional language features such as algebraic datatypes, **match** and **if** statements, and even loop constructs. Instead, it relies on Church encodings to define these constructs in-language. This simplifies the semantics and ensures that the opportunistic evaluation is applied uniformly, thereby maximizing parallelism. In other settings, the use of such encodings might result in an unacceptable performance overhead, but for chaining LLMs—and for scripting in general—evaluation performance is bottlenecked by external calls.

To evaluate the effectiveness of our approach, we have implemented  $\lambda^O$  in a framework called EPIC (Expressive, Parallel, opportunistIc Calculus). EPIC is embedded in Python, allowing users to write  $\lambda^O$  programs using Python's syntax; furthermore, arbitrary Python functions, including mainstream machine learning frameworks, are available as external calls. Programs written in EPIC are evaluated using our opportunistic evaluation strategy, which enables automatic parallelization without any additional user effort. We use EPIC to implement several case studies that experimentally demonstrate the effectiveness of our approach; in particular, we observe performance speedups ranging from 1.5× to 4.8× depending on the task. In summary, our contributions are:

- The design of an expressive calculus  $\lambda^O$  for composing primitive operations and an *op-portunistic* evaluation strategy that automatically achieves a high degree of parallelism (Section 3).
- An implementation of  $\lambda^O$  called EPIC in Python, where  $\lambda^O$  programs can be written using Python syntax, and have the ability to call Python functions (Section 4).
- Three case-studies implemented in EPIC that demonstrate the effectiveness of our approach: (1) Tree-of-Thoughts [28], which solves logic problems by combining LLMs and search (Section 5.1); (2) tool use [24], where we give OpenAI GPT the ability to search Wikipedia and consult other LLMs (Section 5.2); and (3) constrained decoding [21], where we draw samples from a local LLM that are guaranteed to be valid JSON (Section 5.3).

#### 2 MOTIVATING EXAMPLE

We begin with a simple motivating example to demonstrate the kinds of structured LLM programs that practitioners might want to write. We then show how the example contains a large amount of latent parallelism, and finally how our approach is able to automatically exploit that parallelism.

Suppose Bob is a vegetarian and would like to vacation in diverse parts of the world. He could ask ChatGPT for "vegetarian-friendly tourist destinations", but it would then suggest locations known for their vegetarianism. (This is known as "anchoring bias", and is exhibited by both LLMs and humans.) But he's not interested in tourism about vegetarianism, he just want to be able to eat while on vacation.

Avoiding this anchoring by simply changing the LLM prompt can be difficult. Using structured interactions—rather than simple prompting—often works better. For instance, instead of asking directly for vegetarian-friendly locations, Bob could first just ask for popular destinations, and *then* filter for the ones that are vegetarian friendly. Though Bob would likely not have a database of "vegetarian-friendliness of locations", judging the vegetarian-friendliness of a location is a second task that the LLM could perform.

In Python, OpenAI's API can be used to implement the following functions:

```
def get_tourist_destinations_in(continent : str) -> List[str]: ...
def get_vegetarian_friendliness(destination : str) -> str: ...
```

Then, tourist destinations and their vegetarian-friendliness can be found with:

```
continents = ["Africa", ..., "Oceania"]
for continent in continents:
    destinations = get_tourist_destinations_in(continent)
    for destination in destinations:
        score = get_vegetarian_friendliness(destination)
        print(continent + " | " + destination + " | " + score)
```

Unfortunately, this program takes a long time to finish executing: each API call takes about 5 seconds to run, and the whole program takes about 450 seconds to run. This is particularly unfortunate, since the program exhibits a high degree of parallelism: each continent can be processed in parallel, and each destination within a continent can be processed in parallel. Taking advantage of this parallelism brings the total running time down to about 20 seconds, a more than  $20 \times$  speedup.

Recent work has introduced several DSLs for LLM programming, including LangChain [10], LlamaIndex [17], Guidance [1], SGLang [31], and DSPy [15]. However, none of them automatically parallelize this kind of loop, and some cannot handle control flow at all.

Another option is to manually parallelize this code, e.g. by manually creating new processes and passing messages between them, or with approaches like async/await. However, writing parallel code is known to be significantly more complex and error-prone. It is thus unsurprising that, in practice, machine learning practitioners often forgo parallelism. For a more detailed comparison to manual parallelization methods, see Section 6.1.

Instead, we propose using a language that is opportunistic and parallel *by default*. Users write their intent, e.g. two nested for loops, "as if" execution were sequential; then, the runtime automatically executes the program as eagerly, and with as much parallelism, as possible.

For demonstration purposes, consider in Figure 1 (a) a simplified version of our example, with only the outer loop, abridged variable and continent names, and only two continents. Because the runtime knows the value of cs, it can unfold the loop to get (b), suffixing every variable in the loop body with "\_1" or "\_2" to ensure uniqueness. Then, because the values of c\_1 and c\_2 are known, the runtime can dispatch external requests get\_ds(c\_1) and get get\_ds(c\_2), replacing them with special TASK symbols to get (c). At this point, there is no work to do until one of the external calls returns and resolves its task. Suppose the second task resolves first, giving ds\_2 a concrete value, getting (d). Even though the task ds\_1 is still pending, c\_2 and ds\_2 have concrete values, so c\_2+ds\_2 can be computed to get (e). Now that the runtime knows the argument to the second print, it can print to the user; it can also garbage-collect c\_2 and ds\_2 since they are no longer referenced, to get (f). Note that, if instead of print, there had been a different function (or

```
cs = ["Af", "Oc"]
                     c_1 = Af''
                                             c_1 = Af''
                                                                            c_1 = Af''
for c in cs:
                                             ds_1 = TASK[get_ds("Af")]
  ds = get_ds(c)
                     ds_1 = get_ds(c_1)
                                                                            ds_1 = TASK[get_ds("Af")]
  print(c+ds)
                     print(c_1+ds_1)
                                             print(c_1+ds_1)
                                                                           print(c_1+ds_1)
                     c_2 = "0c"
                                            c_2 = "0c"
                                                                           c_2 = "0c"
                                                                           ds_2 = ["Ho","Ja"]
                                            ds_2 = TASK[get_ds("Oc")]
                     ds_2 = get_ds(c_2)
                     print(c_2+ds_2)
                                            print(c_2+ds_2)
                                                                           print(c_2+ds_2)
      (a)
                             (b)
                                                        (c)
                                                                                       (d)
c_1 = Af''
                            c_1 = Af''
                                                         c_1 = Af''
ds_1 = TASK[get_ds("Af")]
                            ds_1 = TASK[get_ds("Af")] ds_1 = ["Ca"]
print(c_1+ds_1)
                            print(c_1+ds_1)
                                                         print(c_1+ds_1)
                                                                                 # print("Af[Ca]")
c_2 = "0c"
ds_2 = ["Ho", "Ja"]
                                                         # print("Oc[Ho,Ja]")
print("Oc[Ho, Ja]")
                            # print("Oc[Ho,Ja]")
                                                                                 # print("Oc[Ho, Ja]")
           (e)
                                        (f)
                                                                  (g)
                                                                                         (h)
```

Fig. 1. A conceptual demonstration of how our approach achieves automatic parallelization for the program (a), evaluating to the final result (h).

the inner loop from our initial example), the runtime could have continued to dispatch and resolve tasks independently of the outstanding task  $ds_1$ . Eventually,  $ds_1$  will resolve, to get (g). Finally,  $c_1+ds_1$  can be computed and the unused  $c_1$  and  $ds_1$  garbage collected, to get (h).

This is all possible because the code is essentially pure: if the tasks were to mutate state on a remote server, we would need to worry about the order in which they were executed. However, LLM sampling and most other inference-time machine learning operations do not mutate state. For simplicity, we assumed in our example that the execution order of the print statements did not matter. In general, the user can force print or other calls to execute in the correct order; for a more thorough treatment of printing and other sequential effects, see Section 6.3.

#### 3 LANGUAGE

This section describes the syntax and semantics of our language,  $\lambda^O$ , for defining opportunistically parallel computations. The language is a core calculus, similar in expressiveness to a pure, untyped lambda calculus. However, instead of anonymous function definitions and function calls, all function definitions and calls are explicitly named, similar to ANF [12] or SSA [11]. Moreover, unlike a traditional sequential (small-step) call-by-value or call-by-need operational semantics,  $\lambda^O$  provides parallel evaluation by inlining *all* top-level function calls *simultaneously*. This behavior, together with constructs such as conditionals and loops based on Church encodings, is sufficient to extract the parallelism implicit in the kinds of programs show in Section 2.

#### 3.1 Syntax

*Grammar.* The syntax, shown in Figure 2 (a), consists of expressions (e), bodies (b), and statements (s). The grammar is parameterized with respect to a set C of primitive values c, which in our implementation are Python objects. In the formalism, bound variable names (x, y, f, p) and hole names (a) are taken to be globally unique, a1 to avoid bureaucratic alpha-conversion and variable capture issues. Variable binding sites are prefixed with a1 in the grammar (though it is omitted in concrete syntax). Statements are separated with a semicolon (or a new line in concrete syntax).

<sup>&</sup>lt;sup>1</sup>An invariant maintained by the operational semantics.

```
e := (\$x_1, \ldots, \$x_n) : b
                                                   (expr)
                                                                              (w, f):
                                                                         1
b := s_1; \ldots; s_k; return y_1, \ldots, y_m
                                                   (body)
                                                                                                        # def
                                                                                  g := def(x):
                                                                         2
s := \$f := \operatorname{def} e
                                                   (stmt-fundef)
                                                                                       y1 := f(x)
                                                                                                        # call
                                                                                       y2 := f(y1)
                                                                                                        # call
    | y_1, \ldots, y_m := f(x_1, \ldots, x_n)
                                                   (stmt-call)
                                                                                                        # pack
                                                                                       p := (f, f)
    | p := (x_1, \ldots, x_n)
                                                   (stmt-pack)
                                                                                       return y1, p
                                                                                  z1, p1 := g(w)
                                                                                                        # call
    | (\$y_1, \ldots, \$y_n) := p
                                                   (stmt-unpack)
                                                                                  (f1, f2) := p1
                                                                                                        # unpack
    | p := prim c
                                                   (stmt-prim)
                                                                                  z2, p2 := f2(z1) # call
    | y_1, \ldots, y_n := \text{task } c_f(c_1, \ldots, c_n)
                                                  (stmt-task)
                                                                                  p3 := prim "foo" # prim
                                                                                  z3 := task exp(2) # task
                                                   (stmt-hole)
                                                                                  return z2
                               (a)
                                                                                                 (b)
```

Fig. 2. The grammar of  $\lambda^O$  (a). An example program in  $\lambda^O$  (b).

Expressions, e, are both the top-level program and the content of a function definition (stmt-def), and consist of a sequence of variable binding sites (for input parameters) and a body. As a running example, in Figure 2 (b), there are two expressions: the top-level (lines 1-12) and a function definition (lines 2-6). Bodies, b, consist of a sequence of statements and a sequence of returned variables (bodies in example: lines 2-12 and 3-6). Function definitions bind an expression to a function name variable (in example: lines 2-6). Calls are to a named function and arguments (previously bound) and bind results to output variables (in example: line 3, line 4, line 7, and line 9). Pack constructs a tuple, binding a sequence of component variables to a named tuple variable (in example: line 5). Dually, unpack extracts the components of a named tuple p, binding them to a sequence of variables (in example: line 8). Prims bind a primitive value to a variable (in example: line 10). Tasks contain a primitive function and primitive arguments and bind results to bind output variables (in example: line 11); they represent the unfulfilled calls to externally-defined services, such as LLMs. Although syntactically similar, it is useful to distinguish tasks from function calls because they are treated differently by the semantics.

Holes (h) are included in the grammar only to facilitate decomposing expressions, and are not present in ordinary programs (and are not shown in the example). For instance, to represent an expression e containing a statement  $s_1$ , we use the notation  $e = e_1[s_1]$ , where  $e_1$  is an expression with a single hole, and  $e_1[s_1]$  is the expression obtained by filling that hole with  $s_1$ . An expression e with a contiguous sequence of n statements can be written  $e = e_1[s_1; \ldots; s_n]$ . And an expression e with e sequences of statements in different parts of the expression, of lengths e through e and e written e in e and e written e in e and e are e and e are e are e are e and e are e are e and e are e are e and e are e and e are e are e are e are e and e are e and e are e are e are e and e are e are e and e are e are e are e and e are e are e are e are e are e and e are e are e are e are e are e are e and e are e are e are e and e are e and e are e are e are e are e and e are e

*Notation.* For concision, we use vector notation  $\overrightarrow{t_i}^{i\in[n]}$  to denote a sequence  $t_1, t_2, \ldots, t_n$ . When unambiguous, we elide the length and write  $\overrightarrow{t_i}^i$ . We adopt the convention that different vectors with the same index variable (e.g. i) share the same implicit length. Decompositions of terms using holes can be written concisely using vector notation:

$$e_1[s_{1,1};\ldots;s_{1,n_1}|\ldots|s_{m,1};\ldots;s_{m,n_m}] = e_1[\overrightarrow{s_{1,j_1}}^{j_1}|\ldots|\overrightarrow{s_{m,j_m}}^{j_m}] = e_1[\overrightarrow{s_{1,j_1}}^{j_1}]$$

<sup>&</sup>lt;sup>2</sup>We use the "pack" and "unpack" terminology because, in a typed version of this language, these could be generalized to subsume the introduction and elimination forms for existential types.

$$\frac{H;G,\overrightarrow{x_i^*}^i \vdash b\dashv H'}{H;G\vdash(\overrightarrow{x_i^*}^j):b\dashv H'} \text{WF-expr} \qquad \frac{\overline{H_{k-1};G_{k-1}\vdash s_k\dashv H_k;G_k^*} \qquad \overrightarrow{y_j^*}^j \in G_\ell}{H_0;G_0\vdash\overrightarrow{s_k^*}^{k\in[\ell]}; \ \text{return} \ \overrightarrow{y_j^*}^j \dashv H_\ell} \text{WF-body} \\ \frac{H;G\vdash e\dashv H'}{H;G\vdash f:= \text{def} \ e\dashv H';G,f} \text{WF-def} \qquad \frac{\overrightarrow{x_i^*}^i \in G}{H;G\vdash p:=(\overrightarrow{x_i^*}^i)\dashv H;G,p} \text{WF-prack} \\ \overline{H_i^*G\vdash p:=(\overrightarrow{x_i^*}^i)\dashv H;G,p} \text{WF-prim} \\ \overline{H_i^*G\vdash p:= \text{prim} \ c\dashv H;G,p} \text{WF-prim} \\ \overline{H_i^*G\vdash p:= \text{prim} \ c\dashv H;G,p} \text{WF-hole} \\ \frac{-;-\vdash e\dashv -}{e \text{ well-formed}} \text{WF-prog}$$

Fig. 3. The rules for syntactic well-formedness of terms in  $\lambda^O$ .

*Well-Formedness.* An expression is *well-formed* if (1) all variables are bound exactly once, before their usage, and in the same or higher scope as any usage, and (2) hole names are used linearly. These properties are defined using variable contexts G and hole contexts G, which are just sets of identifiers. We write G, X to both assert  $X \notin G$  and denote the set  $G \cup \{X\}$  (and similarly for G).

Well-formedness is defined in Figure 3. The judgment  $H; G \vdash s \dashv H'; G'$  says that the statement s has access to free variables drawn from context G, and that it (possibly) defines new variables, which are added to the resulting context G'. Similarly, if s is a hole in H, then it is consumed to produce a residual hole context  $H' \subseteq H$ . The judgment  $H; G \vdash e \dashv H'$  is similar, except that expressions cannot introduce new variable bindings, so there is no output variable context. A top-level program is well-formed if it is valid in empty contexts and has no residual holes. Note that in a well-formed program, all bound variables are distinct; thus, the set of variables defined by a statement uniquely identify that statement (like SSA). The operational semantics preserves and exploits this property.

Syntax Manipulations. For an expression e whose free variables include  $\overrightarrow{x_i}^i$ , the (parallel) substitution of variables  $\overrightarrow{y_i}^i$  for  $\overrightarrow{x_i}^i$  (written  $e\{\overrightarrow{y_i/x_i}^i\}$ ) is obtained by replacing each occurrence of  $x_i$  in e with  $y_i$ . We write  $e_1 =_{\alpha} e_2$  to mean that  $e_1$  and  $e_2$  are  $\alpha$ -equivalent (i.e. equivalent up to consistent renaming of bound variables). We define lhs(s) to be the set of variables that occur on the left-hand side of the statement s, or  $\emptyset$  if s is a hole. As noted previously, given a statement s that is not a hole, then the statement s in a (well-formed) expression e[s] is uniquely identified by the set lhs(s).

Syntactic Sugar. In this paper, we adopt several syntactic conventions to improve readability:

- (1) Variable names may be duplicated, and the new definition shadows the old one. x := f(x); x := g(x) desugars to  $x^2 := f(x)$ ;  $x^3 := g(x^2)$ .
- (2) If a statement defines a variable that is used only once, we may elide the statement and write the right-hand side of the statement at the variable occurrence.
  - z := g(f(x)) desugars to y := f(x); z := g(y)
- (3) prim annotations are elided in most contexts.
  b := a + "foo" desugars to b := (prim +)(a, prim "foo"), which desugars again to
  plus := prim +; foo := prim "foo"; b := plus(a, foo)
- (4) Tuples may be unpacked in binding positions (function parameters statement outputs). ((a, b), c) := p desugars to (ab, c) := p; (a, b) := ab

(w, f):		(w, f):	(w, f):	(w, f):
g := <b>def</b> (x):	(c1_x):	g := <b>def</b> (x):	g := <b>def</b> (x):	g := <b>def</b> (x):
y := f(x)	$c1_y := f(c1_x)$	y := f(x)	y := f(x)	y := f(x)
return y	return c1_y	return y	return y	return y
z1 := g(w)		z1 := g(w)	z1 := g(w)	z1 := g(w)
z2 := g(z1)		z2 := g(z1)		
		$c1_y := f(c1_x)$	$c1_y := f(c1_x)$	$c1_y := f(z1)$
return z2		return z2	return c1_y	<pre>return c1_y</pre>
(a) Initial, e	(b) Fresh copy of g	(c) Intermediate I	(d) Intermediate II	(e) Final, $e'$

Fig. 4. An example applying the "step-call" rule for  $e \Rightarrow_{z2} e'$ . Bold indicates changes and additions from the previous step. Strikethrough indicates deletions.

## (5) Recursive function definitions desugar as described in Section 3.6.

Semantic Equivalence. An important property is that statements can be re-ordered without impacting the semantics, as long as data dependencies are preserved. Conceptually, terms represent directed acyclic data-flow graphs, in which the use of a bound variable denotes a data-flow dependency. For instance:

b := f(a); d := g(c); e := h(b,d) and d := g(c); b := f(a); e := h(b,d) are semantically equivalent—we can permute the syntactic ordering of the bindings for b and d because their right-hand-sides do not exhibit any data dependencies. Ordinary sequential evaluation of these terms could cause them to exhibit distinct behaviors, for instance, if f diverges while g uses an external prim operation. Our operational semantics will instead evaluate them both in parallel, allowing us to consider these terms equivalent. In general, since we assume that each external call commutes with every other external call, the denotational semantics of a term is essentially the data-flow graph between its external calls.

#### 3.2 Semantics

Before presenting the full evaluation for terms, we first define a small-step semantics for individual statements that captures the essence of evaluation. The core of the semantics is function inlining: for a call to f where the definition of f is known, we replace the statement calling f with the statements in f's body. The semantics is a relation  $e[s] \Rightarrow_W e'$ , denoting that an expression of the form e[s] steps to e', where  $W = \text{lhs}(s) \subseteq \text{Var}$  identifies the statement s that is being stepped.

Before discussing the semantics formally, consider the example in Figure 4, where the expression in (a) is stepped at the call defining z2, i.e.  $e \Rightarrow_{z2} e'$ . First, a fresh copy of the function g is made, allocating fresh, globally unique names to every bound variable (but not free variables, such as f), shown in (b). Then the call statement defining z2 is replaced by the fresh statements from the copy of g, forming intermediate I (c). (Note that intermediates I and II are not well-formed expressions.) Next, the output variables bound by the call (z2) are replaced throughout intermediate I by the fresh copies (c1\_y) of the function's return values (y), forming intermediate II (d). Finally, the fresh versions of the function's parameters (c1\_x) are replaced by the call's arguments (z1), forming the result e' (e).

The semantics is given formally in Figure 5. The example in Figure 4 is an instance of the "step-call" rule, which applies when the statement being stepped is a call  $(s_c)$  where the function f being called is itself defined by another statement  $(s_f)$ . (Thus, the entire expression can be decomposed as  $e[s_f \mid s_c]$ .) Note that this rule does not apply if the function being called is a parameter, call result, task result, primitive, or tuple. Nor does it apply if there is a mismatch between the number of the

$$s_f = "f := \operatorname{def}(\overrightarrow{x_i^i}) : \overrightarrow{s_k^k}; \operatorname{return} \overrightarrow{y_j^j}" \qquad s_c = "\overrightarrow{z_j^j} := f(\overrightarrow{w_i^i})" \qquad \overrightarrow{x_i^j} : \overrightarrow{s_k^j}, \overrightarrow{y_j^j} = \operatorname{freshen}(\overrightarrow{x_i^i}, \overrightarrow{s_k^k}, \overrightarrow{y_j^j}) \\ e[s_f \mid s_c] \Rightarrow_{\overrightarrow{z_j^j}} e[s_f \mid \overrightarrow{s_k^j} \mid \{\overrightarrow{y_j/z_j}\} \{ \overrightarrow{w_i/x_i^i} \} \\ \frac{s_p = "p := (\overrightarrow{x_i^i})" \qquad s_u = "(\overrightarrow{y_i^i}) := p"}{e[s_p \mid s_u] \Rightarrow_{\overrightarrow{y_i^i}} e[s_p \mid \varnothing] \{ \overrightarrow{x_i/y_i} \}} \operatorname{step-unpack} \\ \frac{s_f = "f := \operatorname{prim} c_f" \qquad \overrightarrow{s_i} = "x_i := \operatorname{prim} c_i^{\Rightarrow i} \qquad s_c = "\overrightarrow{z_k^k} := f(\overrightarrow{x_i^i})" \qquad \overrightarrow{z_j^j} = \operatorname{freshen}(\overrightarrow{z_j^j}) \\ e[s_f \mid \overrightarrow{s_i^i} \mid s_c] \Rightarrow_{\overrightarrow{z_k^k}} e[s_f \mid \overrightarrow{s_i^i} \mid \overrightarrow{z_j^j} := \operatorname{task} c_f(\overrightarrow{c_i^i})] \{ \overrightarrow{z_j/z_j} \} \\ \frac{f \notin e}{e[f := \operatorname{def}...] \Rightarrow_f e[\varnothing]} \operatorname{step-def} \qquad \frac{p \notin e}{e[p := (...)] \Rightarrow_p e[\varnothing]} \operatorname{step-prim} \\ \frac{e \Rightarrow_W e'}{e \Rightarrow_W^i e'} \operatorname{totalstep-step} \\ \frac{\forall e' \quad e \Rightarrow_W e'}{e \Rightarrow_W^i e} \operatorname{totalstep-stuck} \\ \frac{\forall e' \quad e \Rightarrow_W e'}{e \Rightarrow_W^i e} \operatorname{totalstep-stuck} \\ \frac{\forall e' \quad e \Rightarrow_W e'}{e \Rightarrow_W^i e} \operatorname{totalstep-stuck} \\ \end{array}$$

Fig. 5. The rules for the  $e \Rightarrow_W e'$  (step) and  $e \Rightarrow_W^{\dagger} e'$  (totalstep) relations.

call arguments and the function parameters, or between the number of function return values and call outputs. Both cases are essentially runtime type errors, and could be statically prevented with a type system.

The meta-function  $\overrightarrow{x_i}^i$ ,  $\overrightarrow{s_k}^k$ ,  $\overrightarrow{y_j}^j$  = freshen( $\overrightarrow{x_i}^i$ ,  $\overrightarrow{s_k}^k$ ,  $\overrightarrow{y_j}^j$ ) makes a copy of each  $s_k$ , but with globally fresh versions of the bound variables, including  $x_i$  and the variables defined by left-hand sides of each  $s_k$ ; it also returns the new variables,  $y_j'$  that have replaced  $y_j$  in  $s_k'$ . The expression  $e[s_f \mid \overrightarrow{s_k'}^k]$  is intermediate I, which is formed by replacing the call statement  $s_c$  by the fresh function statements  $\overrightarrow{s_k}^k$ . Intermediate II is  $e[s_f \mid \overrightarrow{s_k'}^k] \{\overrightarrow{y_j'/z_j}^j\}$ , formed by substituting the fresh versions of f's return values  $(y_j')$  for the variables that bound the call's outputs  $(z_j)$ . Finally, in  $e[s_f \mid \overrightarrow{s_k'}^k] \{\overrightarrow{y_j'/z_j}^j\} \{\overrightarrow{w_i/x_i^i}^i\}$ , the call arguments  $(w_i)$  are substituted for the fresh versions of f's parameters  $(x_i')$ . Note that the order of substitutions here does matter: if the function being inlined were the identity (x1): return x1, then  $y_1' = x_1'$ , so the first substitution would replace  $z_1$  with  $z_1'$  and then the second substitution would replace  $z_1'$  with  $z_1'$  and thus replace the original  $z_1$  occurrences with  $z_1'$  being substitution in the opposite order would leave the original  $z_1$  occurrences replaced with  $z_1'$  in the result, which would be incorrect.

The "step-unpack" rule is operationally similar to "step-call", but simpler: it applies when there is an unpack of p, where p is itself known to be a pack. Stepping erases the unpack and replaces the variables  $y_i$  that it bound with the tuple components  $x_i$ .

The "step-primcall" rule applies in similar contexts to "step-call", but with the requirement that both the function f being called and all arguments  $x_i$  are themselves known to be primitives. The call statement is then replaced by a task statement containing those primitives. In order to ensure that each statement has a unique left-hand side, fresh variables  $z_i$  are allocated, and are substituted for  $z_i$  throughout. At this stage of the operational semantics, tasks are considered to be "opaque external calls"—they don't reduce in any way.

Lastly, "step-def", "step-pack", and "step-prim" serve as garbage collectors: if there are function definitions, tuple constructions, or primitives that are never used, we can simply discard them. Note

$$e_0 = (\vec{x_i^i}); \vec{s_k^i} \in [\ell]; \text{return } \vec{y_j^i}, \quad \overrightarrow{W_k} = \text{lhs}(\vec{s_k})^k \qquad \overrightarrow{e_{k-1}} \Rightarrow_{W_k}^{\uparrow} e_k \\ e_0 \mapsto e_\ell \qquad \qquad \text{reduce}$$

Fig. 6. The definition of the  $e \rightarrow e'$  (reduce) relation.

that this is correct even in the presence of effects via primitive calls, as none of these statements can trigger a primitive call on its own.

This notion of stepping is deterministic, but partial: not all statements in all terms will be able to step. Thus, we define a total version  $\Rightarrow^{\dagger}$  that mimics  $\Rightarrow$  when possible ("totalstep-step"), and otherwise relates terms to themselves ("totalstep-stuck"); in particular, for an expression of the form  $e = (\vec{x_i}^i): \vec{s_k}^k$ ; return  $\vec{y_j}^i$  and every  $s_k$ , there exists e' such that  $e \Rightarrow_{\text{lhs}(s_k)}^{\dagger} e'$ , which is not true for  $\Rightarrow_{\text{lhs}(s_k)}$ . This relation will be useful for defining reduction in the next section.

#### 3.3 Reduction

Having defined the semantics for stepping individual statements, we now define single-step opportunistic reduction for expressions,  $e \mapsto e'$ . The idea is to step all top-level statements (i.e. those not inside of a **def**) in the expression in simultaneously. Formally, this amounts to stepping all of the top-level statements in the original expression, e, one at a time using the  $\Rightarrow_W^{\dagger}$  relation. Recall that statements are uniquely identified by the variables on their left-hand side, so W specifies which statement steps. Thus, we begin by collecting the  $W_i$  for each  $s_i$  in the initial term e; then, we perform one step for each  $W_i$ . This ensures that only the "original" top-level statements are reduced; new statements created during this parallel step are not themselves reduced, allocating equal attention to all parts of the term. Figure 6 defines this relation formally. Note that the use of  $\Rightarrow_W^{\dagger}$  prevents stuck statements (e.g. due to an unresolved "task") from blocking reduction elsewhere.

Figure 7 illustrates this process. In (a), we have a term with three top-level statements (defining g, z1, and z2), and we begin by considering the first one (defining g). It is a function definition, but "step-def" does not apply, since g is referenced on lines 6 and 8. In (b), we consider the statement defining z1. It is a call to g, whose definition is known, so "step-call" applies. Finally, in (c), we

```
(w, f):
                               (w, f):
                                                         (w, f):
                                                                                     (w, f):
                                g := def (x):
    >>g := def (x):
                                                           g := def (x):
                                                                                       g := def(x):
       y := f(x)
                                 y := f(x)
                                                            y := f(x)
                                                                                         y := f(x)
        return y
                                 return y
                                                            return y
                                                                                         return y
      z1 := g(w)
                              >>z1 := g(w)
                                                            z1 := g(w)
                                                            c1_y := f(w)
                                                                                       c1_y := f(w)
8
      z2 := g(z1)
                                z2 := g(z1)
                                                         >>z2 := g(c1_y)
                                                                                 8
                                                                                       z2 := g(c1_y)
                                                                                       c2_y := f(c1_y)
9
      return z2
                                 return z2
                                                            return z2
                                                                                       return c2_y
10
                                                      10
                                                                                10
         (a) e_0
                                    (b) e_1
                                                               (c) e_2
                                                                                           (d) e_3
```

Fig. 7. An example reducing  $e_0 \mapsto e_3$ , stepping once of the three top-level statements. First,  $e_0 \Rightarrow_{\mathbf{g}}^{\dagger} e_1$  does nothing, since g occurs elsewhere in  $e_0$ , and so "step-def" does not apply. Second,  $e_1 \Rightarrow_{\mathbf{Z}1}^{\dagger} e_2$  inlines the call to g defining z1, via "step-call". Third,  $e_2 \Rightarrow_{\mathbf{Z}2}^{\dagger} e_3$  inlines the call to g defining z2, via "step-call". The >> indicates the statement  $s_k$  under consideration at each step. Bold indicates changes and additions from the previous step. Strikethrough indicates deletions.

$$\frac{e[h] = (\overrightarrow{x_{\alpha}}^{*\alpha}) \colon \overrightarrow{s_{\gamma}}^{\gamma}; h; \overrightarrow{s_{\delta}}^{\delta}; \text{ return } \overrightarrow{w_{\beta}}^{\beta}}{b \in C(c_f, \overrightarrow{c_i}^{i}) \qquad b = \overrightarrow{s_k}^{k}; \text{ return } \overrightarrow{y_j}^{j} \qquad \overrightarrow{s_k}^{k}, \overrightarrow{y_j}^{j} = \text{ freshen}(\overrightarrow{s_k}^{k}, \overrightarrow{y_j}^{j})}{e[\overrightarrow{z_j}^{j}: = \text{task } c_f(\overrightarrow{c_i}^{i})] \Rrightarrow_{\overrightarrow{z_j}^{*j}} e[\overrightarrow{s_k}^{j}] \{\overrightarrow{y_j'/z_j}^{j}\}} \text{resolve}$$

Fig. 8. The definition of the  $e \Rightarrow_W e'$  (task resolution) relation, parameterized by an external semantics C.

consider the statement defining z2. Note that we do not consider the statement defining c1\_y, since it was not present in  $e_0$ . Again "step-call" applies, yielding the final term (d).

## 3.4 Task Resolution and Program Execution

Though  $\rightarrow$  reduction can step terms, one thing is missing: tasks can be created by "step-primcall", but they can never be resolved. Because tasks are meant to model external calls, their semantics must be provided by the runtime. Let B be the set of all well-formed, closed bodies, b. We assume the existence of a relation C between nonempty sequences of primitives C and bodies B, where bodies are the results returned by calls; formally,  $C(c_f, c_1, \ldots, c_n) \subseteq B$ . Often, the returned bodies will be somewhat degenerate, simply **return** c; For example, numeric primitives +,  $\emptyset$ , 1,  $\ldots$  have deterministic semantics with relations given by, e.g.,  $C(+,1,3) = \{\text{return } 4\}$ .

On the other hand, some primitives may have nondeterministic semantics. For instance, a primitive sample for sampling, applied to a vector of probabilities,  $[p1, \ldots, pn]$ , has semantics given by, e.g.,  $C(\text{sample}, [p1, \ldots, pn]) = \{\text{return } 1, \ldots, \text{return } n\}$ . In order to handle such nondeterminism consistently, tasks are resolved only at the top level of a program, *not* inside of function definitions. If a task were resolved inside of a function definition, then every subsequent call to that function would get the same result from the nondeterministic task. By waiting until the function is called, and thus its task statements inlined to the top level, different calls to the same function can yield different nondeterministic results from their tasks.

Sometimes, the returned bodies are more complicated, particularly when a primitive call affects control flow of the program, which are implemented using first-class functions (discussed in detail in Section 3.5). For instance, we might have an **if** primitive, which converts primitive Booleans to Church-encoded Booleans:

```
C(if,false) = {return (def (case_t, case_f): return case_f)}
C(if,true) = {return (def (case_t, case_f): return case_t)}
```

In general, *task resolution* is formalized by another relation,  $e \Rrightarrow_W e'$ , defined in Figure 8. Tasks can only be resolved if they are defined by a top-level statement (the hole h in e[h] must be top-level). A task  $c_f(c_1, \ldots, c_n)$  may be resolved to any body  $b \in C(c_f, c_1, \ldots, c_n)$ . A fresh copy is made of that body, the fresh statements replace the "task" statement that was resolved, and variables are renamed (analogous to "step-call"). As with  $\Rightarrow_W$ , the W subscript uniquely identifies which primitive task is being resolved. We write  $\Rightarrow$  for the union over all such resolution step relations,  $\Rightarrow := \bigcup_W \Rightarrow_W$ .

Finally, we define *program execution* as the arbitrary interleaving of reduction and resolution steps,  $\leadsto := (\rightarrowtail \cup \Longrightarrow)^*$ . Though the exact reduction sequence is nondeterministic, the final result is unaffected by the order in which tasks are resolved. In particular, the *only* source of nondeterminism in the final result is due to nondeterminism in the external semantics C. We can characterize these properties via the following propositions (recalling that  $=_{\alpha}$  is alpha-equivalence):

 $<sup>^{3}</sup>$ Recall that this desugars to y := prim c; return y.

PROPOSITION 3.1 (DETERMINACY). If C is deterministic (i.e. whenever  $b_1, b_2 \in C(c_f, c_1, \ldots, c_n)$ , then  $b_1 =_{\alpha} b_2$ ), then  $\leadsto$  is confluent (i.e. for any well-formed e, if  $e \leadsto e_1$  and  $e \leadsto e_2$ , then there exist  $e_{12} =_{\alpha} e_{21}$  such that  $e_1 \leadsto e_{12}$  and  $e_2 \leadsto e_{21}$ ). Determinacy of  $\leadsto$  for terminating reductions is a corollary of its confluence.

PROPOSITION 3.2 (COMMUTATIVITY OF TASK RESOLUTION). For any well-formed e, if  $e \Rightarrow_{W_1} e_1$  and  $e \Rightarrow_{W_2} e_2$  and  $W_1 \neq W_2$ , then there exist  $e_{12} =_{\alpha} e_{21}$  such that  $e_1 \Rightarrow_{W_2} e_{12}$  and  $e_2 \Rightarrow_{W_1} e_{21}$ .

Informally, commutativity says that the order in which two distinct tasks are resolved doesn't matter; it is a form of local, strong confluence. Note that that Proposition 3.2 holds only for distinct tasks (i.e. when  $W_1 \neq W_2$ ). It is not true if  $W_1 = W_2$ , and the previously described sample provides the counterexample: the program  $e = \text{``()}: x := \text{sample [0.5, 0.5]}; \text{ return x''} would step nondeterministically: } e \Rightarrow_{x} \text{``()}: \text{ return 0''} \text{ and } e \Rightarrow_{x} \text{``()}: \text{ return 1''}, \text{ breaking confluence.}$  However, that is the *intended* semantics of such calls. On the other hand, as the proposition demonstrates, two separate calls, even to the same external function like sample, do commute.

# 3.5 Representing Control-Flow with Church Encodings

So far,  $\lambda^O$  lacks both explicit control-flow constructs, like "if" or "for", and support for structured data (e.g. algebraic data types for defining lists and trees). However, all of these constructs can be defined in-language using Church encodings [9]. Importantly, the choice to use such a representation is not just a matter of taste: because they uniformly represent these features as functions (i.e. suspended computations) and calls (i.e. explicit control-flow transitions), Church encodings, when combined with our opportunistic evaluation strategy, *naturally expose* opportunities for parallelism. Ordinarily, the interpretive overhead of such encodings would make them impractical for carrying out significant computations. However, in our setting, the computational bottleneck is the high latency of external tasks, so the cost of Church encodings is insignificant. Their benefit is allowing us to structure all computations as potentially parallel computations, where data-dependencies are made explicit by function application. Moreover, their use automatically preserves the determinacy and commutativity properties that  $\lambda^O$  already enjoys.

Booleans. The Church encodings of if, true, and false are as follows:

```
if := def (b, case_true, case_false): return b(case_true, case_false)
false := def (t, f): return f
true := def (t, f): return t
```

These evaluate as expected. For example:

```
c := if(false, a, b) \rightsquigarrow c := false(a, b) \rightsquigarrow c := b
```

As mentioned previously, external tasks can return these Church-Boolean values to affect the control-flow behavior of the full computation.

*Lists.* We can use a similar strategy to implement datatypes that provide good parallel evaluation behavior. For instance, the Church encoding of a list [a, b, c] can be written as:

```
mylist := (init, item):
    acc := item(init, a)
    acc := item(acc, b)
    acc := item(acc, c)
```

Here, the encoding of the list is essentially an iterator (i.e. a "fold") that is specialized to the contents of the list. When given an initial value, init, and an operation, item, which combines a list element with the running accumulated value, a call to this function returns the accumulated result of iterating over a, then b, then c.

Using this intuition, we can define operations for iterating over and constructing lists as follows:

```
iter_list := def (1, init, each): return l(init, each)
list_empty := def (init, item): return init
list_cons := def (hd, tl): return (def (init, item):
    acc := item(init, hd))
    return iter_list(tl, acc, item)
list_concat := def (l1, l2): return (def (init, item):
    acc := iter_list(l1, init, item)
    return iter_list(l2, acc, item))
```

With these lists, the operational semantics automatically unrolls loops, which is crucial for achieving parallelism. For instance, in a context with definitions for init and each, we have:

At this point, all three calls to each are at the top level, so they will be executed concurrently.

### 3.6 Unbounded Recursion

So far, every program we have described is guaranteed to terminate, including the fold operations provided by Church encodings. This precludes many practical programs: for example, sampling tokens from an LLM until a period token is sampled, which may never terminate, requires unbounded recursion. Fortunately, this form of control-flow can also easily be encoded, using fixpoint operators from the untyped lambda calculus. Here we present one based on the call-by-value fixpoint combinator [5], which we call fix. If we need a function f, conceptually of type  $I \to O$ , to be recursive, we instead define a non-recursive function,  $f_s: (I \to O) \times I \to O$ . The definition of  $f_s$  is the same as that of f, except that recursive calls are replaced with calls to the first argument (the second argument is f's input). Then,  $f:=fix(f_s)$ . Conceptually, fix has the type  $(I \to O) \times I \to O) \to (I \to O)$ , and can be defined as follows:

```
fix_s := def (fix_s, f_s): return (def (i):
    f := fix_s(fix_s, f_s)
    return f_s(f, i))
fix := def (f_s):
    return fix_s(fix_s, f_s)
```

Given some  $f_s$ , we can see how  $fix(f_s)$  unfolds recursively:

```
f := def (i):
f := fix\_s(fix\_s, f\_s)
y := f(a)
f := def (i):
f := fix\_s(fix\_s, f\_s)
return f\_s(f, i)
y := f\_s(f, a)
y := f(a)
```

Note that, under our reduction scheme, it unfolds on an as-needed basis. If f\_step does not make a recursive call with some input i, then no more unfolding will occur.

#### 4 IMPLEMENTATION

#### 4.1 Reduction

While the reduction relation  $e \mapsto e'$  is deterministic, its presentation in Section 3.3 is not algorithmic. In Epic, we implement it with a single pass over e. In particular, while scanning over the statements of e, we maintain a current context  $\Gamma$  and a current substitution  $\sigma$ , and we build up the statements of e'. The context stores, for each variable, whether it is free, and if not, which statement bound it, while the substitution stores whether a variable should be replaced by some other variable. For statements that do not step, the current substitution  $\sigma$  is applied to them before being appended to the output, and their left-hand variables are added to the context. For statements that do step, their left-hand variables are added to the substitution.

Case Study	Task	Sequential	Opportunistic	Speedup
Tree-of-Thought	Game of 24	$118.16 \pm 25.22$	$24.60 \pm 6.16$	4.8×
Tool Use	Fact Checker Panel	$14.91 \pm 2.95$	$4.66 \pm 0.72$	3.2×
Tool Use	Brainstorming	$108.87 \pm 62.70$	$33.77 \pm 14.93$	$3.2 \times$
Constrained Decoding	Constrained Sampling	$220.59 \pm 19.13$	$145.35 \pm 13.12$	1.5×

Fig. 12. Running time in seconds (mean  $\pm$  standard deviation, across 10 trials) of a sequential baseline evaluator and our opportunistic evaluator.

# 4.2 External Functions, Task Management, and Evaluation

The set *C* of primitives is the set of Python objects in the runtime—that is, syntactic "prim" statements contain references to arbitrary Python objects. Python objects referenced by "call" statements are assumed either to be ordinary Python functions or Python async coroutines.

When the reduction encounters a "step-primcall" to cf with arguments  $c1, \ldots, cn$ , first it checks whether cf is a function or a coroutine. If it is a function, the runtime immediately executes cf with its arguments, and its results are bound in e' to the result, executing synchronously and skipping task creation and resolution altogether. This is useful for simple external calls like manipulation of Python strings that would not benefit from parallelization.

When instead cf is a coroutine, it is scheduled as a task with Python's async machinery and added to a global set of unresolved tasks. The task reference is then stored in a "task" statement (which is a slight deviation from the syntax in Section 3.1, for ease of implementation). There is no syntactic facility for users to define tasks; instead, they make a "call" to a "prim", and all "task"s are created by a "step-primcall". This ensures that "task" statements only occur at the top level, and that they reference a member of the global set of unresolved tasks.

When the reduction encounters a "task" statement, it checks whether the Python async task has a value. If so, the value is assumed to be a body, and the task is resolved, replacing the "task" statement with the statements in the body.

The evaluation loop proceeds by repeatedly running the reduction. If the reduction changes the term, evaluation continues. If the term does not change, it checks whether there are any outstanding tasks. If so, it sleeps until one of them has completed and continues evaluating. If the term does not change and there are no outstanding tasks, evaluation terminates.

## 5 CASE-STUDIES

We describe three case studies that demonstrate the effectiveness of Epic: (1) Tree-of-Thought [28] (Section 5.1), (2) tool use [24] (Section 5.2), and (3) constrained decoding [21] (Section 5.3). We summarize results across all case-studies in Figure 12. All experiments were run on a machine with two Intel Xeon Gold 6148 2.40GHz 20-core/40-thread CPUs and 754 GiB of RAM.

## 5.1 Case Study: Tree-of-Thought

*Background.* Though LLMs have been successful at fuzzy, common-sense tasks, they have been shown to struggle with constrained, logical reasoning [28]. For instance, when asked to do arithmetic or solve a crossword puzzle, LLMs consistently make mistakes. As such, recent work has sought to improve their logical reasoning capabilities, often by combining them with conventional algorithms.

One recent approach in this vein, "Tree-of-Thoughts" [28] (ToT), integrates LLMs into graph search algorithms, solving constrained tasks such as arithmetic games and crossword puzzles much more successfully than prior approaches.

```
beam_search := def (search_space, scorer):
                                                            scorer_value := def (cands):
1
      (init, expand, depth) := search_space
                                                            scored := list_empty
2
      front := list_singleton(init)
                                                               each_cand := def (scored, cand):
3
                                                        21
      each_step := def (front):
                                                                score := llm_get_value(cand)
4
                                                        22
        cands := list_empty
                                                                scored := list_append(scored, (cand, score))
5
                                                        23
        each_state := def (cands, state):
                                                                return scored
6
                                                        24
          new_l := expand(state)
                                                               scored := iter_list(cands, scored, each_cand)
7
                                                        25
          each_new := def (cands, new):
                                                        26
                                                               return scored
8
            cands := list_append(cands, new)
9
                                                        27
10
            return cands
                                                        28
                                                             scorer_vote := def (cands):
          cands := iter_list(new_l, cands, each_new)
                                                        29
                                                               scores := llm_get_vote(cands)
11
          return cands
                                                        30
                                                               return list_zip(cands, scores)
12
        cands := iter_list(front, cands, each_state)
13
14
        scored := scorer(cands)
        selected := select_best_k(scored)
15
        return selected
16
      front := iter_nat(depth, front, each_step)
17
      return front
18
```

Fig. 13. An implementation in EPIC of beam search and ToT's two scoring functions.

For example, one such task is solving  $5 \times 5$  crossword puzzles: given 5 horizontal and 5 vertical natural-language hints, the goal is to fill a  $5 \times 5$  grid with letters such that each row and column forms a 5-letter word, matching its corresponding hint. As a search space, states are partially filled grids, and state expansion is the filling of a row or column with a word. Note that, while the constraints between vertical and horizontal words are challenging for the LLM, this problem cannot be solved purely logically, since the words have to match natural-language hints. As such, it is natural to consider combining LLMs with conventional search procedures.

A key observation in ToT's approach is that LLMs can be used to implement both a state expansion function (e.g. choosing a row or a column and a word to fill it with) and a state scoring function (e.g. judging whether a partially filled grid is likely to be completable).

They propose two different expansion methods. One is to ask the LLM to take one step (e.g. "The crossword so far is XYZ. What is the next word and location you would fill in?"), but sample many times from the same prompt to get multiple possibilities. The other method is to ask the LLM to generate a list of possibilities (e.g. "The crossword so far is XYZ. Please give a bulleted list of possible words and locations to fill in next."). They observe that the different approaches work well for different kinds of problems. (For crosswords, they use the latter method.)

They also propose two different scoring methods for sets of states. One is to ask the LLM to score the quality of states individually (e.g. "The crossword so far is XYZ. On a scale of 1-10, how likely is it that it can be completed?"). The other method is to ask the LLM to vote for the best one (e.g. "Consider partially completed crosswords XYZ1, ..., XYZn. Which is the most likely to be solvable? Please give an index from 1 to n.").

Their primary search algorithm is beam search<sup>4</sup>. Beam search is semi-greedy, with a parameter k that interpolates between depth-first search (k=1) and breadth-first search ( $k=\infty$ ). Beam search maintains a frontier of states of size at most k, initialized to the initial search state. At each step, it expands all nodes in the frontier to get a set of candidates (if each expansion returned n nodes, there would be  $k \cdot n$  candidates). The candidates are then scored by a scoring function, and finally a selection function reduces the set of candidates to a new frontier of size k (e.g. by taking the k candidates with the highest scores).

<sup>&</sup>lt;sup>4</sup>They refer to it as "BFS".

Our implementation. We implement beam search as shown in Figure 13. The frontier, front, is a list, initialized to contain only init. A step of search iterates over each state in the frontier and calls expand on it to get a list of new states (new\_1), which is itself iterated over, with each new state added to the set of candidates, cands. Then scorer scores them, returning a list of pairs, each containing a state and its score, and finally  $select_best_k$  chooses k of them, which become the frontier of the next step of search.

Figure 13 also shows the two different scoring functions ToT considers, one of which is expected as the scorer parameter when instantiating beam\_search. The first one, scorer\_value, operates on each candidate independently, making an LLM call, <code>llm\_get\_value</code>, which returns a numeric score. The second one, <code>scorer\_vote</code>, in contrast, sends <code>all</code> candidates to the LLM in a single query, <code>llm\_get\_vote</code>, asking it to choose which ones are most promising.

Note several opportunities for parallelism and eager task dispatch:

- (1) In beam\_search, when looping over states in the frontier (lines 6-13), the calls to expand (line 7), which involves an expensive LLM query, can be parallelized. This is because the call does not depend on cands, which comes from a previous loop iteration, but rather only on state, the current item from front.
- (2) In scorer\_value, when looping over candidates (lines 21-25), the calls to llm\_get\_value (line 21) can be similarly parallelized.
- (3) If scorer\_value is used as scorer in beam\_search, each call to each\_cand (defined on line 21) will correspond to a call to list\_append on line 9. By executing each\_cand immediately after list\_append is called, the high-latency llm\_get\_value call (line 22) can be made without waiting for the entire list of candidates to be available.

The ToT authors' implementation is completely sequential, despite the large speedup that can be achieved by exploiting these opportunities. This suggests that the parallelization options currently available constitute an excessive burden on developers and researchers. By contrast, the implementation in Epic achieves all three, with the code as-written<sup>5</sup>, and without the user explicitly considering parallelization or eagerness of dispatch at all.

Opportunity (3) is particularly tricky to exploit in a more traditional programming language like Python. Though it could be easily achieved by "inlining" the definition of scorer\_value into beam\_search—essentially just removing line 14, renaming cands to scored, and replacing line 9 with the lines 22 and 23—this would break modularity. Because scorer\_vote does not map over candidates in the way that scorer\_value does, such specialization can't be shared across the two scoring functions. Achieving the same degree of parallelism *compositionally*, without such specialization, requires significant refactoring of both the beam\_search and scorer functions: rather than scorers taking lists of candidates, they would instead take some kind of communication channel on which they could listen for new candidates. This greatly increases code complexity.

Evaluation. We implemented ToT as shown in Figure 13 and evaluated its runtime on a task from ToT's "Game of 24" domain, which consists of simple arithmetic problems. The LLM used was OpenAI's GPT-3.5-Turbo. Due to randomness in LLM sampling, different trials took different amounts of time. We compared our opportunistic evaluation to a sequential baseline evaluation. They took  $24.60 \pm 6.16$  and  $118.16 \pm 25.22$  seconds, respectively (mean  $\pm$  standard deviation, across 10 trials), for a  $4.8 \times$  speedup.

<sup>&</sup>lt;sup>5</sup>With only trivial syntactic changes, this is the code that runs in Epic.

```
wiki_lookup := def (topic):
gpt_tu := def (t_func, t_descr, conv):
  resp, t_calls := gpt(t_descr, conv)
                                                      page_name := wiki_top_search_result(topic)
  conv := list_append(conv, resp)
                                                      return wiki_page_summary(page_name)
  each_call := def (conv, call_arg):
   result := t_func(call_arg)
                                                    fact_checker := def (fact):
   conv := list_append(conv, result)
                                                      conv := ["You are a rigorous fact checker.",
                                                               "Is " + fact + " true?"]
   return conv
                                                      wiki_descr := "Get topic info from Wikipedia"
  conv := iter_list(t_calls, conv, each_call)
  used_tool := len(t_calls) >= 0
                                                      conv := gpt_tu(wiki_lookup, wiki_descr, conv)
                                                      response := conv_last_message(conv)
  case_true := def ():
    return gpt_tu(t_func, t_descr, conv)
                                                      return response
  case_false := def ():
    return conv
  return if(used_tool, case_true, case_false)
```

Fig. 14. An implementation in EPIC of a fact-checker chatbot using ChatGPT and Wikipedia tool-use.

## 5.2 Case Study: Tool Use

Background. Recent research has augmented LLMs with "tools", allowing them to look up information, run computations, and perform actions [24]. For instance, because LLMs often hallucinate facts, they benefit from being able to reference Wikipedia; since they struggle with inherently computational tasks like arithmetic, they benefit from having access to a calculator; and since they merely output text, they cannot send email on their own.

To accomplish this, LLMs are typically told, as part of their textual input, what tools they have access to, what parameters those tools expect, and to output JSON in a particular format to invoke a tool. This JSON is then interpreted as the parameters for a tool call (e.g., what topic to look up on Wikipedia, what expression to evaluate, or what email to send). The result of the tool call (e.g., text from Wikipedia, the numerical result, or whether the email was sent successfully) is then passed back to the LLM in JSON format, and the LLM then generates additional tokens.

Some LLMs are designed specifically as "chatbots", such as OpenAI's ChatGPT. Rather than merely receiving and generating a sequence of tokens, these chatbots take and generate sequences of messages, which can be from the user ("What is the capital of Alaska?"), the LLM ("The capital of Alaska is Juneau."), the system ("You are a helpful chatbot that courteously but directly answers users' questions."), or a tool response ("{"state": "AK", "capital": "Juneau"}").

Our implementation. Figure 14 (gpt\_tu) shows how to use OpenAI's API to do tool use. First, the external call gpt makes an HTTP request to their API, taking a tool description (t\_descr) and a list of conversation messages so far (conv), and returning the model's response message (resp) and a list of tool calls that the model wants to make (t\_calls). Next, we append the model's response to the conversation. Then, for each tool call, we call the tool implementation (t\_func) and append the tool result. Finally, if tool calls were made, we make a recursive call so that the model can continue generating using the tool call results. If no tool calls were made, generation is complete.

We might implement a "Wikipedia lookup" tool (Figure 14, wiki\_lookup). Since the model likely does not know the exact titles of Wikipedia articles, we can make an HTTP request to Wikipedia's search API (wiki\_top\_search\_result). If an article is found, we can then make another request to Wikipedia's summary API, which gives a short blurb about an article (wiki\_page\_summary). Finally, we can use our tool to make a fact-checker with ChatGPT (Figure 14, fact\_checker). We simply feed an appropriate prompt, a description of our Wikipedia tool, and the tool implementation wikipedia\_lookup into our gpt\_tu function.

```
fc_panel := def (fact):
    resps = ""
    each := def (resps):
        resp := fact_checker(fact)
        resps := str_cat(resps, resp, "\n")
        resps := nat_iter(5, resps, each)
    resps = "def (goal):
        conv := ["You are a creative brainstormer.",
        "How can I " + goal + "?"]
        fcp_descr := "Ask fact checkers"
        conv := gpt_tu(fcp_descr, fc_panel, conv)
        response := conv_last_message(conv)
        return response
    return response
```

Fig. 15. An implementation in Epic of nested tool-use.

We can already see an opportunity for parallelization: at each step, the LLM can make an arbitrary number of calls to Wikipedia, each of which involves two HTTP requests to Wikipedia's API. Because such network requests have significant latency, independent requests should be made in parallel.

Suppose we want to collect multiple samples from our fact-checker and concatenate them on different lines (Figure 15, fc\_panel). Now there is additional parallelism, this time between the different calls to fact\_checker. This can be taken even further by nesting tool use: we could make a "brainstormer" by instructing the LLM to be creative, but allow it to check key facts with our fc\_panel function as a tool (Figure 15, brainstormer).

Evaluation. In Epic, all of these parallelization opportunities are obtained for free, with the code as-written. Failing to exploit them has a significant performance penalty: for fc\_panel, our opportunistic evaluation takes  $4.66 \pm 0.72$  seconds, while a sequential baseline takes  $14.91 \pm 2.95$  seconds; for brainstormer, our opportunistic evaluation takes  $33.77 \pm 14.93$  seconds, while a sequential baseline takes  $108.87 \pm 62.70$  (mean  $\pm$  standard deviation, across 10 trials). In both cases, opportunistic evaluation is  $3.2 \times$  faster. The LLM used was OpenAI's GPT-3.5-Turbo.

# 5.3 Case Study: Local Sampling with Constraints

*Background.* So far, we have mostly considered the use of remote LLMs. Local LLMs, often running on GPUs, sometimes offer more flexibility, but they also present challenges.

Remote LLMs typically offer an interface that takes a string and returns one or more sampled strings, but typically do not offer fine-grained control of the decoding process. Under the hood, LLMs take a sequence of tokens and return a probability distribution over the next token. The standard decoding strategies are greedy decoding (taking the most likely token at each step), sampling (randomly sampling according to the probabilities), and beam search (using a semi-greedy approach to find high-probability token sequences).

However, having direct access to the probabilities offers additional flexibility in decoding. One important example is *constrained decoding* [21], where samples from the LLM are guaranteed to parse according to some grammar. A common instance of this is to produce data in JSON format, which can then be parsed and used programmatically for downstream tasks.

One way to implement constrained decoding is to sample as usual, except if a sampled token would cause the parser to fail, then to backtrack. In Figure 16, starting with a tokenized prompt (seq), the current token sequence is fed into the LLM to get a probability distribution (distr), the probability distribution is sampled from to get a new token (next\_tok), and this token is appended to the current token sequence (new\_seq). Now, to constrain decoding to return only valid JSON, this program rejects any sampled token that causes an incremental JSON parser to throw an error. In particular, the function json\_get\_parseable\_prefix returns the maximal prefix of its input that does not cause a parse error. The program calls this function on new\_seq to ensure that only valid JSON is produced. Finally, the processes repeats until JSON sequence is complete.

```
decode_json := def (seq):
1
                                                                  case_cont := def ():
                                                            7
     distr := llm(seq)
2
                                                                    return decode_json(json_seq)
     next_tok := sample(distr)
3
                                                                  case_done := def ():
     new_seq := list_append(seq, next_tok)
4
                                                                    return json_seq
                                                           10
     json_seq := json_get_parseable_prefix(json_seq)
5
                                                                  return if(stop, case_cont, case_done)
                                                           11
     stop := json_complete(json_seq)
```

Fig. 16. An implementation in Epic of constrained decoding.

In the local LLM setting, assuming we only have enough GPU resources to run one copy of the model, then we may not expect to get as much value out of parallelism. However, machine learning frameworks such as PyTorch [20] and TensorFlow [3] are designed to operate in a data-parallel fashion on *batches* of inputs, which can lead to dramatically better performance. While it is in principle possible to rewrite the sequential code in Figure 16 to pass a batch of inputs to the 11m call, it would result in significantly more complex code that obscures the algorithmic content.

*Our implementation.* Instead of manually batching tensors, we can *auto-batch* them, collecting related tasks from throughout the program and executing in batch, allowing the programmer to write the simple versions from Figure 16. Better still, high-latency validation operations no longer block decoding of other sequences.

With auto-batching, the external operation 11m no longer does work itself, but rather it adds its input to a queue and waits. A separate worker thread operates in cycles: in each cycle it collects all inputs in the queue, batches them together, calls the underlying LLM on the entire batch, and finally unbatches the results and notifies the waiting 11m calls. Note that auto-batching in this way is not possible in a sequential language, since the 11m calls block. Fortunately, our opportunistic evaluation identifies these parallelizable 11m operations, which can then be batched.

While existing inference servers have been designed to facilitate auto-batching [30], they require that the user manually expose parallelism in their client code to improve performance. In particular, for auto-batching to improve performance, the user must write the program in a way that makes multiple concurrent calls to the inference server. For instance, naïvely executing the program in Figure 16 would not result in any performance improvements: every inference server call would wait for a value to be returned before continuing, resulting in a batch size of one.

However, when this program is executed using our runtime, it automatically exposes parallelism across different samples in the beam, enabling the inference server to perform batching.

Evaluation. We ran the JSON decoder (Figure 16) with our opportunistic evaluation and the auto-batcher, as well as with a sequential baseline. The running times (mean  $\pm$  standard deviation, across 10 trials) were 145.35  $\pm$  13.12 (opportunistic) and 220.59  $\pm$  19.13 (sequential), for a speedup of 1.5×. The LLM used was GPT-Neo-125M [7], through HuggingFace's Transformers library [27] and PyTorch [20].

#### 6 DISCUSSION

# 6.1 Relation to Async/Await Concurrency

A common and idiomatic way to achieve parallel computation in Python is via the *async/await* pattern.<sup>6</sup> This pattern is an instance of cooperative concurrency: only one Python task runs at a

<sup>&</sup>lt;sup>6</sup>Similar facilities for asynchronous concurrency exist in many other languages, including JavaScript, Haskell, OCaml, Rust, and Swift, among others, with varying degrees of type system and compiler support. Here we focus on Python approaches because its use is prevalent in machine learning systems.

```
cs = ["Af", ..., "Oc"]
1
                                     1
                                     2
                                                                             c_ts = []
2
    c = "Af"
                                         c = "Af"
                                                                             for c in cs:
3
                                     3
    ds = await get_ds(c)
                                     4
                                         ds = await get_ds(c)
                                                                                  ds = get_ds(c)
                                                                                  c_ts.append(ds)
                                                                         5
5
                                     5
                                                                             all_ds = await gather(*c_ts)
6
                                     6
                                                                         6
                                         s_ts = []
                                     7
                                                                         7
                                                                             s_meta = []
7
                                                                             s_ts = []
                                     8
                                                                         8
8
    for d in ds:
                                     9
                                         for d in ds:
                                                                             for c, ds in zip(cs, all_ds):
9
10
                                    10
                                                                        10
                                                                                  for d in ds:
         s = await get_vf(d)
                                             s_ts.append(get_vf(d))
                                                                                      s_meta.append((c, d))
11
                                    11
                                                                        11
                                                                                      s_ts.append(get_vf(d))
12
                                    12
                                                                        12
                                                                             all_s = await gather(*s_ts)
                                         all_s = await gather(*s_ts)
13
                                    13
                                                                        13
                                         for d, s in zip(ds, all_s):
                                                                             for (c, d), s in zip(s_meta, all_s):
                                    14
14
         print(c+d+s)
                                    15
                                             print(c+d+s)
                                                                                  print(c+d+s)
15
                                                         (b)
                     (a)
                                                                                              (c)
```

Fig. 17. Several async implementations of the motivating example from Section 2. (a) and (b) implement just the outer loop, while (c) implements the entire example. (a) is a "naïve" approach, achieving no parallelism, while (b) and (c) are "staged".

time, but when a task makes a blocking call, such as a network request, it yields control to other waiting tasks, allowing multiple blocking calls to occur in parallel.

Tasks are specified with "coroutines" (async def my\_coroutine(a : A) -> B: ...). When a coroutine taking an A and returning a B is called, rather than returning a plain value (B), it instead returns an "awaitable" reference Awaitable[B], which is similar to a "promise" or a "future". Inside coroutines, await awaitable\_b can be used to convert an Awaitable[B] into a B, blocking (and yielding control to other tasks) if the value is not yet available. Revisiting the example in Section 2, assume the following are implemented with external LLM calls:

```
async def get_ds(c : str) -> List[str]: ...
async def get_vf(d : str) -> str: ...
```

We begin by simplifying the example to have only the inner loop, writing it with async in Figure 17 (a). Unfortunately, this use of async actually achieves no parallelism: in the loop, we wait until we have s before continuing to the next iteration.

To actually exploit the parallelism in this program, we need to make more invasive changes, rewriting the program into two loops, in Figure 17 (b): the first loop (lines 9-11) dispatches the score requests for each destination, then all requests are awaited simultaneously via gather, and then the second loop (lines 14-15) prints the results.

While the amount of additional code and added complexity may not seem too bad, this solution works only for a single loop. Implementing the original example with two nested loops requires yet more invasive changes. This version, in Figure 17 (c), essentially processes the results in two stages: the first stage gets the destinations for each continent, in parallel (lines 1-6); the second stage gets the scores for all destinations, in parallel (lines 7-13).

The original, simple structure of two nested **for** loops has become four **for** loops, with several pieces of intermediate state for tracking tasks and associated metadata. Moreover, although the overall runtime is improved dramatically (this version is 20× faster), the *latency* (i.e. the time from program start until the first output), is *increased* by about 1.5×. Latency has been shown to be important for end-user experience, which is why ChatGPT's interface streams output to the user.

The added latency arises because this version of the code waits until it has destinations for *all* the continents before requesting *any* score, and then waits for *all* the scores before printing

Approach	Latency	Median	Total
Naïve	$15 \pm 3$	$247 \pm 33$	$462 \pm 52$
Staged	$23 \pm 3$	$23 \pm 3$	$23 \pm 3$
Pipelined	$10 \pm 1$	$14 \pm 1$	$22 \pm 3$

Fig. 18. Running time (seconds, mean ± standard deviation, across 30 trials) for several async implementations of the motivating example from Section 2, with both loops. "Latency" is the time until the first result is printed. "Total" is the time until the final result is printed. "Median" is the time until 50% of results are printed.

```
1
   ():
                                                       case_heads := def ():
                                              10
     past := []
2
                                              11
                                                       return (past, cur)
     cur := "Tell a story."
3
                                                       (past, cur) := if(c, case_heads, case_tails)
                                              12
     each := def ((past, cur)):
                                                       resp := gpt(cur)
                                              13
      c := coin_flip()
                                              14
                                                       cur := str_cat(cur, resp)
       case_tails := def ():
6
                                              15
                                                       return (past, cur)
7
         past := list_append(past, cur)
                                                     (past, cur) := iter_nat(10, each, (past, cur))
                                              16
         cur := "Tell a story."
8
                                              17
                                                    return list_append(past, cur)
         return (past, cur)
```

Fig. 19. Example of dynamic data dependencies that can be handled by Epic.

anything. To improve latency, ideally, as soon as a destination is returned from the first loop, it would be pipelined into the scores request, and, likewise, as soon as any score is available, it would be printed. Comparing this "pipelined" approach to the "staged" and "naïve" approaches, the pipelined approach outperforms the naïve approach on latency (1.5×) while being at least as fast as the staged approach in total running time (see Figure 18).

Unfortunately, implementing the pipelined approach requires still more invasive changes to the code, and requires us to break the async abstraction, manually maintaining sets of finished and unfinished tasks. (For an implementation, see Appendix A.) This dramatically increases the code complexity and programmer burden, when all we wanted conceptually was two nested loops.

Given the added complexity of parallelizing their code, it is unsurprising that programmers often do not do so, instead opting for simple, synchronous, and blocking approaches. PyTorch [20] and TensorFlow [3], the two most popular neural network frameworks, do not even support async, instead relying on multiprocessing and manual message passing. In this example, the straightforward, "naïve" implementation of nested loops in EPIC automatically provides the performance of "pipelined", including total running time and latency, without any manual effort by the user.

# 6.2 Handling Dynamic Data-Dependencies

Consider the example in Figure 19. Here, each loop iteration calls gpt, a high-latency remote LLM. However, whether these calls depend on the previous loop iteration or are passed the constant "Tell a story." is determined randomly, by coin\_flip.

This example is hard for many existing parallelization strategies to handle: static approaches will not work, since the dependencies are not known until execution time; async/await requires manual task management, similar to what we saw in the previous example; and fork/join parallelism is ineffective, since not all loop iterations are independent.

However, this scenario poses no issue for opportunistic evaluation: the number of iterations is known, so the loop can be unrolled. The coin flips are all independent, and so can be evaluated in parallel. At that point, each conditional can also be resolved in parallel. Finally, the data-dependencies

between gpt calls are known, as a flat data-flow graph, and calls to gpt can be evaluated in as parallel a manner as that data-flow graph allows.

#### 6.3 Non-Commutative Effects

One of our key observations is that, for many effects in LLM programming, the order of evaluation does not matter—the effects commute. However, some effects, such as printing and file IO, do not commute. This can partially be addressed by EPIC already: rather than print having conceptual type  $Str \rightarrow 1$ , data-dependencies can be introduced between print calls by changing its type to be Output  $\times$   $Str \rightarrow$  Output and threading an Output object between calls. For example, in o := print(o, "foo"); o := print(o, "bar"), EPIC sequentializes the print calls. This idiom could benefit from the addition of linearity to EPIC, in order to rule out partial orderings for effects like print, e.g. o1 := print(o0, "foo"); o2 := print(o0, "bar"). However, we leave this for future work.

#### 6.4 Relation to Lambda Calculus

Our calculus,  $\lambda^O$ , has advantages over the standard untyped lambda calculus: defining opportunistic evaluation in lambda calculus is tricky, since it lacks explicit let-bindings; and the normal forms of lambda calculus do not allow sharing in the way that Epic's do ("g(f(x),f(x))" vs "y := f(x); g(y,y)"). However, it's easy to see that programs in untyped lambda calculus can be translated to programs in  $\lambda^O$ , as shown in Figure 20; here,  $[-]]^{top}$  is the top-level translation of a closed lambda term into a  $\lambda^O$  term. Most of the work is done by [-]], which transforms a lambda term into a list of statements (the computation) and a variable (the name of the result). As with ANF or SSA forms, the translation simply generates fresh names for each of the intermediate steps of computation. Note that this translation does not necessarily preserve the language semantics; the opportunistic parallel semantics we use here would do more reduction than is typical in either call-by-value or call-by-name evaluation strategies for lambda terms (but it also does not do full reduction, which evaluates under lambda abstractions). To preserve the operational semantics, we conjecture that this translation could be composed with a CPS translation, which would make the order of evaluation explicit and independent of the target evaluation order.

#### 7 RELATED WORK

*DSLs for LLM Programming*. Recent work has developed several Python DSLs for different aspects of LLM programming. Most of these techniques are orthogonal to our language and execution model and could be integrated in future work.

LangChain [10] allows users to build "chains" of LLMs and other components, including arbitrary functions, analogous to pipelines in shell scripts. However, it is unable to express more complex use-cases, such as Tree-of-Thoughts [28], which was recently added to LangChain as a primitive

Fig. 20. Translation of untyped lambda calculus into  $\lambda^{O}$ .

component. LangChain has some support for parallel execution and plans to support Python's async in the future.

LlamaIndex [17] is a library to help users structure data, such as internal company documents, for provision to LLMs for use in tasks like retrieval-augmented generation [16], a form of tool-use.

SGLang [31], Guidance [1], and LMQL [6] are Python embedded DSLs that facilitate advanced prompting, interleaving interactions with a LLMs with arbitrary Python constructs. However, they are unable to express more complex use-cases, such as Tree-of-Thoughts. SGLang supports explicit fork/join parallelism. SGLang has a compiler mode that builds a data-flow graph, but it does not support control-flow. SGLang's interpreter mode, Guidance, and LMQL all rely on Python for control-flow and do not do automatic parallelization.

Galois [23] proposes treating LLMs as databases and querying them with SQL. DSPy [15] is a language for specifying prompting strategies, along with a framework for fine-tuning models and learning prompts to optimize a dataset performance metric.

Languages for Parallel Computation. Parallel Haskell [18] leverages purity for efficient parallelization. However, it requires manual user annotations for "evaluation strategies", and it requires that the code be truly pure. Effects, even commuting ones, must be serialized via the IOMonad. Concurrent Haskell [14] supports effects, but requires the user to manually fork and synchronize processes.

NESL [8] is a data-parallel language that pioneered nesting of parallel constructs. However, it still requires that the user manually introduce parallelism via the "apply-to-each" operator.

Sequent Calculi. Our language draws inspiration from Ideograph [19], which represents programs directly as higher-order data-flow graphs and has a similar parallel evaluation strategy. Our "step-call" rule is closely related to sequent calculi for linear logic [13], in particularly the "adsorption" rule from the Dyadic System  $\Sigma_2$  [4].

#### 8 CONCLUSION

We present a novel language for writing programs that compose LLMs in a way that automatically exposes parallelism. Our language exploits the fact that typical LLM calls are essentially pure, evaluating under a novel strategy called opportunistic evaluation. In three case studies, we demonstrate how our framework can be used to automatically parallelize sequential implementations of a number of popular paradigms for chaining LLMs. Our experimental results demonstrate that our framework automatically produces speedups of between 1.5× and 4.8×. Our work demonstrates the significant opportunities for designing programming languages for writing software that incorporates LLMs.

#### REFERENCES

- [1] 2022. Guidance. https://github.com/guidance-ai/guidance
- $[2]\ \ 2023.\ \textit{Official Repo of Tree of Thoughts}.\ \ \text{https://github.com/princeton-nlp/tree-of-thought-llm}$
- [3] Martín Abadi. 2016. TensorFlow: learning functions at scale. In *Proceedings of the 21st ACM SIGPLAN international conference on functional programming*. 1–1.
- [4] Jean-Marc Andreoli. 1992. Logic programming with focusing proofs in linear logic. *Journal of logic and computation* 2, 3 (1992), 297–347.
- [5] Hendrik Pieter Barendregt. 1985. *The lambda calculus its syntax and semantics*. Studies in logic and the foundations of mathematics, Vol. 103. North-Holland.
- [6] Luca Beurer-Kellner, Marc Fischer, and Martin Vechev. 2023. Prompting Is Programming: A Query Language for Large Language Models. Proc. ACM Program. Lang. 7, PLDI, Article 186 (jun 2023), 24 pages. https://doi.org/10.1145/3591300
- [7] Sid Black, Gao Leo, Phil Wang, Connor Leahy, and Stella Biderman. 2021. GPT-Neo: Large Scale Autoregressive Language Modeling with Mesh-Tensorflow. https://doi.org/10.5281/zenodo.5297715 If you use this software, please cite it using these metadata..

- [8] Guy E Blelloch. 1995. NESL: A nested data-parallel language (version 3.1). Citeseer.
- [9] Corrado Böhm and Alessandro Berarducci. 1985. Automatic synthesis of typed λ-programs on term algebras. *Theoretical Computer Science* 39 (1985), 135–154.
- [10] Harrison Chase. 2022. LangChain. https://github.com/langchain-ai/langchain
- [11] Ron Cytron, Jeanne Ferrante, Barry K. Rosen, Mark N. Wegman, and F. Kenneth Zadeck. 1991. Efficiently Computing Static Single Assignment Form and the Control Dependence Graph. ACM Trans. Program. Lang. Syst. 13, 4 (Oct. 1991), 451–490. https://doi.org/10.1145/115372.115320
- [12] Cormac Flanagan, Amr Sabry, Bruce F Duba, and Matthias Felleisen. 1993. The Essence of Compiling with Continuations. In *Proceedings of the ACM SIGPLAN 1993 conference on Programming Language Design and Implementation (PLDI)*. 237–247.
- [13] Jean-Yves Girard. 1987. Linear logic. Theoretical computer science 50, 1 (1987), 1–101.
- [14] Simon Peyton Jones, Andrew Gordon, and Sigbjorn Finne. 1996. Concurrent haskell. In POPL, Vol. 96. 295-308.
- [15] Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan, Saiful Haq, Ashutosh Sharma, Thomas T Joshi, Hanna Moazam, et al. 2023. Dspy: Compiling declarative language model calls into self-improving pipelines. arXiv preprint arXiv:2310.03714 (2023).
- [16] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. Advances in Neural Information Processing Systems 33 (2020), 9459–9474.
- [17] Jerry Liu. 2022. LlamaIndex. https://doi.org/10.5281/zenodo.1234
- [18] Simon Marlow. 2013. Parallel and concurrent programming in Haskell: Techniques for multicore and multithreaded programming. "O'Reilly Media, Inc.".
- [19] Stephen Mell, Osbert Bastani, and Steve Zdancewic. 2023. Ideograph: A Language for Expressing and Manipulating Structured Data. Electronic Proceedings in Theoretical Computer Science 377 (April 2023), 65–84. https://doi.org/10. 4204/eptcs.377.4
- [20] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. Pytorch: An imperative style, high-performance deep learning library. Advances in neural information processing systems 32 (2019).
- [21] Gabriel Poesia, Oleksandr Polozov, Vu Le, Ashish Tiwari, Gustavo Soares, Christopher Meek, and Sumit Gulwani. 2022. Synchromesh: Reliable code generation from pre-trained language models. *arXiv preprint arXiv:2201.11227* (2022).
- [22] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog* 1, 8 (2019), 9.
- [23] Mohammed Saeed, Nicola De Cao, and Paolo Papotti. 2023. Querying large language models with SQL. arXiv preprint arXiv:2304.00472 (2023).
- [24] Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2024. Toolformer: Language models can teach themselves to use tools. Advances in Neural Information Processing Systems 36 (2024).
- [25] Torsten Scholak, Nathan Schucher, and Dzmitry Bahdanau. 2021. PICARD: Parsing incrementally for constrained auto-regressive decoding from language models. arXiv preprint arXiv:2109.05093 (2021).
- [26] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. Advances in neural information processing systems 35 (2022), 24824–24837.
- [27] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Perric Cistac, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. 2020. Transformers: State-of-the-Art Natural Language Processing. Association for Computational Linguistics, 38–45. https://www.aclweb.org/anthology/2020.emnlp-demos.6
- [28] Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2024. Tree of thoughts: Deliberate problem solving with large language models. *Advances in Neural Information Processing Systems* 36 (2024).
- [29] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. arXiv preprint arXiv:2210.03629 (2022).
- [30] Gyeong-In Yu, Joo Seong Jeong, Geon-Woo Kim, Soojeong Kim, and Byung-Gon Chun. 2022. Orca: A distributed serving system for {Transformer-Based} generative models. In 16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22). 521–538.
- [31] Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Jeff Huang, Chuyue Sun, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E Gonzalez, et al. 2023. Efficiently programming large language models using sglang. arXiv preprint arXiv:2312.07104 (2023).

#### A PIPELINED ASYNC IMPLEMENTATION OF MOTIVATING EXAMPLE

```
continent = "Africa"
destinations = await tourist_destinations_in(continent)
score_tasks = []
for destination in destinations:
    task = asyncio.create_task(vegetarian_friendliness(destination))
    score_tasks.append(task)

tasks_pending = list(score_tasks)
while len(tasks_pending) > 0:
    tasks_done, tasks_pending = await asyncio.wait(
        tasks_pending, return_when = asyncio.FIRST_COMPLETED)
    for task_done in tasks_done:
        destination = destinations[score_tasks.index(task_done)]
        score = await task_done
        print(continent + " | " + destination + " | " + score)
```

Fig. 21. Fully pipelined async implementation of the motivating example in Python, with just the outer loop. Described in Section 6.1.

```
continents = ["Africa", ..., "Oceania"]
continent_tasks = []
for continent in continents:
    task = asyncio.create_task(tourist_destinations_in(continent))
    continent_tasks.append(task)
tasks_pending = list(continent_tasks)
score meta = \Gamma
score_tasks = []
while len(tasks_pending) > 0:
    tasks_done, tasks_remaining = await asyncio.wait(tasks_pending,
        return_when = asyncio.FIRST_COMPLETED)
    tasks_pending = list(tasks_remaining)
    for task_done in tasks_done:
        if task_done in continent_tasks:
            continent = continents[continent_tasks.index(task_done)]
            destinations = await task_done
            for destination in destinations:
                new_task = asyncio.create_task(
                    vegetarian_friendliness(destination))
                score_meta.append((continent, destination))
                score_tasks.append(new_task)
                tasks_pending.append(new_task)
        elif task_done in score_tasks:
            continent, destination = score_meta[score_tasks.index(task_done)]
            score = await task_done
            print(continent + " | " + destination + " | " + score)
```

Fig. 22. Fully pipelined async implementation of the motivating example in Python, with both loops. Described in Section 6.1.