Qiong Nan<sup>1,2</sup>, Qiang Sheng<sup>1</sup>, Juan Cao<sup>1,2</sup>, Beizhe Hu<sup>1,2</sup>, Danding Wang<sup>1</sup>, Jintao Li<sup>1</sup>

<sup>1</sup>Institute of Computing Technology, Chinese Academy of Sciences

<sup>2</sup>University of Chinese Academy of Sciences

{nanqiong19z,shengqiang18z,caojuan,hubeizhe21s,wangdanding,jtli}@ict.ac.cn

## ABSTRACT

Fake news detection plays a crucial role in protecting social media users and maintaining a healthy news ecosystem. Among existing works, comment-based fake news detection methods are empirically shown as promising because comments could reflect users' opinions, stances, and emotions and deepen models' understanding of fake news. Unfortunately, due to exposure bias and users' different willingness to comment, it is not easy to obtain diverse comments in reality, especially for early detection scenarios. Without obtaining the comments from the "silent" users, the perceived opinions may be incomplete, subsequently affecting news veracity judgment. In this paper, we explore the possibility of finding an alternative source of comments to guarantee the availability of diverse comments, especially those from silent users. Specifically, we propose to adopt large language models (LLMs) as a user simulator and comment generator, and design GenFEND, a generated feedback-enhanced detection framework, which generates comments by prompting LLMs with diverse user profiles and aggregating generated comments from multiple subpopulation groups. Experiments demonstrate the effectiveness of GenFEND and further analysis shows that the generated comments cover more diverse users and could even be more effective than actual comments.

## CCS CONCEPTS

Computing methodologies → Natural language processing;
 Human-centered computing → Social media.

## **KEYWORDS**

Fake News Detection, Large Language Models, Synthetic Data, Comment Generation

## **1** INTRODUCTION

The rapid spread of fake news on social media platforms can lead to substantial losses within a short period [45, 48]. For example, a fake news post reporting an explosion in the White House triggered panic and caused the Dow Jones index to fall 100 points in just two minutes [9]. More seriously, the malicious use of large language models (LLMs) facilitates fake news creation and may bring larger risks in the near future [3, 5, 17, 59]. Although human countermeasures like establishing reporting mechanisms [58] and conducting fact-checking [49] have been adopted, their inevitable lagged effect makes it hard to achieve the ultimate goal of moderating fake news as early as possible. Therefore, recent studies have focused on automatic fake news detection.

Existing fake news detection methods generally rely on analyzing news content or introducing external resources as references [41].




Figure 1: Existing fake news detection methods rely on (a) the news content itself and (b) limited comments from actively commenting users only. Unlike (a) and (b), our GenFEND uses (c) diverse comments generated by large language models from both potentially active and silent simulated users.

Among the resources, comments from social media users play a valuable role and have been shown promising helpfulness [31]. The unique advantage of comment-based methods can be attributed to the support of crowd intelligence, which reflects various users' understanding of news, such as opinions [66], stances [29], and emotions [71]. By perceiving and aggregating the patterns behind crowd signals, detectors would differentiate real and fake news more easily. Unfortunately, maintaining the quantity and quality of user comments is hard in real-world scenarios due to the following reasons: (1) At the early stage of news dissemination, it is unlikely to attract a wide audience to comment. (2) Even if after a period of dissemination, the available comments only reflect opinions from partial, active user groups that are willing to make comments, due to the intrinsic commenting unwillingness of specific users. For example, comments from users with higher degrees and professional knowledge may help detect misleading scientific news, but such users may rarely view and comment on suspicious posts. (3) Moreover, the distribution of available comments is often unstable due to the exposure bias influenced by factors like issued time, recommender system preferences, etc., making it harder for detectors to mine clear, stable patterns. For example, a memorized pattern may be ineffective due to formally active users' inactivation and key comments missing. Therefore, with limited comments, existing comment-based detectors can only have a limited observation and biased understanding of crowd feedback, which ultimately risks the detection performance. It is valuable to find a surrogate of comments from real users that comprehensively reflects crowd intelligence and facilitates a deep news understanding in fake news detection.

In this paper, we leverage comments generated from large language models (LLMs) as an alternative. LLMs like ChatGPT possess impressive capabilities in natural language understanding and generation [12, 47, 54, 57]. Moreover, LLMs can simulate user behaviors following specific instructions in various applications, such as dialogue [22, 36, 62] and recommender systems [16]. Along this line, we prompt LLMs to generate diverse comments by roleplaying different users, as depicted in Figure 1. To use generated comments for detection enhancement, we address two key challenges: (1) How to generate diverse comments using LLMs? (2) How to utilize the comments effectively?

To tackle these challenges, we propose a Generated Feedback Enhanced Detection (GenFEND) framework, which enhances fake news detection performance regardless of the availability of actual comments by real users. we pre-define different user profiles by combining the attributes of gender, age, and education, according to which we prompt LLMs to generate diverse comments by role-playing these users to get comprehensive user feedback. After extracting the semantic features of all generated comments, we split them into multiple subpopulation groups under each demographic view. We further perform an average operation in each subpopulation group to get overall feedback and calculate the subpopulationlevel divergences to represent differences. The final representation of generated comments is obtained via intra-view and inter-view aggregations. Experiments demonstrate the effectiveness of Gen-FEND to enhance fake news detection performance. Our main contributions are as follows:

- Idea: We propose to induce LLMs to role-play social media users to generate diverse comments as a substitute for actual-posted ones for fake news detection.
- Framework: We design GenFEND, a generated feedback enhanced fake news detection framework, which generates diverse user comments, analyzes them from a multi-subpopulation perspective, and aggregates the derived features from both intraand inter-demographic views.
- Effects: Experiments demonstrate the effectiveness of GenFEND to enhance fake news detection performance and show the unique value of LLM-generated comments. The code is available at https://github.com/ICTMCG/GenFEND.

## 2 RELATED WORK

Fake News Detection. According to the sources of information used, methods for fake news detection can be clustered into two groups: content-based, and external resource-based methods [15].

Content-based methods often extract style features [33, 75], semantic features [14, 70, 72], emotion features [1, 71] from textual content and visual features from appended images or videos in some multi-modal approaches [6, 34, 35, 43]. Recently, many researchers have investigated the (multi-modal) LLMs' capability as auxiliary tools for fake news detection, because of their remarkable performance in real-world knowledge understanding and reasoning [13, 24, 25, 51, 52, 63, 64]. We focus on the textual information in this paper. However, the performance of content-based methods is often limited by their vulnerability to fake news that intentionally mimics the style of real news [11, 60]. An alternative solution is to leverage auxiliary information from external resources, such as users [4, 27, 42], comments [18, 29, 42, 71], propagation structures [27], news environments [38], and extra knowledge [20, 67] because they introduce the crowd's help and provide related useful knowledge. User comments are widely used because they are more informative than user attributes and easier to obtain compared to propagation structures and extra knowledge. Different individuals' viewpoints from user comments can help identify fake news. However, the performance of comment-based methods is largely influenced by the quantity and quality of actual comments, especially in early detection scenarios. As an alternative, prompting LLMs to generate reactions is initially applied in recent works [26, 50]. Following this line, we propose using LLMs to generate rich and diverse comments as a substitute for actual ones and enable a more comprehensive fake news understanding.

Comment Generation for News-Related Applications. Comment generation is a sub-task to automatically produce human-like texts that express opinions on a given object. In news-related applications, comment-generation techniques can help synthesize pseudo comments to replace or supplement human-written comments and support social bot services for a more interactive discussion. Yang et al. [68] modeled a "read-attend-comment" procedure with an encoder-decoder framework to generate comments more attentive to the key points in news articles. Wang et al. [53] unified reader-aware topic modeling and saliency detection to improve the generation quality. Zou et al. [76] adopted an attribute-level contrastive learning method to better control the mentioned elements. Specified to fake news detection, Le et al. [21] and Liang et al. [23] generated comments as a malicious attack on detection models. Yanagi et al. [65] generated comments with news articles and actual comments provided to replace actual ones. Again, recent studies explored instructing LLMs to generate highly readable and human-like responses [22, 36, 44, 54, 69]. A contemporary work, DELL [50], leverages LLMs to generate comments for social graph simulation and assists in graph-based fake news detection. Our proposed GenFEND shares a similar direction, but we do not intend to simulate real-world social relationships like DELL, which generally only reflects active users' reactions. Instead, GenFEND generates comments from multiple subpopulations within diverse views and makes veracity judgments based on a comprehensive understanding and analysis of both active and silent users.

## **3 PROPOSED FRAMEWORK: GENFEND**

Fake news detection is generally formulated as a binary classification task between fake and real news [41]. Given a news piece *o* (and




Figure 2: Overview of Generated Feedback Enhanced Detection (GenFEND) framework. (a) Multi-View Comment Generation: Pre-define different user profiles with three demographic characteristics (gender, age, and education); Then, prompt the LLM to generate comments by role-playing these users. (b) Multi-Subpopulation Feedback Understanding: Split generated comments into different subpopulation groups for each view; Extract the semantic feature  $s_p^{mean}$  for each subpopulation group p and diversity representation  $d^{\mathcal{V}}$  for each view  $\mathcal{V}$ ; (c) Aggregation and Classification: Perform intra-view aggregation by operating dot-product between semantic features  $\{s_p^{mean}\}_{p \in \{1,...,m_{\mathcal{V}}\}}$  in each view  $\mathcal{V}$  and news feature  $e^o$ ; Perform inter-view aggregation to get final feature r of generated comments with a fusion gate guided by news feature  $e^o$  and diversity representation  $d = \bigoplus_{\mathcal{V} \in \{\mathcal{G}, \mathcal{A}, \mathcal{E}\}} d^{\mathcal{V}}$  as input; Concatenate r and  $e^o$  (and  $e^c_{actual}$  if available) for classification.

elicited comments  $C_{actual}$ ), we first generate a group of comments C based on o. With the learned news piece's feature  $e^o$  (actual comments' feature  $e^c_{actual}$ ) and generated comments' feature r, we aim to learn a content-only model  $f(e^o, r) \rightarrow y$  or a comment-based model  $f(e^o, e^c_{actual}, r) \rightarrow y$ , where y is the ground-truth veracity label. Figure 2 overviews the proposed framework, GenFEND, which consists of multi-view comment generation, multi-subpopulation feedback understanding, and aggregation and classification.

#### 3.1 Multi-View Comment Generation

Given a news piece *o*, we aim to generate diverse comments from different types of users. We first select three typical user attributes, i.e., gender, age, and education, which closely correlate with the difference between real and fake news. Existing studies reveal that there are gender differences of interest in discussion participation for different fake news topics [2, 37], reflecting their different viewpoints. Controlling the gender attribute can capture such differences for comment generation. Moreover, age and educational level are empirically proved to correlate with cognitive abilities such as remembering and understanding, significantly influencing belief in fake news [10]. Including the two factors could better cover the target audiences of specific fake news. These attributes can certainly be from one single user, so we utilize all three demographic attributes mentioned above to set user profiles from

multiple views via combination<sup>1</sup>. Specifically, the assignments to the three attributes are:

- Gender: male; female.
- Age: under 17 years old; 18 to 29 years old; 30 to 49 years old; 50 to 64 years old; over 65 years old.
- Education: a college graduate; has not graduated from college; has a high school diploma or less.

By combining different assignments of gender, age, and education, we obtain 30 different user profiles. The combinations are then used to prompt the LLM to generate comments by role-playing the 30 types of users:

#### **Prompt 1: Comment Generation Prompt**

**System Prompt:** Suppose you are a [*gender*] Twitter user. You are [*age*]. Educationally, you [*education*]. You will be provided with an article. You should write one comment about the article. Note that your comment needs to match your identity, and should be brief and natural, like normal Twitter users.

Context Prompt: news: [the given news o]

<sup>&</sup>lt;sup>1</sup>Due to the limit of generation cost, we did not cover all possible user attributes but chose the three frequently considered ones based on existing studies.

## 3.2 Multi-Subpopulation Feedback Understanding

To comprehensively analyze user feedback produced in § 3.1, we propose understanding these comments from a multi-subpopulation perspective, where the subpopulation groups are split based on the attributes in the three views. For example, there are two groups from the gender view, male and female. Given the news piece o and generated n corresponding comments  $C = \{c_1, ..., c_n\}$ , we adopt pre-trained sentence transformers to encode comments C into *dim*-dimensional embeddings as  $E^c = \{e_1^c, ..., e_n^c\}$ , where  $e_i^c \in$  $\mathbb{R}^{dim}$ ,  $1 \leq i \leq n$ . We denote gender, age, and education views as  $\mathcal{G}, \mathcal{A}, \mathcal{E}$  respectively. For each view  $\mathcal{V} \in {\mathcal{G}, \mathcal{A}, \mathcal{E}}$ , we split user comments C into  $m_V$  different subpopulation groups, which are  $C_1, ..., C_{m_V}$ , where  $C_1 \cup ... \cup C_{m_V} = C$ , and  $C_p \cap C_q = \emptyset (p \neq q)$ and  $p, q \in \{1, ..., m_V\}$ ). Here,  $m_G = 2, m_{\mathcal{A}} = 5$ , and  $m_{\mathcal{E}} = 3$ . The corresponding comments embeddings in subpopulation group  $C_p$ are denoted as  $E^{c_p} = \{ e_i^c \}_{c_i \in C_p}$ . To perceive the reactions reflected by comments from different groups, we adopt two operations to reflect the overall viewpoint shared among users in the same group and the discrepancy across different groups respectively.

**Overall Semantic Feature Extraction.** To understand users' overall viewpoints in the same subpopulation group, we average embeddings of comments for each subpopulation group. The semantic feature for the subpopulation group  $C_p$  in view  $\mathcal{V}$  is formulated as:

$$s_p^{mean} = \frac{1}{|E^{c_p}|} \sum_{e_i^c \in E^{c_p}} e_i^c,$$
(1)

where  $p \in \{1, ..., m_V\}$ , and  $|E^{c_p}|$  is the number of comments in subpopulation group  $C_p$ .

**Diversity Representation Extraction.** The divergence of viewpoints among different subpopulation groups indicates the diversity of feedback under the specific view. We assume different dimensions distributed in the comments' embedding space represent different viewpoints and we calculate the KL divergence based on the comments' embedding to measure the diversity of viewpoints for each view. Specifically, for each pair of subpopulation groups  $C_p$  and  $C_q$ , the distribution divergence is calculated as follows:

$$d_{p,q} = \frac{1}{|E^{c_p}||E^{c_q}|} \sum_{e_i^c \in E^{c_p}, e_j^c \in E^{c_q}} \text{kl\_div}(\hat{e}_i^c, \hat{e}_j^c),$$
(2)

where  $E^{c_p}$  and  $E^{c_q}$  are embeddings of comments in the subpopulation group  $C_p$  and  $C_q$  respectively,  $|E^{c_p}|$  and  $|E^{c_q}|$  are the numbers of comments in  $C_p$  and  $C_q$ .  $\hat{e}^c_i = \text{Softmax}(e^c_i)$ , which transform the embeddings into probability distributions. kl\_div( $\cdot, \cdot$ ) is the Kullback-Leiber divergence operation. After calculating the distribution divergence between every pair of subpopulation groups, we obtain the diversity representation  $d^{\mathcal{V}}$  for view  $\mathcal{V}$  as follows:

$$d^{\mathcal{V}} = \bigoplus_{p,q \in \{1,\dots,m_{\mathcal{V}}\}, p \neq q} d_{p,q}.$$
 (3)

Finally, we obtain semantic features  $s_p^{mean}$  for each subpopulation group  $C_p$  and diversity representation  $d^{\mathcal{V}}$  for each view  $\mathcal{V} \in \{\mathcal{G}, \mathcal{A}, \mathcal{E}\}$ .

## 3.3 Aggregation and Classification

To better enhance fake news detection performance, it is necessary to generate high-quality comment representations that can represent user feedback from multiple subpopulation groups. Note that different views specialize in different analyzing perspectives, and comments from different subpopulation groups in each view reflect the characteristics of viewpoints from such perspectives. Therefore, to aggregate comments features of multi-subpopulation groups, both intra-view aggregation and inter-view aggregation are considered.

**Intra-View Aggregation.** Cross-subpopulation correlations can provide complementary information at each view. Therefore, we design a cross-subpopulation fusion module to learn the overall semantic feature for each view  $\mathcal{V}$ .

Specifically, given the news' content feature  $e^o \in \mathbb{R}^{dim}$  and the comments' semantic feature  $s_p^{mean}$  of each subpopulation group  $C_p$ , we obtain weights  $w^V$  for subpopulation groups by calculating the dot-product between  $e^o$  and  $\left\{s_p^{mean}\right\}_{p \in \{1,...,m_V\}}$ , which can be formulated as:

$$\boldsymbol{s}_{cat}^{\mathcal{V}} = \left[\boldsymbol{s}_{1}^{mean}; ...; \boldsymbol{s}_{m_{\mathcal{V}}}^{mean}\right],\tag{4}$$

$$w^{\mathcal{V}} = \operatorname{Softmax}(\mathbf{s}_{cat}^{\mathcal{V}} \cdot \mathbf{e}^{o^{\mathsf{T}}} / \sqrt{dim}),$$
 (5)

where  $s_{cat}^{\mathcal{V}} \in \mathbb{R}^{m_{\mathcal{V}} \times dim}$  denotes the stacking of semantic features of all subpopulation groups in the view  $\mathcal{V}, w^{\mathcal{V}} \in \mathbb{R}^{m_{\mathcal{V}} \times 1}$  denotes the weights for subpopulation groups, and *dim* is the embedding dimension of comments features.

With  $w^{\mathcal{V}}$ , we operate subpopulation-level aggregation to obtain the semantic feature  $s^{\mathcal{V}} \in \mathbb{R}^{dim}$  for view  $\mathcal{V}$  as follows:

$$\boldsymbol{s}^{\mathcal{V}} = \boldsymbol{w}^{\mathcal{V}^{\mathsf{T}}} \cdot \boldsymbol{s}_{cat}^{\mathcal{V}}.$$
 (6)

**Inter-View Aggregation.** The subpopulation-level divergences and the topic of the news content can help measure the relative importance of different views. To this end, we utilize a view gate to aggregate the three views adaptively. We use the news content feature  $e^o \in \mathbb{R}^{dim}$  and diversity representation  $d = \bigoplus_{V \in \{\mathcal{A}, \mathcal{G}, \mathcal{E}\}} d^V$  as input to guide the aggregation. The inter-view aggregation module outputs a vector a, denoting the weight of each view for a specific news piece:

$$\boldsymbol{a} = \text{Softmax}(G(\boldsymbol{e}^{\boldsymbol{o}} \oplus \boldsymbol{d}; \boldsymbol{\theta})), \tag{7}$$

where  $G(\cdot; \theta)$  is the view gate,  $\theta$  is the parameters of the view gate, and the view gate  $G(\cdot; \theta)$  is a two-layer feed-forward network. We use Softmax( $\cdot$ ) to normalize the output of  $G(\cdot; \theta)$  and  $a = [a^{\mathcal{G}}, a^{\mathcal{A}}, a^{\mathcal{E}}]$  is the weight vector denoting the importance of each view. The generated comments' final feature is:

$$\boldsymbol{r} = \sum_{\boldsymbol{\mathcal{V}} \in \{\boldsymbol{\mathcal{G}}, \boldsymbol{\mathcal{A}}, \boldsymbol{\mathcal{E}}\}} a^{\boldsymbol{\mathcal{V}}} \boldsymbol{s}^{\boldsymbol{\mathcal{V}}}.$$
(8)

**Classification.** With the aggregated representation r, we predict the probability of news piece o being fake with:

$$\hat{y} = \begin{cases} \text{Sigmoid}(\text{MLP}(\boldsymbol{r} \oplus \boldsymbol{e}^{o})) & \text{w/o actual cmts,} \\ \text{Sigmoid}(\text{MLP}(\boldsymbol{r} \oplus \boldsymbol{e}^{o} \oplus \boldsymbol{e}^{c}_{actual})) & \text{w/ actual cmts.} \end{cases}$$
(9)

We optimize all the parameters by minimizing the cross-entropy loss with backpropagation. The loss function for one sample is:

$$\mathcal{L} = -y \log \hat{y} - (1 - y) \log(1 - \hat{y}),$$
(10)

where *y* is the ground-truth label of news piece *o* (1 for fake and 0 for real), and  $\hat{y} \in [0, 1]$  is the predicted probability of *o* being fake.

Table 1: Datasets statistics.

Dataset	Train		Valid	ation	Т				
	Fake	Real	Fake	Real	Fake	Real	Total		
Weibo21	2,883	2,179	540	702	539	724	7,567		
#comments	76,015	72,152	8,234	9,766	8,576	10,032	184,775		
GossipCop	1,816	3,775	552	820	844	483	8,260		
#comments	16,823	29,723	4,054	6,046	3,652	6,091	66,389		
LLM-mis	410	289	118	82	59	42	1,000		
#comments	(no comments provided)								

#### **4 EXPERIMENTS**

The experiments are to answer the following evaluation questions: **EQ1** Can GenFEND improve fake news detection performance?

**EQ2** How effective is the GenFEND archtecture? **EQ3** How effective are generated comments and why?

#### 4.1 Experimental Setup

**Datasets.** We conduct experiments on three public datasets, including human-written **Weibo21** [30], **GossipCop** [40], and the LLM-generated **LLM-mis** [5]. For the Weibo21 and GossipCop datasets, we did the train-validation-test set split chronologically to simulate real-world scenarios. For LLM-mis, we did a random split because of the lack of actual timestamps for generated samples. Table 1 shows the dataset statistics.

Baselines. For Weibo21 and GossipCop datasets, we compare with two groups of fake news detection methods. The first group is content-only methods: (1) LLM w/ cnt: A zero-shot method that directly prompts an LLM to make veracity judgments with only news content provided; (2) BERT [8]: A pre-trained language model that is widely used as the text encoder for fake news detection [19, 30, 61], with the last layer finetuned conventionally; (3) ENDEF [74]: A method that removes entity bias to obtain generalizable features; (4) EANN-text [55]: A model which aims to learn event-invariant representations for fake news detection. Here we use its text-only version. The second group is comment-based methods: (1) LLM w/ actual cmts: A zero-shot method that directly prompts an LLM to make veracity judgments with both news content and actual comments provided; (2) dEFEND [39]: A model that develops a sentence-comment co-attention sub-network for fake news detection; (3) DualEmo [71]: A framework that considers both publisher emotion, social emotion, and their gap for fake news detection; (4) CAS-FEND(tea) [31]: The CAS-FEND teacher module that exploits user comments from both semantic and emotional aspects.

For the LLM-mis dataset which only contains generated misinformation samples, we include LLM *w*/ cnt, BERT [8], ENDEF [74], and **DELL** [50] for comparison. DELL is a recently proposed method that exploits LLMs to generate user comments and perform proxy tasks for fake news detection. It uses four ensemble strategies to get the final judgment. In our experiments, we use the same user attributes for DELL and GenFEND to ensure fairness.

Implementation Details. We prompt GLM-4 [73] for Weibo21, and GPT-3.5-Turbo (version 0125) [32] for GossipCop in comment generation and veracity judgment. For comment generation, the sampling temperature is set to 0.95 for GLM-4 and 1.0 for GPT-3.5-Turbo to guarantee diversity and creativity. max\_tokens is 100. For veracity judgment, the sampling temperature is set to 0.1 for GLM-4 and GPT-3.5-Turbo to get definitive answers (see Prompt 2, in which underlined text is only for LLM w/ actual cmts). For non-LLM methods, we adopt bert-base-chinese for Weibo21 and bert-base-uncased for GossipCop/LLM-mis to encode news content. The maximum number of tokens of news content is 170. We adopt sentence transformers to obtain comment embeddings (Dmetaembedding-zh<sup>2</sup> for Weibo21 and bge-large-en-v1.5<sup>3</sup> for GossipCop and LLM-mis). dim is set to 768 and 1024 for Chinese and English, respectively. To evaluate the effect of GenFEND, we utilize the feature of news content from the baseline methods as  $e^{o}$  in Figure 2. For comment-based methods, we concatenate  $e^{o}$  with the feature of actual comments for final classification.

#### Prompt 2: Prompt for Veracity Judgment

**System Prompt**: Given the following news piece and the corresponding comments, predict the veracity of this news piece. The comments are collected from social media users. If the news piece is more likely to be fake, return 1; otherwise, return 0. Please refrain from providing ambiguous assessments such as undetermined.

**Context Prompt:** news: [*the given news o*]; comments: [*user comments*  $c_1, c_2, ...$ ]. The answer (Arabic numerals) is:

**Metrics.** We report experimental results in five metrics, including the accuracy (Acc), area under the ROC curve (AUC), macro F1 score (macF1), and F1 score for the fake/real class (F1-fake/F1-real).

## 4.2 Main Results (EQ1)

Tables 2 and 3 show the results of GenFEND and the compared methods on the three datasets. We have the following observations: (1) **GenFEND brings valuable information beyond news content.** From the results in the content-only methods (Group 1 in Table 2 and Table 3), we find that content-only methods have improved with GenFEND, even comparable with some comment-based detectors. The results indicate that generated comments are a supplement to news content and a surrogate of actual comments, which can improve early detection performance.

(2) **GenFEND provides additional information beyond actual comments.** From the results in the comment-based methods (Group 2 in Table 2), we find that comment-based detectors have improved with GenFEND, which demonstrates a more comprehensive understanding of news content obtained from diverse generated comments.

(3) **GenFEND performs better than DELL.** Table 3 shows that the best and the second best results in almost all metrics are from BERT *w*/ GenFEND and ENDEF *w*/ GenFEND, which exceed the

<sup>&</sup>lt;sup>2</sup>https://huggingface.co/DMetaSoul/Dmeta-embedding-zh

<sup>&</sup>lt;sup>3</sup>https://huggingface.co/BAAI/bge-large-en-v1.5

Table 2: Performance of LLM prediction (w/ cnt and w/ actual cmts), and other content-only and comment-based methods with or without GenFEND on the Weibo21 and GossipCop datasets. The better result for each comparison pair is bolded.

Category	Method	Weibo21				GossipCop					
		macF1	Acc	AUC	F1-real	F1-fake	macF1	Acc	AUC	F1-real	F1-fake
	LLM w/ cnt	0.6795	0.6825	0.7119	0.6486	0.7105	0.6029	0.6774	0.6043	0.7750	0.4309
	BERT	0.7625	0.7633	0.8439	0.7749	0.7500	0.8073	0.8259	0.8931	0.8670	0.7477
	w∕ GenFEND	0.7926	0.7935	0.8648	0.8079	0.7769	0.8457	0.8576	0.9137	0.8885	0.8029
Cnt-Only Methods	ENDEF	0.7701	0.7717	0.8477	0.7870	0.7532	0.8298	0.8463	0.9002	0.8826	0.7770
	w/ GenFEND	0.7898	0.7900	0.8617	0.7923	0.7775	0.8395	0.8515	0.9131	0.8835	0.7954
	EANN-text	0.7212	0.7240	0.7986	0.7467	0.6956	0.8179	0.8348	0.8904	0.8733	0.7626
	w/ GenFEND	0.7497	0.7560	0.8100	0.7603	0.7273	0.8279	0.8425	0.8969	0.8780	0.7779
	LLM w/ actual cmts	0.7663	0.7664	0.7868	0.7607	0.7718	0.6360	0.6654	0.6351	0.7394	0.5326
	dEFEND	0.7995	0.8005	0.8832	0.8133	0.7857	0.8670	0.8794	0.9382	0.9076	0.8265
	w∕ GenFEND	0.8102	0.8188	0.8875	0.8295	0.7991	0.8904	0.8913	0.9581	0.9131	0.8512
Cmt-Based Methods	DualEmo	0.7834	0.7837	0.8823	0.7987	0.7925	0.8864	0.8802	0.9341	0.9040	0.8620
	w∕ GenFEND	0.8083	0.8084	0.8992	0.8120	0.8102	0.9004	0.9135	0.9557	0.9358	0.8688
	CAS-FEND(tea)	0.8181	0.8187	0.9016	0.8287	0.8074	0.9188	0.9261	0.9716	0.9432	0.8944
	w/ GenFEND	0.8217	0.8200	0.9094	0.8309	0.8112	0.9250	0.9398	0.9822	0.9477	0.9084

Table 3: Performance of LLM *w*/ cnt by zero-shot prompting, DELL with different ensemble strategy, and content-only methods (i.e., BERT and ENDEF) with and without GenFEND on the LLM-mis dataset. The best and the second-best results are bolded and <u>underlined</u>.

Method	macF1	Acc	AUC	F1-real	F1-fake
LLM w/ cnt	0.5037	0.5050	0.5282	0.5283	0.4792
DELL Single	0.8648	0.8713	0.9503	0.8354	0.8943
DELL Vanilla	0.8670	0.8713	0.9500	0.8434	0.8908
DELL Confidence	0.8589	0.8614	0.9435	0.8409	0.8772
DELL Selective	0.8440	0.8515	0.9402	0.8101	0.8780
BERT	0.8570	0.8614	0.9463	0.8325	0.8816
w∕ GenFEND	0.8798	0.8837	0.9507	0.8588	<u>0.9009</u>
ENDEF	0.8591	0.8614	0.9435	0.8409	0.8772
w∕ GenFEND	0.8883	0.8911	0.9435	0.8706	0.9060

performance of DELL with different ensemble strategies. The superiority of GenFEND indicates the effectiveness of diverse comment generation and subsequent feedback understanding.

(4) GenFEND is more effective for identifying fake news than excluding real news. In most cases on the weibo21 and GossipCop datasets, GenFEND brings a larger performance improvement in F1-fake than in F1-real, which indicates that the generated comments might contain knowledge and experience that can identify the typical fake news patterns in reality. This makes GenFEND more practical because identifying more fake news pieces is generally a priority in a real-world deployment.

## 4.3 Effectiveness of GenFEND Arch. (EQ2)

We compare with several variants of GenFEND (§ 4.3.1) and decrease the number of actual comments (§ 4.3.2) to evaluate the importance of different components in GenFEND and the robustness of GenFEND.

Table 4: Performance comparison between GenFEND and its ablative variants. "-" indicates "not applicable", as LLM-mis does not provide actual comments.

	Wei	bo21	Gossi	рСор	LLM-mis		
Method	macF1	Acc	macF1	Acc	macF1	Acc	
BERT w/ GenFEND	0.7926	0.7935	0.8457	0.8576	0.8798	0.8837	
w/o gender view	0.7768	0.7787	0.8295	0.8448	0.8632	0.8701	
w/o age view	0.7861	0.7870	0.8307	0.8470	0.8699	0.8754	
w/o education view	0.7836	0.7838	0.8319	0.8515	0.8668	0.8698	
w/o reweighting	0.7735	0.7736	0.8320	0.8441	0.8588	0.8679	
w/o fusion gate	0.7897	0.7895	0.8399	0.8501	0.8604	0.8713	
dEFEND w/ GenFEND	0.8102	0.8188	0.8904	0.8913	-	-	
w/o gender view	0.8071	0.8084	0.8697	0.8817	-	-	
w/o age view	0.7980	0.7989	0.8883	0.8968	-	-	
w/o education view	0.7988	0.7997	0.8770	0.8892	-	-	
w/o reweighting	0.7954	0.7963	0.8702	0.8813	-	-	
w/o fusion gate	0.8001	0.8014	0.8787	0.8890	-	-	

4.3.1 Importance of Different Views and Their Aggregation. To demonstrate the effectiveness of selected views, we obtain three one-view-removed variants for BERT w/ GenFEND and dEFEND w/ GenFEND. As shown in Table 4, the removal of each view consistently caused performance decreases, which indicates that the demographic information from all three views can provide useful information to improve the comments' comprehensiveness and benefit the subsequent analysis in Multi-Subpopulation Feedback Understanding. As further demonstrated by the case in Table 5, the introduction of the gender view could exactly reflect the controversial point concerning the male-female relationship in this fake news piece. After analysis of generated comments from the three views, our proposed GenFEND successfully captured such a key point, assigned the highest weight to the gender view, and correctly identified news fakeness.

To demonstrate the effectiveness of intra- and inter-view aggregations, we replace the *Subpopulation Reweighting* and *Inter-View Fusion Gate* modules with a simple average pooling. From Table 5, we

# Table 5: A fake news case about a family affair, where the gender view gains the highest weight.

**News:** According to a news report, a man consecutively heard phone rings at 02:01 am on November 11 and noticed many weird transactions of his four credit cards! He initially thought his cards had been stolen, but upon closer inspection, he found that it was all from online shopping malls. When he went to the study room, he found his wife shopping on the computer. After figuring out that about 230,000 CNY was spent in total, he suddenly fainted. His wife dialed 120. Despite an attempt at resuscitation, he finally died at 6 am.

gender view: 0.5442 age view: 0.1459 education view: 0.3110




Figure 3: Early detection performance of dEFEND and dE-FEND w/ GenFEND with 1, 2, 4, 8, and 16 actual comments for the testing data.

see that the replacement of intra- or inter-view aggregations leads to a performance drop, with a larger drop for the intra-view, which demonstrates that adaptively weighting different subpopulation groups and fusing different views are important for a comprehensive and effective understanding of news.

4.3.2 Robustness of GenFEND when Decreasing the Number of Actual Comments. To explore GenFEND's capability of early detection, we evaluate the impact of GenFEND for comment-based methods when the number of actual comments varies. Experimental results from previous sections demonstrate the effectiveness of generated comments partnering with full actual comments It is more inspiring to investigate whether GenFEND can improve the fake news detection performance of comment-based methods with fewer actual comments available (i.e., at the earlier stage).

We experiment with dEFEND and set the number of actual comments of testing data to 1, 2, 4, 8, and 16, and compare the two versions with or without GenFEND. As depicted by Figure 3, dE-FEND w/ GenFEND surpasses dEFEND when the number of actual comments is limited, which indicates that GenFEND improves dE-FEND's early detection performance.

## 4.4 Effectiveness of Generated Comments (EQ3)

To investigate the impact of generated comments, we analyze from three aspects: comparing generated comments with actual comments (§ 4.4.1), comparing generated comments from silent and active users (§ 4.4.2), analyzing the diversity of users (§ 4.4.3), and evaluating the generated comments' conformity to pre-defined user attributes (§ 4.4.4). 4.4.1 Comparison of Generated Comments and Actual Comments. To evaluate the effect of generated comments compared to actual comments, we adopt LLM w/ comment, BERT w/ GenFEND, and dEFEND w/ GenFEND by providing actual comments and generated comments respectively. To obtain the user profiles for actual comments, we prompt GPT-3.5-Turbo by calling its API to predict pseudo user profiles:

#### Prompt 3: Prompt for User Profile Prediction

**System Prompt:** Given a news-comment pair, you should predict the commenter's gender, age, and education level. Note the gender should be chosen from {male, female}; the age should be chosen from { $\leq 17$ ; 18-29; 30-49; 50-64;  $\geq 65$ }; the education level should be chosen from {high school diploma or less; an undergraduate; a college graduate}. Your prediction should follow the format as {'gender': g; 'age': a; 'education level': e}.

**Context Prompt:** news: [*the given news o*]; comment: [*one user comment c*]

We count the different number of user profiles of actual comments for each news piece and find that only 7 of 30 for Weibo21 and 3 of 30 for GossipCop are covered on average, which can result in many empty subpopulation groups in Multi-Subpopulation Feedback Understanding. Under the circumstances, we experiment by adding an empty string for all subpopulation groups. From the experimental results in Table 6, we find that: (1) Generated comments bring more effects than actual comments in almost all cases for BERT/dEFEND w/GenFEND, which benefits from the effective collocation of generated diverse comments and the following understanding procedure; (2) The LLM's performance on GossipCop is better when generated comments rather than actual ones are provided, showing the usefulness of generated comments themselves. However, the case is different for Weibo21. We speculate that it is because patterns in actual comments of Weibo21 are easier to capture and different from those in generated ones.

4.4.2 Comparison of Generated Comments from Silent and Active Users. With the pseudo profiles of actual commentators obtained in § 4.4.1, we regard users with the same profiles as actual commentators as "active users", and the others as "silent users". To prove the importance of diverse users in GenFEND, we investigate how the generated comments from silent users and active users contribute to GenFEND respectively. By referring to actual commentators' pseudo profiles, we split the generated comments into two clusters: silent and active users' comments and conduct experiments to evaluate their impacts. Specifically, we adopt BERT w/ GenFEND and dEFEND w/ GenFEND for evaluation. Based on the results shown in Table 7, we have the following findings: (1) Only utilizing active users' comments or silent users' comments leads to a performance drop compared to utilizing all generated ones, which indicates that both silent users and active users have positive and complementary effects. (2) In most cases, models using generated silent users' comments outperform those using active users' ones, showing the former's superior usefulness. This confirms that considering potential silent users and generating such comments inaccessible in reality is helpful for fake news detection.

Table 6: Performance comparison with actual comments and generated comments for LLM, content-only method BERT and comment-based method dEFEND. The best results for each comparison pair are bolded.

Method	Comment Type	Weibo21				GossipCop					
		macF1	Acc	AUC	F1-real	F1-fake	macF1	Acc	AUC	F1-real	F1-fake
LLM w/ comment	actual	<b>0.7597</b>	<b>0.7601</b>	<b>0.7824</b>	0.7506	<b>0.7689</b>	0.6360	0.6654	0.6351	0.7394	0.5326
	generated	0.7403	0.7482	0.7384	<b>0.7857</b>	0.6984	<b>0.6567</b>	<b>0.6917</b>	<b>0.6532</b>	<b>0.7664</b>	<b>0.5471</b>
BERT w/ GenFEND	actual	0.7805	0.7816	0.8540	0.8048	0.7762	0.8390	0.8523	<b>0.9189</b>	0.8852	0.7928
	generated	<b>0.7926</b>	<b>0.7935</b>	<b>0.8648</b>	<b>0.8079</b>	<b>0.7769</b>	<b>0.8457</b>	<b>0.8576</b>	0.9137	<b>0.8885</b>	<b>0.802</b> 9
dEFEND w/ GenFEND	actual	0.7995	0.8005	0.8832	0.8133	0.7857	0.8670	0.8794	0.9382	0.9076	0.8265
	generated	<b>0.8102</b>	<b>0.8188</b>	<b>0.8875</b>	<b>0.8295</b>	<b>0.7991</b>	<b>0.8904</b>	<b>0.8913</b>	<b>0.9581</b>	<b>0.9131</b>	<b>0.851</b> 2

Table 7: Performance comparison of LLM, content-only method BERT and comment-based method dEFEND with generated comments from active and silent users. The best and the second-best results for each comparison pair are bolded and underlined, respectively.

Method	I.I There is	Wei	bo21	GossipCop		
Method	User Type	macF1	Acc	macF1	Acc	
	active	0.7334	0.7398	0.6459	0.6806	
LLM w/ gen cmt	silent	0.7379	0.7379	0.6586	0.7076	
0	all	0.7403	0.7482	0.6567	0.6917	
	active	0.7825	0.7834	0.8393	0.8523	
BERT w/ GenFEND	silent	0.7925	0.7937	0.8400	0.8553	
	all	0.7926	0.7935	0.8457	0.8576	
	active	0.7921	0.7931	0.8697	0.8817	
dEFEND w/ GenFE	0.8019	0.8025	0.8797	0.8922		
	all	0.8102	0.8188	0.8904	<u>0.8913</u>	




Figure 4: Macro F1 scores of BERT *w*/ GenFEND with 30 generated comments from different numbers of users (30/15/10). Each user generates the same number of comments.

4.4.3 Impacts of User Diversity. To conduct a quantitative analysis of the impact of user diversity, we experiment with three groups of generated comments that cover different numbers of user types. Specifically, besides the generated comments in the main experiment (Table 2), we prompt LLMs to generate another two pieces of comments for each type of user and obtain 90 generated comments in total. For a fair comparison, we guarantee that the three groups contain the same number of comments in total (here, 30), i.e., 30 different users × 1 comment per user for Group 1,  $15 \times 2$  for Group 2, and  $10 \times 3$  for Group 3. We use the full set of user types for Group 1, randomly select 15 out of the 30 types for Group 2, and again




Figure 5: Average conformity scores of generated comments to each attribute. The bars are in "male; female" order for gender, from young to old for age, and from low-level to high-level degree for education.

randomly select 10 out of 15 for Group 3. We re-use the same 30 generated comments in the main experiments for Group 1.

As shown in Figure 4, with the three groups of comments provided, the macro F1 score of BERT w/ GenFEND decreases when the number of users (of different types) decreases, even if more comments are provided by each user. This confirms our initial assumption that user diversity is of great importance for comment generation in fake news detection.

4.4.4 Conformity Evaluation of Generated Comments to User Attributes. We set a human evaluation to measure how generated comments conform to specified user attributes. Specifically, we use a subset of 300 generated comments from Weibo21 and Gossip-Cop (150 for each), which covers all 30 user types. Given a news piece and its corresponding generated comments, we ask participants to judge how possible a given comment is from the user with pre-defined attributes (less likely/likely/very likely). We recruited 20 participants (experienced in social media discussion), each of whom accomplished the task in about one hour on average and was paid their hourly income. As depicted in Figure 5, generated comments are scored with a high degree of conformity to user attributes, maintaining user and comment diversity.

## 5 CASE ANALYSIS

We analyze three cases from the testing set, aiming to know the individual usefulness of the generated comments rather than the compound effects of generated comments and feedback understanding (Table 8). The predictions are from dEFEND, with actual

Table 8: Three cases from the testing set. In Cases 1 and 2, the detector predicted incorrectly using actual comments but did correctly using mixed (actual and generated) comments. Case 3 is a failure case, even if mixed comments were provided. For all cases, we list at most three representative comments in the actual and generated comment list for brevity.

(Case 1) Real News: Many people believe that yogurt is rich in probiotics, which can balance intestinal flora and promote intestinal motility. Actually, research finds that yogurt does not improve digestion.

Actual Comments: • Well, it is the first time I've heard about it. • Really?

Generated Comments: ① It turns out that drinking yogurt may not necessarily promote digestion. Knowledge received! I usually like to drink yogurt. Seems that I need to pay more attention to my diet. ② So that is what it is. I used to believe yogurt helps digestion. It seems that we should pay more attention to food pairing and not just rely on yogurt. ③ I have always thought that yogurt is helpful for digestion. It seems that learning more professional knowledge is needed when selecting foods later. I will forward it to everyone. Don't be misled by wrong knowledge anymore!

(Case 2) Fake News: There is a rumor that the Maserati driver, a woman who caused the car accident, is suffering from mental illness.

Actual Comments: • Money makes the mare go. • So simple. She has a father being in power in the government! • Every time something goes wrong, they use this excuse. Can't they find some new ones? If she has a mental illness, then let her stay in a mental hospital!

Generated Comments: 1 It is too outrageous! How could someone use mental illness as an excuse? 2 Is it reliable? If that's the case, the situation will be complicated. Hope the departments concerned can provide accurate inquiry results. 3 Oh god. How could this be? Hope it will come out in the wash ASAP.

(Case 3, Failure Case) Fake News: Recently in Guangzhou. Miss Li, a female foreign teacher from the UK, mainly worked as an onsite tutor for students. Though her course was expensive, she was still very popular among students. However, this foreign teacher's unique skill was to have a sexual relationship with those who had a good English score! A parent discovered this and called the police. Further investigation revealed that five other students had the same experience. Such a "reward" is almost unheard of. It is truly despicable for such an expensive foreign language teacher to do such an evil.

Actual Comments: ① So did the children's English grades improve? ② Haha! It's truly a "combination" of virtue and art! ③ Teaching by example? Generated Comments: ① This is too scary, how could there be such a teacher? This is not education. This is a crime! I hope such behavior can be severely punished by the law and we can protect children's safety! ④ This is completely a moral decay, and the law must not be lenient. ③ This is so shocking! As a teacher, it is truly irresponsible for students and society to use one's position to do such a thing.

or mixed (actual and generated) comments provided. In Case 1 (real news), actual comments are mostly of a questioning tone and thus not diverse, probably causing the model's misjudgment. In contrast, the generated comments provided additional positive feedback, helping correct the prediction. This indicates that a partial observation of users' reactions might negatively impact distinguishing the fake from the real, especially when comment distribution is overly biased. Differently, the fake case (Case 2) sparks more generated comments of doubtful and questioning tones, helping the model finally correct the prediction. The two cases confirm the potential of LLM-generated comments in helping detection, especially when actual comments are not diverse or even unavailable. Case 3 is a failure case. We attribute the failure to the limited coverage of user responses, mostly about expressing anger, sarcasm, and disgust. We did not find generated comments that question the underlying news intent, which is recently considered important for this task [56].

## 6 CONCLUSION AND DISCUSSION

We proposed using large language models as news comment generators for improving comment-based fake news detection, especially when only a limited number or even none of the actual comments are available. To obtain diverse comments and analyze them more comprehensively, we designed the **GenFEND** framework to enhance fake news detection with generated comments, which features multi-subpopulation feedback understanding and intraand inter-view aggregations. Experimental results on three public datasets demonstrated GenFEND's effective enhancements for content-only and comment-based fake news detection. Further analysis reveals that GenFEND's effectiveness was derived from the broader coverage of potentially active and silent users and the multi-view multi-subpopulation analysis on generated comments. Discussion. Technically, GenFEND exemplified how synthetic data empowers fake news detection. We identified the unnoticed and probably unavoidable limitations of existing detectors using actual user comments. As a substitute, we carefully designed a solution that elicits LLMs' capabilities in understanding natural language and playing specific roles for useful data synthesis. Despite this, we do not intend to do extremely real simulations of actual cases but to provide an educated imagination of discussions among different types of users. This idea allows us to leverage the advantages of LLMs and meanwhile avoid their disabilities (e.g., hard to speak as informally as social media users after alignment). Though our solution is domain-specific, it can serve as a useful reference for developing data-centric solutions for other social media tasks. From the application view, this research again exhibited the dual role of LLMs [28]: They are not only misinformation creators but can also serve as defenders against misinformation.

Limitation and Future Work. We identify the following limitations of this paper: (1) Besides gender, age, and education views, other demographic factors might also be useful for diversifying generated comments. We plan to extend and test more factors in the GenFEND development. (2) Though generated comments have been shown helpful in fake news detection, they are not always more effective than actual comments (e.g., dEFEND prefers actual ones), indicating that rooms still exist in finding better strategies to utilize generated comments. (3) Due to privacy concerns, we identify potentially active user types by inferring the profiles of actual commenting users, which may bring errors. (4) We conducted experiments on two well-recognized yet costly API-based LLMs to ensure comment comprehensiveness based on their good instruction-following capability but did not test open-source models like LLaMA [46], ChatGLM-3, and Gemma [7]. We plan to test more deployable LLMs at a lower cost.

#### REFERENCES

- Oluwaseun Ajao, Deepayan Bhowmik, and Shahrzad Zargari. 2019. Sentiment Aware Fake News Detection on Online Social Networks. In 2019 IEEE International Conference on Acoustics, Speech and Signal Processing. IEEE, 2507–2511. https: //doi.org/10.1109/ICASSP.2019.8683170
- [2] Ester Almenar, Sue Aran-Ramspott, Jaume Suau, and Pere Masip. 2021. Gender Differences in Tackling Fake News: Different Degrees of Concern, but Same Problems. *Media and Communication* 9, 1 (2021), 229–238. https://doi.org/10. 17645/mac.v9i1.3523
- [3] Dipto Barman, Ziyi Guo, and Owen Conlan. 2024. The Dark Side of Language Models: Exploring the Potential of LLMs in Multimedia Disinformation Generation and Dissemination. *Machine Learning with Applications* (2024), 100545.
- [4] Carlos Castillo, Marcelo Mendoza, and Barbara Poblete. 2011. Information Credibility on Twitter. In Proceedings of the 20th International Conference on World Wide Web. Association for Computing Machinery, 675–684. https://doi. org/10.1145/1963405.1963500
- [5] Canyu Chen and Kai Shu. 2023. Can LLM-Generated Misinformation Be Detected?. In The Twelfth International Conference on Learning Representations.
- [6] Ziwei Chen, Linmei Hu, Weixin Li, Yingxia Shao, and Liqiang Nie. 2023. Causal Intervention and Counterfactual Reasoning for Multi-modal Fake News Detection. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). Association for Computational Linguistics, 627–638. https://doi.org/10.18653/v1/2023.acl-long.37
- [7] Google DeepMind. 2024. Gemma: Open Models Based on Gemini Research and Technology. arXiv preprint arXiv:2403.08295 (2024).
- [8] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers). Association for Computational Linguistics, 4171–4186. https: //doi.org/10.18653/v1/N19-1423
- Patti Domm. 2013. False Rumor of Explosion at White House Causes Stocks to Briefly Plunge; AP Confirms Its Twitter Feed Was Hacked. https://www.cnbc. com/id/100646197. Accessed: 2024-05-20.
- [10] Stefan Gaillard, Zoril A. Oláh, Stephan Venmans, and Michael Burke. 2021. Countering the Cognitive, Linguistic, and Psychological Underpinnings Behind Susceptibility to Fake News: A Review of Current Literature With Special Focus on the Role of Age and Digital Literacy. Frontiers in Communication 6 (2021). https://doi.org/10.3389/fcomm.2021.661801
- [11] Axel Gelfert. 2018. Fake News: A Definition. Informal Logic 38, 1 (2018), 84–117. https://doi.org/10.22329/il.v38i1.5068
- [12] Naicheng Guo, Hongwei Cheng, Qianqiao Liang, Linxun Chen, and Bing Han. 2024. Integrating Large Language Models with Graphical Session-Based Recommendation. arXiv preprint arXiv:2402.16539 (2024).
- [13] Beizhe Hu, Qiang Sheng, Juan Cao, Yuhui Shi, Yang Li, Danding Wang, and Peng Qi. 2024. Bad Actor, Good Advisor: Exploring the Role of Large Language Models in Fake News Detection. Proceedings of the AAAI Conference on Artificial Intelligence 38, 20 (2024), 22105–22113.
- [14] Beizhe Hu, Qiang Sheng, Juan Cao, Yongchun Zhu, Danding Wang, Zhengjia Wang, and Zhiwei Jin. 2023. Learn over Past, Evolve for Future: Forecasting Temporal Trends for Fake News Detection. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 5: Industry Track). Association for Computational Linguistics, 116–125. https://doi.org/10.18653/v1/2023.acl-industry.13
- [15] Linmei Hu, Siqi Wei, Ziwang Zhao, and Bin Wu. 2022. Deep learning for fake news detection: A comprehensive survey. AI Open 3 (2022), 133–155. https: //doi.org/10.1016/j.aiopen.2022.09.001
- [16] Feiran Huang, Zhenghang Yang, Junyi Jiang, Yuanchen Bei, Yijie Zhang, and Hao Chen. 2024. Large Language Model Interaction Simulator for Cold-Start Item Recommendation. arXiv preprint arXiv:2402.09176 (2024).
- [17] Bohan Jiang, Zhen Tan, Ayushi Nirmal, and Huan Liu. 2024. Disinformation Detection: An Evolving Challenge in the Age of LLMs. In Proceedings of the 2024 SIAM International Conference on Data Mining (SDM). SIAM, 427–435.
- [18] Zhiwei Jin, Juan Cao, Yongdong Zhang, and Jiebo Luo. 2016. News Verification by Exploiting Conflicting Social Viewpoints in Microblogs. Proceedings of the AAAI Conference on Artificial Intelligence 30 (2016). https://doi.org/10.1609/aaai. v30i1.10382
- [19] Rohit Kumar Kaliyar, Anurag Goswami, and Pratik Narang. 2021. FakeBERT: Fake News Detection in Social Media with a BERT-based Deep Learning Approach. *Multimedia Tools and Applications* 80, 8 (2021), 11765–11788.
- [20] Ziyi Kou, Lanyu Shang, Yang Zhang, and Dong Wang. 2022. HC-COVID: A Hierarchical Crowdsource Knowledge Graph Approach to Explainable COVID-19 Misinformation Detection. Proceedings of the ACM on Human-Computer Interaction 6, GROUP, Article 36 (2022). https://doi.org/10.1145/3492855
- [21] Thai Le, Suhang Wang, and Dongwon Lee. 2020. MALCOM: Generating Malicious Comments to Attack Neural Fake News Detection Models. In 2020 IEEE International Conference on Data Mining. IEEE, 282–291. https://doi.org/10.1109/

ICDM50108.2020.00037

- [22] Tianlin Li, Xiaoyu Zhang, Chao Du, Tianyu Pang, Qian Liu, Qing Guo, Chao Shen, and Yang Liu. 2024. Your Large Language Model is Secretly a Fairness Proponent and You Should Prompt it Like One. arXiv preprint arXiv:2402.12150 (2024).
- [23] Jiayi Liang, Xi Zhang, Yuming Shang, Sanchuan Guo, and Chaozhuo Li. 2023. Clean-label Poisoning Attack against Fake News Detection Models. In 2023 IEEE International Conference on Big Data (BigData). 3614–3623. https://doi.org/10. 1109/BigData59044.2023.10386777
- [24] Hui Liu, Wenya Wang, Haoru Li, and Haoliang Li. 2024. TELLER: A Trustworthy Framework for Explainable, Generalizable and Controllable Fake News Detection. arXiv preprint arXiv:2402.07776 (2024).
- [25] Qiang Liu, Xiang Tao, Junfei Wu, Shu Wu, and Liang Wang. 2024. Can Large Language Models Detect Rumors on Social Media? arXiv preprint arXiv:2402.03916 (2024).
- [26] Yuhan Liu, Xiuying Chen, Xiaoqing Zhang, Xing Gao, Ji Zhang, and Rui Yan. 2024. From Skepticism to Acceptance: Simulating the Attitude Dynamics Toward Fake News. arXiv preprint arXiv:2403.09498 (2024).
- [27] Yang Liu and Yi-Fang Brook Wu. 2020. FNED: A Deep Network for Fake News Early Detection on Social Media. ACM Transactions on Information Systems 38, 3, Article 25 (2020), 33 pages. https://doi.org/10.1145/3386253
- [28] Jason Lucas, Adaku Uchendu, Michiharu Yamashita, Jooyoung Lee, Shaurya Rohatgi, and Dongwon Lee. 2023. Fighting Fire with Fire: The Dual Role of LLMs in Crafting and Detecting Elusive Disinformation. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing. Association for Computational Linguistics, 14279–14305. https://doi.org/10.18653/v1/2023. emnlp-main.883
- [29] Jing Ma, Wei Gao, and Kam-Fai Wong. 2018. Detect Rumor and Stance Jointly by Neural Multi-task Learning. In Companion Proceedings of the The Web Conference 2018. International World Wide Web Conferences Steering Committee, 585–593. https://doi.org/10.1145/3184558.3188729
- [30] Qiong Nan, Juan Cao, Yongchun Zhu, Yanyan Wang, and Jintao Li. 2021. MD-FEND: Multi-domain Fake News Detection. In Proceedings of the 30th ACM International Conference on Information & Knowledge Management. Association for Computing Machinery, 3343–3347. https://doi.org/10.1145/3459637.3482139
- [31] Qiong Nan, Qiang Sheng, Juan Cao, Yongchun Zhu, Danding Wang, Guang Yang, Jintao Li, and Kai Shu. 2023. Exploiting User Comments for Early Detection of Fake News Prior to Users' Commenting. arXiv preprint arXiv:2310.10429 (2023).
- [32] OpenAI. 2022. ChatGPT: Optimizing Language Models for Dialogue. https: //openai.com/blog/chatgpt/. Accessed: 2024-03-05.
- [33] Piotr Przybyla. 2020. Capturing the Style of Fake News. Proceedings of the AAAI Conference on Artificial Intelligence 34, 01 (2020), 490–497. https://doi.org/10. 1609/aaai.v34i01.5386
- [34] Peng Qi, Yuyan Bu, Juan Cao, Wei Ji, Ruihao Shui, Junbin Xiao, Danding Wang, and Tat-Seng Chua. 2023. FakeSV: A Multimodal Benchmark with Rich Social Context for Fake News Detection on Short Video Platforms. Proceedings of the AAAI Conference on Artificial Intelligence 37, 12 (2023), 14444–14452. https: //doi.org/10.1609/aaai.v37i12.26689
- [35] Peng Qi, Juan Cao, Xirong Li, Huan Liu, Qiang Sheng, Xiaoyue Mi, Qin He, Yongbiao Lv, Chenyang Guo, and Yingchao Yu. 2021. Improving Fake News Detection by Using an Entity-enhanced Framework to Fuse Diverse Multimodal Clues. In Proceedings of the 29th ACM International Conference on Multimedia. Association for Computing Machinery, 1212–1220. https://doi.org/10.1145/ 3474085.3481548
- [36] Ivan Sekulić, Silvia Terragni, Victor Guimarães, Nghia Khau, Bruna Guedes, Modestas Filipavicius, André Ferreira Manso, and Roland Mathis. 2024. Reliable LLM-based User Simulator for Task-Oriented Dialogue Systems. arXiv preprint arXiv:2402.13374 (2024).
- [37] Qiang Sheng, Juan Cao, H Russell Bernard, Kai Shu, Jintao Li, and Huan Liu. 2022. Characterizing Multi-Domain False News and Underlying User Effects on Chinese Weibo. *Information Processing & Management* 59, 4 (2022), 102959.
- [38] Qiang Sheng, Juan Cao, Xueyao Zhang, Rundong Li, Danding Wang, and Yongchun Zhu. 2022. Zoom Out and Observe: News Environment Perception for Fake News Detection. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). Association for Computational Linguistics, 4543–4556. https://doi.org/10.18653/v1/2022.acl-long.311
- [39] Kai Shu, Limeng Cui, Suhang Wang, Dongwon Lee, and Huan Liu. 2019. dE-FEND: Explainable Fake News Detection. In Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. Association for Computing Machinery, 395–405. https://doi.org/10.1145/3292500.3330935
- [40] Kai Shu, Deepak Mahudeswaran, Suhang Wang, Dongwon Lee, and Huan Liu. 2020. FakeNewsNet: A Data Repository with News Content, Social Context, and Spatiotemporal Information for Studying Fake News on Social Media. *Big Data* 8, 3 (2020), 171–188. https://doi.org/10.1089/big.2020.0062
- [41] Kai Shu, Amy Sliva, Suhang Wang, Jiliang Tang, and Huan Liu. 2017. Fake News Detection on Social Media: A Data Mining Perspective. ACM SIGKDD Explorations Newsletter 19 (2017), 22–36. https://doi.org/10.1145/3137597.3137600

- [42] Kai Shu, Guoqing Zheng, Yichuan Li, Subhabrata Mukherjee, Ahmed Hassan Awadallah, Scott Ruston, and Huan Liu. 2020. Leveraging multi-source weak social supervision for early detection of fake news. arXiv preprint arXiv:2004.01732 (2020).
- [43] Shivangi Singhal, Rajiv Ratn Shah, Tanmoy Chakraborty, Ponnurangam Kumaraguru, and Shin'ichi Satoh. 2019. SpotFake: A Multi-modal Framework for Fake News Detection. In 2019 IEEE Fifth International Conference on Multimedia Big Data (BigMM). 39–47. https://doi.org/10.1109/BigMM.2019.00-44
- [44] Chenkai Sun, Jinning Li, Yi Fung, Hou Chan, Tarek Abdelzaher, ChengXiang Zhai, and Heng Ji. 2023. Decoding the Silent Majority: Inducing Belief Augmented Social Graph with Large Language Model for Response Forecasting. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing. Association for Computational Linguistics, 43–57. https://doi.org/10.18653/v1/2023.emnlp-main.4
- [45] Samia Tasnim, Md Mahbub Hossain, and Hoimonty Mazumder. 2020. Impact of rumors and misinformation on COVID-19 in social media. *Journal of Preventive Medicine and Public Health* 53, 3 (2020), 171–174.
- [46] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288 (2023).
- [47] Arpita Vats, Vinija Jain, Rahul Raja, and Aman Chadha. 2024. Exploring the Impact of Large Language Models on Recommender Systems: An Extensive Review. arXiv preprint arXiv:2402.18590 (2024).
- [48] Soroush Vosoughi, Deb Roy, and Sinan Aral. 2018. The spread of true and false news online. *Science* 359, 6380 (2018), 1146–1151. https://doi.org/10.1126/science. aap9559
- [49] Nathan Walter, Jonathan Cohen, R Lance Holbert, and Yasmin Morag. 2020. Factchecking: A meta-analysis of what works and for whom. *Political communication* 37, 3 (2020), 350–375.
- [50] Herun Wan, Shangbin Feng, Zhaoxuan Tan, Heng Wang, Yulia Tsvetkov, and Minnan Luo. 2024. DELL: Generating Reactions and Explanations for LLM-Based Misinformation Detection. arXiv preprint arXiv:2402.10426 (2024).
- [51] Bo Wang, Jing Ma, Hongzhan Lin, Zhiwei Yang, Ruichao Yang, Yuan Tian, and Yi Chang. 2024. Explainable Fake News Detection with Large Language Model via Defense Among Competing Wisdom. In *Proceedings of the ACM on Web Conference 2024*. Association for Computing Machinery, New York, NY, USA, 2452–2463. https://doi.org/10.1145/3589334.3645471
- [52] Longzheng Wang, Xiaohan Xu, Lei Zhang, Jiarui Lu, Yongxiu Xu, Hongbo Xu, and Chuang Zhang. 2024. MMIDR: Teaching Large Language Model to Interpret Multimodal Misinformation via Knowledge Distillation. arXiv preprint arXiv:2403.14171 (2024).
- [53] Wei Wang, Piji Li, and Hai-Tao Zheng. 2021. Generating Diversified Comments via Reader-Aware Topic Modeling and Saliency Detection. *Proceedings of the* AAAI Conference on Artificial Intelligence 35 (2021), 13988–13996. https://doi. org/10.1609/aaai.v35i16.17647
- [54] Xiaolong Wang, Yile Wang, Sijie Cheng, Peng Li, and Yang Liu. 2024. DEEM: Dynamic Experienced Expert Modeling for Stance Detection. arXiv preprint arXiv:2402.15264 (2024).
- [55] Yaqing Wang, Fenglong Ma, Zhiwei Jin, Ye Yuan, Guangxu Xun, Kishlay Jha, Lu Su, and Jing Gao. 2018. EANN: Event Adversarial Neural Networks for Multi-Modal Fake News Detection. In Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. Association for Computing Machinery, 849–857. https://doi.org/10.1145/3219819.3219903
- [56] Zhengjia Wang, Danding Wang, Qiang Sheng, Juan Cao, Silong Su, Yifan Sun, Beizhe Hu, and Siyuan Ma. 2023. Understanding News Creation Intents: Frame, Dataset, and Method. arXiv preprint arXiv:2312.16490 (2023).
- [57] Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al.

2022. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682* (2022).

- [58] Weibo. 2021. Weibo Community Convention (Trial). https://service.account. weibo.com/roles/gongyue. Accessed: 2024-05-13.
- [59] World Economic Forum. 2024. Global Risks Report 2024. https://www3.weforum. org/docs/WEF\_The\_Global\_Risks\_Report\_2024.pdf. Accessed: 2024-05-13.
   [60] Jiaying Wu and Bryan Hooi. 2023. Fake News in Sheep's Clothing: Robust
- [60] Jiaying Wu and Bryan Hooi. 2023. Fake News in Sheep's Clothing: Robust Fake News Detection Against LLM-Empowered Style Attacks. arXiv preprint arXiv:2310.10830 (2023).
- [61] Lianwei Wu and Yuan Rao. 2020. Adaptive Interaction Fusion Networks for Fake News Detection. In Proceedings of the 24th European Conference on Artificial Intelligence. https://doi.org/10.3233/FAIA200348
- [62] Chengxing Xie, Canyu Chen, Feiran Jia, Ziyu Ye, Kai Shu, Adel Bibi, Ziniu Hu, Philip Torr, Bernard Ghanem, and Guohao Li. 2024. Can Large Language Model Agents Simulate Human Trust Behaviors? arXiv preprint arXiv:2402.04559 (2024).
- [63] Rongwu Xu, Brian S Lin, Shujian Yang, Tianqi Zhang, Weiyan Shi, Tianwei Zhang, Zhixuan Fang, Wei Xu, and Han Qiu. 2023. The Earth is Flat because...: Investigating LLMs' Belief towards Misinformation via Persuasive Conversation. arXiv preprint arXiv:2312.09085 (2023).
- [64] Keyang Xuan, Li Yi, Fan Yang, Ruochen Wu, Yi R Fung, and Heng Ji. 2024. LEMMA: Towards LVLM-Enhanced Multimodal Misinformation Detection with External Knowledge Augmentation. arXiv preprint arXiv:2402.11943 (2024).
- [65] Yuta Yanagi, Ryohei Orihara, Yuichi Sei, Yasuyuki Tahara, and Akihiko Ohsuga. 2020. Fake News Detection with Generated Comments for News Articles. In 2020 IEEE 24th International Conference on Intelligent Engineering Systems. 85–90. https://doi.org/10.1109/INES49302.2020.9147195
- [66] Shuo Yang, Kai Shu, Suhang Wang, Renjie Gu, Fan Wu, and Huan Liu. 2019. Unsupervised Fake News Detection on Social Media: A Generative Approach. Proceedings of the AAAI Conference on Artificial Intelligence 33 (2019), 5644–5651. https://doi.org/10.1609/aaai.v33i01.33015644
- [67] Zhiwei Yang, Jing Ma, Hechang Chen, Hongzhan Lin, Ziyang Luo, and Yi Chang. 2022. A Coarse-to-fine Cascaded Evidence-Distillation Neural Network for Explainable Fake News Detection. In Proceedings of the 29th International Conference on Computational Linguistics. International Committee on Computational Linguistics, Gyeongju, Republic of Korea, 2608–2621. https: //aclanthology.org/2022.coling-1.230
- [68] Ze Yang, Can Xu, Wei Wu, and Zhoujun Li. 2019. Read, Attend and Comment: A Deep Architecture for Automatic News Comment Generation. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). Association for Computational Linguistics, 5077–5089. https://doi.org/ 10.18653/v1/D19-1512
- [69] Erxin Yu, Jing Li, and Chunpu Xu. 2024. PopALM: Popularity-Aligned Language Models for Social Media Trendy Response Prediction. arXiv preprint arXiv:2402.18950 (2024).
- [70] Feng Yu, Qiang Liu, Shu Wu, Liang Wang, and Tieniu Tan. 2017. A Convolutional Approach for Misinformation Identification. In Proceedings of the 26th International Joint Conference on Artificial Intelligence. AAAI Press, 3901–3907. https://doi.org/10.24963/ijcai.2017/545
- [71] Xueyao Zhang, Juan Cao, Xirong Li, Qiang Sheng, Lei Zhong, and Kai Shu. 2021. Mining Dual Emotion for Fake News Detection. In *Proceedings of the Web Conference 2021*. Association for Computing Machinery, 3465–3476. https: //doi.org/10.1145/3442381.3450004
- [72] Yuchen Zhang, Xiaoxiao Ma, Jia Wu, Jian Yang, and Hao Fan. 2024. Heterogeneous Subgraph Transformer for Fake News Detection. In *Proceedings of the* ACM on Web Conference 2024. Association for Computing Machinery, 1272–1282. https://doi.org/10.1145/3589334.3645680
- [73] Zhipu AI. 2024. GLM-4. https://open.bigmodel.cn/dev/howuse/glm4. Accessed: 2024-03-05.
- [74] Yongchun Zhu, Qiang Sheng, Juan Cao, Shuokai Li, Danding Wang, and Fuzhen Zhuang. 2022. Generalizing to the Future: Mitigating Entity Bias in Fake News Detection. In Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval. Association for Computing Machinery, 2120–2125. https://doi.org/10.1145/3477495.3531816
- [75] Yongchun Zhu, Qiang Sheng, Juan Cao, Qiong Nan, Kai Shu, Minghui Wu, Jindong Wang, and Fuzhen Zhuang. 2023. Memory-Guided Multi-View Multi-Domain Fake News Detection. *IEEE Transactions on Knowledge and Data Engineering* 35, 7 (2023), 7178–7191. https://doi.org/10.1109/TKDE.2022.3185151
- [76] Hanyi Zou, Nan Xu, Qingchao Kong, and Wenji Mao. 2023. Controllable News Comment Generation based on Attribute Level Contrastive Learning. In 2023 IEEE International Conference on Intelligence and Security Informatics. 1–6. https: //doi.org/10.1109/ISI58743.2023.10297146