

On the Formalization of the Notion of an Interactive Algorithm

C.A. Middelburg

ORCID: <https://orcid.org/0000-0002-8725-0197>

Informatics Institute, Faculty of Science, University of Amsterdam
Science Park 900, 1098 XH Amsterdam, the Netherlands

C.A.Middelburg@uva.nl

Abstract. An earlier paper gives an account of a quest for a satisfactory formalization of the classical informal notion of an algorithm. In this paper, an attempt is made to generalize the results of that quest to the informal notion of an interactive algorithm. The notion of an interactive proto-algorithm is introduced. Interactive algorithms are expected to be equivalence classes of interactive proto-algorithms under an appropriate equivalence relation. As in the non-interactive case, three equivalence relations are defined. Two of them are deemed to be bounds for an appropriate equivalence relation and the third is likely an appropriate one.

Keywords: interactive algorithm · interactive proto-algorithm · algorithmic equivalence · computational equivalence

1 Introduction

In many works from the mathematical and computer science literature, including standard works such as [7,8,10,12], the notion of an algorithm is informally characterized by properties that are considered the most important ones of an algorithm. Most of those characterizations agree with each other and indicate that an algorithm is considered to express a pattern of behaviour by which all instances of a computational problem can be solved. In [11] is reported on a quest for a satisfactory formalization of the classical informal notion of an algorithm. The notion of a proto-algorithm defined in that paper has most properties that are generally considered to belong to the important ones of an algorithm and moreover does not depend on any particular machine model or algorithmic language. This makes it neither too concrete nor too abstract to be an suitable basis for investigating what exactly an algorithm is in the setting of the currently predominant type of computation, namely interactive computation.

The algorithms of the kind that emerged due to the advent of interactive computation are usually called interactive algorithms. They are mainly described with sentences like “An interactive algorithm is an algorithm that can interact with the environment in which it is applied”. However, there is no consensus on which properties characterize interactive algorithms well. In [2], a specific view on the nature of interactive algorithms is discussed in detail, culminating in a

characterization of interactive algorithms by a number of postulates. The view concerned is the only one found in the computer science literature so far. Some of its details are based on choices whose impact on the generality of the characterization is not clear. Despite the fact that interactive algorithms are currently widespread, no other work aimed at a satisfactory formalization of the notion of an interactive algorithm has been reported in the computer science literature. This state of affairs motivated me to start a quest for a satisfactory formalization of the notion of an interactive algorithm. The ultimate goal of this quest is to provide a semantic basis for languages to describe interactive algorithms.

Due to the advent of interactive computation, several related models of interactive computation have been proposed. They are based on variants of Turing machines, to wit interactive Turing machines [9], persistent Turing machines [5], and reactive Turing machines [1]. In this paper, the starting point for the formalization of the notion of an interactive algorithm is a characterization of the notion by properties suggested by those models of interactive computation. Based on that, the notion of an interactive proto-algorithm is introduced. Like the notion of a proto-algorithm, the notion of an interactive proto-algorithm is introduced with the thought that interactive algorithms are equivalence classes of interactive proto-algorithms under an appropriate equivalence relation. Three equivalence relations on interactive proto-algorithms are defined. Two of them give bounds for an appropriate equivalence relation and the third one is likely an appropriate one.

This paper is organized as follows. First, an intuitive characterization of the notion of an interactive algorithm is given by properties that are considered to belong to the most important ones of an interactive algorithm (Section 2). Next, the formal notion of an interactive proto-algorithm is introduced and the isomorphism relation on interactive proto-algorithms is defined (Section 3). After that, it is defined what a run of an interactive proto-algorithm is and what is computed by an interactive proto-algorithm (Section 4). Then, two equivalence relations on interactive proto-algorithms are defined (Section 5). Finally, some concluding remarks are made (Section 6).

In this paper, an attempt is made to generalize the work on the classical notion of an algorithm presented in [11] to the notion of an interactive algorithm. In Sections 2 and 3, this has led to text overlap with [11].

2 The Informal Notion of an Interactive Algorithm

In this paper, the notion of a classical algorithm concerns the original notion of an algorithm, i.e. the notion that is intuitively characterized in standard works from the mathematical and computer science literature such as [7,8,10,12], and the notion of an interactive algorithm concerns a generalization of the original notion of an algorithm. What are interactive algorithms according to this notion are sometimes called sequential interactive algorithms in the computer science literature. Seeing the terminology used for proposed generalizations of the origi-

nal notion of an algorithm, a classical algorithm could also be called a sequential non-interactive algorithm.

Because a classical algorithm is considered to express a pattern of behaviour by which all instances of a classical computational problem can be solved, a classical computational problem should be described without reference to the notion of a classical algorithm:

A classical computational problem is a problem where, given a value from a certain set of input values, a value from a certain set of output values that is in a certain relation to the given input value must be produced if it exists. The input values are also called the instances of the problem and an output value that is in the certain relation to a given input value is also called a solution for the instance concerned.

From the existing viewpoints on what a classical algorithm is, it follows that the following properties must be considered the most important ones of a classical algorithm:

1. a classical algorithm is a finite expression of a pattern of behaviour by which all instances of a classical computational problem can be solved;
2. the pattern of behaviour expressed by a classical algorithm is made up of discrete steps, each of which consists of performing an elementary operation or inspecting an elementary condition unless it is the initial step or a final step;
3. the pattern of behaviour expressed by a classical algorithm is such that there is one possible step immediately following a step that consists of performing an operation;
4. the pattern of behaviour expressed by a classical algorithm is such that there is one possible step immediately following a step that consists of inspecting a condition for each outcome of the inspection;
5. the pattern of behaviour expressed by a classical algorithm is such that the initial step consists of inputting an input value of the problem concerned;
6. the pattern of behaviour expressed by a classical algorithm is such that, for each input value of the problem concerned for which a correct output value exists, a final step is reached after a finite number of steps and that final step consists of outputting a correct output value for that input value;
7. the steps involved in the pattern of behaviour expressed by a classical algorithm are precisely and unambiguously defined and can be performed exactly in a finite amount of time.

The viewpoints on interactive computation that are expressed in computer science publications such as [3,5,9] are the basis of the following description of an interactive computational problem:

An interactive computational problem is a problem where, given a possibly infinite sequence of values from a certain set of input values, a possibly infinite sequence of values from a certain set of output values that is in a certain causal relation to the given sequence of input values

must be produced if it exists. Causal here means that, for each n , for each two sequences of input values with a common prefix of length n , for each sequence of output values with a prefix of length n that is related to one of those two sequences of input values, there exists a sequence of output values with the same prefix that is related to the other of those two sequences of input values. The sequences of input values are called the instances of the problem and a sequence of output values that is in the certain relation to a given sequence of input values is called a solution for the instance concerned.

Classical computational problems can be considered the simplest interactive computational problems.

Classical algorithms are not adequate for solving interactive computational problems. From the viewpoints on interactive computation referred to above, it follows that:

- with the exception of properties 2 and 6, the most important properties of a classical algorithm are also considered to belong to the most important properties of an interactive algorithm;
- the following generalizations of properties 2 and 6 are considered to belong to the most important properties of an interactive algorithm:
 - 2'. the pattern of behaviour expressed by an interactive algorithm is made up of discrete steps, each of which consists of performing an elementary operation or inspecting an elementary condition unless it is the initial step, a final step, an input step or an output step;
 - 6'. the pattern of behaviour expressed by an interactive algorithm is such that, for each finite sequence of input values of the problem concerned for which a correct sequence of output values exists, after this sequence has been inputted, a final step is reached after a finite number of steps and that final step consists of outputting the last output value of a correct sequence of output values;
- the following property is also considered to belong to the most important ones of an interactive algorithm:
 - 8. the pattern of behaviour expressed by an interactive algorithm is such that:
 - a. there is one possible step immediately following a step that is an input step or an output step;
 - b. an input step immediately follows an output step and an output step is immediately followed by an input step;
 - c. an input step consists of inputting an input value of the problem concerned and an output step consists of outputting an output value that is correct for the sequence of input values inputted so far.

Properties 1, 2', 3, 4, 5, 6', 7, and 8 give an intuitive characterization of the notion of an interactive algorithm and form the starting point for the formalization of this notion in upcoming sections. They have been derived from the viewpoints on interactive computation that are expressed in computer science

publications such as [3,5,9]. In those publications, it is usually mentioned at most in passing that an interactive algorithm expresses a pattern of behaviour. Following [4], this point is central here.

The characterization of the notion of an interactive algorithm given by the above-mentioned properties of an interactive algorithm reflects a rather operational view of what an interactive algorithm is. In a more abstract view of what an interactive algorithm is, an interactive algorithm expresses a collection of patterns of behaviour that are equivalent in some well-defined way. We will come back to this at the end of Section 3.

3 Interactive Proto-Algorithms

In this section, the notion of an interactive proto-algorithm is introduced. The thought is that interactive algorithms are equivalence classes of interactive proto-algorithms under an appropriate equivalence relation. An equivalence relation that is likely an appropriate one is introduced in Section 5.

The notion of an interactive proto-algorithm will be defined in terms of three auxiliary notions. The definition of one of these auxiliary notions is based on the well-known notion of a rooted labeled directed graph. However, the definitions of this notion given in the mathematical and computer science literature vary. Therefore, the definition that is used in this paper is given first.

Definition. A rooted labeled directed graph G is a sextuple (V, E, L_v, L_e, l, r) , where:

- V is a non-empty finite set, whose members are called the vertices of G ;
- E is a subset of $V \times V$, whose members are called the edges of G ;
- L_v is a countable set, whose members are called the vertex labels of G ;
- L_e is a countable set, whose members are called the edge labels of G ;
- l is a partial function from $V \cup E$ to $L_v \cup L_e$ such that
 - for all $v \in V$ for which $l(v)$ is defined, $l(v) \in L_v$ and
 - for all $e \in E$ for which $l(e)$ is defined, $l(e) \in L_e$,
 called the labeling function of G ;
- $r \in V$, called the root of G .

The additional graph theoretical notions defined below are also used in this paper.

Definition. Let $G = (V, E, L_v, L_e, l, r)$ be a rooted labeled directed graph. Then a cycle in G is a sequence $v_1 \dots v_{n+1} \in V^*$ such that, for all $i \in \{1, \dots, n\}$, $(v_i, v_{i+1}) \in E$, $\text{card}(\{v_1, \dots, v_n\}) = n$, and $v_1 = v_{n+1}$. Let, moreover, $v \in V$. Then the indegree of v , written $\text{indegree}(v)$, is $\text{card}(\{v' \mid (v', v) \in E\})$ and the outdegree of v , written $\text{outdegree}(v)$, is $\text{card}(\{v' \mid (v, v') \in E\})$.

We proceed with defining the three auxiliary notions, starting with the notion of an alphabet. This notion concerns the symbols used to refer to the operations and conditions involved in the steps of which the pattern of behaviour expressed by an interactive algorithm is made up.

Definition. An alphabet Σ is a couple (F, P) , where:

- F is a countable set, whose members are called the function symbols of Σ ;
- P is a countable set, whose members are called the predicate symbols of Σ ;
- F and P are disjoint sets and $\text{ini}, \text{fin}, \text{in}, \text{out} \in F$.

We write \tilde{F} , where F is the set of function symbols of an alphabet, for the set $F \setminus \{\text{ini}, \text{fin}, \text{in}, \text{out}\}$.

The function symbols and predicate symbols of an alphabet refer to the operations and conditions, respectively, involved in the steps of which the pattern of behaviour expressed by an interactive algorithm is made up. The function symbols ini and fin refer to inputting a first input value and outputting a last output value, respectively, and the function symbols in and out refer to inputting a non-first input value and outputting a non-last output value, respectively.

We are now ready to define the notions of an interactive- Σ -algorithm graph and a Σ -interpretation. They concern the pattern of behaviour expressed by an interactive algorithm.

Definition. Let $\Sigma = (F, P)$ be an alphabet. Then an interactive- Σ -algorithm graph G is a rooted labeled directed graph (V, E, L_v, L_e, l, r) such that

- $L_v = F \cup P$;
- $L_e = \{0, 1\}$;
- for all $v \in V$:
 - $l(v) = \text{ini}$ iff $v = r$;
 - if $l(v) = \text{ini}$, then $\text{indegree}(v) = 0$, $\text{outdegree}(v) = 1$, and, for the unique $v' \in V$ for which $(v, v') \in E$, $l((v, v'))$ is undefined;
 - if $l(v) = \text{fin}$, then $\text{indegree}(v) > 0$ and $\text{outdegree}(v) = 0$;
 - if $l(v) \in \tilde{F} \cup \{\text{in}, \text{out}\}$, then $\text{indegree}(v) > 0$, $\text{outdegree}(v) = 1$, and, for the unique $v' \in V$ for which $(v, v') \in E$, $l((v, v'))$ is undefined;
 - if $l(v) \in P$, then $\text{indegree}(v) > 0$, $\text{outdegree}(v) = 2$, and, for the unique $v' \in V$ and $v'' \in V$ with $v' \neq v''$ for which $(v, v') \in E$ and $(v, v'') \in E$, $l((v, v'))$ is defined, $l((v, v''))$ is defined, and $l((v, v')) \neq l((v, v''))$;
- for all $(v, v') \in E$, $l(v) = \text{out}$ iff $l(v') = \text{in}$;
- for all cycles $v_1 \dots v_{n+1}$ in G , there exists a $v \in \{v_1, \dots, v_n\}$ such that $l(v) \in F$.

Interactive- Σ -algorithm graphs are somewhat reminiscent of program schemes as defined, for example, in [13].

In the above definition, the condition on cycles in an interactive- Σ -algorithm graph excludes infinitely many consecutive steps, each of which consists of inspecting a condition.

In the above definition, the conditions regarding the vertices and edges of an interactive- Σ -algorithm graph correspond to the essential properties of an interactive algorithm mentioned in Section 2 that concern its structure. Adding an interpretation of the symbols of the alphabet Σ to an interactive- Σ -algorithm graph yields something that has all of the mentioned essential properties of an interactive algorithm.

Definition. Let $\Sigma = (F, P)$ be an alphabet. Then a Σ -interpretation \mathcal{I} is a quadruple (D, D_i, D_o, I) , where:

- D is a set, called the main domain of \mathcal{I} ;
- D_i is a set, called the input domain of \mathcal{I} ;
- D_o is a set, called the output domain of \mathcal{I} ;
- I is a total function from $F \cup P$ to the set of all total computable functions from D_i to D , D to D_o , D to D or D to $\{0, 1\}$ such that:
 - $I(\text{ini})$ is a function from D_i to D ;
 - $I(\text{fin})$ is a function from D to D_o ;
 - $I(\text{in})$ is a function from $D \times D_i$ to D ;
 - $I(\text{out})$ is a function from D to D_o ;
 - for all $f \in \bar{F}$, $I(f)$ is a function from D to D ;
 - for all $p \in P$, $I(p)$ is a function from D to $\{0, 1\}$;
- there does not exist a $D' \subset D$ such that:
 - for all $d_i \in D_i$, $I(\text{ini})(d_i) \in D'$;
 - for all $d_i \in D_i$, for all $d \in D'$, $I(\text{in})(d, d_i) \in D'$;
 - for all $f \in \bar{F}$, for all $d \in D'$, $I(f)(d) \in D'$.

The minimality condition on D in the above definition is considered desirable, but has not yet proven essential.

The pattern of behavior expressed by an interactive algorithm can be fully represented by the combination of an alphabet Σ , an interactive- Σ -algorithm graph G , and a Σ -interpretation \mathcal{I} . This brings us to defining the notion of an interactive proto-algorithm.

Definition. An interactive proto-algorithm A is a triple (Σ, G, \mathcal{I}) , where:

- Σ is an alphabet, called the alphabet of A ;
- G is an interactive- Σ -algorithm graph, called the algorithm graph of A ;
- \mathcal{I} is a Σ -interpretation, called the interpretation of A .

Henceforth, we assume a dummy value \perp such that, for all interactive proto-algorithms $A = (\Sigma, G, \mathcal{I})$, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$, $\perp \notin D_i$, $\perp \notin D_o$, and $\perp \notin V \times D$.

The intuition is that an interactive proto-algorithm is something that goes from one state to another.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$. Then a state of A is a triple $(d_i, c, d_o) \in (D_i \cup \perp) \times ((V \times D) \cup \perp) \times (D_o \cup \perp)$ such that:

- if $c \neq \perp$, then $d_i = \perp$ iff $d_o = \perp$;
- if $c = \perp$, then $d_i = \perp$ iff $d_o \neq \perp$.

A state $s \in D_i \times \{\perp\} \times \{\perp\}$ is called an *initial state*, a state $s \in \{\perp\} \times \{\perp\} \times D_o$ is called a *final state*, a state $s \in \{\perp\} \times (V \times D) \times \{\perp\}$ is called an *internal state*, and a state $s \in D_i \times (V \times D) \times D_o$ is called an *interaction state*.

Henceforth, we write \mathcal{S}_A , where A is an interactive proto-algorithm, for the set of all states of A . We write $\mathcal{S}_A^{\text{ini}}$, $\mathcal{S}_A^{\text{fin}}$, and $\mathcal{S}_A^{\text{int}}$ for the subsets $D_i \times \{\perp\} \times \{\perp\}$, $\{\perp\} \times \{\perp\} \times D_o$, and $\{\perp\} \times (V \times D) \times \{\perp\}$, respectively, of \mathcal{S}_A .

Suppose that $A = (\Sigma, G, \mathcal{I})$ is an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$. A goes from one state to the next state by making a step, it starts in an initial state, and if it does not keep making steps forever, it stops in a final state. The following is an informal explanation of how the state that A is in determines what the step to the next state consists of and what the next state is:

- if A is in initial state (d_i, \perp, \perp) and $l(v) = \text{ini}$, then the step to the next state consists of applying function $I(\text{ini})$ to d_i and the next state is the unique internal state $(\perp, (v', d'), \perp)$ such that $(r, v') \in E$, and $I(\text{ini})(d_i) = d'$;
- if A is in internal state $(\perp, (v, d), \perp)$ and $l(v) \in \tilde{F}$, then the step to the next state consists of applying function $I(l(v))$ to d and the next state is the unique internal state $(\perp, (v', d'), \perp)$ such that $(v, v') \in E$, and $I(l(v))(d) = d'$;
- if A is in internal state $(\perp, (v, d), \perp)$ and $l(v) \in P$, then the step to the next state consists of applying function $I(l(v))$ to d and the next state is the unique internal state $(\perp, (v', d), \perp)$ such that $(v, v') \in E$, and $I(l(v))(d) = l((v, v'))$;
- if A is in internal state $(\perp, (v, d), \perp)$ and $l(v) = \text{out}$, then the step to the next state consists of applying function $I(\text{out})$ to d and the next state is an interaction state $(d_i, (v', d), d_o)$ such that $(v, v') \in E$, $I(\text{out})(d) = d_o$, and $d_i \in D_i$;
- if A is in interaction state $(d_i, (v, d), d_o)$ and $l(v) = \text{in}$, then the step to the next state consists of applying function $I(\text{in})$ to (d, d_i) and the next state is the unique internal state $(\perp, (v', d'), \perp)$ such that $(v, v') \in E$ and $I(\text{in})(d, d_i) = d'$;
- if A is in internal state $(\perp, (v, d), \perp)$ and $l(v) = \text{fin}$, then the step to the next state consists of applying function $I(\text{fin})$ to d and the next state is the unique final state (\perp, \perp, d_o) such that $I(\text{fin})(d) = d_o$.

This informal explanation of how the state that A is in determines what the next state is, is formalized by the algorithmic step function δ_A^a defined in Section 4.

A classical proto-algorithm is a special case of an interactive proto-algorithm.

Definition. A classical proto-algorithm is an interactive proto-algorithm (Σ, G, \mathcal{I}) , where $G = (V, E, L_v, L_e, l, r)$, such that, for all $v \in V$, $l(v) \notin \{\text{in}, \text{out}\}$.

Classical proto-algorithms are called proto-algorithms in [11]. Most definitions and results concerning interactive proto-algorithms from this paper are generalizations of definitions and results from that paper.

Because interactive proto-algorithms are considered too concrete to be called interactive algorithms the term interactive proto-algorithm has been chosen instead of the term interactive algorithm. For example, from a mathematical point

of view, it is natural to consider the behavioral patterns expressed by isomorphic interactive proto-algorithms to be the same. Isomorphism of interactive proto-algorithms is defined as expected.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ and $A' = (\Sigma', G', \mathcal{I}')$ be interactive proto-algorithms, where $\Sigma = (F, P)$, $\Sigma' = (F', P')$, $G = (V, E, L_v, L_e, l, r)$, $G' = (V', E', L'_v, L'_e, l', r')$, $\mathcal{I} = (D, D_i, D_o, I)$, and $\mathcal{I}' = (D', D'_i, D'_o, I')$. Then A and A' are isomorphic, written $A \cong A'$, if there exist bijections $\beta_f : F \rightarrow F'$, $\beta_p : P \rightarrow P'$, $\beta_v : V \rightarrow V'$, $\beta_d : D \rightarrow D'$, $\beta_i : D_i \rightarrow D'_i$, $\beta_o : D_o \rightarrow D'_o$, and $\beta_b : \{0, 1\} \rightarrow \{0, 1\}$ such that:

- $\beta_f(\text{ini}) = \text{ini}$ and $\beta_f(\text{fin}) = \text{fin}$;
- for all $v, v' \in V$, $(v, v') \in E$ iff $(\beta_v(v), \beta_v(v')) \in E'$;
- for all $v \in V$ with $l(v) \in F$, $\beta_f(l(v)) = l'(\beta_v(v))$;
- for all $v \in V$ with $l(v) \in P$, $\beta_p(l(v)) = l'(\beta_v(v))$;
- for all $(v, v') \in E$ with $l((v, v'))$ is defined, $\beta_b(l((v, v'))) = l'((\beta_v(v), \beta_v(v')))$;
- for all $d_i \in D_i$, $\beta_d(I(\text{ini})(d_i)) = I'(\text{ini})(\beta_i(d_i))$;
- for all $d \in D$, $\beta_o(I(\text{fin})(d)) = I'(\text{fin})(\beta_d(d))$;
- for all $d \in D$, for all $d_i \in D_i$, $\beta_d(I(\text{in})(d, d_i)) = I'(\text{in})(\beta_d(d), \beta_i(d_i))$;
- for all $d \in D$, $\beta_o(I(\text{out})(d)) = I'(\text{out})(\beta_d(d))$;
- for all $d \in D$ and $f \in \tilde{F}$, $\beta_d(I(f)(d)) = I'(\beta_f(f))(\beta_d(d))$;
- for all $d \in D$ and $p \in P$, $\beta_b(I(p)(d)) = I'(\beta_p(p))(\beta_d(d))$.

It is intuitive clear what isomorphism of interactive proto-algorithms is. Unfortunately, its precise definition is not easy to memorize.

Interactive proto-algorithms may also be considered too concrete in a way not covered by isomorphism of interactive proto-algorithms. This issue is addressed in Section 5 and leads there to the introduction of two other equivalence relations.

An interactive proto-algorithm could also be defined as a quadruple $(D, D_i, D_o, \overline{G})$ where \overline{G} is a graph that differs from a interactive- Σ -algorithm graph in that its vertex labels are computable functions from D_i to D , D to D_o , D to D or D to $\{0, 1\}$ instead of function and predicate symbols from Σ . I consider the definition of a interactive proto-algorithm given earlier more insightful because it isolates as much as possible the operations to be performed and the conditions to be inspected from its structure.

4 On Steps, Runs and What is Computed

In Section 3, the intuition was given that an interactive proto-algorithm A is something that goes through states. It was informally explained how the state that it is in determines what the step to the next state consists of and what the next state is. The algorithmic step function δ_A^a that is defined below formalizes this. The computational step function δ_A^c that is also defined below is like the algorithmic step function δ_A^a , but conceals the steps that consist of inspecting conditions.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$. Then the algorithmic step function δ_A^a induced by A is the total function from \mathcal{S}_A to $\mathcal{P}(\mathcal{S}_A) \setminus \emptyset$ such that for all $d, d' \in D$, $d_i \in D_i$, $d_o \in D_o$, and $v, v' \in V$:¹

$$\begin{aligned}
(\perp, (v', d), \perp) \in \delta_A^a((d_i, \perp, \perp)) & \quad \text{iff } l(r) = \text{ini}, (r, v') \in E, \text{ and} \\
& \quad I(\text{ini})(d_i) = d, \\
(\perp, (v', d'), \perp) \in \delta_A^a((\perp, (v, d), \perp)) & \quad \text{iff } l(v) \in \tilde{F}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d) = d', \\
(\perp, (v', d), \perp) \in \delta_A^a((\perp, (v, d), \perp)) & \quad \text{iff } l(v) \in P, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d) = l((v, v')), \\
(d_i, (v', d), d_o) \in \delta_A^a((\perp, (v, d), \perp)) & \quad \text{iff } l(v) = \text{out}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d) = d_o, \\
(\perp, (v', d'), \perp) \in \delta_A^a((d_i, (v, d), d_o)) & \quad \text{iff } l(v) = \text{in}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d, d_i) = d', \\
(\perp, \perp, d_o) \in \delta_A^a((\perp, (v, d), \perp)) & \quad \text{iff } l(v) = \text{fin} \text{ and} \\
& \quad I(\text{fin})(d) = d_o, \\
(\perp, \perp, d_o) \in \delta_A^a((\perp, \perp, d_o)) &
\end{aligned}$$

and the computational step function δ_A^c induced by A is the total function from \mathcal{S}_A to $\mathcal{P}(\mathcal{S}_A) \setminus \emptyset$ such that, for all $d, d' \in D$, $d_i \in D_i$, $d_o \in D_o$, and $v, v', v'' \in V$:

$$\begin{aligned}
(\perp, (v', d), \perp) \in \delta_A^c((d_i, \perp, \perp)) & \quad \text{iff } l(r) = \text{ini}, (r, v') \in E, \text{ and} \\
& \quad I(\text{ini})(d_i) = d, \\
(\perp, (v', d'), \perp) \in \delta_A^c((\perp, (v, d), \perp)) & \quad \text{iff } l(v) \in \tilde{F}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d) = d', \\
(\perp, (v'', d'), \perp) \in \delta_A^c((\perp, (v, d), \perp)) & \quad \text{iff } l(v) \in P, (v, v') \in E, \\
& \quad I(l(v))(d) = l((v, v')), \text{ and} \\
& \quad (\perp, (v'', d'), \perp) \in \delta_A^c((\perp, (v', d), \perp)), \\
(d_i, (v', d), d_o) \in \delta_A^c((\perp, (v, d), \perp)) & \quad \text{iff } l(v) = \text{out}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d) = d_o, \\
(\perp, (v', d'), \perp) \in \delta_A^c((d_i, (v, d), d_o)) & \quad \text{iff } l(v) = \text{in}, (v, v') \in E, \text{ and} \\
& \quad I(l(v))(d, d_i) = d', \\
(\perp, \perp, d_o) \in \delta_A^c((\perp, (v, d), \perp)) & \quad \text{iff } l(v) = \text{fin} \text{ and} \\
& \quad I(\text{fin})(d) = d_o, \\
(\perp, \perp, d_o) \in \delta_A^c((\perp, \perp, d_o)) &
\end{aligned}$$

Below, we define what a run of an interactive proto-algorithm is and what is computed by an interactive proto-algorithm. To this end, we first introduce some auxiliary definitions.

¹ We write $\mathcal{P}(S)$, where S is a set, for the powerset of S .

In the coming definitions, we write \mathcal{A}^∞ for the set of all sequences over \mathcal{A} that are finite or countably infinite, $\langle \rangle$ for the empty sequence, $\langle a \rangle$ for the sequence having a as sole element, $\alpha \frown \alpha'$ for the concatenation of sequences α and α' , and $\alpha[n]$ for the n th element of the sequence α if there exists a prefix of α with length n and otherwise the last element of α .

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$. Then the algorithmic semi-run set function srs_A^a induced by A and the computational semi-run set function srs_A^c induced by A are the total functions from \mathcal{S}_A to $\mathcal{P}(\mathcal{S}_A^\infty)$ such that for all $s \in \mathcal{S}_A$:

$$\begin{aligned} srs_A^a(s) &= \{\langle s \rangle \frown \sigma \mid (\exists s' \in \delta_A^a(s)) \sigma \in srs_A^a(s')\} \text{ if } s \notin \mathcal{S}^{\text{fin}}, \\ srs_A^a(s) &= \{s\} \text{ if } s \in \mathcal{S}^{\text{fin}}. \end{aligned}$$

and

$$\begin{aligned} srs_A^c(s) &= \{\langle s \rangle \frown \sigma \mid (\exists s' \in \delta_A^c(s)) \sigma \in srs_A^c(s')\} \text{ if } s \notin \mathcal{S}^{\text{fin}}, \\ srs_A^c(s) &= \{s\} \text{ if } s \in \mathcal{S}^{\text{fin}}. \end{aligned}$$

Moreover, the input value stream extraction function ivs_A for A and the output value stream extraction function ovs_A for A are the total functions from \mathcal{S}_A^∞ to D_i^∞ and D_o^∞ , respectively, such that for all $d_i \in D_i \cup \{\perp\}$, $d_o \in D_o \cup \{\perp\}$, $c \in (V \times D) \cup \{\perp\}$, and $\sigma \in \mathcal{S}_A^\infty$:

$$\begin{aligned} ivs_A((d_i, c, d_o) \frown \sigma) &= d_i \frown ivs_A(\sigma) \text{ if } d_i \neq \perp, \\ ivs_A((d_i, c, d_o) \frown \sigma) &= ivs_A(\sigma) \text{ if } d_i = \perp, \\ ivs_A(\langle \rangle) &= \langle \rangle \end{aligned}$$

and

$$\begin{aligned} ovs_A((d_i, c, d_o) \frown \sigma) &= d_o \frown ovs_A(\sigma) \text{ if } d_o \neq \perp, \\ ovs_A((d_i, c, d_o) \frown \sigma) &= ovs_A(\sigma) \text{ if } d_o = \perp, \\ ovs_A(\langle \rangle) &= \langle \rangle. \end{aligned}$$

The following definition concerns what a run of an interactive proto-algorithm is. As with steps, a distinction is made between algorithmic runs and computational runs.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$, and let $\alpha \in D_i^\infty$. Then the algorithmic run of A on α , written $\rho_A^a(\alpha)$, is the unique $\sigma \in srs_A^a((\alpha[1], \perp, \perp))$ such that $ivs_A(\sigma) = \alpha$ and the computational run of A on α , written $\rho_A^c(\alpha)$, is the unique $\sigma \in srs_A^c((\alpha[1], \perp, \perp))$ such that $ivs_A(\sigma) = \alpha$.

The existence of a unique $\sigma \in srs_A^a((\alpha[1], \perp, \perp))$ or $\sigma \in srs_A^c((\alpha[1], \perp, \perp))$ such that $ivs(\sigma) = \alpha$ assumed in the above definitions is easily proved by transfinite induction on the length of α .

When defining what is computed by an interactive proto-algorithm, a distinction must be made between convergent runs and divergent runs.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, and let $\sigma \in \mathcal{S}_A^\infty$. Then σ is divergent if there exists a suffix σ' of σ such that $\sigma' \in \mathcal{S}_A^{\text{int}\infty}$, and σ is convergent if σ is not divergent.

The following definition concerns what is computed by an interactive proto-algorithm.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ be an interactive proto-algorithm, where $\Sigma = (F, P)$, $G = (V, E, L_v, L_e, l, r)$, and $\mathcal{I} = (D, D_i, D_o, I)$. Then the function \widehat{A} computed by A is the partial function from D_i^∞ to D_o^∞ such that for all $\alpha \in D_i^\infty$:

$$\begin{aligned} \widehat{A}(\alpha) &= \text{ovs}(\rho_A^a(\alpha)) \text{ if } \rho_A^a(\alpha) \text{ is convergent,} \\ \widehat{A}(\alpha) &\text{ is undefined if } \rho_A^a(\alpha) \text{ is divergent.} \end{aligned}$$

Let, moreover, $\alpha \in D_i^*$ be such that $\widehat{A}(\alpha)$ is defined. Then the number of algorithmic steps to compute $\widehat{A}(\alpha)$ by A , written $\#_{\text{astep}}(A, \alpha)$, is the length of $\rho_A^a(\alpha)$.

5 Algorithmic and Computational Equivalence

If an interactive proto-algorithm A' can mimic an interactive proto-algorithm A step-by-step, then we say that A is algorithmically simulated by A' . If the steps that consist of inspecting conditions are ignored, then we say that A is computationally simulated by A' . Algorithmic and computational simulation can be formally defined using the step functions defined in Section 4.

Definition. Let $A = (\Sigma, G, \mathcal{I})$ and $A' = (\Sigma', G', \mathcal{I}')$ be two interactive proto-algorithms, where $G = (V, E, L_v, L_e, l, r)$, $G' = (V', E', L'_v, L'_e, l', r')$, $\mathcal{I} = (D, D_i, D_o, I)$, and $\mathcal{I}' = (D', D'_i, D'_o, I')$. Then an algorithmic simulation of A by A' is a set $R \subseteq \mathcal{S}_A \times \mathcal{S}_{A'}$ such that:

- for all $s \in \mathcal{S}_A$ and $s' \in \mathcal{S}_{A'}$:
 - if $s \in \mathcal{S}_A^{\text{ini}}$, then there exists an $s' \in \mathcal{S}_{A'}^{\text{ini}}$ such that $(s, s') \in R$;
 - if $s' \in \mathcal{S}_{A'}^{\text{fin}}$, then there exists an $s \in \mathcal{S}_A^{\text{fin}}$ such that $(s, s') \in R$;
 - if $(s, s') \in R$ and $t \in \delta_A^a(s)$, then there exists a $t' \in \delta_{A'}^a(s')$ such that $(t, t') \in R$;
- for all $((d_i, c, d_o), (d'_i, c', d'_o)) \in R$:
 - $d_i = \perp$ iff $d'_i = \perp$;
 - $d_o = \perp$ iff $d'_o = \perp$;
- there exist total functions $\gamma_i : D_i \rightarrow D'_i$ and $\gamma_o : D_o \rightarrow D'_o$ such that for all $((d_i, c, d_o), (d'_i, c', d'_o)) \in R$:
 - if $d_i \neq \perp$, then $d'_i = \gamma_i(d_i)$;
 - if $d'_o \neq \perp$, then $d_o = \gamma_o(d'_o)$

and a computational simulation of A by A' is a set $R \subseteq \mathcal{S}_A \times \mathcal{S}_{A'}$ such that:

- for all $s \in \mathcal{S}_A$ and $s' \in \mathcal{S}_{A'}$:
 - if $s \in \mathcal{S}_A^{\text{ini}}$, then there exists an $s' \in \mathcal{S}_{A'}^{\text{ini}}$ such that $(s, s') \in R$;

- if $s' \in \mathcal{S}_{A'}^{\text{fin}}$, then there exists an $s \in \mathcal{S}_A^{\text{fin}}$ such that $(s, s') \in R$;
- if $(s, s') \in R$ and $t \in \delta_A^c(s)$, then there exists a $t' \in \delta_{A'}^c(s')$ such that $(t, t') \in R$;
- for all $((d_i, c, d_o), (d'_i, c', d'_o)) \in R$:
 - $d_i = \perp$ iff $d'_i = \perp$;
 - $d_o = \perp$ iff $d'_o = \perp$;
- there exist total functions $\gamma_i : D_i \rightarrow D'_i$ and $\gamma_o : D'_o \rightarrow D_o$ such that for all $((d_i, c, d_o), (d'_i, c', d'_o)) \in R$:
 - if $d_i \neq \perp$ or $d'_i \neq \perp$, then $d'_i = \gamma_i(d_i)$;
 - if $d_o \neq \perp$ or $d'_o \neq \perp$, then $d_o = \gamma_o(d'_o)$.

A is algorithmically simulated by A' , written $A \sqsubseteq_a A'$, if there exists an algorithmic simulation of A by A' .

A is computationally simulated by A' , written $A \sqsubseteq_c A'$, if there exists a computational simulation of A by A' .

A is algorithmically equivalent to A' , written $A \equiv_a A'$, if $A \sqsubseteq_a A'$ and $A' \sqsubseteq_a A$.

A is computationally equivalent to A' , written $A \equiv_c A'$, if $A \sqsubseteq_c A'$ and $A' \sqsubseteq_c A$.

The conditions imposed on an algorithmic or computational simulation R of an interactive proto-algorithm A by an interactive proto-algorithm A' include, in addition to the usual transfer conditions, also conditions that guarantee that a state of A is only related by R to a state of A' of the same kind (initial, final, internal or interaction) and conditions that guarantee that states of A with the same input value are only related by R to states of A' with the same input value and that states of A' with the same output value are only related by R to states of A with the same output value.

The following lemma will be used below.

Lemma 1. *Let $A = (\Sigma, G, \mathcal{I})$ and $A' = (\Sigma', G', \mathcal{I}')$ be interactive proto-algorithms, where $\Sigma = (F, P)$, $\Sigma' = (F', P')$, $G = (V, E, L_v, L_e, l, r)$, $G' = (V', E', L'_v, L'_e, l', r')$, $\mathcal{I} = (D, D_i, D_o, I)$, and $\mathcal{I}' = (D', D'_i, D'_o, I')$, and let $R \subseteq \mathcal{S}_A \times \mathcal{S}_{A'}$ and $\gamma_i : D_i \rightarrow D'_i$ be such that, for all $d_i \in D_i$, $((d_i, \perp, \perp), (\gamma_i(d_i), \perp, \perp)) \in R$. Then R is an algorithmic simulation of A by A' only if, for all $\alpha \in D_i^\infty$, for all $n \in \mathbb{N}^+$, $(\rho_A^\alpha(\alpha)[n], \rho_{A'}^\alpha(\gamma_i^\infty(\alpha))[n]) \in R$, where the function $\gamma_i^\infty : D_i^\infty \rightarrow D'_i^\infty$ is the pointwise extension of γ_i .*

Proof. This is easily proved by induction on n . □

The following theorem tells us that, if an interactive proto-algorithm A is algorithmically simulated by an interactive proto-algorithm A' , then (a) the function computed by A' models the function computed by A (in the sense of e.g. [6]) and (b) for each sequence of input values for which A reaches a final step, A' does so in the same number of algorithmic steps.

Theorem 1. *Let $A = (\Sigma, G, \mathcal{I})$ and $A' = (\Sigma', G', \mathcal{I}')$ be interactive proto-algorithms, where $\Sigma = (F, P)$, $\Sigma' = (F', P')$, $G = (V, E, L_v, L_e, l, r)$, $G' = (V', E', L'_v, L'_e, l', r')$, $\mathcal{I} = (D, D_i, D_o, I)$, and $\mathcal{I}' = (D', D'_i, D'_o, I')$. Then $A \sqsubseteq_a A'$ only if there exist total functions $\gamma_i : D_i \rightarrow D'_i$ and $\gamma_o : D'_o \rightarrow D_o$ such that:*

- (1) for all $\alpha \in D_1^\infty$, $\widehat{A}(\alpha)$ is defined only if $\widehat{A}'(\gamma_1^\infty(\alpha))$ is defined;
- (2) for all $\alpha \in D_1^\infty$ and $\alpha' \in D_0^\infty$, $\widehat{A}(\alpha) = \alpha'$ only if $\gamma_0^\infty(\widehat{A}'(\gamma_1^\infty(\alpha))) = \alpha'$;
- (3) for all $\alpha \in D_1^*$ such that $\widehat{A}(\alpha)$ is defined, $\#_{\text{astep}}(A, \alpha) = \#_{\text{astep}}(A', \gamma_1^\infty(\alpha))$;

where γ_1^∞ is the pointwise extension of γ_1 to a function from D_1^∞ to D_1^∞ and γ_0^∞ is the pointwise extension of γ_0 to a function from D_0^∞ to D_0^∞ .

Proof. Because $A \sqsubseteq_a A'$, there exists an algorithmic simulation of A by A' . Let R be an algorithmic simulation of A by A' , let γ_1 be the unique function from D_1 to D_1' such that, for all $d_i \in D_1$, $((d_i, \perp, \perp), (\gamma_1(d_i), \perp, \perp)) \in R$, and let γ_0 be the unique function from D_0' to D_0 such that, for all $d_o' \in D_0'$, $((\perp, \perp, \gamma_0(d_o')), (\perp, \perp, d_o')) \in R$. By Lemma 1, for all $\alpha \in D_1^\infty$, for all $n \in \mathbb{N}$, $(\rho_A^a(\alpha)[n], \rho_{A'}^a(\gamma_1^\infty(\alpha))[n]) \in R$. From this and the definition of an algorithmic simulation, it immediately follows that, for all $\alpha \in D_1^\infty$, for all $n \in \mathbb{N}$:

- (a) $\rho_A^a(\alpha)[n] \notin \mathcal{S}_A^{\text{int}}$ only if $\rho_{A'}^a(\gamma_1^\infty(\alpha))[n] \notin \mathcal{S}_{A'}^{\text{int}}$;
- (b) for all $d_i \in D_1$ and $d_o \in D_0$:
 - $\rho_A^a(\alpha)[n] = (d_i, \perp, \perp)$ only if $\rho_{A'}^a(\gamma_1^\infty(\alpha))[n] = (\gamma_1(d_i), \perp, \perp)$;
 - $\rho_A^a(\alpha)[n] = (\perp, \perp, d_o)$ only if there exists a $d_o' \in D_0'$ such that $\gamma_0(d_o') = d_o$ and $\rho_{A'}^a(\gamma_1^\infty(\alpha))[n] = (\perp, \perp, d_o')$;
 - there exists a $c \in (V \times D)$ such that $\rho_A^a(\alpha)[n] = (d_i, c, d_o)$ only if there exists a $c' \in (V' \times D')$ and a $d_o' \in D_0'$ such that $\gamma_0(d_o') = d_o$ and $\rho_{A'}^a(\gamma_1^\infty(\alpha))[n] = (\gamma_1(d_i), c', d_o')$.

From (a) and the definition of the function computed by an interactive proto-algorithm, (1) immediately follows, from (b) and the definition of the function computed by an interactive proto-algorithm, (2) immediately follows, and from (b) and the definition of $\#_{\text{astep}}$, (3) immediately follows. \square

It is easy to see that Theorem 1 goes through as far as (1) and (2) are concerned if algorithmic simulation is replaced by computational simulation. However, (3) does not go through if algorithmic simulation is replaced by computational simulation.

The following theorem tells us how isomorphism, algorithmic equivalence, and computational equivalence are related.

Theorem 2. *Let A and A' be interactive proto-algorithms. Then:*

- (1) $A \cong A'$ only if $A \equiv_a A'$
- (2) $A \equiv_a A'$ only if $A \equiv_c A'$.

Proof. Let $A = (\Sigma, G, \mathcal{I})$ and $A' = (\Sigma', G', \mathcal{I}')$ be interactive proto-algorithms, where $\Sigma = (F, P)$, $\Sigma' = (F', P')$, $G = (V, E, L_v, L_e, l, r)$, $G' = (V', E', L'_v, L'_e, l', r')$, $\mathcal{I} = (D, D_1, D_0, I)$, and $\mathcal{I}' = (D', D'_1, D'_0, I')$.

Part 1. Let $\beta_v, \beta_d, \beta_i$, and β_o be as in the definition of \cong , let $\beta_v^\perp, \beta_d^\perp, \beta_i^\perp$, and β_o^\perp be the extensions of $\beta_v, \beta_d, \beta_i$, and β_o , respectively, with the value \perp such that $\beta_v^\perp(\perp) = \perp$, $\beta_d^\perp(\perp) = \perp$, $\beta_i^\perp(\perp) = \perp$, and $\beta_o^\perp(\perp) = \perp$, let β be the bijection from \mathcal{S}_A to $\mathcal{S}_{A'}$ defined by $\beta(d_i, (v, d), d_o) = (\beta_i^\perp(d_i), (\beta_v^\perp(v), \beta_d^\perp(d)), \beta_o^\perp(d_o))$, and let $R = \{(s, \beta(s)) \mid s \in \mathcal{S}_A\}$. Then R is an algorithmic simulation of A by

A' . This is easily proved by showing that, for all $(s, s') \in R$, the conditions from the definition of an algorithmic simulation are satisfied. Hence, $A \sqsubseteq_a A'$. The proof of $A' \sqsubseteq_a A$ is done in the same way.

Part 2. Because $A \equiv_a A'$, there exists an algorithmic simulation of A by A' . Let R be an algorithmic simulation of A by A' . Then R is also a computational simulation of A by A' . This is easily proved by showing that, for all $(s, s') \in R$, the conditions from the definition of a computational simulation are satisfied. Hence, $A \sqsubseteq_c A'$. The proof of $A' \sqsubseteq_c A$ is done in the same way. \square

The opposite implications do not hold in general. That is, there exist interactive proto-algorithms A and A' for which it does not hold that $A \cong A'$ if $A \equiv_a A'$ and there exist interactive proto-algorithms A and A' for which it does not hold that $A \equiv_a A'$ if $A \equiv_c A'$. In both cases, the construction of a general illustrating example for classical proto-algorithms described in [11] also works for interactive proto-algorithms.

The definition of algorithmic equivalence suggests that the patterns of behaviour expressed by algorithmically equivalent interactive proto-algorithms must be considered the same. This suggests in turn that interactive algorithms are equivalence classes of interactive proto-algorithms under algorithmic equivalence.

If two interactive proto-algorithms are computationally equivalent, then, for each input value, they lead to the same sequence of operations being performed. The point of view should not be taken that the patterns of behaviour expressed by computationally equivalent interactive proto-algorithms are the same: the steps that consist of inspecting a condition are treated as if they do not belong to the patterns of behaviour.

The relevance of the computational equivalence relation is that any equivalence relation that captures the sameness of the patterns of behaviour expressed by interactive proto-algorithms to a higher degree than the algorithmic equivalence relation must be finer than the computational equivalence relation.

6 Concluding Remarks

Based on the classical informal notion of an algorithm, the notion of a proto-algorithm is introduced in [11]. The notion of an interactive proto-algorithm introduced in this paper is a generalization of that notion. Several further generalizations are worth studying, e.g. the notion of a non-deterministic interactive proto-algorithm and the notion of a parallel interactive proto-algorithm.

The generalization of the notion of an interactive proto-algorithm to a notion of a non-deterministic interactive proto-algorithm is easy: weaken, in the definition of an interactive- Σ -algorithm graph, the outdegree of vertices labeled with a function symbol other than `fin` to greater than zero. In the case of a non-deterministic interactive proto-algorithm, most definitions involving one or more interactive proto-algorithms need an obvious adaptation. In the case of the definition of algorithmic equivalence, a not-so-obvious alternative adaptation is

worth considering: two non-deterministic interactive proto-algorithms A and A' are algorithmically equivalent if there exist an algorithmic simulation R of A by A' and an algorithmic simulation R' of A' by A such that $R' = R^{-1}$. The condition $R' = R^{-1}$ guarantees that A and A' have the same non-deterministic choice structure.

The generalization of the notion of an interactive proto-algorithm to a notion of a parallel interactive proto-algorithm is more involved. In general, there is internal interaction, i.e. interaction between interactive proto-algorithms that are part of a parallel interactive proto-algorithm. Therefore, an interactive proto-algorithm that is part of a parallel interactive proto-algorithm should be able to interact via different channels. This requires an adaptation of the notion of an interactive algorithm introduced in this paper. Moreover, it is likely that, in the case of a parallel interactive proto-algorithm, most definitions involving one or more interactive proto-algorithms need a not-so-obvious adaptation.

References

1. Baeten, J.C., Luttik, B., van Tilburg, P.: Reactive Turing machines. *Information and Computation* **231**, 143–166 (2013). <https://doi.org/10.1016/j.ic.2013.08.010>
2. Blass, A., Gurevich, Y.: Ordinary interactive small-step algorithms, i. *ACM Transactions on Computational Logic* **7**(2), 363–419 (2006). <https://doi.org/10.1145/1131313.1131320>
3. Broy, M.: Computability and realizability for interactive computations. *Information and Computation* **241**, 277–301 (2015). <https://doi.org/10.1016/j.ic.2014.12.019>
4. Dijkstra, E.W.: *A Short Introduction to the Art of Programming*, EWD, vol. 316. Technische Hogeschool Eindhoven (1971)
5. Goldin, D.Q., Smolka, S.A., Attie, P.C., Sonderegger, E.L.: Turing machines, transition systems, and interaction. *Information and Computation* **194**(2), 101–128 (2004). <https://doi.org/10.1016/j.ic.2004.07.002>
6. Jones, C.B.: *Systematic Software Development Using VDM*. Prentice-Hall, second edn. (1990)
7. Kleene, S.C.: *Mathematical Logic*. John Wiley and Sons, New York (1967)
8. Knuth, D.E.: *The Art of Computer Programming: The Fundamental Algorithms*. Addison Wesley Longman, Redwood City, CA, third edn. (1997)
9. van Leeuwen, J., Wiedermann, J.: Beyond the Turing limit: Evolving interactive systems. In: Pacholski, L., Ružička, P. (eds.) *SOFSEM 2001. Lecture Notes in Computer Science*, vol. 2234, pp. 90–109. Springer-Verlag (2001). https://doi.org/10.1007/3-540-45627-9_8
10. Mal'cev, A.I.: *Algorithm and Recursive Functions*. Wolters-Noordhoff, Groningen, NL (1970)
11. Middelburg, C.A.: On the formalization of the notion of an algorithm. *Computing Research Repository* (2024). <https://doi.org/10.48550/arXiv.2401.08366>
12. Rogers, H.: *Theory of Recursive Functions and Effective Computability*. McGraw-Hill, New York (1967)
13. Weyuker, E.J.: Modifications of the program scheme model. *Journal of Computer and System Sciences* **18**(3), 281–293 (1979). [https://doi.org/10.1016/0022-0000\(79\)90036-9](https://doi.org/10.1016/0022-0000(79)90036-9)