

Knapsack with Vertex Cover, Set Cover, and Hitting Set

Palash Dey   

Indian Institute of Technology Kharagpur, India

Ashlesha Hota ¹  

Indian Institute of Technology Kharagpur, India

Sudeshna Kolay   

Indian Institute of Technology Kharagpur, India

Sipra Singh ² 

Indian Institute of Technology Kharagpur, India

Abstract

Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, with vertex weights $(w(u))_{u \in \mathcal{V}}$, vertex values $(\alpha(u))_{u \in \mathcal{V}}$, a knapsack size s , and a target value d , the VERTEX COVER KNAPSACK problem is to determine if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that \mathcal{U} forms a vertex cover, $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$, and $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$. In this paper, we closely study the VERTEX COVER KNAPSACK problem and its variations, such as VERTEX COVER KNAPSACK WITH BUDGET, MINIMAL VERTEX COVER KNAPSACK, and MINIMUM VERTEX COVER KNAPSACK, for both general graphs and trees. We first prove that the VERTEX COVER KNAPSACK problem belongs to the complexity class NP-complete and then study the complexity of the other variations. We generalize the problem to SET COVER and d-HITTING SET versions and design polynomial time H_g -factor approximation algorithm for the SET COVER KNAPSACK WITH TARGET VALUE problem and d-factor approximation algorithm for d-HITTING SET KNAPSACK WITH TARGET VALUE using primal dual method. We further show that SET COVER KNAPSACK WITH BUDGETED WEIGHT and d-HITTING SET KNAPSACK WITH BUDGETED WEIGHT are hard to approximate in polynomial time. Additionally, we develop a fixed parameter tractable algorithm running in time $8^{\mathcal{O}(\text{tw})} \cdot n \cdot \min\{s, d\}$ where tw , s , d , n are respectively treewidth of the graph, the size of the knapsack, the target value of the knapsack, and the number of items for the MINIMAL VERTEX COVER KNAPSACK problem.

2012 ACM Subject Classification

Keywords and phrases Vertex cover knapsack, Vertex cover knapsack with budget, Minimal vertex cover knapsack, Minimum vertex cover knapsack, Hitting set, Set cover

Digital Object Identifier 10.4230/LIPIcs...

1 Introduction

The VERTEX COVER problem is a well-studied classical problem in graph theory and operations research. Given a graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$, the VERTEX COVER problem aims to find a minimum vertex subset $\mathcal{V}' \subseteq \mathcal{V}$ such that for every edge $(u, v) \in \mathcal{G}[\mathcal{E}]$, either u or v or both exist in \mathcal{V}' . In this paper, we explore a novel variation of the classical VERTEX COVER problem in the

¹ Joint Author

² First Author



© Author: Please provide a copyright holder;

licensed under Creative Commons License CC-BY 4.0

Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

context of the KNAPSACK. In the KNAPSACK problem, we are given a set of n items, $\mathcal{X} = \{1, 2, \dots, n\}$ and a knapsack of capacity b . Each item $i \in [n]$ is associated with size θ_i and values p_i . The computational question is to find a subset $\mathcal{I} \subseteq \mathcal{X}$ to be put into the knapsack of capacity b that maximizes the value of the knapsack without exceeding its capacity constraint. This paper delves into the problem VERTEX COVER KNAPSACK, where given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, with vertex weights $(w(u))_{u \in \mathcal{V}}$, vertex values $(\alpha(u))_{u \in \mathcal{V}}$, a knapsack size s , and a target value d , the VERTEX COVER KNAPSACK problem is to determine if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that \mathcal{U} forms a vertex cover, $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$, and $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$. We study several interesting variations of this problem like VERTEX COVER KNAPSACK WITH BUDGET, MINIMAL VERTEX COVER KNAPSACK, and MINIMUM VERTEX COVER KNAPSACK. These problems are formally defined in Section 2. VERTEX COVER is a special case of SET COVER and 2-HITTING SET. We design polynomial time approximation algorithms for SET COVER KNAPSACK WITH TARGET VALUE problem and show similar results for d-HITTING SET and VERTEX COVER KNAPSACK. We also show that VERTEX COVER KNAPSACK WITH BUDGETED WEIGHT does not admit a polynomial time approximation algorithm unless $P = NP$.

These problems often find applications in various domains, including wireless network design, especially in the context of leasing mobile towers. Consider a scenario where a company aims to establish mobile towers in different areas to efficiently serve its customers while minimizing leasing costs within a budget constraint. Additionally, the company must ensure that it meets the target or subscribed customer base. This situation can be depicted through an undirected weighted graph \mathcal{G} , where vertices symbolize towers and edges represent the connectivity range. Each tower vertex is associated with a value, indicating the number of customers it can serve, and a weight, representing the leasing cost. Moreover, there exists a budget constraint, limiting the total cost the company can afford for leasing towers, alongside a target value representing the desired total value in terms of the number of customers served.

In the subsequent sections, we first present a brief overview of the efforts made in the realm of the VERTEX COVER problem in Section 1.2. We formally define the problems in Section 2. We show the classical NP Completeness results in Section 3. We develop polynomial time approximation algorithms and a fixed parameter tractable algorithm in Section 4 and Section 5 respectively. We conclude our efforts in Section 6.

1.1 Contributions

We study the computational complexity of the problems VERTEX COVER KNAPSACK, VERTEX COVER KNAPSACK WITH BUDGET, MINIMUM VERTEX COVER KNAPSACK, and MINIMAL VERTEX COVER KNAPSACK. For each of these problems, we resolve their complexity with respect to general graphs and trees. We design a polynomial time 2-approximation algorithm for the problem using primal dual method. Further we also demonstrate that the VERTEX COVER KNAPSACK, MINIMUM VERTEX COVER KNAPSACK and MINIMAL VERTEX COVER KNAPSACK all admit fixed parameter tractable algorithms with *treewidth* as the parameter. Our main contributions are highlighted in Table 1.

1.2 Related Work

VERTEX COVER is a well-studied NP-complete problem in Graph Theory. Given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, a vertex cover for \mathcal{G} is any subset $\mathcal{V}' \subseteq \mathcal{V}$ that contains at least one endpoint from

VERTEX COVER KNAPSACK	strongly NP-complete (Theorem 7) pseudo-polynomial for trees (Corollary 33) $2^{\mathcal{O}(\text{tw})} \cdot n \cdot \min\{s, d\}$ (Theorem 29)
VERTEX COVER KNAPSACK WITH BUDGET	strongly NP-complete (Theorem 8) pseudo-polynomial for trees (Corollary 30) $\mathcal{O}(n^2 \cdot \min\{s, (\alpha(\mathcal{V}))\})$ (Corollary 30)
MINIMUM VERTEX COVER KNAPSACK	NP hard (Observation 11) NP-complete for trees $4^{\mathcal{O}(\text{tw})} \cdot n \cdot \min\{s, d\}$ (Theorem 31)
MINIMAL VERTEX COVER KNAPSACK	strongly NP-complete (Theorem 9) NP-complete for trees (Theorem 10) no poly-time approx. algorithm (Theorem 28) $8^{\mathcal{O}(\text{tw})} \cdot n \cdot \min\{s, d\}$ (Theorem 32)
SET COVER KNAPSACK WITH TARGET VALUE	poly-time f-approx. algorithm (Theorem 21) poly-time H_g -approx algorithm (Theorem 23)
SET COVER KNAPSACK WITH BUDGETED WEIGHT	no poly-time approx. algorithm (Theorem 25)
d-HITTING SET KNAPSACK WITH TARGET VALUE	poly-time d-approx. algorithm (Corollary 22)
d-HITTING SET KNAPSACK WITH BUDGETED WEIGHT	no poly-time approx. algorithm (Corollary 26)
VERTEX COVER KNAPSACK WITH TARGET VALUE	poly-time 2-approx. algorithm (Corollary 24)
VERTEX COVER KNAPSACK WITH BUDGETED WEIGHT	no poly-time approx. algorithm (Corollary 27)

■ **Table 1** Summary of results

every edge. The problem is also investigated to be NP-complete in planar graphs with a degree at most 3 [19][20]. *Weighted VERTEX COVER* (WVC) is the weighted version studied in different literature where the sum of weights of all the vertices in a VERTEX COVER must be $\leq c$ (where $c \in \mathbb{R}^+$). If all the weights of the vertices are 1, it is called *Unweighted VERTEX COVER* (UVC). In the paper [25], Niedermeier and Rossmanith proved that WVC is *fixed-parameter tractable* if the weights are positive integers or real numbers ≥ 1 , but it is *not* fixed-parameter tractable if the weights are positive real numbers unless $\mathbf{P} = \mathbf{NP}$. They used a dynamic programming algorithm with complexity $\mathcal{O}((1.3788)^c + cn)$, where n is the number of vertices of the input graph. Later, Fomin et al [17] provided an algorithm to improve the running time to $\mathcal{O}((1.357)^c \cdot n)$. Chlebík and Chlebíková [7] proposed an exact algorithm by using the crown reduction technique for solving the Minimum Weighted Vertex Cover (MWVC) problem, whose decision version is WVC. Approximation algorithms for MWVC are described here [1]. Linear time 2-approximation algorithms exist for both UVC [29] and WVC [3]. These results become improved with a better approximation factor for UVC [23] and WVC [4].

k -VERTEX COVER (the decision version of the Minimum VERTEX COVER problem) finds a vertex cover of size at most k (where $k \in \mathbb{Z}^+$) or returns that no such size of VERTEX COVER exists. This problem is FPT. The first FPT algorithm for this problem with a time complexity of $\mathcal{O}(2^k \cdot n)$ was given by Downey and Fellows [12]. They used the technique of bounded search trees. S. Buss [12] proved that this problem is solvable in $\mathcal{O}(k^k + n)$ time. The algorithm developed by Papadimitriou and Yannakakis [28] has a running time of $\mathcal{O}(3^k \cdot n)$. In the paper [2], Balasubramanian et al. gave an algorithm with a running time of $\mathcal{O}((1.324718)^k \cdot k^2 + kn)$ using bounded search techniques. Downey et al.[11] developed an algorithm using kernelization and search tree methods with a complexity of $\mathcal{O}((1.31951)^k \cdot k^2 + kn)$. Later, Niedermeier and Rossmanith[24] provided an algorithm with complexity $\mathcal{O}((1.29175)^k \cdot k^2 + kn)$. Another FPT algorithm with a running time of $\mathcal{O}(\max(1.25542)^k \cdot k^2, (1.2906)^k \cdot k + kn)$

XX:4 Knapsack with Vertex Cover, Set Cover, and Hitting Set

was given by Stege and Fellows [15]. The best-known result, provided by Harris and Narayanaswamy [21], gives an algorithmic complexity of $\mathcal{O}((1.25284)^k + kn)$.

MAXIMUM MINIMAL VERTEX COVER (MMVC) is a problem of finding a minimal VERTEX COVER of cardinality at least k . This problem admits a polynomial kernel in terms of the number of vertices and can be solved in $\mathcal{O}(2^k + p(n))$ time using a search tree algorithm, where p is some polynomial [16]. Later, Peter Damaschke [9] proved that MMVC is solvable in time $\mathcal{O}(1.62^k)$. For general graphs, Boria et al [5] showed that this problem is polynomially approximable within the ratio $n^{-1/2}$ and inapproximable within the ratio $n^{\varepsilon-1/2}$ unless $\mathbf{P} = \mathbf{NP}$, where $\varepsilon > 0$. They proved that this problem is FPT and can be solved in $\mathcal{O}(1.5739^{opt})$ with respect to the cardinality of the optimal solution (opt), in $\mathcal{O}^*(2.8284^M)$ with respect to the size of the maximum matching (M), and also with respect to the treewidth.

Various approximation algorithms have been explored for the SET COVER problem like f factor, $\log n$ and $\log d$, factor approximation ratios [30]. Here n and d denote the number of elements in the universe and frequency of the most frequent element respectively. Delbot and Laforest in [10] concluded that we cannot hope to have an approximation algorithm for vertex cover better than 2.

There are several other variations of the classical VERTEX COVER problem studied in the literature, such as *Connected* VERTEX COVER in [22], [14], and *Eternal Connected* VERTEX COVER in [26], [18]. In this study, we explore a novel variant of the VERTEX COVER problem, namely VERTEX COVER KNAPSACK. Given an undirected weighted graph \mathcal{G} , the size of the knapsack, and a target value, the computational question is to compute a vertex cover that yields the maximum profit without exceeding the size of the knapsack. We formally define the problem in Section 2. Our main results prove that this problem is NP-complete.

2 Preliminaries

► **Definition 1** (VERTEX COVER KNAPSACK). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, size s of knapsack, and target value d , compute if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that:*

1. \mathcal{U} is a vertex cover.
2. $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$,
3. $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$

We denote an arbitrary instance of VERTEX COVER KNAPSACK by $(\mathcal{G}, (w(u))_{u \in \mathcal{V}}, (\alpha(u))_{u \in \mathcal{V}}, s, d)$.

► **Definition 2** (VERTEX COVER KNAPSACK WITH BUDGET). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, budget k of the vertex cover, size s of knapsack, and target value d , compute if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that:*

1. \mathcal{U} is a VERTEX COVER of size at most k ,
2. $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$,
3. $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$

We denote an arbitrary instance of VERTEX COVER KNAPSACK WITH BUDGET by $(\mathcal{G}, (w(u))_{u \in \mathcal{V}}, (\alpha(u))_{u \in \mathcal{V}}, s, d, k)$.

► **Definition 3** (MINIMUM VERTEX COVER KNAPSACK). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, size s of knapsack, and target value d , compute if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that:*

1. \mathcal{U} is minimum VERTEX COVER,
2. $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$,
3. $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$

We denote an arbitrary instance of MINIMUM VERTEX COVER KNAPSACK by $(\mathcal{G}, (w(u))_{u \in \mathcal{V}}, (\alpha(u))_{u \in \mathcal{V}}, s, d)$.

► **Definition 4** (MINIMAL VERTEX COVER KNAPSACK). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, size s of knapsack, and target value d , compute if there exists a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices such that:*

1. \mathcal{U} is a minimal VERTEX COVER,
2. $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$,
3. $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$

We denote an arbitrary instance of MINIMAL VERTEX COVER KNAPSACK by $(\mathcal{G}, (w(u))_{u \in \mathcal{V}}, (\alpha(u))_{u \in \mathcal{V}}, s, d)$.

► **Definition 5** (TREEWIDTH). *Let $G = (V_G, E_G)$ be a graph. A tree-decomposition of a graph G is a pair $(\mathbb{T} = ((V_{\mathbb{T}}, E_{\mathbb{T}}), \mathcal{X} = \{X_t\}_{t \in V_{\mathbb{T}}})$, where \mathbb{T} is a tree where every node $t \in V_{\mathbb{T}}$ is assigned a subset $X_t \subseteq V_G$, called a bag, such that the following conditions hold.*

- ▷ $\bigcup_{t \in V_{\mathbb{T}}} X_t = V_G$,
- ▷ for every edge $\{x, y\} \in E_G$ there is a $t \in V_{\mathbb{T}}$ such that $x, y \in X_t$, and
- ▷ for any $v \in V_G$ the subgraph of \mathbb{T} induced by the set $\{t \mid v \in X_t\}$ is connected.

The *width* of a tree decomposition is $\max_{t \in V_{\mathbb{T}}} |X_t| - 1$. The *treewidth* of G is the minimum width over all tree decompositions of G and is denoted by $\text{tw}(G)$.

A tree decomposition $(\mathbb{T}, \mathcal{X})$ is called a *nice edge tree decomposition* if \mathbb{T} is a tree rooted at some node r where $X_r = \emptyset$, each node of \mathbb{T} has at most two children, and each node is of one of the following kinds:

- ▷ **Introduce node**: a node t that has only one child t' where $X_t \supset X_{t'}$ and $|X_t| = |X_{t'}| + 1$.
- ▷ **Forget vertex node**: a node t that has only one child t' where $X_t \subset X_{t'}$ and $|X_t| = |X_{t'}| - 1$.
- ▷ **Join node**: a node t with two children t_1 and t_2 such that $X_t = X_{t_1} = X_{t_2}$.
- ▷ **Leaf node**: a node t that is a leaf of \mathbb{T} , and $X_t = \emptyset$.

We additionally require that every edge is introduced exactly once. One can show that a tree decomposition of width t can be transformed into a nice tree decomposition of the same width t and with $\mathcal{O}(t|V_G|)$ nodes [8]. For a node $t \in \mathbb{T}$, let \mathbb{T}_t be the subtree of \mathbb{T} rooted at t , and $V(\mathbb{T}_t)$ denote the vertex set in that subtree. Then G_t is the subgraph of G where the vertex set is $\bigcup_{t' \in V(\mathbb{T}_t)} X_{t'}$ and the edge set is the union of the set of edges introduced in each

XX:6 Knapsack with Vertex Cover, Set Cover, and Hitting Set

$t', t' \in V(\mathbb{T}_t)$. We denote by $V(G_t)$ the set of vertices in that subgraph, and by $E(G_t)$ the set of edges of the subgraph.: a node t that is a leaf of \mathbb{T} , and $X_t = \emptyset$.

In this paper, we sometimes fix a vertex $v \in V_G$ and include it in every bag of a nice edge tree decomposition $(\mathbb{T}, \mathcal{X})$ of G , with the effect of the root bag and each leaf bag containing v . For the sake of brevity, we also call such a modified tree decomposition a nice tree decomposition. Given the tree \mathbb{T} rooted at the node r , for any nodes $t_1, t_2 \in V_{\mathbb{T}}$, the distance between the two nodes in \mathbb{T} is denoted by $\text{dist}_{\mathbb{T}}(t_1, t_2)$.

3 Results: Classical NP Completeness

► **Definition 6** (VERTEX COVER). *Given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ and a positive integer k , compute if there exists a subset $\mathcal{V}' \subseteq \mathcal{V}$ such that at least one end-point of every edge belongs to \mathcal{V}' and $|\mathcal{V}'| \leq k$. We denote an arbitrary instance of VERTEX COVER by (\mathcal{G}, k) .*

In this section, we show that VERTEX COVER KNAPSACK is strongly NP-complete by reducing it from VERTEX COVER (see, Definition 6).

► **Theorem 7.** VERTEX COVER KNAPSACK is strongly NP-complete for general graph.

Proof. Clearly, VERTEX COVER KNAPSACK \in NP. We reduce VERTEX COVER to VERTEX COVER KNAPSACK to prove NP-hardness. Let $(\mathcal{G}(\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), k)$ be an arbitrary instance of VERTEX COVER of size k . We construct the following instance $(\mathcal{G}'(\mathcal{V}' = \{u_i : i \in [n]\}, \mathcal{E}'), (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d)$ of VERTEX COVER KNAPSACK.

$$\begin{aligned}\mathcal{V}' &= \{u_i : v_i \in \mathcal{V}, \forall i \in [n]\} \\ \mathcal{E}' &= \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}, i \neq j, \forall i, j \in [n]\} \\ w(u_i) &= 1, \alpha(u_i) = 1 \quad \forall i \in [n] \\ s &= d = k\end{aligned}$$

The VERTEX COVER KNAPSACK problem has a solution iff VERTEX COVER has a solution.

Let $(\mathcal{G}', (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d)$ of VERTEX COVER KNAPSACK such that \mathcal{W}' be the resulting subset of \mathcal{V}' with (i) \mathcal{W}' is a VERTEX COVER, (ii) $\sum_{u \in \mathcal{W}'} w(u) = k$, (iii) $\sum_{u \in \mathcal{W}'} \alpha(u) = k$

This means that the set \mathcal{W}' is a VERTEX COVER which gives the maximum profit k for the bag capacity of size k . In other words, \mathcal{W}' is a VERTEX COVER of size k . Since $\mathcal{W}' = \{u_i : v_i \in \mathcal{W}, \forall i \in [n]\}$, \mathcal{W} is a VERTEX COVER of size k . Therefore, the VERTEX COVER instance is an YES instance.

Conversely, let us assume that VERTEX COVER instance (\mathcal{G}, k) is an YES instance.

Then there exists a subset $\mathcal{W} \subseteq \mathcal{V}$ of size k such that it outputs a VERTEX COVER.

Consider the set $\mathcal{W}' = \{u_i : v_i \in \mathcal{W}, \forall i \in [n]\}$. Since each vertex of \mathcal{W}' is involved with weight 1 and produces profit amount 1, \mathcal{W}' is a VERTEX COVER of max bag size and total profit k . Therefore, the VERTEX COVER KNAPSACK instance is an YES instance. ◀

3.1 VERTEX COVER KNAPSACK WITH BUDGET

In this section, we show that VERTEX COVER KNAPSACK WITH BUDGET is strongly NP-complete by reducing it from VERTEX COVER (see, definition 6).

► **Theorem 8.** VERTEX COVER KNAPSACK WITH BUDGET *is strongly NP-complete for general graph.*

Proof. Clearly, VERTEX COVER KNAPSACK WITH BUDGET \in NP. We reduce VERTEX COVER to VERTEX COVER KNAPSACK WITH BUDGET to prove NP-hardness. Let $(\mathcal{G}(\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), k)$ be an arbitrary instance of VERTEX COVER of size k . We construct the following instance $(\mathcal{G}'(\mathcal{V}' = \{u_i : i \in [n]\}, \mathcal{E}'), (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d, k')$ of VERTEX COVER KNAPSACK WITH BUDGET.

$$\begin{aligned}\mathcal{V}' &= \{u_i : v_i \in \mathcal{V}, \forall i \in [n]\} \\ \mathcal{E}' &= \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}, i \neq j, \forall i, j \in [n]\} \\ w(u_i) &= 1, \alpha(u_i) = 1 \quad \forall i \in [n] \\ s &= d = k' = k\end{aligned}$$

The VERTEX COVER KNAPSACK WITH BUDGET problem has a solution iff VERTEX COVER has a solution.

Let $(\mathcal{G}'(\mathcal{V}', \mathcal{E}'), (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d, k')$ of VERTEX COVER KNAPSACK WITH BUDGET such that \mathcal{W}' be the resulting subset of \mathcal{V}' with (i) \mathcal{W}' is a VERTEX COVER of size at most k' , (ii) $\sum_{u \in \mathcal{W}'} w(u) \leq s = k'$, (iii) $\sum_{u \in \mathcal{W}'} \alpha(u) \geq d = k'$.

This means that the set \mathcal{W}' is a VERTEX COVER which gives the maximum profit k' for the bag capacity of k' . Now, since $k' = k$ and $\mathcal{W}' = \{u_i : v_i \in \mathcal{W}, \forall i \in [n]\}$, we can say that \mathcal{W} is a VERTEX COVER of size k . Therefore, the VERTEX COVER instance is an YES instance.

Conversely, let us assume that VERTEX COVER instance (\mathcal{G}, k) is an YES instance.

Then there exists a subset $\mathcal{W} \subseteq \mathcal{V}$ of size k such that it outputs a VERTEX COVER.

Since $\mathcal{W}' = \{u_i : v_i \in \mathcal{W}, \forall i \in [n]\}$ and each vertex of \mathcal{W}' is involved with weight 1 and produces profit amount 1 in the reduced graph \mathcal{G}' , \mathcal{W}' is a VERTEX COVER of max bag size and total profit k . Also we have, $k = k'$. Therefore, the VERTEX COVER KNAPSACK WITH BUDGET instance is an YES instance. ◀

3.2 MINIMAL VERTEX COVER KNAPSACK

We show that MINIMAL VERTEX COVER KNAPSACK is strongly NP-complete by reducing it from MAXIMUM MINIMAL VERTEX COVER which is a NP-complete problem.

► **Theorem 9.** MINIMAL VERTEX COVER KNAPSACK *is strongly NP-complete for general graph.*

Proof. Clearly, MINIMAL VERTEX COVER KNAPSACK \in NP. Since, the decision version of MAXIMUM MINIMAL VERTEX COVER is NP-complete, we reduce MAXIMUM MINIMAL VERTEX COVER to MINIMAL VERTEX COVER KNAPSACK to prove NP-completeness. Let $(\mathcal{G}(\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), k)$ be an arbitrary instance of MAXIMUM MINIMAL VERTEX COVER of size k .

XX:8 Knapsack with Vertex Cover, Set Cover, and Hitting Set

We construct the following instance $(\mathcal{G}'(\mathcal{V}' = \{u_i : i \in [n]\}, \mathcal{E}'), (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d)$ of MINIMAL VERTEX COVER KNAPSACK.

$$\begin{aligned}\mathcal{V}' &= \{u_i : v_i \in \mathcal{V}, \forall i \in [n]\} \\ \mathcal{E}' &= \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}, i \neq j, \forall i, j \in [n]\} \\ w(u_i) &= 1, w(u_j) = 0 \quad \text{for some } i, j \in [1, n] \\ \alpha(u_i) &= 1 \quad \forall i \in [1, n] \\ s &= d = k\end{aligned}$$

The reduction of MAXIMUM MINIMAL VERTEX COVER to MINIMAL VERTEX COVER KNAPSACK works in polynomial time. The MINIMAL VERTEX COVER KNAPSACK problem has a solution iff MAXIMUM MINIMAL VERTEX COVER has a solution.

Let $(\mathcal{G}'(\mathcal{V}', \mathcal{E}'), (w(u))_{u \in \mathcal{V}'}, (\alpha(u))_{u \in \mathcal{V}'}, s, d)$ of MINIMAL VERTEX COVER KNAPSACK such that \mathcal{W} be the resulting subset of \mathcal{V}' with (i) \mathcal{W} is a minimal VERTEX COVER, (ii) $\sum_{u \in \mathcal{W}} w(u) \leq s = k$, (iii) $\sum_{u \in \mathcal{W}} \alpha(u) \geq d = k$.

From the above condition (i), as \mathcal{W} is minimal VERTEX COVER we can not remove any vertex from \mathcal{W} which gives another VERTEX COVER. Now, since we rewrite the second and third conditions as $|\mathcal{W}| \leq k$ and $|\mathcal{W}| \geq k$. So, $|\mathcal{W}|$ must be k . Now, let $\mathcal{I} = \{v_i : u_i \in \mathcal{W}, \forall i \in [n]\}$. Since \mathcal{W} is the Minimal VERTEX COVER of size k , then $\mathcal{I} (\subseteq \mathcal{V})$ must be MAXIMUM MINIMAL VERTEX COVER set of size at least k . Therefore, the MAXIMUM MINIMAL VERTEX COVER instance is an YES instance.

Conversely, let us assume that MAXIMUM MINIMAL VERTEX COVER instance (\mathcal{G}, k) is an YES instance.

Then there exists a subset $\mathcal{I} \subseteq \mathcal{V}$ of size $\geq k$ such that it outputs an MAXIMUM MINIMAL VERTEX COVER. Let $\mathcal{W} = \{u_i : v_i \in \mathcal{I}, \forall i \in [n]\}$. Since \mathcal{I} is an MAXIMUM MINIMAL VERTEX COVER of size $\geq k$, then \mathcal{W} must be a Minimal VERTEX COVER of size k . So, $\sum_{u \in \mathcal{W}} w(u) \leq k = s$ and $\sum_{u \in \mathcal{W}} \alpha(u) \geq k = d$. Now, we want to prove that \mathcal{W} is a minimal VERTEX COVER.

Therefore, the MINIMAL VERTEX COVER KNAPSACK instance is an YES instance. ◀

► **Theorem 10.** MINIMAL VERTEX COVER KNAPSACK is NP-complete for trees.

Proof. Clearly, MINIMAL VERTEX COVER KNAPSACK for tree \in NP. We reduce MINIMAL VERTEX COVER KNAPSACK from KNAPSACK to prove hardness. Given, an arbitrary instance $(\mathcal{X}, (\theta_i)_{i \in \mathcal{X}}, (p_i)_{i \in \mathcal{X}}, b, q)$ of KNAPSACK, we create an instance of MINIMAL VERTEX COVER KNAPSACK for trees by forming a complete binary tree $\mathcal{T} = (\mathcal{V}, \mathcal{E})$ that has n nodes in its penultimate level and denote an instance as $(\mathcal{T}, (w(u))_{u \in \mathcal{T}}, (\alpha(u))_{u \in \mathcal{T}}, s, d)$. The construction steps is as follows:

1. We construct a complete binary tree \mathcal{T} such that the penultimate level of this tree has n nodes representing the n items.
2. Without loss of generality we assume, that $n = |\mathcal{X}| = 2^k$ because suppose there exists n such that $2^{k-1} < n < 2^k$, add $2^k - n$ items to \mathcal{X} each with size = 0 and profit = 0, where $k \geq 0$.
3. Let $\mathcal{V}' \subseteq \mathcal{T}[\mathcal{V}]$ denote the vertices belonging to the penultimate level of the tree \mathcal{T} .

4. Set $w(u_i)_{u_i \in \mathcal{V}'} = \theta_i, \alpha(u_i)_{u_i \in \mathcal{V}'} = p_i, w(u_i)_{u_i \in \mathcal{V} - \mathcal{V}'} = 0, \alpha(u_i)_{u_i \in \mathcal{V} - \mathcal{V}'} = 0$
 $s = b, d = q$

This construction takes polynomial time.

We now show that $\text{KNAPSACK} \leq_p \text{MINIMAL VERTEX COVER KNAPSACK}$.

The $\text{MINIMAL VERTEX COVER KNAPSACK}$ problem has a solution if and only if KNAPSACK has a solution.

$\text{MINIMAL VERTEX COVER KNAPSACK} \rightarrow \text{KNAPSACK}$

Let $(\mathcal{T}, (w(u))_{u \in \mathcal{V}}, (\alpha(u))_{u \in \mathcal{V}}, s, d)$ be an instance of $\text{MINIMAL VERTEX COVER KNAPSACK}$ such that \mathcal{W} be the resulting subset of \mathcal{V} with

1. \mathcal{W} is a minimal VERTEX COVER ,
2. $\sum_{u \in \mathcal{W}} w(u) = b$,
3. $\sum_{u \in \mathcal{W}} \alpha(u) = d$

This means that the set \mathcal{W} is a minimal VERTEX COVER , which gives the maximum profit d for the bag capacity of size b . In other words, $\mathcal{W} \cap \mathcal{V}' = \mathcal{W}' \neq \phi$ i.e. \mathcal{W} must contain at least a subset of \mathcal{V}' in order to attain the required profit d because $\mathcal{W} - \mathcal{V}'$ has vertices whose weight = 0, and profit = 0. As per our construction, \mathcal{V}' contains the vertices denoting the n items of \mathcal{X} in KNAPSACK . Therefore, the KNAPSACK instance is an YES instance.

$\text{KNAPSACK} \rightarrow \text{MINIMAL VERTEX COVER KNAPSACK}$

Let $(\mathcal{X}, (\theta_i)_{i \in \mathcal{X}}, (p_i)_{i \in \mathcal{X}}, b, q)$ be an instance of KNAPSACK such that \mathcal{I} be the resulting subset of \mathcal{X} with

1. $\sum_{i \in \mathcal{I}} \theta_i \leq b$,
2. $\sum_{i \in \mathcal{I}} p_i \geq q$

The minimal vertex cover knapsack must pick vertices from \mathcal{V}' otherwise it cannot meet the desired value d as all vertices of $\mathcal{V} - \mathcal{V}'$ have weight and value equal to 0.

We obtain a minimal VERTEX COVER for \mathcal{T} by recursively constructing the solution set, \mathcal{W} as:

1. if $u \in \mathcal{T}[\mathcal{I}]$, include u in \mathcal{W} and delete $\mathcal{N}[u]$ from \mathcal{T}
2. if $u \notin \mathcal{T}[\mathcal{I}]$, include $\mathcal{N}(u)$ in \mathcal{W} delete $\mathcal{N}[u]$ from \mathcal{T}
3. solve for minimal vertex cover on the induced sub-graph where weight and profit associated with each vertex is 0.

Therefore, the $\text{MINIMAL VERTEX COVER KNAPSACK}$ for tree is an YES instance.

◀

3.3 MINIMUM VERTEX COVER KNAPSACK

► **Observation 11.** *This problem is not known to be in NP, even the decision version of this problem for the general graph.*

4 Results: Polynomial Time Approximation Algorithms

In this section, we define optimization versions of the VERTEX COVER KNAPSACK problem. We consider the following two versions:

► **Definition 12** (VERTEX COVER KNAPSACK WITH TARGET VALUE). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, and target value d , compute a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices that minimizes the total weight $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u)$ such that:*

1. \mathcal{U} is a vertex cover.
2. $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u) \geq d$

► **Definition 13** (VERTEX COVER KNAPSACK WITH BUDGETED WEIGHT). *Given an undirected graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, weight of vertices $(w(u))_{u \in \mathcal{V}}$, value of vertices $(\alpha(u))_{u \in \mathcal{V}}$, and size s of knapsack, compute a subset $\mathcal{U} \subseteq \mathcal{V}$ of vertices that maximizes the total value $\alpha(\mathcal{U}) = \sum_{u \in \mathcal{U}} \alpha(u)$ such that:*

1. \mathcal{U} is a vertex cover.
2. $w(\mathcal{U}) = \sum_{u \in \mathcal{U}} w(u) \leq s$,

We formulate VERTEX COVER KNAPSACK WITH TARGET VALUE problem as the following integer linear programming, in which the primal variable x_i indicates whether vertex $v_i \in \mathcal{V}$ is chosen to be in the solution or not:

$$\text{minimize } \sum_{u \in \mathcal{V}} w(u)x_u$$

Subject to:

$$\begin{aligned} x_u + x_v &\geq 1, \forall (u, v) \in \mathcal{E} \\ \sum_{u \in \mathcal{V}} \alpha(u)x_u &\geq d \\ x_u &\in \{0, 1\}, \forall u \in \mathcal{V} \end{aligned}$$

We replace the constraints $x_u \in \{0, 1\}$, with $x_u \geq 0, \forall u \in \mathcal{V}$ to obtain linear programming relaxation of the integer linear program.

► **Observation 14.** *The relaxed linear programming of the above integer linear programming has an unbounded integrality gap. Consider an edgeless graph $\mathcal{G} (\mathcal{V}, \mathcal{E})$ such that $\mathcal{E} = \emptyset$. Let $\mathcal{V} = \{v_1, v_2\}$, $w(v_1) = 0, w(v_2) = 1, \alpha(v_1) = d - 1$ and $\alpha(v_2) = d$. The optimal solution to integer linear programming sets $x_{v_1} = 0, x_{v_2} = 1$, for a total weight of 1. However, the solution to the relaxed linear programming sets $x_{v_1} = 1, x_{v_2} = 1/d$ and has total weight of $1/d$. Thus, in this case the integrality gap is at least $\frac{1}{1/d} = d$.*

We also consider a generalized version of VERTEX COVER problem i.e. SET COVER problem.

► **Definition 15** (SET COVER). *Given a universe \mathcal{U} of n elements and some subsets $\mathcal{S}_1, \mathcal{S}_2, \dots, \mathcal{S}_m$ where each $\mathcal{S}_i \subseteq \mathcal{U}$, and a non negative weight $w(i) \geq 0$ for each subset $\mathcal{S}_i, \forall i \in [m]$. The goal is to find $\mathcal{I} \subseteq \{1, 2, \dots, m\}$ that minimizes $\sum_{i \in \mathcal{I}} w(i)$ subject to $\bigcup_{i \in \mathcal{I}} \mathcal{S}_i = \mathcal{U}$.*

Vertex cover is a special case of set cover. Interestingly, if each set \mathcal{S}_i , $\forall i \in [m]$, is assigned with a non-negative value in addition to weight, and we look for a solution to the SET COVER that not only minimizes the weight but also maximizes the value, then we call this problem as SET COVER KNAPSACK. Now it is easy to see that, SET COVER KNAPSACK problem is also NP-complete and hence we cannot hope to have a deterministic polynomial time algorithm unless $P \neq NP$. The optimization versions of the SET COVER KNAPSACK problem are SET COVER KNAPSACK WITH TARGET VALUE and SET COVER KNAPSACK WITH BUDGETED WEIGHT. In SET COVER KNAPSACK WITH TARGET VALUE, the desired solution must be a solution to the SET COVER problem and must meet the desired value, say d with minimum weight. On the other hand, the solution to the SET COVER KNAPSACK WITH BUDGETED WEIGHT problem, must maximize the value while not exceeding the given weight, say s . We formally define the problems below.

► **Definition 16** (SET COVER KNAPSACK WITH TARGET VALUE). *Given a universe \mathcal{U} of n elements and a family of subsets $\mathcal{F} = \{1, 2, \dots, m\}$ where each $\mathcal{S}_i \subseteq \mathcal{U}$, $\forall i \in [m]$ and a non negative weight $w(i) \geq 0$ and value $\alpha(i) \geq 0$ for each subset \mathcal{S}_i , $\forall i \in [m]$. The goal is to find $\mathcal{I} \subseteq \{1, 2, \dots, m\}$ that minimizes $\sum_{i \in \mathcal{I}} w(i)$ subject to $\bigcup_{i \in \mathcal{I}} \mathcal{S}_i = \mathcal{U}$ such that the total value is at least d .*

► **Definition 17** (SET COVER KNAPSACK WITH BUDGETED WEIGHT). *Given a universe \mathcal{U} of n elements and a family of subsets $\mathcal{F} = \{1, 2, \dots, m\}$ where each $\mathcal{S}_i \subseteq \mathcal{U}$, $\forall i \in [m]$, and a non negative weight $w(i) \geq 0$ and value $\alpha(i) \geq 0$ for each subset \mathcal{S}_i , $\forall i \in [m]$. The goal is to find $\mathcal{I} \subseteq \{1, 2, \dots, m\}$ that maximizes $\sum_{i \in \mathcal{I}} \alpha(i)$ subject to $\bigcup_{i \in \mathcal{I}} \mathcal{S}_i = \mathcal{U}$ such that the total weight is at most s .*

Till now we have considered the VERTEX COVER KNAPSACK problem for planar graphs. We now generalise the problem for hyper-graphs using d-HITTING SET. The d-HITTING SET problem is one of the fundamental combinatorial optimization problems: given a set of points \mathcal{P} and a set of geometric objects \mathcal{D} in the plane, the goal is to compute a small-sized subset of \mathcal{P} that hits all objects in \mathcal{D} [6]. This problem suitably capture the vertex cover problem on hyper-graphs [13].

► **Definition 18** (d-HITTING SET). *Given a universe \mathcal{U} of n elements and a family of subsets $\mathcal{F} = \mathcal{S}_1, \mathcal{S}_2, \dots, \mathcal{S}_m$ where each $\mathcal{S}_i \subseteq \mathcal{U}$ $\forall i \in [m]$, $|\mathcal{S}_i| \leq d$, and a non negative weight $w(j) \geq 0$ for each element j , $\forall j \in [n]$. The goal is to find $\mathcal{J} \subseteq \{1, 2, \dots, n\}$ that minimizes $\sum_{j \in \mathcal{J}} w(j)$ such that each subset \mathcal{S}_i is hit by some element in \mathcal{J} .*

It is easy to see that SET COVER is dual to d-HITTING SET, meaning that it is exactly the same problem, i.e we are looking for a set cover in the dual set system. There is a ρ factor approximation algorithm for d-HITTING SET if and only if there is a ρ factor approximation algorithm for SET COVER [27]. Similar to the SET COVER KNAPSACK, we can formulate d-HITTING SET KNAPSACK problem. In the d-HITTING SET problem we assign values and weights to the elements of the Universe.

► **Definition 19** (d-HITTING SET KNAPSACK WITH TARGET VALUE). *Given a universe \mathcal{U} of n elements and a family of subsets $\mathcal{F} = \mathcal{S}_1, \mathcal{S}_2, \dots, \mathcal{S}_m$ where each $\mathcal{S}_i \subseteq \mathcal{U}$ $\forall i \in [m]$, $|\mathcal{S}_i| \leq d$, and a non negative weight $w(j) \geq 0$ and a non negative value $\alpha(j)$, $\forall j \in [n]$. The goal is to find $\mathcal{J} \subseteq \{1, 2, \dots, n\}$ that minimizes $\sum_{j \in \mathcal{J}} w(j)$ such that each subset \mathcal{S}_i is hit by some element in \mathcal{J} and the total value is at least d .*

XX:12 Knapsack with Vertex Cover, Set Cover, and Hitting Set

► **Definition 20** (d-HITTING SET KNAPSACK WITH BUDGETED WEIGHT). *Given a universe \mathcal{U} of n elements and a family of subsets $\mathcal{F} = \mathcal{S}_1, \mathcal{S}_2, \dots, \mathcal{S}_m$ where each $\mathcal{S}_i \subseteq \mathcal{U} \forall i \in [m]$, $|\mathcal{S}_i| \leq d$, and a non negative weight $w(j) \geq 0$ and a non negative value $\alpha(j)$, $\forall j \in [n]$. The goal is to find $\mathcal{J} \subseteq \{1, 2, \dots, n\}$ that maximizes $\sum_{j \in \mathcal{J}} \alpha(j)$ such that each subset \mathcal{S}_i is hit by some element in \mathcal{J} and the total weight is at most s .*

We now focus on the SET COVER problem due to the ease of exposition. We formulate SET COVER KNAPSACK WITH TARGET VALUE problem as the following integer linear programming, in which the primal variable x_i indicates whether set \mathcal{S}_i is chosen to be in the solution or not:

$$\begin{aligned} & \text{minimize } \sum_{i \in [m]} w(i)x_i \\ & \text{Subject to:} \\ & \sum_{i: e_j \in \mathcal{S}_i} x_i \geq 1, \forall e_j \in \mathcal{U} \\ & \sum_{i \in [m]} \alpha(i)x_i \geq d \\ & x_i \in \{0, 1\}, \forall i \in [m] \end{aligned}$$

The above formulation has a bad integrality gap. We think of an alternative formulation where for each subset $\mathcal{A} \subseteq \mathcal{F}$ of sets such that $\alpha(\mathcal{A}) = \sum_{i \in \mathcal{A}} \alpha(i) < d$. We define the residual value $d_{\mathcal{A}} = d - \alpha(\mathcal{A})$. Given the set \mathcal{A} , we simplify the problem on the sets $\mathcal{F} - \mathcal{A}$, where the target value is now $d_{\mathcal{A}}$. We also reduce the value of the each set $\mathcal{S}_i \in \mathcal{F} - \mathcal{A}$ to be the minimum of its own value and $d_{\mathcal{A}}$ i.e let $\alpha^{\mathcal{A}}(i) = \min(\alpha(i), d_{\mathcal{A}})$. We can now give the following Integer linear programming formulation of the problem:

$$\begin{aligned} & \text{minimize } \sum_{i \in [m]} w(i)x_i \\ & \text{Subject to:} \\ & \sum_{i: e_j \in \mathcal{S}_i} x_i \geq 1, \forall e_j \in \mathcal{U} \\ & \sum_{i \in \mathcal{F} - \mathcal{A}} \alpha^{\mathcal{A}}(i)x_i \geq d_{\mathcal{A}}, \forall \mathcal{A} \subseteq \mathcal{F} \\ & x_i \in \{0, 1\}, \forall i \in [m] \end{aligned}$$

We replace the constraints $x_i \in \{0, 1\}$, with $x_i \geq 0$ to obtain linear programming relaxation of the integer linear program. The dual of the linear programming relaxation is :

$$\begin{aligned} & \text{maximize } \sum_{\mathcal{A}: \mathcal{A} \subseteq \mathcal{F}} d_{\mathcal{A}}y_{\mathcal{A}} + \sum_{j \in [n]} y_j \\ & \text{Subject to:} \\ & \sum_{j: e_j \in \mathcal{S}_i} y_j \leq w(i), \forall \mathcal{S}_i \in \mathcal{F} \\ & \sum_{\mathcal{A} \subseteq \mathcal{F}: i \notin \mathcal{A}} \alpha^{\mathcal{A}}(i)y_{\mathcal{A}} \leq w(i), \forall i \in \mathcal{F} \\ & y_{\mathcal{A}} \geq 0, \forall \mathcal{A} \subseteq \mathcal{F} \end{aligned}$$

We can now give a primal dual algorithm in Algorithm 1 for the SET COVER KNAPSACK WITH TARGET VALUE problem by modifying the algorithm given in [30] using the primal dual formulations given above.

■ **Algorithm 1** Primal Dual algorithm for the SET COVER KNAPSACK WITH TARGET VALUE problem

```

1:  $y \leftarrow 0$ 
2:  $\mathcal{A} \leftarrow \emptyset$ 
3: while  $\alpha(\mathcal{A}) < d$  do
4:   Increase  $y_{\mathcal{A}}$  until for some  $i \in \mathcal{F} - \mathcal{A}$ ,  $\sum_{\mathcal{B} \subseteq \mathcal{F}: i \notin \mathcal{B}} \alpha^{\mathcal{B}}(i) y_{\mathcal{B}} \leq w(i)$ 
5:    $\mathcal{A} \leftarrow \mathcal{A} \cup \{i\}$ 
6: end while
7:  $\mathcal{X} \leftarrow \mathcal{A}$ 
8:  $\mathcal{A}' \leftarrow \mathcal{A}$ 
9: while  $\exists e_j \notin \bigcup_{i \in \mathcal{A}'} \mathcal{S}_i$  do
10:  Increase  $y_j$  until there is some  $l$  with  $e_j \in \mathcal{S}_l$  such that  $\sum_{j: e_j \in \mathcal{S}_l} y_j \leq w(l)$ 
11:   $\mathcal{A}' \leftarrow \mathcal{A}' \cup \{l\}$ 
12: end while
13: return  $\mathcal{A}'$ 

```

► **Theorem 21.** *Algorithm 1 is a f -approximation algorithm for the SET COVER KNAPSACK WITH TARGET VALUE problem, where f is the frequency of the most frequent element.*

Proof. Let \mathcal{A}' be the output set of our algorithm that contains the indices of the sets that are picked up. Suppose our algorithm returns ALG

$$ALG = \sum_{i \in \mathcal{A}'} w(i) x_i \tag{1}$$

$$= \sum_{i \in \mathcal{X}} w(i) x_i + \sum_{i \in \mathcal{A}' - \mathcal{X}} w(i) x_i \tag{2}$$

Let OPT be the optimal solution to the SET COVER KNAPSACK WITH TARGET VALUE problem l be the final set selected by the algorithm after termination of the first while loop, and let \mathcal{X} be the sets returned at the end of the first while loop. Since the while condition terminates when $\alpha(\mathcal{A}) \geq d$, we know that $\alpha(\mathcal{X}) \geq d$; since set l was added to \mathcal{X} , it must be the case that before l was added, the total value of the set of items was less than d , so that $\alpha(\mathcal{X} - \{l\}) < d$. Following the standard primal-dual analysis, we know that

$$\sum_{i \in \mathcal{X}} w(i) = \sum_{i \in \mathcal{X}} \sum_{\mathcal{A} \subseteq \mathcal{F}: i \notin \mathcal{A}} \alpha^{\mathcal{A}}(i) y_{\mathcal{A}}. \tag{3}$$

Reversing the double sum, we have that

$$\sum_{i \in \mathcal{X}} \sum_{\mathcal{A} \subseteq \mathcal{F}: i \notin \mathcal{A}} \alpha^{\mathcal{A}}(i) y_{\mathcal{A}} = \sum_{\mathcal{A} \subseteq \mathcal{F}} y_{\mathcal{A}} \sum_{i \in \mathcal{X} - \mathcal{A}} \alpha^{\mathcal{A}}(i). \tag{4}$$

Note that in any iteration of the algorithm except the last one, adding the next set i to the current sets in \mathcal{A} did not cause the value of the knapsack to become at least d ; that

XX:14 Knapsack with Vertex Cover, Set Cover, and Hitting Set

is, $\alpha(i) < d - \alpha(\mathcal{A}) = d_{\mathcal{A}}$ at that point in the algorithm. Thus, for all sets $i \in \mathcal{A}$ except l , $\alpha^{\mathcal{A}}(i) = \min(\alpha(i), d_{\mathcal{A}}) = \alpha(i)$, for the point in the algorithm at which \mathcal{A} was the current set of sets. Thus, we can rewrite

$$\sum_{i \in \mathcal{X} - \mathcal{A}} \alpha^{\mathcal{A}}(i) = \alpha^{\mathcal{A}}(l) + \sum_{i \in \mathcal{X} - \mathcal{A}: i \neq l} \alpha^{\mathcal{A}}(i) = \alpha^{\mathcal{A}}(l) + \alpha(\mathcal{X} - \{l\}) - \alpha(\mathcal{A}). \quad (5)$$

Note that $\alpha^{\mathcal{A}}(l) \leq d_{\mathcal{A}}$ by definition, and as argued at the beginning of the proof $\alpha(\mathcal{X} - \{l\}) < d$ so that $\alpha(\mathcal{X} - \{l\}) - \alpha(\mathcal{A}) < d - \alpha(\mathcal{A}) = d_{\mathcal{A}}$; thus, we have that

$$\alpha^{\mathcal{A}}(l) + \alpha(\mathcal{X} - \{l\}) - \alpha(\mathcal{A}) < 2d_{\mathcal{A}}. \quad (6)$$

Therefore,

$$\sum_{i \in \mathcal{X}} w(i) = \sum_{\mathcal{A} \subseteq \mathcal{F}} y_{\mathcal{A}} \sum_{i \in \mathcal{X} - \mathcal{A}} \alpha^{\mathcal{A}}(i) < 2 \sum_{\mathcal{A} \subseteq \mathcal{F}} d_{\mathcal{A}} y_{\mathcal{A}} \leq 2\text{OPT}, \quad (7)$$

where the final inequality follows by weak duality since $\sum_{\mathcal{A} \subseteq \mathcal{F}} d_{\mathcal{A}} y_{\mathcal{A}} + \sum_{j \in [n]} y_j$ is the dual objective function.

Note that our algorithm also returns $\sum_{i \in \mathcal{A}' - \mathcal{X}} w(i)x_i$. It is interesting to see that our algorithm picks $\mathcal{A}' - \mathcal{X}$ sets only when \mathcal{X} does not constitute a valid set cover. Therefore, given \mathcal{X} our original problem now reduces to find only a valid set cover as the desired value is already met by \mathcal{X} .

We know that the primal dual algorithm for the SET COVER problem is a f factor approximation algorithm where f is the frequency of the most frequent element, see [30].

Therefore, from Equation 7, we have

$$ALG = \sum_{i \in \mathcal{A}'} w(i)x_i \quad (8)$$

$$= \sum_{i \in \mathcal{X}} w(i)x_i + \sum_{i \in \mathcal{A}' - \mathcal{X}} w(i)x_i \quad (9)$$

$$\leq 2 \sum_{\mathcal{A} \subseteq \mathcal{I}} d_{\mathcal{A}} y_{\mathcal{A}} + f \sum_{j \in [n]} y_j \quad (10)$$

$$\leq f \left(\sum_{\mathcal{A} \subseteq \mathcal{I}} d_{\mathcal{A}} y_{\mathcal{A}} + \sum_{j \in [n]} y_j \right) \quad (11)$$

$$= f\text{OPT} \quad (12)$$

◀

► **Corollary 22.** *Similar to Theorem 21, we obtain a d -factor approximation algorithm for the d -HITTING SET KNAPSACK WITH TARGET VALUE problem.*

There exists a H_g - approximation algorithm for the SET COVER problem [30]. We now present an alternative approximation algorithm that returns a H_g factor solution for the SET COVER problem, where g is the size of the maximum sized subset using the dual fitting analysis.

■ **Algorithm 2** A $\max(2, H_g)$ -algorithm for SET COVER KNAPSACK WITH TARGET VALUE problem

```

1:  $y \leftarrow 0$ 
2:  $\mathcal{A} \leftarrow \emptyset$ 
3: while  $\alpha(\mathcal{A}) < d$  do
4:   Increase  $y_{\mathcal{A}}$  until for some  $i \in \mathcal{F} - \mathcal{A}$ ,  $\sum_{\mathcal{B} \subseteq \mathcal{F}: i \notin \mathcal{B}} \alpha^{\mathcal{B}}(i) y_{\mathcal{B}} \leq w(i)$ 
5:    $\mathcal{A} \leftarrow \mathcal{A} \cup \{i\}$ 
6: end while
7:  $\mathcal{X} \leftarrow \mathcal{A}$ 
8:  $\mathcal{U}' \leftarrow \mathcal{U} - \bigcup_{i \in \mathcal{X}} \mathcal{S}_i$ 
9:  $\mathcal{F}' \leftarrow \mathcal{F} - \mathcal{X}$ 
10:  $I \leftarrow \emptyset$ 
11:  $\hat{\mathcal{S}}_i \leftarrow \mathcal{S}_i$  for all  $i \in \mathcal{F}'$ 
12: while  $I$  is not a set cover for  $\mathcal{U}'$  do
13:    $l \leftarrow \arg \min_{i: \hat{\mathcal{S}}_i \neq \emptyset} \frac{w(i)}{|\hat{\mathcal{S}}_i|}$ 
14:    $I \leftarrow I \cup \{l\}$ 
15:    $\hat{\mathcal{S}}_i \leftarrow \hat{\mathcal{S}}_i - \mathcal{S}_l$  for all  $i \in \mathcal{F}'$ 
16: end while
17: return  $\mathcal{X} \cup I$ 

```

► **Theorem 23.** *Algorithm 2 returns a solution indexed by $\mathcal{X} \cup I$ such that*

$$\sum_{i \in \mathcal{X} \cup I} w(i) \leq \max(2, H_g) \cdot \text{OPT}.$$

Proof. To prove the theorem, we construct an infeasible dual solution y such that

$$\sum_{i \in I} w_i = \sum_{j=1}^n y_j. \quad (13)$$

We will then show that $y' = \frac{1}{H_g} y$ is a feasible dual solution. By the weak duality theorem,

$$\sum_{i=j}^n y'_j \leq \text{LP OPT}, \quad (14)$$

so that

$$\sum_{i \in I} w_i = \sum_{j=1}^n y_j = H_g \sum_{j=1}^n y'_j \leq H_g \cdot \text{OPT}. \quad (15)$$

In order to construct the infeasible dual solution y , suppose we choose to add subset \mathcal{S}_i to our solution in iteration k . Then for each $e_j \in \hat{\mathcal{S}}_i$, we set $y_j = \frac{w(i)}{|\hat{\mathcal{S}}_i|}$. Since each $e_j \in \hat{\mathcal{S}}_i$ is uncovered in iteration k , and is then covered for the remaining iterations of the algorithm (because we added subset \mathcal{S}_i to the solution), the dual variable y_j is set to a value exactly once; in particular, it is set in the iteration in which element e_j is covered. Furthermore,

$$w(i) = \sum_{i: e_j \in \hat{\mathcal{S}}_i} y_j \quad (16)$$

XX:16 Knapsack with Vertex Cover, Set Cover, and Hitting Set

i.e, the weight of the subset \mathcal{S}_i chosen in the k -th iteration is equal to the sum of the duals y_j of the uncovered elements that are covered in the k -th iteration. This immediately implies that

$$\sum_{j \in \mathcal{I}} w(i) = \sum_{i=1}^n y_j. \quad (17)$$

It remains to prove that the dual solution $y' = \frac{1}{H_g}y$ is feasible. We must show that for each subset \mathcal{S}_i ,

$$\sum_{i: e_j \in \mathcal{S}_i} y'_j \leq w(i). \quad (18)$$

Pick an arbitrary subset \mathcal{S}_i . Let a_k be the number of elements in this subset that are still uncovered at the beginning of the k -th iteration, so that $a_1 = |\mathcal{S}_i|$, and $a_{l+1} = 0$. Let A_k be the uncovered elements of \mathcal{S}_i covered in the k -th iteration, so that $|A_k| = a_k - a_{k+1}$. If subset \mathcal{S}_p is chosen in the k -th iteration, then for each element $e_j \in A_k$ covered in the k -th iteration,

$$y'_j = \frac{w_p}{H_g |\hat{\mathcal{S}}_p|} \leq \frac{w(i)}{H_g a_k}, \quad (19)$$

where $\hat{\mathcal{S}}_p$ is the set of uncovered elements of \mathcal{S}_p at the beginning of the k -th iteration. The inequality follows because if \mathcal{S}_p is chosen in the k -th iteration, it must minimize the ratio of its weight to the number of uncovered elements it contains. Thus,

$$\begin{aligned} \sum_{i: e_j \in \mathcal{S}_i} y'_j &= \sum_{k=1}^l \sum_{i: e_j \in A_k} y'_j \\ &\leq \sum_{k=1}^l (a_k - a_{k+1}) \frac{w(i)}{H_g a_k} \\ &\leq \frac{w(i)}{H_g} \sum_{k=1}^l \frac{a_k - a_{k+1}}{a_k} \\ &\leq \frac{w(i)}{H_g} \sum_{k=1}^l \left(\frac{1}{a_k} + \frac{1}{a_k - 1} + \dots + \frac{1}{a_{k+1} + 1} \right) \\ &\leq \frac{w(i)}{H_g} \sum_{i=1}^{|\mathcal{S}_i|} \frac{1}{i} \\ &= \frac{w(i)}{H_g} H_{|\mathcal{S}_i|} \\ &\leq w(i), \end{aligned}$$

where the final inequality follows because $|\mathcal{S}_i| \leq g$.

Now we know,

$$ALG = \sum_{i \in \mathcal{X}} w(i)x_i + \sum_{i \in \mathcal{I}} w(i)x_i \quad (20)$$

From Equation 7, we know that $\sum_{i \in \mathcal{X}} w(i)x_i$ is at most $2 \leq 2OPT$. Also, from Equation 15, we have $\sum_{i \in \mathcal{I}} w(i)x_i$ is at most H_g . Therefore,

$$ALG = \sum_{i \in \mathcal{X}} w(i)x_i + \sum_{i \in \mathcal{I}} w(i)x_i \quad (21)$$

$$\leq 2 \sum_{A: A \subseteq \mathcal{F}} d_{\mathcal{A}} y_{\mathcal{A}} + H_g \sum_{j \in [n]} y_j \quad (22)$$

$$= \max(2, H_g) \left(\sum_{A: A \subseteq \mathcal{F}} d_{\mathcal{A}} y_{\mathcal{A}} + \sum_{j \in [n]} y_j \right) \quad (23)$$

$$= \max(2, H_g) OPT \quad (24)$$

◀

We obtain the following corollary from Theorem 21.

Since VERTEX COVER KNAPSACK is a special case of the SET COVER KNAPSACK problem it follows that:

► **Corollary 24.** *There is a 2-approximation algorithm for the VERTEX COVER KNAPSACK WITH TARGET VALUE problem.*

However, surprisingly the same cannot be said about the SET COVER KNAPSACK WITH BUDGETED WEIGHT problem. Interestingly, SET COVER KNAPSACK WITH BUDGETED WEIGHT problems turns out to be hard to approximate.

► **Theorem 25.** *For any $\rho > 1$, there does not exist a ρ -approximation algorithm for the SET COVER KNAPSACK WITH BUDGETED WEIGHT problem, unless $P = NP$.*

Proof. Suppose there exists a ρ -approximation algorithm for SET COVER KNAPSACK WITH BUDGETED WEIGHT problem. We consider the VERTEX COVER problem, which is NP-complete. In the VERTEX COVER problem, we are given a graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$ and an integer k , and we must decide if there exists a subset $\mathcal{V}' \subseteq \mathcal{V}$ of size at most k such that each edge $e \in \mathcal{E}$ is covered by at least one vertex in \mathcal{V}' . Given an instance of the VERTEX COVER problem, we can define an instance of the SET COVER KNAPSACK WITH BUDGETED WEIGHT problem by setting the universe of elements to be the set of edges, $\mathcal{U} = \{e_1, e_2, \dots, e_n\}, \forall e_j \in \mathcal{E}$, the family of subsets to be the vertices that contain the edges that are incident to the corresponding vertices, $\mathcal{F} = \{v_1, v_2, \dots, v_n\}, \forall v_i \in \mathcal{V}$, where each $v_i = \{e_j \in \mathcal{E} : e_j \text{ is incident on } v_i\}$. We set the weight and value of each v_i to be 1 $\forall v_i \in \mathcal{F}$: there exists a vertex cover of size k if and only if the optimal value for this SET COVER KNAPSACK WITH BUDGETED WEIGHT instance is k . Furthermore, any ρ approximation algorithm must always produce a solution $\leq \rho k$ if such a solution exists. Therefore, we can answer the decision version of the VERTEX COVER problem in polynomial time contradicting the assumption that $P \neq NP$. ◀

Similar results hold for the dual problem:

► **Corollary 26.** *For any $\rho > 1$, there does not exist a ρ -approximation algorithm for the d -HITTING SET KNAPSACK WITH BUDGETED WEIGHT problem, unless $P = NP$.*

It is easy to see that vertex cover is a 2-HITTING SET problem and follows that:



XX:18 Knapsack with Vertex Cover, Set Cover, and Hitting Set

► **Corollary 27.** *For any $\rho > 1$, there does not exist a ρ -approximation algorithm for the VERTEX COVER KNAPSACK WITH BUDGETED WEIGHT problem, unless $P = NP$.*

At this point, we revisit the MINIMAL VERTEX COVER KNAPSACK problem. Interestingly, it turns out that both the versions: target value and budgeted weight are hard to approximate. To see this, let us first consider the MINIMAL VERTEX COVER KNAPSACK problem with target value. Consider the value and weight associated with each vertex to be 1 and set the target value $d = k$. Solving this problem is equivalent to answer the question if there exists a MINIMUM VERTEX COVER KNAPSACK of size k . Thus, by adjusting the value of k from 1 to n , we can have an answer for the minimum VERTEX COVER problem in polynomial time, contradicting the assumption $P \neq NP$. Similar to Theorem 25, MINIMAL VERTEX COVER KNAPSACK problem with budgeted weight is also hard to approximate.

► **Theorem 28.** *The MINIMAL VERTEX COVER KNAPSACK problem with target value and the MINIMAL VERTEX COVER KNAPSACK problem with budgeted weight do not admit a polynomial time ρ -approximation algorithm for any $\rho > 1$, unless $P = NP$.*

However, we do not rule out the possibility of a fixed parameter tractable (FPT) algorithm. In the next section, we give a FPT algorithm for the MINIMAL VERTEX COVER KNAPSACK problem on graphs with bounded treewidth.

5 Results: Parameterized Complexity

In this section, we design a dynamic programming algorithm for the MINIMAL VERTEX COVER KNAPSACK problem, parameterized by the *treewidth* of the input graph. There exists $2^{tw} \cdot tw^{O(1)} \cdot n$ algorithm for the VERTEX COVER problem [8]. Using a similar approach we can have dynamic programming algorithms for the VERTEX COVER KNAPSACK and MINIMUM VERTEX COVER KNAPSACK.

► **Theorem 29.** *There is an algorithm for VERTEX COVER KNAPSACK with running time $2^{O(tw)} \cdot n \cdot \min\{s, d\}$ where n is the number of vertices in the input graph, tw is the treewidth of the input graph, s is the input size of the knapsack and d is the input target value.*

Proof Sketch. Let $(G = (V_G, E_G), (w(u))_{u \in V_G}, (\alpha(u))_{u \in V_G}, s, d)$ be an input instance of Vertex Cover Knapsack such that $tw = tw(G)$. We consider a nice tree decomposition $(\mathbb{T} = (V_{\mathbb{T}}, E_{\mathbb{T}}), \mathcal{X})$ of G that is rooted at a node r .

We define a function $\ell : V_{\mathbb{T}} \rightarrow \mathbb{N}$. For a vertex $t \in V_{\mathbb{T}}$, $\ell(t) = \text{dist}_{\mathbb{T}}(t, r)$, where r is the root. Note that this implies that $\ell(r) = 0$. Let us assume that the values that ℓ takes over the nodes of \mathbb{T} is between 0 and L . Now, we describe a dynamic programming algorithm over $(\mathbb{T}, \mathcal{X})$ for Vertex Cover Knapsack .

States: We maintain a DP table D where a state has the following components:

1. t represents a node in $V_{\mathbb{T}}$.
2. \mathbb{S} represents a subset of the vertex subset X_t

Interpretation of States: For each node $t \in \mathbb{T}$ we keep a list $D[t, \mathbb{S}]$ for each $\mathbb{S} \subseteq X_t$, holding the vertex cover knapsack \mathbb{S}' of G_v with $\mathbb{S}' \cap X_t = \mathbb{S}$ if such a \mathbb{S}' exist, and $D[t, \mathbb{S}] = \infty$ otherwise.

For each state $[t, \mathbb{S}]$, we initialize $D[t, \mathbb{S}]$ to the list $\{(0, 0)\}$. Our computation shall be such that in the end each $D[t, \mathbb{S}]$ stores the set of all undominated feasible pairs (w, α) for the state $[t, \mathbb{S}]$.

Dynamic Programming on D : We describe the following procedure to update the table D . We start updating the table for states with nodes $t \in V_{\mathbb{T}}$ such that $\ell(t) = L$. When all such states are updated, then we move to update states where the node t has $\ell(t) = L - 1$, and so on till we finally update states with r as the node — note that $\ell(r) = 0$. For a particular j , $0 \leq j < L$ and a state $[t, \mathbb{S}]$ such that $\ell(t) = j$, we can assume that $D[t', \mathbb{S}']$ have been evaluated for all t' such that $\ell(t') > j$ and all subsets \mathbb{S}' of $X_{t'}$. Now we consider several cases by which $D[t, \mathbb{S}]$ is updated based on the nature of t in \mathbb{T} :

1. Suppose t is a leaf node with $X_t = \{v\}$. Then $D[t, \{v\}] = (w(v), \alpha(v))$ and $D[t, \emptyset]$ stores the pair $(0, 0)$.
2. Suppose t is an introduce node. Then it has an only child t' where $X_{t'} \subset X_t$ and there is exactly one vertex v that belongs to X_t but not $X_{t'}$. Then for all $\mathbb{S} \subseteq X_t$: First, suppose \mathbb{S} is not a vertex cover of $G[X_t]$, we set $D[t, \mathbb{S}] = \infty$.
Next, suppose $v \in \mathbb{S}$. Then for each pair (w, α) in $D[t', \mathbb{S} \setminus \{v\}]$, if $w + w(v) \leq s$ we add $(w + w(v), \alpha + \alpha(v))$ to the set in $D[t, \mathbb{S}]$. Otherwise we copy all pairs of $D[t', \mathbb{S}]$ to $D[t, \mathbb{S}]$.
3. Suppose t is a forget vertex node. Then it has an only child t' where $X_t \subset X_{t'}$ and there is exactly one vertex v that belongs to $X_{t'}$ but not to X_t . Then for all $\mathbb{S} \subseteq X_t$, we copy all feasible undominated pairs stored in $D[t', \mathbb{S}]$ to $D[t, \mathbb{S}]$. If any pair stored in $D[t, \mathbb{S}]$ is dominated by any pair of $D[t', \mathbb{S} \cup \{v\}]$, we copy only the undominated pairs to $D[t, \mathbb{S}]$.
4. Suppose t is a join node. Then it has two children t_1, t_2 such that $X_t = X_{t_1} = X_{t_2}$. Then for all $\mathbb{S} \subseteq X_t$, let $(w_{\mathbb{S}}, \alpha_{\mathbb{S}})$ be the total weight and value of the vertices in \mathbb{S} . Consider a pair (w_1, α_1) in $D[t_1, \mathbb{S}]$ and a pair (w_2, α_2) in $D[t_2, \mathbb{S}]$. Suppose $w_1 + w_2 - w_{\mathbb{S}} \leq s$. Then we add $(w_1 + w_2 - w_{\mathbb{S}}, \alpha_1 + \alpha_2 - \alpha_{\mathbb{S}})$ to $D[t, \mathbb{S}]$.

Finally, in the last step of updating $D[t, \mathbb{S}]$, we go through the list saved in $D[t, \mathbb{S}]$ and only keep undominated pairs.

Running time: There are n choices for the fixed vertex v . Upon fixing v and adding it to each bag of $(\mathbb{T}, \mathcal{X})$ we consider the total possible number of states. Observe that the number of subproblems is small: for every node t , we have only $2^{|X_t|}$ choices of S . Also, we do not need to remember \mathbb{S} explicitly; remembering the undominated and feasible weight and profit pair will suffice. For each state, for each w there can be at most one pair with w as the first coordinate; similarly, for each α there can be at most one pair with α as the second coordinate. Thus, the number of undominated pairs in each $D[t, \mathbb{S}]$ is at most $\min\{s, d\}$ time. Since the given graph \mathcal{G} has a bounded treewidth of at most tw , it is possible to construct a data structure in time $tw^{\mathcal{O}(1)} \cdot n$ that allows performing adjacency queries in time $\mathcal{O}(tw)$. For each node t it takes time $2^{tw} \cdot tw^{\mathcal{O}(1)} \cdot \min\{s, d\}$ to compute all the values $D[t, \mathbb{S}]$. Since we can assume that the number of nodes of the given tree decompositions is $\mathcal{O}(tw \cdot n)$, the total running time of the algorithm is $2^{\mathcal{O}(tw)} \cdot n \cdot \min\{s, d\}$ where n is the number of vertices in the input graph, tw is the treewidth of the input graph, s is the input size of the knapsack and d is the input target value. ◀

The maximum allowed value for tw is n , as we cannot have treewidth greater than the size of the nodes i.e n . With the above algorithm, we have a pseudo-polynomial time algorithm for trees since treewidth = 1. The following corollary holds for trees.

XX:20 Knapsack with Vertex Cover, Set Cover, and Hitting Set

► **Corollary 30.** *There is an algorithm for VERTEX COVER KNAPSACK WITH BUDGET for trees with complexity $\mathcal{O}(n^2 \cdot \min\{s, (\alpha(\mathcal{V}))\})$.*

We can suitably modify the algorithm for VERTEX COVER KNAPSACK to obtain an algorithm for MINIMUM VERTEX COVER KNAPSACK. Here we keep track of each $i \in [n]$ i.e. we check if there exists a valid vertex cover of size i . Thus, the number of states is bounded in FPT of n . We obtain the following theorem:

► **Theorem 31.** *There is an algorithm for MINIMUM VERTEX COVER KNAPSACK with running time $4^{\mathcal{O}(tw)} \cdot n \cdot \min\{s, d\}$ where n is the number of vertices in the input graph, tw is the treewidth of the input graph, s is the input size of the knapsack and d is the input target value.*

Interestingly, the same standard approach does not seem to hold good for the MINIMAL VERTEX COVER KNAPSACK. This is so because in case of a join node, say t , there can exist a vertex in the solution that is not redundant in either of the subgraphs rooted at t_1 and t_2 , where t_1 and t_2 are the children of t , but it becomes redundant for the subgraph rooted at t . We discuss an algorithm for MINIMAL VERTEX COVER KNAPSACK next.

► **Theorem 32.** *There is an algorithm for MINIMAL VERTEX COVER KNAPSACK with running time $8^{\mathcal{O}(tw)} \cdot n \cdot \min\{s, d\}$ where n is the number of vertices in the input graph, tw is the treewidth of the input graph, s is the input size of the knapsack and d is the input target value.*

Proof. Let $(G = (V_G, E_G), (w(u))_{u \in V_G}, (\alpha(u))_{u \in V_G}, s, d)$ be an input instance of Minimal Vertex Cover Knapsack such that $tw = tw(G)$. We consider a nice edge tree decomposition $(\mathbb{T} = (V_{\mathbb{T}}, E_{\mathbb{T}}), \mathcal{X})$ of G that is rooted at a node r .

We define a function $\ell : V_{\mathbb{T}} \rightarrow \mathbb{N}$. For a vertex $t \in V_{\mathbb{T}}$, $\ell(t) = \text{dist}_{\mathbb{T}}(t, r)$, where r is the root. Note that this implies that $\ell(r) = 0$. Let us assume that the values that ℓ takes over the nodes of \mathbb{T} is between 0 and L . Now, we describe a dynamic programming algorithm over $(\mathbb{T}, \mathcal{X})$ for MINIMAL VERTEX COVER KNAPSACK.

States: We maintain a DP table D where a state has the following components:

1. t represents a node in $V_{\mathbb{T}}$.
2. V_1, V_2 are subsets of the bag X_t , not necessarily disjoint.
3. V_1 represents the intersection of X_t with the minimal vertex cover knapsack of the subgraph $G_t \setminus$ the edges incident on $V_2 \setminus V_1$.

Interpretation of States: For each node $t \in \mathbb{T}$ we keep a list $D[t, V_1, V_2]$ for each $\mathbb{S} \subseteq X_t$, holding the minimal vertex cover knapsack S' of G_t with $S' \cap X_t = \mathbb{S} = V_1 \cup V_2$, if such a S' exist, and $D[t, V_1, V_2] = (\infty, \infty)$ otherwise. For a node t , V_1 is the intersection of X_t with the minimal vertex cover knapsack of the subgraph $G_t \setminus$ the edges incident on $V_2 \setminus V_1$.

Genesis of the subsets V_1 and V_2 : We wish to capture the information about the minimal solution in the subgraph defined by removing the edges incident on $V_2 \setminus V_1$. Maintaining this information at every node is essential to compute the minimal solution, especially in case of a join node. Consider that a node t is a join node i.e. it has two children t_1 and t_2 such that $X_t = X_{t_1} = X_{t_2}$. The nodes t_1 and t_2 are the root nodes for the subgraphs G_{t_1} and G_{t_2} . Here we guess a subset of vertices $\mathbb{S} \subseteq X_t$. In this case, it may so happen that

all vertices in \mathbb{S} might not be non-redundant. To see this, let us consider the graph G_{t_1} and observe how the vertices in \mathbb{S} could be redundant in G_{t_1} . Define V'_1 as the intersection of the minimal solution \mathbb{S}' with graph $G_{t_1} \setminus X_{t_1}$. Similarly, call V'_2 as the intersection of the minimal solution \mathbb{S}' with graph $G_{t_2} \setminus X_{t_2}$. Consider a vertex $a \in V'_1$, $b \in V_2$ and $c \in G_{t_2} \setminus (X_{t_2} \cup V'_2)$. Now it is easy to see that the vertex $b \in V_2$ is redundant in the subgraph G_{t_1} , however it is not redundant with respect to G_{t_2} . To keep track of non redundant vertices, we require to compute the intersection of a minimal solution in each subgraph of G_{t_1} , i.e we assume two subsets W_1 and W_2 of V_1 and maintain W_1 in G_{t_1} such that it contains all non redundant vertices of the minimal solution in the subgraph $G_{t_1} \setminus$ edges incident on $(W_2 \cap V_2) \setminus W_1$. In a similar fashion, W_2 stores all the non redundant vertices of the minimal solution in the subgraph $G_{t_2} \setminus$ edges incident on $(W_1 \cup V_2) \setminus W_1$. In other words, in particular for the case of a join node t , for a given pair of subsets V_1 and V_2 , V_1 is the intersection of X_t with a minimal solution. The set V_1 is further sub divided into sets W_1 and W_2 such that W_1 stores the non redundant vertices of the minimal solution in the graph G_{t_1} . We find $W_1 \subseteq V_1$, by checking whether the removal a vertex in V_1 , can still form a vertex cover of G_{t_1} , if so then we place that vertex in W_2 . Thus, we check for all such vertices and place only the non redundant vertices in W_1 for the subgraph G_{t_1} . Similarly, we compute the non redundant vertices of G_{t_2} , in W_2 . Now we can now easily compute the non redundant minimal vertex cover knapsack entries for $D[t, V_1, V_2]$ i.e. in t_1 , the state $D[t_1, W_1, W_2 \cup V_2]$ has to be looked up and in t_2 , $D[t_2, W_2, W_1 \cup V_2]$ has to be looked up.

For each state $D[t, V_1, V_2]$, we initialize $D[t, V_1, V_2]$ to the list $\{(0, 0)\}$. Our computation shall be such that in the end each $D[t, V_1, V_2]$ stores the set of all undominated feasible pairs (w, α) for the state $[t, V_1, V_2]$.

Dynamic Programming on D : We describe the following procedure to update the table D . We start updating the table for states with nodes $t \in V_{\mathbb{T}}$ such that $\ell(t) = L$. When all such states are updated, then we move to update states where the node t has $\ell(t) = L - 1$, and so on till we finally update states with r as the node — note that $\ell(r) = 0$. For a particular j , $0 \leq j < L$ and a state $[t, V_1, V_2]$ such that $\ell(t) = j$, we can assume that $D[t', V_1, V_2]$ have been evaluated for all t' , such that $\ell(t') > j$ and all subsets \mathbb{S}' of $X_{t'}$. Now we consider several cases by which $D[t, V_1, V_2]$ is updated based on the nature of t in \mathbb{T} :

1. Suppose t is a leaf node with $X_t = \{v\}$. Then $D[t, v, \emptyset] = (w(v), \alpha(v))$, or $D[t, \emptyset, v] = (0, 0)$ and $D[t, \emptyset, \emptyset]$ stores the pair $(0, 0)$.
2. Suppose t is an introduce node. Then it has an only child t' where $X_{t'} \subset X_t$ and there is exactly one vertex v that belongs to X_t but not $X_{t'}$. Then for all $\mathbb{S} \subseteq X_t$: First, suppose \mathbb{S} is not a vertex cover of $G[X_t]$, we set $D[t, V_1, V_2] = (\infty, \infty)$.
Otherwise, we have three cases:
 - a. Case 1: If $v \notin V_1 \cup V_2$, then we copy each pair (w, α) from $D[t', V_1, V_2]$
 - b. Case 2: If $v \in V_1$, then
 - i. we check if $N(v) \setminus V_1 \neq \emptyset$, then
 - A. if for each pair (w, α) in $D[t', V_1 \setminus \{v\}, V_2]$, $w + w(v) \leq s$, then add all such pairs $(w + w(v), \alpha + \alpha(v))$ in $D[t', V_1 \setminus \{v\}, V_2]$ to $D[t, V_1, V_2]$.
 - B. otherwise copy each pair (w, α) from $D[t', V_1 \setminus \{v\}, V_2]$ to $D[t, V_1, V_2]$.
 - ii. Otherwise we store (∞, ∞) .
 - c. Case 3: $v \in V_2$, then for each pair (w, α) in $D[t', V_1, V_2 \setminus \{v\}]$, we copy each pair of $D[t', V_1, V_2 \setminus \{v\}]$ to $D[t, V_1, V_2]$.

3. Suppose t is a forget vertex node. Then it has an only child t' where $X_t \subset X_{t'}$ and there is exactly one vertex v that belongs to $X_{t'}$ but not to X_t . We copy each undominated (w, α) pair stored in $D[t', V_1 \cup \{v\}, V_2]$, $D[t', V_1, V_2 \cup \{v\}]$ and $D[t', V_1, V_2]$ to $D[t, V_1, V_2]$.
4. Suppose t is a join node. Then it has two children t_1, t_2 such that $X_t = X_{t_1} = X_{t_2}$. Let $(w(V_1 \cap V_2), \alpha(V_1 \cap V_2))$ be the total weight and value of the vertices in $V_1 \cap V_2$. Then for all $W_1, W_2 \subseteq V_1 \subseteq X_t$, consider a pair (w_1, α_1) in $D[t_1, W_1, W_2 \cup V_2]$ and a pair (w_2, α_2) in $D[t_2, W_2, W_1 \cup V_2]$. Suppose $w_1 + w_2 - w(V_1 \cap V_2) \leq s$. Then we add $(w_1 + w_2 - w(V_1 \cap V_2), \alpha_1 + \alpha_2 - \alpha(V_1 \cap V_2))$ to $D[t, V_1, V_2]$.

Finally, in the last step of updating $D[t, V_1, V_2]$, we go through the list saved in $D[t, V_1, V_2]$ and only keep undominated pairs.

Correctness of the algorithm: We demonstrate the correctness of our algorithm by analyzing each case.

In each state we maintain the invariant $V_1, V_2 \subseteq X_t$ such that $V_1 = X_t \cap$ minimal vertex cover knapsack of $G_t \setminus$ edges incident on $V_2 \setminus V_1$. By definition,

1. **Leaf node:** Recall that in our modified nice tree decomposition we have added a vertex v to all the bags. Suppose a leaf node contains a single vertex v , $D[L, v, \emptyset] = (w(v), \alpha(v))$, $D[L, \emptyset, v] = (0, 0)$ and $D[L, \emptyset, \emptyset]$ stores the pair $(0, 0)$. This is true in particular when $i = L$, the base case. From now we can assume that for a node t with $\ell(t) = j < L$ all $D[t', V_1, V_2]$ entries are correct and correspond to minimal vertex cover in $G_{t'}$ when $\ell(t') > j$.
2. **Introduce node:** When t is an introduce node, there is a child t' . We are introducing a vertex v and the edges associated with it G_t . Since $\ell(t') > \ell(t)$, by induction hypothesis all entries in $D[t', V_1 \setminus \{v\}, V_2]$ and $D[t', V_1, V_2 \setminus \{v\}]$, $\forall V_1 \setminus \{v\}, V_2 \setminus \{v\} \subseteq X_{t'}$ are already computed. We update pairs in $D[t, V_1, V_2]$ from $D[t', V_1 \setminus \{v\}, V_2]$ and $D[t', V_1, V_2 \setminus \{v\}]$ such that either v is considered as part of a minimal solution or not.
3. **Forget node:** When t is a forget node, there is a child t' . We are forgetting a vertex v and the edges associated with it G_t . Since $\ell(t') > \ell(t)$, by induction hypothesis all entries in $D[t', V_1 \cup \{v\}, V_2]$, $D[t', V_1, V_2 \cup \{v\}]$, and $D[t', V_1, V_2]$, $\forall V_1, V_2, V_1 \cup \{v\}, V_2 \cup \{v\} \subseteq X_{t'}$ are already computed. We copy each undominated (w, α) pair stored in $D[t', V_1 \cup \{v\}, V_2]$, $D[t', V_1, V_2 \cup \{v\}]$ and $D[t', V_1, V_2]$ to $D[t, V_1, V_2]$.
4. **Join node:** When t is a forget node, there are two children t_1 and t_2 of t , such that $X_t = X_{t_1} = X_{t_2}$. For all subsets $V_1 \subseteq X_t$ we partition V_1 into two subsets W_1 and W_2 (not necessarily disjoint) such that W_1 is the intersection of X_{t_1} with minimal solution in the graph $G_{t_1} \setminus$ edges incident on $(W_2 \cup V_2) \setminus W_1$. Similarly, W_2 is the intersection of X_{t_2} with minimal solution in the graph $G_{t_2} \setminus$ edges incident on $(W_1 \cup V_2) \setminus W_2$. By the induction hypothesis, the computed entries in $D[t_1, W_1, W_2 \cup V_2]$ and $D[t_2, W_2, W_1 \cup V_2]$ where $W_1 \cup W_2 = V_1$ are correct and store the non redundant minimal vertex cover for the subgraph G_{t_1} in W_1 and similarly, W_2 for G_{t_2} . Now we add $(w_1 + w_2 - w(V_1 \cap V_2), \alpha_1 + \alpha_2 - \alpha(V_1 \cap V_2))$ to $D[t, V_1, V_2]$.

Running Time: There are n choices for the fixed vertex v . Upon fixing v and adding it to each bag of $(\mathbb{T}, \mathcal{X})$ we consider the total possible number of states. Observe that the number of subproblems is small: for every node t , we have only $2^{|X_t|}$ choices of S , $2^{|S|}$ choices for V_1 and $2^{|V_1|}$ choices for W_1 i.e., $\mathcal{O}(8^{|X_t|})$. Also, we do not need to remember \mathbb{S} explicitly; remembering the undominated and feasible weight and profit pair will suffice. Therefore, are at most $\mathcal{O}(n) \cdot 8^{\text{tw}+1}$ states. For each state, since we are keeping only undominated

pairs, for each w there can be at most one pair with w as the first coordinate; similarly, for each α there can be at most one pair with α as the second coordinate. Thus, the number of undominated pairs in each $D[t, V_1, V_2]$ is at most $\min\{s, d\}$. By the description of the algorithm, the maximum length of the list stored at $D[t, V_1, V_2]$ during updation, but before the check is made for only undominated pairs, is $8^{tw+1} \cdot \min\{s, d\}$. Thus, updating the DP table at any vertex takes $8^{tw+1} \cdot \min\{s, d\}$ time. Since there are $\mathcal{O}(n \cdot tw)$ vertices in \mathbb{T} , the total running time of the algorithm is $8^{\mathcal{O}(tw)} \cdot n \cdot \min\{s, d\}$. ◀

The treewidth of a tree is 1. This implies the following corollary:

► **Corollary 33.** *There exists an algorithm for VERTEX COVER KNAPSACK for trees running in time $\mathcal{O}(n \cdot \min\{s, d\})$.*

The above corollary also implies that VERTEX COVER KNAPSACK for trees is pseudo polynomial.

6 Conclusion

We study the classical Knapsack problem with the graph theoretic constraints, namely vertex cover and its interesting variants like MINIMUM VERTEX COVER KNAPSACK, MINIMAL VERTEX COVER KNAPSACK and VERTEX COVER KNAPSACK WITH BUDGET for both general graphs and trees. We show that the VERTEX COVER KNAPSACK is strongly NP-complete and show the computational complexity of the other variants. We also discuss the generalized version of the problem i.e. SET COVER KNAPSACK and d-HITTING SET. Our results show the existence of a 2-factor approximation algorithm for VERTEX COVER KNAPSACK WITH TARGET VALUE and the unlikeliness of a ρ -factor algorithm for VERTEX COVER KNAPSACK WITH BUDGETED WEIGHT. Parameterized by the treewidth of a given graph, we also prove that all the variants admit FPT algorithms.

References

- 1 Giorgio Ausiello, Pierluigi Crescenzi, Giorgio Gambosi, Viggo Kann, Alberto Marchetti-Spaccamela, and Marco Protasi. *Complexity and approximation: Combinatorial optimization problems and their approximability properties*. Springer Science & Business Media, 2012.
- 2 R Balasubramanian, Michael R Fellows, and Venkatesh Raman. An improved fixed-parameter algorithm for vertex cover. *Information Processing Letters*, 65(3):163–168, 1998.
- 3 Reuven Bar-Yehuda and Shimon Even. A linear-time approximation algorithm for the weighted vertex cover problem. *Journal of Algorithms*, 2(2):198–203, 1981.
- 4 Reuven Bar-Yehuda and Shimon Even. A local-ratio theorem for approximating the weighted vertex cover problem. In *North-Holland Mathematics Studies*, volume 109, pages 27–45. Elsevier, 1985.
- 5 Nicolas Boria, Federico Della Croce, and Vangelis Th Paschos. On the max min vertex cover problem. *Discrete Applied Mathematics*, 196:62–71, 2015.
- 6 Norbert Bus, Nabil H Mustafa, and Saurabh Ray. Practical and efficient algorithms for the geometric hitting set problem. *Discrete Applied Mathematics*, 240:25–32, 2018.
- 7 Miroslav Chlebík and Janka Chlebíková. Crown reductions for the minimum weighted vertex cover problem. *Discrete Applied Mathematics*, 156(3):292–312, 2008.
- 8 Marek Cygan, Fedor V Fomin, Lukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh. *Parameterized algorithms*, volume 5. Springer, 2015.
- 9 Peter Damaschke. Parameterized algorithms for double hypergraph dualization with rank limitation and maximum minimal vertex cover. *Discrete Optimization*, 8(1):18–24, 2011.
- 10 François Delbot and Christian Laforest. Analytical and experimental comparison of six algorithms for the vertex cover problem. *Journal of Experimental Algorithmics (JEA)*, 15:1–1, 2010.
- 11 Rodney G Downey, Michael R Fellows, and Ulrike Stege. Parameterized complexity: A framework for systematically confronting computational intractability. *Contemporary Trends in Discrete Mathematics*, 49:49–99, 1997.
- 12 Rodney G Downey and Michael Ralph Fellows. *Parameterized complexity*. Springer Science & Business Media, 2012.
- 13 Stephane Durocher and Robert Fraser. Duality for geometric set cover and geometric hitting set problems on pseudodisks. In *CCCG*, 2015.
- 14 Bruno Escoffier, Laurent Gourvès, and Jérôme Monnot. Complexity and approximation results for the connected vertex cover problem in graphs and hypergraphs. *Journal of Discrete Algorithms*, 8(1):36–49, 2010.
- 15 MR Fellows and U Stege. An improved fixed-parameter-tractable algorithm for vertex cover. *Relatório técnico, Department of Computer Science, ETH Zurich*, 1999.
- 16 Henning Fernau. *Parameterized algorithmics: A graph-theoretic approach*. PhD thesis, Citeseer, 2005.
- 17 Fedor V Fomin, Serge Gaspers, and Saket Saurabh. Branching and treewidth based exact algorithms. In *Algorithms and Computation: 17th International Symposium, ISAAC 2006, Kolkata, India, December 18–20, 2006. Proceedings 17*, pages 16–25. Springer, 2006.
- 18 Toshihiro Fujito and Tomoya Nakamura. Eternal connected vertex cover problem. In *Theory and Applications of Models of Computation: 16th International Conference, TAMC 2020, Changsha, China, October 18–20, 2020, Proceedings 16*, pages 181–192. Springer, 2020.
- 19 Michael R Garey and David S. Johnson. The rectilinear steiner tree problem is np-complete. *SIAM Journal on Applied Mathematics*, 32(4):826–834, 1977.
- 20 Michael R Garey and David S Johnson. Computers and intractability. *A Guide to the*, 1979.
- 21 David G. Harris and N. S. Narayanaswamy. A faster algorithm for vertex cover parameterized by solution size. In Olaf Beyersdorff, Mamadou Moustapha Kanté, Orna Kupferman, and Daniel Lokshtanov, editors, *41st International Symposium on Theoretical Aspects of Computer*

- Science, STACS 2024, March 12-14, 2024, Clermont-Ferrand, France*, volume 289 of *LIPICs*, pages 40:1–40:18. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2024. URL: <https://doi.org/10.4230/LIPICs.STACS.2024.40>, doi:10.4230/LIPICs.STACS.2024.40.
- 22 Yuchao Li, Wei Wang, and Zishen Yang. The connected vertex cover problem in k -regular graphs. *Journal of Combinatorial Optimization*, 38:635–645, 2019.
 - 23 Burkhard Monien and Ewald Speckenmeyer. Ramsey numbers and an approximation algorithm for the vertex cover problem. *Acta Informatica*, 22:115–123, 1985.
 - 24 Rolf Niedermeier and Peter Rossmanith. Upper bounds for vertex cover further improved. In *STACS 99: 16th Annual Symposium on Theoretical Aspects of Computer Science Trier, Germany, March 4–6, 1999 Proceedings 16*, pages 561–570. Springer, 1999.
 - 25 Rolf Niedermeier and Peter Rossmanith. On efficient fixed-parameter algorithms for weighted vertex cover. *Journal of Algorithms*, 47(2):63–77, 2003.
 - 26 Kaustav Paul and Arti Pandey. Eternal connected vertex cover problem in graphs: Complexity and algorithms. In *Conference on Algorithms and Discrete Applied Mathematics*, pages 179–193. Springer, 2024.
 - 27 Steven S. Skiena. *Set and String Problems*, pages 620–656. Springer London, London, 2008. doi:10.1007/978-1-84800-070-4_18.
 - 28 Ulrike Stege and Michael Ralph Fellows. An improved fixed parameter tractable algorithm for vertex cover. *Technical report/Departement Informatik, ETH Zürich*, 318, 1999.
 - 29 Vijay V Vazirani. *Approximation algorithms*, volume 1. Springer, 2001.
 - 30 David P Williamson and David B Shmoys. *The design of approximation algorithms*. Cambridge university press, 2011.
- 