Quantifying Misalignment Between Agents: Towards a Sociotechnical Understanding of Alignment

Aidan Kierans¹, Avijit Ghosh^{2,1}, Hananel Hazan³, Shiri Dori-Hacohen¹

¹University of Connecticut ²Hugging Face ³Tufts University aidan.kierans@uconn.edu, avijit.g@uconn.edu, hananel@hazan.org.il, shiridh@uconn.edu

Abstract

Existing work on the alignment problem has focused mainly on (1) qualitative descriptions of the alignment problem; (2) attempting to align AI actions with human interests by focusing on value specification and learning; and/or (3) focusing on a single agent or on humanity as a monolith. Recent sociotechnical approaches highlight the need to understand complex misalignment among multiple human and AI agents. We address this gap by adapting a computational social science model of human contention to the alignment problem. Our model quantifies misalignment in large, diverse agent groups with potentially conflicting goals across various problem areas. Misalignment scores in our framework depend on the observed agent population, the domain in question, and conflict between agents' weighted preferences. Through simulations, we demonstrate how our model captures intuitive aspects of misalignment across different scenarios. We then apply our model to two case studies, including an autonomous vehicle setting, showcasing its practical utility. Our approach offers enhanced explanatory power for complex sociotechnical environments and could inform the design of more aligned AI systems in real-world applications.

Code —

https://github.com/RIET-lab/quantifying-misalignment

1 Introduction

In recent years, growing concerns have emerged about the AI alignment problem (e.g. Russell 2019; Christian 2020). With respect to the current AI systems that exist today, Russell (Russell 2019) made the bold yet compelling claim that social media AI today is already misaligned with humanity (e.g. through extensive disinformation spread). As agentic AI systems are growing in importance and increasingly deployed (Kapoor et al. 2024), concerns about misalignment of agent-based systems have grown (Chan et al. 2023; Gabriel et al. 2024). Yet with few exceptions (e.g. Critch and Krueger 2020), much prior work focuses on single AI settings (Ji et al. 2024), on value specification and learning (Critch and Krueger 2020; Leike et al. 2018), or centers technosolutionist fixes. A healthier alternative would train a sociotechnical lens (Lazar and Nelson 2023) on multi-agent settings (Gabriel et al. 2024), which may include a complex mix of AI agents and humans, potentially holding a dizzying array of competing and often conflicting goals. Critch and Krueger posed

the question, "where could one draw the threshold between 'not very well aligned' and 'misaligned'[..]?" (2020, pg. 14), while Lazar and Nelson recently called for a "sociotechnical approach to AI safety," stating unequivocally that "no group of experts (especially not technologists alone) should unilaterally decide what risks count, what harms matter, and to which values safe AI should be aligned" (2023). In order to gain a deeper understanding of alignment of AI in its sociotechnical environment, we need to expand our definitions of alignment towards a sociotechnical, agent-based understanding of misalignment that accounts for the complexity of real-world systems in an increasingly AI-agentic world. The question emerges: with whom are agents aligned or misaligned, and on what areas? The alignment of an AI agent or system might be with an adversary, rather than with the developers and/or owners of it; and the alignment-or lack thereof-might be context-, user-, or agent-dependent.

To that end, we propose a novel probabilistic model of misalignment that is predicated on the population of agents being observed (whether human, AI, or any combination thereof), as well as the problem area at hand and, by extension, the agents' values and sense of importance regarding that area. To do so, we extend and adapt a model of contention from computational social science (Jang, Dori-Hacohen, and Allan 2017) and apply the adapted model to the alignment problem.

Our contributions in this paper are as follows:

- 1. We introduce a novel mathematical model of misalignment which accounts for a population of human and AI agents, and which is parameterized by problem areas, allowing any pair of agents to be simultaneously *both* aligned *and* misaligned. Our model affords explanatory power for the complexity of real-world, sociotechnical settings in which AI agents are deployed.
- We simulate a set of worlds with a variety of agents, problem areas, and goals in order to study key drivers of misalignment under our model.
- We showcase important features of our model in two case studies that are difficult to account for in previous models, namely, (a) a shopping recommender system and (b) a precrash autonomous vehicle (AV) decision-making setting.

The remainder of the paper is organized as follows: after sharing related work (\S 2), we define the model mathematically (\S 3). We then describe the setup of our simulation (§4) and discuss the results of different initial settings (§5). Next, we turn to our two case studies (§6), before sharing a discussion (§7) and concluding remarks (§8).

2 Related Work

The deployment of powerful agentic AI systems has led to increased concerns about misalignment (Chan et al. 2023; Gabriel et al. 2024). Several researchers argue that existing AI systems already exacerbate threats to information ecosystems and collective decision-making (Bucknall and Dori-Hacohen 2022; Russell 2019; Bak-Coleman et al. 2021; Seger et al. 2020). However, most prior work defines misalignment as a global characteristic of an AI system, often as a binary (Sierra et al. 2021). Recent work in machine ethics attempts to answer questions like "whom should AI align with?", while others measure alignment with respect to "human values" (Ji et al. 2024). However, while some researchers have noted alignment issues posed by value pluralism (Gabriel 2020), methods for measuring (mis)alignment between different cultures and AI agents remain underdeveloped.

In order to expand our understanding on misalignment to address this gap, our work draws significant inspiration from a computational model of contention in human populations proposed by Jang, Dori-Hacohen, and Allan (2017). Their model quantifies the proportion of people in disagreement on stances regarding a topic, parameterized by the observed group of individuals. We extend this approach in several key ways: (1) we adapt the model to capture misalignment with respect to goals, rather than stances on topics; (2) we extend the population to include both human and AI agents, allowing for analysis of mixed-agent scenarios; (3) we introduce the concept of "problem areas" to segment and analyze alignment across different domains of interaction; (4) our model allows for varying levels of goal conflict and importance weights, providing a more nuanced representation of alignment dynamics. While the contention paper focused on controversy in public discourse (Jang, Dori-Hacohen, and Allan 2017), our model provides a framework for quantifying misalignment in complex sociotechnical systems where humans and AI agents interact. This approach offers greater explanatory power for real-world scenarios and potential applications in AI alignment and safety research.

3 Modeling misalignment in populations

Our approach to modeling misalignment rests on a key observation: understanding and "solving" the AI alignment problem requires first grappling with the challenges of aligning humans. Human conflicts are ubiquitous, highlighting the difficulty of alignment even without AI agents. Building on the computational model for contention (Jang, Dori-Hacohen, and Allan 2017), we adapt the approach to capture misalignment with respect to goals. Our model allows for a hybrid population of human and AI agents, quantifying misalignment based on individuals' goals in problem areas.

Definitions and Notation. We define $\mathcal{A} = \{a_1..a_n\}$ as a set of *n* agents and $\mathcal{P} = \{p_1..p_m\}$ as a set of *m* problem areas of interest to at least one agent in \mathcal{A} . h(a, g, j) is a relationship denoting that agent *a* holds goal *g* in problem area j. g_j^i is the goal held by agent i in problem area j, and w_j^i is the weight, representing the importance that agent i assigns to problem area j.

We define $\hat{\mathcal{G}}_j = \{g_1, g_2, ..., g_k\}$ as the set of k non-zero goals with regards to problem area j in the set of agents \mathcal{A} . We use g_0 to denote that an agent holds no goal with respect to problem area j:

$$h(a, g_0, j) \iff \nexists g \in \hat{\mathcal{G}}_j \text{ s.t. } h(a, g, j).$$

Let $\mathcal{G}_j = \{g_0\} \cup \hat{\mathcal{G}}_j$ be the set of k + 1 extant goals with regard to j in \mathcal{A} .

Measuring Conflict. We introduce a measure, *c*, to denote the incompatibility of a pair of goals:

- $c(g_x, g_y) = 1$: Goals g_x and g_y are in complete conflict; they are mutually exclusive.
- $c(g_x, g_y) = 0$: Goals g_x and g_y are completely compatible and aligned.

By construction, $c(g_x, g_x) = 0$ and $c(g_x, g_0) = 0$.

Goal Groups. We define a goal group as a subset of agents that holds the same goal:

$$\mathcal{A}_g = \{a \in \mathcal{A} | h(a, g, j)\}$$

By construction, $\mathcal{A} = \bigcup_{g} \mathcal{A}_{g}$.

Quantifying Misalignment. Assuming agents regard each p with equal weight, we can quantify misalignment as the probability that two randomly selected agents will hold incompatible goals:

$$Pr(0|\mathcal{A}, p) := Pr(a_1, a_2 \text{ selected randomly from } \mathcal{A})$$
$$\cdot c(g_n^1, g_n^2)$$

The multiplication of the probability and conflict components calculates an expected conflict between two randomly selected agents' goals. By doing this for all possible pairs of agents, we obtain an overall measure of misalignment in the population for a given problem area. Note that the equation assumes that all agents are equally likely to be selected; and that the conflict function $c(\cdot, \cdot)$ allows for varying degrees of conflict between goals, rather than just binary conflict/no-conflict situations. Finally, the equation provides a single scalar value representing the overall misalignment in the population for a specific problem area. The benefit of this approach is that it affords a simple representation capturing the real-world phenomena of "strange bedfellows," where a pair agents may be highly aligned in one specific area despite being highly misaligned in others.

Mutually Exclusive Goals. To simplify our analysis, we can consider scenarios with mutually exclusive goals. This approach allows for a more straightforward quantification of misalignment. We introduce the following constraints:

- 1. Every agent holds only one goal in a problem area.
- 2. Each goal is in conflict with each other goal.
- 3. A lack of a goal (g_0) is not in conflict with any explicit goal.

Algorithm 1: Initialize World

Require: $m = |\mathcal{P}|, n = |\mathcal{A}|, K = [|\mathcal{G}_1|, ..., |\mathcal{G}_m|]$ Require: Randomize, Range, Preset 1: world. $\mathcal{P} \leftarrow [p_1, \ldots, p_m]$ 2: **for** j = 1 to *m* **do** world. p_j . $\mathcal{G} \leftarrow [g_1, \ldots, g_{K[j]}]$ 3: 4: for k = 1 to K[j] do for l = k + 1 to K[j] do 5: if Randomize.conflict = TRUE then 6: 7: world. $p_i.c(g_k,g_l) \leftarrow$ random(Range.conflict.min, .max) 8: else 9: world. $p_i.c(q_k,q_l) \leftarrow \text{Preset.conflict}[j][k][l]$ 10: end if end for 11: end for 12: 13: end for world \leftarrow ADD-AGENTS(world, Randomize, Range, 14: Preset, m, n) 15: return world

Under these constraints, we can compute $\Pr(0|\mathcal{A},p)$ as follows:

$$Pr(0|\mathcal{A}, p) = \frac{\sum_{g \in \mathcal{G}} \sum_{g' \in \mathcal{G}, g' < g} 2|\mathcal{A}_g||\mathcal{A}_{g'}|}{|\mathcal{A}|^2}$$

Where $|\mathcal{A}_g|$ is the number of agents holding goal g and $|\mathcal{A}|$ is the total number of agents. The alignment probability is then simply $Pr(1|\mathcal{A}, p) = 1 - Pr(0|\mathcal{A}, p)$.

This equation allows us to derive a parametric quantity for misalignment of uniformly distributed agents in the range $[0, \frac{|\hat{\mathcal{G}}|-1}{|\hat{\mathcal{G}}|}].$

Overall Misalignment Across Problem Areas. To determine the misalignment of \mathcal{A} across all problem areas, we take the arithmetic mean of $Pr(0|\mathcal{A}, p)$ across all p's for that \mathcal{A} . Some problem areas are more important to us than others, and this importance changes depending on the agent. To aggregate misalignment accordingly, let each agent have a weight parameter w for each problem area, such that 0 is the minimum amount an agent can care about a problem area, and 1 is the maximum amount. Then, multiply each problem area's misalignment by the geometric mean of the sampled agents' weights for that p. This gives us the following equation:

$$\begin{split} Pr(0|\mathcal{A},\mathcal{P}) &:= \\ \frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} \Big(Pr(a_1, a_2 \text{ selected randomly from } \mathcal{A}) \\ &\cdot c(g_p^1, g_p^2) \cdot \sqrt{w_p^1 \cdot w_p^2} \Big) \end{split}$$

Interpreting Misalignment Scores. The misalignment score provides insights into the degree of goal conflict within a set of agents:

• A score of 0 indicates perfect alignment (all agents share identical or fully compatible goals).

Algorithm 2: Create and add agents to world

Rec	uire: world, Randomize, Range, Preset, m, n
1:	for $i = 1$ to n do
2:	$a_i \leftarrow \{\}$
3:	for $j = 1$ to m do
4:	if Randomize.goals = TRUE then
5:	$a_i.g_j^i \leftarrow random(world.p_j.\mathcal{G})$
6:	else
7:	$a_i.g_i^i \leftarrow \text{Preset.goals[i][j]}$
8:	end if
9:	if Randomize.weights = TRUE then
10:	$a_i.w_i^i \leftarrow random(Range.weights.min, .max)$
11:	else
12:	$a_i.w_i^i \leftarrow \text{Preset.weights[i][j]}$
13:	end if [°]
14:	end for
15:	world. $\mathcal{A} \leftarrow $ world. $\mathcal{A} \cup \{a_i\}$
16:	end for
17:	return world

- A score approaching $\frac{|\hat{\mathcal{G}}|-1}{|\hat{\mathcal{G}}|}$ indicates high misalignment (goals are evenly distributed and in conflict).
- Intermediate scores suggest varying degrees of misalignment, which can be further analyzed by examining specific goal distributions and conflict levels.

This model provides a flexible framework for analyzing misalignment in complex scenarios involving multiple agents, problem areas, and goals. It can be applied to a wide range of situations, from social dynamics to AI alignment challenges.

4 Simulation & Experimental Setup

To gain a deeper understanding of how different variables in our model influence misalignment, especially in largerscale settings, we conducted a series of simulations. These empirical experiments complement our theoretical model and inform our later case studies.

We created abstract "worlds" with various configurations of problem areas, goals, agents, conflict scores, and importance weights. This approach allowed us to systematically explore the impact of changing one or more variables on overall misalignment scores.

Our simulation framework, outlined in Algorithms 1 and 2, initializes a world with specified parameters and populates it with agents. Each problem area has one or more goals (including a null goal with zero weight), and agents hold one goal per problem area. We treat an agent with zero weight in a problem area as equivalent to holding no goal in that area.

We conducted the following experiments, each focusing on different aspects of our model:

1. Varying Problem Areas: We randomly assigned nonzero goals to agents, plotting results for different numbers of problem areas, each with three goals. All agents held their goals with maximum weight, and all goal pairs had maximum conflict values (Figure 1).

- 2. Varying Goals: Similar to the first experiment, but we kept the number of problem areas constant and varied the number of goals (Figure 2).
- 3. Weight Sensitivity: We investigated the effect of changing weights for a single goal group. We simulated 1000 agents, varying the weight of Goal 1 in Problem Area 1 for agents holding that goal, while keeping all other goals at maximum weight. We plotted this for 1 to 4 problem areas with 2 or 4 goals each (Figure 3).
- 4. **Goal Distribution**: We plotted 1000 agents distributed deterministically among 2 or more goals, varying the proportion of agents assigned to goal 1 and distributing the remaining agents evenly to the remaining goals. All conflicts and weights were kept constant at 1 (Figure 4).
- Conflict Levels: We varied the number of goals in each problem area and plotted the results using different numbers of problem areas and conflict levels, while randomly assigning each agent's weights for their goals (Figure 5).

For overall population misalignment across multiple problem areas, we used the arithmetic mean of area-specific misalignment scores. We allowed agents' weights across problem areas to sum to more than 1, as normalizing weights led to unintuitive results where misalignment scores depended more on the number of problem areas than on the agents' relative prioritization of each area. In these experiments, we excluded null goals in order to make the effects more clear.

5 Results

We present key findings from the five experiments that explore different aspects of misalignment dynamics.

Effect of Population Size and Problem Areas Figure 1 illustrates how misalignment evolves as we increase the number of agents, with varying numbers of problem areas. The results reveal a consistent pattern across different numbers of problem areas. Initially, there is high variance in misalignment due to the random distribution of goals among a small number of agents. However, as the population size increases, the misalignment converges to a stable value. Notably, this convergence point is independent of the number of problem areas, because the overall misalignment is calculated as the arithmetic mean across all areas and each problem area has the same population misalignment. This finding demonstrates that our model captures the intuitive notion that larger populations tend to stabilize in their overall misalignment, even when individual problem areas may have different early dynamics. It suggests that in complex multi-agent systems, the aggregate level of misalignment becomes more predictable as the number of agents grows.

Impact of Goal Count Figure 2 shows how the number of goals in each problem area affects misalignment. The experiment reveals a clear relationship between the number of goals and the level of misalignment. As the number of goals per problem area increases, so does the overall misalignment. For a problem area with with $\hat{\mathcal{G}}$ non-zero goals, the misalignment approaches $(\hat{\mathcal{G}} - 1)/\hat{\mathcal{G}}$ as the number of agents grows. This pattern aligns with the intuitive understanding that a greater



Figure 1: Varying Problem Areas. Random goal assignment, 3 goals per problem area, 100 runs per data point, max weight and conflict values. Null goals disallowed.



Figure 2: Varying Goals. Random goal assignment, 4 problem areas, 100 runs per data point, max weight and conflict values. Null goals disallowed.

number of mutually exclusive goals leads to higher potential for misalignment within a population. The result highlights our model's ability to capture the complexity of multi-goal scenarios, reflecting the increased potential for conflict as the number of distinct goals grows. It suggests that in real-world situations, systems with a higher number of competing objectives are likely to exhibit greater levels of misalignment, emphasizing the importance of goal prioritization and conflict resolution in multi-agent environments.

Weight Sensitivity Figure 3 examines the effect of changing weights for a single goal group in one problem area, while keeping other weights at maximum. When the weight of one goal group is reduced to zero in a single problem area, it effectively eliminates misalignment for that specific area. This demonstrates the model's ability to capture scenarios where certain objectives become irrelevant or unimportant to a subset of agents. As more problem areas are added to the simulation, the impact of weight changes in a single area diminishes, reflecting the model's capability to balance multiple concerns. Interestingly, when the number of goals per problem area is increased to four, the misalignment starts at a higher level and approaches 0.75, consistent with the $(\hat{\mathcal{G}} - 1)/\hat{\mathcal{G}}$ pattern observed in the previous experiment. These findings show-



Figure 3: Weight Sensitivity. 100 agents, 100 runs per data point, maximum conflict, random goal assignment. Null goals disallowed.



Figure 4: Goal Distribution. 1000 agents, 1 problem area, max conflict and weight. Null goals disallowed.

case our model's sensitivity to goal weights and its ability to capture nuanced interactions between problem areas. They suggest that in complex systems, the relative importance assigned to different goals can significantly influence overall alignment, and that this effect is modulated by the number and nature of the problem areas under consideration.

Goal Distribution Effects Figure 4 shows how misalignment changes as we vary the proportion of agents assigned to different goals. The experiment reveals dynamics of misalignment in populations with varying goal allocations. Notably, misalignment reaches its peak when goals are evenly distributed among agents. Specifically, for a problem area with $\hat{\mathcal{G}}$ non-zero goals, the maximum misalignment occurs when the proportion of agents assigned to any single goal is $1/\hat{\mathcal{G}}$. As the population becomes more homogeneous in its goals that is, as a larger proportion of agents adopt the same goal the overall misalignment decreases. This pattern holds true regardless of the total number of goals, though the peak misalignment value increases with the number of available goals. The results suggest (in line with our intuitions) that in realworld scenarios, populations with a diverse and balanced set of objectives may experience higher levels of misalignment compared to those with a more dominant goal or consensus.

Conflict Levels and Problem Area Interactions Figure 5 explores the effects of varying conflict levels across different



Figure 5: **Conflict Levels.** 120 agents, 100 runs, random weight range (0.25, 0.75). Null goals disallowed.

numbers of problem areas and goals. Each problem area is assigned a single conflict value for all of its goal pairs.

The analysis of conflict levels and problem area interactions reveals complex dynamics in our misalignment model. As expected, misalignment increases with both the number of goals and the level of conflict between goals. However, the effect of multiple problem areas is more nuanced, depending on the average conflict across those areas rather than their individual values. Notably, scenarios with the same average conflict level converge to similar misalignment values, regardless of how that average is achieved across different problem areas. This finding suggests that our model can effectively capture the aggregate effect of conflicts across multiple domains, providing a holistic view of misalignment in complex environments. More broadly, these results demonstrate our model's capability to handle intricate scenarios with varying conflict levels across multiple problem areas, offering a sophisticated tool for analyzing misalignment in multi-faceted, real-world situations where conflicts may be unevenly distributed across different domains of interaction.

Thus, our simulation experiments validate key properties of our misalignment model, demonstrating its ability to capture intuitive aspects of multi-agent alignment while revealing non-obvious dynamics in complex scenarios. With these findings as a solid foundation, we now move on to applying our model to realistic case studies.

6 Case Studies

To demonstrate the robustness and applicability of our misalignment model, we present two distinct case studies: a shopping recommender system and an autonomous vehicle pre-collision scenario.

Shopping Recommender System Consider an AI-based recommender system employed by a hybrid "big-box" retailer with both online and brick-and-mortar presence. This system mediates between the retailer and its customers, potentially leading to varying degrees of alignment or misalignment depending on the specific shopping context.

Figure 6 illustrates two scenarios:

1. **Grocery Shopping:** A customer uses the retailer's mobile app to quickly order groceries for curbside pickup. The



Figure 6: Shopping Recommender System scenarios. Top: Aligned grocery shopping. Bottom: Misaligned impulse purchasing.

Goal	Description	Weight (w)
$g_{p_f}^c$	Convenience at low price	$w_{p_f}^c = 0.8$
$g_{p_h}^c$	Avoid impulse buying	$w_{p_h}^c = 0.6$
$g_{p_f}^R$	Increase net profits	$w_{p_f}^R = 0.9$
$g_{p_h}^R$	Move inventory	$w_{p_h}^R = 0.7$
$g_{p_f}^{R^S}$	Maximize checkout value	$w_{p_f}^{R^S} = 1.0$
$g_{p_h}^{R^S}$	Maximize checkout value	$w_{p_h}^{R^S} = 1.0$

Table 1: Shopping scenario goals and weights

recommender system suggests familiar items and meal combinations, saving time and providing convenience. This scenario demonstrates alignment between customer, retailer, and recommender system goals.

2. **Impulse Purchasing:** Late at night, the same customer is led by the recommender system to purchase unnecessary clearance holiday items. This results in guilt, wasted money and time, and refunded items, demonstrating misalignment between all parties' interests.

Let's map this scenario to our model:

- Agents: $A = \{c, R, R^S\}$, where c is the customer, R is the retailer, and R^S is the recommender system.¹
- Problem Areas: $\mathcal{P} = \{p_f, p_h\}$, where p_f is food and grocery shopping and p_h is household item shopping.

We can now calculate the misalignment for each problem area using our model:

$$Pr(0|\mathcal{A}, p) = \frac{1}{|\mathcal{A}|^2} \sum_{a_1, a_2 \in \mathcal{A}} c(g_{a_1}, g_{a_2}) \cdot \sqrt{w_{a_1} \cdot w_{a_2}}$$

And the overall misalignment:

$$Pr(0|\mathcal{A}, \mathcal{P}) = \frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} Pr(0|\mathcal{A}, p)$$

This results in the following scores: $Pr(0|\mathcal{A}, p_f) = 0.09$, $Pr(0|\mathcal{A}, p_h) = 0.42$, $Pr(0|\mathcal{A}, \mathcal{P}) = 0.26$. This lines up

Food: H			Iousehold:					
	g^{c}	g^R	g^{R^S}			g^c	g^R	g^{R^S}
g^c	0	0.1	0.1	-	g^c	0	0.5	0.9
g^R		0	0.1		g^R		0	0.3
g^{R^S}			0		g^{R^S}			0

Table 2: Lower triangular matrices representing goal conflicts in two problem areas. Left: Conflict matrix for problem area p_f (Food). Right: Conflict matrix for problem area p_h (Household). The entries represent the conflict values between goals g^c , g^R , and g^{R^S} , with diagonal entries set to 0, indicating no conflict with themselves.

with our intuition that all three agents are much more aligned w/r/t the grocery area than the household area. Overall, this case study demonstrates how our model can capture the nuanced misalignment in e-commerce scenarios, where goals may align in one context (grocery shopping) but conflict in another (impulse shopping), and where recommender system incentives may lead to subtle reward hacking.

Autonomous Vehicle Pre-collision Scenario We analyze scenario 17 from the CARLA (Car Learning to Act) challenge: "Obstacle avoidance without prior action." (Dosovit-skiy et al. 2017) This scenario involves an autonomous vehicle encountering an unexpected pedestrian and needing to perform an emergency maneuver.



Figure 7: CARLA scenario 17 - Autonomous vehicle encountering a pedestrian (Dosovitskiy et al. 2017).

Figure 7 illustrates the scenario where the autonomous vehicle must make rapid decisions to avoid a collision while considering various factors such as passenger safety, pedestrian safety, and traffic rules. In this case:

- Agents: $\mathcal{A} = \{a_v, a_h\}$, where a_v is the autonomous vehicle and a_h is the human pedestrian.
- Problem Areas: $\mathcal{P} = \{p_1, ..., p_8\}$, corresponding to penalized categories of traffic events in the CARLA challenge.

Goals for both agents in all problem areas are to avoid the described event (e.g., collision, traffic violation). Weights for a_v are derived from CARLA penalty coefficients for each event, and estimated for a_h :

While both agents seemingly hold the same goals (avoiding each event), we assume that pedestrian and AV goals may conflict in *how* they wish to avoid incident, and simulate this as some level of conflict between g_p^v and g_p^h for each p.

To obtain population misalignment scores, we simulate a world with 1000 agents that are pedestrians or autonomous

¹Though we only use one instance of each agent here, it is easy to add agents to any category and recalculate misalignment accordingly.

Goal	Description	Weights		
$g_{p1}^{v h}$	No pedestrian collision	$w_{p1}^v = 0.50$	$w_{p1}^h = 0.99$	
$g_{p2}^{v h}$	No vehicle collision	$w_{p2}^v = 0.40$	$w_{p2}^h = 0.15$	
$g_{p3}^{v h}$	No static object collision	$w_{p3}^v = 0.35$	$w_{p3}^h = 0.15$	
$g_{p4}^{v h}$	No red light violation	$w_{p4}^v = 0.30$	$w_{p4}^h = 0.05$	
$g_{p5}^{v h}$	No stop sign violation	$w_{p5}^v = 0.20$	$w_{p5}^h = 0.05$	
$g_{p6}^{v h}$	No route blockage	$w_{p6}^v = 0.30$	$w_{p6}^h = 0.05$	
$g_{p7}^{v h}$	Keep appropriate speed	$w_{p7}^v = 0.30$	$w_{p7}^h = 0.01$	
$g_{p8}^{v h}$	No yield violation	$w_{p8}^v = 0.30$	$w_{p8}^h = 0.05$	

Table 3: Autonomous vehicle case. "v|h" means each goal is held by both vehicle and human (pedestrian), though their weights vary.



Figure 8: CARLA scenario, 1000 agents, assuming goals conflict.

vehicles (see Figure 8). As in the goal distribution experiment from Figure 4, a population with opposing goals has the highest misalignment when those goals are most evenly distributed. We note that even when pedestrian and car goals are as conflicted as possible, the high number of problem areas and low weights of most of the problem areas in the autonomous vehicle case study result in low misalignment at almost all times. To confirm that this is indeed an effect of the low weights, we also show what the curves would look like if the weights were all set to 1.

7 Discussion

Our approach enables modeling misalignment in diverse contexts, from international relations to family disagreements. It captures a variety of real-world phenomena, such as the "strange bedfellows" effect and reward hacking, and allows for misalignment that varies across different populations and problem areas, providing a comprehensive framework for understanding alignment dynamics in diverse contexts. By addressing the fundamental challenge of defining alignment in a world where humans—and not just AI agents—are frequently misaligned, our model affords the analysis of complex scenarios ranging from localized disputes to global conflicts.

Implications for AI Risk. In the context of AI risk analysis, our work contributes to the understanding of existential

risks posed by misaligned AI (Avin et al. 2018; Baum et al. 2019; Ord 2020; Bucknall and Dori-Hacohen 2022). By reframing misalignment as primarily a human-centered problem, we align with recent research on AI's impact on human decision-making and societal structures (Russell 2019; Bak-Coleman et al. 2021; Seger et al. 2020). Our model provides a tool for analyzing potential AI-powered conflicts and their broader implications (Boulanin et al. 2019; Johnson 2019; Lin 2019; Maas, Matteuci, and Cooke 2022), highlighting the complexity of aligning AI with human values.

Limitations. Our model does not address whether an agent's actions have positive or negative outcomes for the agent itself. The question of how an agent's goals could be learned remains open, although progress has been made by others in this space (Brown et al. 2021). Due to space constraints, we also do not address how to apply our model to an agent or agents with internally-conflicting goals.

8 Conclusion

We introduce a novel misalignment model which advances the understanding of AI alignment by focusing on multi-agent settings and diverse problem areas. Building on a computational social science model of contention in human populations (Jang, Dori-Hacohen, and Allan 2017), we introduce a framework that captures the nuanced, multi-faceted nature of alignment in complex sociotechnical systems. Our simulations demonstrate that our model's misalignment scores accurately reflect changes in key variables, providing a robust tool for analyzing multi-agent alignment scenarios. This approach offers a more nuanced and realistic understanding of misalignment than simple binary classifications or global numeric values, better reflecting the complexities of real-world interactions between humans and AI systems.

Broader Impacts. Our approach encourages AI safety and alignment researchers to avoid reductionist traps, such as attempting to align AI narrowly with individuals or humanity as a whole, or adopting an overly techno-solutionist mindset. We hope to spark more conversation about the sociotechnical aspects of the alignment problem and the need for interdisciplinary collaboration in addressing these challenges.

Future Work. Future research could extend our model to entities beyond humans and AI, including social constructs like nation-states and corporations (alluded to in the retail case study), as well as biological entities from cellular interactions to ecosystems. This expansion could provide insights into alignment dynamics in diverse complex systems.

Challenges remain in precisely defining problem areas, particularly when they involve combinations or gestalts of sub-areas, have mutual dependencies, or when selecting relevant states from potentially infinite possibilities. Addressing these challenges to produce more rigorous definitions of problem areas is an important direction for future work.

Finally, applying our model to existing multi-agent simulations, such as those in MeltingPot (Leibo et al. 2021), DeepMind's Concordia (Vezhnevets et al. 2023), or other population simulations (Piatti et al. 2024; Foxabbott et al. 2023) could yield valuable insights into the dynamics of misalignment in complex multi-agent systems.

References

Avin, S.; Wintle, B. C.; Weitzdörfer, J.; Ó hÉigeartaigh, S. S.; Sutherland, W. J.; and Rees, M. J. 2018. Classifying global catastrophic risks. *Futures*, 102: 20–26.

Bak-Coleman, J. B.; Alfano, M.; Barfuss, W.; Bergstrom, C. T.; Centeno, M. A.; Couzin, I. D.; Donges, J. F.; Galesic, M.; Gersick, A. S.; Jacquet, J.; Kao, A. B.; Moran, R. E.; Romanczuk, P.; Rubenstein, D. I.; Tombak, K. J.; Van Bavel, J. J.; and Weber, E. U. 2021. Stewardship of global collective behavior. *Proceedings of the National Academy of Sciences*, 118(27).

Baum, S. D.; Armstrong, S.; Ekenstedt, T.; Häggström, O.; Hanson, R.; Kuhlemann, K.; Maas, M. M.; Miller, J. D.; Salmela, M.; Sandberg, A.; Sotala, K.; Torres, P.; Turchin, A.; and Yampolskiy, R. V. 2019. Long-term trajectories of human civilization. *Foresight*, 21(1): 53–83.

Boulanin, V.; Avin, S.; Sauer, F.; Borrie, J.; Scheftelowitsch, D.; Bronk, J.; Stoutland, P. O.; Hagström, M.; Topychkanov, P.; Horowitz, M. C.; Kaspersen, A.; King, C.; Amadae, S.; and Rickli, J.-M. 2019. The Impact of Artificial Intelligence on Strategic Stability and Nuclear Risk, Volume I, Euro-Atlantic Perspectives. Technical report, SIPRI.

Brown, D. S.; Schneider, J.; Dragan, A.; and Niekum, S. 2021. Value Alignment Verification. In Meila, M.; and Zhang, T., eds., *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, 1105–1115. PMLR.

Bucknall, B. S.; and Dori-Hacohen, S. 2022. Current and Near-Term AI as a Potential Existential Risk Factor. In *Proceedings of the 2022 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '22, 119–129. New York, NY, USA: Association for Computing Machinery. ISBN 9781450392471.

Chan, A.; Salganik, R.; Markelius, A.; Pang, C.; Rajkumar, N.; Krasheninnikov, D.; Langosco, L.; He, Z.; Duan, Y.; Carroll, M.; et al. 2023. Harms from increasingly agentic algorithmic systems. In *Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency*, 651–666.

Christian, B. 2020. *The Alignment Problem: Machine Learning and Human Values*. WW Norton & Company.

Critch, A.; and Krueger, D. 2020. AI Research Considerations for Human Existential Safety (ARCHES). *CoRR*, abs/2006.04948.

Dosovitskiy, A.; Ros, G.; Codevilla, F.; Lopez, A.; and Koltun, V. 2017. CARLA: An open urban driving simulator. In *Conference on robot learning*, 1–16. PMLR.

Foxabbott, J.; Deverett, S.; Senft, K.; Dower, S.; and Hammond, L. 2023. Defining and Mitigating Collusion in Multi-Agent Systems. In *Multi-Agent Security Workshop* @ *NeurIPS'23*.

Gabriel, I. 2020. Artificial Intelligence, Values, and Alignment. *Minds and Machines*, 30(3): 411–437.

Gabriel, I.; Manzini, A.; Keeling, G.; Hendricks, L. A.; Rieser, V.; Iqbal, H.; Tomašev, N.; Ktena, I.; Kenton, Z.; Rodriguez, M.; El-Sayed, S.; Brown, S.; Akbulut, C.; Trask, A.; Hughes, E.; Bergman, A. S.; Shelby, R.; Marchal, N.; Griffin, C.; Mateos-Garcia, J.; Weidinger, L.; Street, W.; Lange, B.; Ingerman, A.; Lentz, A.; Enger, R.; Barakat, A.; Krakovna, V.; Siy, J. O.; Kurth-Nelson, Z.; McCroskery, A.; Bolina, V.; Law, H.; Shanahan, M.; Alberts, L.; Balle, B.; de Haas, S.; Ibitoye, Y.; Dafoe, A.; Goldberg, B.; Krier, S.; Reese, A.; Witherspoon, S.; Hawkins, W.; Rauh, M.; Wallace, D.; Franklin, M.; Goldstein, J. A.; Lehman, J.; Klenk, M.; Vallor, S.; Biles, C.; Morris, M. R.; King, H.; y Arcas, B. A.; Isaac, W.; and Manyika, J. 2024. The Ethics of Advanced AI Assistants. arXiv:2404.16244.

Jang, M.; Dori-Hacohen, S.; and Allan, J. 2017. Modeling controversy within populations. In *Proceedings of the ACM SIGIR International Conference on Theory of Information Retrieval*, 141–149.

Ji, J.; Qiu, T.; Chen, B.; Zhang, B.; Lou, H.; Wang, K.; Duan, Y.; He, Z.; Zhou, J.; Zhang, Z.; Zeng, F.; Ng, K. Y.; Dai, J.; Pan, X.; O'Gara, A.; Lei, Y.; Xu, H.; Tse, B.; Fu, J.; McAleer, S.; Yang, Y.; Wang, Y.; Zhu, S.-C.; Guo, Y.; and Gao, W. 2024. AI Alignment: A Comprehensive Survey. arXiv:2310.19852. Johnson, J. 2019. Artificial intelligence & future warfare: implications for international security. *Defense & Security Analysis*, 35(2): 147–169.

Kapoor, S.; Stroebl, B.; Siegel, Z. S.; Nadgir, N.; and Narayanan, A. 2024. AI agents that matter. *arXiv preprint arXiv:2407.01502*.

Lazar, S.; and Nelson, A. 2023. AI safety on whose terms? Leibo, J. Z.; Dueñez-Guzman, E. A.; Vezhnevets, A.; Agapiou, J. P.; Sunehag, P.; Koster, R.; Matyas, J.; Beattie, C.; Mordatch, I.; and Graepel, T. 2021. Scalable Evaluation of Multi-Agent Reinforcement Learning with Melting Pot. In Meila, M.; and Zhang, T., eds., *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, 6187–6199. PMLR.

Leike, J.; Krueger, D.; Everitt, T.; Martic, M.; Maini, V.; and Legg, S. 2018. Scalable agent alignment via reward modeling: a research direction. ArXiv:1811.07871 [cs, stat]. Lin, H. 2019. The existential threat from cyber-enabled information warfare. *Bulletin of the Atomic Scientists*, 75(4): 187–196.

Maas, M. M.; Matteuci, K.; and Cooke, D. 2022. Military Artificial Intelligence as Contributor to Global Catastrophic Risk. In *Cambridge Conference on Catastrophic Risks 2020*. Draft available at https://papers.ssrn.com/sol3/papers.cfm? abstract_id=4115010.

Ord, T. 2020. *The Precipice: Existential Risk and the Future of Humanity*. Hachette Books. ISBN 978-0316484916.

Piatti, G.; Jin, Z.; Kleiman-Weiner, M.; Schölkopf, B.; Sachan, M.; and Mihalcea, R. 2024. Cooperate or Collapse: Emergence of Sustainable Cooperation in a Society of LLM Agents. arXiv:2404.16698.

Russell, S. 2019. *Human Compatible: Artificial Intelligence and the Problem of Control.* Penguin.

Seger, E.; Avin, S.; Pearson, G.; Briers, M.; Ó hÉigeartaigh, S.; and Bacon, H. 2020. Tackling threats to informed decisionmaking in democratic societies: Promoting epistemic security in a technologicall-advanced world. Technical report, The Alan Turing Institute, Defence and Security Programme. Sierra, C.; Osman, N.; Noriega, P.; Sabater-Mir, J.; and Perelló, A. 2021. Value alignment: a formal approach. ArXiv:2110.09240, arXiv:2110.09240.

Vezhnevets, A. S.; Agapiou, J. P.; Aharon, A.; Ziv, R.; Matyas, J.; Duéñez-Guzmán, E. A.; Cunningham, W. A.; Osindero, S.; Karmon, D.; and Leibo, J. Z. 2023. Generative agent-based modeling with actions grounded in physical, social, or digital space using Concordia. *arXiv preprint arXiv:2312.03664*.

A AI Risk Analysis

As mentioned in §7, our work contributes to the AI existential risk literature. A 2022 paper presented potential pathways from current and near-term AI to increased x-risk, which does not presuppose AGI (Bucknall and Dori-Hacohen 2022); instead, the authors propose that power struggles such as AIpowered international and state-corporate conflicts may play a large role in increased x-risk (and/or other catastrophic tail risks) due to other, non-AGI risk sources such as nuclear war, runaway climate change, and so forth. Crucially, several papers have argued that current AI is already misaligned with humanity (e.g., Bucknall and Dori-Hacohen 2022; Russell 2019) and also that humanity's collective sense-making and decision-making capacities are already being compromised and diminished by present-day AI, such as the recommender systems at the core of social media platforms (e.g., Bak-Coleman et al. 2021; Bucknall and Dori-Hacohen 2022; Seger et al. 2020).

By recasting misalignment as first and foremost a humancentered problem, rather than an AI-centric problem, and drawing on existing literature that studies human conflict and contention, our paper ties directly into this line of research that suggests that AI may serve to increase, accelerate and intensify the risks of human conflict—already a thorny and arguably intractable problem even before AI's advent (Boulanin et al. 2019; Johnson 2019; Lin 2019; Maas, Matteuci, and Cooke 2022). Furthermore, by providing a flexible framework that can be used to account for, analyze and quantify misalignment among a vast array of agents, both human and artificial, our work holds significant promise to advance our field's understanding of the alignment problem.

Finally, our model encourages AI safety and alignment researchers to avoid the potentially reductionist traps of (a) "narrowly" aligning AI with either individual humans or humanity as a whole by highlighting the challenges in aligning any diverse group of individuals, whether that group includes AI agents or not; and (b) adopting a techno-optimistic and/or techno-positivist mindset that naively supposes that the alignment problem can be solved by technological means alone. We sincerely hope that our paper sparks more conversation in the AI safety and alignment communities about the sociotechnical aspects of the alignment problem, and the need to include a diverse group of researchers and practitioners with expertise in diverse domains far beyond computer science and philosophy departments; and by extension, contributes to improving humanity's odds of finding realistic and sustainable approaches to reducing x-risk.

B Entropy

Our maximum-weight, maximum-conflict formulation of misalignment bears an interesting resemblance to entropy in information theory.

For a problem area with $\hat{\mathcal{G}}$ non-zero goals which are mutually exclusive and uniformly distributed, our misalignment measure approaches:

$$\lim_{\mathcal{A}|\to\infty} Pr(0|\mathcal{A},p) = \frac{\hat{\mathcal{G}}-1}{\hat{\mathcal{G}}}$$

This can be rewritten in a form that resembles measures of diversity or impurity:

$$Pr(0|\mathcal{A},p) \approx 1 - \sum_{i=1}^{\hat{\mathcal{G}}} p_i^2$$

where p_i is the proportion of agents holding goal *i*.

Interestingly, this formula is equivalent to the Gini impurity, and is the inverse of the Simpson diversity index in ecology. While not directly equivalent to Shannon entropy, it shares some conceptual similarities:

1. Both our misalignment measure and entropy reach their maximum values when the distribution is uniform (i.e., when all goals are equally represented). 2. Both provide a measure of "disorder" or diversity in a system.

However, there are important distinctions:

1. Shannon entropy is calculated as $-\sum p_i \log p_i$, which differs from our quadratic form. 2. Our measure has a fixed upper bound of $(\hat{\mathcal{G}} - 1)/\hat{\mathcal{G}}$, while Shannon entropy's upper bound increases with $\hat{\mathcal{G}}$. 3. Our model incorporates additional features like g_0 (the null goal), pairwise goal conflicts, and importance weights, which are not present in standard entropy calculations.

This connection suggests that groups holding incompatible goals can be viewed as carriers of information, with higher misalignment indicating greater "disorder" or uncertainty in the system. Entropy or "heat" (in both the metaphoric and literal, thermodynamic senses of the word) would be maximal when misaligned agent groups are each $\frac{|\mathcal{A}_g|}{|\mathcal{A}|}$ and identical in size.

C Assumptions and Restrictions

In the paper as a whole:

- 1. Agents can be either human or AI.
- 2. The "no goal" option (g_0) is not in conflict with any explicit goal.
- 3. Conflict between goals is symmetric; $c(g_x, g_y) = c(g_y, g_x).$
- 4. Conflict values range from 0 (completely compatible) to 1 (completely incompatible).
- 5. Each agent assigns a weight to each problem area, representing its importance.
- 6. Importance "weights" are non-negative and can sum to more than 1 across problem areas.

- 7. The model assumes a static snapshot of agents' goals and doesn't account for dynamic changes over time. However, time-series misalignment data can be created by analyzing misalignment repeatedly over time.
- 8. The model doesn't address potential synergies or positive interactions between different goals.
- 9. The model assumes that all agents within a population are equally likely to be selected for comparison.
- 10. The model doesn't consider hierarchical relationships or power dynamics between agents.

Extra restrictions in the "Mutually Exclusive Goals" paragraph:

- 1. Each agent has a single goal for each problem area.
- 2. Goals within a problem area are mutually exclusive.
- 3. The "no goal" option (q_0) is not in conflict with any explicit goal.

D Theorems and Proofs/Derivations

D.1 Misalignment Probability

Theorem 1: The probability of misalignment between two randomly selected agents a_1 and a_2 in a problem area p is given by:

$$Pr(0|\mathcal{A}, p) := Pr(a_1, a_2 \text{ selected randomly from } \mathcal{A})$$

 $\cdot c(g_n^1, g_n^2)$

where $c(g_p^1,g_p^2)$ is the conflict between the goals of a_1 and a_2 in problem area p.

Derivation: The probability of misalignment is the product of two factors:

- 1. The probability of selecting two agents randomly from the population A. Assuming uniform random selection with replacement, this probability is $\frac{1}{|\mathcal{A}|^2}$.
- 2. The degree of conflict between the goals of these two agents, given by $c(g_p^1, g_p^2)$.

Multiplying these factors gives the probability that two randomly selected agents will have conflicting goals in problem area p.

D.2 Misalignment with Mutually Exclusive Goals

Theorem 2: For a problem area with mutually exclusive goals, the misalignment probability is:

$$Pr(0|\mathcal{A}, p) = \frac{\sum_{g \in \mathcal{G}} \sum_{g' \in \mathcal{G}, g' < g} 2|\mathcal{A}_g||\mathcal{A}_{g'}|}{|\mathcal{A}|^2} \qquad (1)$$

where \mathcal{A}_q is the set of agents holding goal q.

Derivation: For mutually exclusive goals, we consider all pairs of distinct goals:

- 1. The double summation $\sum_{g \in \mathcal{G}} \sum_{g' \in \mathcal{G}, g' < g}$ iterates over all unique pairs of goals.
- 2. For each pair, $|\mathcal{A}_{q}| |\mathcal{A}_{q'}|$ is the number of agent pairs with these goals.
- 3. We multiply by 2 to account for order (agent 1 having goal g and agent 2 having goal g', and vice versa).

4. Dividing by $|\mathcal{A}|^2$ normalizes by the total number of possible agent pairs.

This gives the probability of selecting two agents with different goals, which equals the misalignment probability for mutually exclusive goals.

D.3 Misalignment Upper Bound

Theorem 3: The maximum misalignment for a uniformly distributed population with $|\hat{\mathcal{G}}|$ non-zero goals is:

Max Misalignment =
$$\frac{|\hat{\mathcal{G}}| - 1}{|\hat{\mathcal{G}}|}$$
 (2)

Proof: In a uniformly distributed population:

- 1. Each goal is held by $\frac{|\mathcal{A}|}{|\hat{\mathcal{G}}|}$ agents.
- 2. The probability of selecting two agents with different goals is $\frac{|\hat{\mathcal{G}}|-1}{|\hat{\mathcal{G}}|}$.
- 3. This probability is maximized when goals are mutually exclusive and maximally conflicting.

Therefore, $\frac{|\hat{\mathcal{G}}|-1}{|\hat{\mathcal{G}}|}$ represents the upper bound of misalignment.

D.4 Overall Misalignment Across Problem Areas

Theorem 4: The overall misalignment across all problem areas \mathcal{P} is:

$$\begin{aligned} Pr(0|\mathcal{A}, \mathcal{P}) &:= \frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} \left(Pr(a_1, a_2 \\ \text{selected randomly from } \mathcal{A}) \cdot c(g_p^1, g_p^2) \cdot \sqrt{w_p^1 \cdot w_p^2} \right) \end{aligned}$$

where w_p^i is the weight agent *i* assigns to problem area *p*. **Derivation** We derive this formula by extending the misalignment calculation for a single problem area to multiple areas, incorporating weights to reflect the importance of each area to the agents involved.

1. For each problem area p, we start with the basic misalignment probability from Theorem 1:

$$Pr(0|\mathcal{A}, p) := Pr(a_1, a_2 \text{ selected randomly from } \mathcal{A})$$
$$\cdot c(g_n^1, g_n^2)$$

2. We incorporate the importance of the problem area to both agents using their weights. We use the geometric mean of the weights:

$$\sqrt{w_p^1\cdot w_p^2}$$

Justification for geometric mean:

- It captures the "middle ground" between two agents' weightings.
- It reduces the impact on misalignment when one agent cares little about an area and another cares a lot.
- It's less sensitive to extreme values than the arithmetic mean.
- The square root keeps the result on the same scale as the original weights.

3. We multiply the basic misalignment probability by this geometric mean of weights:

$$Pr(0|\mathcal{A},p)\cdot\sqrt{w_p^1\cdot w_p^2}$$

4. To get the overall misalignment, we sum this weighted misalignment over all problem areas:

$$\sum_{p \in \mathcal{P}} \left(Pr(0|\mathcal{A}, p) \cdot \sqrt{w_p^1 \cdot w_p^2} \right)$$

5. Finally, we take the arithmetic mean across all problem areas by dividing by $|\mathcal{P}|$:

$$\frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} \left(Pr(0|\mathcal{A}, p) \cdot \sqrt{w_p^1 \cdot w_p^2} \right)$$

Justification for arithmetic mean:

- It gives equal importance to each problem area in the overall score, before taking the agents' importance weights into account.
- It allows for intuitive interpretation: equal increases and decreases in different areas cancel out.
- It's consistent with the idea that misalignment in each area contributes additively to overall misalignment.

Note that weights are allowed to sum to more than 1 across problem areas for each agent. This allows agents to care deeply about multiple areas without forcing trade-offs, reflecting real-world scenarios where agents can care strongly about many issues simultaneously.

D.5 Misalignment Convergence

Theorem 5: As the number of agents *n* approaches infinity, the misalignment score converges to a stable value independent of the number of problem areas, given that all problem areas have the same number of goals and conflict structure.

Proof: Let \mathcal{G} be the number of goals in each problem area, and c(i, j) be the conflict between goals *i* and *j*.

- 1. As $n \to \infty$, by the law of large numbers, the proportion of agents with goal i in any problem area converges to $\frac{1}{G}$ for all *i*.
- 2. The misalignment score for a single problem area is:

$$M = \sum_{i=1}^{\mathcal{G}} \sum_{j=1}^{\mathcal{G}} \left(\frac{1}{\mathcal{G}} \cdot \frac{1}{\mathcal{G}} \cdot c(i,j) \right)$$

3. This can be simplified to:

$$M = \frac{1}{\mathcal{G}^2} \sum_{i=1}^{\mathcal{G}} \sum_{j=1}^{\mathcal{G}} c(i,j)$$

- 4. Since the conflict structure is the same for all problem areas, this value M is identical for each problem area.
- 5. The overall misalignment across problem areas (Theorem 4) is the average of individual problem area misalignments:

Overall
$$M = \frac{1}{|\mathcal{P}|} \sum_{p=1}^{|\mathcal{P}|} M = M$$

where $|\mathcal{P}|$ is the number of problem areas.

6. Therefore, as $n \to \infty$, the overall misalignment converges to M, which is independent of the number of problem areas.

D.6 Goal Count and Misalignment Relationship

Theorem 6: For a problem area with $\hat{\mathcal{G}}$ non-zero goals, as the number of agents n approaches infinity, the misalignment score approaches:

$$\lim_{n \to \infty} \text{Misalignment} = \frac{\hat{\mathcal{G}} - 1}{\hat{\mathcal{G}}}$$
(3)

Proof: This follows directly from Theorem 3:

- 1. As $n \to \infty$, the distribution of agents across goals approaches uniformity.
- 2. In this limit, the probability of selecting two agents with different goals is $\frac{\hat{\mathcal{G}}-1}{\hat{\mathcal{G}}}$.
- 3. For mutually exclusive and maximally conflicting goals, this probability equals the misalignment score.

Maximum Misalignment with Uniform D.7 Distribution

Theorem 7: For a problem area with $\hat{\mathcal{G}}$ non-zero goals, the maximum misalignment occurs when the proportion of agents assigned to any single goal is $1/\hat{\mathcal{G}}$.

Proof: Let p_i be the proportion of agents with goal *i*. The misalignment is:

$$M = 1 - \sum_{i=1}^{\hat{\mathcal{G}}} p_i^2$$
 (4)

subject to the constraint $\sum_{i=1}^{\hat{\mathcal{G}}} p_i = 1$. Using the method of Lagrange multipliers:

- 1. Form the Lagrangian: $L = 1 \sum_{i=1}^{\hat{\mathcal{G}}} p_i^2 \lambda(\sum_{i=1}^{\hat{\mathcal{G}}} p_i 1)$ 2. Set partial derivatives to zero: $\frac{\partial L}{\partial p_i} = -2p_i \lambda = 0$ for all i
- 3. This implies all p_i are equal. Given the constraint, $p_i =$ $1/\mathcal{G}$ for all *i*.

Therefore, the uniform distribution maximizes misalignment.

E Hardware and Software

All experiments were run on the following hardware:

- 1. OS: Windows 10
- 2. CPU: AMD Ryzen 9 5900HX with Radeon Graphics 3.30 GHz
- 3. CPU Cores: 8
- 4. CPU Threads: 16
- 5. RAM: 15.40 GB
- 6. GPU: NVIDIA GeForce RTX 3080 Laptop GPU

These are the software versions used for the experiments:

- 1. Python Version: 3.12.4
- 2. NumPy Version: 2.0.1
- 3. Matplotlib Version: 3.9.1