Bootstrapping Referring Multi-Object Tracking

Yani Zhang¹ Dongming Wu² Wencheng Han³ Xingping Dong^{1†}

¹ School of Computer Science, Wuhan University, ² Beijing Institute of Technology, ³ SKL-IOTSC, CIS, University of Macau zebrazyn@whu.edu.cn, xingping.dong@gmail.com

Abstract

Referring multi-object tracking (RMOT) aims at detecting and tracking multiple objects following human instruction represented by a natural language expression. Existing RMOT benchmarks are usually formulated through manual annotations, integrated with static regulations. This approach results in a dearth of notable diversity and a constrained scope of implementation. In this work, our key idea is to bootstrap the task of referring multi-object tracking by introducing discriminative language words as much as possible. In specific, we first develop Refer-KITTI into a large-scale dataset, named Refer-KITTI-V2. It starts with 2,719 manual annotations, addressing the issue of class imbalance and introducing more keywords to make it closer to real-world scenarios compared to Refer-KITTI. They are further expanded to a total of 9,758 annotations by prompting large language models, which create 617 different words, surpassing previous RMOT benchmarks. In addition, the end-to-end framework in RMOT is also bootstrapped by a simple yet elegant temporal advancement strategy, which achieves better performance than previous approaches. The source code and dataset is available at https: //github.com/zyn213/TempRMOT.

1 Introduction

Given a language expression, the goal of referring multi-object tracking is to utilize it as a semantic cue for detecting and tracking multiple objects within a video sequence. Despite being an emerging task, it has gained widespread attention due to its potential advantages in various applications such as video editing [1], human-computer interaction [2], and autonomous driving [3]. While it shares a historical connection with multi-object tracking [4], its distinctiveness lies in the introduction and utilization of natural language expressions. To accommodate practical applications, this innovative task requires the ability to handle a broad range of languages to the fullest extent possible.

Existing datasets, such as [2; 5; 6; 7], are typically created through manual annotations combined with static regulations. This process requires significant human effort and often results in limited natural language expressions with uniform syntactic structures. According to the statistical data in Table 1, we find that current RMOT datasets have a semantic homogeneity. For instance, the Refer-Dance [5] contains 1,985 expressions but only 48 unique ones, indicating a high level of repetition. Similar issues are found in Refer-KITTI [2]. Furthermore, these repetitive and simplistic expressions indicate a limited vocabulary, which is far away from a satisfactory application. These problems motivate us to highlight the significance of rich semantic information for RMOT.

To introduce as much semantic information as possible with minimal manpower, we design a threestep semi-automatic labeling pipeline to efficiently generate labels for the new dataset. First, language items are identified and linked to bounding boxes using an annotation system that supports automatic propagation. In this work, we use the term "language item" to refer to a basic attribute of objects.

[†]Corresponding author.

Table 1: **Comparison of current RMOT datasets.** GroOT* represents the MOT17 subset with tracklet captions, which is similar to our RMOT task. Expressions refer to the total number of expressions in each video, while distinct expressions refer to the total number of unique expressions in the entire dataset. Referent ratio is the proportion of referent objects to the total number of objects.

Datasets	Videos	Expressions	Expressions per Video	Distinct Expressions	Words	Referent ratio
Refer-KITTI [2][CVPR'23]	18	895	49.7	215	49	0.965
GroOT* [6][NeurIPS '23]	14	1547	23.8	1161	260	-
Refer-Dance [5] [CVPR'24]	65	1985	30.5	48	25	0.939
Refer-KITTI-V2(Ours)	21	9758	464.6	7193	617	0.988

Examples of language items include class (e.g. car and people), color (e.g. white and blue) and action (e.g. moving and walking). Second, we systematically combine these items following specific rules to generate initial language prompts. Finally, we generate more language prompts based on manual annotations using a large language model (LLM). More details will be discussed in § 3.1. In this way, we propose a new and large-scale dataset, Refer-KITTI-V2, consisting of 21 videos with a total of 9,758 expressions, which is almost 5× larger than other datasets. Our dataset includes 7,193 distinct expressions and 617 different words, highlighting the diversity of semantic information.

Thanks to its diverse semantics, there are several key contributions make Refer-KITTI-V2 a unique and valuable asset to the community. (*i*) **Complex motion states**. Recent approaches [8; 9] and datasets [10; 3] have emphasized the importance of understanding multi-modal motion information for referring expressions. Our dataset includes basic motion states such as "walking" and "moving", as well as more complex states like "speedier", "decelerating" and "brake", as shown in Fig. 1. (*ii*) **Linguistic flexibility**. We use a wide range of words and expressions to describe the same concept, offering multiple variations like "moving cars in the same direction of the ego car" and "autos moving in the same direction as ours". This variety enhances the richness and flexibility of our descriptions. (*iii*) **Multi-perspective descriptions**. Different from the MOT17 [4] subset in GroOT [6] that separate appearance and action into distinct expressions, our semantic expressions integrate multiple aspects, ensuring a holistic and detailed understanding of the objects. As depicted in Fig. 1, Refer-KITTI-V2 incorporates comprehensive details, e.g. color, position, and motion. Other subsets in GroOT are either not open-source or do not align with our specific tasks.

In addition, existing end-to-end methods focus only on single-frame modeling [2], failing to handle temporal-wise challenges, such as object occlusion and motion recognition. To bootstrap RMOT method, we propose a temporally enhanced end-to-end framework, named TempRMOT. Specifically, we introduce a query-based temporal enhancement modul based on the popular DETR-like framework, which associates multiple video frames using query features to create a robust long-temporal representation. Our mode achieves state-of-the-art performance across multiple datasets, demonstrating significant enhancements for both HOTA and AssA.

In summary, our main contributions are three-fold: **First**, we propose a three-step semi-automatic labeling pipeline and introduce a new language-guided multi-object tracking dataset, Refer-KITTI-V2. This dataset features diverse and multifaceted textual descriptions covering appearance, complex motion, position, *etc.* **Second**, we develop a query-based temporal enhanced framework, named TempRMOT. It models long-term spatial-temporal interaction in terms of Transformer [11] query features. **Third**, our approach outperforms existing state-of-the-art method by a remarkable margin, e.g., +3.16% HOTA on Refer-KITTI and +4.04% HOTA on Refer-KITTI-V2 [2]. Experimental results confirm the effectiveness of our model on RMOT task.

2 Related works

Referring Multi-Object Tracking Benchmark. To address the limitation of the previous referring understanding tasks only recognizing a single referent object within a video using a natural language expression, Wu *et.al.* [2] are the first to propose referring multi-object tracking (RMOT). The core idea of RMOT is employing a language expression as a semantic cue to track the corresponding objects. Here, the referent object number is flexible, including multiple objects, one object and none. Wu *et.al.* [2] construct the first benchmark Refer-KITTI, which is developed from the common



Figure 1: **Representative examples of Refer-KITTI-V2.** Its language expressions are generated by manual annotation and further extended by LLMs. And it possess the advantages of complex motion states, linguistic flexibility and multi-perspective descriptions, showing strong semantic diversity.

multi-object tracking dataset KITTI [12] with annotating descriptions. iKUN [5] further proposes Refer-Dance, which extends DanceTrack [13] with text annotations. Type-to-Track [6] introduces another large-scale RMOT benchmark GroOT based on multi-object tracking datasets that includes MOT17 [4], TAO [14], and MOT20 [15]. Despite impressive development, current RMOT benchmarks are typically created via manual labeling. Their formulation is coupled with static regulations, thereby leading to a scarcity of significant variety and a limited range of applicability.

Referring Multi-Object Tracking Method. Along with the first RMOT benchmark, the baseline model TransRMOT [2] is simultaneously introduced. It is built upon the end-to-end multi-object tracking method MOTR [16], which modifies MOTR to adapt the cross-modal input. Different from TransRMOT, the latter approache, iKUN [5], typically follow a two-stage paradigm. It first explicitly extract object tracklets, and then select object tracklets matched with the language expression. While the two-stage methods allow for more thorough refinement and filtering of potential candidates, their architectures are commonly complicated and have more computational requirements, which are far away from being satisfied. Therefore, in this work, we focus more on designing a powerful end-to-end method for RMOT task.

Query-based Temporal Modeling. Employing query vectors and proposals as a means to augment long-temporal modeling within Transformer-based architectures has become a prevalent approach for addressing video understanding tasks [17; 18; 19; 20; 21; 22]. This is because Transformer-based model uses a set of queries to represent objects, where each query refers to a low-dimensional vector that contains object information. Utilizing these semantically rich and low-dimensional vectors to model temporal relationship is efficient and effective. For example, MeMOT [17] proposes a memory module to store and read query embedding of past frames to enhance the detection and tracking of the current frame. Distinct from previous works, this research primarily focuses on exploring the influence of query-based temporal modeling on language-conditioned video understanding.

3 Dataset Overview

3.1 Data Collection and Annotation

As shown in Fig. 2, we design a three-step semi-automatic labeling pipeline to efficiently generate training labels for the new dataset. Several representative examples are shown in Fig. 1, which showcase significant diversity. For more examples of the datasets please see the Appendix A.

Step 1: Language Item Collection. We categorize the content of each prompt into different basic attributes, referred to as "language items" in this paper. These items include class (*e.g.* car and people), color (*e.g.* white and blue), position (*e.g.* left, right, and in front of), and action (*e.g.* moving, walking, and turning). During this step, we annotate the corresponding language items for each video. The KITTI dataset provides instance-level bounding box annotations, where the same instance retains the same ID across frames. Following Refer-KITTI [2], we click on the target object when it appears and disappears, and provide language items matched. The annotation system automatically populates the labels between the starting and ending frames, saving the label information (i.e. frame ID, object ID, and box coordinates) along with the corresponding expressions.



Figure 2: **Language Prompt Annotation Pipeline** consists of three steps: language element collection, prompt generation, and prompt expansion. Firstly, we use an efficient labeling tool to associate instances in each video with language elements at low human cost. Then, we manually create 2719 accurate language descriptions. Finally, leveraging the powerful language understanding capabilities of large language models, we expand the new annotations with language descriptions.

Step 2: Prompt Generation. After obtaining the language items for each video, we apply predefined rules to generate initial prompts. These rules include formats like "{*class*}-in-{*color*, *position*, *direction*}" and "{*class*}-which-are-{*action*}". For example, as shown in Fig. 2, we select the language item sets "turning" and "black", along with the matching rule "The-{*color*}-{*motion*}-cars". By combining these items with their corresponding bounding boxes in the video using the AND operation, we obtain a new set, resulting in the prompt "The black turning cars". In our dataset, we manually select meaningful attribute combinations and filter out combinations with an insufficient number of bounding boxes in the video sequence to ensure their effectiveness. This process ensures prompt accuracy and provides a reliable foundation for subsequent prompt expansion.

Step 3: Prompt Expansion. After step 2, we generated 2,719 prompts. To further enhance linguistic diversity, we employ a large language model (LLM) to create a wider range of semantic expressions. For each expression generated in the second step and those in the Refer-KITTI dataset, we require GPT-3.5 [23] to generate four alternative representations that preserve the original meaning. To ensure the accuracy and consistency of these new expressions, we also implement a two-step validation process. First, we task GPT-3.5 with verifying that each new expression retained the same meaning as the original. Following this, we assign each video to three independent annotators who further review and filter the results. These annotators evaluate whether the newly generated expressions accurately reflect the original video's context and meaning. With the help of the large language model, we significantly enrich our database and ultimately obtained 9,758 semantic expressions.

3.2 Dataset Statistics

In Table 1, we compare our dataset with the existing open-source RMOT dataset, where GroOT* represents the MOT17 subset with tracklet captions, similar to our RMOT task. The results indicate that our dataset has the highest number of natural expressions, the greatest variety of distinct expressions and words, highlighting the diversity of our semantic information. Next, we discuss how the proposed dataset, Refer-KITTI-V2, intentionally increases the complexity of language-conditioned video understanding by addressing the challenges of both linguistic and visual modalities.



Figure 3: Distribution of proportion of referenced objects.

Video Content. Our Refer-KITTI-V2 is built on one of the most popular datasets for multi-object tracking, KITTI [12]. The training set for KITTI provides 21 high-resolution and long temporal videos. Unlike Refer-KITTI, which abandon three over-complex videos and only use the remaining 18 videos to annotate, we use the all 21 videos to formulate a more challenge datasets, with the maximum count reaching up to 1,059 frames. These deliberate design choices enhance the complexity and difficulty of Refer-KITTI-V2, posing greater challenges for language-conditioned video understanding tasks.

Referent Objects. In Fig. 3, we present distribution of proportion of referenced objects, which indicates the varying frequency of how many objects each expression refers to in the video. Our dataset stands out as our expressions cover a wide range of object counts. This contrasts with existing datasets such as Refer-Dance [5], where 94.86% of expressions are null, and GroOT [6], where expressions on average refer to a small proportion of objects. Additionally, we have intentionally included expressions unrelated to the video content to increase the dataset's difficulty, a feature absent in Refer-KITTI. This highlights the superior coverage and complexity of our ex-



Figure 4: Word cloud of Refer-KITTI-V2.

pressions. Expressions in Refe-KITTI-V2 primarily describe between 1 to 25 instances, with the maximum count reaching up to 105 objects. On average, each expression in the video contains approximately 6.69 objects. As depicted in Table 1, we possess the highest referent ratio, indicating that our expressions encompass the majority of objects in the dataset. By fully utilizing the annotated objects, we have increased the complexity of the task.

Language Expression. We also show the word cloud of Refer-KITTI-V2 in Fig. 4. From the word cloud figure, we can observe that Refer-KITTI-V2 includes numerous words such as "driving" and "moving", which describe motion information, as well as "left" and "red", which describe the appearance and position of objects.

4 Method

The overall architecture of our method bootstrapped for RMOT is illustrated in Fig. 5. It builds on Transformer-based RMOT model [2] and is further improved by a simple yet effective temporal enhancement module. In this section, we first revisit this Transformer-based model in § 4.1 and then introduce the temporal enhancement module in § 4.2.

4.1 Transformer-Based Referring Multi-Object Tracking Model

This model represents objects as queries, which will be fed into a decoder to probe desired features from cross-modal features and update themselves. Similar to MOTR [16], it categorize queries into two types: those used for representing new targets in the current frame and those representing instance objects from the previous frame. At each timestamp, the Transformer-based RMOT first accepts a video frame, a language expression, and a set of learnable queries as input. Its output comprises target bounding boxes, categories, and a set of embeddings corresponding to the expression.

Formally, let F_t denote the extracted visual features at timestamp t, and S denote the encoded linguistic features. The two vanilla features are then mapped into the same dimension and fed into a *fusion encoder* (ξ) to perform cross-modal fusion using a cross attention module, which helps align features of different modalities. In this paper, we represent the cross-modal feature as M_t :

$$\boldsymbol{M}_t \leftarrow \boldsymbol{\xi}(\boldsymbol{Q} = \boldsymbol{F}_t, \boldsymbol{K} = \boldsymbol{S}, \boldsymbol{V} = \boldsymbol{S}). \tag{1}$$

As mentioned above, the Transformer-based RMOT use the queries Q_t to represents objects. After building relations within Q_t using *Object Encoder* (\mathcal{E}), it adopt an attention-based detection architecture, named *Object Decoder* (\mathcal{D}) to decode the cross-modal features M_t :

$$\boldsymbol{B}_{t}^{D}, \boldsymbol{Q}_{t}^{D} \leftarrow \mathcal{D}(\boldsymbol{M}_{t}, \boldsymbol{\mathcal{E}}(\boldsymbol{Q}_{t})),$$
(2)



Figure 5: **Overall architecture of our TempRMOT.** It consists of two main components: Transformer-based RMOT and temporal enhancement module. The Transformer-based RMOT accepts a video frame, a language expression, and a set of learnable queries as input. Its output comprises a set of embeddings corresponding to the objects. The temporal enhancement module harnesses a memory mechanism to integrate temporal information for query enhancement. Our loss includes detection loss $\mathcal{L}^{\mathcal{P}}$, based image-level detection and spatio-temporal loss $\mathcal{L}^{\mathcal{R}}$ based on temporal modeling.

where B_t^D and Q_t^D are the detected bounding boxes and updated query features, respectively. B_t^D and Q_t^D are respectively fed into the temporal enhancement module to provide the foundational box coordinates and the hidden state for current bounding box predictions.

4.2 Temporal Enhancement Module

The Transformer-based RMOT model uses aggregated cross-modal features and a set of learnable query to generate detected bounding boxes. In this section, we expand on this by incorporating temporal modeling, achieved by harnessing a memory mechanism to aggregate historical information across multiple frames. The specific design is illustrated in Fig. 6.

Query Memory. As shown in Fig. 5, we propose an $N \times K$ query memory to store the query sets from the previous moments, where N represents the number of stored frames, and K is the number of objects stored per frame. This memory operates on a first-in, first-out (FIFO) principle. As new frame information is added, the oldest data in the queue is discarded. The $N \times K$ query memory serves as a dynamic repository that adapts continuously as new data flows in, thereby "remembering" information across time steps. The FIFO mechanism ensures that the system's memory consumption remains constant, even as new information is continuously integrated, making it highly suitable for environments with limited computational resources.

Temporal Decoder. As illustrated in Fig. 6, the Temporal Decoder is composed of 4 layers.



Figure 6: The details of the temporal enhancement module. Mainly contains two parts: temporal decoder and object decoder.

Each layer consists of three main components: self-attention, cross-attention, and a feedforward neural network. The query from the Transformer-based RMOT is first updated through self attention and then utilized as the key (K), while the stored set of queries in the memory mechanism acts both as the query (Q) and value (V). We convert the timestamps into positional embedding to further refine our model's processing capabilities. This arrangement allows for the implementation of an attention mechanism to apply focus across time axes. The queries stored in memory represent historical data, providing a rich contextual background that significantly enhances the model's understanding of temporal dynamics. By integrating this historical context with current data through an attention

Table 2: **Comparison with state-of-the-art methods** on Refer-KITTI. "E" means "End to End". "[†]" represents results after frame correction. The best results are in bold.

Method	E	HOTA	DetA	AssA	DetRe	DetPr	AssRe	AssPr	LocA
FairMOT [†] [24]	X	22.78	14.43	39.11	16.44	45.48	43.05	71.65	74.77
DeepSORT [25]	X	25.59	19.76	34.31	26.38	36.93	39.55	61.05	71.34
ByteTrack [†] [26]	X	24.95	15.50	43.11	18.25	43.48	48.64	70.72	73.90
CStrack [27]	X	27.91	20.65	39.10	33.76	32.61	43.12	71.82	79.51
TransTrack [28]	X	32.77	23.31	45.71	32.33	42.23	49.99	78.74	79.48
TrackFormer [29]	X	33.26	25.44	45.87	35.21	42.10	50.26	78.92	79.63
iKUN [5]	×	48.84	35.74	66.80	51.97	52.25	72.95	87.09	-
EchoTrack [30]	 ✓ 	39.47	31.19	51.56	42.65	48.86	56.68	81.21	79.93
DeepRMOT [31]	1	39.55	30.12	53.23	41.91	47.47	58.47	82.16	80.49
TransRMOT [†] [2]	1	46.56	37.97	57.33	49.69	60.10	60.02	89.67	90.33
MLS-Track [7]	\checkmark	49.05	40.03	60.25	59.07	54.18	65.12	88.12	-
TempRMOT(Ours)	1	52.21	40.95	66.75	55.65	59.25	71.82	87.76	90.40

mechanism, the temporal decoder is able to more effectively recognize patterns and relationships in object changes over time, achieving effective alignment with semantic information.

Object Decoder. The Object Decoder shares a similar network structure with the Temporal Decoder, with the main difference being in the positional embedding. It is designed to foster a distinct and discriminative feature representation from a spatial perspective. The query set updated by the Temporal Decoder is further refined in the Object Decoder with positional embedding. The sequential Temporal Decoder and Object Decoder lead to Q_t^R :

$$\boldsymbol{Q}_{t}^{R} = \mathbf{ObjectDecoder}\left(\mathbf{TemporalDecoder}(\boldsymbol{Q}_{t}^{D})\right).$$
 (3)

Track Refinement. We then refine the object bounding boxes using a query set enriched with temporal information. Specifically, a multi-layer perceptron (MLP) is employed to predict coordinate residuals, leading to B_t^R :

$$\boldsymbol{B}_{t}^{R} = \boldsymbol{B}_{t}^{D} + \mathbf{MLP}(\boldsymbol{Q}_{t}^{R}).$$

$$\tag{4}$$

4.3 Loss Functions

Our loss is divided into two parts, detection loss $\mathcal{L}^{\mathcal{D}}$ and spatio-temporal loss $\mathcal{L}^{\mathcal{R}}$:

$$\mathcal{L}^{\mathcal{D}} = \lambda_{cls}^{D} \mathcal{L}_{cls}^{D} + \lambda_{box}^{D} \mathcal{L}_{box}^{D} + \lambda_{cls}^{D} \mathcal{L}_{cls}^{D},$$
(5)

where λ_{cls}^D are focal loss for classification, λ_{box}^D are L1 loss and the generalized IoU loss for bounding box regression and λ_{cls}^D are focal loss for referring. \mathcal{L}_{cls}^D , \mathcal{L}_{box}^D and \mathcal{L}_{cls}^D are generated by \mathbf{Q}^D . The spatio-temporal loss $\mathcal{L}^{\mathcal{R}}$ are calculated using the following formula:

$$\mathcal{L}^{\mathcal{R}} = \lambda_{cls}^{R} \mathcal{L}_{cls}^{R} + \lambda_{box}^{R} \mathcal{L}_{box}^{R} + \lambda_{cls}^{R} \mathcal{L}_{cls}^{R}, \tag{6}$$

where λ_{cls}^R are focal loss for classification, λ_{box}^R are L1 loss and the generalized IoU loss for bounding box regression and λ_{cls}^R are focal loss for referring. \mathcal{L}_{cls}^R , \mathcal{L}_{box}^R and \mathcal{L}_{cls}^R are generated by Q^R . Therefore, the final loss is:

$$\mathcal{L} = \mathcal{L}^{\mathcal{D}} + \mathcal{L}^{\mathcal{R}}.$$
(7)

5 Experiments

5.1 Experimental Setup

Dataset. For comprehensive evaluation, we conducted experiments on three datasets: Refer-KITTI, Refer-KITTI-V2 and KITTI. For detailed descriptions of the datasets please see the Appendix B.

Evaluation Metric. We follow the standard evaluation protocols to evaluate our method. The main metric we used is "Higher Order Tracking Accuracy" (HOTA) [32]. Additionally, we analysis the contribution decomposed into detection accuracy (DetA) and association accuracy(AssA).

Method	E	HOTA	DetA	AssA	DetRe	DetPr	AssRe	AssPr	LocA
Refer-KITTI-V2									
FairMOT [24]	X	22.53	15.80	32.82	20.60	37.03	36.21	71.94	78.28
ByteTrack [26]	X	24.59	16.78	36.63	22.60	36.18	41.00	69.63	78.00
iKUN [5]	×	10.32	2.17	49.77	2.36	19.75	58.48	68.64	74.56
TransRMOT [2]	 ✓ 	31.00	19.40	49.68	36.41	28.97	54.59	82.29	89.82
TempRMOT(Ours)	1	35.04	22.97	53.58	34.23	40.41	59.50	81.29	90.07
KITTI									
TransRMOT [2] TempRMOT(Ours)	1	61.52 63.47	57.16 56.09	66.51 72.04	64.19 61.56	81.23 83.68	69.80 76.07	91.60 89.67	90.88 91.19

Table 3: **Comparison with state-of-the-art methods** on Refer-KITTI-V2 and KITTI. "E" means "End to End". The best results are in bold.

Table 4: Ablation studies of different frame lengths in temporal memory.

Length	HOTA	DetA	AssA		Length	HOTA	DetA	AssA	
3	33.64	21.96	51.66		5	34.72	22.59	53.49	
4	34.41	22.43	52.90		6	34.78	22.73	53.32	
5	34.72	22.59	53.49		8	35.04	22.97	53.58	
(a) Different lengths for training.					(b) Different lengths for inference.				

Implementation Details. We take ResNet50 [33] and RoBERTa [34] as our encoder in default. For Refer-KITTI and Refer-KITTI-V2, memory lengths are 4 and 5, respectively. Using Adam with a learning rate of 1e-5, reduced 10x from the 40th epoch, we train for 60 epochs on 4 RTX 4090 GPUs. Please see the Appendix C for more details.

5.2 State-of-the-art Comparison

Refer-KITTI. As shown in Table 2, we compare our method with existing approaches on Refer-KITTI. In the original benchmark, we noted that there was a discrepancy between predicted frames and actual frames when obtaining ground truth. We addressed this issue by correcting results provided by [2], which includes FairMOT [24], ByteTrack [26], and TransRMOT [2]. The corrected results are denoted by FairMOT[†], ByteTrac[†] and TransRMOT[†], respectively. TempRMOT sets a new stateof-the-art record with a HOTA score of 55.21, surpassing the previous best, MLS-Track[7], by 3.16% and requiring only an additional 0.006 seconds per frame for the temporal enhancement module.

Refer-KITTI-V2. In Table 3, we report results on Refer-KITTI-V2. We developed a series of CNNbased competitors by integrating our cross-modal fusion module into the detection component of multi-object tracking models like FairMOT [24] and ByteTrack [26] for more fair comparison. These competitors adopt a tracking-by-detection approach, employing independent trackers to associate each reference box. On this novel dataset, TempRMOT also achieves the state-of-the-art performance, surpassing the closest competitor TransRMOT [2] by margins of 4.04%, 3.57%, and 3.9% on HOTA, DetA, and AssA, respectively. The results show the generalization and scalability of TempRMOT.

KITTI. We further evaluate these methods on KITTI dataset in Table 3, using the same data split protocol as in Refer-KITTI-V2 for simplicity. Compared to TransRMOT [2], our approach achieves the best performance on the HOTA metric, with a substantial improvement of 5.53% on the AssA metric (72.04% vs 66.51%), highlighting the effectiveness of our temporal enhanced framework.

5.3 Ablation Study

Module Effectiveness. To investigate the effect of each component in our model, we conduct ablation studies on Refer-KITTI-V2. As shown in Table 5, the Temporal Decoder emerges as the most critical design element. Integrating Temporal Decoder results in a 3.32% HOTA performance boost compared to the vanilla baseline, which is adopted from TransRMOT [2] with our reproduction. Solely introducing the Object Decoder prompts the smallest, but it is helpful as well. Moreover, sequentially incorporating object decoder and track refinement on top of Temporal Decoder gradually enhances the



Figure 7: Visualization of predictions from TransRMOT and our TempRMOT. TempRMOT not only successfully detects and tracks objects but also accurately understands complex instructions related to motion without wrong identification. Best view in color.

overall performance. The best overall performance is achieved when all three components (Temporal Decoder, Object Decoder, and Track Refinement) are used together.

Number of Temporal Memory. The TempRMOT relies on memory mechanism to store historical information from the first N moments. We initially investigate the impact of memory length during the training phase on the model, as shown in Table 4a. Here, the length of memory is set consistent between the inference and training phases. The results indicate that as the length increases, all metrics also increase. Subsequently, we fix the memory length to 5 during the training phase and sequentially increase it during the inference phase, with results presented in Table 4b. Similarly, the results demonstrate that with more aggregated historical information, the model performs better, emphasizing the importance of temporal modeling in RMOT.

5.4 Qualitative Results

We visualize several typical results in Fig. 7. As seen, TempRMOT can accurately tracking objects and understand complex instructions related to motion. For example, when handling instructions "cars in front of ours", TransRMOT loses track of objects, which are not present in TempRMOT. Additionally, our model is capable of distinguishing objects belonging to the same class but with different mo-

Table 5: Ablation study of our method on Refer-KITTI-v2

Temporal	Object	Track Re-	HOTA	DetA	AssA
Decoder	Decode	finement			
X	X	X	31.00	19.40	49.68
1	X	X	34.32	22.36	52.79
X	1	X	31.79	19.88	50.96
1	1	X	34.46	22.73	52.37
1	✓	✓	35.04	22.97	53.58

tion states. For example, as shown in Fig. 7, TransRMOT misclassifies standing pedestrians as walking, while TempRMOT accurately detects and tracks walking pedestrians. More comparisons can be seen in the Appendix D.

6 Conclusion

In this work, we presented Refer-KITTI-V2, a significantly expanded and diverse dataset for RMOT, with 9,758 expressions and 617 unique words. Our dataset addressed the limitations of previous benchmarks by introducing complex motion states, linguistic flexibility, and multi-angle descriptions. Additionally, we also introduced TempRMOT, a simple yet effective framework for query-based temporal modeling on language-conditioned video understanding. Extensive experiments showed that our TempRMOT remarkably outperforms existing state-of-the-art methods.

Limitations. The TempRMOT framework has shown remarkable performance in multi-modal understanding. Nonetheless, it still faces limitations, particularly in accurately detecting small objects. We believe that devising explicit designs to address these issues will be a promising future direction.

Real World Impact. The Refer-KITTI-V2 dataset and TempRMOT model are expected to significantly advance the RMOT task and benefit industries such as video editing. However, it is important to note that research involving Refer-KITTI-V2 and TempRMOT should be conducted with caution to prevent potential misuse that could infringe on personal privacy.

References

- Bahjat Kawar, Shiran Zada, Oran Lang, Omer Tov, Huiwen Chang, Tali Dekel, Inbar Mosseri, and Michal Irani. Imagic: Text-based real image editing with diffusion models. In CVPR, 2023.
- [2] Dongming Wu, Wencheng Han, Tiancai Wang, Xingping Dong, Xiangyu Zhang, and Jianbing Shen. Referring multi-object tracking. In CVPR, 2023. 1, 2, 3, 5, 7, 8, 12, 14
- [3] Dongming Wu, Wencheng Han, Tiancai Wang, Yingfei Liu, Xiangyu Zhang, and Jianbing Shen. Language prompt for autonomous driving. *arXiv preprint*, 2023. 1, 2
- [4] Anton Milan, Laura Leal-Taixé, Ian Reid, Stefan Roth, and Konrad Schindler. Mot16: A benchmark for multi-object tracking. arXiv preprint arXiv:1603.00831, 2016. 1, 2, 3
- [5] Yunhao Du, Cheng Lei, Zhicheng Zhao, and Fei Su. ikun: Speak to trackers without retraining. In CVPR, 2024. 1, 2, 3, 5, 7, 8
- [6] Pha Nguyen, Kha Gia Quach, Kris Kitani, and Khoa Luu. Type-to-track: Retrieve any object via promptbased tracking. In *NeurIPS*, 2024. 1, 2, 3, 5
- [7] Zeliang Ma, Song Yang, Zhe Cui, Zhicheng Zhao, Fei Su, Delong Liu, and Jingyu Wang. Mls-track: Multilevel semantic interaction in rmot. arXiv preprint arXiv:2404.12031, 2024. 1, 7, 8
- [8] Shuting He and Henghui Ding. Decoupling static and hierarchical motion perception for referring video segmentation. In *CVPR*, 2024. 2
- [9] Linfeng Yuan, Miaojing Shi, and Zijie Yue. Losh: Long-short text joint prediction network for referring video object segmentation. In CVPR, 2024. 2
- [10] Henghui Ding, Chang Liu, Shuting He, Xudong Jiang, and Chen Change Loy. Mevis: A large-scale benchmark for video segmentation with motion expressions. In *ICCV*, 2023. 2
- [11] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NeurIPS*, 2017. 2
- [12] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *CVPR*, 2012. **3**, **5**, **14**
- [13] Peize Sun, Jinkun Cao, Yi Jiang, Zehuan Yuan, Song Bai, Kris Kitani, and Ping Luo. Dancetrack: Multi-object tracking in uniform appearance and diverse motion. In CVPR, 2022. 3
- [14] Achal Dave, Tarasha Khurana, Pavel Tokmakov, Cordelia Schmid, and Deva Ramanan. Tao: A large-scale benchmark for tracking any object. In ECCV, 2020. 3
- [15] Patrick Dendorfer, Hamid Rezatofighi, Anton Milan, Javen Shi, Daniel Cremers, Ian Reid, Stefan Roth, Konrad Schindler, and Laura Leal-Taixé. Mot20: A benchmark for multi object tracking in crowded scenes. arXiv preprint arXiv:2003.09003, 2020. 3
- [16] Fangao Zeng, Bin Dong, Yuang Zhang, Tiancai Wang, Xiangyu Zhang, and Yichen Wei. Motr: End-to-end multiple-object tracking with transformer. In ECCV, 2022. 3, 5
- [17] Jiarui Cai, Mingze Xu, Wei Li, Yuanjun Xiong, Wei Xia, Zhuowen Tu, and Stefano Soatto. Memot: Multi-object tracking with memory. In CVPR, 2022. 3
- [18] Fei He, Haoyang Zhang, Naiyu Gao, Jian Jia, Yanhu Shan, Xin Zhao, and Kaiqi Huang. Inspro: Propagating instance query and proposal for online video instance segmentation. *NeurIPS*, 2022. 3
- [19] Shihao Wang, Yingfei Liu, Tiancai Wang, Ying Li, and Xiangyu Zhang. Exploring object-centric temporal modeling for efficient multi-view 3d object detection. In *ICCV*, 2023. 3
- [20] Zheng Qin, Sanping Zhou, Le Wang, Jinghai Duan, Gang Hua, and Wei Tang. Motiontrack: Learning robust short-term and long-term motions for multi-object tracking. In CVPR, 2023. 3

- [21] Junlong Li, Bingyao Yu, Yongming Rao, Jie Zhou, and Jiwen Lu. Tcovis: Temporally consistent online video instance segmentation. In *ICCV*, 2023. 3
- [22] Xiao Hu, Basavaraj Hampiholi, Heiko Neumann, and Jochen Lang. Temporal context enhanced referring video object segmentation. In WACV, 2024. 3
- [23] OpenAI. https://chat.openai.com, 2023. 4
- [24] Yifu Zhang, Chunyu Wang, Xinggang Wang, Wenjun Zeng, and Wenyu Liu. Fairmot: On the fairness of detection and re-identification in multiple object tracking. *IJCV*, 2021. 7, 8
- [25] Nicolai Wojke, Alex Bewley, and Dietrich Paulus. Simple online and realtime tracking with a deep association metric. In *ICIP*, 2017. 7
- [26] Yifu Zhang, Peize Sun, Yi Jiang, Dongdong Yu, Fucheng Weng, Zehuan Yuan, Ping Luo, Wenyu Liu, and Xinggang Wang. Bytetrack: Multi-object tracking by associating every detection box. In ECCV, 2022. 7, 8
- [27] Chao Liang, Zhipeng Zhang, Xue Zhou, Bing Li, Shuyuan Zhu, and Weiming Hu. Rethinking the competition between detection and reid in multiobject tracking. *IEEE TIP*, 2022. 7
- [28] Peize Sun, Jinkun Cao, Yi Jiang, Rufeng Zhang, Enze Xie, Zehuan Yuan, Changhu Wang, and Ping Luo. Transtrack: Multiple object tracking with transformer. arXiv preprint arXiv:2012.15460, 2020.
- [29] Tim Meinhardt, Alexander Kirillov, Laura Leal-Taixe, and Christoph Feichtenhofer. Trackformer: Multiobject tracking with transformers. In CVPR, 2022. 7
- [30] Jiacheng Lin, Jiajun Chen, Kunyu Peng, Xuan He, Zhiyong Li, Rainer Stiefelhagen, and Kailun Yang. Echotrack: Auditory referring multi-object tracking for autonomous driving. In arXiv preprint arXiv:2402.18302, 2024. 7
- [31] Wenyan He, Yajun Jian, Yang Lu, and Hanzi Wang. Visual-linguistic representation learning with deep cross-modality fusion for referring multi-object tracking. In *ICASSP*, 2024. 7
- [32] Jonathon Luiten, Aljosa Osep, Patrick Dendorfer, Philip Torr, Andreas Geiger, Laura Leal-Taixé, and Bastian Leibe. Hota: A higher order metric for evaluating multi-object tracking. *IJCV*, 2021. 7
- [33] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In CVPR, 2016. 8, 12
- [34] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692, 2019. 8, 12
- [35] Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. arXiv preprint arXiv:2010.04159, 2020. 12
- [36] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In ECCV, 2014. 12

Appendix

A More representative examples of Refer-KITTI-V2

We provide more representative examples of Refer-KITTI-V2 in Fig. 8. As shown, the dataset includes the expression "autos in black", highlighting the color and type of vehicles. Another example refers to "automobiles that are braking on the right", specifying both the action and location of the vehicles. Additionally, there are descriptions like "the men are on the right side and they have t-shirts on", detailing the position, gender, clothing, and number of individuals. Lastly, the language expression such as "folk in black t-shirt and pant" provides a concise yet descriptive representation of people based on their attire. These varied examples demonstrate the richness and specificity of semantic information captured in Refer-KITTI-V2, enhancing the understanding and interpretation of objects and actions in autonomous driving scenarios.

B Datasets Details

For a comprehensive evaluation, we conduct experiments on three video datasets: Refer-KITTI, Refer-KITTI. Refer-KITTI stands as the inaugural publicly available RMOT dataset, comprising 18 videos and 818 annotations. Among these, 15 videos, featuring 660 descriptions, are allocated for training purposes, while the remaining 3 videos, accompanied by 158 descriptions, are designated for testing. We construct Refer-KITTI-V2 by extending KITTI, comprising 17 videos with 8,873 annotations for training and 4 videos with 897 annotations for testing. All ablation experiments are conducted Refer-KITTI-V2.

C Implementation Details

Model Details. We utilize a text encoder derived from RoBERTa [34], coupled with ResNet50 [33] as our visual backbone. The final three layers from the visual backbone are used to generate multi-scale features $\{I_t^3, I_t^4, I_t^5\}$ with spatial down-sampling rates of $\{8, 16, 32\}$, respectively. Besides, the lowest resolution feature map I_t^6 is added via a 3×3 convolution with a spatial stride of 2 on the I_t^5 . We use a 1×1 convolution to reduce visual and linguistic futures to d=256 before being input to the Fusion Encoder for cross-model feature extraction. The length of memory used in the temporal enhancement module is N=4 for Refer-KITTI and N=5 for Refer-KITTI-V2.

Training. Following the setting of TransRMOT [2], the parameters of Transformer-Encoder and Transformer-Decoder are initialized from the official Deformable DETR [35] with iterative bounding track refinement weights pre-trained on the COCO dataset [36]. The parameters in the text encoder are kept frozen during the training process and all remaining parameters are randomly initialized. Our optimization strategy employs Adam with a base learning rate of 1e-5, except for the visual backbone, which uses a learning rate of 1e-5. Beginning from the 40th epoch, we decrease the learning rate by a factor of 10. The coefficients for losses are set as $\lambda_{cls}^D = 5$, $\lambda_{L_1}^D = 2$, $\lambda_{giou}^D = 2$, $\lambda_{ref}^R = 2$, $\lambda_{ref}^R = 2$. We conduct end-to-end training of the entire network with a batch size of 1 for 60 epochs on 4 RTX 4090 GPUs.

Inference. During inference, our model operates without the need for post-processing. We employ a score threshold $\beta_{score} = 0.6$ and a reference threshold $\beta_{ref} = 0.4$ to filter target objects.

D Additional Qualitative Results.

Compared to the previous models, TempRMOT has made significant improvements in ensuring the continuity of tracking targets, greatly reducing cases of target loss during the tracking process. For instance, as shown in Fig. 9, when dealing with the command "moving cars", instances of object tracking loss frequently occurred in TransRMOT, whereas in TempRMOT, this issue does not exist. This advantage is mainly attributed to our newly introduced temporal enhancement module, which, by analyzing multi-frame data, can effectively capture and understand variations in object velocity, thereby enhancing the precise grasp of motion information.



"automobiles that are braking on the right"



"the men are on the right side and they have t-shirts on"



"folk in black t-shirt and pants"

Figure 8: More representative examples of Refer-KITTI-V2.



(c) "parking cars"

Figure 9: Visualization of predictions from TransRMOT and our TempRMOT.

Furthermore, our model is able to distinguish situations where objects belong to the same category but have different motion states. Given the expression "left cars which are parking", TransRMOT often mistakenly identified moving vehicles as stationary, whereas TempRMOT can differentiate these complex motion states. Additionally, TempRMOT enhances its ability to recognize object motion variations by aggregating information from multiple frames. A specific example is shown in the scenario depicted in Fig. 9, where a red car pauses its movement when encountering a traffic light. When the motion status of the vehicle changes and aligns with semantic information, our model can correctly identify and continuously track this car, demonstrating its outstanding environmental adaptability and target tracking continuity.

Licenses of KITTI [12], Refer-KITTI[2], and Refer-KITTI-V2 (Ours): CC BY-NC-SA 3.0, MIT, and CC BY 4.0, respectively.