The Reasonable Effectiveness of Speaker Embeddings for Violence Detection

Sarthak Jain^{*1}, Orchid Chetia Phukan^{*2}, Arun Balaji Buduru², Rajesh Sharma^{2,3}

¹GGSIPU, New Delhi, India, ²IIIT-Delhi, India, ³University of Tartu, Estonia *equal contribution

sarthakjainssjj@gmail.com, orchidp@iiitd.ac.in

Abstract

In this paper, we focus on audio violence detection (AVD). AVD is necessary for several reasons, especially in the context of maintaining safety, preventing harm, and ensuring security in various environments. This calls for accurate AVD systems. Like many related applications in audio processing, the most common approach for improving the performance, would be by leveraging self-supervised (SSL) pre-trained models (PTMs). However, as these SSL models are very large models with million of parameters and this can hinder real-world deployment especially in compute-constraint environment. To resolve this, we propose the usage of speaker recognition models which are much smaller compared to the SSL models. Experimentation with speaker recognition model embeddings with SVM & Random Forest as classifiers, we show that speaker recognition model embeddings perform the best in comparison to state-ofthe-art (SOTA) SSL models and achieve SOTA results.

Index Terms: Violence Detection, Speaker Embeddings, x-vector

1. Introduction

Violence not only inflicts immediate harm but also leaves lasting scars on the fabric of society. The ripple effects extend beyond individual victims, impacting families, neighborhoods, and entire communities. As such, ensuring public safety and security becomes paramount, requiring proactive measures to address violence and foster environments where all members can thrive without fear of harm or injustice. In response to the negative effects associated with violence, previous research has made substantial leap towards violence detection through use of various modalities. In this work, we focus on audio violence detection (AVD). AVD has advantages in conditions such as in areas with low visibility or at night for detecting violence, in comparison to visual or audio-visual violence where access to a visual monitoring device will be required. Researchers have explored AVD with methods ranging from classical machine learning to deep learning [1, 2]. However, despite all these advancements AVD still lacks in accuracy and considering the importance of AVD, systems with higher accuracy are need of the hour

Following related speech and audio processing applications, the most common and beneficial way to boost up a system performance would be using embeddings from pre-trained models (PTMs) especially self-supervised (SSL) PTMs [3]. However, these state-of-the-art (SOTA) SSL PTMs are very large with millions of parameters that may hinder real-world deployment of AVD systems especially in scenarios with less compute power. In response, in this work, we propose to use embeddings extracted from speaker recognition PTMs, models pre-trained primarily for speaker recognition for AVD which is much smaller in size than the SSL PTMs. With comprehensive comparative analysis, we show that x-vector (speaker recognition) embeddings attains the topmost performance. This topmost behavior of x-vector embeddings can be attributed to its effectiveness in capturing intensity, intonation, etc more effectively than SSL PTMs for AVD.

2. Application

In this section, we discuss various parts of the proposed AVD application. Firstly, we discuss the various PTMs whose embeddings are used in our study and the classifiers. Followed by the database considered and the results of the experiments. Lastly, we discuss the workings of the application and how a user can interact with the application.

Pre-Trained Models: We use SOTA SSL PTMs WavLM [4] and Unispeech-SAT [5] because of its performance in various applications in SUPERB. For speaker recognition PTMs, we choose x-vector [6] and ECAPA [7] due to their SOTA performance in speaker recognition. The number of parameters of the PTMs are 94.7M, 94.68M, 7M, 20M for wavLM, Unispeech-SAT, x-vector, ECAPA respectively. We extract embeddings of 768 from the last hidden state of SSL PTMs through average pooling and for x-vector, we extract embeddings of dimension of 512.

Classifiers: We experiment with Random Forest (RF) and Support Vector Machine (SVM) classifier with default parameters. We train the models with 5-fold where four folds will be used for training and fifth fold for testing.

Database and Pre-Processing: We use AVD database¹ used by Zhu et al. [8]. We divided each of the violence and non violence audio files into sub audio files of 2.5 sec following [8] and results in dataset with non-violence audios of 7241 and violent audios of 1374. We resample the audios to 16kHz for passing as input to the PTMs.

Experimental Results: The evaluation results of the various models are presented in Table 1. Models trained with speaker recognition models (x-vector, ECAPA) embeddings performed the best. This can be attributed to their supremacy in capturing speech characteristics such as intensity, intonation, etc more effectively. We use the best model Random Forest trained with x-vector embeddings as backend model in the application.

User Interface: Working and Backend Details: The user interface of the application is presented in Figure 1. In mode 1 (Figure 1 (a)), user can use *Start Recording* and *Stop Recording* button to record real-world audio for AVD and in mode 2 (Figure 1 (b)) user can upload a audio with *Choose File* button for

¹https://www.kaggle.com/datasets/fangfangz/ audio-based-violence-detection-dataset



Figure 1: Audio Violence Detection Application; Application architecture pipeline is presented in Figure 1 (a) with the flow of information when the input audio is provided to the final inference received by the user through the user interface; Figure 1(c) shows the confusion matrix of the best model RF with x-vector embeddings

Table 1: Performance Scores; Scores are average of 5 folds; Scores are presented in %; F1 is macro-average F1-Score; MFCCs are used as baseline

РТМ		Accuracy		F1
Random Forest				
x-vector ECAPA MFCC Unispeech-SAT WaveLM		99.14 94.01 72.46 94.07 91.05		98.40 87.42 49.01 87.99 80.61
Support Vector Machine				
x-vector ECAPA MFCC Unispeech-SAT WaveLM		99.13 98.02 71.93 97.73 95.53		98.38 98.02 48.71 95.87 91.40

detecting violence in the uploaded audio. With *Predict* button, we can get the predictions out of the application. We have used React.Js and Flask for creating the Front-End and the Back-End for model inference respectively. The average inference time for a 1 min audio file is around 1 sec, thus making it deployable to real-world use. **3** Conclusion

^{rid use.} **3. Conclusion**

In this demonstration, we've created an application that harnesses speaker recognition model embeddings to enhance AVD. The application streamlines the process of detecting violent activities across surveillance feeds without access to visualmonitoring device. Overall, the application offers law enforcement agencies a powerful tool for more efficient and effective monitoring, ultimately enhancing public safety.

4. References

 A. M. Yildiz, P. D. Barua, S. Dogan, M. Baygin, T. Tuncer, C. P. Ooi, H. Fujita, and U. R. Acharya, "A novel tree pattern-based violence detection model using audio signals," *Expert systems with applications*, vol. 224, p. 120031, 2023.

- [2] A. Bakhshi, J. García-Gómez, R. Gil-Pita, and S. Chalup, "Violence detection in real-life audio signals using lightweight deep neural networks," *Procedia Computer Science*, vol. 222, pp. 244– 251, 2023.
- [3] S. wen Yang, P.-H. Chi, Y.-S. Chuang, C.-I. J. Lai, K. Lakhotia, Y. Y. Lin, A. T. Liu, J. Shi, X. Chang, G.-T. Lin, T.-H. Huang, W.-C. Tseng, K. tik Lee, D.-R. Liu, Z. Huang, S. Dong, S.-W. Li, S. Watanabe, A. Mohamed, and H. yi Lee, "SUPERB: Speech Processing Universal PERformance Benchmark," in *Proc. Interspeech* 2021, 2021, pp. 1194–1198.
- [4] S. Chen, C. Wang, Z. Chen, Y. Wu, S. Liu, Z. Chen, J. Li, N. Kanda, T. Yoshioka, X. Xiao, J. Wu, L. Zhou, S. Ren, Y. Qian, Y. Qian, J. Wu, M. Zeng, X. Yu, and F. Wei, "Wavlm: Large-scale selfsupervised pre-training for full stack speech processing," *IEEE Journal of Selected Topics in Signal Processing*, vol. 16, no. 6, pp. 1505–1518, 2022.
- [5] S. Chen, Y. Wu, C. Wang, Z. Chen, Z. Chen, S. Liu, J. Wu, Y. Qian, F. Wei, J. Li, and X. Yu, "Unispeech-sat: Universal speech representation learning with speaker aware pre-training," in *ICASSP* 2022 - 2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2022, pp. 6152–6156.
- [6] D. Snyder, D. Garcia-Romero, G. Sell, D. Povey, and S. Khudanpur, "X-vectors: Robust dnn embeddings for speaker recognition," in 2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2018, pp. 5329–5333.
- [7] B. Desplanques, J. Thienpondt, and K. Demuynck, "ECAPA-TDNN: Emphasized Channel Attention, Propagation and Aggregation in TDNN Based Speaker Verification," in *Proc. Interspeech* 2020, 2020, pp. 3830–3834.
- [8] F. Zhu-Zhou, D. Tejera-Berengué, R. Gil-Pita, M. Utrilla-Manso, and M. Rosa-Zurera, "Computationally constrained audio-based violence detection through transfer learning and data augmentation techniques," *Applied Acoustics*, vol. 213, p. 109638, 2023.