Classification Modeling with RNN-Based, Random Forest, and XGBoost for Imbalanced Data: A Case of Early Crash Detection in ASEAN-5 Stock Markets

Deri Siswara¹*, Agus M. Soleh², Aji Hamim Wigena³

^{1,2,3} Statistics and Data Sciences Department, Faculty of Mathematics and Natural Sciences, IPB University, Indonesia

Abstract.

This research aims to evaluate the performance of several Recurrent Neural Network (RNN) architectures including Simple RNN, Gated Recurrent Units (GRU), and Long Short-Term Memory (LSTM), compared to classic algorithms such as Random Forest and XGBoost in building classification models for early crash detection in ASEAN-5 stock markets. The study is examined using imbalanced data, which is common due to the rarity of market crashes. The study analyzes daily data from 2010 to 2023 across the major stock markets of the ASEAN-5 countries, including Indonesia, Malaysia, Singapore, Thailand, and Philippines. Market crash is identified as the target variable when the major stock price indices fall below the Value at Risk (VaR) thresholds of 5%, 2.5% and 1%. predictors involving technical indicators of major local and global markets as well as commodity markets. This study includes 213 predictors with their respective lags (5, 10, 15, 22, 50, 200) and uses a time step of 7, expanding the total number of predictors to 1491. The challenge of data imbalance is addressed with SMOTE-ENN. The results show that all RNN-Based architectures outperform Random Forest and XGBoost. Among the various RNN architectures, Simple RNN stands out as the most superior, mainly due to the data characteristics that are not overly complex and focus more on short-term information. This study enhances and extends the range of phenomena observed in previous studies by incorporating variables like different geographical zones and time periods, as well as methodological adjustments.

Keywords: early crash detection; GRU; LSTM; RNN; Random Forest; XGBoost

INTRODUCTION

Artificial Neural Networks (ANNs) are artificial intelligence (AI) models that mimic the human brain's functioning and as the basis of deep learning approachment. Introduced in the 1990s, ANNs has through rapid development over the past two decades with advancements in computer power, AI technology, and data availability [1]. The term 'architecture' in ANNs, is more commonly used than 'algorithm'. ANNs architectures are typically employed in supervised learning problems. Recurrent Neural Network (RNN) is one notable ANN architecture developed for predicting sequential data (sequences) [2].

In cases which involving sequential data prediction, there are various types of problems based on the sequence of input and output. Firstly, sequence prediction, such as in weather forecasting and predicting future stock market prices based on historical data. Secondly, sequence classification, as in DNA sequence classification and sentiment analysis to predict the sentiment of text such as positive or negative reviews. Thirdly, sequence generation, include the generating captions for images, where an image is given as input, and then a sequence of words describing the image is produced. Lastly, sequence-to-sequence prediction, like multi-step time series forecasting, which predicts a series of observations for a future time period [3]. All of these cases can be solved using recurrent neural network (RNN) architectures.

The architecture of Recurrent Neural Networks (RNN) has undergone several significant developments, with two of the most popular are Long Short-Term Memory (LSTM) and Gated Recurrent Units (GRU). LSTM is capable of retaining information for long periods and is more effective at learning long-term dependencies in a dataset. Meanwhile, GRU is a simplified version of LSTM which combines several gates in LSTM into one or two gates, making it more computationally efficient and often faster in training without sacrificing much capability in modeling long-term dependencies. GRU has proven effective in various applications, often delivering performance that comparable to LSTM with a more compact structure. However, its effectiveness depends greatly on the specific case or application being addressed [4].

¹*Corresponding author.

Email addresses: derikayz@gmail.com (Siswara), agusms@apps.ipb.ac.id. (Soleh), aji_hw@apps.ipb.ac.id (Wigena)

In fields other than genetics, text, and images, Recurrent Neural Networks (RNNs) and their derivatives are frequently applied in prediction of financial dataset, particularly for stock market price movements. In this context, RNNs are typically used to forecast future prices, like predicting the next day's stock prices or the trend for several days ahead. This application is reflected in studies by Li and Qian [5] and Jin et al. [6]. RNNs are also utilized to predict whether stock prices will go up or down, a binary trend prediction, as researched by Zhao et al. [7]. However, a significant research gap exists in predicting substantial and unusual price drops, known as market crash. These often occur during crises, such as the 2007 subprime mortgage crisis or the 2020 COVID-19 pandemic. Yet, market crash also able to take place outside major crises due to a variety of factors, as noted by Smith et al. [8].

Early detection in financial markets is frequently research's key area aimed at assessing financial market. Both machine learning and deep learning techniques are commonly used in these studies. For example, Bluwstein et al. [9] utilized machine learning for predicting recessions, while Tölö [10] applied Recurrent Neural Networks (RNN) for detecting financial crises. These researchers focused on the financial market roundly, involve various macroeconomic factors. The research focuses on early detection in stock markets, where market crash is defined as an anomaly or a decline in which prices are unacceptable or fall outside of an investor's risk tolerance.

Research related to early detection of crash in stock markets using machine learning and deep learning has garnered significant interest in recent years. Chatzis et al. [11] investigated the mechanisms of crash transmission in international stock markets utilizes daily data of 39 countries, employed the Neural Networks and Support Vector Machines. Their findings suggest Deep Neural Networks deployment significantly enhance the classification accuracy, also provide a robust alternative to develop more efficient and sensitive tools towards risk for global systemic early detection. Another study by Moser [12] examined the use of RNN-LSTM models and classic machine learning to predict stock market crash, reveal that simpler models are more effective than the complex ones in various scenarios. Meanwhile, Dichtl et al. [13] demonstrated models based on Support Vector Machines are more advanced in predicting stock market crash in the Eurozone compared to other models.

This research aims to compare the performance of several RNN-based architectures, including Simple RNN, GRU, and LSTM, alongside classic machine learning algorithms such as Random Forest and XGBoost, for early crash detection in stock markets. This study enhances and extends the range of phenomena observed in previous studies by incorporating variables like different geographical zones and time periods, as well as methodological adjustments. Technical indicators from both local and global financial markets are utilized as predictors. The stock market samples used in this research are from the ASEAN-5 zones. The occurrence of market crashes leads to imbalanced target data classes, since a market crash is a rare phenomenon. Consequently, this study also addresses the presence of imbalanced data classes, enabling the examination of RNNs and classic machine learning characteristics in such contexts. Philosophically, this study posits that for any cases involving temporal or time series data, sequence-based models (such as RNNs) are more appropriate than classic machine learning approaches. Therefore, to provide a comparative analysis, algorithms like Random Forest and XGBoost are employed, with XGBoost being particularly noted for its robust handling of imbalanced data classes [14]. This makes it especially interesting to explore the comparative performance of these models.

METHODS

This study focuses on data from the five largest stock markets in the ASEAN-5 region, which includes Indonesia, Malaysia, Singapore, Thailand, and the Philippines, creating a total of five datasets. The data are publicly available from Yahoo Finance[15]. The data used consists of irregular daily stock prices, as stock market trading only occurs on weekdays, from the year 2010 to 2023. The target variable, market crash, is determined based on the decrease in the primary stock price indices below a specified value at risk (VaR) threshold [11], [16], [17] which are 5%, 2.5%, and 1%. These thresholds reflect the level of risk that might be acceptable to investors. For example, a 5% VaR threshold suggests that, based on historical distribution of returns, the lowest 5% of returns are considered market crash, while the rest are considered as normal. Therefore, the target variable is characterized as binary data. Similar scenarios are also applied for VaR thresholds of 2.5% and 1%. Based on three imbalance class scenarios, total 15 datasets (5 markets × 3 VaR scenarios).

The predictors include technical indicators such as return rate, Moving Average (MA), Exponential Moving Average (EMA), the difference between opening and closing stock prices, Relative Strength Index (RSI), and Moving Average Convergence Divergence (MACD). These indicators are derived from both local and global major stock markets, as well as currency exchange rates and commodity markets. Global markets which also included in the predictors are the Dow Jones Industrial (DJI), NASDAQ, European markets (EURO), Japanese markets (JPAN), and the Green Index (FAN), while the considered commodities include crude oil, gold, and bonds. Currency exchange rates involve the value of each ASEAN-5 country's currency towards the US dollar. MA and EMA are further subdivided into lags of the 5th, 10th, 15th, 20th, 22nd, 50th, and 200th day, resulting total of 213 predictors. The analysis is conducted using time steps of 7, which means each predictor has 7 lags (from X_{t-1} to X_{t-7}), leading to total of 1491 predictors for each dataset. The current time point Xt is excluded to focus the model on predicting the following day outcomes, enabling market crash early detection of one day in advance.

Various machine learning models were implemented across five ASEAN-5 stock markets datasets. These models include Simple RNN, LSTM, and GRU architectures, as well as the Random Forest and XGBoost algorithms. The best-performing model was selected based on four primary metrics: precision-recall curve (PRC), balanced accuracy, false alarm rate, and hit rate [11]. The PRC is critical in assessing the trade-off between precision and recall, particularly for the minority class, highly relevant for imbalanced data sets. Balanced accuracy offers a fair assessment of a model performance across both classes. The false alarm rate measures the frequency of incorrect market crash predictions. In the study, the false alarm rate is inverted to facilitate interpretation. The hit rate assesses the model's ability to accurately detect market crashes. The determination of best hyperparameters for each model was carried out through a grid search process, involving a predefined range of values for each architecture and algorithm.

Architectures / Algorithms	Hyperparameter		
Simple RNN, LSTM, and GRU	Time Steps: [7],		
	N Neuron: [32, 64, 128],		
	<i>N Layers</i> : [1, 2],		
	Learning Rate: [0.001, 0.01, 0.1], Epochs: [50]		
	Early Stop		
Random Forest	N Estimators: [100, 200, 300],		
	Max Depth: [10, 20, 30]		
XGBoost	N Estimators: [100, 200, 300].		
	Learning Rate: [0.01, 0.1, 0.2].		
	<i>Max Depth</i> : [3, 4, 5]		

Table 1. Grid hyperparameter on each model

Each analysis in this research began with the model implementation without addressing the issue of imbalanced data, expressed as a baseline. This initial step is influential for understanding how the models perform under the dataset's natural conditions. Subsequently, to overcome the challenges caused by imbalanced data condition, a specific treatment was applied utilizing the Synthetic Minority Over-sampling Technique (SMOTE) in conjunction with Edited Nearest Neighbors (ENN). This method combines an oversampling technique, which adds samples to the minority class, and cleaning technique aims to remove ambiguous or overlapping samples. Hence, further analyses were conducted with imbalanced data handling to observe any improvements or changes in model performance based on the predefined metrics. The use of the SMOTE-ENN has been demonstrated to be effective as evidenced by research of Mukhlashin et al. [18].

The stages of analysis in this research are visualized in Figure 1 and described as follows:



Figure 1. A flowchart of the analysis stages

- 1. Data collection and data pre-processing
 - a. Each one of the datasets are sourced from Yahoo Finance.
 - b. Form predictor variables, consists of technical indicators from each dataset [19].
 - c. Establish target variables with three scenarios based on Value at Risk (VaR) return thresholds: 5% (moderate), 2.5% (high), and 1% (extreme). Labeled as "Crash" if the return is below the specified threshold.
 - d. Imputation process to complete missing data which caused by operational time differences between local and global markets using K-Nearest Neighbors (KNN) [20]. This imputation generates no more than 20% of the data because variables with a missing data proportion exceeding 20% have been previously eliminated [21].
- 2. Data exploration
- 3. Data splitting into data training, validation data, and data testing to perform the Time Series Cross Validation (TSCV) [22]. Training data combination and validation data are utilized to find the optimal hyperparameter. Meanwhile, there are combination of data training and data testing to evaluate final performance. The data partition details are as follows:

Κ	Data training period	Data validation period
1	01-01-201031-12-2011	01-01-201231-12-2013
2	01-01-201031-12-2013	01-01-201431-12-2015
3	01-01-201031-12-2015	01-01-201631-12-2019
		Data testing period
4	01-01-201031-12-2019	01-01-202031-12-2023

Table 2. Data partition details

- 4. Analyzes the ASEAN-5 datasets with Simple RNN, LSTM, and GRU architectures, also Random Forest, and XGBoost algorithms through TSCV process so that results evaluation metrics for each architecture/algorithm.
- 5. Visualizes early crash detection with foremost architecture/algorithm.

RESULT AND DISCUSSION

Data exploration

Various instances of stock market crashes have occurred in the ASEAN-5 zone, with patterns of crash occurrences that are relatively similar as shown in Figure 2. Exploring the points of crash occurrences in each market forms the basis for data partitioning for TSVC and also the determination of predictors. The data partitioning has irregular intervals, as it turns out there are years when no crashes occurred at all in some markets. The global financial crisis is the main cause of crashes in the ASEAN-5 stock markets. These markets are relatively easily shaken simultaneously by global shocks, considering that the stock markets in this zone are still developing. Some global financial crises that align with the occurrences of crashes in the ASEAN-5 stock markets include the Chinese Stock Market Crisis (2015-2016), the US Market Sell-Off (2015-2016), and the COVID-19 Pandemic (2020).



Figure 2. The crashes that occurred in the ASEAN-5 stock markets under the 2.5% VaR scenario

Evaluation

The initial analysis was conducted using various algorithms and architectures without taking into account the class imbalance of the data, which means that no resampling process was performed on the dataset to handle the imbalance issue. This initial analysis acts as a baseline. In the baseline evaluation, it was revealed that the RNN-Based architecture, failed to predict srock market crash (hit rate = 0). Only Random Forest succeeds in the 2.5% VaR scenario despite the trade-off of a low false alarm rate. Consequently, the baseline results reveal the need for imbalanced data handling strategies to improve the quality of predictive models. Subsequent analysis integrating the SMOTE-ENN approach shows substantial performance improvements.

As illustrated in Figure 3, the distribution of performance values across the ASEAN-5 dataset with a 1% VaR crash scenario records a significant improvement in the evaluation metrics after the application of the SMOTE-ENN technique.



Figure 3. Performance evaluation on datasets with VaR 1% ASEAN-5 based on metrics (a) Hit Rate, (b) Balance accuracy score, (c) PRC score, and (d) False alarm rate

The architectures of RNN-Based (RNN, LSTM, and GRU) demonstrated higher performance in hit rate, balanced accuracy, and PRC scores compared to Random Forest and XGBoost. This indicates their effectiveness in predicting market crashs 1-day ahead within the ASEAN-5 dataset, although with marginally lower false alarm rate relative to XGBoost. Table 3 concisely encapsulates the performance comparison by presenting average values for these metrics which provides an integrated perspective of the relative efficacy of each algorithm/architecture.

Algorithms / architectures	False Alarm Rate	Hit Rate	Balance Accuracy	PRC Score
Dataset 1%				
RNN	0.975	0.278	0.626	0.072
LSTM	0.973	0.226	0.600	0.058
GRU	0.982	0.257	0.620	0.068
RF	0.850	0.126	0.488	0.015
XGBoost	0.987	0.038	0.512	0.016
Dataset 2.5%				
RNN	0.853	0.362	0.608	0.066
LSTM	0.834	0.366	0.600	0.067
GRU	0.846	0.343	0.594	0.067
RF	0.988	0.008	0.498	0.028
XGBoost	0.971	0.108	0.539	0.040
Dataset 5%				
RNN	0.885	0.266	0.575	0.074
LSTM	0.867	0.276	0.571	0.067

Table 3. Average values of each algorithms'/architectures' performances on every dataset

Algorithms / architectures	False Alarm Rate	Hit Rate	Balance Accuracy	PRC Score
GRU	0.902	0.260	0.581	0.072
RF	0.982	0.064	0.523	0.059
XGBoost	0.943	0.149	0.546	0.062

*Thickened values show the leading evaluation values among all algorithms/architectures

Generally speaking, the performance analysis indicates that RNN-Based (RNN, LSTM, and GRU) consistently outperform Random Forest and XGBoost in terms of hit rate, balanced accuracy, and PRC score across datasets with different VaR crash thresholds. This specifies higher effectiveness in detecting market crashs. While XGBoost has highest false alarm rate in the 1% VaR dataset, Random Forest shows the highest false alarm rate in the 2.5% and 5% VaR datasets, indicate its better tendency in reducing false crashs. The false alarm rate of RNN-Based is considered to be within acceptable limits. Eventually, the accuracy in early detection of market crash (hit rate) is prioritized as a metric due to its importance in minimizing potential investment losses [11].

The superiority of the RNN-Based architecture over Random Forest and XGBoost in this study is because RNN-Based is well suited for modeling time dependencies. This makes RNN-Based more effective than tree-based models in capturing time dynamics [23]. RNNs can handle variable-length sequences in time series data that often contain irregular sampling intervals [24]. This flexibility is not inherently available in models like Random Forest or XGBoost, which typically rely on fixed-length feature vectors [25].

Thereafter, in case of comparing the performance among the RNN-Based architectures, Simple RNN demonstrates better performance compared to its developments, LSTM and GRU. LSTM slightly outperforms in hit rate for datasets with 2.5% and 5% VaR, but Simple RNN maintains its superiority in balanced accuracy. This finding suggests that the datasets used in the research might not be overly complex or not require extensive processing of long-term historical information, aligning with the basic capabilities of Simple RNN that prioritize short-term memory [26].

Further analysis on each country within ASEAN-5 shows that RNN-Based performance is generally superior to Random Forest and XGBoost algorithms, although there is a slight exception on the Thailand dataset (Figure 4). On the Thailand dataset with 1% VaR, Random Forest recorded the highest hit rate and balance accuracy beating RNN-Based. These results suggest that there is potential to develop better architectures or apply different architectures depending on the study and the characteristics of stock market data in ASEAN-5 which may differ.





Figure 4. Performance evaluation on datasets with VaR 1% scenario of each country with metrics (a) Hit rate, (b) Balance accuracy score, (c) PRC score, and (d) False alarm rate

Overall, the performance of the hit rate metric in this study is in the interval of 0%-64% with an average of 21%. This value is certainly still relatively low and there needs to be better model and architecture development. However, when compared to previous research, the value is still at a consistent interval. Research by Chatzis et al. [11] has a hit rate value interval of 38%-59%, Moser's [12] has a hit rate value interval of 45%-71%, and research by Dichtl et al. [13] has an interval of 9%-50% hit rate value. The hit rate value in this study is relatively similar to Dichtl et al. [13] because they faced the dataset in the same period as the financial crisis due to COVID-19 which gave significant anomalies in the stock market.

Visualization

The market crash early detection model becomes more useful when the crash probability visualization is combined with the best algorithm or architecture [27]. Figure 5 displays the visualization of the early detection model using RNN for the Indonesian dataset with 1% VaR crash over the period 2020-2023. In this case, the RNN demonstrated the ability to detect crash 1-day ahead in advance with a hit rate that did not exceed 50% of the total crash incidents that actually occurred. However, Simple RNN was significantly successful in identifying market crash during the crisis caused by the COVID-19 pandemic in March 2020 with few false alarms. False alarms in crisis periods can be useful for investors to raise higher alertness. Outside of the crisis predictions as it cannot effectively foresee those distinctive patterns that have not appeared previously [28].



Figure 5. The early crash detection models for Indonesian dataset with VaR 1% using Simple RNN architectures during 2020-2023

CONCLUSION

The RNN-Based architecture are recommended as a more effective approach to modeling early crash detection of stock market in the case of ASEAN-5, compared to classical machine learning models such as Random Forest and XGBoost, despite the need to address class imbalance. Of the various RNN-Based architectures, simple RNN stands out as the most superior, largely due to the less complex characteristics of the data and more focus on short-term information. Although the maximum balance accuracy in predicting crash is only 64%, the results are still relatively capable of detecting high market crash or sharp declines in stock prices, as experienced during market crisis periods.

In order to improve performance, it is necessary to develop an architecture that emphasizes the development of RNN-Based types such as bidirectional and stacked techniques[29]. In addition, another effort that can be made is to extend the time steps so that the information stored can be more comprehensive in evaluating the performance of the LSTM and GRU models[30]. Finally, for each case and each country's different data characteristics, it is necessary to adjust the basic architecture and model individually. Finally, future researchers need to capture crash predictions that occur continuously (>1 day).

REFERENCES

- [1] I. Casas, "Networks, Neural," in *International Encyclopedia of Human Geography*, Elsevier, 2020, pp. 381–385. doi: 10.1016/B978-0-08-102295-5.10410-X.
- R. DiPietro and G. D. Hager, "Deep learning: RNNs and LSTM," in *Handbook of Medical Image Computing and Computer Assisted Intervention*, Elsevier, 2020, pp. 503–519. doi: 10.1016/B978-0-12-816176-0.00026-0.
- [3] Jason Brownlee, "How to Develop LSTM Models for Time Series Forecasting," *Machinelearningmastery*, 2018.
- [4] R. Zhu, X. Tu, and J. Xiangji Huang, "Deep learning on information retrieval and its applications," in *Deep Learning for Data Analytics*, Elsevier, 2020, pp. 125–153. doi: 10.1016/B978-0-12-819764-6.00008-9.
- [5] C. Li and G. Qian, "Stock Price Prediction Using a Frequency Decomposition Based GRU Transformer Neural Network," *Applied Sciences*, vol. 13, no. 1, p. 222, Dec. 2022, doi: 10.3390/app13010222.
- [6] Z. Jin, Y. Yang, and Y. Liu, "Stock closing price prediction based on sentiment analysis and LSTM," *Neural Comput Appl*, vol. 32, no. 13, pp. 9713–9729, Jul. 2020, doi: 10.1007/s00521-019-04504-2.
- [7] J. Zhao, D. Zeng, S. Liang, H. Kang, and Q. Liu, "Prediction model for stock price trend based on recurrent neural network," *J Ambient Intell Humaniz Comput*, vol. 12, no. 1, pp. 745–753, Jan. 2021, doi: 10.1007/s12652-020-02057-0.
- [8] M. F. Smith, I. Sinha, R. Lancioni, and H. Forman, "Role of Market Turbulence in Shaping Pricing Strategy," *Industrial Marketing Management*, vol. 28, no. 6, pp. 637–649, Nov. 1999, doi: 10.1016/S0019-8501(98)00037-6.
- [9] K. Bluwstein, M. Buckmann, A. Joseph, S. Kapadia, and Ö. Şimşek, "Credit growth, the yield curve and financial crisis prediction: Evidence from a machine learning approach," *J Int Econ*, vol. 145, p. 103773, Nov. 2023, doi: 10.1016/j.jinteco.2023.103773.
- [10] E. Tölö, "Predicting systemic financial crises with recurrent neural networks," *Journal of Financial Stability*, vol. 49, p. 100746, Aug. 2020, doi: 10.1016/j.jfs.2020.100746.
- S. P. Chatzis, V. Siakoulis, A. Petropoulos, E. Stavroulakis, and N. Vlachogiannakis,
 "Forecasting stock market crisis events using deep and statistical machine learning techniques," *Expert Syst Appl*, vol. 112, pp. 353–371, Dec. 2018, doi: 10.1016/j.eswa.2018.06.032.
- [12] R. Moser, "Predicting stock market crashes: An attempt with statistical machine learning techniques and neural networks," 2018. Accessed: Dec. 12, 2023. [Online]. Available: https://towardsdatascience.com/predicting-stock-market-crashes-with-statistical-machinelearning-techniques-and-neural-networks-bb66bc3e3ccd

- [13] H. Dichtl, W. Drobetz, and T. Otto, "Forecasting Stock Market Crashes via Machine Learning," *Journal of Financial Stability*, vol. 65, p. 101099, Apr. 2023, doi: 10.1016/j.jfs.2022.101099.
- [14] C. Wang, C. Deng, and S. Wang, "Imbalance-XGBoost: leveraging weighted and focal losses for binary label-imbalanced classification with XGBoost," *Pattern Recognit Lett*, vol. 136, pp. 190– 197, Aug. 2020, doi: 10.1016/j.patrec.2020.05.035.
- [15] Yahoo Finance, "Yahoo Finance stock market live, quotes, business & finance news," Yahoo Finance. [Online]. Available: https://finance.yahoo.com/
- [16] P. Giot and S. Laurent, "Value-at-risk for long and short trading positions," *Journal of Applied Econometrics*, vol. 18, no. 6, pp. 641–663, Nov. 2003, doi: 10.1002/jae.710.
- [17] W. Mensi, M. Ur Rehman, D. Maitra, K. Hamed Al-Yahyaee, and A. Sensoy, "Does bitcoin comove and share risk with Sukuk and world and regional Islamic stock markets? Evidence using a time-frequency approach," *Res Int Bus Finance*, vol. 53, p. 101230, Oct. 2020, doi: 10.1016/j.ribaf.2020.101230.
- [18] P. A. R. Mukhlashin, A. Fitrianto, A. M. Soleh, and W. Z. A. W. Muhamad, "Ensemble learning with imbalanced data handling in the early detection of capital markets," *Journal of Accounting and Investment*, vol. 24, no. 2, pp. 600–617, 2023.
- [19] S. Anbaee Farimani, M. Vafaei Jahan, A. Milani Fard, and S. R. K. Tabbakh, "Investigating the informativeness of technical indicators and news sentiment in financial market price prediction," *Knowl Based Syst*, vol. 247, 2022, doi: 10.1016/j.knosys.2022.108742.
- [20] S. Zhang, "Nearest neighbor selection for iteratively kNN imputation," *Journal of Systems and Software*, vol. 85, no. 11, 2012, doi: 10.1016/j.jss.2012.05.073.
- [21] G. Kyureghian, O. Capps, and R. M. Nayga, "A Missing Variable Imputation Methodology with an Empirical Application," *Advances in Econometrics*, vol. 27, no. 1, pp. 313–337, Jan. 2011, doi: 10.1108/S0731-9053(2011)000027A015.
- [22] A. Deng, "Time series cross validation: A theoretical result and finite sample performance," *Econ Lett*, vol. 233, 2023, doi: 10.1016/j.econlet.2023.111369.
- [23] L. Qu, M. Zhang, Z. Li, and W. Li, "Temporal Backtracking and Multistep Delay of Traffic Speed Series Prediction," *J Adv Transp*, vol. 2020, pp. 1–13, Dec. 2020, doi: 10.1155/2020/8899478.
- [24] P. B. Weerakody, K. W. Wong, G. Wang, and W. Ela, "A review of irregular time series data handling with gated recurrent neural networks," *Neurocomputing*, vol. 441, 2021, doi: 10.1016/j.neucom.2021.02.046.
- [25] L. Mou, P. Ghamisi, and X. X. Zhu, "Deep Recurrent Neural Networks for Hyperspectral Image Classification," *IEEE Transactions on Geoscience and Remote Sensing*, vol. 55, no. 7, pp. 3639– 3655, Jul. 2017, doi: 10.1109/TGRS.2016.2636241.
- [26] A. Sherstinsky, "Fundamentals of Recurrent Neural Network (RNN) and Long Short-Term Memory (LSTM) network," *Physica D*, vol. 404, p. 132306, Mar. 2020, doi: 10.1016/j.physd.2019.132306.
- [27] Z. Yuan, Y. Wang, and C. Sun, "Construction schedule early warning from the perspective of probability and visualization," *Journal of Intelligent and Fuzzy Systems*, vol. 32, no. 1, 2017, doi: 10.3233/JIFS-161084.
- [28] Y. Cai, N. Zhang, and S. Zhang, "GRU and LSTM Based Adaptive Prediction Model of Crude Oil Prices: Post-Covid-19 and Russian Ukraine War," in ACM International Conference Proceeding Series, Association for Computing Machinery, Jan. 2023, pp. 9–15. doi: 10.1145/3584816.3584818.
- [29] C. Liu, Y. Zhang, J. Sun, Z. Cui, and K. Wang, "Stacked bidirectional LSTM RNN to evaluate the remaining useful life of supercapacitor," *Int J Energy Res*, vol. 46, no. 3, 2022, doi: 10.1002/er.7360.

[30] S. Gao *et al.*, "Short-term runoff prediction with GRU and LSTM networks without requiring time step optimization during sample generation," *J Hydrol (Amst)*, vol. 589, 2020, doi: 10.1016/j.jhydrol.2020.125188.