Semantic-Aware Resource Allocation Based on Deep Reinforcement Learning for 5G-V2X HetNets

Zhiyu Shao, Qiong Wu, Senior Member, IEEE, Pingyi Fan, Senior Member, IEEE, Nan Cheng, Senior Member, IEEE, Qiang Fan, Jiangzhou Wang, Fellow, IEEE

Abstract—This letter proposes a semantic-aware resource allocation (SARA) framework with flexible duty cycle (DC) coexistence mechanism (SARADC) for 5G-V2X Heterogeneous Network (HetNets) based on deep reinforcement learning (DRL) proximal policy optimization (PPO). Specifically, we investigate V2X networks within a two-tiered HetNets structure. In response to the needs of high-speed vehicular networking in urban environments, we design a semantic communication system and introduce two resource allocation metrics: high-speed semantic transmission rate (HSR) and semantic spectrum efficiency (HSSE). Our main goal is to maximize HSSE. Additionally, we address the coexistence of vehicular users and WiFi users in 5G New Radio Unlicensed (NR-U) networks. To tackle this complex challenge, we propose a novel approach that jointly optimizes flexible DC coexistence mechanism and the allocation of resources and base stations (BSs). Unlike traditional bit transmission methods, our approach integrates the semantic communication paradigm into the communication system. Experimental results demonstrate that our proposed solution outperforms traditional bit transmission methods with traditional DC coexistence mechanism in terms of HSSE and semantic throughput (ST) for both vehicular and WiFi users.

Index Terms—Semantic communication, vehicular networks, resource allocation, unlicensed spectrum bands, proximal policy optimization (PPO).

I. INTRODUCTION

T HE fifth-generation (5G) networks aim to provide highspeed, low-latency, and reliable communication services for a wide range of applications, such as vehicle-to-everything (V2X) communications [1], [2], [3]. However, challenges arise in capacity and spectrum efficiency due to the increasing number of users, data demands and proliferation of connected devices [4], [5], [6], [7].

In dense urban areas, where user densities and traffic volumes are high, traditional networking mechanisms may not

This work was supported in part by the National Natural Science Foundation of China under Grant No. 61701197, in part by the National Key Research and Development Program of China under Grant No.2021YFA1000500(4), in part by the 111 Project under Grant No. B12018.

Zhiyu Shao, Qiong Wu are with the School of Internet of Things Engineering, Jiangnan University, Wuxi 214122, China (e-mail: zhiyushao@stu.jiangnan.edu.cn, qiongwu@jiangnan.edu.cn)

Pingyi Fan is with the Department of Electronic Engineering, Beijing National Research Center for Information Science and Technology, Tsinghua University, Beijing 100084, China (e-mail: fpy@tsinghua.edu.cn).

Nan Cheng is with the State Key Lab. of ISN and School of Telecommunications Engineering, Xidian University, Xi'an 710071, China (e-mail: dr.nan.cheng@ieee.org).

Qiang Fan is with Qualcomm, San Jose, CA 95110, USA (e-mail: qf9898@gmail.com).

Jiangzhou Wang is with the School of Engineering, University of Kent, CT2 7NT Canterbury, U.K. (email: j.z.wang@kent.ac.uk).

suffice to address capacity challenges [8], [9], [10], [11]. Deploying small cells and heterogeneous networks (HetNets) [12] becomes a promising solution to enhance network capacity by increasing the number of antennas on smaller base stations [13], [14], [15], [16].

1

Spectrum scarcity presents another challenge, as traditional communication methods fail to efficiently utilize the limited spectrum. This inefficiency prompts a shift to semantic communication [17], [18], [19], [20]. Semantic communication, focusing on transmitting the meaning of information rather than raw data, has a potential in reducing network traffic and alleviating spectrum scarcity. Recent studies have begun exploring semantic communication in various domains such as images [21], text [22], audio [23] and so on.

5G New Radio Unlicensed (NR-U) is a new radio technology that expands 5G HetNets' capacity by operating in unlicensed bands [24]. In this case, coexistence mechanisms with other wireless networks such as WiFi has to be taken into account due to interference. There are two existing coexistence mechanisms between NR-U and WiFi: one is listen before talk (LBT) [25]; the other mechanism is carrier sensing adaptive transmission (CSAT) [26], where base stations (BSs) reserve specific time slots for WiFi access points (APs) using duty cycle (DC) transmission. However, owing to the uncertainty of channel access, NR-U has a worse performance than continuous operation in licensed bands, and thus traditional NR-U and WiFi coexistence mechanisms pose a new challenge for 5G networks.

Furthermore, Traditional bit-based resource allocation which is derived from statistical knowledge of source symbols neglects semantic information, complicating spectrum utilization. This approach focuses on the quantity of bits transmitted rather than meaning, leading to inefficient spectrum use. To improve spectrum efficiency, resource allocation must be reconsidered from a semantic perspective, optimizing transmission and addressing the limitations of existing NR-U and WiFi coexistence mechanisms.

To handle the above issue, this letter introduces semantic communication into a two-tier HetNet vehicular communication system in urban environments for the first time. We propose a flexible DC approach to address coexistence issues between vehicular and WiFi users in NR-U networks, while introducing HRS and HSSE metrics in the resource allocation optimization. We design a semantic-aware resource allocation framework with flexible DC coexistence mechanism (SARADC) algorithm, which applies PPO DRL to optimize flexible DC and resource allocation based on semantic awareness to maximize semantic throughput (ST)¹. Experimental results demonstrate that our proposed algorithm outperforms other baselines in terms of HSSE and ST for both vehicular and WiFi users.

II. SYSTEM MODEL

As shown in Fig.1, we focus on V2X communication in a high-speed urban environment where N vehicles are initially distributed on the roads with different mobility directions. Each vehicle moves along its selected direction randomly in the environment at a constant speed V, resulting in N V2I links. In this work, we consider a two-tier HetNets deployment: the first tier comprises B_1 macro base stations (MaBs), providing broad coverage and high-capacity communication services operating in licensed frequency bands; the second tier comprises B_2 micro base stations (MiBs) operate in unlicensed frequency bands and provide dense coverage, high-speed and low-latency communication services primarily for areas with high vehicular density. These two tiers of base stations, denoted as $B = \{B_1, B_2\}$, accompanied by W APs. The MaBs and MiBs each have R_1 and R_2 RBs, respectively. The N vehicles and W WiFi APs are equipped with DeepSC models [27] to encode textual data "How is the road condition?" into semantic information and decode semantic information back to the original textual data "Road ahead is congested, please proceed with caution." Note that the model is pre-trained on BS, and then the trained semantic DeepSC transmitter models are broadcasted and employed directly by all vehicles due to the complex semantic information extraction during training process.



Fig. 1. The semantic-aware resource allocation system

A. DeepSC Transceivers and Novel Metrics

The *n*-th transmitter vehicle generates a sentence S_n with l words, where $S_n = [s_{n,1}, s_{n,2}, \ldots, s_{n,l}, \ldots, s_{n,l_q}]$. The sentence is then input into the encoding part of the DeepSC in the vehicle in order to extract semantic information X_n from S_n , given by:

$$X_n = ch_\beta \left(se_\alpha \left(S_n \right) \right),\tag{1}$$

where $se_{\alpha}(\cdot)$ and $ch_{\beta}(\cdot)$ are the semantic and channel encoder networks with parameters α and β , respectively. The semantic symbol vector is $X_n = [x_{n,1}, x_{n,2}, \ldots, x_{n,ul}]$, where u represents the average number of semantic symbols used

for each word. Then the encoded semantic information is transmitted via the wireless channel. The received semantic signal is represented as:

$$Y_n = H_{n,i}X_n + N, (2)$$

where $H_{n,i}$ is the channel gain for the *i*-th V2I link, N is the noise. So the signal-to-interference-noise Ratio (SINR) for the *n*-th vehicle is

$$SINR_{n,b,r} = \frac{\eta_{n,b,r} P_{n,b,r} H_{n,b,r}}{I_{n,b,r} + \delta^2},$$
 (3)

where $\eta_{n,b,r}$ is a binary indicators, and $\eta_{n,b,r} = 1$ means that *n*-th vehicle transmits semantic data to *b*-th BS using *r*th RB. $P_{n,b,r}$ and $H_{n,b,r}$ are the transmit power and channel gain from *n*-th vehicle to *b*-th BS on the *r*-th RB, $I_{n,b,r}$ is the interference on the *r*-th RB of *b*-th BS incurred by other BS including both MaBs and MiBs, which can be represented as:

$$I_{n,b,r} = \begin{cases} \sum_{\substack{\hat{n}=1\\\hat{n}\neq n}}^{N} \sum_{\substack{\hat{b}=1\\\hat{n}\neq n}}^{B_2} \eta_{\hat{n},\hat{b},r} P_{\hat{n},\hat{b},r} H_{\hat{n},b,r} & if \ b \in B_1 \\ \sum_{\substack{\hat{n}=1\\\hat{n}\neq n}}^{N} \sum_{\substack{\hat{b}=1\\\hat{b}=1}}^{B_1} \eta_{\hat{n},\hat{b},r} P_{\hat{n},\hat{b},r} H_{\hat{n},b,r} & if \ b \in B_2, \end{cases}$$
(4)

So the decoded signal can be represented as

$$\hat{S}_{n} = se_{\mu}^{-1} \left(ch_{\nu}^{-1} \left(Y_{n} \right) \right), \tag{5}$$

where $se_{\mu}^{-1}(\cdot)$ is the semantic decoder network with the parameter μ , and $ch_{\nu}^{-1}(\cdot)$ is the channel decoder network with the parameter ν . The Cross-entropy (CE) is used as the loss function to quantify the difference between \hat{S}_n and the original sentence S_n to get the DeepSC model. To evaluate the semantic communication performance, we employ semantic similarity as a performance metric ξ [28], given by:

$$\xi = \frac{B(S_n)B(\hat{S}_n)}{\|B(S_n)\| \|B(\hat{S}_n)\|}.$$
(6)

Here, $B(\cdot)$ represents the bidirectional encoder representation of the Transformers (BERT) model for sentences, and ξ indicates the highest similarity between the two sentences where $0 \le \xi \le 1$. Assuming text datasets is $\Upsilon = \sum_{i=n}^{N} S_n$, the average

semantic information for each sentence is $I = \sum_{i=n}^{N} I_n p(S_n)$, where I_n is the semantic information of sentence S_n . $p(S_n)$ represents the probability of sentence S_n appearing in the text datasets. Similarly, the average length for each sentence is $L = \sum_{i=n}^{N} l_n p(S_n)$. The HSR can be expressed as

$$HSR = W \frac{I}{uL} \xi, \tag{7}$$

where the unit of u is sut [27], thus the unit of HSR is suts/s. Therefore, we can further derive the metric HSSE:

$$HSSE = \frac{HSR}{W} = \frac{I}{u_q L} \xi, \tag{8}$$

which stands for the efficiency of transmitting semantic information in symbols per unit of available bandwidth. Note

¹The source code has been released at: https://github.com/qiongwu86/Semantic-Aware-Resource-Allocation-Basedon-Deep-Reinforcement-Learning-for-5G-V2X-HetNets

that the unit of HSSE is suts/s/Hz. In Eq. (8), the value of $\frac{I}{L}$ depends on the type of source, and thus, it is a constant, which can be omitted during optimization. ξ is modeled as $\xi = \Psi(u, SINR)$, as described in [27].

B. Flexible DC Mechanism

Since vehicles use NR-U for semantic transmission and WiFi employs unlicensed spectrum, collisions may occur due to overlapping frequency bands. Fig. 2 shows that a fixed time slot T is divided into two segments: in T_1 , vehicles exclusively transmit semantic data packets over NR-U, WiFi users access the unlicensed spectrum in T_2 . The time durations of T_1 and T_2 are adaptable based on network requirements.



Fig. 2. SADC Mechanism

According to (7), the ST of vehicle users is $ST_n = HSR_n \times T_1$ As the transmission rate of WiFi users within proximity of *n*-th vehicle is R_w . The ST of WiFi users according to IEEE 802.11ax (WiFi 6) [27] is $ST_w = \frac{R_w}{\mu} \times T_2$, where $\frac{R_w}{\mu}$ is HSR_w and μ is the number of average semantic symbol per word.

C. Optimization Problem

The objective of jointly optimizing SARADC mechanism is to maximize the average HSSE. That is to find the optimal channel allocation β , power allocation p, and the time period T_1 for vehicles exclusively transmitting semantic data packets over NR-U and the number of average semantic symbols per word μ . The optimization problem can be expressed as follows:

$$P_0: \max_{\beta, p, T_1, \mu} HSSE_n/N \tag{9a}$$

s.t.
$$\sum_{n=1}^{N} ST_n \ge \underline{ST_n},$$
 (9b)

$$\sum_{n=1}^{N} ST_w \ge \underline{ST_w},\tag{9c}$$

$$\sum_{n=1}^{N} \eta_{n,b,r} \le 1 \qquad \forall b \in \mathcal{B}, \forall r \in R,$$
(9d)

$$\begin{array}{l}n=1\\x_i > \xi_{th}, \end{array} \tag{9e}$$

$$u \in \{0, 1, \cdots, u_{\max}\}.$$
 (9f)

Constraints (9b) and (9c) ensure that both vehicle users and WiFi users meets their minimum thresholds ST_n and ST_v , respectively. Constraint (9d) ensures that each resource block (RB) is allocated to at most one vehicle, following OFDMA principles. Constraint (9e) imposes a minimum requirement on semantic similarity ξ_{th} . Constraint (9f) limits the average number of semantic symbols per word within u_{max} range.

III. PROPOSED SARADC ALGORITHM APPROACH

To address the above problem, we propose a SARADC algorithm utilizes Deep Reinforcement Learning (DRL), specifically Proximal Policy Optimization (PPO), to address the challenges posed by rapidly changing channel conditions in high-speed vehicular networks. By leveraging DRL, the algorithm can adapt to dynamic environments and complex state spaces, thus optimizing resource allocation, including semantic data transmission, thereby enhancing communication efficiency. The algorithm is expressed as follows:

At each time step t, the state of each vehicle agent within the network includes various parameters such as instant channel gain $h_{n,b,r}^t$, SINR $SINR_{n,b,r}^t$ when connected to *b*-th BS on *r*-th RB, HSSE of the vehicle $HSSE_{nn,b,r}^t$, the HSSE of the WiFi at the previous time $HSSE_{wn,b,r}^{t-1}$ and the previous interference $I_{n,b,r}^{t-1}$ from other vehicles to *b*-th BS on *r*-th RB. Thus, the state of each agent can be represented as

$$s_{n}^{t} = \left[h_{n,b,r}^{t}, SINR_{n,b,r}^{t}, HSSE_{n,n,b,r}^{t}, HSSE_{w_{n,b,r}^{t-1}}, I_{n,b,r}^{t-1}\right]$$
(10)

After observing the environment state s_n^t , each agent takes an action a_n^t according to a specific policy π . The actions include BS and RB allocation β_n^t , allocated transmission power p_n^t , the proportion of DC for vehicle connected to MiBs $\theta_1_n^t$ and the number of semantic symbols represented by each word μ_n^t . Thus, the action of each agent can be represented as

$$a_{n}^{t} = \left[\beta_{n}^{t}, p_{n}^{t}, T_{1n}^{t}, \mu_{n}^{t}\right].$$
(11)

After taking action a_n^t , each agent receives a reward r_n^t to evaluate its behavior, and the environment transits to the next state s_n^{t+1} . The system further penalizes the agent by including a penalty factor C if a RB is shared by multiple vehicles, and rewards the agent if the ST of WiFi exceeds a minimum threshold. The reward for each agent can be expressed as

$$r_n^t = \frac{\sum_{n=1}^{N} ST_n}{N\underline{ST_n}} \omega \left(ST_w, \underline{ST_w}\right) - C\psi \left(\beta_n^t\right).$$
(12)

Here, the function ω satisfies constraint (9c), and function ψ satisfies (9d), which are shown as below:

$$\omega(x,y) = \begin{cases} 1, x \ge y\\ 0, x < y \end{cases}$$
(13)

$$\psi\left(\beta_{v}^{t}\right) = \begin{cases} 1, \sum_{r=1}^{R} \beta_{v}^{t} > 1\\ 0, otherwise. \end{cases}$$
(14)

Meanwhile, the cumulative discounted reward is $R_n^t = \sum_{\tau=0}^{\infty} \gamma^{\tau} r_n^{t+\tau}$, where γ is the discount factor, which lies in the range (0, 1).

PPO algorithm consists of two neural networks: actor network and critic network. The actor network ,represented by parameters θ , determines the probability distribution of actions a_n^t given a state s_n^t . The critic network, represented by parameters θ^v , estimates the expected return given a state. Meanwhile, the old parameters of the actor and critic neural networks, denoted as θ_{old} and θ_{old}^v , respectively, are used to constrain the variation of the current policy. The agent interacts with the environment using the old policy network and collects a batch of experiences $(s_n^t, a_n^t, r_n^t, s_n^{t+1})$. Subsequently, these experiences are utilized to update the parameters θ and θ^v iteratively. During this process, the advantage function is computed and normalized based on the cumulative discounted

Algorithm 1: SARADC Algorithm solving P_0

Input: $\pi, \theta, \theta^v, \theta_{old}, \theta^v_{old}$ **Output:** the optimal policy parameter π^* Initialize parameters $\theta_{old} = \theta, \theta_{old}^v = \theta^v;$ Initialize replay experience buffer R; for episode from 1 to E_{max} do do for t from 1 to t_{\max} do do Receive observation state s_n^t ; Select action $a_n^t = \pi \left(a_n^t \left| s_n^t; \theta_{old} \right. \right)$ using the old policy; Observe reward r_n^t and next state s_n^{t+1} ; Store tuple $(s_n^t, a_n^{t'}, r_n^t, s_n^{t+1})$ in R; Compute advantages A_t according to (15) Normalize A_t for epochs from 1 to K_{\max} do do Randomly sample a batch of bs experiences from the replay buffer R; Compute actor loss according to (16)Compute critic loss according to (17)Compute total loss according to (18)Update actor-critic parameters θ and θ^v according to (19) and (20); Update old actor-critic parameters θ_{old} and θ_{old}^v with θ and θ^v .

reward while the value function estimation can be represented as

$$A_{t} = \left(R_{n}^{t} - V\left(s_{n}^{t}\right)\right) / A_{t\max}$$
(15)

Once a sufficient number of experiences is collected, a batch of experiences is randomly sampled from the replay experience buffer R. The log probability of actions $\pi(a_n^t | s_n^t; \theta)$ and state values $V(s_n^t; \theta^v)$ under the current policy are computed using θ and θ^v . Similarly, $\pi(a_n^t | s_n^t; \theta_{old})$ and $V(s_n^t; \theta_{old}^v)$ under the old policy are computed based on θ_{old} and θ_{old}^v . The loss of the actor network is

$$L^{actor}(\theta) = -\min\left(r_t(\theta)A_t, clip\left(r_t(\theta), 1-\varepsilon, 1+\varepsilon\right)A_t\right),$$
(16)

where $r_t(\theta) = \exp(\pi(a_n^t | s_n^t; \theta) - \pi(a_n^t | s_n^t; \theta_{old}))$ is the ratio of the log probability of new actions to that of old ones, and $clip(\cdot)$ limits the range of $r_t(\theta)A_t$ by clipping. The loss of the critic network is

$$L^{critic}(\theta^{v}) = 0.5 \left(R_n^t - V\left(s_n^t; \theta^{v} \right) \right)^2 \tag{17}$$

the total loss of the actor-critic network is

$$L^{total}(\theta, \theta^{v}) = L^{actor}(\theta) + L^{critic}(\theta^{v}) - c \times (entropy),$$
(18)

where $entropy = -\pi (a_n^t | s_n^t; \theta) \times \log (\pi (a_n^t | s_n^t; \theta))$ is entropy bonus, and c is entropy regularization coefficient.

The parameters θ and θ^v of the actor and critic networks are updated using gradient descent

$$\theta = \theta - \alpha \cdot \nabla \theta \cdot L^{total}(\theta, \theta^v) \tag{19}$$

$$\theta^{v} = \theta^{v} - \alpha \cdot \nabla \theta^{v} \cdot L^{total}(\theta, \theta^{v})$$
(20)

The pseudo code of training process for the proposed SARADC scheme is summarized in Algorithm 1.

IV. SIMULATION RESULTS

In this section, we will evaluate the performance of the proposed SARADC algorithm using Python 3.7 as the simulation tool. We consider a scenario with 5 vehicles in a square area spanning $1000 \times 1000 \ m^2$ with a fixed speed of 36 km/s. The channel condition is updated every 100ms with the path loss $128.1 + 37.6 \log (d)$, where d represents the distance between vehicles and BSs. The parameters are shown in Table I. To

TABLE I PARAMETERS OF SYSTEM MODEL.

Parameter	Value
Bandwidth of each RB	15 KHz
Numbers of RB	12
Time slot T	1 ms
Maximum rate of the WiFi R_w	12 Mb/s
Carrier frequency $f_{carrier}$	5 GHz
BS height $h_{vehicle}$	25 m and 1.5 m
Vehicle height h_{BS}	1.5 m
Maximum of semantic similarity ξ_{th}	0.9
Minimum of transformer factor u_{\max}	20 bits/word
V2I deviation of shadowing	8 dB
Noise power σ^2	-114 dBm

evaluate the performance of the proposed SARADC algorithm with flexible DC, we compare our algorithm against four baselines as below while selecting HSSE and ST as performance metrics:

- DDPG: SARA based on DDPG (deep deterministic policy gradient) RL with flexible DC.
- TD3: SARA based on TD3 (twin delayed deep deterministic policy gradient) RL with flexible DC.
- Fixed and random: SARA based on PPO RL with fixed DC and random DC.
- DDPG_NO_SC: A bits resource allocation algorithm based on DDPG RL with flexible DC, which does not consider semantic symbols.



Fig. 3. Reward during training process

Fig. 3 illustrates the reward of the training process. Our SARADC algorithm achieves faster convergence and higher stability, yielding superior cumulative rewards with equivalent training iterations. Compared to TD3 and DDPG algorithms, SARADC with PPO DRL ensures training stability by constraining policy changes. Additionally, PPO effectively balances exploration and exploitation, expediting convergence



6000 5000 1000 2000 0 5ARADC TD3 Policies DDPG

(c) The ST of vehicles and WiFi

Fig. 4. Variations of HSSE and ST under different algorithms

to optimal solutions for complex tasks like SARA and DC allocation.

Fig. 4(a) illustrates the HSSE of vehicles and WiFi users under different algorithms. Overall, WiFi users demonstrate higher HSSE than vehicles due to its higher bandwidth demands. Our SARADC algorithm excels in HSSE, surpassing TD3 and DDPG algorithms. The stability of PPO DRL enables SARADC to explore and exploit the environment effectively, resulting in a higher HSSE than TD3 and DDPG. Additionally, all algorithms incorporating semantic information outperform DDPG_NO_SC that is based on traditional communication. This is attributed to the fact that the meaningful and useroriented data conveyed by semantic information ensures more efficient resource utilization.

Fig. 4(b) illustrates the relationship between HSSE and μ . As μ increases, the HSSE of our proposed algorithm and other semantic-information-based algorithm remains constant. This resulted constancy arises from the fact that the system transmitting semantic information is independent of the transforming factor μ . DDPG_NO_SC algorithm gradually decrease as μ increases. Specifically, when μ is less than 8 bits/word (i.e., a word is encoded by less than 8 bits), our proposed algorithm outperforms traditional algorithms. This suggests that the choice of semantic source coding scheme is crucial.

Fig. 4(c) illustrates the total ST of vehicles and WiFi users under different algorithms and DC strategies. It can be seen that fixed or random DC strategies leads to lower total ST due to their lower flexibility and adaptability in meeting network demands. In contrast, our proposed algorithm consistently outperforms the other two algorithms, TD3 and DDPG, irrespective of the DC strategy employed. This is because our adoption of PPO DRL enables faster identification of optimal strategies.

V. CONCLUSION

This letter proposed a SARADC framework tailored for 5G-V2X HetNets using DRL with PPO. It incorporated semantic communication in high-speed vehicular networking, offering a more efficient and user-oriented approach by maximizing the HSSE for all vehicles to get the optimal resource allocation strategy. We compared our proposed algorithm with other four baseline methods. Our proposed SARADC can achieve excellent performance in terms of HSSE and ST, proving the effectiveness of the proposed scheme and semantic communication. The conclusions are summarized as follows:

- 1) Our proposed SARADC algorithm achieves higher HSSE with meaningful, user-oriented semantic data, ensuring efficient resource utilization.
- Fixed or random DC esult in lower total system throughput due to their lack of adaptability. In contrast, our flexible DC adapts to demand, boosting performance.
- When data was mapped to less than 8 bits using traditional encoding, the use of semantic information transmission showed noticeable advantages.

REFERENCES

- Y. Zhang, N. Cheng, Y. Dai, Z. Yin, W. Quan, Y. Zhou, and N. Zhang, "Resource scheduling for embb and urllc multiplexing in noma-based vanets: A dual time-scale approach," *IEEE Transactions on Vehicular Technology*, pp. 1–14, 2023.
- [2] Q. Wu, S. Wang, H. Ge, P. Fan, Q. Fan, and K. B. Letaief, "Delaysensitive task offloading in vehicular fog computing-assisted platoons," *IEEE Transactions on Network and Service Management*, vol. 21, no. 2, pp. 2012–2026, 2024.
- [3] Q. Wu, S. Wang, H. Ge, P. Fan, Q. Fan, and K. B. Letaief, "Delaysensitive task offloading in vehicular fog computing-assisted platoons," *IEEE Transactions on Network and Service Management*, vol. 21, no. 2, pp. 2012–2026, 2024.
- [4] Q. Wu, X. Wang, Q. Fan, P. Fan, C. Zhang, and Z. Li, "High stable and accurate vehicle selection scheme based on federated edge learning in vehicular networks," *China Communications*, vol. 20, no. 3, pp. 1–17, 2023.
- [5] J. Zhang, P. Fan, and K. B. Letaief, "Network coding for efficient multicast routing in wireless ad-hoc networks," *IEEE Transactions on Communications*, vol. 56, no. 4, pp. 598–607, 2008.
- [6] Z. Yao, J. Jiang, P. Fan, Z. Cao, and V. Li, "A neighbor-table-based multipath routing in ad hoc networks," in *The 57th IEEE Semiannual Vehicular Technology Conference, 2003. VTC 2003-Spring.*, vol. 3, 2003, pp. 1739–1743 vol.3.
- [7] K. Xiong, C. Chen, G. Qu, P. Fan, and K. B. Letaief, "Group cooperation with optimal resource allocation in wireless powered communication networks," *IEEE Transactions on Wireless Communications*, vol. 16, no. 6, pp. 3840–3853, 2017.
- [8] Q. Wu, Y. Zhao, Q. Fan, P. Fan, J. Wang, and C. Zhang, "Mobility-aware cooperative caching in vehicular edge computing based on asynchronous federated and deep reinforcement learning," *IEEE Journal of Selected Topics in Signal Processing*, vol. 17, no. 1, pp. 66–81, 2023.
- [9] F. Jing, W. Qiong, H. JunFeng, and F. Jing, "Optimal deployment of wireless mesh sensor networks based on delaunay triangulations," in 2010 International Conference on Information, Networking and Automation (ICINA), vol. 1, 2010, pp. V1–370–V1–374.
- [10] Q. Wu, W. Wang, P. Fan, Q. Fan, H. Zhu, and K. B. Letaief, "Cooperative edge caching based on elastic federated and multi-agent deep reinforcement learning in next-generation networks," *IEEE Transactions* on Network and Service Management, pp. 1–1, 2024.

- [11] Q. Wu, W. Wang, P. Fan, Q. Fan, H. Zhu, and K. B. Letaief, "Cooperative edge caching based on elastic federated and multi-agent deep reinforcement learning in next-generation networks," *IEEE Transactions* on Network and Service Management, pp. 1–1, 2024.
- [12] Q. Wu, W. Wang, P. Fan, Q. Fan, J. Wang, and K. B. Letaief, "Urllcawared resource allocation for heterogeneous vehicular edge computing," *IEEE Transactions on Vehicular Technology*, pp. 1–16, 2024.
- [13] T. Li, P. Fan, Z. Chen, and K. B. Letaief, "Optimum transmission policies for energy harvesting sensor networks powered by a mobile control center," *IEEE Transactions on Wireless Communications*, vol. 15, no. 9, pp. 6132–6145, 2016.
- [14] Q. Wu and J. Zheng, "Performance modeling and analysis of the adhoc mac protocol for vanets," in 2015 IEEE International Conference on Communications (ICC), 2015, pp. 3646–3652.
- [15] Q. Wu, S. Xia, Q. Fan, and Z. Li, "Performance analysis of ieee 802.11p for continuous backoff freezing in iov," *Electronics*, vol. 8, no. 12, p. 1404, 2019. [Online]. Available: https://www.mdpi.com/ 2079-9292/8/12/1404
- [16] Y. J. Zhang and K. Letaief, "Adaptive resource allocation and scheduling for multiuser packet-based ofdm networks," in 2004 IEEE International Conference on Communications (IEEE Cat. No.04CH37577), vol. 5, 2004, pp. 2949–2953 Vol.5.
- [17] X. Luo, H.-H. Chen, and Q. Guo, "Semantic communications: Overview, open issues, and future research directions," *IEEE Wireless Communications*, vol. 29, no. 1, pp. 210–219, 2022.
- [18] D. Long, Q. Wu, Q. Fan, P. Fan, Z. Li, and J. Fan, "A power allocation scheme for mimo-noma and d2d vehicular edge computing based on decentralized drl," *Sensors*, vol. 23, no. 7, p. 3449, 2023. [Online]. Available: https://www.mdpi.com/1424-8220/23/7/3449
- [19] W. Qiong, S. Shuai, W. Ziyang, F. Qiang, F. Pingyi, and Z. Cui, "Towards v2i age-aware fairness access: A dqn based intelligent vehicular node training and test method," *Chinese Journal of Electronics*, vol. 32, no. 6, pp. 1230–1244, 2023.
- [20] W. Chen, L. Dai, K. B. Letaief, and Z. Cao, "A unified cross-layer framework for resource allocation in cooperative networks," *IEEE Transactions on Wireless Communications*, vol. 7, no. 8, pp. 3000–3012, 2008.
- [21] E. Bourtsoulatze, D. Burth Kurka, and D. Gündüz, "Deep joint sourcechannel coding for wireless image transmission," *IEEE Transactions on Cognitive Communications and Networking*, vol. 5, no. 3, pp. 567–579, 2019.
- [22] Y. Wang, M. Chen, W. Saad, T. Luo, S. Cui, and H. V. Poor, "Performance optimization for semantic communications: An attention-based learning approach," in 2021 IEEE Global Communications Conference (GLOBECOM), 2021, pp. 1–6.
- [23] T. Han, Q. Yang, Z. Shi, S. He, and Z. Zhang, "Semantic-preserved communication system for highly efficient speech transmission," *IEEE Journal on Selected Areas in Communications*, vol. 41, no. 1, pp. 245–259, 2023.
- [24] N. Patriciello, S. Lagén, B. Bojović, and L. Giupponi, "Nr-u and ieee 802.11 technologies coexistence in unlicensed mmwave spectrum: Models and evaluation," *IEEE Access*, vol. 8, pp. 71 254–71 271, 2020.
- [25] M. Haghshenas and M. Magarini, "Nr-u and wi-fi coexistence enhancement exploiting multiple bandwidth parts assignment," in 2022 IEEE 19th Annual Consumer Communications & Networking Conference (CCNC), 2022, pp. 260–263.
- [26] B. Yin, H. Hu, B. Xi, Q. Liu, Y. Zheng, and Z. Zhang, "Joint radio resources allocation in the coexisting nr-u and wi-fi networks," in 2021 IEEE 32nd Annual International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), 2021, pp. 1532–1538.
- [27] L. Yan, Z. Qin, R. Zhang, Y. Li, and G. Y. Li, "Resource allocation for text semantic communications," *IEEE Wireless Communications Letters*, vol. 11, no. 7, pp. 1394–1398, 2022.
- [28] H. Xie, Z. Qin, G. Y. Li, and B.-H. Juang, "Deep learning enabled semantic communication systems," *IEEE Transactions on Signal Processing*, vol. 69, pp. 2663–2675, 2021.