# A tutorial on fairness in machine learning in healthcare

Jianhui Gao<sup>1</sup>, Benson Chou<sup>1</sup>, Zachary R. McCaw<sup>2</sup>, Hilary Thurston<sup>3</sup>,

Paul Varghese<sup>4</sup>, Chuan Hong<sup>5</sup>, and Jessica Gronsbell<sup>1,6,7</sup>

<sup>1</sup>Department of Statistical Sciences, University of Toronto, Toronto, ON, Canada

<sup>2</sup>Department of Biostatistics, Harvard T.H. Chan School of Public Health, Boston, MA, USA

<sup>3</sup>Department of Gender & Sexuality Studies, York University, Toronto, ON, Canada <sup>4</sup>Verily Life Sciences, Cambridge, MA, USA

<sup>5</sup>Department of Biostatistics, Duke University Raleigh, NC, USA

<sup>6</sup>Department of Family & Community Medicine, University of Toronto, Toronto, ON, Canada <sup>7</sup>Department of Computer Science, University of Toronto, Toronto, ON, Canada

### Correspondence to:

Jessica Gronsbell

Postal address: 700 University Ave, Toronto, ON, Canada, M5G 1Z5

Email: j.gronsbell@utoronto.ca.

Telephone number: 416-978-3452

Keywords: Fairness; Machine Learning; Predictive Models; Tutorial Word count: 3986/4000

## ABSTRACT

**OBJECTIVE:** Ensuring that machine learning (ML) algorithms are safe and effective within all patient groups, and do not disadvantage particular patients, is essential to clinical decision making and preventing the reinforcement of existing healthcare inequities. The objective of this tutorial is to introduce the medical informatics community to the common notions of fairness within ML, focusing on clinical applications and implementation in practice.

**TARGET AUDIENCE:** As gaps in fairness arise in a variety of healthcare applications, this tutorial is designed to provide an understanding of fairness, without assuming prior knowledge, to researchers and clinicians who make use of modern clinical data.

**SCOPE:** We describe the fundamental concepts and methods used to define fairness in ML, including an overview of why models in healthcare may be unfair, a summary and comparison of the metrics used to quantify fairness, and a discussion of some ongoing research. We illustrate some of the fairness methods introduced through a case study of mortality prediction in a publicly available electronic health record dataset. Finally, we provide a user-friendly R package for comprehensive group fairness evaluation, enabling researchers and clinicians to assess fairness in their own ML work.

## INTRODUCTION

There are myriad potential applications of machine learning (ML) in healthcare, including automated disease detection, computed-aided diagnosis, and personalized treatment planning [1]. However, there is substantial evidence that, without appropriate forethought and planning, ML models can exacerbate existing inequities in healthcare by making less accurate decisions for certain groups or individuals [2]. Within medical imaging, state of the art ML models used for disease diagnosis, risk prediction, and triage management are known to underperform within minority groups defined by protected attributes, including sex, race, and ethnicity [3–13]. A recent study found that deep learning models used to detect 14 common diseases from chest X-rays significantly under-diagnosed Hispanic females, potentially resulting in delays in treatment if deployed in practice [11]. In the same vein, ML models developed with electronic health record (EHR) and claims data exhibit similarly biased performance by under-performing in particular subgroups [14, 15]. In a landmark paper, researchers found that a widely-used commercial risk prediction model for identifying patients with complex health needs for high-risk care management performed significantly worse for Black patients relative to white patients [16]. Consequently, the model reduced the number of black patients designated for necessary extra care by over 50%.

As applications of ML in healthcare become commonplace, it is crucial to recognize, account for, and mitigate such disparities in model performance. Broadly, an ML model is said to be *fair* if it does not discriminate against an individual or group [17]. Concepts of fairness have been extensively studied across various disciplines, including social choice theory, game theory, economics, and law [18–24]. Building on these principles, the subfield of fairness within ML provides a framework for evaluating and mitigating bias throughout the model development and deployment process. Although fairness has been an extremely active area of research over the past decade, evaluating and implementing fairness within ML for healthcare is relatively nascent [25–27]. For instance, a recent systematic review of articles utilizing ML for EHR-based phenotyping found that only 5% of studies assessed fairness [28]. Similarly, a review of EHR-based prediction models found that most studies only investigate the overall performance of ML models and do not interrogate potential biases [29]. Beyond EHR applications, several scoping reviews of clinical ML models found that the adoption of fairness remains inconsistent, which can be partially attributed to a knowledge gap between ML and clinical researchers [27, 30, 31]. Moreover, more than two dozen definitions of fairness have been proposed, making it a particularly challenging domain to navigate.

To increase familiarity with this important topic within medical informatics, we provide a didactic introduction to the fundamental concepts and methods of fairness within ML. This tutorial is designed to serve as a starting point for informaticians and clinical researchers exploring the rich and nuanced fairness literature and is complementary to book chapters, workshops, articles, and software that are references on the topic. Supplementary Tables S1 and S2 provide a detailed comparison of our tutorial with existing literature and software. In contrast to other references, we focus specifically on healthcare applications and include a fully reproducible case study of mortality prediction on publicly available EHR data from the Medical Information Mart for Intensive Care (MIMIC) clinical database [32]. We also introduce a user-friendly R package that offers a full suite of methods for group fairness evaluation, some of which are not currently available in existing software.

We begin our tutorial with a discussion of why ML models can be unfair by introducing biases that can arise throughout the model development process using examples from the literature. We then provide a formal introduction to the most common fairness framework, group fairness, and illustrate how many group fairness definitions are incompatible, meaning that they cannot be simultaneously satisfied. We also present a case study on mortality prediction using our group fairness R package to reinforce these concepts. We then introduce individual and causal fairness and close with a discussion of existing approaches and some ongoing research.

### WHY ML MODELS ARE UNFAIR

ML models are unfair due to *biases* in the data, in the model, and/or in the deployment of the model (Figure 1) [25, 33–39]. The data used in healthcare applications most often measures and categorizes people and therefore encodes societal structures, injustices, and stereotypes, such as gender, racial, and age bias [40, 41]. In addition to societal bias, data can also fail to represent the population of interest due the sampling method, time of collection, or data quality issues (e.g., missing, mismeasured, or not enough data). In the fairness literature, data with these undesirable properties are informally referred to as "biased" [17, 42]. Choices made during model training and evaluation can also incorporate and amplify bias in the data, such as selecting an inappropriate outcome, model, or metric(s) and data used for evaluation. During deployment, bias can be introduced when users selectively disregard or overly trust a model's outputs, which can further reinforce existing societal bias. Table 1 details some common sources of bias together with an example from the healthcare literature. A more comprehensive review of causes of unfairness and applications outside of healthcare can be found in [41] and [34].

It is important to note bias should be a primary consideration throughout the ML pipeline, from problem formulation to model deployment [43]. Building on existing AI reporting guidelines, a bias evaluation checklist has recently been proposed to enable practitioners to systematically and holistically address bias in clinical predictive models [25, 44, 45]. The fairness criteria we introduce in the subsequent section play an important role in this process. They are typically integrated directly into model training to ensure fairness or used as evaluative metrics to measure disparities after the model has been trained [46].



Figure 1: Sources of bias in ML. Unfairness arises from bias in the process of generating data, modeling data, and deploying the model. This figure is adapted from [47] and [48].

## WHAT IT MEANS FOR A MODEL TO BE FAIR

In spite of the numerous fairness definitions, existing criteria primarily fall into three categories: *group fairness, individual fairness,* and *causal fairness.* Group fairness is a popular framework which includes criteria that deem a model fair if its predictions are

(a) Bias in the data				
Type of Bias	Definition	Example		
Historical Bias	The data reflects long-standing so-	Clinical word embeddings trained on large corpora of text,		
	cietal disparities encoded within the	such as clinical notes from healthcare systems, reflect biases		
	data over time.	about ethnic minorities [49].		
Selection Bias	The data is not representative of the	Data in volunteer-based biobanks does not reflect the general		
	population of interest.	population as participation rates are higher among women,		
		older age groups, and individuals with higher socioeconomic		
		status. [50].		
Measurement	The data contains variables that are	Gender identity is often recorded in EHRs without provider		
Bias	collected or measured inaccurately.	education and therefore does not accurately represent an in-		
		dividual's identity [51].		
Temporal Bias	The data captures a specific time pe-	Pediatric mental health visits were lower than expected for		
	riod that may not reflect current or	individuals with lower socioeconomic status during the first		
	future conditions.	year of the COVID-19 pandemic [52].		
Minority Bias	The data lacks adequate representa-	Most of the data for genetic studies is from European ances-		
	tion from the minority group for the	try populations [53].		
	model to accurately learn.			
Missing Data	The data has variables that are incom-	Patients from low-income backgrounds have higher rates of		
Bias	pletely measured.	missing medical measurements, which is often due to in-		
		equities in access to healthcare [54].		

(a) Bias in the data

(b) Bias in the model

Type of Bias	Definition	Example
Label Bias	An imperfect proxy is selected to train	Healthcare cost was used as a proxy for healthcare need in
	a model instead of the outcome of in-	a commercial algorithm used to identify patients for high-
	terest.	risk care management programs. The algorithm significantly
		under-identified black patients as less money is spent on
		black patients relative to similarly healthy white patients
		[16].
Algorithmic	Properties of a model and/or its train-	Differentially private prediction models for mortality per-
Bias	ing algorithm create or amplify bias in	formed poorly for minority groups [55].
	the data.	
Evaluation	An inappropriate choice of benchmark	EuroSCORE, a widely used cardiac surgery risk evaluation
Bias	data or metrics are used for evalua-	model, was only evaluated on European patients and exhib-
	tion.	ited decreased performance in other populations [56].

### (c) Bias in deployment

Type of Bias	Definition	Example
1 Jpc of Blas	Beimition	
Automation	Humans overly trust model outputs,	A computer-aided detection system that scans mammograms
Bias	sometimes even against their own	and marks suspicious areas of potential cancer features had
	knowledge.	lower sensitivity for women aged 40–49 compared to older age
		groups. A clinician using this system can disproportionately
		miss cancers for this age group [57].
Dismissal Bias	Humans ignore model recommenda-	If the computer-aided detection system also has a lower pos-
	tions, often due to frequent false	itive predictive value for women aged 40–49, then clinicians
	alerts.	may disregard its recommendations, as they are more likely
		to be false positives [58].

Table 1: Common biases that arise in machine learning (ML) applications in healthcare.

similarly accurate or calibrated across a predefined set of groups. These groups are most often defined by a protected attribute(s) such as age or race<sup>1</sup> [34]. Common protected attributes used in the healthcare literature are summarized in Table 2. In contrast, individual fairness requires that the model provide similar predictions to similar individuals based on user-defined similarity metrics [24]. Causal fairness criteria rely on causal models to link observed disparities in model performance to their underlying cause [61]. Group fairness criteria are referred to as "oblivious" as they equate fairness with parities based solely on the distribution of the data, while individual and causal fairness criteria require additional context in the form of the similarity metrics and causal models, respectively [47, 62]. We therefore only illustrate group fairness in our case study and refer readers to several excellent resources for individual and causal fairness. As we will soon see, many fairness, including some different types of group, individual, and causal fairness and their incompatibilities, is presented in Figure 2.

Attribute	Availability in MIMIC-II	Examples
Age	$\checkmark$	[9, 63-65]
Disability		[63]
Marital Status	$\checkmark$	[66]
National Origin		[65]
Race	$\checkmark$	[9, 25, 33, 63-67]
Sex	$\checkmark$	[9, 63, 65-67]
Socioeconomic Status	$\checkmark$	[9, 25, 33, 64-66]

Table 2: Commonly used protected attributes in ML in healthcare. Examples of studies that evaluate fairness with respect to each protected attribute and the availability of each attribute in the the MIMIC-II database used in our case study.

<sup>&</sup>lt;sup>1</sup>Sensitive attribute and protected attribute are used interchangeably [59]. Fairness is also evaluated across groups defined by social determinants of health (e.g., income and education) [60].



Figure 2: **Taxonomy of fairness criteria.** Fairness criteria primarily fall into three categories: group fairness, individual fairness, and causal fairness. In contrast to group fairness criteria which can be inferred from the distribution of the data, individual and causal require additional considerations based on the context. Many fairness criteria cannot be simultaneously satisfied and incompatibilities are depicted with a red X.

### NOTATION

We use a small amount of notation to introduce mathematical definitions of various criteria that complement our discussion in the main text. We denote the outcome of interest as Y, the features used for model training as  $\mathbf{X}^2$ , and the categorical variable for the protected attribute as A.  $\mathbf{X}$  may or may not contain A and we discuss this issue when we introduce individual fairness. We let  $S = \hat{f}(\mathbf{X})$  be the output from the ML model, where  $\hat{f}$  is learned from a set of training data. For example, when Y is continuous, S is simply the predicted value of Y. In the context of classification, Y is a binary label for membership in the positive or negative class and S is the predicted probability of being in the positive class, referred to as the risk score. The final prediction, D, is positive if S exceeds a pre-determined classification threshold and negative otherwise.

<sup>&</sup>lt;sup>2</sup>Note that **X** does not have to be a vector; it could be an image, text, tensor, or any other type of data.

### **GROUP FAIRNESS**

Group fairness criteria require ML models to perform similarly across groups of interest and are the most popular fairness framework [68]. The criteria primarily fall into three categories: *independence, separation*, and *sufficiency* [17, 69]. We provide mathematical definitions of various criteria, their interpretation in the context of a healthcare example, and include additional metrics that do not fall within the three categories in Table 3. In the following discussion of group fairness, we focus on classification as it is most widely used and well-studied [34, 47, 70]. Supplementary Section 2.1 reviews measures of discrimination and calibration as many group fairness definitions for classification are based on them [34]. Additional approaches for settings with continuous outcomes, continuous and categorical protected attributes that define more than two groups, and multiple protected attributes (i.e., subgroup fairness) are discussed in Supplementary Sections 2.2 - 2.5.

### INDEPENDENCE

Under independence, an ML model is said to be fair if its predictions do not depend on the protected attribute (i.e.,  $D \perp A^3$ ). Statistical (or demographic) parity is a common measure of independence that requires that the model classify individuals into the positive class at the same rate in each group [24, 71]. Conditional statistical parity relaxes this concept by requiring the rate of positive classifications to be the same within more granular groups defined by the protected attribute and other relevant factors. Independence-based metrics are infrequently used in healthcare settings as the prevalence of clinical outcomes often differs across groups (e.g., heart disease in males and females). Moreover, enforcing independence may prevent a model from learning a possible association between the protected attribute and the outcome, which can decrease the overall performance of the model for the entire population [72, 73].

 $<sup>^{3} \</sup>bot\!\!\!\bot$  denotes statistical independence.

#### SEPARATION

Separation requires that the prediction does not depend on the protected attribute within the positive and negative classes (i.e.,  $D \perp A \mid Y$ ). This implies that, among individuals in the positive (or negative) class, the rate of making a positive (or negative) prediction is consistent across groups. Common separation-based metrics therefore aim to equalize error rates across the groups, including the false negative rate (known as equality of opportunity), false positive rate (known as *predictive equality*), or both (known as *equalized*) odds). These metrics have been widely used in clinical settings as misclassified predictions can have severe consequences in practice. For instance, a recent study evaluated equality of opportunity in the context of chest X-ray diagnostics, where a false negative corresponded to incorrectly identifying a patient as not having "no finding" on their X-ray [11]. Stateof-the-art computer vision models were found to have higher false negative rates in several intersectional under-served subpopulations, such as Hispanic female patients. There are also situations where prioritizing equalized odds is appropriate [62]. In the context of rapid screening tools for COVID-19 in emergency departments, a high false negative rate can lead to insufficient monitoring of COVID-19 while a high false positive rate can result in unnecessary additional testing [74]. Additional separation-based metrics are detailed in Table 3, including balance for the positive class and balance for the negative class [75].

### SUFFICIENCY

Sufficiency aims to equalize error rates among individuals with similar predictions [70]. Formally, sufficiency requires that the label does not depend on the protected attribute given the prediction ( i.e.,  $Y \perp A \mid D$ ). The prediction is therefore "sufficient" for predicting the outcome in the sense that it subsumes the protected attributes [17]. Common sufficiency-based metrics focus on equalizing the positive predictive value (known as *predictive parity*), both the positive and negative predictive value (known as *conditional use accuracy equality*), and calibration (known as *well-calibration*)[42, 69, 75, 76]. Within healthcare, ML models that fail to meet sufficiency criteria have led to inequitable resource allocation. For example, in models predicting in-hospital patient deterioration, achieving predictive parity ensures that the allocation of intensive care unit beds is based solely on medical need rather than protected attributes so that care is provided to those most in need [77]. In terms of calibration-based metrics, a commercial algorithm to enroll patients into a high-risk care management program was shown to violate well-calibration. At equivalent risk scores, Black patients were in significantly poorer health than white patients and therefore had to be sicker for enrollment into the program [16].

### INCOMPATIBILITIES

Independence, sufficiency, and separation provide different perspectives on what it means for a model to be fair. Except under highly restrictive conditions, it is not possible for an algorithm to fulfill all criteria at the same time [42, 62, 78]. As such, it is important for researchers to choose which group fairness considerations are most relevant to the specific context.

More specifically, the following pairs are *incompatible* in the sense that they cannot generally be simultaneously satisfied: independence and sufficiency, independence and separation, and separation and sufficiency. A basic requirement for any of these pairs to be satisfied is that the outcome and the protected attribute are marginally independent (i.e.,  $Y \perp A$ ). In classification problems, this implies that the probability of being in the positive class is the same across groups, which can be violated in many clinical applications (e.g., disease prevalence varies by age). Our case-study in the next section reinforces these incompatibilities and additional mathematical details are provided in Supplementary Section 3.

Metric	Definition	Interpretation	Relax- ation				
Independence $(D \perp A)$							
Statistical Parity	$P(D = 1 \mid A = a_0) = P(D = 1 \mid A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	In all-cause mortality prediction, the probability of the model predicting mortality is the same for males and fe- males.					
Conditional Statistical Parity	$P(D = 1   \mathbf{Z}, A = a_0) = P(D = 1   \mathbf{Z}, A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	In all-cause mortality prediction, the probability of the model predicting mortality is the same for males and fe- males after adjusting for age and pre-existing conditions.	~				
Separation (I	$D \perp\!\!\!\perp A \mid Y)$						
Equalized Odds	$\begin{array}{l} P(D=1 \mid Y=0, A=a_0) = P(D=1 \mid Y=0, A=a_1)  \text{and} \\ P(D=0 \mid Y=1, A=a_0) = P(D=0 \mid Y=1, A=a_1)  \forall a_0, a_1 \in \mathcal{A} \end{array}$	In predicting asthma exacerbation in children, the rates of false positives (children without exacerbation incor- rectly identified as having exacerbation) and false nega- tives (children with exacerbation incorrectly identified as not having exacerbation) are the same for children from low and high socio-economic classes [79].					
Predictive Equality	$\begin{array}{llllllllllllllllllllllllllllllllllll$	A model predicting cardiovascular disease (CVD) diag- noses CVD in males and females without CVD at the same rate [80].	~				
Equal Op- portunity	$P(D = 0   Y = 1, A = a_0) = P(D = 0   Y = 1, A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	A model predicting a suspicious finding from a chest X- rays misses findings in males and females at the same rate [81].	~				
Balance for Positive Class	$\mathbb{E}(S \mid Y = 1, A = a_0) = \mathbb{E}(S \mid Y = 1, A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	In a model used to screen for lung cancer from chest X- rays, the average predicted score of people with lung can- cer is equal for males and females [81].	~				
Balance for Negative Class	$\mathbb{E}(S \mid Y = 0, A = a_0) = \mathbb{E}(S \mid Y = 0, A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	In a model used to screen for lung cancer from chest X- rays, the average risk scores among males and females without lung cancer are equal [81].	~				
Sufficiency (Y	$' \perp A \mid D)$						
Conditional Use Ac- curacy Equality	$\begin{array}{l} P(Y=1 \mid D=1, A=a_0) = P(Y=1 \mid D=1, A=a_1) \text{ and } \\ P(Y=0 \mid D=0, A=a_0) = P(Y=0 \mid D=0, A=a_1)  \forall a_0, a_1 \in \mathcal{A} \end{array}$	In predicting hospital readmission, the probability of be- ing readmitted given the model makes that prediction and the probability of not being readmitted given the model makes that prediction is the same for Black and white patients [82].					
Predictive Parity	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	In predicting hospital readmission, the probability of be- ing readmitted given the model makes that prediction is the same for Black and white patients [82].	V				
Well Cali- bration	$P(Y = 1 \mid S = s, A = a) = s  \forall a \in \mathcal{A}, s \in [0, 1]$	In a model used to predict in-hospital mortality, the pre- dicted event rates match the observed event rates at all values of the risk score for males and females [83].					
Test Fair- ness	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	In a model used to predict in-hospital mortality, the pre- dicted event rates are the same for males and females at all values of the risk score [83].	~				
Other							
Brier Score Parity	$\mathbb{E}[(Y-S)^2 \mid A = a_0] = \mathbb{E}[(Y-S)^2 \mid A = a_1],  \forall a_0, a_1 \in \mathcal{A}$	In a model used to enroll patients into high-risk care man- agement programs, the mean squared error between the risk score and the label is the same for Black and White patients [16].					
Overall Accuracy Equality	$P(D = Y \mid A = a_0) = P(D = Y \mid A = a_1)  \forall a_0, a_1 \in \mathcal{A}$	In a model used to screen for lung cancer from chest X- rays, the probability of a correct classification (i.e., cor- rectly classifying a patient as having or not having lung cancer) is the same for males and females [81].					
Treatment Equality	$\frac{\#\{D=0,Y=1,A=a_0\}}{\#\{D=1,Y=0,A=a_0\}} = \frac{\#\{D=0,Y=1,A=a_1\}}{\#\{D=1,Y=0,A=a_1\}}  \forall a_0, a_1 \in \mathcal{A}$	In a model used to screen for lung cancer from chest X- rays, the ratio of the false negatives and false positives is the same for both males and females [81].					

Table 3: Common group fairness criteria. Mathematical definitions of group fairness criteria, an interpretation in the context of an example from the literature, and an indication of whether the criterion is a relaxation of independence, separation, or sufficiency. Symbols: # = number of, P = probability, E = expected value. Notations: Y: outcome,  $\mathbf{X}$ : features used for model training, A: protected attribute that takes value in the set  $\mathcal{A}$ , S: risk score, D: final prediction based on thresholding S,  $\mathbf{Z}$ : additional set of features.

#### CASE STUDY

As group fairness metrics are often used to evaluate bias after model training, we illustrate their application in a case study using a publicly available dataset on 1,776 ICU patients from MIMIC-II [32, 84]. We focus on predicting 28-day mortality and evaluate disparities in model performance across the protected attribute of sex which is recorded as either male or female.<sup>4</sup> Our purpose is to highlight the capabilities of our R package and reinforce the concepts of independence, separation, and sufficiency. We therefore evaluate all metrics rather than selecting one for the problem at hand. Table 4 shows point estimates and 95% confidence intervals (CIs) for both the difference and ratio of various metrics, which are easily obtained from our package. Details of the data processing and modeling are in Supplementary Section 4 and the methods used for constructing the 95% CIs are in Supplementary Section 5. All analyses can be replicated using the code and tutorial at: https://jianhuig.github.io/FairnessTutorial/index.html.

The group fairness incompatibilities are illustrated in our case study. Independence is likely violated as the estimated mortality rates are for males and females are different (14% vs. 19%, respectively). Our model only satisfies sufficiency criteria, but neither independence nor separation criteria. The measures of statistical parity indicate that the model predicts a significantly higher mortality rate for females, even after conditioning on age. Given that the estimated mortality rates are different in females and males, strictly enforcing independence may not be advisable. With respect to separation, we observe that equal opportunity is not satisfied. Practically, these disparities could lead to higher rates of undetected mortality risk among male individuals and insufficient care. On the other hand, the sufficiency criterion of predictive parity is satisfied. Lastly, three additional metrics from Table 3 that do not fall within the three aforementioned categories that

<sup>&</sup>lt;sup>4</sup>MIMIC-IV is the most current release of data, but publicly available data exists for MIMIC-II. We also acknowledge that sex is not binary, but recorded this way in the MIMIC-II data [85].

measure calibration and	/or	discrin	nination	$\operatorname{are}$	satisfied.
-------------------------	-----	---------	----------	----------------------	------------

Fairness Metric	Female	Male	Difference	95% CI for the difference	Ratio	95% CI for the ratio
Independence						
Statistical Parity	17%	8%	9%	[5%, 13%]	2.12	[1.49, 3.04]
Conditional Statistical Parity (Age $\geq 60$ )	34%	21%	13%	[5%, 21%]	1.62	[1.17, 2.23]
Separation						
Equal Opportunity	38%	62%	-24%	[-39%, -9%]	0.61	[0.44, 0.86]
Predictive Equality	8%	3%	5%	[2%, 8%]	2.67	[1.39, 5.12]
Balance for Positive Class	46%	37%	9%	[4%, 14%]	1.24	[1.09, 1.42]
Balance for Negative Class	15%	10%	5%	[3%, 7%]	1.5	[1.28, 1.75]
Sufficiency	Sufficiency					
Predictive Parity	62%	66%	-4%	[-21%, 13%]	0.94	[0.72, 1.23]
Other						
Brier Score Parity	9%	8%	1%	[-1%, 3%]	1.12	[0.89, 1.42]
Overall Accuracy Equality	87%	88%	-1%	[-5%, 3%]	0.99	[0.94, 1.04]
Treatment Equality	5.11	13.6	-8.49	[-32.96, 15.98]	0.38	[0.1, 1.34]

Table 4: Group fairness evaluation in the MIMIC-II mortality case study. Each metric quantifies disparities in model performance across males and females. Differences and ratios are presented alongside 95% confidence intervals (CIs).

### INDIVIDUAL FAIRNESS

In contrast to group fairness criteria that target the average performance of a model across groups, individual fairness ensures that "any two individuals who are similar with respect to a particular task should be classified similarly" [24]. One of the first works on individual fairness, *fairness through awareness* (FTA), formalized the notion of similarity by defining metrics that measure the distance between individuals and their predictions. Roughly speaking, fairness is achieved if the distance between the prediction for any two individuals is at most the distance between them. The choice of distance metric for the predictions depends on the type of outcome under study. For example, the Euclidean distance is used for logit transformed predicted probabilities in classification while the absolute difference of the hazard function has been used for survival analysis [86, 87]. However, the metric used to measure the similarity between individuals has been a focus of ongoing research as it encodes exactly how individuals are similar, which relies on an "awareness" of the context. In the original FTA paper, the authors suggest leaving the choice of metric to domain experts. As there is currently no agreed upon standard, various strategies have been proposed to learn the metric from available data [88–90]. A recent scoping review on individual fairness in healthcare provides a comprehensive list of individual fairness methods and corresponding software [31].

It is important to note that FTA is a counter approach to fairness through unawareness (FTU), which is intended to be a catch all solution to prevent bias by not explicitly including protected attributes into modeling [91]. However, removing the protected attributes from a model warrants careful consideration. First, protected attributes may serve as critical predictors for the outcome of interest, such as age in sepsis or cardiovascular disease prediction and race in cancer screening models [92–94]. Excluding these predictors can diminish the overall predictive accuracy and impact all individuals adversely or even lead to bias against the majority group. Second, protected attributes are often highly correlated with non-protected attributes. Simply removing protected attributes from the model does not prevent the model from inferring them from other attributes. FTU is therefore not always ethical or achievable [95]. Lastly, individual fairness is motivated by an inherent weakness in group fairness criteria that only consider average model performance within groups. That is, there are situations in which group fairness can be satisfied, but individuals within a group can be discriminated against. The incompatibilities among individual and group fairness have been examined in [70, 96–98]. For example, when group-specific prevalences of an outcome differ, the predictions must be adjusted to achieve statistical parity and obtain an equal rate of positive predictions across the groups. This can cause individuals with similar characteristics to receive different predictions based solely on their protected attributes, which contradicts the principle of individual fairness.

### CAUSAL FAIRNESS

We conclude with a brief overview of causal fairness, a topic that has gained popularity in recent years and itself worth a tutorial in the context of healthcare. As the name suggests,

causal fairness criteria evaluate the causal relationship between a protected attribute and a model's prediction rather than a performance measure or distance metric as in group and individual fairness [30]. A deep understanding of causal fairness requires knowledge of causal inference and we refer readers to several general and fairness-focused reviews on the topic [99–105]. We introduce one way of incorporating causality into what it means to be fair based on counterfactuals, which are simply "what-if" statements [99, 100]. In the context of fairness, the counterfactual can be the unobserved prediction that would have happened if the protected attribute had been different [91, 102, 106]. One of the first counterfactual-based fairness criteria, simply called (individual) *counterfactual fairness*, deems a model fair if the observed and counterfactual predictions align for an individual when their protected attribute is changed, given all other variables are held constant [91].

To better explain this concept, we briefly introduce directed acyclic graphs (DAGs). DAGs consist of nodes that represent variables and edges that connect them to illustrate their causal relationships and are used to formulate many causal fairness criteria [99]. For purposes of illustration, consider an over-simplified view of the world in predicting length of stay in the hospital. The DAG in Figure 3 illustrates that the prediction is directly related to previous diagnoses, age, and prescriptions, yet race could indirectly influence the prediction through its impact on access to healthcare, which in turn influences historical diagnoses [107]. When predicting length of stay in the hospital, counterfactual fairness is satisfied if, for example, the predicted length of stay for a black person is the same prediction they would have received if they were counterfactually born a white person, given all other variables are held constant. However, counterfactual fairness can generally not be quantified from observed data [91, 102, 108].

Other quantities from the causal inference literature have since been proposed, such as counterfactual parity which measures a population-level, rather than a individual-level, causal effect of the protected attribute on the prediction [47, 109, 110]. Conditional counterfactual fairness is a stronger criteria that considers the total effect of the protected attribute on the prediction conditional on a set of relevant observed variables [91]. In our length of stay prediction example, this means that for each group of individuals with identical characteristics (e.g., those with the same historical diagnosis, age and prescriptions), the length of stay in the hospital does not change if their race were counterfactually altered. These definitions, as well as extensions of the previously introduced group and individual fairness measures, are formally introduced in Supplementary Section 6. Further work on causal fairness, such as path-specific and interventional fairness, are detailed in [108, 111–115].



Figure 3: Directed acyclic graph (DAG) for predicting length of stay in the hospital. The DAG illustrates the relationships among various factors influencing the predicted length of hospital stay. Historical diagnoses, age, and prescriptions have a direct influence on predicted length of stay. Race indirectly affects the prediction through access to care, which in turn influences historical diagnoses.

## DISCUSSION

In this tutorial, we introduced three primary notions of fairness: group, individual, and causal fairness. We discussed incompatibilities among different fairness definitions and also illustrated group fairness with real-world EHR data using our R package. We close by commenting on some ongoing research relevant to the topics introduced in this tutorial.

### **BIAS MITIGATION**

While this paper focuses on how to define fairness, strategies for mitigating bias within ML applications are an equally active area of research. A recent systematic review presents various bias mitigation strategies and their use in practice [116]. A necessary step in any bias mitigation strategy is to select the fairness definition that the mitigation strategy will attempt to enforce. Group fairness metrics are the most common targets, though alternative strategies have recently been proposed [117]. Broadly, bias mitigation can be performed by de-biasing the training data (pre-processing), during model training (inprocessing), and after model training (post-processing). Pre-processing techniques include resampling or reweighting samples to correct imbalances among groups. One approach to in-processing is to include additional regularization terms to penalize a model's deviation from a pre-specified fairness metric. In post-processing, for example, a technique to achieve equalized odds is to set distinct decision thresholds for different groups [62]. However, a practical consideration in any bias mitigation strategy is the well-known tradeoff between achieving fairness and high overall accuracy and calibration [48, 118, 119]. Strategies for bias mitigation throughout the ML pipeline have recently been discussed in [43].

### **REVISITING THE INCOMPATIBILITIES**

The group fairness incompatibilities may be discouraging for practitioners aiming to achieve fairness. For example, the theorems show that it is not possible to equalize the group-specific true positive rates and positive predictive values when predicting an outcome that has different prevalence across groups of interest. A relaxed notion of fairness, known as *approximate fairness* or  $\epsilon$ -fairness, allows for a small margin of error in

the group fairness metrics presented in Table 3. [120, 121]. That is, rather than enforcing exact equality between metrics, approximate fairness deems a model fair if the difference between metrics does not exceed some small value,  $\epsilon$ . [121] demonstrates that it is possible for an model to satisfy approximate fairness across the false negative rate, false positive rate, and positive predictive value, even when moderate prevalence differences between groups exist. This finding offers a promising pathway for applying fairness in real-world settings where exact parity is often unachievable.

### MISSING DATA

Missing data is a critical challenge to fairness evaluation in healthcare applications. Traditional imputation methods used to address missingness in features have been observed to worsen gaps in fairness and fairness-aware imputation strategies have been recently proposed [122, 123]. Missingness in the outcome as well as the protected attribute can also occur, which brings challenges to both model training and evaluation. For example, in many EHR and medical imaging applications, the outcome of interest is only available for a small subset of data as it is obtained from time-consuming and expensive annotation. Semi-supervised strategies for fair model training and fairness evaluation are an active area of research [124–127].

In many settings, the protected attribute of interest may also be unavailable or measured incorrectly. Note that some protected attributes are missing from Table 2, such as religion, gender identity, and sexual orientation, which are rarely available in healthcare data. For instance, most healthcare organizations have yet to integrate sexual orientation data collection into routine care due to the absence of standardized collection practices, the inability of EHR systems to capture structured data, and the socio-cultural challenges of self-reporting [51, 128, 129]. Advances in fairness have therefore largely omitted sexual orientation, which underscores the necessity of future research to acknowledge "a

multiplicity of considerations, from privacy preservation, context sensitivity and process fairness, to an awareness of sociotechnical impact and the increasingly important role of inclusive and participatory research processes" [130].

## CONCLUSION

Fairness is a framework to prevent the reinforcement or exacerbation of existing inequities when integrating ML models in healthcare. We provide an introduction to the landscape of fairness, including how bias can arise and a summary and comparison of existing metrics. We also introduced a group fairness R package for researchers to apply in their own problems.

## FUNDING

J. Gronsbell is grateful for support of an NSERC Discovery Grant (RGPIN-2021-03734) and a University of Toronto Data Science Institute Seed Funding for Methodologists Grant.

## AUTHOR CONTRIBUTIONS

JeG conceived and supervised the study. JeG, JiG, and BC drafted the manuscript. JiG and BC conducted experiments on simulated and real clinical data and developed the R package. PV provided clinical oversight, ZM and CH provided additional guidance on ML, and HT provided ethical oversight. All authors provided valuable feedback on the manuscript.

## References

- Rajpurkar, P., Chen, E., Banerjee, O. & Topol, E. J. AI in health and medicine. Nature medicine 28, 31–38 (2022).
- 2. Grote, T. & Keeling, G. Enabling Fairness in Healthcare Through Machine Learning. *Ethics and Information Technology* **24**, 39 (2022).
- 3. Rajpurkar, P. et al. CheXNet: Radiologist-Level Pneumonia Detection on Chest X-Rays with Deep Learning arXiv:1711.05225 [cs, stat]. Dec. 2017.
- Roest, C., Fransen, S. J., Kwee, T. C. & Yakar, D. Comparative Performance of Deep Learning and Radiologists for the Diagnosis and Localization of Clinically Significant Prostate Cancer at MRI: A Systematic Review. eng. *Life (Basel, Switzerland)* 12, 1490 (Sept. 2022).
- 5. Lin, M. et al. Evaluate underdiagnosis and overdiagnosis bias of deep learning model on primary open-angle glaucoma diagnosis in under-served populations. eng. AMIA Joint Summits on Translational Science proceedings. AMIA Joint Summits on Translational Science 2023, 370–377 (2023).
- 6. Ting, D. S. W. *et al.* Development and Validation of a Deep Learning System for Diabetic Retinopathy and Related Eye Diseases Using Retinal Images From Multiethnic Populations With Diabetes. eng. *JAMA* **318**, 2211–2223 (Dec. 2017).
- Liu, X. et al. A comparison of deep learning performance against health-care professionals in detecting diseases from medical imaging: a systematic review and metaanalysis. English. The Lancet Digital Health 1. Publisher: Elsevier, e271–e297 (Oct. 2019).
- 8. Lee, H. *et al.* Machine Learning Approach to Identify Stroke Within 4.5 Hours. eng. *Stroke* **51**, 860–866 (Mar. 2020).
- Seyyed-Kalantari, L., Liu, G., McDermott, M., Chen, I. Y. & Ghassemi, M. CheXclusion: Fairness gaps in deep chest X-ray classifiers arXiv:2003.00827 [cs, eess, stat]. Oct. 2020.
- Larrazabal, A. J., Nieto, N., Peterson, V., Milone, D. H. & Ferrante, E. Gender imbalance in medical imaging datasets produces biased classifiers for computeraided diagnosis. eng. *Proceedings of the National Academy of Sciences of the United States of America* 117, 12592–12594 (June 2020).
- Seyyed-Kalantari, L., Zhang, H., McDermott, M. B. A., Chen, I. Y. & Ghassemi, M. Underdiagnosis bias of artificial intelligence algorithms applied to chest radiographs in under-served patient populations. en. *Nature Medicine* 27. Number: 12 Publisher: Nature Publishing Group, 2176–2182 (Dec. 2021).

- 12. Puyol-Antón, E. *et al.* Fairness in Cardiac Magnetic Resonance Imaging: Assessing Sex and Racial Bias in Deep Learning-Based Segmentation. *Frontiers in Cardio*vascular Medicine **9** (2022).
- 13. Bressem, K. K. *et al.* Deep learning for detection of radiographic sacroiliitis: achieving expert-level performance. en. *Arthritis Research & Therapy* **23**, 106 (Apr. 2021).
- Li, F. *et al.* Evaluating and mitigating bias in machine learning models for cardiovascular disease prediction. *Journal of Biomedical Informatics* 138, 104294 (Feb. 2023).
- Banda, J. M., Shah, N. H. & Periyakoil, V. S. Characterizing subgroup performance of probabilistic phenotype algorithms within older adults: a case study for dementia, mild cognitive impairment, and Alzheimer's and Parkinson's diseases. *JAMIA Open* 6, 00ad043 (July 2023).
- 16. Obermeyer, Z., Powers, B., Vogeli, C. & Mullainathan, S. Dissecting racial bias in an algorithm used to manage the health of populations. *Science* **366**. Publisher: American Association for the Advancement of Science, 447–453 (2019).
- 17. Barocas, S., Hardt, M. & Narayanan, A. *Fairness and machine learning: limitations and opportunities* eng (The MIT Press, Cambridge, Massachusetts, 2023).
- Young, H. P. Equity: in theory and practice 1. Princeton paperback printing. eng (Princeton Univ. Press, Princeton, NJ, 1995).
- Roemer, J. E. Equality of opportunity eng (Harvard Univ. Press, Cambridge, Mass., 1998).
- Roemer, J. E. *Theories of distributive justice* 1. Harvard Univ. Press paperback ed. eng (Harvard Univ. Press, Cambridge, Mass., 1998).
- Rawls, J. A theory of justice Rev. ed (Belknap Press of Harvard University Press, Cambridge, Mass, 1971).
- 22. Rawls, J. & Kelly, E. *Justice as fairness: a restatement* (Harvard University Press, Cambridge, Mass, 2001).
- Hutchinson, B. & Mitchell, M. 50 years of test (un) fairness: Lessons for machine learning in Proceedings of the conference on fairness, accountability, and transparency (2019), 49–58.
- Dwork, C., Hardt, M., Pitassi, T., Reingold, O. & Zemel, R. Fairness through awareness in Proceedings of the 3rd Innovations in Theoretical Computer Science Conference (Association for Computing Machinery, New York, NY, USA, Jan. 2012), 214–226.
- Wang, H. E. *et al.* A bias evaluation checklist for predictive models and its pilot application for 30-day hospital readmission models. *Journal of the American Medical Informatics Association* 29. Publisher: Oxford University Press, 1323–1333 (2022).

- Feng, Q., Du, M., Zou, N. & Hu, X. Fair Machine Learning in Healthcare: A Review arXiv:2206.14397 [cs]. Aug. 2022.
- Liu, M. et al. A translational perspective towards clinical AI fairness. en. npj Digital Medicine 6. Number: 1 Publisher: Nature Publishing Group, 1–6 (Sept. 2023).
- 28. Yang, S., Varghese, P., Stephenson, E., Tu, K. & Gronsbell, J. Machine learning approaches for electronic health records phenotyping: a methodical review. *Journal of the American Medical Informatics Association* **30**, 367–381 (Feb. 2023).
- Chen, F., Wang, L., Hong, J., Jiang, J. & Zhou, L. Unmasking Bias in Artificial Intelligence: A Systematic Review of Bias Detection and Mitigation Strategies in Electronic Health Record-Based Models. *Journal of the American Medical Informatics Association*, ocae060 (Mar. 2024).
- Plecko, D. & Bareinboim, E. Causal Fairness Analysis arXiv:2207.11385 [cs, stat]. July 2022.
- Anderson, J. W. & Visweswaran, S. Algorithmic Individual Fairness for Healthcare: A Scoping Review. medRxiv, 2024–03 (2024).
- 32. Raffa, J. Clinical Data from the MIMIC-II Database for a Case Study on Indwelling Arterial Catheters: 2016.
- Rajkomar, A., Hardt, M., Howell, M. D., Corrado, G. & Chin, M. H. Ensuring fairness in machine learning to advance health equity. *Annals of internal medicine* 169. Publisher: American College of Physicians, 866–872 (2018).
- Mehrabi, N., Morstatter, F., Saxena, N., Lerman, K. & Galstyan, A. A Survey on Bias and Fairness in Machine Learning. ACM Computing Surveys 54, 115:1–115:35 (July 2021).
- Fazelpour, S. & Danks, D. Algorithmic bias: Senses, sources, solutions. en. *Philoso-phy Compass* 16. \_eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1111/phc3.12760, e12760 (2021).
- 36. Mhasawade, V., Zhao, Y. & Chunara, R. Machine learning and algorithmic fairness in public and population health. *Nature Machine Intelligence* **3**, 659–666 (2021).
- Xu, J. et al. Algorithmic fairness in computational medicine. English. eBioMedicine 84. Publisher: Elsevier (Oct. 2022).
- Drukker, K. *et al.* Toward fairness in artificial intelligence for medical image analysis: identification and mitigation of potential biases in the roadmap from data collection to model deployment. *Journal of Medical Imaging* 10. Publisher: SPIE, 061104 (Apr. 2023).
- Ferrara, E. Fairness and Bias in Artificial Intelligence: A Brief Survey of Sources, Impacts, and Mitigation Strategies. en. Sci 6. Number: 1 Publisher: Multidisciplinary Digital Publishing Institute, 3 (Mar. 2024).

- Iliadis, A. & Russo, F. Critical data studies: An introduction. Big Data & Society 3, 2053951716674238 (2016).
- 41. Suresh, H. & Guttag, J. A framework for understanding sources of harm throughout the machine learning life cycle in Proceedings of the 1st ACM Conference on Equity and Access in Algorithms, Mechanisms, and Optimization (2021), 1–9.
- Chouldechova, A. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data* 5. Publisher: Mary Ann Liebert, Inc. 140 Huguenot Street, 3rd Floor New Rochelle, NY 10801 USA, 153–163 (2017).
- Gichoya, J. W. et al. AI pitfalls and what not to do: mitigating bias in AI. The British Journal of Radiology 96, 20230023 (2023).
- 44. Wolff, R. F. *et al.* PROBAST: a tool to assess the risk of bias and applicability of prediction model studies. *Annals of internal medicine* **170**, 51–58 (2019).
- 45. Liu, X. *et al.* Reporting guidelines for clinical trial reports for interventions involving artificial intelligence: the CONSORT-AI extension. *The Lancet Digital Health* **2**, e537–e548 (2020).
- Pessach, D. & Shmueli, E. A Review on Fairness in Machine Learning. ACM Computing Surveys 55, 51:1–51:44 (Feb. 2022).
- Mitchell, S., Potash, E., Barocas, S., D'Amour, A. & Lum, K. Algorithmic fairness: Choices, assumptions, and definitions. *Annual Review of Statistics and Its Application* 8. Publisher: Annual Reviews, 141–163 (2021).
- 48. Mbakwe, A. B., Lourentzou, I., Celi, L. A. & Wu, J. T. Fairness metrics for health AI: we have a long way to go. *EBioMedicine* **90** (2023).
- Zhang, H., Lu, A. X., Abdalla, M., McDermott, M. & Ghassemi, M. Hurtful words: quantifying biases in clinical contextual word embeddings in proceedings of the ACM Conference on Health, Inference, and Learning (2020), 110–120.
- Fry, A. et al. Comparison of Sociodemographic and Health-Related Characteristics of UK Biobank Participants With Those of the General Population. en. American Journal of Epidemiology 186, 1026–1034 (Nov. 2017).
- Kronk, C. A. *et al.* Transgender data collection in the electronic health record: current concepts and issues. *Journal of the American Medical Informatics Association* 29. Publisher: Oxford University Press, 271–284 (2022).
- 52. Toulany, A. et al. Sociodemographic Differences in Physician-Based Mental Health and Virtual Care Utilization and Uptake of Virtual Care Among Children and Adolescents During the COVID-19 Pandemic in Ontario, Canada: A Population-Based Study. en. The Canadian Journal of Psychiatry 68. Publisher: SAGE Publications Inc, 904–915 (Dec. 2023).

- Martin, A. R. *et al.* Clinical use of current polygenic risk scores may exacerbate health disparities. en. *Nature Genetics* 51. Number: 4 Publisher: Nature Publishing Group, 584–591 (Apr. 2019).
- Chapman, K. A., Machado, S. S., van der Merwe, K., Bryson, A. & Smith, D. Exploring Primary Care Non-Attendance: A Study of Low-Income Patients. eng. J Prim Care Community Health 13, 21501319221082352 (2022).
- Suriyakumar, V. M., Papernot, N., Goldenberg, A. & Ghassemi, M. Chasing your long tails: Differentially private prediction in health care settings in Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency (2021), 723-734.
- 56. Debray, T. P. A. *et al.* A guide to systematic review and meta-analysis of prediction model performance. en. *BMJ* **356.** Publisher: British Medical Journal Publishing Group Section: Research Methods & amp; Reporting, i6460 (Jan. 2017).
- 57. Lehman, C. D. *et al.* Diagnostic Accuracy of Digital Screening Mammography With and Without Computer-Aided Detection. en. *JAMA Internal Medicine* **175**, 1828 (Nov. 2015).
- Ancker, J. S. *et al.* Effects of Workload, Work Complexity, and Repeated Alerts on Alert Fatigue in a Clinical Decision Support System. *BMC Medical Informatics and Decision Making* 17, 36 (Apr. 2017).
- 59. Caton, S. & Haas, C. Fairness in Machine Learning: A Survey. *ACM Computing Surveys*. Just Accepted (Aug. 2023).
- McCradden, M. D., Joshi, S., Mazwi, M. & Anderson, J. A. Ethical limitations of algorithmic fairness solutions in health care machine learning. *The Lancet Digital Health* 2, e221–e223 (2020).
- 61. Plecko, D. & Bareinboim, E. Causal Fairness Analysis 2022.
- Hardt, M., Price, E., Price, E. & Srebro, N. Equality of Opportunity in Supervised Learning in Advances in Neural Information Processing Systems 29 (Curran Associates, Inc., 2016).
- 63. Garriga, R. *et al.* Machine learning model to predict mental health crises from electronic health records. *Nature Medicine* **28**, 1240–1248 (2022).
- Schuch, H. S. *et al.* Fairness of Machine Learning Algorithms for Predicting Foregone Preventive Dental Care for Adults. *JAMA Network Open* 6, e2341625 (Nov. 2023).
- 65. Yfantidou, S. et al. Beyond Accuracy: A Critical Review of Fairness in Machine Learning for Mobile and Wearable Computing 2023.

- 66. Wang, H., Li, Y., Naidech, A. & Luo, Y. Comparison between machine learning methods for mortality prediction for sepsis patients with different social determinants. *BMC Medical Informatics and Decision Making* **22**, 156 (June 2022).
- Yuan, C., Linn, K. A. & Hubbard, R. A. Algorithmic Fairness of Machine Learning Models for Alzheimer Disease Progression. *JAMA Network Open* 6, e2342203 (Nov. 2023).
- Awasthi, P., Cortes, C., Mansour, Y. & Mohri, M. Beyond individual and group fairness. arXiv preprint arXiv:2008.09490 (2020).
- Berk, R., Heidari, H., Jabbari, S., Kearns, M. & Roth, A. Fairness in Criminal Justice Risk Assessments: The State of the Art. en. *Sociological Methods & Research* 50. Publisher: SAGE Publications Inc, 3–44 (July 2018).
- Castelnovo, A. *et al.* A clarification of the nuances in the fairness metrics landscape. en. *Scientific Reports* **12.** Number: 1 Publisher: Nature Publishing Group, 4209 (Mar. 2022).
- Corbett-Davies, S., Pierson, E., Feller, A., Goel, S. & Huq, A. Algorithmic decision making and the cost of fairness in Proceedings of the 23rd acm sigkdd international conference on knowledge discovery and data mining (2017), 797–806.
- 72. Pfohl, S. et al. Creating Fair Models of Atherosclerotic Cardiovascular Disease Risk 2019.
- 73. Lei, H., Gohari, A. & Farnia, F. On the Inductive Biases of Demographic Paritybased Fair Learning Algorithms http://arxiv.org/abs/2402.18129. Feb. 2024.
- Yang, J., Soltan, A. A. S., Eyre, D. W. & Clifton, D. A. Algorithmic Fairness and Bias Mitigation for Clinical Machine Learning with Deep Reinforcement Learning. *Nature Machine Intelligence* 5, 884–894 (Aug. 2023).
- Kleinberg, J., Mullainathan, S. & Raghavan, M. Inherent Trade-Offs in the Fair Determination of Risk Scores in ([object Object], 2017), 23 pages, 503645 bytes.
- Guo, C., Pleiss, G., Sun, Y. & Weinberger, K. Q. On Calibration of Modern Neural Networks en. in Proceedings of the 34th International Conference on Machine Learning ISSN: 2640-3498 (PMLR, July 2017), 1321–1330.
- 77. Byrd IV, T. F. *et al.* Validation of a Proprietary Deterioration Index Model and Performance in Hospitalized Adults. *JAMA Network Open* **6**, e2324176 (July 2023).
- Corbett-Davies, S., Gaebler, J. D., Nilforoshan, H., Shroff, R. & Goel, S. The Measure and Mismeasure of Fairness. *Journal of Machine Learning Research* 24, 1–117 (2023).
- 79. Juhn, Y. J. et al. Assessing Socioeconomic Bias in Machine Learning Algorithms in Health Care: A Case Study of the HOUSES Index. Journal of the American Medical Informatics Association : JAMIA 29, 1142–1151 (Apr. 2022).

- 80. Varga, T. V. Algorithmic fairness in cardiovascular disease risk prediction: overcoming inequalities. *Open Heart* **10** (2023).
- 81. Ueda, D. *et al.* Artificial intelligence-supported lung cancer detection by multiinstitutional readers with multi-vendor chest radiographs: a retrospective clinical validation study. *BMC Cancer* **21**, 1120 (Oct. 2021).
- Raza, S. & Bashir, S. R. Auditing ICU Readmission Rates in an Clinical Database: An Analysis of Risk Factors and Clinical Outcomes in 2023 IEEE 11th International Conference on Healthcare Informatics (ICHI) (IEEE Computer Society, June 2023), 722–726.
- 83. Röösli, E., Bozkurt, S. & Hernandez-Boussard, T. Peeking into a black box, the fairness and generalizability of a MIMIC-III benchmarking model. *Scientific Data* **9** (Jan. 2022).
- 84. Mit Critical Data. Secondary Analysis of Electronic Health Records (Springer International Publishing, Cham, 2016).
- Lancaster, R., Marks, J., Fausto-Sterling, A. & Fuentes, A. Complexities of gender and sex 2023.
- Keya, K. N., Islam, R., Pan, S., Stockwell, I. & Foulds, J. in *Proceedings of the* 2021 SIAM International Conference on Data Mining (SDM) 190–198 (Society for Industrial and Applied Mathematics, Jan. 2021).
- Rahman, M. M. & Purushotham, S. Fair and Interpretable Models for Survival Analysis in Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (Association for Computing Machinery, New York, NY, USA, Aug. 2022), 1452–1462.
- 88. Kim, M., Reingold, O. & Rothblum, G. Fairness through computationally-bounded awareness. Advances in neural information processing systems **31** (2018).
- Ilvento, C. Metric learning for individual fairness. arXiv preprint arXiv:1906.00250 (2019).
- Mukherjee, D., Yurochkin, M., Banerjee, M. & Sun, Y. Two simple ways to learn individual fairness metrics from data in International Conference on Machine Learning (2020), 7097–7107.
- Kusner, M. J., Loftus, J., Russell, C. & Silva, R. Counterfactual Fairness in Advances in Neural Information Processing Systems 30 (Curran Associates, Inc., 2017).
- Damen, J. A. A. G. *et al.* Prediction Models for Cardiovascular Disease Risk in the General Population: Systematic Review. *BMJ (Clinical research ed.)* 353, i2416 (May 2016).

- 93. Chicco, D. & Jurman, G. Survival prediction of patients with sepsis from age, sex, and septic episode number alone. *Scientific reports* **10**, 17156 (2020).
- 94. Cirillo, D. *et al.* Sex and gender differences and biases in artificial intelligence for biomedicine and healthcare. *NPJ digital medicine* **3**, 1–11 (2020).
- Banja, J., Gichoya, J. W., Martinez-Martin, N., Waller, L. A. & Clifford, G. D. Fairness as an Afterthought: An American Perspective on Fairness in Model Developer-Clinician User Collaborations. *PLOS Digital Health* 2, e0000386 (Nov. 2023).
- 96. Friedler, S. A., Scheidegger, C. & Venkatasubramanian, S. On the (im)possibility of fairness arXiv:1609.07236 [cs, stat]. Sept. 2016.
- 97. Binns, R. On the apparent conflict between individual and group fairness in Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency (Association for Computing Machinery, New York, NY, USA, Jan. 2020), 514–524.
- Xu, S. & Strohmer, T. On the (In)Compatibility between Group Fairness and Individual Fairness arXiv:2401.07174 [cs, math, stat]. Jan. 2024.
- 99. Pearl, J. Causal inference in statistics: An overview (2009).
- 100. Hernán, M. A. & Robins, J. M. Causal inference 2010.
- Loftus, J. R., Russell, C., Kusner, M. J. & Silva, R. Causal Reasoning for Algorithmic Fairness May 2018.
- 102. Fawkes, J., Evans, R. & Sejdinovic, D. Selection, ignorability and challenges with causal fairness in Conference on Causal Learning and Reasoning (2022), 275–289.
- Makhlouf, K., Zhioua, S. & Palamidessi, C. Survey on Causal-based Machine Learning Fairness Notions June 2022.
- 104. Carey, A. N. & Wu, X. The Causal Fairness Field Guide: Perspectives From Social and Formal Sciences. *Frontiers in Big Data* **5** (Apr. 2022).
- 105. Nilforoshan, H., Gaebler, J. D., Shroff, R. & Goel, S. Causal conceptions of fairness and their consequences in International Conference on Machine Learning (PMLR, 2022), 16848–16887.
- 106. Bynum, L. E., Loftus, J. R. & Stoyanovich, J. A New Paradigm for Counterfactual Reasoning in Fairness and Recourse. arXiv preprint arXiv:2401.13935 (2024).
- 107. Pfohl, S. R., Duan, T., Ding, D. Y. & Shah, N. H. Counterfactual Reasoning for Fair Clinical Risk Prediction en. in Proceedings of the 4th Machine Learning for Healthcare Conference ISSN: 2640-3498 (PMLR, Oct. 2019), 325–358.
- 108. Salimi, B., Rodriguez, L., Howe, B. & Suciu, D. Interventional fairness: Causal database repair for algorithmic fairness in Proceedings of the 2019 International Conference on Management of Data (2019), 793–810.

- 109. Pearl, J. *Causality: Models, Reasoning, and Inference* 2nd ed. (Cambridge University Press, Sept. 2009).
- 110. Alves, G. *et al.* Survey on fairness notions and related tensions. *EURO Journal on Decision Processes* **11**, 100033 (Jan. 2023).
- Chiappa, S. Path-Specific Counterfactual Fairness. Proceedings of the AAAI Conference on Artificial Intelligence 33, 7801–7808 (July 2019).
- Nabi, R. & Shpitser, I. Fair Inference on Outcomes. Proceedings of the AAAI Conference on Artificial Intelligence 32 (Apr. 2018).
- 113. Wu, Y., Zhang, L., Wu, X. & Tong, H. in Proceedings of the 33rd International Conference on Neural Information Processing Systems 306, 3404–3414 (Curran Associates Inc., Red Hook, NY, USA, Dec. 2019).
- 114. Zhang, L., Wu, Y. & Wu, X. A Causal Framework for Discovering and Removing Direct and Indirect Discrimination en. in Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence (International Joint Conferences on Artificial Intelligence Organization, Melbourne, Australia, Aug. 2017), 3929– 3935.
- Zuo, A., Li, Y., Wei, S. & Gong, M. Interventional Fairness on Partially Known Causal Graphs: A Constrained Optimization Approach arXiv:2401.10632 [cs]. Mar. 2024.
- Hort, M., Chen, Z., Zhang, J. M., Harman, M. & Sarro, F. Bias mitigation for machine learning classifiers: A comprehensive survey. ACM Journal on Responsible Computing (2023).
- 117. Goethals, S., Calders, T. & Martens, D. Beyond Accuracy-Fairness: Stop evaluating bias mitigation methods solely on between-group metrics. *arXiv preprint arXiv:2401.13391* (2024).
- 118. Menon, A. K. & Williamson, R. C. The cost of fairness in binary classification en. in Proceedings of the 1st Conference on Fairness, Accountability and Transparency ISSN: 2640-3498 (PMLR, Jan. 2018), 107–118.
- 119. Brahmbhatt, A., Rathore, V., Singla, P., *et al.* Towards Fair and Calibrated Models. *arXiv preprint arXiv:2310.10399* (2023).
- Denis, C., Elie, R., Hebiri, M. & Hu, F. Fairness guarantee in multi-class classification arXiv:2109.13642 [math, stat]. Mar. 2023.
- 121. Bell, A. et al. The Possibility of Fairness: Revisiting the Impossibility Theorem in Practice in Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency https://doi.org/10.1145/3593013.3594007 (Association for Computing Machinery, New York, NY, USA, June 2023), 400–422.

- 122. Zhang, Y. & Long, Q. Fairness in missing data imputation. *arXiv preprint arXiv:2110.12002* (2021).
- 123. Zhang, Y. & Long, Q. Fairness-aware missing data imputation in Workshop on Trustworthy and Socially Responsible Machine Learning, NeurIPS 2022 (2022).
- 124. Wick, M., Tristan, J.-B., et al. Unlocking fairness: a trade-off revisited. Advances in neural information processing systems **32** (2019).
- 125. Ji, D., Smyth, P. & Steyvers, M. Can i trust my fairness metric? assessing fairness with unlabeled data and bayesian inference. Advances in Neural Information Processing Systems 33, 18600–18612 (2020).
- Choi, K., Grover, A., Singh, T., Shu, R. & Ermon, S. Fair generative modeling via weak supervision in International Conference on Machine Learning (2020), 1887– 1898.
- 127. Gao, J. et al. Semi-Supervised ROC Analysis for Reliable and Streamlined Evaluation of Phenotyping Algorithms. Journal of the American Medical Informatics Association 31, 640–650 (Feb. 2024).
- 128. Grasso, C., McDowell, M. J., Goldhammer, H. & Keuroghlian, A. S. Planning and implementing sexual orientation and gender identity data collection in electronic health records. *Journal of the American Medical Informatics Association* 26, 66–70 (2019).
- 129. Ruberg, B. & Ruelos, S. Data for queer lives: How LGBTQ gender and sexuality identities challenge norms of demographics. *Big Data & Society* 7, 2053951720933286 (2020).
- 130. Tomasev, N., McKee, K. R., Kay, J. & Mohamed, S. Fairness for unobserved characteristics: Insights from technological impacts on queer communities in Proceedings of the 2021 AAAI/ACM Conference on AI, Ethics, and Society (2021), 254–265.

## Supplementary Materials

Jianhui Gao<sup>1</sup>, Benson Chou<sup>1</sup>, Zachary R. McCaw<sup>2</sup>, Hilary Thurston<sup>3</sup>,

Paul Varghese<sup>4</sup>, Chuan Hong<sup>5</sup>, and Jessica Gronsbell<sup>1,6,7</sup>

<sup>1</sup>Department of Statistical Sciences, University of Toronto, Toronto, ON, Canada
<sup>2</sup>Department of Biostatistics, Harvard T.H. Chan School of Public Health, Boston, MA, USA
<sup>3</sup>Department of Gender & Sexuality Studies, York University, Toronto, ON, Canada
<sup>4</sup> Verily Life Sciences, Cambridge, MA, USA
<sup>5</sup>Department of Biostatistics, Duke University Raleigh, NC, USA
<sup>6</sup>Department of Family & Community Medicine, University of Toronto, ON, Canada

<sup>7</sup>Department of Computer Science, University of Toronto, Toronto, ON, Canada

## Contents

1	Cor	nparison with Existing Literature and Software	3		
2 Group Fairness Criteria					
	2.1	Statistical Metrics for Model Evaluation	4		
	2.2	Continuous Outcome	5		
	2.3	Categorical Protected Attributes	5		
	2.4	Continuous Protected Attributes	6		
	2.5	Subgroup Fairness	6		
3	Gro	oup Fairness Incompatibilities	7		
	3.1	Independence versus Sufficiency	$\overline{7}$		

	3.2	Independence versus Separation	7
	3.3	Sufficiency versus Separation	7
4	Cas	e Study	8
	4.1	Dataset	8
	4.2	Data Preprocessing	8
	4.3	Model Building	8
5	Cor	nstruction of Confidence Intervals	10
6	Cau	ısal Fairness Criteria	11

Reference	Specific to Healthcare	Fairness Categories	Code Available	Illustrated with Real Data	Inference	Format	
This Tutorial	$\checkmark$	G, I, S, C	R	$\checkmark$	$\checkmark$	Article	
Reviews and S	Surveys	-	-				
[1]	×	G, I, S	×	×	×	Article	
[2]	×	G, I, C	×	×	$\checkmark$	Article	
[3-9]	×	G, I, C	×	×	×	Article	
[10]	×	G, C	Python	$\checkmark$	×	Article	
[11-15]	$\checkmark$	G	×	×	×	Article	
Tutorials	Tutorials						
[16]	$\checkmark$	G, I, S	Python	$\checkmark$	×	Slides	
[17]	×	G	Python	$\checkmark$	×	Slides, Video	
[18, 19]	×	G	×	$\checkmark$	×	Slides, Video	
[20]	×	G, C	×	$\checkmark$	×	Slides, Video	
[21]	×	G, I	×	×	×	Video	

## 1 Comparison with Existing Literature and Software

Table S1: Comparison of current tutorial with existing literature on algorithmic fairness. G: Group fairness, I: Individual fairness, S: Subgroup fairness, C: Causality-based fairness

Toolkit	Supported Languages	Point Estimates Type	Confidence Interval Availability
Our Package	R	Difference, Ratio	$\checkmark$
Fairness Package [22]	R	Ratio	×
Fairlearn [23]	Python	Difference, Ratio	×
Aequitas [24]	Python	Ratio	×
AI Fairness 360 [25]	Python, R	-	×
TensorFlow Fairness Indicators [26]	Python	-	×

Table S2: Comparison of our R package with existing fairness toolkits. The last two toolkits are based on direct visualizations of model performance metrics. The metrics included in each toolkits are generally very similar.

## 2 Group Fairness Criteria

### 2.1 Statistical Metrics for Model Evaluation

Model performance in classification is typically evaluated from two perspectives: discrimination and calibration. The mathematical and intuitive definitions of various discrimination and calibration metrics are presented in Table S3. Discrimination evaluates an ML model's capacity to distinguish between the positive and negative class while calibration evaluates the level of agreement between the risk score and the observed frequency of that outcome. A model is calibrated if, among the proportion of observations with a risk score of s, a fraction s have the positive outcome. A well-calibrated model is crucial for clinical decision-making as it ensures the risk scores derived from ML model accurately reflect the true likelihood of a positive outcome [27]. While numerous measures of calibration exist, we present the Brier score (BS) and mean absolute error (MAE). A BS or MAE closer to 0 indicates a more calibrated model. It is worth noting that both BS and MAE remains valid when Y is continuous. In this context, the BS is equivalent to the mean squared error (MSE).

Metric	Definition	Explanation
Discrimination	•	
True Positive (TP)	$\#\{Y=1, D=1\}$	Count of correctly classified positives.
False Positive (FP)	$\#\{Y=0, D=1\}$	Negatives incorrectly classified as positives.
True Negative (TN)	$\#\{Y=0, D=0\}$	Count of correctly classified negatives.
False Negative (FN)	$\#\{Y = 1, D = 0\}$	Positives incorrectly classified as negatives.
True Positive Rate (TPR)	$P(D=1 \mid Y=1) = \frac{TP}{TP+FN}$	Proportion of positives correctly classified.
True Negative Rate (TNR)	$P(D=0 \mid Y=0) = \frac{TN}{TN+FP}$	Proportion of negatives correctly classified.
False Positive Rate (FPR)	$P(D=1 \mid Y=0) = \frac{FP}{FP+TN}$	Proportion of negatives incorrectly classified.
False Negative Rate (FNR)	$P(D=0 \mid Y=1) = \frac{FN}{TP+FN}$	Proportion of positives incorrectly classified.
Positive Predictive Value (PPV)	$P(Y=1 \mid D=1) = \frac{TP}{TP+FP}$	Proportion of predicted positives that are true.
Negative Predictive Value (NPV)	$P(Y=0 \mid D=0) = \frac{TN}{TN+FN}$	Proportion of predicted negatives that are true.
Accuracy (ACC)	$P(D=Y) = \frac{TP+TN}{TP+FP+TN+FN}$	Overall proportion of correctly classified.
Calibration		
Brier's Score (BS)*	$\mathbb{E}[(S-Y)^2]$	Mean squared difference between predicted probabilities and outcomes.
Mean Absolute Error (MAE)*	$\mathbb{E} S-Y $	Mean absolute difference between predicted probabilities and outcomes

Table S3: Statistical metrics for evaluating classification performance. Symbols: # = number of, P = probability, E = expected value. Notations: Y : outcome of interest, S : model output, D : predicted outcome by thresholding S. An asterisk (\*) indicates that the metrics are applicable whether Y is binary or continuous.

### 2.2 Continuous Outcome

Many clinical applications involve models for predicting continuous outcomes, such as healthcare costs. In Table S3, we briefly touched on a few metrics that can be used to evaluate the performance of an algorithm when the outcome is continuous. The parity between these metrics can be used to evaluate fairness analogously to the setting of a binary outcome. Recently, [28] proposed methods to measure independence, separation, and sufficiency for continuous outcomes by estimating conditional densities or using mutual information, though their methods are limited to binary protected attributes. An alternative approach involves conducting conditional statistical tests, such as testing independence through the Hirschfeld-Gebelein-Renyi maximal correlation coefficient, which accommodates both continuous outcomes and protected attributes [29]. This is an ongoing area of research and we encourage readers to consult [28, 30] for further discussion of the topic.

### 2.3 Categorical Protected Attributes

When the protected attributes are binary, natural measures of parity include the difference and the ratio as we introduced in the main text of tutorial. However, many protected attributes define more than two groups, such as race and marital status. One approach for such protected attributes is to directly visualize the metrics in toolkit such as AI Fairness 360 [25]. However, this method has notable limitations, including subjective judgment and challenges when dealing with numerous subgroups [31]. To address these issues, various meta-metrics have been proposed and applied to quantify group-wise disparities into a single metric. [31] have summarized common meta-metrics from the literature, which we present in Table S4 below. These metrics primarily focus on two key aspects: extremum and variability of model performances among groups.

Meta-Metrics	Formula	Type
max-min difference	$\max_j \mathcal{M}_j - \min_j \mathcal{M}_j$	Extremum
max-min ratio	$\frac{\max_{j} \mathcal{M}_{j}}{\min_{j} \mathcal{M}_{j}}$	Extremum
max absolute difference	$\max_{j} \left  \mathcal{M}_{j} - \frac{1}{K} \sum_{i=1}^{K} \mathcal{M}_{i} \right $	Extremum
mean absolute deviation	$\frac{1}{K}\sum_{j=1}^{K} \left  \mathcal{M}_{j} - \frac{1}{K}\sum_{i=1}^{K} \mathcal{M}_{i} \right $	Variability
variance	$\frac{1}{K-1}\sum_{j=1}^{K}\left(\mathcal{M}_{j}-\frac{1}{K}\sum_{i=1}^{K}\mathcal{M}_{i} ight)^{2}$	Variability
generalized entropy index $(\alpha \neq 0, 1)$	$\frac{1}{K\alpha(\alpha-1)}\sum_{j=1}^{K}\left[\left(\frac{\mathcal{M}_{j}}{\frac{1}{K}\sum_{i=1}^{K}\mathcal{M}_{i}}\right)^{\alpha}-1\right]$	Variability

Table S4: Meta-metrics for evaluating fairness across K protected groups.  $\mathcal{M}_j$  denotes a model performance metric (e.g., the true positive rate) for  $j = 1, \ldots, K$ . These meta-metrics summarize a model's performance metric,  $\mathcal{M}_j$ , across  $j = 1, \ldots, K$  groups.

### 2.4 Continuous Protected Attributes

When dealing with continuous protected attributes, such as age, applying thresholds or bins may introduce threshold effects [29]. Only very recently, [29] proposed using the Hirschfeld-Gebelein-Rényi (HGR) maximal correlation coefficient as a metric to measure fairness for continuous protected attributes. This is an ongoing area of research and we encourage readers to consult [29, 32] and references therein.

### 2.5 Subgroup Fairness

When multiple attributes are of interest (e.g., sex = {male, female} and race = {white, black}), a model can be fair in both groups, but show disparities in an intersectional subgroup (e.g., {black male}), a phenomenon known as "Fairness Gerrymandering" [33]. Subgroup fairness or intersectional fairness selects a specific fairness constraint, such as statistical parity or equalized odds, and then evaluates it across a large collection of subgroups. For instance, a recent study evaluated a chest X-ray algorithm across the 8 possible intersectional subgroup of income = {high, low}, insurance = {high, low}, race = {white, non-white} by evaluating the differences between the maximum and minimum false positive rates [34].

## 3 Group Fairness Incompatibilities

### 3.1 Independence versus Sufficiency

If the outcome and protected groups are dependent  $(Y \not\perp A)$ , then it is not possible to achieve both independence and sufficiency. Specifically, when Y is binary and prevalence differs across protected groups, an algorithm cannot simultaneously satisfy these two criteria.

### 3.2 Independence versus Separation

Besides the dependency between the outcome and protected group  $(Y \not\perp A)$ , if prediction also depends on the outcome  $(D \not\perp Y)$ , independence and separation are incompatible. It is important to note that this statement only holds for binary outcomes. If the prediction is not entirely uninformative for predicting the labels, then there should be correlation between the prediction and the label (i.e.  $D \not\perp Y$ ). However, with unequal prevalence across protected groups, satisfying both criteria simultaneously would yield predictions that are essentially uninformative.

### 3.3 Sufficiency versus Separation

Besides the dependency between the outcome and protected group  $(Y \not\perp A)$ , if the density of the joint distribution of protected attributes, prediction, and outcome ((A, D, Y)) is strictly positive, then sufficiency and separation are incompatible. For binary outcomes, the second condition means that there is at least one false prediction. In other words, the prediction cannot completely determine the outcome. Consequently, with unequal prevalence across protected groups, achieving both sufficiency and separation becomes unattainable unless the algorithm gives perfect predictions.

### 4 Case Study

### 4.1 Dataset

The dataset used in Case Study is derived from the MIMIC-II critical care database. It contains clinical data and outcomes used to "investigate the effectiveness of indwelling arterial catheters in hemodynamically stable patients with respiratory failure regarding mortality outcomes" [35]. The dataset includes 46 variables, including demographics, clinical characteristics such as white blood cell count and heart rate during ICU stays, and a 28-day mortality indicator on 1,776 patients. It is publicly available at https://physionet.org/content/mimic2-iaccd/1.0/.

### 4.2 Data Preprocessing

We removed three variables that had more than 10% missing values: body mass index (26.2%), first partial pressure of oxygen (10.5%), and first partial pressure of carbon dioxide (10.5%). For the remaining variables with missing values, we imputed the missing data with their respective medians. Additionally, we removed the variable 'sepsis\_flg' as it was absent in all records. Lastly, four variables — death in hospital, death in ICU, day post ICU admission of censoring or death, and censored or death—were removed because they cannot be used as predictors for mortality as they are inherently dependent on the outcome being predicted.

### 4.3 Model Building

We used the first 700 individuals as the training set to fit a random forest (RF) model and the remaining 1,076 individuals served as the testing set. The hyperparameters for the RF model were set to use 1000 trees and a random sampling of 6 variables at each split, determined by the square root of the number of predictors. The area under the receiver operating characteristic curve (AUC) for our model on the test set is 0.90. Additionally, the accuracy of this random forest classification model on the test set is 0.88. We selected a cut-off value of 0.41 for fairness evaluation, as it achieves a false positive rate (FPR) of approximately 5%.

### 5 Construction of Confidence Intervals

We illustrate the procedure for constructing confidence intervals (CIs) using false positive rate (FPR). Let  $\widehat{\text{FPR}}_a$  and  $\operatorname{FPR}_a$  represent the estimated and true FPRs in group  $a \in \mathcal{A}$ . We construct Wald-type CIs based on the following result:  $\sqrt{n} \left( \widehat{\text{FPR}}_a - \text{FPR}_a \right)$  is asymptotic normal with mean 0 for all  $a \in \mathcal{A}$  [e.g. 36]. Let  $\widehat{\Delta}_{\text{FPR}} = \widehat{\text{FPR}}_{a_1} - \widehat{\text{FPR}}_{a_0}$  represent the estimated difference between group  $a_1$  and  $a_0$ . It follows that  $\sqrt{n} \left( \widehat{\Delta}_{\text{FPR}} - \Delta_{\text{FPR}} \right)$ is asymptotic normal with mean 0. To estimate the standard error of  $\widehat{\Delta}_{\text{FPR}}$ , we a nonparametric bootstrap [37]. For each bootstrap iteration b in  $\{1,...,B\}$ , we sample the data with replacement within each group and then calculate  $\widehat{\Delta}_{\text{FPR}}^{(b)}$ . The estimated standard error is the empirical standard error of the difference:

$$\widehat{\operatorname{se}}\left[\widehat{\Delta}_{\operatorname{FPR}}\right] = \sqrt{\frac{1}{B-1}\sum_{b=1}^{B}\left(\widehat{\Delta}_{\operatorname{FPR}}^{(b)} - \frac{1}{B}\sum_{b=1}^{B}\widehat{\Delta}_{\operatorname{FPR}}^{(b)}\right)^{2}}.$$

The corresponding Wald-based  $100(1 - \alpha)\%$  CI is given by  $\widehat{\Delta}_{\text{FPR}} \pm z_{1-\alpha/2} * \widehat{\text{se}} \left[\widehat{\Delta}_{\text{FPR}}\right]$ , where  $z_{1-\alpha/2}$  is the  $100(1 - \alpha/2)$  percentile of the standard normal distribution.

To construct a  $100(1 - \alpha)\%$  Wald-type CI for the ratio  $\hat{\rho}_{\text{FPR}} = \frac{\widehat{\text{FPR}}_{a_1}}{\widehat{\text{FPR}}_{a_0}}$ , we note that  $\sqrt{n} \left[ \log (\hat{\rho}_{\text{FPR}}) - \log (\rho_{\text{FPR}}) \right]$  is asymptotic normal with mean 0. For each bootstrap iteration b in  $\{1, ..., B\}$ , we sample the data with replacement within each group and then calculate  $\log \left[ \hat{\rho}_{\text{FPR}}^{(b)} \right]$ . The estimated standard error of the log ratio is:

$$\widehat{\operatorname{se}}\left[\log\left(\widehat{\rho}_{\mathrm{FPR}}\right)\right] = \sqrt{\frac{1}{B-1}\sum_{b=1}^{B}\left\{\log\left[\widehat{\rho}_{\mathrm{FPR}}^{(b)}\right] - \frac{1}{B}\sum_{b=1}^{B}\log\left[\widehat{\rho}_{\mathrm{FPR}}^{(b)}\right]\right\}^{2}}.$$

The corresponding  $100(1 - \alpha)\%$  CI is given by  $\exp \{\log [\hat{\rho}_{FPR}] \pm z_{1-\alpha/2} * \hat{se} [\log (\hat{\rho}_{FPR})]\},\$ where  $z_{1-\alpha/2}$  is the  $100(1 - \alpha/2)$  percentile of the standard normal distribution.

Metric	Definition
Counterfactual	$P(D = 1   Y^1 = 0, A = a_0) = P(D = 1   Y^1 = 0, A = a_1)$ and
Equalized Odds	$P(D = 0   Y^1 = 1, A = a_0) = P(D = 0   Y^1 = 1, A = a_1), \forall a_0, a_1 \in A$
	$ \mathcal{A} $
Counterfactual	$P(Y^1 = 1 \mid D = 1, A = a_0) = P(Y^1 = 1 \mid D = 1, A = a_0), \forall a_0, a_1 \in A$
Predictive Parity	$ \mathcal{A} $
Principal Fairness	$P(D = 1   R, A = a_0) = P(D = 1   R, A = a_1)$ for each R and
	$\forall a_0, a_1 \in \mathcal{A}$
Conditional Prin-	$P(D = 1   R, \mathbf{Z}, A = a_0) = P(D = 1   \mathbf{Z}, R, A = a_1)$ for each R and
cipal Fairness	$\forall a_0, a_1 \in \mathcal{A}$
Counterfactual	E(D(a)) = E(D(a'))
parity	
Conditional coun-	$E(D(a) \mid \mathbf{Z}) = E(D(a') \mid \mathbf{Z})$
terfactual fairness	

## 6 Causal Fairness Criteria

Table S5: Some common notions of causal fairness. Symbols: P = probability, E = expectation. Notations: S : risk score, D : final prediction based on thresholding S, A : protected attribute that takes value in the set  $\mathcal{A}, Y^0$  : potential outcome if the decision had been  $D = 0, Y^1$  : potential outcome if the decision had been D = 1, R:  $(Y^0, Y^1), \mathbb{Z}$ : additional set of features, D(a): the prediction when one's protected attribute is  $a \in \mathcal{A}$ 

## References

- Mehrabi, N., Morstatter, F., Saxena, N., Lerman, K. & Galstyan, A. A Survey on Bias and Fairness in Machine Learning. ACM Computing Surveys 54, 115:1–115:35 (July 2021).
- 2. Plecko, D. & Bareinboim, E. Causal Fairness Analysis 2022.
- Verma, S. & Rubin, J. Fairness definitions explained in Proceedings of the international workshop on software fairness (2018), 1–7.
- Mitchell, S., Potash, E., Barocas, S., D'Amour, A. & Lum, K. Prediction-Based Decisions and Fairness: A Catalogue of Choices, Assumptions, and Definitions. *Annual Review of Statistics and Its Application* 8. arXiv:1811.07867 [stat], 141–163 (Mar. 2021).
- 5. Makhlouf, K., Zhioua, S. & Palamidessi, C. On the Applicability of Machine Learning Fairness Notions. ACM SIGKDD Explorations Newsletter 23, 14–23 (May 2021).
- Wang, X., Zhang, Y. & Zhu, R. A brief review on algorithmic fairness. en. Management System Engineering 1, 7 (Nov. 2022).
- Makhlouf, K., Zhioua, S. & Palamidessi, C. Survey on Causal-based Machine Learning Fairness Notions June 2022.
- 8. Alves, G. *et al.* Survey on fairness notions and related tensions. *EURO Journal on Decision Processes* **11**, 100033 (Jan. 2023).
- 9. Caton, S. & Haas, C. Fairness in Machine Learning: A Survey. *ACM Computing Surveys*. Just Accepted (Aug. 2023).
- Nilforoshan, H., Gaebler, J. D., Shroff, R. & Goel, S. Causal conceptions of fairness and their consequences in International Conference on Machine Learning (PMLR, 2022), 16848–16887.
- Rajkomar, A., Hardt, M., Howell, M. D., Corrado, G. & Chin, M. H. Ensuring fairness in machine learning to advance health equity. *Annals of internal medicine* 169. Publisher: American College of Physicians, 866–872 (2018).
- 12. Wang, H. E. *et al.* A bias evaluation checklist for predictive models and its pilot application for 30-day hospital readmission models. *Journal of the American Medical Informatics Association* **29.** Publisher: Oxford University Press, 1323–1333 (2022).
- 13. Yfantidou, S. et al. Beyond Accuracy: A Critical Review of Fairness in Machine Learning for Mobile and Wearable Computing 2023.
- Chen, R. J. et al. Algorithmic fairness in artificial intelligence for medicine and healthcare. en. Nature Biomedical Engineering 7. Number: 6 Publisher: Nature Publishing Group, 719–742 (June 2023).

- Chen, F., Wang, L., Hong, J., Jiang, J. & Zhou, L. Unmasking Bias in Artificial Intelligence: A Systematic Review of Bias Detection and Mitigation Strategies in Electronic Health Record-Based Models. *Journal of the American Medical Informatics Association*, ocae060 (Mar. 2024).
- Ahmad, M. A., Patel, A., Eckert, C., Kumar, V. & Teredesai, A. Fairness in Machine Learning for Healthcare in Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (Association for Computing Machinery, New York, NY, USA, Aug. 2020), 3529–3530.
- Ghani, R., Rodolfa, K. T., Saleiro, P. & Jesus, S. Addressing Bias and Fairness in Machine Learning: A Practical Guide and Hands-on Tutorial in Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (Association for Computing Machinery, New York, NY, USA, Aug. 2023), 5779–5780.
- Chang, K.-W., Prabhakaran, V. & Ordonez, V. Bias and Fairness in Natural Language Processing en-us. in (Nov. 2019).
- Bird, S., Kenthapadi, K., Kiciman, E. & Mitchell, M. Fairness-Aware Machine Learning: Practical Challenges and Lessons Learned in Proceedings of the Twelfth ACM International Conference on Web Search and Data Mining (Association for Computing Machinery, New York, NY, USA, Jan. 2019), 834–835.
- Farnadi, G., Liao, Q. & Creager, E. Algorithmic fairness: at the intersections Tutorial in NeurIPS (2022).
- 21. Arvind Narayanan. Tutorial: 21 fairness definitions and their politics in (Mar. 2018).
- Kozodoi, N. & V. Varga, T. fairness: Algorithmic Fairness Metrics R package version 1.2.1 (2021).
- Weerts, H. et al. Fairlearn: Assessing and Improving Fairness of AI Systems. Journal of Machine Learning Research 24, 1–8 (2023).
- Saleiro, P. et al. Aequitas: A Bias and Fairness Audit Toolkit arXiv:1811.05577 [cs]. Apr. 2019.
- Bellamy, R. K. *et al.* AI Fairness 360: An extensible toolkit for detecting, understanding, and mitigating unwanted algorithmic bias. *arXiv preprint arXiv:1810.01943* (2018).
- 26. Developers, T. TensorFlow Mar. 2024.
- Van Calster, B. *et al.* Calibration: the Achilles heel of predictive analytics. *BMC Medicine* 17, 230 (Dec. 2019).
- Steinberg, D., Reid, A. & O'Callaghan, S. Fairness Measures for Regression via Probabilistic Classification arXiv:2001.06089 [cs, stat]. Mar. 2020.

- Mary, J., Calauzènes, C. & Karoui, N. E. Fairness-Aware Learning for Continuous Attributes and Treatments en. in Proceedings of the 36th International Conference on Machine Learning ISSN: 2640-3498 (PMLR, May 2019), 4382–4391.
- 30. Kim, E. *et al.* Measuring Fairness Using Probable Segmentation for Continuous Sensitive Attributes. en (Oct. 2023).
- 31. Lum, K., Zhang, Y. & Bower, A. De-biasing "bias" measurement in 2022 ACM Conference on Fairness, Accountability, and Transparency (2022), 379–389.
- Giuliani, L., Misino, E. & Lombardi, M. Generalized disparate impact for configurable fairness solutions in ML in Proceedings of the 40th International Conference on Machine Learning 202 (JMLR.org, July 2023), 11443–11458.
- Kearns, M., Neel, S., Roth, A. & Wu, Z. S. Preventing Fairness Gerrymandering: Auditing and Learning for Subgroup Fairness en. in Proceedings of the 35th International Conference on Machine Learning ISSN: 2640-3498 (PMLR, July 2018), 2564– 2572.
- Moukheiber, D., Mahindre, S., Moukheiber, L., Moukheiber, M. & Gao, M. Looking Beyond What You See: An Empirical Analysis on Subgroup Intersectional Fairness for Multi-label Chest X-ray Classification Using Social Determinants of Racial Health Inequities Mar. 2024.
- 35. Raffa, J. Clinical Data from the MIMIC-II Database for a Case Study on Indwelling Arterial Catheters: 2016.
- Gronsbell, J. L. & Cai, T. Semi-Supervised Approaches to Efficient Evaluation of Model Prediction Performance. *Journal of the Royal Statistical Society. Series B* (Statistical Methodology) 80, 579–594 (2018).
- Efron, B. & Tibshirani, R. Bootstrap Methods for Standard Errors, Confidence Intervals, and Other Measures of Statistical Accuracy. *Statistical Science* 1, 54–75 (Feb. 1986).