# PUSHING THE LIMIT OF SOUND EVENT DETECTION WITH MULTI-DILATED FREQUENCY DYNAMIC CONVOLUTION

Hyeonuk Nam, Yong-Hwa Park

Korea Advanced Institute of Science and Technology, South Korea {frednam, yhpark}@kaist.ac.kr

#### ABSTRACT

Frequency dynamic convolution (FDY conv) has been a milestone in the sound event detection (SED) field, but it involves a substantial increase in model size due to multiple basis kernels. In this work, we propose partial frequency dynamic convolution (PFD conv), which concatenates static conventional 2D convolution branch output and dynamic FDY conv branch output in order to minimize model size increase while maintaining the performance. Additionally, we propose multi-dilated frequency dynamic convolution (MDFD conv), which integrates multiple dilated frequency dynamic convolution (DFD conv) branches with different dilation size sets and a static branch within a single convolution module, achieving a 3.2% improvement in polyphonic sound detection score (PSDS) over FDY conv. Proposed methods with extensive ablation studies further enhance understanding and usability of FDY conv variants.

*Index Terms*— sound event detection, frequency dynamic convolution, dilated convolution, partial frequency dynamic convolution, multi-dilated frequency dynamic convolution

#### 1. INTRODUCTION

Sound event detection (SED) aims to identify target sound events within audio recordings and specify their onset and offset times. SED has applications in robotics, automation, and media information retrieval [1, 2, 3]. The advent of deep learning has spurred extensive research in SED. Initially, SED development borrowed methods from other domains but has since evolved with techniques tailored specifically for SED [4, 5, 6, 7, 8, 9, 10]. Among these, frequency dynamic convolution (FDY conv) represents a significant advancement in the field. Widely adopted, including by the winners of the Detection and Classification of Acoustic Scenes and Events (DCASE) 2023 Challenge Task 4, FDY conv improves SED performance substantially [6, 11]. By reducing the translational equivariance of 2D convolution in the frequency dimension and adapting convolution kernels to input content, FDY Conv has greatly enhanced SED performance. This pivotal development has inspired follow-up studies [6, 8, 11, 12, 13].

FDY conv originates from dynamic convolution, which was proposed for efficient convolutional neural network (CNN), but it involves a substantial increase in model size due to multiple basis kernels [7, 14]. FDY Conv with four basis kernel almost triples the number of parameters in convolutional recurrent neural network (CRNN). Thus lighter alternative is needed for more efficient SED. In this context, time-frame frequency-wise squeeze and excitation has been proposed [10], but it does not solve translational equivariance problem of 2D convolution on frequency dimension.

To minimize the parameter increase in FDY conv, we propose *partial frequency dynamic convolution (PFD conv)*. By concatenating conventional 2D convolution output and FDY conv output, PFD conv effectively reduces the model size while retaining the performance. Furthermore, by introducing multiple dynamic branches, we can employ multiple independent FDY convs in single convolution layer. To further enhance the performance, multiple dilated frequency dynamic convolution (DFD conv) modules with different dilation size sets are added to the static convolution branch [13]. Resultant *multi-dilated frequency dynamic convolution (MDFD conv)* outperforms FDY conv by 3.2% in terms of polyphonic sound detection score (PSDS).

The main contributions of this paper are as follows:

- 1. We introduce the concept of concatenating static and dynamic convolution branches for efficient SED, and adding multiple dynamic branches to further enhance SED performance.
- Extensive ablation studies showed the minimum proportions of static and dynamic branches, and also showed various combinations of FDY conv and DFD conv branches for optimal performance.
- 3. Proposed *partial frequency dynamic convolution (PFD conv)* reduces the model size by 51.9% while retaining the performance of FDY conv.

This work was supported by the Institute of Civil Military Technology Cooperation funded by the Defense Acquisition Program Administration and Ministry of Trade, Industry and Energy of Korean government under grant No. UM22409RD4, and Korea Research Institute of Ships and Ocean engineering a grant from Endowment Project of "Development of Open Platform Technologies for Smart Maritime Safety and Industries" funded by Ministry of Oceans and Fisheries(PES4880).



Fig. 1. An illustration of partial frequency dynamic convolution operation which consists of dynamic FDY conv branch and static conventional 2D convolution branch. x and y are input and output of PFD conv. N and M determine the proportion of output of which FDY conv is applied.

 Proposed multi-dilated frequency dynamic convolution (MDFD conv) aggregates DFD conv branches with varying dilation size sets to outperform FDY conv by 3.2%.

### 2. METHODS

#### 2.1. Partial Frequency Dynamic Convolution

Partial frequency dynamic convolution (PFD conv) concatenates the FDY conv output and the conventional 2D convolution output. Since only a part of PFD conv output channels are obtained from FDY conv, the parameter count is proportionally reduced. Translational equivariance of 2D convolution on frequency dimension does not always harm SED considering that pitch-shifted sound events are easily recognized by people thus neighboring frequency bins should share similar convolution kernels. Thus, some of convolution output channels could benefit from frequency-wise translational equivariance. This should be also potential reason why using limited number of basis kernel for FDY conv is optimal for SED. Thus, the proposed PFD conv can maintain or enhance SED performance while reducing the model size. Fig. 1 illustrate the procedure for PFD conv, where dynamic branch processes FDY conv while static branch processes conventional 2D convolution then the output is concatenated.

#### 2.2. Multi-Dilated Frequency Dynamic Convolution

To further develop PFD conv, we could use more dynamic branches to independently process multiple FDY convs. In addition, we could adopt dilated frequency dynamic convolution (DFD conv) for dynamic branches as well. Therefore, we propose Multi-dilated frequency dynamic convolution (MDFD conv). As illustrated in Fig. 2, we could apply multiple DFD conv dynamic branches with single 2D convolution static branch. While multiple static branches could be used as well, it is simply grouped convolution and is not considered in this work. While MDFD conv is not as light as PFD conv, it includes various dilation size sets using multiple DFD conv modules to further enhance SED performance.



**Fig. 2**. An illustration of multi-dilated frequency dynamic convolution operation. It involves multiple dynamic DFD conv branches and single static branch.

# 3. EXPERIMENTAL SETUPS

#### 3.1. Implementation Details

Domestic environment sound event detection (DESED) dataset is used to train, validate and test SED models in this work. DESED is composed of synthesized strongly labeled dataset, real weakly labeled dataset, real unlabeled dataset and real strongly labeled dataset [2]. No external dataset is used in this work.

We extract mel spectrograms from audio waveforms and input them into CRNN-based SED models. The CRNN models in this work consists of 7 convolution layers, where the first convolution layer uses conventional 2D convolution and the rest convolution layers use FDY conv or its variants for Table 1, 2 and 3. To additionally apply FDY conv on first convolution layer, we introduce pre-convolution before the first convolution on Table 4. When DFD conv modules are applied, the last convolution layer uses non-dilated FDY conv as in [13].

Data augmentation methods applied in this work includes frame shift [2], mixup [15], time masking [16] and FilterAugment [17]. We applied median filter with 7 frames (corresponding to 450ms) for all classes as post processing.

#### **3.2. Evaluation Metrics**

To evaluate SED performance, polyphonic sound detection score (PSDS) was used [18]. For DCASE challenge 2021 and 2022 task4 [2], two types of PSDS were used. Among them, PSDS2 is more specific to audio tagging than SED, thus we only used PSDS1 in this work [19, 20]. PSDS results listed in the tables are the best score from 12 separate training runs.

models	Params(M)	PSDS1
CRNN	4.428	0.410
PFD-CRNN (1/32)	4.794	0.436
PFD-CRNN (1/16)	4.996	0.434
PFD-CRNN (1/8)	5.401	0.442
PFD-CRNN (2/8)	6.209	0.439
PFD-CRNN (3/8)	7.018	0.443
PFD-CRNN (4/8)	7.827	0.439
PFD-CRNN (5/8)	8.635	0.436
PFD-CRNN (6/8)	9.444	0.441
PFD-CRNN (7/8)	10.253	0.443
FDY-CRNN	11.061	0.441

**Table 1**. Performance of partial frequency dynamic convolution models with varying proportion of dynamic branch.

 
 Table 2. Performance of multi-frequency dynamic convolutions models.

models	# DYbr	Params(M)	PSDS1
FDY-CRNN	1	11.061	0.441
PFD-CRNN (1/8)	1	5.401	0.442
MFD-CRNN (1/32)	4	5.896	0.430
MFD-CRNN (1/16)	2	5.566	0.439
MFD-CRNN (1/8)	2	6.374	0.439
MFD-CRNN (1/8)	3	7.348	0.444
MFD-CRNN (1/8)	4	8.322	0.440
MFD-CRNN (1/8)	5	9.296	0.449
MFD-CRNN (1/8)	6	10.270	0.452
MFD-CRNN (1/8)	7	11.243	0.445
MFD-CRNN (1/8)	8	12.217	0.447

#### 4. RESULTS AND DISCUSSION

#### 4.1. Partial Frequency Dynamic Convolution

The results of PFD conv using various proportion is shown in Table 1. From the table, PFD-CRNN (1/N) denotes that 1/N of output channel by FDY conv module and the rest of the channels are from static convolution. We experimented PFD conv with 1/32, 1/16 and n/8 where n = 1, 2, ..., 7 as the number of channels on CNN module in CRNN is multiple of 32; 32, 64, 128, 256, 256, 256, 256 from 1st to 7th convolution layers. Note that FDY-CRNN is equivalent to PFD-CRNN with proportion 8/8. The results show that with a proportion above 1/8, PFD-CRNN's PSDS is slightly worse or similar to that of FDY-CRNN, except for the model with a proportion 5/8. But PFD-CRNNs with proportion 1/16and 1/32 perform worse than FDY-CRNN. The most efficient model is PFD-CRNN with proportion 1/8, which only introdue 22.0% of additional parameters to CRNN and reduces 51.9% of parameters from FDY-CRNN while retaining the performance by FDY-CRNN.

#### 4.2. Multi-Frequency Dynamic Convolution

To test the effect of multiple FDY conv modules without dilation, we experimented with MDFD conv without dilation

Fable 3.	Performance	of multi-dilated	frequency	dynamic
convolutio	on models with	n varving dilation	size sets.	

models	Dilation	PSDSI	
FDY-CRNN	(1)	0.441	
PFD-CRNN (1/8)	(1)	0.442	
MFD-CRNN (1/8)	(1)×5	0.449	
MDFD-CRNN (1/8)	(1)×4+(2)	0.449	
MDFD-CRNN (1/8)	(1)×4+(3)	0.448	
MDFD-CRNN (1/8)	$(1) \times 4 + (2,2)$	0.448	
MDFD-CRNN (1/8)	$(1) \times 4 + (2,3)$	0.451	
MDFD-CRNN (1/8)	$(1) \times 4 + (3,3)$	0.446	
MDFD-CRNN (1/8)	$(1) \times 4 + (2,2,3)$	0.446	
MDFD-CRNN (1/8)	$(1) \times 4 + (2,3,3)$	0.451	
MDFD-CRNN (1/8)	$(1) \times 3 + (2,3) \times 2$	0.448	
MDFD-CRNN (1/8)	$(1) \times 3 + (2,2,3) \times 2$	0.449	
MDFD-CRNN (1/8)	$(1) \times 3 + (2,3,3) \times 2$	0.450	
MDFD-CRNN (1/8)	$(1) \times 3 + (2,3) + (2,3,3)$	0.451	
MDFD-CRNN (1/8)	(1)×2+(2,3)×3	0.449	
MDFD-CRNN (1/8)	$(1) \times 2 + (2,2,3) \times 3$	0.452	
MDFD-CRNN (1/8)	$(1) \times 2 + (2,3,3) \times 3$	0.447	
MDFD-CRNN (1/8)	$(1) \times 2 + (2,3) + (2,2,3) + (2,3,3)$	0.447	

in this subsection. We call this module as multi-frequency dynamic convolution (MFD conv). The result is shown in Table 2, where #DYbr stantds for the number of dynamic branches. Four 1/32 and two 1/16 FDY modules are tested to verify if 1/8 of dynamic output channels are beneficial, but the results show that 1/8-sized FDY module is minimum that does not harm the performance compared to FDY conv. Furthermore, we experimented on multiple 1/8-sized FDY modules for further performance enhancement. The results is that five and six branches improve SED performance, while still lighter than FDY conv model. This results demonstrates that multiple dynamic branches enhances SED performance, possibly by learning different dynamic pattern recognition by each branch. Also, we infer from the results that minimum required static branch channel proportion is  $1/4 \sim 3/8$  since less proportion deteriorates the performance.

#### 4.3. Multi-Dilated Frequency Dynamic Convolution

By introducing dilation to the MFD-CRNN model with five dynamic branches which showed good size to performance compromise, we experimented on dilating some of five dynamic branches in order to diversity the roles by different dynamic branches. The results are shown in Table 3, where dilation is notated to show only frequency-wise dilation and dilation size of 1 (meaning no dilation) is omitted. All dynamic branches have four basis kernels. For example,  $(1) \times$  $3 + (2,3) \times 2$  means 3 dynamic branches are not dilated and two dynamic branches have 2 non-dilated basis kernel, one basis kernel with dilation size of 2 and the last basis kernel with dilation size 3. Application of dilation results in similar or slightly better performance as in [13]. While ap-

models	# Channels	Dilation	Params(M)	PSDS1
FDY-CRNN	8/8 (32,64,128,256)	(1)	11.061	0.441
DFD-CRNN	8/8 (32,64,128,256)	(2,3)	11.061	0.448
PFD-CRNN (1/8)	8/8 (32,64,128,256)	(1)	5.401	0.442
MFD-CRNN (1/8)	8/8 (32,64,128,256)	(1)×5	9.296	0.449
MDFD-CRNN (1/8)	8/8 (32,64,128,256)	$(1) \times 2 + (2,3) + (2,2,3) + (2,3,3)$	9.296	0.447
FDY-CRNN	11/8 (44,88,176,352)	(1)	19.317	0.434
MDFD-CRNN (1/8)	11/8 (44,88,176,352)	(1)×8	18.157	0.449
MDFD-CRNN (1/8)	11/8 (44,88,176,352)	$(1) \times 5 + (2,3) + (2,2,3) + (2,3,3)$	18.157	0.455
MDFD-CRNN (1/8)	14/8 (56,112,224,448)	$(1) \times 5 + (2,2) + (3,3) + (2,2,3,3) + (2,3) + (2,2,3) + (2,3,3)$	30.894	0.433

Table 4. Performance of multi-dilated frequency dynamic convolution models with pre-convolution and varying channel sizes.

plication of dilation adds new expanded and diversified dynamic branches, it removes the FDY branch without dilation so it might increase and decrease the performance at the same time. We interpret the results that as much as DFD conv branch benefits SED, FDY conv branch also contributes well.

# 4.4. Multi-Dilated Frequency Dynamic Convolution with Pre-convolution and Varying Channel sizes

We experimented the effect of additionally introduced dynamic branches with expanded channel sizes in Table 4. In addition, to further enhance the performance, pre-convolution module with output channel size of 16 is added in front of CNN module to add MDFD conv to 1st convolution layer. Without pre-convolution, the input channel size of 1st convolution layer is one, thus it is meaningless to extract Kfrequency-adaptive attention weights from single channel. Addition of three dilated dynamic branches with varying dilation sizes results in PSDS1 of 0.455, which outperforms FDY-CRNN by 3.2%. With post-processing, it could be further enhanced. However, adding six dilated dynamic branches results in worse performance, showing that too many dynamic branches rather harms the performance. While it involves far more parameters, the results show that several dynamic branches without dilation helps the performance and adding right amount of dilated dynamic branches enhances the performance.

#### 4.5. MDFD Conv on SED with Heterogeneous Datasets

To compare the performance of MDFD conv with state-ofthe-art models, we implemented MDFD conv on DCASE 2024 challenge Task 4 baseline and included audio models pre-trained on external dataset (BEATs and audio teacher student transformer) [21, 22, 23, 24] as shown in Table 5. Change-detection-based sound event bounding boxes (cSEBBs) is used as post-processing. Self-training using AudioSet further enhances the performance. Evaluation metric used is true PSDS1 [25]. The resultant model outperforms last years DCASE challenge winner without ensemble [6]. Also, ABC+MDFD-CRNN best model performs close to ATST-SED model with fine-tuning ATST-frame [24]. With finetuning of ATST-frame or additional AudioSet for training, **Table 5.** Performance of MDFD-CRNN with pre-trained audio models. Pp, mf and cw stand for post processing, median filter and class-wise. ABC stands for model with ASTS, BEATs and CRNN. Other state-of-the-art models are the models trained without additional AudioSet.

models	PP	tPSDS1
FDY-LKA-CRNN + BEATs [6]	cw mf	0.525
CRNN + ATSTframe (frozen) [24]	cw mf	0.492
CRNN + ATSTframe (fine-tuned) [24]	cw mf	0.583
ABC	mf	0.507
ABC + PFD-CRNN (1/8)	mf	0.517
ABC + MDFD-CRNN (1/8)	mf	0.524
ABC	cSEBBs	0.546
ABC + PFD-CRNN (1/8)	cSEBBs	0.558
ABC + MDFD-CRNN (1/8)	cSEBBs	0.577

ABC+MDFD-CRNN best model is expected to be further enhanced [24, 21].

# 5. CONCLUSION

To reduce the model size of FDY-CRNN, proposed partial frequency dynamic convolution concatenates output of FDY conv module and conventional static 2D convolution module. As a result, by applying FDY conv to only 1/8 of the channel output, PFD-CRNN reduced the number of parameters by 51.9% compared to FDY-CRNN. In addition, by introducing more dynamic branches, we introduced multi-frequency dynamic convolution module to further enhance PSDS1 from 0.441 to 0.452. Proposed multi-dilated frequency dynamic convolution applies dilation to multiple dynamic branches to further enhance the performance. The best model in this work achieves PSDS1 of 0.455, outperforming FDY-CRNN by 3.2%. Extensive ablation studies showed that minimum proportion of dynamic branches is 1/8, minimum proportion of static branch is  $1/4 \sim 3/8$ , and non-dilated FDY conv branches also help performance thus additional DFD conv branches could be used to further enhance the performance. Implementation of MDFD-CRNN on DCASE 2024 challenge Task 4 baseline shows comparable performances to previous state-of-the-art models without additional AudioSet.

# 6. REFERENCES

- Tuomas Virtanen, Mark D. Plumbley, and Dan Ellis, *Computational Analysis of Sound Scenes and Events*, pp. 3–11, 71–77, Springer Publishing Company, Incorporated, 1st edition, 2017.
- [2] Nicolas Turpault, Romain Serizel, Ankit Parag Shah, and Justin Salamon, "Sound event detection in domestic environments with weakly labeled data and soundscape synthesis," in Workshop on Detection and Classification of Acoustic Scenes and Events, 2019.
- [3] Emre Çakır, Giambattista Parascandolo, Toni Heittola, Heikki Huttunen, and Tuomas Virtanen, "Convolutional recurrent neural networks for polyphonic sound event detection," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 25, no. 6, pp. 1291– 1303, 2017.
- [4] Koichi Miyazaki, Tatsuya Komatsu, Tomoki Hayashi, Shinji Watanabe, Tomoki Toda, and Kazuya Takeda, "Convolution-augmented transformer for semisupervised sound event detection," Tech. Rep., DCASE2020 Challenge, 2020.
- [5] Xu Zheng, Han Chen, and Yan Song, "Zheng ustc team's submission for dcase2021 task4 – semisupervised sound event detection," Tech. Rep., DCASE2021 Challenge, 2021.
- [6] Ji Won Kim, Sang Won Son, Yoonah Song, Hong Kook Kim, Il Hoon Song, and Jeong Eun Lim, "Semisupervised learning-based sound event detection using frequency dynamic convolution with large kernel attention for DCASE challenge 2023 task 4," Tech. Rep., DCASE2023 Challenge, 2023.
- [7] Hyeonuk Nam, Seong-Hu Kim, Byeong-Yun Ko, and Yong-Hwa Park, "Frequency Dynamic Convolution: Frequency-Adaptive Pattern Recognition for Sound Event Detection," in *Proc. Interspeech*, 2022.
- [8] Shengchang Xiao, Xueshuai Zhang, and Pengyuan Zhang, "Multi-dimensional frequency dynamic convolution with confident mean teacher for sound event detection," in *International Conference on Acoustics*, *Speech and Signal Processing (ICASSP)*, 2023.
- [9] Kang Li, Yan Song, Li-Rong Dai, Ian McLoughlin, Xin Fang, and Lin Liu, "ast-sed: an effective sound event detection method based on audio spectrogram transformer," in *International Conference on Acoustics*, *Speech and Signal Processing (ICASSP)*, 2023.
- [10] Hyeonuk Nam, Seong-Hu Kim, Deokki Min, and Yong-Hwa Park, "Frequency & channel attention for computationally efficient sound event detection," in *Workshop*

on Detection and Classification of Acoustic Scenes and Events, 2023.

- [11] Shengchang Xiao, Jiakun Shen, Aolin Hu, Xueshuai Zhang, Pengyuan Zhang, and Yonghong Yan, "Sound event detection with weak prediction for dcase 2023 challenge task4a," Tech. Rep., DCASE2023 Challenge, 2023.
- [12] Deokki Min, Hyeonuk Nam, and Yong-Hwa Park, "Auditory neural response inspired sound event detection based on spectro-temporal receptive field," in Workshop on Detection and Classification of Acoustic Scenes and Events, 2023.
- [13] Samuele Cornell, Janek Ebbers, Constance Douwes, Irene Martín-Morató, Manu Harju, Annamaria Mesaros, and Romain Serizel, "Diversifying and expanding frequency-adaptive convolution kernels for sound event detection," arXiv preprint arXiv:2406.05341, 2024.
- [14] Yinpeng Chen, Xiyang Dai, Mengchen Liu, Dongdong Chen, Lu Yuan, and Zicheng Liu, "Dynamic convolution: Attention over convolution kernels," in *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.
- [15] Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz, "mixup: Beyond empirical risk minimization," in *International Conference on Learning Representations*, 2018.
- [16] Daniel S. Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D. Cubuk, and Quoc V. Le, "SpecAugment: A Simple Data Augmentation Method for Automatic Speech Recognition," in *Proc. Interspeech*, 2019.
- [17] Hyeonuk Nam, Seong-Hu Kim, and Yong-Hwa Park, "Filteraugment: An acoustic environmental data augmentation method," in *International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2022.
- [18] Çağdaş Bilen, Giacomo Ferroni, Francesco Tuveri, Juan Azcarreta, and Sacha Krstulović, "A framework for the robust evaluation of sound event detection," in *International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2020, pp. 61–65.
- [19] Hyeonuk Nam, Byeong-Yun Ko, Gyeong-Tae Lee, Seong-Hu Kim, Won-Ho Jung, Sang-Min Choi, and Yong-Hwa Park, "Heavily augmented sound event detection utilizing weak predictions," Tech. Rep., DCASE2021 Challenge, 2021.
- [20] Janek Ebbers, Francois G. Germain, Gordon Wichern, and Jonathan Le Roux, "Sound event bounding boxes," *arXiv preprint arXiv:2406.04212*, 2024.

- [21] Jort F. Gemmeke, Daniel P. W. Ellis, Dylan Freedman, Aren Jansen, Wade Lawrence, R. Channing Moore, Manoj Plakal, and Marvin Ritter, "Audio set: An ontology and human-labeled dataset for audio events," in 2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2017.
- [22] Sanyuan Chen, Yu Wu, Chengyi Wang, Shujie Liu, Daniel Tompkins, Zhuo Chen, Wanxiang Che, Xiangzhan Yu, and Furu Wei, "Beats: Audio pre-training with acoustic tokenizers," in *International Conference on Machine Learning*, 2023.
- [23] Xian LI and Xiaofei Li, "Atst: Audio representation learning with teacher-student transformer," in *Proc. Interspeech*, 2022.
- [24] Nian Shao, Xian Li, and Xiaofei Li, "Fine-tune the pretrained atst model for sound event detection," in *International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2024.
- [25] Janek Ebbers, Reinhold Haeb-Umbach, and Romain Serizel, "Threshold independent evaluation of sound event detection scores," in *International Conference* on Acoustics, Speech and Signal Processing (ICASSP), 2022.