Similarity-aware Syncretic Latent Diffusion Model for Medical Image Translation with Representation Learning.

Tingyi Lin¹, Pengju Lyu^{1,4}, Jie Zhang², Yuqing Wang³, Cheng Wang¹, and Jianjun Zhu^{1,3,*}

¹ Hanglok-Tech Co., Ltd., Hengqin 519000, China

² Guangdong Provincial Key Laboratory of Tumor Interventional Diagnosis and Treatment, Zhuhai People's Hospital, Zhuhai Hospital Affiliated with Jinan

University, Zhuhai Guangdong 519000, China.

³ Center of Interventional Radiology & Vascular Surgery, Department of Radiology, Zhongda Hospital, Medical School, Southeast University, Nanjing 210009, China.

⁴ City University of Macau, Macau 999078, China.

* corresponding author: jj.zhu@hanglok-tech.cn

Abstract. Non-contrast CT (NCCT) imaging may reduce image contrast and anatomical visibility, potentially increasing diagnostic uncertainty. In contrast, contrast-enhanced CT (CECT) facilitates the observation of regions of interest (ROI). Leading generative models, especially the conditional diffusion model, demonstrate remarkable capabilities in medical image modality transformation. Typical conditional diffusion models commonly generate images with guidance of segmentation labels for medical modal transformation. Limited access to authentic guidance and its low cardinality can pose challenges to the practical clinical application of conditional diffusion models. To achieve an equilibrium of generative quality and clinical practices, we propose a novel Syncretic generative model based on the latent diffusion model for medical image translation (S²LDM), which can realize high-fidelity reconstruction without demand of additional condition during inference. S²LDM enhances the similarity in distinct modal images via syncretic encoding and diffusing, promoting amalgamated information in the latent space and generating medical images with more details in contrast-enhanced regions. However, syncretic latent spaces in the frequency domain tend to favor lower frequencies, commonly locate in identical anatomic structures. Thus, S²LDM applies adaptive similarity loss and dynamic similarity to guide the generation and supplements the shortfall in high-frequency details throughout the training process. Quantitative experiments confirm the effectiveness of our approach in medical image translation. Our code will release lately.

Keywords: Image translation · Latent diffusion model · Representation learning · Cosine similarity.

T. Lin et al.

1 Introduction

Computerized Tomography (CT) imaging technology provides non-invasive, detailed cross-sectional images for clinical observation, disease diagnosis, and treatment guidance. Contrast-enhanced CT (CECT) with CT angiography (CTA) specializes in vascular imaging[6], effectively enhancing regions of interest, such as vascular lesions or other organs lesions. Despite its diagnostic benefits, CTA's reliance on intravascular injection of costly iodinated contrast agents (ICAs) poses risks for patients with iodine allergy and renal insufficiency, limiting its clinical application[1]. Therefore, obtaining CECT-like images from NCCT images can reduce reliance on ICAs and deliver more precise pathological details, with potential for further development.

Generally, the diagnostic process for hepatic diseases involves multi-phase CECT images such as arterial and venous phases. In contrast to the NCCT images, the former emphasizes vascular enhancement, while the latter focuses on enhancing relevant organs or tissues. Emphasizing subtle yet crucial distinctions between NCCT images and images from other phases is imperative for generating CECT-like images, which ensure a comprehensive and accurate depiction of vascular and organ structures.

In recent years, significant progresses have been achieved in medical image translation based on deep learning methods, particularly among generative adversarial network models[17][4] and diffusion models[14][9]. Chandrashekar et al.[2] uses a 2D Cycle-GAN[18] for generating arterial phase aneurysmal sections, through which can discriminate lumen and intra-luminal thrombus. In 3D medical image translation, Choi et al. uses 3D Pix2pix[7] to convert noncontrast thoracic CT to CECT images with a better depiction of mediastinal lymph nodes. Khader et al.[8] shows that diffusion probabilistic models can synthesize high quality MRI and CT images, which can be used in breast segmentation. Wang et al.[16] takes latent diffusion models as generative prior for high resolution MRI reconstruction.

Although many diffusion model have demonstrate their great transformation ability in medical image translation, most of which are overlooking that mutual representation with multi-modal images information. Actually, different modalities for the same anatomy should share similar representation distributions, with disparities highlighting contrast-enhanced regions, crucial for emphasizing in synthesize images. Instead of solely taking target images as ground truth for model training, we leverage pertinency of both two modal images during encoding. Concretely, we design an adaptive similarity loss based on representation learning to converge model's generation towards disparities. Such a simple yet effective approach enhances mutual representation in latent spaces, indicating contrast-enhanced regions without conditional guidance and achieving equal emphasis on these areas. Considering generation capability during training, we incorporate a dynamic similarity mask, which aids early model fitting to structural regions and later fitting to contrast-enhanced regions.

The contributions of our model include: (1) we explore the relation between contrast-enhanced regions and representation similarity in latent space to optimize generation tendency. (2) we propose a novel similarity-guided diffusion model with designed syncretic autoencoder. (3) The S²LDM has successfully synthesized high-quality CECT-like images by leveraging the unique modalities of both NCCT and CECT images.

2 Method

In this section, we outline our data acquisition and processing in Sec.2.1 first. Secondary, we provide an overview of our proposed method in Sec.2.2. Third, we describe our designed multi-modal images compression method in Sec.2.3. Finally, we introduce a strategy regarding similarity-guided diffusion model in Sec.2.4.

2.1 Database

We evaluate our proposed method on an in-house multi-phase abdomen CT datasets (MP-ACT), which contains 164 pairs of non-contrast and arterial phase images, as well as 170 pairs of non-contrast and venous phase images. The MP-ACT datasets is methodically split into training and validation subsets, maintaining a 4:1 ratio for both arterial and venous phases (training data: 132 (A) and 136 (V), validation data: 32 (A) and 34 (V)). For achieving uniformity in grayscale range, we set all original data to window width to 400 HU (Houndfield Unit) and window level to 0 HU. Furthermore, we perform random cropping on all training data patches, each of size $256 \times 256 \times 48$.

2.2 Method Architecture

The limitations of individual generative approaches arise from their tendency to allocate an excessive capacity to self-modeling, or their insufficient efficiency in capturing subtle yet high-frequency details in medical images. To address this, numerous studies have adopted a two-stage approach, guaranteeing highfidelity generations while afford enough perceptual information to the secondstage generative model. Following the design of LDM[15], we propose a medical image translation model in a two-stage as depicted in Fig.1.

Assuming that the pairwise training subsets $\{(x_n, x_c)\}_{i=1}^M$ consists of equal number of non-contrast and contrast-enhanced CT images, our goal is to train an high-fidelity generative model to transform x_n into x_c . In subgraph (A) of Fig.1, we first train an autoencoder to provide a low-dimensional and representative latent space, symbolically equivalent to the pixels space. Instead of using contrast-enhanced CT images for conditional guidance, we take pair of them as input to the syncretic encoder \mathcal{E} , and accordingly generate reconstructed contrast-enhanced CT image \tilde{x}_c from the CECT decoder \mathcal{D} .

It is noteworthy that both embeddings of non-contrast and contrast-enhanced CT images are obtained after encoding, and the similarity between these two embeddings are further utilized in latent space. Representations from different



Fig. 1. Diagram of our proposed Syncretic Latent Diffusion Model. (A) illustrates the pixels space for our generation CECT images from latent space, while (B) illustrates the diffusion and denoising processes of similarity-guided embeddings.

phases but of the same anatomy tend to converge, making similarity a useful distribution for analyzing non-contrast and contrast-enhanced regions.

2.3 Image Compression

Adhering to established clinical protocols, surgeons commonly prefer to noncontrast CT images rather than contrast-enhanced CT images. However, many previous studies overlook the opportunity to fully leverage multi-modal images within the constraints of clinical applications. Considering the aforementioned factors, we combine the embeddings of the two modal images using the designed syncretic encoder \mathcal{E} to enhance their mutual representation through representation learning. As depicted in Fig.2, the proposed syncretic encoder contains two identical architectures, both of which share the same weight during training.

Drawing inspiration from Chen et al.[3], our objective is to maximize the similarity between embeddings E_n and E_c derived from the same anatomy in dual-phase CT images. This endeavor is undertaken to bolster the perceptual information extracted from multi-modal images. Moreover, we also argue that the dissimilarity among mutual embeddings matters to the generation of target images, particularly in regions that contrast-enhanced. we have made slight modifications to the focal loss[12], tailoring the feature-wise similarities loss more focus on dissimilar and contrast-enhanced regions. The formulation is as follows,

$$L_{sim} = -\frac{1}{|Embs|} \sum_{i=1}^{Embs} (\frac{1 - \langle E_n^i, E_c^i \rangle}{2})^{\gamma} \log(\frac{1 + \langle E_n^i, E_c^i \rangle}{2}),$$
(1)



Fig. 2. Diagram of our image compression model with syncretic encoder. The right subgraph illustrates the model's distinct compression strategies during the training and validation process.

where E_n^i and E_c^i are elements from the set *Embs*, representing the feature-wise similarities. $\langle \cdot, \cdot \rangle$ denotes the cosine similarity between two distinct embeddings in the latent space, whose range is [-1, 1]. γ a constant to assign adaptive weights to feature-wise similarities. In this paper, we set $\gamma = 1$.

Apart from the aforementioned similarity loss, our image compression model is based on VQ-GAN[5], is trained using reconstruction loss, quantization loss based on generative objectives, and patch-based adversarial objectives. Hence, our syncretic generative model is trained via minimize sum of total loss L_{auto} during autoencoder training process, as illustrated in Fig.2. The loss is formulated as follows,

$$L_{auto} = \lambda_r L_{rec}(x_F, \tilde{x}_c) + \lambda_q L_{quan}(E_c, E_c) + \lambda_s L_{sim}(E_c, E_n), \tag{2}$$

where λ_r , λ_q and λ_s represent the weights of L_{rec} , L_{quan} and L_{sim} , respectively. x_F denotes contrast-enhanced CT images following high-frequency enhancement.

To sum up, the encoder \mathcal{E} is specifically crafted for dual-encoding noncontrast and contrast-enhanced CT images during training but is capable of performing translation tasks relying solely on non-contrast CT image. Additional details about the two distinct strategies are also presented in the right subgraph of Fig.2.

2.4 Latent Diffusion Model

A typical resolution to mitigate excessive computational burden in reconstructing images in pixel space is to compress them into latent space. Several notable studies have demonstrated the efficacy of diffusion models in high-resolution image synthesis without incurring excessive computational costs. With the objective of transforming one modality image into another, most diffusion models directly incorporate the target image as an additional input during the second stage of model training. While this design has demonstrated superior results, 6 T. Lin et al.

we propose that including them in autoencoder training and subsequently utilizing their embeddings in the diffusion process can achieve comparable or even superior performance.

Following this intuition, we introduce a series of adjustments to refine the two embeddings within the diffusion model with similarity guidance. Concretely, given two embeddings E_n and E_c from different modalities, we utilize a dynamic feature-wise similarity mask S with the same shape to iteratively focus on regions of interest at current epoch. Obviously, our intention is to enhance the representativeness of E_n in the contrast-enhanced regions, therefore, it becomes imperative to gradually guide the model to transfer large and high-similarity regions to small and low-similarity regions during diffusion model training. The formulation of S is as follows,

$$S = \min\left[\alpha \frac{\tau}{\mathcal{T}} + \frac{1 + \langle E_n, E_c \rangle}{2}, 1\right], \tag{3}$$

where τ and \mathcal{T} represents the current epoch and total epochs respectively. \mathcal{S} represents the dynamic cosine similarity between the corresponding embeddings from non-contrast and contrast-enhanced CT images at epoch τ . α is a constant that controls the rate of changes in similarity and is set to 2.

In medical image translation, conditional diffusion models utilize a condition autoencoder for synthesis control, with guidance from conditions such as target modal images and segmentation. Different with these methods, we turn the additional information at the beginning of diffusion to facilitate the original embedding, making it more flexible to control synthesis process. Specifically, we employ feature-wise multiplication to reinforce the direction we anticipate with dynamic similarity guidance. Bases on non-contrast and contrast-enhanced CT images pairs, we optimize the model via,

$$L_{diff} := \mathbb{E}_{\mathcal{E}(x_n, x_c), \epsilon \sim \mathcal{N}(0, 1), t} \left[\left| \left| \epsilon - \epsilon_{\theta}(E_n \otimes \mathcal{S}, t) \right| \right|_2^2 \right], \tag{4}$$

where \otimes denotes feature-wise multiplication, and t is uniformly sampled from $\{1, \dots, T\}$.

Similar to the validation process of the syncretic autoencoder, we also accomplish image generation solely based on non-contrast CT images through a straightforward process that converts the feature-wise similarity mask into an all-ones matrix.

3 Experiments

3.1 Implementation details

For both syncretic autoencoder and diffusion model training, our designed twostage models utilize the MP-ACT dataset (introduced in Sec.2.1). The image compression employs VQ-GAN, and the diffusion model is based on LDM, implemented using PyTorch¹ and MONAI² libraries. During autoencoder training,

¹ https://pytorch.org/

² https://monai.io/

we set batch size as 1 including one pair of two phases CT image during autoencoder training, while adapt AdamW optimizer with an initial learning rate of 2×10^{-6} for 1000 iterations on two A800 GPUs. During diffusion model training, we set batch size as 2 and times steps as 1000 for 5000 iterations on three A6000 GPUs. To evaluate our proposed method, we adopt Normalized Mean Absolute Error (NMAE), Peak Signal-to-Noise Ratio (PSNR) and Structural Similarity Index Measure (SSIM) to evaluate the generation quality.

3.2 Comparison with exciting model

To prove our method's validity, we conduct comparative experiments with following state of the art generative model in Tab.1 on our in-house MP-ACT datasets. All of experiments are designed to perform images translation between two different phases: from NCCT images to arterial and venous phase CECT images. While other models evaluate performance by taking both source and target images as inputs, exclusively employ non-contrast CT images for the image translation tasks.

Table 1. Comparison with existing methods on MP-ACT datasets

Method	$NCCT \Rightarrow CECT (A)$			$NCCT \Rightarrow CECT (V)$			
	$\mathrm{NMSE}\downarrow$	$\mathrm{PSNR}\uparrow$	$\mathrm{SSIM}\uparrow\big $	$\mathrm{NMSE}\downarrow$	$\mathrm{PSNR}\uparrow$	$\mathrm{SSIM}\uparrow$	
Zhu et al.[18]	0.146	25.03	0.796	0.161	24.67	0.804	
Isola et al.[7]	0.132	24.77	0.819	0.155	24.84	0.818	
Kong et al.[11]	0.108	25.86	0.854	0.129	25.31	0.857	
Lyu et al.[13]	0.103	25.92	0.889	0.115	25.58	0.879	
Kim et al. $[10]$	0.098	26.19	0.872	0.123	25.36	0.862	
$S^{2}LDM$ (ours)	0.087	26.33	0.895	0.106	25.79	0.883	

As seen in Tab.1, our proposed method outperforms most of generative models in quantitative evaluations. In Fig.3, it is evident that the results obtained with S²LDM closely approximate realistic contrast-enhanced regions, particularly in vascular tissue. The green arrows distinctly illustrate the enhancement facilitated by our syncretic encoder and similarity-guided diffusion model in specific cases.

3.3 Ablation study

To validate the effectiveness of each component in our method, we conduct experiments shown in Tab.2, gradually ablating individual components of S²LDM. Specifically, we analyze the syncretic encoder \mathcal{E} , adaptive similarity loss \mathcal{L}_{sim} , and the dynamic similarity mask \mathcal{S} , examining their abilities during model training. The hyperparameters remain consistent in all ablation experiments.



Fig. 3. Visualization of results from S^2LDM and comparison models on venous phase.

Table 2. Ablation study on the effectiveness of various components in S^2LDM

Ablations	Various components				$ \qquad \text{NCCT} \Rightarrow \text{CECT} (V)$			
	E	\mathcal{L}_{sim}	S	1	$MSE\downarrow$	$\mathrm{PSNR}\uparrow$	SSIM \uparrow	
(a)					0.133	25.22	0.857	
(b)	\checkmark				0.127	25.43	0.862	
(c)	\checkmark	\checkmark			0.112	25.66	0.872	
(d)	\checkmark		\checkmark		0.120	25.64	0.865	
$S^{2}LDM$	\checkmark	\checkmark	\checkmark		0.106	25.79	0.883	

As observed in Tab.2, our baseline experiment (a) involves the original latent diffusion model without any additional components. In (b), we introduce \mathcal{E} during autoencoder training. For experiments (c) and (d), we individually incorporate \mathcal{L}_{sim} and \mathcal{S} based on (b). It is evident that each component contributes to the enhancement of medical image translation performance.

4 Conclusion

In this paper, we present a novel image translation model named S^2LDM , specifically designed for transformation from non-contrast CT images to contrastenhanced CT images. Building upon LDM, we further explore the application of similarity between two distinct modalities within diffusion model. Specifically, we incorporate a syncretic encoder to enhance proximity based on representation learning, coupled with adaptive similarity loss to emphasize dissimilarity during the training of the image compression model. Meanwhile, we emphasize on reinforcing contrast-enhanced regions in latent spaces, potentially manifesting as dissimilarities in two embeddings. To tackle this, we employ a dynamic similarity mask to gradually guide the model toward convergence in contrast-enhanced regions. Through comparisons and ablation studies, we validate the effectiveness of S^2LDM in medical image translation.

5 Acknowledgements

The study was supported by the National Natural Science Foundation of China (81827805, 82130060, 61821002, 92148205), National Key Research and Development Program (2018YFA0704100, 2018YFA0704104), Project funded by China Postdoctoral Science Foundation (2021M700772), Zhuhai Industry-University-Research Collaboration Program (ZH22017002210011PWC), Jiangsu Provincial Medical Innovation Center (CXZX202219), Collaborative Innovation Center of Radiation Medicine of Jiangsu Higher Education Institutions, Nanjing Life Health Science and Technology Project (202205045), and Jiangsu Province Science and Technology Support Project (BE2023769). The funding sources had no role in the writing of the report or the decision to submit the paper for publication.

References

- 1. Bae, K.T.: Intravenous contrast medium administration and scan timing at ct: considerations and approaches. Radiology **256**(1), 32–61 (2010)
- Chandrashekar, A., Shivakumar, N., Lapolla, P., Handa, A., Grau, V., Lee, R.: A deep learning approach to generate contrast-enhanced computerised tomography angiograms without the use of intravenous contrast agents. European Heart Journal 41(Supplement 2), ehaa946–0156 (2020)
- Chen, X., He, K.: Exploring simple siamese representation learning. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 15750–15758 (2021)
- Dalmaz, O., Yurt, M., Çukur, T.: Resvit: Residual vision transformers for multimodal medical image synthesis. IEEE Transactions on Medical Imaging 41(10), 2598–2614 (2022)
- Esser, P., Rombach, R., Ommer, B.: Taming transformers for high-resolution image synthesis. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 12873–12883 (2021)
- Hansen, N.J.: Computed tomographic angiography of the abdominal aorta. Radiologic Clinics 54(1), 35–54 (2016)
- Isola, P., Zhu, J.Y., Zhou, T., Efros, A.A.: Image-to-image translation with conditional adversarial networks. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 1125–1134 (2017)
- Khader, F., Müller-Franzes, G., Tayebi Arasteh, S., Han, T., Haarburger, C., Schulze-Hagen, M., Schad, P., Engelhardt, S., Baeßler, B., Foersch, S., et al.: Denoising diffusion probabilistic models for 3d medical image generation. Scientific Reports 13(1), 7303 (2023)
- Kim, B., Ye, J.C.: Diffusion deformable model for 4d temporal medical image generation. In: International Conference on Medical Image Computing and Computer-Assisted Intervention. pp. 539–548. Springer (2022)

- 10 T. Lin et al.
- Kim, J., Park, H.: Adaptive latent diffusion model for 3d medical image to image translation: Multi-modal magnetic resonance imaging study. In: Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision. pp. 7604–7613 (2024)
- Kong, L., Lian, C., Huang, D., Hu, Y., Zhou, Q., et al.: Breaking the dilemma of medical image-to-image translation. Advances in Neural Information Processing Systems 34, 1964–1978 (2021)
- Lin, T.Y., Goyal, P., Girshick, R., He, K., Dollár, P.: Focal loss for dense object detection. In: Proceedings of the IEEE international conference on computer vision. pp. 2980–2988 (2017)
- Lyu, J., Fu, Y., Yang, M., Xiong, Y., Duan, Q., Duan, C., Wang, X., Xing, X., Zhang, D., Lin, J., et al.: Generative adversarial network-based noncontrast ct angiography for aorta and carotid arteries. Radiology **309**(2), e230681 (2023)
- Özbey, M., Dalmaz, O., Dar, S.U., Bedel, H.A., Özturk, Ş., Güngör, A., Çukur, T.: Unsupervised medical image translation with adversarial diffusion models. IEEE Transactions on Medical Imaging (2023)
- Rombach, R., Blattmann, A., Lorenz, D., Esser, P., Ommer, B.: High-resolution image synthesis with latent diffusion models. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 10684–10695 (2022)
- Wang, J., Levman, J., Pinaya, W.H.L., Tudosiu, P.D., Cardoso, M.J., Marinescu, R.: Inversesr: 3d brain mri super-resolution using a latent diffusion model. In: International Conference on Medical Image Computing and Computer-Assisted Intervention. pp. 438–447. Springer (2023)
- Yu, B., Zhou, L., Wang, L., Shi, Y., Fripp, J., Bourgeat, P.: Ea-gans: edge-aware generative adversarial networks for cross-modality mr image synthesis. IEEE transactions on medical imaging 38(7), 1750–1762 (2019)
- Zhu, J.Y., Park, T., Isola, P., Efros, A.A.: Unpaired image-to-image translation using cycle-consistent adversarial networks. In: Proceedings of the IEEE international conference on computer vision. pp. 2223–2232 (2017)