# **REVEAL-IT: REinforcement learning with Visibility** of Evolving Agent poLicy for InTerpretability

Shuang Ao<sup>1</sup>, Simon Khan<sup>2</sup>, Haris Aziz<sup>1</sup>, Flora D. Salim<sup>1</sup>, University of New South Wales Sydney<sup>1</sup>; Air Force Research Laboratory<sup>2</sup>; {shuang.ao, haris.aziz, flora.salim}@unsw.edu.au, simon.khan@us.af.mil.

#### Abstract

Understanding the agent's learning process, particularly the factors that contribute to its success or failure post-training, is crucial for comprehending the rationale behind the agent's decision-making process. Prior methods clarify the learning process by creating a structural causal model (SCM) or visually representing the distribution of value functions. Nevertheless, these approaches have constraints as they exclusively function in 2D-environments or with uncomplicated transition dynamics. Understanding the agent's learning process in complicated environments or tasks is more challenging. In this paper, we propose REVEAL-IT, a novel framework for explaining the learning process of an agent in complex environments. Initially, we visualize the policy structure and the agent's learning process for various training tasks. By visualizing these findings, we can understand how much a particular training task or stage affects the agent's performance in test. Then, a GNN-based explainer learns to highlight the most important section of the policy, providing a more clear and robust explanation of the agent's learning process. The experiments demonstrate that explanations derived from this framework can effectively help in the optimization of the training tasks, resulting in improved learning efficiency and final performance.

### 1 Introduction

Reinforcement learning (RL) involves an agent acquiring the ability to make decisions within an environment to maximize the total reward obtained over a series of attempts. The recent achievements in resolving decision-making challenges prove the effectiveness of this paradigm, e.g., video games (Lillicrap et al., 2016; Mnih et al., 2015), robotic controlling (Kaelbling, 1993). Despite many remarkable achievements in recent decades, applying RL methods in the real world remains challenging. One of the main obstacles is that RL agents lack a fundamental understanding of the world and must, therefore, learn from scratch through numerous trial-and-error interactions. Nevertheless, the challenge of verifying and forecasting the actions of RL agents frequently impedes their use in real-world scenarios.

This difficulty is exacerbated when RL is paired with deep neural networks' generalization and symbolic power. Insufficient comprehension of the agent's functioning impedes the ability to intervene when needed or have confidence in the agent's rational and secure behavior. Explainability in RL refers to the ability to understand and interpret the decisions made by an RL agent. Explanations reflect the knowledge learned by the agent, facilitating in-depth understanding, and they also allow researchers to participate efficiently in the design and continual optimization of an algorithm (Miller, 2017). Recent work (Chen & Liu, 2023; Nielsen et al., 2008) in explaining RL models to gain insights into the agent's decision-making process. Some (Deshpande et al., 2020; Bellemare et al., 2017)

propose to understand the agent's action by visualizing the distribution of the value function or state value, which is straightforward but limited by the environments, i.e., the distribution of the learned value function is easy to understand in 2D environments but unfeasible in 3D environments.

A line of recent work in explanation and causal RL (Pearl, 1989; Rubin, 1974; Schölkopf et al., 2021) proposes to understand agent's behavior based on a single moment or a single action. Intuitively speaking, a one-step explanation is acceptable, but is it the best way to understand the agent's behavior? For example, Pearl (2009) proposes learning a causal model to understand what causes an agent to succeed or fail in a given task. However, establishing a causal model with precise causal assumptions in complex environments is challenging and inefficient (Martens et al., 2006; Sainani, 2018; Cui et al., 2020). On the other hand, this becomes more challenging in a long-horizon task as the agent must do hundreds of steps before accomplishing the task. Hence, we debate the definition of a good interpretability framework for providing explanations in RL. Firstly, to answer the question, "Why can an agent succeed or fail in a task?". Indeed, we may deduce the pertinent factors from the agent's training process. Similar to how we may make a general assessment of a person's test performance based on their learning process, an agent also requires certain abilities to accomplish a specific task. The agent's mastery of these abilities during the training process will directly impact its ability to effectively complete the task. Conversely, a proficient explanation can enhance the comprehension of the agent's actions and facilitate the agent's improvement of its performance (Schölkopf et al., 2021; Sontakke et al., 2020). Finally, an effective interpretability framework necessitates providing intuitive and comprehensible explanations.



Figure 1: The main structure of REVEAL-IT. Assume that we need to train an RL agent within an environment to accomplish complex tasks, while directly training the agent on these tasks is challenging and inefficient. In practical application, we will devise sequences of pre-defined sub-tasks (sub-task 1, sub-task 2,..., sub-task N) for training. In REVEAL-IT, we implement the RL agent in the given environment, allowing it to explore and collect data. Subsequently, we train the controller (the control policy  $\pi_{\theta}$ ), using the collected data. Then, we visualize the policy updates with a node-link diagram. The visualization will depict the structure of the policy and highlight the specific sections that have been updated. After that, REVEAL-IT employs a GNN-based explanation to examine policy updates and ascertain the significant capabilities that the policy has acquired in a certain sub-task. This will help us comprehend how much a sub-task has improved the agent's performance in the test. Furthermore, the GNN-based explainer provides a clearer and more accurate comprehension of the value of each sub-task in training. This can enhance the effectiveness and efficiency of designing RL training task sequences in real-world settings.

Based on the discussion about a good interpretability mechanism, we propose understanding the agent's performance after training from a more fundamental perspective, i.e., **the learning process of the policy and the sequences of training tasks**. By focusing on the policy and tasks, we may effectively mitigate this problem. They possess a minimum of three evident benefits: (1) Both the training tasks and the policy provide well-organized and generalizable information, allowing it to work in diverse environments. (2) The information presented in the policy is aligned with the agent's capacities. The limitation of the policy rests in our ability to extract intuitive explanations from the high-dimensional information it provides to understand the actions and behaviors of the agent. (3) When compared to SCM or counterfactual methods, which can not deal with the big and complicated problems that can not be seen in the real world, using structured training tasks as the

goal can solve this problem. This can be further enhanced by extracting relevant information from the policy. At this location, the agent's learning progress can serve as a temporal framework to enhance our comprehension of the agent's behavior.

Considering the preceding discussion, we propose a novel explanation framework, REVEAL-IT. This framework can visually represent updating the policy and the agent's learning process. Additionally, it can offer explanations for the training tasks. This paradigm facilitates a more intuitive comprehension of how agents acquire knowledge in various tasks, identifies which tasks are more efficient in training agents, and explains the reasons for their effectiveness. Simultaneously, this architecture can offer a dependable foundation for developing and optimizing the task sequences. In REVEAL-IT, we first adopt a node-link diagram to visualize the structure of the policy. This design enables humans to directly see the updates made by the RL agent during training. By doing so, we can gain insights into the reasons behind the agent's success or failure during testing. Simultaneously, we can also perceptibly observe and compare the components of the policy that exist autonomously or are common across several tasks in diverse training scenarios. This offers a visual foundation for aiding the design of training tasks in intricate contexts. Then, We adopt a GNN-based explainer that learns from the policy update process and subsequently analyzes its correlation with the policy's functionality during evaluation. This analysis aims to comprehend the connection between the behaviors performed during training and test. Note that while this explainer will not directly view the data collected from the environment, it is trained in sync with the RL agent. Essentially, we may consider the training of this explainer as a POMDP problem. In the experiments, we test REVEAL-IT in various environments, and the results demonstrate the ability to effectively elucidate the agent's learning process in the training task, optimize the sequence of tasks, and enhance the effectiveness of reinforcement learning.

# 2 Related Works

**Explainability for RL.** Explainable RL methods can be classified into two main groups: post hoc approaches and intrinsic approaches (Puiutta & Veith, 2020; Heuillet et al., 2020). Post hoc explanations are given after the model is executed, while intrinsic approaches inherently provide transparency. Post hoc explanations, such as the saliency map approach (Greydanus et al., 2017; Mott et al., 2019), frequently depend on correlations. Nevertheless, as previously stated, inferences made from correlations might be incorrect and inadequate in addressing causal inquiries. Conversely, intrinsic approaches like linear regression or decision trees can be used to provide intrinsic explanations. However, the modeling power of these algorithms may be insufficient to explain complicated behaviors effectively (Puiutta & Veith, 2020).

**Explanation in real world.** It is important to mention that the actual use of causal RL in real-world scenarios is still restricted. In order to enhance its broad applicability, it is imperative that we thoroughly analyze the obstacles presented by reality. Dulac-Arnold et al. (2020); Paduraru et al. (2021) have identified nine significant obstacles that are impeding the practical application of RL: restricted data samples; uncertain and substantial time delays; complex input with high dimensions; adherence to safety constraints; incomplete observability; multi-objective or unspecified reward functions; minimal time delays; learning from offline data; and the requirement for explainability. This paper will specifically cover the process of explaining RL in a high-dimensional environment.

**GNN Explainability.** Explainability is a major and necessary characteristic in the field of Graph Neural Network (GNN) study. We primarily focus on GNN explainability strategies that prioritize highlighting the important features of the input, rather than offering explanations at the model level. Gradient and feature-based approaches utilize gradients or feature values to evaluate the informativeness of various input features. For example, GRAD (Ying et al., 2019) and ATT (Velickovic et al., 2017) assess the significance of edges by utilizing gradients and attention weights, respectively. Perturbation-based techniques assess the significance of features by analyzing the performance of GNNs when subjected to different input perturbations (Luo et al., 2020; Ying et al., 2019; Yuan et al., 2021). For example, GNNExplainer (Ying et al., 2019) uses a method to learn a mask that explains each prediction individually, whereas PGExplainer (Luo et al., 2020) use a deep neural network to identify the most important connections across many predictions. SubgraphX (Yuan et al., 2021) is a perturbation approach that utilizes the Shapley values of features obtained from the MCTS algorithm to identify explanations. One recent method, RGExplainer (Shan et al., 2021), utilizes reinforcement learning to generate an explanation subgraph centered on a chosen beginning point. MATE (Spinelli et al., 2021), a novel meta-explanation technique that aims to enhance the interpretability of GNNs

during the training process. The objective is to enhance the comprehensibility of the GNN by iteratively training both the GNN itself and a baseline explanation, to acquire an internal representation of the GNN. MixupExplainer (Zhang et al., 2023), similar to our GNN-based explainer, seeks to address the problem of distributional shifts in explanations by combining an explanatory subgraph with a random subgraph. This leads to a clarification that is more closely in line with the graphs observed during the explanation phase.

# **3** Preliminaries

Our framework comprises of two parts. One is the RL policy visualization module that shows the policy update in training and policy activation in the test. This module is based on fully connected neural networks' well-established node-link diagram representation. The other is a GNN-based explainer, trained to analyze the visualized results in the first module and underly the important update in the training phase. We can further explore the relationship between different training tasks and the contribution of a specific training task/phase to the final performance. Now, we provide more details on these two parts:

#### 3.1 Reinforcement Learning and Visualization

**Reinforcement Learning.** The problem of controlling an agent can be modeled as a Markov decision process (MDP), denoted by the tuple { $S, A, P, R, \mu_0, \gamma$ }, where S and A represent the set of state space and action space respectively,  $P : S \times A \times S \rightarrow [0, 1]$  is the transition probability function that yields the probability of transitioning into the next state  $s_{t+1}$  after taking an action  $a_t$  at state  $s_t$ , and  $R : S \times A \rightarrow \mathbb{R}$  is the reward function that assigns the immediate reward for taking an action  $a_t$  at state  $s_t$ , and  $\gamma \in [0, 1]$  denotes the discount factor. We can use a deep RL algorithm to train the agent (e.g., DQN (Mnih et al., 2015), A2C (Mnih et al., 2016), SAC (Haarnoja et al., 2018b), PPO Schulman et al. (2017), etc.). In the experiments of this paper, we use DQN and PPO as the fundational RL methods. Note that any online RL algorithm can be accepted.

**Visualization.** The visualization should meet the following goals: summarize the unique properties of MLP networks in RL and reflect lessons learned from prior tasks. First, the visualization should handle networks large enough to solve complicated tasks. Second, the visualization should depict the network architecture with a node-link diagram. Third, the visualization should allow users to easily experiment with the input-output process of the network, allowing them to judge the network's robustness to translational variance, rotational variance, and ambiguous input. Fourth, the visualization should allow users to view details on individual nodes, such as the activation level, the calculation being performed, the learned parameters (i.e., the node's weights), and the numerical inputs and outputs. We choose to visualize the policy with a node-link diagram, and the only issue with a straightforward implementation of a node-link diagram is that large networks yield a dense mass of edges between layers. We base the visualization model on Harley (2015), which can choose to display some or all of the weights connected to a certain node, and you can record and correspond to the changes in the value of a specific part of the weights during the training process.

#### Algorithm 1 REVEAL-IT

1:	1: <b>Initialize:</b> control policy $\pi_{\theta}$ , RL replay buffer $\mathcal{B} \leftarrow \emptyset$ , RL update data $\mathcal{D} \leftarrow \emptyset$ , a set of training							
	tasks $\mathcal{D}_T$ , training tasks important score $y_T$ ;							
2:	for t in interations do							
3:	if $t = 1$ then	▷ Sample training task sequence						
4:	Randomly sample training task sequence $Seq_t$ in $\mathcal{D}_T$							
5:	else							
6:	Sample training tasks $Seq_t$ in terms of $y_T$							
7:	end if							
8:	RL exploration and collect data to $\mathcal{B}$ following $Seq_t$	▷ RL exploration						
9:	Update $\pi_{\theta}$ using samples from $\mathcal{B}$	_						
10:	Visualize policy update and save update information into 2	D ▷ Visualization						
11:	Train GNN to predict $y_T$ based on $\mathcal{D}$	▷ Train GNN explainer						
12:	end for	-						

#### 3.2 Background on GNN-based Explainer

This section establishes the notation and provides an overview of GNN's structured explainer. Assume that we have visualized the learning progress of the RL policy with node-link diagrams following Alg. 1. Let  $G_O$  denote the observed diagram on edges E (corresponding to the weights) and nodes V (corresponding to the node in the policy network) associated with D-dimensional node features  $\mathcal{X} = \{x_1, \dots, x_n\}, x_i \in \mathbb{R}^D$ , and  $v_i$  represents the *i*-th node in V. We use the training data of the RL policy to construct the training set for this GNN explainer. In this set, we will record the update information of the policy  $\pi_{\theta}$ , i.e., for a node  $v_T^i$  in the policy at time T, we denote the weights information connected with this node as  $\mathcal{X}_T^i$ , and denote the updated weights connected to this node  $v_T^i$  as  $\mathcal{X}_{T+1}^i$ . Thus, we can construct the dataset for training GNN explainer by calculating the update information by  $|\mathcal{X}_{T+1}^i - \mathcal{X}_T^i|$ .

The *l*-th layer of GNN explainer performs three essential computations: MESSAGE, AGGREGATE and UPDATE. The model first calculates the messages between every pair of nodes by  $m_{ij}^l = MESSAGE(h_i^{l-1}, h_j^{l-1}, r_{ij})$ , where  $h_i^{l-1}$  and  $h_j^{l-1}$  denote the node representations of  $v_i$  and  $v_j$ obtained from the previous layer l-1, respectively, and  $r_{ij}$  represents the relation between them. Next GNN aggregates the messages for each node  $v_i$  by  $m_i^l = AGGREGATE(m_{ij}^l|v_j \in \mathcal{N}(v_i))$ , where  $\mathcal{N}(v_i)$  refers to the neighborhood of  $v_i$ . Finally, the GNN explainer updates the node representation from the previous layer by  $h_i^l = UPDATE(m_i^l, h_i^{l-1})$ . The final embedding for node  $v_i$  after *L* layers of computation is  $z_i = h_i^L$ , which is then used for node classification, i.e., the understanding the critical nodes in the RL agent's evaluation is a crucial pre-requisite for determining the significance of weights updating.

## 4 REVEAL-IT

In REVEAL-IT, assume that we first have a randomly drafted subtask sequence for the RL policy training. We formulate the training scheme of REVEAL-IT as in Alg. 1. We start from the conventional RL training process, i.e., the agent will explore and interact with the environment, trying to complete each sub-task. After the agent collects data, we can apply any online RL algorithm to update the control policy. Subsequently, we will evaluate the performance of the current policy every fixed number of environmental steps the agent taken. Iterate this procedure until the agent acquires a specific quantity of policy update data, at which point we can train the GNN explainer.

The learning objective of GNN explainer on task. The overall goal of the GNN explainer is to learn to optimize the sequences of training tasks in terms of RL agent's learning progress. To achieve this, the GNN explainer needs to be able to predict how much improvement an agent can acquire from a task, i.e., this GNN explainer needs to understand the visualized policy updates collected from previous iterations. Based on the discussion in Sec. 3.2, we denote the prediction task of our GNN explainer as  $\Phi: G_O \rightarrow y$ , where y is the predicted improvement of the RL policy.

**Step 1. Understanding the visualized policy.** We first train the GNN explainer on the learning data collected from the RL. During the RL evaluation, the activated nodes in the policy will be tagged and utilized as the ground truth for the GNN explanation.

Note that the active nodes during evaluation will vary as the RL policy training progresses. This variability may raise issues regarding the stability of GNN's training. However, this problem is non-existent. This is because we require the GNN explainer to evaluate the significance of the training job by considering the RL agent's present level of learning progress. The active nodes in the evaluation and the collected environment reward reflect the capabilities of the current policy. When the policy is updated, especially when the agent's ability is increased, the different activated nodes and the increase in the environment reward can give the GNN predictor the information it needs. This enables the predictor to acquire knowledge on predicting agent's improvement based on the current learning process. Consequently, the GNN predictor can more precisely assess the value of the current training task.

Step 2. Highlight the important updates for explanations. As mentioned in Sec. 3.1, the control policy can be too complex to understand humans even with the visualized diagrams of the policy. Therefore, we also train the GNN explainer should highlight these important nodes and their related updates to humans to achieve a feasible explanation. The GNN explainer aims to partition  $G_O$  into

two subgraphs:

$$G_O = G_X + \Delta G,\tag{1}$$

where  $G_X$  represents the explanatory subgraph reflecting the important edges (corresponding to policy updates), and  $\Delta G$  is the remaining graph containing unimportant edges. When explaining a graph of visualized policy updates, we denote the optimal subgraph by  $G_X^m$ . When  $G_X^m$  is used as input to  $\Phi$ , it can retain the original prediction.  $G_X^m$  is optimal, as removing the features from it would result in a different prediction.

## **5** Experiments

We design our experiments to answer the following questions: (1) Can REVEAL-IT show the learning process of an RL agent in a given environment? (2) Can REVEAL-IT improve the learning efficiency of the agent based on the explanations? Our project can be viewed by: REVEAL-IT.

#### 5.1 Experiments Setup

**Environments.** We base our experiments on two types of benchmarks. The first one is **ALFWorld benchmark** (Shridhar et al., 2021), a cross-modality simulation platform encompassing a wide range of embodied household tasks. ALFWorld combines a textual environment with a visual environment that the Ai2Thor simulator (Kolve et al., 2017) renders for each task. This textual part uses the Planning Domain Definition Language (PDDL) (Ghallab et al., 1998) to turn each pixel observation from the simulator into a text-based observation that is equal to it. It then uses the TextWorld benchmark are categorized into six types: Pick &Place, Clean & Place, Heat & Place, Cool & Place, Look in Light, and Pick Two Objects & Place. Each task requires an agent to execute a series of text-based actions, such as "go to safe 1", "open safe 1", or "heat egg 1 with microwave 1", following a predefined instruction. These actions involve navigating and interacting with the environment. The other benchmark is evaluated in 6 OpenAI RL benchmark domains (Brockman et al., 2016), which are commonly adopted in RL tasks.

The complex tasks in ALFWorld. In ALFWorld, accomplishing a given task requires the agent to complete a sequential arrangement of sub-tasks step by step (as shown in Fig. 2). A task may entail interactions with more than 10 items and necessitate over 30 steps for a human expert to solve, thereby testing an agent's ability in long-term planning, following instructions, and using common knowledge. To facilitate a thorough comprehension, we have included an instance of each task category in the appendix in Fig. 4. Using the orginal tasks directly to train an RL agent is inefficient. Therefore, it is more suitable to use subtask training intuitively. However, this raises the question of how to structure the subtask sequence, specifically if the subtask sequence should remain consistent throughout the training process. What is the criteria for adjusting the subtask sequence? The crucial factor is determining the optimal subtask sequence that aligns with the agent's current training progress.

**Baselines.** The fundamental inquiry of REVEAL-IT is whether it can operate effectively in complex tasks and environments, i.e., does it have the ability to enhance the training efficiency of RL significantly? Can it be modified to suit various reinforcement learning techniques? Hence, we will focus on answering the first question in the ALFWorld. The baseline methods include MiniGPT-4 (Zhu et al., 2023), BLIP-2 (Li et al., 2023), LLaMA-Adapter (Gao et al., 2023) and InstrctBLIP (Dai et al., 2023). They share state-of-the-art and competitive performance in ALFWorld and solely interact with the visual world, aligning with the approach of REVEAL-IT. Our primary emphasis in the OpenAI RL benchmark was on the third question. We use PPO (Schulman et al., 2017), SAC (Haarnoja et al., 2018a), DQN (Mnih et al., 2015) as the fundamental RL algorithms to assess if REVEAL-IT can enhance training efficiency and performance across various approaches.

#### 5.2 Main Results

**Visualization of the learning process in ALFWorld.** In Figure. 2, we visualize the learning process of the RL policy in ALFworld. The RL policy we used in ALFworld is designed as an actor-critic structure consisting of two multi-layer prediction (MLP) networks as "actor" and "critic". Considering that when we evaluate or test the RL agents, the "actor" is responsible for making decisions, we

primarily focus on showcasing the learning process of this aspect of the policy. The actor-network consists of 4 fully connected layers, each including 64 nodes. We implemented ReLU function on the first and third layers to visually identify the activated nodes throughout the evaluation process.



Figure 2: The first line depicts the sequential arrangement of sub-tasks that must be accomplished in a step-by-step manner to fully accomplish a given task. One of the sub-tasks is located on the left side of the second line. The first to third columns of the tree diagram illustrate the RL policy update process. The blue circles represent nodes in the neural network, while the connections between the circles represent weight updates. Thicker connections indicate larger updates in weight amplitude (selected by GNN explainer). The red circles in the tree diagram on the far right illustrate the specific policy nodes that are active during the evaluation process. The links here represent the revised weights throughout the training phase of this subtask. The orange squares indicate the portions of the policy that are common to several sub-tasks. We opt to depict the 8 interconnected nodes with the most significant weight adjustment, facilitating comprehension of the reinforcement learning policy's learning process and highlighting the policy's shared component more distinctly.

**REVEAL-IT brings improvement.** We report the performance of REVEAL-IT on the ALFWorld benchmark in Tab. 1 and compare it to the performance of 7 other representative agents. We report the performance on the OpenAI benchmark in Tab. 2. Given that REVEAL-IT exclusively engages with the visual engine within ALFWorld, the baseline agents similarly only interact with the visual environment, aligning with their configurations as stated in the original paper. We evaluate the primary metric: the success rate, defined as the proportion of completed trials. REVEAL-IT demonstrates significantly better performance than other VLM agents, establishing its superiority. Notably, REVEAL-IT does not rely on LLM agents, unlike other baseline models that utilize pretrained LLM agents to generate planning steps using ALFWorld's text engine during the training phase. This demonstrates that the GNN-based explanation efficiently optimizes the sequence of tasks and significantly enhances the agent's training.

Agent	Success Rate						
Agent		Pick	Clean	Heat	Cool	Look	Pick2
ResNet- 18* (Shridhar et al., 2020)	0.06	-	-	-	-	-	-
MCNN-FPN* (Shridhar et al., 2020)	0.05	-	-	-	-	-	-
MiniGPT-4 (Zhu et al., 2023)	0.16	0.04	0.00	0.19	0.17	0.67	0.06
BLIP-2 (Dai et al., 2023)	0.04	0.00	0.06	0.04	0.11	0.06	0.00
LLaMA-Adapter (Gao et al., 2023)	0.13	0.17	0.10	0.27	0.22	0.00	0.00
InstructBLIP (Dai et al., 2023)	0.22	0.50	0.26	0.23	0.06	0.17	0.00
PPO (Schulman et al., 2017)	0.04	0.01	0.05	0.04	0.07	0.03	0.00
<b>REVEAL-IT</b> (Ours)	0.80	0.66	0.90	0.81	0.80	0.85	0.70
Human Performance*		-	-	-	-	-	-

Table 1: Comparison with the SOTA agents in ALFWorld. \* - reported in the previous work. The highest scores for each task in the same type of environment are highlighted in bold. REVEAL-IT substantially outperforms other SOTA agents of interacting with visual environments, and its success also directs a promising way to achieve human-level performance in ALFWorld.

The optimization of the training task sequences. We report the distribution of the sub-tasks in Fig. 4. As the training progresses, it becomes evident that the GNN-based explainer modifies the distribution of sub-tasks. Fig. 4 (left) shows the distribution of randomly sampled subtasks at the start of the training process. It is evident that the subtask "put" occurs most frequently. During the training, while examining the distribution of subtasks in Fig. 4 (middle left), task "put" remains the most common subtask, the frequencies of "look", "pick", and "find" have experienced a substantial increase. This demonstrates that these three qualities are important for the agent in ALFWorld. This aligns with our inherent comprehension of the environment, wherein the agent must initially acquire the ability to locate and retrieve the relevant item before it can proceed with future activities. As the training advances, the occurrence rate of these three task types declines proportionally (Fig. 4 (middle right)), suggesting that the agent already possesses the necessary skills. Training the agent with these tasks will not significantly enhance its performance. Fig. 4 (right) demonstrates that as the training advances, the training tasks increasingly emphasize the agent's additional skills, which align with the original work's final one or two stages. This indicates that the agent's training is almost over, and the alterations in the distribution of the training task align with our comprehension of the agent's learning process. It is evident that the explainer has comprehended and become proficient in the agent's learning process, enabling them to effectively modify the training tasks.

#### 5.3 Understanding the Relationship between Sub-tasks from Policy

This section will explore how the agent acquires knowledge in various sub-tasks from the perspective of policy. Given that the the different nodes in the policy will be activated in the evaluation, how are the weights linked to these nodes modified? Can GNN-explainer learn to differentiate between the sections that have more significant updates in terms of weight? Fig. 2 illustrates updating the policy during training. Firstly, it is imperative to focus on the modifications in policy updates in every individual row. As training advances, we will observe that the sections with more significant policy updates will undergo modifications (shown by the thick lines). Furthermore, our findings indicate that as the training progresses toward the latter stage, there is a greater overlap between the region with a larger update amplitude and the region triggered by evaluation. This illustrates that GNN explainer

Agent	Environment							
Agent	HalfCheetah	Hopper	InvertedPendulum	Reacher	Swimmer	Walker		
PPO	1846.25 (1.00)	2250.46 (1.00)	986.85 (1.00)	-10.34 (1.00)	108.81 (1.00)	2954.01 (1.00)		
PPO+REVEAL-IT	1921.08 (0.90)	2104.88 (0.90)	1004.92 (0.90)	-11.27 (0.90)	112.51 (0.90)	3148.64 (0.90)		
A2C	1014.02 (1.00)	630.51 (1.00)	1002.45 (1.00)	-27.02 (1.00)	25.28 (1.00)	676.52 (1.00)		
A2C+REVEAL-IT	1147.89 (0.80)	742.17 (0.80)	966.20 (0.80)	-28.54 (0.80)	17.63 (0.80)	810.26 (0.80)		
PG	602.27 (1.00)	2489.07 (1.00)	1028.33 (1.00)	-15.65 (1.00)	62.88 (1.00)	1280.29 (1.00)		
PG+REVEAL-IT	742.33 (0.90)	2253.70 (0.90)	975.04 (0.90)	-13.21 (0.90)	70.66 (0.90)	1546.38 (0.90)		

Table 2: **REVEAL-IT improves learning efficiency on OpenAI GYM benchmark.** In this table, we report the evaluation performance of three RL algorithms and how the performance changes with REVEAL-IT. (-) indicates the environment steps (millions) that an agent takes in training. It's clear that REVEAL-IT makes it easier for RL agents to learn in several different environments.



Figure 3: **The distribution of verbs in training tasks.** This figure demonstrates how REVEAL-IT optimizes the task sequences. We employ various verbs in tasks to differentiate, as each type necessitates distinct capabilities from the agent. The agent training process reflects the task sequence change from left to right. Analyzing the changes in task distribution shows that the "put" type of task is the most prevalent. As the training advances, the initial focus of training tasks is on teaching the agent to locate and retrieve objects in the environment ("look", "pick"). Subsequently, the agent is trained on tasks that require it to acquire other skills, e.g., "clean", "heat", and "examine".

comprehends the connection between policy training and evaluation. By carefully considering each vertical direction, we have identified and emphasized the sections of policies that are common to multiple activities (shown by gray boxes). By analyzing the neural network nodes within the gray box, we discovered that certain tasks, which necessitate agents to possess comparable abilities based on common knowledge, exhibit increasingly evident overlaps in their policies. For instance, the subtasks "open microwave 1" and "take apple 1 from microwave 1" both require the agent to comprehend the spatial location of the microwave. However, the second subtask also demands the agent identify the object "apple" and its specific location. There is less collaboration across distinct subtasks. Upon reviewing the prior distance, we observe that the subtask "put apple 1 on sinkbasin 1" shares some similarities with the previous subtask. Both subtasks are interconnected with "apple 1".

This finding demonstrates why our GNN-based explainer is capable of optimizing subtask sequences, i.e., the agent's learning process consists of both shared and distinct components. Once the agent becomes proficient at the intersecting components, decreasing the frequency of these specific training tasks is advisable. This is because the agent is unable to acquire new knowledge from them, resulting in an improvement of the agent's training efficiency.

# 6 Conclusion and Future Work

We present REVEAL-IT, a novel framework designed to explain the learning process of RL agents in complex environments and tasks while also serving as a foundation for optimizing task sequences. We demonstrate the mechanisms and functionalities of REVEAL-IT in complicated environments. Nevertheless, REVEAL-IT does possess certain constraints. A primary constraint is its ability to adapt to multi-modal challenges. As an illustration, in the ALFWorld, we exclusively implemented the REVEAL-IT within the visual environment. Furthermore, it is worth investigating if REVEAL-IT can effectively transform the knowledge acquired from policies and training problems into natural language, enabling its broader and more direct application in other reinforcement learning domains.

## **Societal Impact**

Our research centers on the explanation of an RL agent's training tasks and performance in a continuous control environment. This study aims to solve the explanation problem for RL in complex environments and tasks. enhancing transparency and interpretability in RL. This framework can promote trust and understanding of AI decision-making processes by explaining an RL agent's training tasks and performance in complex environments. This increased transparency can lead to more responsible and ethical deployment of RL systems in various real-world applications, such as autonomous vehicles, healthcare diagnostics, and financial trading. Technological progressions possess the capability to augment industrial procedures, ameliorate efficacy, and mitigate hazards to human laborers across diverse domains.

## Acknowledgements

This work is supported by the Air Force Office of Scientific Research under award number FA2386-23-1-4066. Case Number: 2024-0624 (original case number(s): AFRL-2024-2944).

#### References

- Bellemare, M. G., Dabney, W., and Munos, R. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, 2017.
- Brockman, G., Cheung, V., Pettersson, L., Schneider, J., Schulman, J., Tang, J., and Zaremba, W. Openai gym, 2016.
- Chen, H. and Liu, C. Safe and sample-efficient reinforcement learning for clustered dynamic environments. *IEEE Control Systems Letters*, 6:1928–1933, 2023.
- Côté, M.-A., Kádár, Á., Yuan, X., Kybartas, B. A., Barnes, T., Fine, E., Moore, J., Hausknecht, M. J., Asri, L. E., Adada, M., Tay, W., and Trischler, A. Textworld: A learning environment for text-based games. *ArXiv*, abs/1806.11532, 2018.
- Cui, Y., Pu, H., Shi, X., Miao, W., and Tchetgen, E. J. T. Semiparametric proximal causal inference. *Journal of the American Statistical Association*, 2020.
- Dai, W., Li, J., Li, D., Tiong, A. M. H., Zhao, J., Wang, W., Li, B. A., Fung, P., and Hoi, S. C. H. Instructblip: Towards general-purpose vision-language models with instruction tuning. *ArXiv*, abs/2305.06500, 2023.
- Deshpande, S., Eysenbach, B., and Schneider, J. G. Interactive visualization for debugging rl. *ArXiv*, abs/2008.07331, 2020.
- Dulac-Arnold, G., Levine, N., Mankowitz, D. J., Li, J., Paduraru, C., Gowal, S., and Hester, T. An empirical investigation of the challenges of real-world reinforcement learning. *ArXiv*, abs/2003.11881, 2020.
- Gao, P., Han, J., Zhang, R., Lin, Z., Geng, S., Zhou, A., Zhang, W., Lu, P., He, C., Yue, X., Li, H., and Qiao, Y. J. Llama-adapter v2: Parameter-efficient visual instruction model. *ArXiv*, abs/2304.15010, 2023.
- Ghallab, M., Knoblock, C., Wilkins, D., Barrett, A., Christianson, D., Friedman, M., Kwok, C., Golden, K., Penberthy, S., Smith, D., Sun, Y., and Weld, D. Pddl - the planning domain definition language. ArXiv, 08 1998.
- Greydanus, S., Koul, A., Dodge, J., and Fern, A. Visualizing and understanding atari agents. *ArXiv*, abs/1711.00138, 2017.
- Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *ArXiv*, abs/1801.01290, 2018a.
- Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *ArXiv*, abs/1801.01290, 2018b.

- Harley, A. W. An interactive node-link visualization of convolutional neural networks. In *ISVC*, pp. 867–877, 2015.
- Heuillet, A., Couthouis, F., and Rodríguez, N. D. Explainability in deep reinforcement learning. *Knowl. Based Syst.*, 214:106685, 2020.
- Imbens, G. W. and Rubin, D. B. Causal Inference for Statistics, Social, and Biomedical Sciences: An Introduction. Cambridge University Press, 2015.
- Kaelbling, L. Learning to achieve goals. In IJCAI, 1993.
- Kolve, E., Mottaghi, R., Han, W., VanderBilt, E., Weihs, L., Herrasti, A., Deitke, M., Ehsani, K., Gordon, D., Zhu, Y., Kembhavi, A., Gupta, A. K., and Farhadi, A. Ai2-thor: An interactive 3d environment for visual ai. *ArXiv*, abs/1712.05474, 2017.
- Li, J., Li, D., Savarese, S., and Hoi, S. C. H. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International Conference on Machine Learning*, 2023.
- Lillicrap, T. P., Hunt, J. J., Pritzel, A., Heess, N. M. O., Erez, T., Tassa, Y., Silver, D., and Wierstra, D. Continuous control with deep reinforcement learning. *CoRR*, abs/1509.02971, 2016.
- Luo, D., Cheng, W., Xu, D., Yu, W., Zong, B., Chen, H., and Zhang, X. Parameterized explainer for graph neural network. ArXiv, abs/2011.04573, 2020.
- Martens, E. P., Pestman, W. R., de Boer, A., Belitser, S. V., and Klungel, O. H. Instrumental variables: Application and limitations. *Epidemiology*, 17:260–267, 2006.
- Miller, T. Explanation in artificial intelligence: Insights from the social sciences. *Artif. Intell.*, 267: 1–38, 2017.
- Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., Graves, A., Riedmiller, M. A., Fidjeland, A. K., Ostrovski, G., Petersen, S., Beattie, C., Sadik, A., Antonoglou, I., King, H., Kumaran, D., Wierstra, D., Legg, S., and Hassabis, D. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.
- Mnih, V., Badia, A. P., Mirza, M., Graves, A., Lillicrap, T. P., Harley, T., Silver, D., and Kavukcuoglu, K. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning*, 2016.
- Mott, A., Zoran, D., Chrzanowski, M., Wierstra, D., and Rezende, D. J. Towards interpretable reinforcement learning using attention augmented agents. *ArXiv*, abs/1906.02500, 2019.
- Nielsen, U. H., Pellet, J.-P., and Elisseeff, A. Explanation trees for causal bayesian networks. *ArXiv*, abs/1206.3276, 2008.
- Paduraru, C., Mankowitz, D. J., Dulac-Arnold, G., Li, J., Levine, N., Gowal, S., and Hester, T. Challenges of real-world reinforcement learning: definitions, benchmarks and analysis. *Machine Learning*, 110:2419 – 2468, 2021.
- Pearl, J. Probabilistic reasoning in intelligent systems networks of plausible inference. In *Morgan Kaufmann series in representation and reasoning*, 1989.
- Pearl, J. Causal inference in statistics: An overview. Statistics Surveys, 3:96–146, 2009.
- Pearl, J., Glymour, M., and Jewell, N. P. Causal inference in statistics: A primer. 2016.
- Puiutta, E. and Veith, E. M. S. P. Explainable reinforcement learning: A survey. ArXiv, abs/2005.06247, 2020.
- Rezende, D. J., Danihelka, I., Papamakarios, G., Ke, N. R., Jiang, R., Weber, T., Gregor, K., Merzic, H., Viola, F., Wang, J. X., Mitrovic, J., Besse, F., Antonoglou, I., and Buesing, L. Causally correct partial models for reinforcement learning. *ArXiv*, abs/2002.02836, 2020.

- Rubin, D. B. Estimating causal effects of treatments in randomized and nonrandomized studies. *Journal of Educational Psychology*, 66:688–701, 1974.
- Sainani, K. L. Instrumental variables: Uses and limitations. PM&R, 10, 2018.
- Schölkopf, B., Locatello, F., Bauer, S., Ke, N. R., Kalchbrenner, N., Goyal, A., and Bengio, Y. Toward causal representation learning. *Proceedings of the IEEE*, 109:612–634, 2021.
- Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. Proximal policy optimization algorithms. *ArXiv*, abs/1707.06347, 2017.
- Shan, C., Shen, Y., Zhang, Y., Li, X., and Li, D. Reinforcement learning enhanced explainer for graph neural networks. In *Neural Information Processing Systems*, 2021.
- Shridhar, M., Yuan, X., Côté, M.-A., Bisk, Y., Trischler, A., and Hausknecht, M. J. Alfworld: Aligning text and embodied environments for interactive learning. *ArXiv*, abs/2010.03768, 2020.
- Shridhar, M., Yuan, X., Côté, M.-A., Bisk, Y., Trischler, A., and Hausknecht, M. ALFWorld: Aligning Text and Embodied Environments for Interactive Learning. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.
- Sontakke, S. A., Mehrjou, A., Itti, L., and Scholkopf, B. Causal curiosity: Rl agents discovering self-supervised experiments for causal representation learning. In *International Conference on Machine Learning*, 2020.
- Spinelli, I., Scardapane, S., and Uncini, A. A meta-learning approach for training explainable graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 35:4647–4655, 2021.
- Velickovic, P., Cucurull, G., Casanova, A., Romero, A., Lio', P., and Bengio, Y. Graph attention networks. ArXiv, abs/1710.10903, 2017.
- Ying, R., Bourgeois, D., You, J., Zitnik, M., and Leskovec, J. Gnnexplainer: Generating explanations for graph neural networks. *Advances in neural information processing systems*, 32:9240–9251, 2019.
- Yuan, H., Yu, H., Wang, J., Li, K., and Ji, S. On explainability of graph neural networks via subgraph explorations. In *International Conference on Machine Learning*, 2021.
- Zhang, J., Luo, D., and Wei, H. Mixupexplainer: Generalizing explanations for graph neural networks with data augmentation. *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2023.
- Zhu, D., Chen, J., Shen, X., Li, X., and Elhoseiny, M. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *ArXiv*, abs/2304.10592, 2023.

# A Visualized task examples in ALFWorld



Figure 4: **Visualized task examples of ALFWorld Shridhar et al. (2021).** This benchmark utilizes various household scenarios created within the Ai2Thor environment. In this environment, all objects can be moved to different locations based on available surfaces and class restrictions. This allows for the generation of a wide range of new tasks by combining different objects and goal positions in a procedural manner.

## **B** More Details about GNN explainer

#### **B.1** GNN explainer highlight the important update

To extract the explanation subgraph  $G_S$ , we first compute the importance weights on edges. A threshold is used to remove low-weight edges, and identify the explanation subgraph  $G_S$ . The ground truth explanations of all datasets are connected subgraphs. Therefore, we identify the explanation as the connected component containing the explained node in GS. We identify the explanation for the generated graph classification by the maximum connected component of  $G_S$ . For all basic RL algorithms, we perform a search to find the maximum threshold such that the explanation is at least of size  $K_M$ . When multiple edges have tied importance weights, all of them are included in the explanation.

#### B.2 How does GNN explainer map the skills of the RL agent?

In REVEAL-IT, the central concern revolves around the GNN explainer's capacity to comprehend the agent's learning prcess and ascertain whether the agent has achieved the certain abilities in accomplishing the task. The GNN explainer is designed to identify and emphasize important updates in the policy. If the nodes associated with these highlighted updates correspond to the nodes engaged by the agent during the evaluation, then it can be inferred that the explanation is cognizant of the specific sections of the policy that align with the agent's essential abilities. Hence, we ascertain the ratio of nodes identified by the GNN explainer and nodes stimulated by the agent in successful tasks and report it in Fig. 5. In this series of comparisons, we incorporated a pre-trained Graph Neural



Figure 5: The results of learning process of the GNN explainer.

Network (GNN) explanation that utilizes data from RL training data from different sequences of training tasks in the same environment. An intriguing observation is that we discovered that the efficacy of the GNN-explainer, when trained on various tasks, was inferior than that of the GNN-explainer taught using a reinforcement learning agent. This discrepancy may arise from the varying demands that different tasks place on the training process of reinforcement learning (RL) agents. Additionally, pre-trained graph neural networks (GNNs) may struggle to accurately comprehend the ongoing RL training progress due to the incorporation of a priori bias.