# QuADTool: Attack-Defense-Tree Synthesis, Analysis and Bridge to Verification

Florian Dorfhuber<sup>1,2</sup> 🖂 florian.dorfhuber@in.tum.de <sup>D</sup>,

Julia Eisentraut<sup>2,3</sup> julia.eisentraut@posteo.de <sup>[D]</sup>, Katharina Klioba<sup>4</sup> katharina.klioba@tuhh.de <sup>[D]</sup>, and Jan Křetínský<sup>1,2</sup> jan.kretinsky@fi.muni.cz <sup>[D]</sup>

<sup>1</sup> Masaryk University, Brno, Czech Republic

<sup>2</sup> Technical University of Munich, Munich, Germany

<sup>3</sup> State Parliament of Northrhine-Westfalia, Germany

<sup>4</sup> Technical University of Hamburg, Hamburg, Germany

**Abstract** Ranking risks and countermeasures is one of the foremost goals of quantitative security analysis. One of the popular frameworks, used also in industrial practice, for this task are *attack-defense trees*. Standard quantitative analyses available for attack-defense trees can distinguish likely from unlikely vulnerabilities. We provide a tool that allows for easy synthesis and analysis of those models, also featuring probabilities, costs and time. Furthermore, it provides a variety of interfaces to existing model checkers and analysis tools.

Unfortunately, currently available tools rely on *precise* quantitative inputs (probabilities, timing, or costs of attacks), which are rarely available. Instead, only statistical, imprecise information is typically available, leaving us with *probably approximately correct* (*PAC*) estimates of the real quantities. As a part of our tool, we extend the standard analysis techniques so they can handle the PAC input and yield rigorous bounds on the imprecision and uncertainty of the final result of the analysis.

# 1 Introduction

Attack trees, e.g., [28, 51], and their extensions are a widespread formalism for threat modeling and risk assessment. Their applications range from analyzing attacks on smart grids [4], ATMs [18], optical power meters [17], SCADA control systems [10, 39, 50, 35, 14] or software supply chains [42] to intelligent autonomous vehicles and vehicular networks [23, 27, 45], secure deployment of HTTPS [49] or cybersecurity awareness trainings for election officials [48]. Moreover, attack trees are particularly useful for meta-modeling threats, combining several risk analyses together, e.g., in telemedicine [26, 44], impersonation attacks in e-learning [46] or IoT systems [31]. Besides these individual usages, attack trees are generally recommended as a means to identify the point of the weakest resistance according to the OWASP CISO AppSec Guide,<sup>5</sup> or to retrospectively understand attacks (through so-called red teams) by NATO's Improving Common Security Risk Analysis report [41].

In practice, there are not enough resources to fix every single vulnerability found in security assessment. Hence, the need to rank their importance arises. Quantitative analysis of attack trees can utilize quantitative information such as probabilities, costs, and timing to compute how likely particular vulnerabilities are, how much the defense may cost, or how long attacks might take. Consequently, it can distinguish unrealistically costly or improbable attacks from those that need to be fixed. While there is a recent body of theoretical work in this direction, e.g. [32, 22, 3, 43, 33, 29, 16], there are two main hindrances to practical use. Firstly, it is the very *limited tool support* for convenient quantitative modeling and analysis. Secondly, it is the uncertainty and imprecision of the quantitative *input* information, arising in this domain even more than elsewhere. Indeed, apart from standard questions like What is the actual failure rate of the security camera?, we may need to ask What is the probability of quessing a password using a database of the most common passwords and one year of CPU time? or How much faster and cheaper is a particular attack going to be next year based on past years' data?

We address both issues: we provide a convenient *tool*, which also features quantitative analysis capable of rigorously reflecting the *uncertainty and imprecision of the quantitative inputs*. To this end, we formalize such models as PAC-quantitative trees. Then, we show how to obtain them practically using our tool and provide an algorithm for their analysis. In order to properly evaluate our tool and the PAC-input quantitative analysis we create a benchmark suite ATBEST of ADT found in literature and ones generated randomly. We make all models available to the public.<sup>6</sup>

**Tool.** We provide QuADTool, a tool for the whole modeling-analysis workflow. The tool can import trees in the DOT format and XML format of ADTool [19]. The graphical interface allows for convenient creating, editing, and combining trees and generating *PAC*-quantities directly from provided data. Further, the tool translates the trees to formats of model checkers UPPAAL [5], PRISM [34], PRISM-games [12], MODEST [21], and STORM [15] (via JANI [7] export of MODEST). Consequently, the GUI effectively interfaces with other available analyses (such as [19, 47]) and to our new *PAC*-input analysis. Besides, to help non-experts successfully construct meaningful models, we provide detailed automatically generated feedback on compliance with the assumptions of each of the offered analyses.

**PAC-quantitative attack-defense trees.** All the previously cited quantitative analyses assume that the quantities (transition probabilities, costs, delays) are

<sup>&</sup>lt;sup>5</sup>https://www.owasp.org/index.php/CISO\_AppSec\_Guide:\_Criteria\_for\_ Managing\_Application\_Security\_Risks

 $<sup>^6\</sup>mathrm{For}$  review, all models are in our artifact at <code>https://zenodo.org/records/11090469</code>.

given as exact numbers, allowing analyses to output exact numbers, too. However, in reality, we often lack perfect quantities. Nonetheless, this data allows us to derive estimates of the actual value, possibly together with confidence intervals bounding these estimates' uncertainty. Hence, we assume the input quantities are probably approximately correct (PAC), i.e., with a given probability in a given interval around the estimate. We demonstrate how easily such trees can be obtained, relying on statistics or time-series analysis. To that end, we consider independent samples of the unknown quantity data (e. g., past years' information). We then extend the traditional bottom-up analyses to bound the final PAC uncertainty resulting from the input quantities' PAC uncertainty. Interestingly, our extended analysis comes with little additional computational cost in comparison to the standard analysis on average-size attack-defense trees. Consequently, our approach allows practitioners to stick to their current analysis and learn about the quality and reliability of its results with almost no additional effort.

To summarize, our contribution is threefold:

- Our tool QuADTool addresses practical needs in attack-defense tree modeling and analysis, including a GUI and a CLI for editing and analyzing ADT. It also gives feedback on suitable exports for further analyses.
- The tool features a novel quantitative analysis of PAC-attack-defense trees, the first extensions of attack-defense trees reflecting the data inaccuracy.
- The tool comes equipped with AT BEnchmark SuiTe (ATBEST), collecting benchmarks from literature as well as randomly generated ones.

**Organization.** The paper is organized as follows. After exemplifying the framework of attack-defense trees in Section 2, the tool functionality is presented in Section 3. We describe our *PAC*-input analysis in Section 4. Section 5 evaluates our contributions experimentally and Section 6 concludes. We provide an artifact with the tool and models<sup>6</sup>.

**Related work.** Besides two industrial tools dedicated to attack-defense tree analysis<sup>7</sup>, which neither support more complex attack-defense tree structures such as [22], nor export to standard model checking tools, there are three dedicated (and up-to-date) *quantitative* attack-defense tree analysis tools:

- ADTool [19] supports attack-defense trees with the operators AND, OR and Sequential-opAnd SAND and attack-defense trees with operators AND and OR. It uses the standard bottom-up traversal for quantitative model checking. In contrast to our tool, ADTool does not support PAC-input analysis. Additionally, one cannot add PAC-input analysis to ADTool as a 'custom' domain since multi-parameter attack-defense trees are not supported. We compare the performance of the bottom-up analysis using ADTool and QuADTool in Section 5.
- ATTop [47] is a software bridging tool, which provides various horizontal and vertical model transformations to the ADTool 2.0 input format or to the

<sup>&</sup>lt;sup>7</sup>see http://www.amenaza.com and http://www.isograph.com/software/

model checker UPPAAL, however not to PRISM or MODEST. *PAC* models and *PAC* analysis are not supported.

- RisQFLan<sup>8</sup> allows specifying attack-defense trees with quantitative constraints using a dedicated probabilistic language (XTEXT grammar)<sup>9</sup>. Statistical model checking and precise analysis using STORM and PRISM are supported. However, RisQFLan neither supports *PAC*-inputs nor continuous-time. Additionally, exports to STORM and PRISM rely on discrete-time Markov chains rather than games or stochastic timed automata. Stochastic model checking in RisQFLan relies on MultiVeStA.<sup>10</sup> Hence RisQFLan does not allow synthesizing optimal attack and defense strategies. However, RisQFLan allows assigning detection-rates to inner nodes and to separate defenses from countermeasures (which we do not feature). Hence, a complete performance comparision between RisQFLan and QuADTool is not possible.

All these quantitative analyses have precise inputs and outputs (rather than PAC values). The resulting uncertainty is not bound, i.e., there is no estimate of how likely the analysis results are close to the actual results. In contrast our PAC analysis takes uncertainty of each input value into account. Hence, our resulting confidence interval covers likely deviations and bounds the uncertainty, which previous quantitative analysis cannot.

Surprisingly, the uncertainty of the input quantities in attack-defense trees has not gained too much attention yet [9, 40, 43]. Buldas et al. [8] present the first approach to account for inconsistency and gaps in historical data and experts' estimates in attack-defense trees. The main limitation of their approach is the *impossibility of reflecting the data accuracy, which is the main contribution of this paper*.

In [36] a new approach to extend quantitative analysis on Attack Trees is presented, that may lift the structural bounds our tool currently has, but does cover a smaller set of operators compared to our approach. Additionally, there is no support for defense operations, yet.

# 2 Attack-Defense Trees

In this section, we briefly recall the notion of *attack-defense trees* (ADT), e.g., [30, 22]. Attack-defense trees are labeled trees, where the root represents the overall goal to attack a system. This goal can be recursively refined into smaller sub-goals, giving rise to descendant nodes, until no further refinement is possible. Inner nodes receive operators as labels binding the roles of the children. The leaves represent *basic events* (denoted BE), unique observable happenings in the real world. They are partitioned into *basic attack steps* and *basic defense steps*.

<sup>&</sup>lt;sup>8</sup>https://github.com/RisQFLan/RisQFLan/wiki

<sup>&</sup>lt;sup>9</sup>While the XTEXT files get compiled to dot-files for graphical display, these are currently not entirely compatible with the QuADTool import.

<sup>&</sup>lt;sup>10</sup>https://github.com/andrea-vandin/MultiVeStA/wiki

**Definition 1 (Attack-Defense Trees [22]).** An attack-defense tree<sup>11</sup> (over a set of basic events BE) is a tuple ADT = (V, E, t) where

- (V, E) is a directed acyclic graph, with a designated goal sink vertex g for the attacker. The source vertices BE  $\subseteq$  V are called basic events. All other vertices, G := V \ BE, are called gates; direct predecessors w.r.t. (V, E) of each gate are called its inputs.
- We additionally require that gates labeled with AND, OR and their sequential versions SAND or SOR have at least two inputs and that other gates have exactly one input.
- $t \colon \ G \to O$  is the type function assigning an operator to each gate.
- − TEdge  $\subseteq$  {v ∈ G | t(v) = TR} × BE are trigger edges from TR gates to BE;
- $\mathsf{REdge} \subseteq \{ v \in G \mid t(v) = \mathtt{RE} \} \times \mathsf{BE} \text{ are reset edges from } \mathtt{RE gates to } BE;$



Figure 1: The ADT from [17] represents ways to gain access to a power meter. We will use this model also in Section 3.4. In Section 5 we evaluate our tool on more complex attack-defense trees.

*Example 1.* In Figure 1, we present a small attack-defense tree representing an attacker (nodes in red) who wants to maliciously gain access to a digital power

<sup>&</sup>lt;sup>11</sup>In literature, *ADT* are often directed acyclic graphs (DAG), yet called trees. Hence, we call our framework attack-defense trees, although the underlying structure is a graph.

meter. The goal node at the top (with a blue border) represents the overall attack goal. All leaves of the tree are basic attack steps (colored red or green). The goal is refined into different subtrees using the operator AND, i.e., all of the subtrees need to be successfully attempted for the overall attack to be successful. The overall attack is successful if, the attacker gained the credentials (event (4)) and successfully entered them (event (9)). Also for the attack to be successful the defender (node in green) must not (event (17) with operator NOT) have installed additional authentication (event (6)). Event (4) is refined with the operator OR meaning it is successfully attempted if one of its children (event (1), (2), (3)) is attempted successfully.

To model complex attack-defense scenarios, a rich set of operators

 $O = \{AND, OR, NOT, SAND, SOR, TR, RE\}$ 

is necessary: Intuitively, AND, OR, NOT behave like their logical counterparts. SAND and SOR pose temporal (but not causal) restrictions on the order in which its children are attempted. Further, for Trigger TR, suppose its child is successfully attempted. In that case, several basic events are activated (*triggered*) for attempting (they cannot be attempted earlier than this). Finally, Reset RE is successfully attempted if its input is attempted successfully. As a side effect, events that have been reset can be attempted again, i.e., we allow players to attempt events several times.

A formal semantics of the operators used in the theoretical development in the subsequent section can be found in Definition 4 in the Appendix. Formal semantics for the remaining operators are not necessary to follow the paper (They can be found in [2, 22, 16]).

## 3 Tool Overview

This section shows the usage of QuADTool both in a graphical user interface and direct command-line access. We evaluate our analyses in Section 5.

#### 3.1 Model Construction

The workflow using QuADTool (see Figure 2) starts with model construction. For convenient modeling, QuADTool supports a dedicated graphical user interface and the following two input formats:

- The DOT-format as described in the Graphviz-Tool [20]. We recommend this format as it supports storing all additional parameters like *PAC*-parameters and simple formatting.
- The XML-format used in ADTool [19]. To ensure compatibility with this tool, our tool only exports strict tree structured ADT without PAC-values to this format.



Figure 2: The Workflow with QuADTool allows for input from four sources. In the next step the nodes can be refined using quantitative date from different sources. Additionally, the tool allows for analysis of said data. In a last step the data can be exported to model-checkers for further analysis.

Our *GUI*, see Figure 3, offers drag-and-drop manipulation of trees, creating new ones from scratch or by import. One can also easily combine existing models by importing several trees and connecting them.

There exist various approaches to attack-defense tree analysis supporting different features (see [51] for a survey on quantitative attack-defense tree analysis). Hence, QuADTool comes with an integrated *feedback system* (see Figure 3) to support the user in finding potential errors or incompatibilities before exporting. Furthermore, it gives advice on which export formats may be beneficial for the particular model.

#### 3.2 **ATBEST** Benchmark Collection for Attack-Defense Trees

To support the standardization and benchmark collection among attack-defense tree researchers and practitioners, we bring forth an attack-tree benchmark collection AT BEnchmark SuiTe (ATBEST) accessible at https://www.model. in.tum.de/~kraemerj/upload/. By uploading a model and registering with a name and email address, users receive a token to access all uploaded models in the database. In more details, our benchmark set consists of 42 models from 24 previously published papers, [37, 50, 30, 28, 4, 32, 3, 43, 18, 19, 22, 33, 47, 29, 1, 17, 31, 46, 8, 23, 26, 42, 48, 45], which we constructed using QuADTool. Additionally, we generated 626 models of various sizes for performance testing. These are binary ADT using the gates AND and OR, created by combining two smaller models with a new root recurrently.

#### 3.3 Obtaining PAC-Quantities for Attack-Defense Trees

After creating a model, we add default values or estimates to basic events (second step in the workflow (see Figure 2)). Our PAC (s. Section 4) assumption is less restrictive than the standard assumption of exact quantities and already applicable to various examples.

To derive *PAC*-parameters, the simplest way is to calculate a Gaussian estimate with confidence intervals. The Gaussian estimate is best for independent

identically distributed (i.i.d.) samples. Our tool allows the generation of those values via csv-input. One can also directly use a AutoRegressive-Moving Average (ARIMA) model [6, 13, 52, 11, 38, 24] inside the tool to derive bounds for cases with time-series data.

Please note that we do not aim to create the best possible time-series model for a given data-set using our tool since this still requires a more detailed analysis. However, we want to allow users to get a reasonably good prediction quickly.

#### 3.4 Analyses

**QuADTool** allows to analyze models using an exact or *PAC* analysis or using existing model checkers.

Like the ADTool, QuADTool supports direct analyses on the tree for exact minimal attack costs, exact minimal attack delays, and exact success probabilities. Additionally, we support our new *PAC*-input analyses for each of these domains.

Furthermore, users can export the final model to various other tools and model checkers using one of the following file formats: XML, DOT, PRISM-, MODEST-, UPPAAL-input-language. For PRISM, we use the semantics in terms of stochastic turn-based games given in [16] and for MODEST and UPPAAL the semantics in terms of stochastic timed automata given in [22]. <sup>12</sup> In the following, we describe the interfaces to other tools and their use in more detail.

Connection to ADTool and ATTop These two attack-defense tree tools have a restricted set of features and expect XML inputs. Thus, we cannot analyze every attack-defense tree constructed in QuADTool using these tools. For instance, whenever a model has multiple root nodes, our export omits all but one tree. Furthermore, the ADTool only supports the operators OR, AND, SAND and no timed events (with clocks or distributions).

**Timed Analysis** Analysis involving time can be either done within QuADTool or outsourced to MODEST or UPPAAL.

The translation to MODEST uses actions for each three-valued logic state, i.e., each basic event can either be undecided, successfully or unsuccessfully attempted. For UPPAAL a similar approach with automata for every state is used. Both approaches can model systems with multiple root nodes and complex operators.

**Game Analysis** Lastly, QuADTool can also export to the PRISM format, not supporting time, but supporting games. In this framework, all basic events have the same chance to be executed at a given (discrete) point in time, impacting the evaluation of sequential operators.

**Integration** We provide the functionality to send a model directly to UP-PAAL cora, ADTool, PRISM-games and MODEST simulator in the GUI, after specifying the Tool location, as seen in Figure 3 (right lower panel).

 $<sup>^{12}\</sup>mathrm{To}$  use STORM, we suggest using the export to MODEST first and then, use their export to the JANI-format.



Figure 3: QuADTool with the case study from [17]. At the bottom, one can see the feedback for the selected export or general issues. On the right, the quantitative results for the selected domain (here probabilities) are given for all nodes with the *PAC*-quantities. Below is the result of a model checker (here ADTool).

# 4 PAC-Quantitative ADT: Fighting the Uncertainty

In this section we describe the technique underlying our tools' functionality to analyze ADT with not fully known quantities. While it is less standard to do so in a tool paper, this is not described elsewhere and thus must be included in the tools' contributions for completeness here.

A standard way to reason about costs, probabilities, and time within attackdefense trees is to equip basic events with quantitative information and use bottom-up traversal algorithms to derive the root's final value [37, 30, 2, 25]. In this section, we augment this analysis to bound the uncertainty resulting from estimating the quantitative values of the basic events.

In Appendix C, we show that our computations of probabilities, costs and delays are correct with reference to standard Boolean and powerset valuations of attack-defense trees [37, 30, 19]. However, standard bottom-up traversal algorithms are efficient and correct only on simpler structures than our *ADT* in Definition 1 (for more details, see [29]). In particular, they require a *static interpretation*, i.e., there is only one shot to decide which basic events players try and which they do not try. Consequently, we restrict ourselves to one of two domains supported by the ADTool (attack-defense trees with gates AND, OR and NOT). For reader's convenience, we exclude TR in this section but include it in Appendix C. Hence, our analysis also covers the second domain of the ADTool.

#### 4.1 Quantitative ADT and PAC-Quantitative ADT

**Quantitative ADT.** Given a type T of the quantitative information, the quantitative ADT is an ADT equipped with a quantitative valuation of basic events  $val_{BE} : BE \rightarrow T$ . The definition is generic to carry over to various settings: While real numbers may represent cost [19], acylic phase-type distributions may, for instance, represent the likelihood of a successful attack over time [2].

*Example 2 (Type).* For success probabilities, we simply take T = [0, 1]. For costs and delays, we take  $T = \mathbb{R}_{>0}$ .

**PAC-Quantities.** In most real-world examples, the quantitative information attached to basic events is rarely known precisely but comes with uncertainty. We call quantitative information *probably approximately correct (PAC)*, if there is an *imprecision bound*  $\epsilon$  and an *uncertainty probability*  $\delta$ , such that the distance between the true value and the given estimate is less than  $\epsilon$  with probability at least  $1 - \delta$ . Formally:

**Definition 2 (PAC).** Let  $\mathsf{T}$  be a set equipped with a metric  $\mathsf{d}$ . We say that a  $\mathsf{T}$ -valued random variable X is  $(\epsilon, \delta)$ -PAC for the true value  $\mathsf{v}$  if the probability<sup>13</sup> of  $X \in \{t \mid \mathsf{d}(t, \mathsf{v}) \leq \epsilon\}$  is (at least)  $1 - \delta$ . Exact values can be considered (0, 0)-PAC.

*Example 3 (Metric).* For probabilities, costs, and delays, the metric is the standard Euclidean distance (absolute value of their difference).

**PAC-Quantitative ADT** Given a type T of the quantitative information, the PAC-quantitative ADT is a quantitative ADT equipped additionally with PAC-parameters  $\epsilon_{be} \in \mathbb{R}_{\geq 0}$  and  $\delta_{be} \in [0, 1]$  for each basic event  $be \in BE$ .

#### 4.2 PAC-Input Extension of Bottom-Up Analyses

Before giving the generic algorithm for the bottom-up propagation of quantitative values [37, 30], we will give a short introduction to bottom-up analyses.

**Bottom-Up Traversal Analysis** Let ADT be an attack-defense tree with set V of nodes, g its root, T a non-empty domain of quantitative information, I an interpretation i.e. a mapping of *ADT*-operators to operations over T, and  $val_{BE}$  a basic-events valuation with input values from T. Then its bottom-up traversal semantics val:  $V \rightarrow T$  for ADT is defined recursively. The valuation of ADT is defined as the value of its root node val(g).

<sup>&</sup>lt;sup>13</sup>The method used to learn the estimate X from data sampled from a distribution parametrized by v usually determines the probability space. For instance, for a v-biased coin with v = 0.49 and 20 samples (coin tosses), the standard statistics methods yield a probability space with highest density of X in 0.49 and inducing the respective confidence intervals for X depending on the outcome of the experiment.

*Example 4 (Probabilistic ADT).* We have already seen that the domain for probabilities is [0, 1]. Here we instantiate the interpretation for probabilities. We define a probabilistic interpretation I (with T = [0, 1]) as follows: (Similar examples for the domain of Cost and Probability can be found in Appendix A)

$$- I(\mathbf{v})(x_1, x_2) = x_1 \cdot x_2, \text{ if } t(\mathbf{v}) = \text{AND} - I(\mathbf{v})(x_1, x_2) = x_1 + x_2 - x_1 \cdot x_2 \text{ for } t(\mathbf{v}) = \text{OR} - I(\text{NOT})(x) = 1 - x$$

**Extension to PAC-Values** In the following, we devise an algorithmic approach that allows us to derive a *PAC*-aware variant from almost any bottom-up traversal analysis (according to its previous definition)<sup>14</sup> as long as it holds  $\mathsf{T} \subseteq \mathbb{R}_{\geq 0}$  for the domain  $\mathsf{T}$ . To this end, we use the notation  $x_i \pm \epsilon_i := [\max(0, x_i - \epsilon_i), x_i + \epsilon_i]^{15}$ .

We propagate the uncertainty along with the nodes during the bottom-up traversal analysis resembling interval arithmetics from canonical error analysis. Whenever the interpretation uses one of the operators  $+, -, \cdot, \max$ , min over  $\mathbb{R}_{\geq 0}$ , for its *PAC*-aware variant, we additionally compute a new uncertainty bound and uncertainty probability for the resulting value. The nodes' uncertainty bound and uncertainty probability are solely based on its operands' uncertainty bounds and uncertainty probabilities.

**PAC-Bounds Propagation** Without any assumptions on the distribution of the uncertainty, operations are as follows: Given values  $x_1, x_2 \in [0, 1]$  that are  $(\epsilon_i, \delta_i)$ -PAC, the uncertainty of

 $\begin{array}{ll} (R_1) & 1-x_i \text{ can be bound by } \epsilon = \epsilon_i. \\ (R_2) & x_1 \cdot x_2 \text{ can be bound by } \epsilon = x_1 \cdot \epsilon_2 + x_2 \cdot \epsilon_1 + \epsilon_1 \cdot \epsilon_2. \\ (R_3) & x_1 + x_2 - x_1 \cdot x_2 \text{ can be bound by } \epsilon = \epsilon_1 + \epsilon_2 + x_1 \cdot \epsilon_2 + x_2 \cdot \epsilon_1 + \epsilon_1 \cdot \epsilon_2 \\ (R_4) & \max(x_1, x_2) \text{ can be bound by } \epsilon = \max(\epsilon_1, \epsilon_2) \\ (R_5) & \min(x_1, x_2) \text{ can be bound by } \epsilon = \max(\epsilon_1, \epsilon_2) \end{array}$ 

For all operations the uncertainty probability  $\delta$  is (at most)  $1 - (1 - \delta_1) \cdot (1 - \delta_2)$ , if all  $x_i$  are independent, and otherwise (at most)  $\delta_1 + \delta_2$ . As probability analysis relies on independence of the basic events, we will use the first bound in the following.

In summary, the result of each of the given operations is  $(\epsilon, \delta)$ -PAC. Furthermore, each constant  $c \in \mathbb{R}$  is (0,0)-PAC.

Example 5 (PAC-Bounds Computation for Probabilities). Let ADT be an attackdefense tree with set V of nodes, let  $\mathsf{val}_{\mathsf{BE}}$  be a PAC probability valuation for basic events, i.e., for every basic event  $\mathsf{be} \in \mathsf{BE}$ , it holds  $\mathsf{val}_{\mathsf{BE}}(\mathsf{be})$  is  $(\epsilon_{\mathsf{be}}, \delta_{\mathsf{be}})$ -PAC for some  $\epsilon_{\mathsf{be}} \in \mathbb{R}_{\geq 0}$  and  $\delta_{\mathsf{be}} \in [0, 1]$ . The uncertainty for  $\mathsf{v} \in \mathsf{V}$  is computed as follows:

<sup>&</sup>lt;sup>14</sup>In fact, the approach is independent of the concrete interpretation I chosen, as long as for  $\mathbb{R}_{\geq 0}$ -interpretation it involves solely the operations +, -, max, min and ·, or *any combination* thereof.

<sup>&</sup>lt;sup>15</sup>For success probabilities, we set  $x_i \pm \epsilon_i \coloneqq [\max(0, x_i - \epsilon_i), \min(x_i + \epsilon_i, 1)]$ 

ID 10 $p: 0.4594491$	ID 10 $p: 0.456463 \epsilon: 0.130461 \delta: 0.226219$
ID 19 $p: 0.9188982$	ID 19 $p: 0.924015 \epsilon: 0.193929 \delta: 0.185494$
ID 4 $p: 0.92818$	ID 4 $p: 0.930528 \epsilon: 0.1894165 \delta: 0.142625$
ID 1 $p: 0.24$	ID 1 $p: 0.233 \epsilon: 0.026214 \delta: 0.05$
ID 2 $p: 0.65$	ID 2 $p: 0.667 \epsilon: 0.029225 \delta: 0.05$
ID 3 $p: 0.73$	ID 3 $p: 0.728 \epsilon: 0.027594 \delta: 0.05$
ID 9 $p: 0.99$	ID 9 $p: 0.993 \epsilon: 0.005170 \delta: 0.05$
ID 17 $p: 0.5$	ID 17 $p: 0.494 \epsilon: 0.031003 \delta: 0.05$
ID 6 $p: 0.5$	ID 6 $p: 0.506 \epsilon: 0.031003 \delta: 0.05$
(a)	(b)

Figure 4: Example evaluation of the model in Figure 1 (a) without *PAC* values and (b) with *PAC*-values. The *PAC*-values were generated by sampling from Bernoulli distributions parameterized by the exact value.

- 1.  $v \in \mathsf{BE}$  and v is not triggerable: return  $(\epsilon_{\mathsf{be}}, \delta_{\mathsf{be}})$ .
- 2. t(v) = AND and  $in_1, in_2$  are its inputs: recursively compute  $(\epsilon_{in_1}, \delta_{in_1})$  and  $(\epsilon_{in_2}, \delta_{in_2})$ . Use rule for multiplication  $R_2$ , i.e., return  $\epsilon = val(in_1) \cdot \epsilon_{in_2} + val(in_2) \cdot \epsilon_{in_1} + \epsilon_{in_1} \cdot \epsilon_{in_2}$  and  $\delta = 1 (1 \delta_{in_1}) \cdot (1 \delta_{in_2})$ 3. t(v) = OR and  $in_1, in_2$  are its inputs: recursively compute  $(\epsilon_{in_1}, \delta_{in_1})$  and
- 3. t(v) = OR and  $in_1, in_2$  are its inputs: recursively compute  $(\epsilon_{in_1}, \delta_{in_1})$  and  $(\epsilon_{in_2}, \delta_{in_2})$ . Use rule  $R_3$ , i.e., return  $\epsilon = \epsilon_{in_1} + \epsilon_{in_2} + val(in_1) \cdot \epsilon_{in_2} + val(in_2) \cdot \epsilon_{in_1} + \epsilon_{in_1} \cdot \epsilon_{in_2}$  and  $\delta = 1 (1 \delta_{in_1}) \cdot (1 \delta_{in_2})$ 4. t(v) = NOT and in is its input: recursively compute  $(\epsilon_{in}, \delta_{in})$ . Use rule  $R_1$ , i.e.,
- 4. t(v) = NOT and in is its input: recursively compute  $(\epsilon_{in}, \delta_{in})$ . Use rule  $R_1$ , i.e., return  $\epsilon = \epsilon_{in}$  and  $\delta = \delta_{in}$

Formally, we can state that the resulting interval is the tightest reflecting the input intervals: Let  $I(v) \in x_v \pm \epsilon_v$  for each  $v \in BE$  and  $g \in G$  then I(g) lies in the interval computed above. Vice versa, for every I(g) in the interval, there are  $I(v) \in x_v \pm \epsilon_v$  (consistent with I(g)). Furthermore, with  $\delta_v$  denoting the probability that  $I(v) \notin x_v \pm \epsilon_v$ , the probability, that the resulting value is outside of the computed *PAC* interval, is at most the computed  $\delta$ .

In QuADTool, we also provide *PAC*-aware bottom-up analyses for delays and costs. The proof of correctness can be found in Appendix D.

Example 6 (Propagation of Uncertainty). In practice,  $\delta = 0.05$  or  $\delta = 0.01$  seem reasonably small uncertainty probabilities for meaningful PAC data (since they are most commonly used significance criteria). As most examples from literature have less than 30 nodes (s. Section 5), a corresponding binary tree would have a depth of 5. This would lead to  $\delta \approx 0.56$  or  $\delta \approx 0.15$  for an initial  $\delta$  of 0.05 or 0.01 at the root node respectively. Thus, selecting data of high confidence i.e. low  $\delta$  is crucial for good overall estimates.

#### 4.3 Analysis Example

We use one of the models introduced by Fila and Widel in [17](s. Figure 1) about manipulating a power meter as example for the analysis workflow with *PAC* 

values. We will use the domain of probability and assign each of the basic events a success probability from the paper (see Figure 4 (a)). For the defender node with id 6 we set the probability to 50% to represent, that only half of the power meters have this function enabled.

Using the exact properties the probability for a successful attack is about 46% (see Figure 4 (a)). To generate the *PAC* values we use R 4.3.1 to sample a Bernoulli distribution, with the exact values as parameter, 1000 times. From these values we use the built-in calculation of our tool to retrieve the *PAC* values using a Gaussian-Estimator.

The propagated values are displayed in Figure 4 (b). The calculations in the tool are done with arbitrary precision. The intermediate values are only rounded for display. Due to the initial confidence level of 5% the confidence level of the overall analysis is about 77%. Taking the  $\epsilon$  in account the analysis returns an estimate of the true probability with confidence interval of about 45.65% [33.61%-57.69%]. So the true value calculated in the exact example lies inside the bound generated by our *PAC*-propagation.

This extended analysis does, however, come with an increased computational effort, which still is inside acceptable bounds (see Section 5).

# 5 Experiments

We discuss the performance of QuADTool on our collection of benchmarks found on ATBEST.

For performance measurements, we used 42 security models, ranging from 5 to 30 nodes, from existing literature (s. Section 3.2), allowing the whole operator set. 17 of them contained operators, that were incompatible with XML. Therefore, they were only used for the remaining formats. We executed the conversion 50 times each on a computer with  $Intel(\mathbf{\hat{R}})Core^{TM}i7$  processor and 16 GB RAM.

In the next step, we conducted experiments on how long the model checkers ADTool, UPPAAL, PRISM-games and MODEST need to analyze the *ADT* success and failure probability on the models previously used for conversion. Every execution was repeated five times.

Lastly, we compare the execution time of PAC analysis with only propagating the probability. Thus, we used 636 model generated randomly only having inner nodes with AND and OR with a size of up to 1355 nodes, since literature examples are limited in amount and size. We calculate the success probability once with and once without PAC values.

**Results** are depicted in Figure 5 and 6. Our experiments show the following:

- Exports to the model checkers UPPAAL, MODEST, PRISM and to the XML format are feasible for models of sizes commonly found in literature. With all except PRISM needing less then a second for each model (see Appendix B).
- Generating the stochastic game explicitly, which the translation to PRISM relies on, is time-consuming for models with more than 30 nodes (see Appendix B). Yet, verification using PRISM may still be of use in practice.



Figure 5: 95%-confidence intervals of time (logarithmic scale) necessary for the corresponding model checker to evaluate models (for the success probability) depicted by the ADT size. Most executions take less than 10 seconds. Y-position of line start corresponds with position in legend. As most models from ATBEST contain mostly player nodes, our timed analysis using MODEST returns stack overflow errors on models of  $size \geq 5$ . PRISM-games runtime seems to be more dependent on model composition, rather than just the size. The evaluation time for QuADTool, ADTool and UPPAAL Cora are all below 1 second.

- The execution time may depend more on the model composition than on the actual size of the underlying tree (see Figure 5, 6).
- Verification using the ADTool and UPPAAL is faster than using PRISM-games or MODEST. If evaluation is possible, the results are returned in less then ten seconds (see Figure 5).
- UPPAAL model checking is useful for more complex objectives, posing an appropriate trade off.
- For PAC vs. non-PAC analysis in QuADTool, the slope of runtime differs roughly by a factor 10. None of the approaches takes more than a few seconds (see Figure 6) even for attack-defense trees with more than 1000 vertices.
- The runtime of ADTool and QuADTool using bottom-up analysis are in the same order in our experiments (see Figure 5).

# 6 Conclusion and Future Work

We have provided a simple tool for synthesis and analysis of attack-defense trees that allows connection to model-checker workflows. The CLI enables further integration into other software pipelines. Settings for various degrees of background knowledge allow also non-experts to access the field of ADT. Furthermore, we provide a simple but effective way to bound the uncertainty in quantitative



Figure 6: Model checking times (mean per size) *PAC* (red triangles) vs. non-*PAC* (blue dots) models in QuADTool. The highest execution time was 1.2s for 1355 nodes.

attack-defense tree analysis, using probably approximately correct inputs *and* outputs, obtaining uncertainty from data. Our experiments show that all analysis can be done in reasonable time even for models much larger than found in literature. Altogether, QuADTool presents several steps making the ADT framework more applicable in practice.

Future Work. Firstly, we aim to support larger models and models with heterogeneous subtrees. To this end, we want to design and implement compositional verification techniques to efficiently analyze, for instance, models where one subtree consists of only AND and OR and one player, another requiring full-fledged timed analysis and a third one games.

Secondly, the semantics in terms of stochastic timed automata and stochastic turn-based games suffer from a blow-up since all sequences of events need to be taken into account. One could employ partial-order reduction techniques in the conversion before model checking to reduce the model size.

Acknowledgments. We want to thank everyone who has contributed case studies to our benchmark collection ATBEST so far. This research was funded in part by the German Research Foundation (DFG) project No. 427755713 *GOPro*, the MUNI Award in Science and Humanities MUNI/I/1757/2021 of the Grant Agency of Masaryk University, the German Academic Scholarship Foundation and the ProSec project.

## A Quantitative Bottom-Up Analyses for Cost and Delays

*Example 7 (Delay ADT).* We define both the minimal and maximal delay interpretation I with  $T = \mathbb{R}_{\geq 0} \times \mathbb{R}_{\geq 0}$ , where the first component represents the delay of succeeding, the second component the delay of failing

- $l(v)((x_1, x_2), (y_1, y_2)) = (max(x_1, y_1), min(x_2, y_2))$  (for minimal delay) and  $(max(x_1, y_1), max(x_2, y_2))$  (for maximal delay), if t(v) = AND.
- $I(\mathbf{v})((x_1, x_2), (y_1, y_2)) = (\min(x_1, y_1), \max(x_2, y_2)) \text{ (for minimal delay) and} I(\mathbf{v})((x_1, x_2), (y_1, y_2)) = (\max(x_1, y_1), \max(x_2, y_2)) \text{ (for maximal delay)}$ if  $t(\mathbf{v}) = OR$

$$- I(NOT)(x_1, x_2) = (x_2, x_1)$$

Example 8 (Cost ADT). We define both the minimal and maximal cost interpretation I with  $T = \mathbb{R}_{\geq 0} \times \mathbb{R}_{\geq 0}$ , where the first component represents the cost of succeeding, the second component the cost of failing.

- $I(\mathbf{v})((x_1, x_2), (y_1, y_2)) = (x_1 + y_1, \min(x_2, y_2))$  (for minimal cost) and  $(x_1 + y_1, \max(x_2, y_2))$  (for maximal cost), if if  $t(\mathbf{v}) = AND$
- $I(v)((x_1, x_2), (y_1, y_2)) = (min(x_1, y_1), x_2 + y_2)$  (for minimal cost) and
- $I(v)((x_1, x_2), (y_1, y_2)) = (\max(x_1, y_1), x_2 + y_2) \text{ (for maximal cost) if } t(v) = OR$ -  $I(NOT)(x_1, x_2) = (x_2, x_1)$

## **B** Conversion Times



Figure 7: Execution times for conversion of DOT-files to the other formats.

## C Correctness of Bottom-Up Traversal Semantics

The following section recalls definitions from [30] and adapts them to our attackdefense tree setting. We only allow trees here (no DAGs). We include the operator TR only if every basic event is triggered by at most one vertex. Additionally, we require that vertices labeled with TR have no successors, and the main tree and the subtrees rooted in vertices with TR to be mutually disjoint. In this case, we can ensure an order satisfying the constraints imposed by TR for each satisfying assignment. In contrast to [30], we allow TR as a restricted variant of SAND<sup>16</sup> and use NOT rather than player swapping to focus on the player controlling an event rather than whether an event is useful or hindering for an attack. Additionally, we assume that every basic event can only occur once in the tree. Thus, we restrict the multiset semantics of [37, 30] to a powerset semantics.

**Definition 3 (Extension of Example 5 - 7).** In each case, I(TR) = Id and I(be) = I(AND) for triggerable basic events  $be \in BE$ .

Let X be a set and let  $X_1, X_2 \subseteq 2^X$ , i.e.  $X_1$  and  $X_2$  are sets of sets with elements in X. We define  $X_1 \otimes X_2 \coloneqq \bigcup_{(x_1, x_2) \in X_{11} \times X_{21}} \{x_1 \cup x_2\}$ . To restrict a set of basic events X to the basic events occurring in the subtree rooted in a vertex  $\mathbf{v}$ , we write  $X|_{\mathbf{v}}$ .

**Definition 4 (Powerset Attack-Defense Trees).** We consider the operators AND,OR, TR and NOT and let all basic events be in  $BA \cup BD$ . We define a powerset interpretation I with  $T = 2^{2^{BE}} \times 2^{2^{BE}}$ .

- $\begin{array}{l} \ \mathsf{I}(\mathsf{v})((X_{11}, X_{12}), (X_{21}, X_{22})) = (X_{11} \otimes X_{21}, X_{21} \cup X_{22} \cup (X_{21} \otimes X_{22}) \cup (X_{12} \otimes X_{21}) \cup (X_{11} \otimes X_{22})) \ if \ \mathsf{v} \ is \ a \ triggerable \ basic \ event \ \mathrm{or} \ \mathsf{t}(\mathsf{v}) = \texttt{AND} \\ \ \mathsf{I}(\mathsf{v})((X_{11}, X_{12}), (X_{21}, X_{22})) = ((X_{11} \cup X_{21} \cup (X_{11} \otimes X_{21}) \cup (X_{12} \otimes X_{21}) \cup (X_{12} \otimes X_{21}) \cup (X_{11} \otimes X_{22})), (X_{12} \otimes X_{22})) \ for \ \mathsf{t}(\mathsf{v}) = \mathsf{OR} \end{array}$
- $\mathsf{I}(\mathsf{NOT})((X_1, X_2)) = (X_2, X_1)$

$$- I(TR) = Id$$

We denote the powerset bottom-up traversal semantics by  $val^{P}$ .

The powerset bottom-up traversal semantics computes two sets of sets. In the first component, we collect all satisfying assignments, in the second one all unsatisfying assignments. Please note that we only denote events, which need to be set to true. All events not contained, need to be set to false.

To compute successful and unsuccessful attacks at once, we need to set  $val_{BE}^{P}(be) := (\{\{be\}\}, \{\emptyset\})$ . For the powerset bottom-up traversal semantics, we implicitely assume this valuation for basic events in the following.

**Definition 5 (Boolean Attack-Defense Trees).** We consider the operators AND, OR, TR and NOT and let all basic events be in  $BA \cup BD$ . We define a Boolean interpretation I with  $T = \{tt, ff\}$ 

 $<sup>^{16}\</sup>mathrm{We}$  use SAND to represent a timed order and TR to represent a logic order.

$$\begin{split} &- \mathsf{I}(\mathsf{v})(x_1, x_2) = \wedge, \, \textit{if } \mathsf{v} \, \textit{ is a triggerable basic event } \mathrm{or} \, \mathsf{t}(\mathsf{v}) = \texttt{AND} \\ &- \mathsf{I}(\mathsf{v}) = \vee \textit{ for } \mathsf{t}(\mathsf{v}) = \mathtt{OR} \\ &- \mathsf{I}(\mathtt{NOT}) = \neg \\ &- \mathsf{I}(\mathtt{TR}) = \mathsf{Id} \end{split}$$

We denote the Boolean bottom-up traversal semantics by  $val^B$ .

Let  $X \subseteq \mathsf{BE}$ . In the following, we denote by  $\mathsf{val}^B_{\mathsf{BE},X}$  the Boolean valuation such that  $\mathsf{val}^B_{\mathsf{BE},X}(\mathsf{be}) = \mathsf{tt}$  if  $\mathsf{be} \in X$  and false, otherwise.

**Theorem 1 (Powerset and Boolean Attack-Defense Trees).** Let ADT = (V, E, t) be an attack-defense tree and let  $val^{P}(v) = (X_1, X_2)$ .

1. 
$$x_1 \in X_1$$
 iff  $\mathsf{val}^B(\mathsf{v}) = \mathsf{tt} \ w.r.t. \ \mathsf{val}^B_{\mathsf{BE},x_1}$   
2.  $x_2 \in X_2$  iff  $\mathsf{val}^B(\mathsf{v}) = \mathsf{ff} \ w.r.t. \ \mathsf{val}^B_{\mathsf{BE},x_2}$ 

*Proof.* Let ADT = (V, E, t) be an attack-defense tree. We proof both claims simultaneously by induction on the structure of the attack-defense tree.

- v is a non-triggerable basic event. By definition  $val^{B}(v) = tt$  iff  $val_{BE}^{B}(v) = tt$ . Since  $val_{BE}^{P}(v) = (\{\{v\}\}, \{\emptyset\})$ , the claims holds true.
- Induction Hypothesis: For all subtrees of v rooted in  $v^*$  holds:
  - 1.  $x_1 \in X_1$  iff  $\mathsf{val}^B(\mathsf{v}^*) = \mathsf{tt}$  w.r.t.  $\mathsf{val}^B_{\mathsf{BE},x_1}$ 2.  $x_2 \in X_2$  iff  $\mathsf{val}^B(\mathsf{v}^*) = \mathsf{ff}$  w.r.t.  $\mathsf{val}^B_{\mathsf{BE},x_2}$
- t(v) = TR: The claim holds by induction hypothesis and the definitions of  $val^{P}$  and  $val^{B}$  (identity function for vertices labelled by TR).
- v ∈ BE and triggered by v<sup>\*</sup> ∈ V. Let val<sup>P</sup>(v<sup>\*</sup>) = (X<sub>1</sub><sup>\*</sup>, X<sub>2</sub><sup>\*</sup>). We have val<sup>P</sup><sub>BE</sub>(v) = ({{v}}, {\emptyset}) and val<sup>B</sup>(v) = val<sup>B</sup>(v<sup>\*</sup>) ∧ val<sup>B</sup>(v). Thus, every satisfying assignment of the subtree rooted in v<sup>\*</sup> extended by v set to true is a satisfying assignment of v. We apply the induction hypothesis to the subtree rooted in v<sup>\*</sup>. Hence, by definition of ⊗ and the induction hypothesis, Claim (1) holds true. Additionally, val<sup>B</sup>(v) = ff if v is set to false (i.e. val<sup>B</sup><sub>BE</sub>(v) = ff) or val<sup>B</sup>(v<sup>\*</sup>) = ff. Hence, by induction hypothesis and the definition of val<sup>P</sup> for triggerable basic events, Claim (2) holds, too.
- t(v) = AND: Analogously to the proof for triggerable basic events. However, the induction hypothesis needs to be used on both subtrees.
- -t(v) = OR: Analogously to the proof for triggerable basic events. However, the induction hypothesis needs to be used for both subtrees and the proofs of the two claims need to be swapped.
- $-\mathbf{t}(\mathbf{v}) = \text{NOT:}$  Let  $\mathbf{v}^*$  be the input of  $\mathbf{v}$  and let  $\text{val}^P(\mathbf{v}^*) = (X_1, X_2)$ . Since  $\text{val}^B(\mathbf{v}) = \text{tt}$  iff  $\text{val}^B(\mathbf{v}^*) = \text{ff}$  by definition and each satisfying assignment of  $\mathbf{v}^*$  is an unsatisfying assignment of  $\mathbf{v}$  by definition, the claim follows from the induction hypothesis.

We have proven Theorem 1 by induction.

$$\begin{split} \operatorname{val}^{\operatorname{Pr}}(\mathsf{v}) &= \sum_{x_1 \in X_1} \prod_{\mathsf{b} \in \{x_1|_{\mathsf{v}}\}} \operatorname{Pr}(\mathsf{b}\mathsf{e}) \cdot \prod_{\mathsf{b} \in \{\mathsf{BE} \setminus x_1\}} 1 - \operatorname{Pr}(\mathsf{b}\mathsf{e}) = \\ &= 1 - \sum_{x_2|_{\mathsf{v}} \in X_2} \prod_{\mathsf{b} \in \{x_2|_{\mathsf{v}}\}} \operatorname{Pr}(\mathsf{b}\mathsf{e}) \cdot \prod_{\mathsf{b} \in \{\mathsf{BE} \setminus x_2|_{\mathsf{v}}\}} 1 - \operatorname{Pr}(\mathsf{b}\mathsf{e}) \\ \operatorname{val}^{\operatorname{Cost}_E,\min}(\mathsf{v}) &= (\min_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Cost}_E(\mathsf{b}\mathsf{e}), \min_{x_2|_{\mathsf{v}} \in X_2} \sum_{\mathsf{b} \in \{x_2|_{\mathsf{v}}\}} \operatorname{Cost}_E(\mathsf{b}\mathsf{e})) \\ \operatorname{val}^{\operatorname{Cost}_E,\max}(\mathsf{v}) &= (\max_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Cost}_E(\mathsf{b}\mathsf{e}), \max_{x_2|_{\mathsf{v}} \in X_2} \sum_{\mathsf{b} \in \{x_2|_{\mathsf{v}}\}} \operatorname{Cost}_E(\mathsf{b}\mathsf{e})) \\ \operatorname{val}^{\operatorname{Cost}_E,\max}(\mathsf{v}) &= (\min_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Delay}(\mathsf{b}\mathsf{e}), \min_{x_2|_{\mathsf{v}} \in X_2} \sum_{\mathsf{b} \in \{x_2|_{\mathsf{v}}\}} \operatorname{Delay}(\mathsf{b}\mathsf{e})) \\ \operatorname{val}^{\operatorname{Delay,\min}}(\mathsf{v}) &= (\max_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Delay}(\mathsf{b}\mathsf{e}), \max_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Delay}(\mathsf{b}\mathsf{e})) \\ \operatorname{val}^{\operatorname{Delay,\max}}(\mathsf{v}) &= (\max_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Delay}(\mathsf{b}\mathsf{e}), \max_{x_1 \in X_1} \sum_{\mathsf{b} \in \{x_1\}} \operatorname{Delay}(\mathsf{b}\mathsf{e})) \end{split}$$

Let ADT = (V, E, t) be an attack-defense tree. We say that a valuation  $val_{BE} : BE \rightarrow \{tt, ff\}$  is a *successful attack* if v(g) = tt, and *unsuccessful attack* otherwise<sup>17</sup>. We say a successful attack is *minimal* if there does not exist an basic event be such that  $val_{BE}(be) = tt$  and the modified valuation  $val^*$  where  $val_{BE}^*(be) = ff$  result both in v(g) = tt.

**Theorem 2 (Correctness w.r.t. Boolean Semantics).** Let ADT = (V, E, t) be an attack-defense tree and  $val_{BE}$  be a successful attack, let  $v \in V$  and  $val_{P}^{P}(v) = (X_1, X_2)$ . The equations in Equation (1) hold.

*Proof.* We prove all claims by an induction on the tree structure.

- v is a non-triggerable basic event. For each of the five functions, the value assigned to the basic event is returned. since  $(X_1|_v, X_2|_v) = (\{\{be\}\}, \{\emptyset\})$ , the claims hold by definition.
- Induction Hypothesis: For subtrees rooted in a vertex  $v^*$ , which are predecessors of the vertex v, the equations in Equation (1) hold where v is instantiated with the specific  $v^*$ .
- t(v) = TR: The claims follow by definition of  $val^{Pr}$ ,  $val^{Cost_E,min}$ ,  $val^{Cost_E,max}$ ,  $val^{Delay,min}$  and  $val^{Delay,max}$  and the induction hypothesis (since TR maps to the identity function in all cases).
- -t(v) = NOT: Let v<sup>\*</sup> be the input of vertex. The claims for val<sup>Cost<sub>E</sub>,min</sup>, val<sup>Cost<sub>E</sub>,max</sup>, val<sup>Delay,min</sup> and val<sup>Delay,max</sup> follow by their definition and the

<sup>&</sup>lt;sup>17</sup>Dually, this can be done for defenses by assigning the goal  $\mathbf{g}$  to the defender. Since we do not use player swapping as in [30], there are no changes necessary to this or the following semantics to apply them to defenses. However, the valuation of the basic events might need to be modified (for instance, excluding costs of the attacker when computing costs of successful defenses). In the following, we only talk about attacks and do not explicitly state that our results are dually correct for defenses.

induction hypothesis (since NOT just swaps the components in these cases). For  $val^{Pr}$ , it holds  $val^{Pr}(v) = 1 - val^{Pr}(v^*)$ . By induction hypothesis, we have

- $1 \operatorname{val}^{\Pr}(\mathsf{v}^*) = 1 \sum_{x_1 \in X_1|_{\mathsf{v}^*}} \prod_{\mathsf{be} \in x_1} \Pr(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_1} 1 \Pr(\mathsf{be})$ . By the definition of  $\operatorname{val}^P$  for NOT, this is equivalent to  $1 \sum_{x_2 \in X_2|_{\mathsf{v}^*}} \prod_{\mathsf{be} \in x_2} \Pr(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_2|_{\mathsf{v}}} 1 \Pr(\mathsf{be})$ .
- $1-\operatorname{val}^{\operatorname{Pr}}(\mathsf{v}^*) = 1-(1-\sum_{x_2\in X_2|_{\mathsf{v}^*}}\prod_{\mathsf{be}\in x_2}\operatorname{Pr}(\mathsf{be})\cdot\prod_{\mathsf{be}\in \mathsf{BE}\setminus x_2}1-\operatorname{Pr}(\mathsf{be}))$ . By definition of  $\operatorname{val}^P$  for NOT, this is equivalent to  $\sum_{x_1\in X_1}1-\prod_{\mathsf{be}\in \mathsf{BE}\setminus x_1}\operatorname{Pr}(\mathsf{be}) = \sum_{x_1\in X_1}\prod_{\mathsf{be}\in x_1}\operatorname{Pr}(\mathsf{be})$
- v is a triggerable basic event and triggered by  $v^*$ . Let  $(X_1, X_2) = val^P(v)$ . We apply the induction hypothesis to  $v^*$ .
  - We apply the induction hypothesis to  $v^*$ . • Let  $(x.y) = val^{Cost_E,min}(v^*)$ . Then,  $val^{Cost_E,min}(v) = (x+Cost_E(v), min(y, Cost_E(v)))$ , which is the same as  $(min_{x_1 \in X_1|_{v^*}} \sum_{be \in x_1} Cost_E(be) + Cost_E(v), min(y, Cost_E(v)))$ . That is  $(min_{x_1 \in X_1} \sum_{be \in x_1} Cost_E(be), min_{x_2 \in X_2} \sum_{be \in x_2} Cost_E(be))$  by the definition of  $val^P$  for triggerable basic events (in the first component, we add the vertex to all satisfying assignments of the input, in the second component, we have a union of all unsatisfying assignments, so the minimal element can be computed this way).
    - Analogously, we can prove the claims for  $val^{Cost_E,max}$ ,  $val^{Delay,min}$  and  $val^{Delay,max}$
    - $\operatorname{val}^{\Pr}(\mathsf{v}) = \operatorname{val}^{\Pr}(\mathsf{v}^*) \cdot \Pr(\mathsf{v})$ . By induction hypothesis, this is equivalent to  $(\sum_{x_1 \in X_1 \mid_{\mathsf{v}^*}} \prod_{\mathsf{be} \in x_1} \Pr(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_1} 1 - \Pr(\mathsf{be})) \cdot \Pr(\mathsf{v}) = \sum_{x_1 \in X_1} \prod_{\mathsf{be} \in x_1} \Pr(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_1} 1 - \Pr(\mathsf{be})$ . On the other hand,

$$1 - \sum_{x_2 \in X_2} \prod_{\mathsf{be} \in x_2} \mathsf{Pr}(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_2} 1 - \mathsf{Pr}(\mathsf{be})$$

is equivalent to  $1 - (k \cdot (1 - \Pr(\mathbf{v})) + k \cdot \Pr(\mathbf{v}) + (1 - k) \cdot (1 - \Pr(\mathbf{v})))$  where  $k = \sum_{x_2 \in X_2|_{\mathbf{v}^*}} \prod_{\mathsf{be} \in x_2} \Pr(\mathsf{be}) \cdot \prod_{\mathsf{be} \in \mathsf{BE} \setminus x_2} 1 - \Pr(\mathsf{be})$  by definition of  $\mathsf{val}^P$  for triggerable basic events. We have  $1 - (k - k \cdot \Pr(\mathbf{v}) + k \cdot \Pr(\mathbf{v}) + 1 - k - \Pr(\mathbf{v}) + k \cdot \Pr(\mathbf{v})) = 1 - (1 - \Pr(\mathbf{v}) + k \cdot \Pr(\mathbf{v})) = \Pr(\mathbf{v}) \cdot (1 - k)$ . By induction hypothesis, this is equivalent to  $\Pr(\mathbf{v}) \cdot \mathsf{val}^{\mathbb{P}}(\mathsf{v}^*)$ , which matches the definition of  $\mathsf{val}^{\mathbb{P}}$  for triggerable basic events.

- t(v) = AND: Analogously to the proof for triggerable basic events. However, the induction hypothesis needs to be used on both subtrees.
- t(v) = OR: Analogously to the proof for triggerable basic events. However, the induction hypothesis needs to be used for both subtrees and the proofs of the two claims need to be swapped.

## D Correctness of PAC Analysis

**Theorem 3 (Correctness of PAC Analysis).** Let ADT = (V, E, t) be an attack-defense tree and let  $val_{BE}$  be a PAC valuation for basic events, i.e., for every basic event  $be \in BE$ , it holds  $val_{BE}(be)$  is  $(\epsilon_{be}, \delta_{be})$ -PAC for some  $\epsilon_{be} \in \mathbb{R}_{\geq 0}$  and  $\delta_{be} \in [0, 1]$ . Let  $(\epsilon_g, \delta_g)$  be the error and the probability computed for the

goal g. For any valuation  $\operatorname{val}_{\mathsf{BE}}^*$  such that  $\operatorname{val}_{\mathsf{BE}}^*(\mathsf{be}) \in \operatorname{val}_{\mathsf{BE}}(\mathsf{be}) \pm \epsilon_{\mathsf{be}}$ , it holds  $val^*(g) \in val(g) \pm \epsilon$ .

*Proof.* Instead of proving the claim directly, we show that for any two PAC values  $x, y \in \mathbb{R}_{\geq 0}$  (with  $\epsilon_x, \delta_x$  and  $\epsilon_y, \delta_y$ ), respectively), it holds: Let  $x^* \in x \pm \epsilon_x$ and  $y^* \in y \pm \epsilon_y$ . Then

- 1.  $(1-x^*) \in (1-x) \pm \epsilon_x$ :  $x^*$  is at most  $\epsilon_x$  away from x, i.e. the values range from  $(1 - (x + \epsilon_x)) = (1 - x) - \epsilon_x$  to  $(1 - (x - \epsilon_x)) = (1 - x) + \epsilon_x$ .
- 2.  $x^* \cdot y^* \in (x \cdot y) \pm x \cdot \epsilon_y + y \cdot \epsilon_x + \epsilon_x \cdot \epsilon_y$ : This claim follows by  $(x \pm \epsilon_x) \cdot (y \pm \epsilon_y) = y \cdot x \pm \epsilon_x \cdot y \pm y \cdot \epsilon_x \pm \epsilon_x \cdot \epsilon_y$ .<sup>18</sup>
- 3.  $x^* + y^* \in x + y \pm (\epsilon_x + \epsilon_y)$ : The claim holds since  $(x + \epsilon_x) + (y + \epsilon_y) =$  $\begin{array}{l} x+y+(\epsilon_x,\epsilon_y) \text{ and } (x-\epsilon_x)+(y-\epsilon_y)=x+y-(\epsilon_x,\epsilon_y).\\ 4. \ x^*+y^*-x^*\cdot y^*\in (x+y-x\cdot y)\pm \epsilon_x+\epsilon_y+x\cdot \epsilon_y+y\cdot \epsilon_x+\epsilon_x\cdot \epsilon_y: \text{ This case} \end{array}$
- combines case 2 and case 3.
- 5.  $\max(x^*, y^*) \in \max(x, y) \pm \max(\epsilon_x, \epsilon_y)$ : Clearly,  $\max(x, y) + \max(\epsilon_x, \epsilon_y)$  is the largest value the term can attain. Since  $\epsilon_x, \epsilon_y \ge 0, \max(x, y) - \max(\epsilon_x, \epsilon_y)$ is the smallest value the term can attain. Thus, the biggest error from the maximal value is given by  $\max(\epsilon_x,\epsilon_y).$   $^{19}$
- 6.  $\min(x^*, y^*) \in \min(x, y) \pm \max(\epsilon_x, \epsilon_y)$ : Clearly,  $\min(x, y) \max(\epsilon_x, \epsilon_y)$  is the smallest value the term can attain. Since  $\epsilon_x, \epsilon_y \ge 0$ ,  $\min(x, y) + \max(\epsilon_x, \epsilon_y)$ is the largest value the term can attain. Thus, the biggest error from the minimal value is given by  $\max(\epsilon_x, \epsilon_y)$ .<sup>19</sup>

The result of Theorem 3 then follows from a straightforward induction on the structure of the tree.

<sup>&</sup>lt;sup>18</sup>While we can bound the error from above clearly to  $\epsilon_1 \cdot x_2 + x_2 \cdot \epsilon_2 + \epsilon_1 \cdot \epsilon_2$ , the respective term  $\epsilon_1 \cdot x_2 - x_2 \cdot \epsilon_2 - \epsilon_1 \cdot \epsilon_2$  for a bound from below is not correct. Nevertheless, we slightly over-estimate the true error from below to keep a centered interval under any circumstances and the claim still holds.

<sup>&</sup>lt;sup>19</sup>Using assumptions on the distribution of the error, more precise estimates are possible.

## References

- Étienne André et al. "Parametric analyses of attack-fault trees". In: 2019 19th International Conference on Application of Concurrency to System Design (ACSD). IEEE. 2019, pp. 33–42.
- F. Arnold et al. "Time-Dependent Analysis of Attacks". In: POST. Vol. 8414. LNCS. Springer, 2014, pp. 285–305.
- Zaruhi Aslanyan, Flemming Nielson, and David Parker. "Quantitative Verification and Synthesis of Attack-Defence Scenarios". In: Computer Security Foundations Symposium (CSF). 2016, pp. 105–119. DOI: 10.1109/ CSF.2016.15. URL: https://doi.org/10.1109/CSF.2016.15.
- [4] Kristian Beckers et al. "Determining the probability of smart grid attacks by combining attack tree and attack graph analysis". In: International Workshop on Smart Grid Security. Springer. 2014, pp. 30–47.
- [5] Gerd Behrmann et al. "UPPAAL 4.0". In: Quantitative Evaluation of Systems (QEST). QEST '06. Washington, DC, USA: IEEE Computer Society, 2006, pp. 125-126. ISBN: 0-7695-2665-9. DOI: 10.1109/QEST.2006.
  59. URL: http://dx.doi.org/10.1109/QEST.2006.59.
- [6] Domenico Benvenuto et al. "Application of the ARIMA model on the COVID-2019 epidemic dataset". In: *Data in Brief* 29 (2020). ISSN: 2352-3409. DOI: 10.1016/j.dib.2020.105340. URL: http://dx.doi.org/10. 1016/j.dib.2020.105340.
- [7] Carlos E Budde et al. "JANI: quantitative model and tool interaction". In: Tools and Algorithms for the Construction and Analysis of Systems (TACAS). Springer. 2017, pp. 151–168.
- [8] Ahto Buldas et al. "Attribute evaluation on attack trees with incomplete information". In: Computers & Security 88 (2020), p. 101630.
- [9] Alessandro Buoni, Mario Fedrizzi, and József Mezei. "A Delphi-based approach to fraud detection using attack trees and fuzzy numbers". In: *Proceeding of the IASK International Conferences*. 2010, pp. 21–28.
- [10] Eric J Byres, Matthew Franz, and Darrin Miller. "The use of attack trees in assessing vulnerabilities in SCADA systems". In: *Proceedings of the international infrastructure survivability workshop*. Citeseer. 2004, pp. 3– 10.
- [11] Chris Chatfield. "Calculating Interval Forecasts". In: Journal of Business & Economic Statistics 11.2 (1993), pp. 121-135. URL: http://www.jstor. org/stable/1391361.
- [12] T. Chen et al. "PRISM-games: A Model Checker for Stochastic Multi-Player Games". In: Tools and Algorithms for the Construction and Analysis of Systems (TACAS). Ed. by N. Piterman and S. Smolka. Vol. 7795. LNCS. Springer, 2013, pp. 185–191.
- [13] J. Contreras et al. "ARIMA models to predict next-day electricity prices". In: *IEEE Transactions on Power Systems* 18.3 (2003), pp. 1014–1020.
- [14] A Ezaz Mohammed AL-Dahasi and B Nazar Abbas Saqib. "Attack tree Model for Potential Attacks Against the SCADA System". In: 2019 27th Telecommunications Forum (TELFOR). IEEE. 2019, pp. 1–4.

- [15] Christian Dehnert et al. "A storm is coming: A modern probabilistic model checker". In: International Conference on Computer Aided Verification. Springer. 2017, pp. 592–600.
- [16] Julia Eisentraut and Jan Křetínský. "Expected Cost Analysis of Attack-Defense Trees". In: International Conference on Quantitative Evaluation of Systems. Springer. 2019, pp. 203–221.
- [17] Barbara Fila and Wojciech Wideł. "Attack-defense trees for abusing optical power meters: A case study and the OSEAD tool experience report". In: *International Workshop on Graphical Models for Security*. Springer. 2019, pp. 95–125.
- [18] Marlon Fraile et al. "Using Attack-Defense Trees to Analyze Threats and Countermeasures in an ATM: A Case Study". In: *The Practice of Enterprise Modeling (IFIP)*. 2016, pp. 326–334. DOI: 10.1007/978-3-319-48393-1\\_24. URL: https://doi.org/10.1007/978-3-319-48393-1%5C\_24.
- Olga Gadyatskaya et al. "Attack Trees for Practical Security Assessment: Ranking of Attack Scenarios with ADTool 2.0". In: *Quantitative Evaluation* of Systems (QEST). Cham: Springer, 2016, pp. 159–162. ISBN: 978-3-319-43425-4. DOI: 10.1007/978-3-319-43425-4\_10. URL: http://dx.doi. org/10.1007/978-3-319-43425-4\_10.
- [20] Emden R. Gansner et al. "A Technique for Drawing Directed Graphs". In: *IEEE TRANSACTIONS ON SOFTWARE ENGINEERING* 19.3 (1993), pp. 214–230.
- [21] Arnd Hartmanns and Holger Hermanns. "The Modest Toolset: An Integrated Environment for Quantitative Modelling and Verification". In: Tools and Algorithms for the Construction and Analysis of Systems (TACAS). Ed. by Erika Ábrahám and Klaus Havelund. Vol. 8413. Lecture Notes in Computer Science. Springer, 2014, pp. 593–598. DOI: 10.1007/978-3-642-54862-8\\_51. URL: https://doi.org/10.1007/978-3-642-54862-8\\_51.
- [22] Holger Hermanns et al. "The Value of Attack-Defence Diagrams". In: *Principles of Security and Trust (POST)*. 2016, pp. 163–185. DOI: 10. 1007/978-3-662-49635-0\\_9. URL: http://dx.doi.org/10.1007/978-3-662-49635-0%5C\_9.
- [23] Meriem Houmer and Moulay Lahcen Hasnaoui. "A risk and security assessment of VANET availability using attack tree concept." In: International Journal of Electrical & Computer Engineering (2088-8708) 10.6 (2020).
- [24] Ifan Hughes and Thomas Hase. *Measurements and their uncertainties: a practical guide to modern error analysis.* Oxford University Press, 2010.
- [25] Ravi Jhawar et al. "Attack trees with sequential conjunction". In: IFIP International Information Security and Privacy Conference. Springer. 2015, pp. 339–353.
- [26] Dong-won Kim, Jin-young Choi, and Keun-hee Han. "Risk managementbased security evaluation model for telemedicine systems". In: *BMC Medical Informatics and Decision Making* 20.1 (2020), pp. 1–14.

- [27] Shiho Kim and Rakesh Shrestha. "Security and Privacy in Intelligent Autonomous Vehicles". In: Automotive Cyber Security. Springer, 2020, pp. 35–66.
- [28] Barbara Kordy, Ludovic Pietre-Cambacedes, and Patrick Schweitzer. "DAG-Based Attack and Defense Modeling: Don't Miss the Forest for the Attack Trees". In: CoRR abs/1303.7397 (2013). URL: http://arxiv.org/abs/ 1303.7397.
- [29] Barbara Kordy and Wojciech Wideł. "On Quantitative Analysis of Attack– Defense Trees with Repeated Labels". In: *Principles of Security and Trust* (*POST*). Ed. by Lujo Bauer and Ralf Küsters. Cham: Springer International Publishing, 2018, pp. 325–346. ISBN: 978-3-319-89722-6.
- Barbara Kordy et al. "Foundations of Attack-Defense Trees". In: Proceedings of the 7th International Conference on Formal Aspects of Security and Trust. FAST'10. Pisa, Italy: Springer-Verlag, 2011, pp. 80–95. ISBN: 978-3-642-19750-5. URL: http://dl.acm.org/citation.cfm?id=1964555.1964561.
- [31] Moez Krichen and Roobaea Alroobaea. "A New Model-based Framework for Testing Security of IoT Systems in Smart Cities using Attack Trees and Price Timed Automata". In: Proceedings of the 14th International Conference on Evaluation of Novel Approaches to Software Engineering. SCITEPRESS-Science and Technology Publications, Lda. 2019, pp. 570– 577.
- [32] Rajesh Kumar, Enno Ruijters, and Mariëlle Stoelinga. "Quantitative Attack Tree Analysis via Priced Timed Automata". In: Formal Modeling and Analysis of Timed Systems (FORMATS). 2015, pp. 156–171. DOI: 10. 1007/978-3-319-22975-1\\_11. URL: https://doi.org/10.1007/978-3-319-22975-1%5C\_11.
- [33] Rajesh Kumar and Mariëlle Stoelinga. "Quantitative Security and Safety Analysis with Attack-Fault Trees". In: *High Assurance Systems Engineering* (*HASE*). 2017, pp. 25–32. DOI: 10.1109/HASE.2017.12. URL: https: //doi.org/10.1109/HASE.2017.12.
- [34] M. Kwiatkowska, G. Norman, and D. Parker. "PRISM 4.0: Verification of Probabilistic Real-time Systems". In: Proc. 23rd International Conference on Computer Aided Verification (CAV'11). Vol. 6806. LNCS. Springer, 2011, pp. 585–591.
- [35] J Lopez et al. "Using Attack Trees to Assess Security Controls for Supervisory Control and Data Acquisition Systems (SCADA)". In: Proceedings of the 7th International Conference on Information Warfare and Security. 2012, pp. 166–177.
- [36] Milan Lopuhaä-Zwakenberg, Carlos E Budde, and Mariëlle Stoelinga. "Efficient and generic algorithms for quantitative attack tree analysis". In: *IEEE Transactions on Dependable and Secure Computing* (2022).
- [37] Sjouke Mauw and Martijn Oostdijk. "Foundations of Attack Trees". In: Proceedings of the 8th International Conference on Information Security and Cryptology. ICISC'05. Seoul, Korea: Springer-Verlag, 2006, pp. 186–

198. DOI: 10.1007/11734727\_17. URL: http://dx.doi.org/10.1007/11734727\_17.

- [38] Tony McGough and Sotiris Tsolacos. "Forecasting commercial rental values using ARIMA models". In: Journal of Property Valuation and Investment (1995).
- [39] Miles A. McQueen et al. "Quantitative Cyber Risk Reduction Estimation Methodology for a Small SCADA Control System". In: *Hawaii International Conference on System Sciences (HICSS)*. HICSS '06. Washington, DC, USA: IEEE Computer Society, 2006, pp. 226–. ISBN: 0-7695-2507-5. DOI: 10.1109/HICSS.2006.405. URL: http://dx.doi.org/10.1109/HICSS. 2006.405.
- [40] Alessandro Buoni; Mario Fedrizzi; Jozsef Mezei. "Combining attack trees and fuzzy numbers in a multi-agent approach to fraud detection". In: *International Journal of Electronic Business* 9.3 (2011), pp. 186–202.
- [41] RTO NATO. Improving Common Security Risk Analysis. Tech. rep. RTO Technical Report TR-IST-049, Research and Technology Organisation of NATO, 2008.
- [42] Marc Ohm et al. "Backstabber's Knife Collection: A Review of Open Source Software Supply Chain Attacks". In: arXiv preprint arXiv:2005.09535 (2020).
- [43] Nihal Pekergin, Sovanna Tan, and Jean-Michel Fourneau. "Quantitative Attack Tree Analysis: Stochastic Bounds and Numerical Analysis". In: *International Workshop on Graphical Models for Security*. Springer. 2016, pp. 119–133.
- [44] JLH Ramos and A Skarmeta. "Assessing Vulnerabilities in IoT-Based Ambient Assisted Living Systems". In: Security and Privacy in the Internet of Things: Challenges and Solutions 27 (2020), p. 94.
- [45] David Robles-Ramirez et al. "Model-based Cybersecurity Engineering for Connected and Automated Vehicles: The FLOURISH Project". In: ().
- [46] Yusep Rosmansyah, Ignatius Hendarto, and Demby Pratama. "Impersonation Attack-Defense Tree". In: International Journal of Emerging Technologies in Learning (iJET) 15.19 (2020), pp. 239–246.
- [47] Enno Ruijters et al. "Uniform analysis of fault trees through model transformations". In: 2017 Annual Reliability and Maintainability Symposium (RAMS). IEEE. 2017, pp. 1–7.
- [48] Carsten Schürmann, Lisa Hartmann Jensen, and Rósa María Sigbjörnsdóttir. "Effective Cybersecurity Awareness Training for Election Officials". In: International Joint Conference on Electronic Voting. Springer. 2020, pp. 196– 212.
- [49] Lorenzo Soligo. "Secure deployment of HTTPS: Analysis and open challenges". B.S. thesis. Università Ca'Foscari Venezia, 2020.
- [50] Chee-Wooi Ten, Chen-Ching Liu, and Manimaran Govindarasu. "Vulnerability assessment of cybersecurity for SCADA systems using attack trees". In: 2007 IEEE Power Engineering Society General Meeting. IEEE. 2007, pp. 1–8.

- [51] Wojciech Widel et al. "Beyond 2014: Formal Methods for Attack Tree-based Security Modeling". In: ACM Computing Surveys (CSUR) 52.4 (2019), pp. 1–36.
- [52] Yi Xiao et al. "A multiscale modeling approach incorporating ARIMA and anns for financial market volatility forecasting". In: *Journal of Systems Science and Complexity* 27.1 (2014), pp. 225–236. ISSN: 1559-7067 1009-6124. DOI: 10.1007/s11424-014-3305-4.