# GC-Bench: A Benchmark Framework for Graph Condensation with New Insights

Shengbo Gong<sup>1</sup>\*, Juntong Ni<sup>1</sup>\*, Noveen Sachdeva<sup>2</sup>, Carl Yang<sup>1</sup>, Wei Jin<sup>1</sup>
<sup>1</sup>Department of Computer Science, Emory University, <sup>2</sup>Google Deepmind {shengbo.gong, juntong.ni}@emory.edu noveen@google.com {j.carlyang, wei.jin}@emory.edu

### Abstract

Graph condensation (GC) is an emerging technique designed to learn a significantly smaller graph that retains the essential information of the original graph. This condensed graph has shown promise in accelerating graph neural networks while preserving performance comparable to those achieved with the original, larger graphs. Additionally, this technique facilitates downstream applications such as neural architecture search and enhances our understanding of redundancy in large graphs. Despite the rapid development of GC methods, a systematic evaluation framework remains absent, which is necessary to clarify the critical designs for particular evaluative aspects. Furthermore, several meaningful questions have not been investigated, such as whether GC inherently preserves certain graph properties and offers robustness even without targeted design efforts. In this paper, we introduce GC-Bench, a comprehensive framework to evaluate recent GC methods across multiple dimensions and to generate new insights. Our experimental findings provide a deeper insights into the GC process and the characteristics of condensed graphs, guiding future efforts in enhancing performance and exploring new applications. Our code is available at https: //github.com/Emory-Melody/GraphSlim/tree/main/benchmark.

### 1 Introduction

Graphs are ubiquitous data structures describing relations of entities and have found applications in various domains such as chemistry [1, 2], bioinformatics [3], epidemiology [4], e-commerce [5, 6] and so on. To harness the wealth of information in graphs, graph neural networks (GNNs) have emerged as powerful tools for exploiting structural information to handle diverse graph-related tasks [7, 8, 9, 5, 10]. However, the proliferation of large-scale graph datasets in practical applications introduce significant computational difficulties for GNN utilization [11, 12, 13]. These large datasets complicate GNN training, as time complexity escalates with the increase of nodes and edges. Furthermore, the extensive sizes of these graphs also strain GPU memory, disk storage, and network communication bandwidth [13].

Inspired by dataset distillation (or dataset condensation) [14, 15, 16] in the image domain, graph condensation (GC) [12, 17, 18, 19] has been proposed to learn a significantly smaller (e.g.,  $1,000 \times$  smaller) graph that retains essential information of the original large graph. This condensed graph is expected to train downstream GNNs in a highly efficient manner with minimal performance degradation. As a data-centric technique, GC complements existing model-centric efforts on GNN acceleration [20, 21], since the direct utilization of condensed graph datasets can further speed up these models. Remarkably, GC not only excels at compressing graph data but also shows promise for

<sup>\*</sup>Equal contribution.

various other applications, such as neural architecture search (NAS) [22], privacy preservation [23], and continual learning [24].

Despite the rapid advancements in this field, the lack of a unified and comprehensive evaluation protocol for GC significantly hinders progress in evaluating, understanding and improving these methods. *First*, existing GC methods adopt different approaches to select the best condensed graphs after condensation, including variations in validation models, reliance on test set results rather than validation outcomes, and inconsistent validation intervals. *Second*, while all methods are evaluated based on their condensation performance, many of them overlook critical aspects such as scalability and NAS effectiveness. *Third*, the impact of design choices during condensation, such as data initialization and decisions about learning the graph structure in condensed graphs, remains poorly understood. *Fourth*, despite the success of GC methods in maintaining GNN performance relative to the original graph, it remains unclear whether they also preserve critical information from the original graph, it may potentially filter out noise, but the robustness of GC methods against distortions has not yet been studied. By systematically addressing these limitations, this work aims to shed light on the successes and pitfalls in current GC research and guide future directions in this evolving area.

Our Contributions. We highlight the contributions of our benchmark as follows:

- A Fair Evaluation Protocol. We establish a graph condensation benchmark by introducing a fair and consistent evaluation protocol that facilitates comparison across methods. This unified evaluation approach properly utilizes validation data to select the most effective condensed graphs.
- **Comprehensive Comparison through Multiple Dimensions.** Based on the fair evaluation protocol, we conduct comprehensive comparisons between existing GC methods, which cover multiple dimensions including performance, scalability, transferability, and NAS effectiveness.
- A Unified Codebase for Benchmarking GC. We provide an open-source, well-structured, and user-friendly codebase specifically designed to facilitate easy integration and evaluation of different GC approaches.
- Novel Insights. Through a comprehensive comparison of these methods, we reveal several findings:
   (a) Graph condensation can achieve higher performance at the same reduction rate compared to vision dataset condensation, but they struggle to scale to larger reduction rates.
  - (b) Trajectory matching or the inner optimization of GNN training on the condensed graph is necessary for obtaining transferability and reliable NAS effectiveness.
  - (c) GC methods exhibit a certain level of robustness against structural noise and attack, yet they are less effective against node feature noise. In addition, structure-based methods tend to be more robust than structure-free ones.
  - (d) Compared to structure-based methods, structure-free methods exhibit strong condensation performance and favorable efficiency but poorer robustness.

*Remark.* It is worth noting that a concurrent work [25] also proposes a benchmark for graph condensation. However, our benchmark differs from theirs in several key aspects: (1) We provide unique analysis on graph property preservation and robustness for existing graph condensation methods. (2) We provide a systematic evaluation on the advantages and disadvantages of structure-free and structure-based methods. (3) We include more extensive comparisons with existing graph reduction methods such as coarsening and coreset selection. (4) We present application results on NAS, while their focus is on continual learning. Both the concurrent work and our study make unique contributions to the field of graph condensation.

### 2 Related Work

### 2.1 Graph Condensation

Graph condensation (GC) is an emerging technique designed to create a significantly smaller graph that preserves the maximum amount of information from the original graph [12, 17, 26, 27, 28, 29]. The goal is to ensure that GNNs trained on this condensed graph exhibit comparable performance to those trained on the original one. Existing GC methods fall into two categories: (1) structure-based methods, which synthesize both node features and graph structure, and (2) structure-free methods, which synthesize only node features and do not explicitly generate graph structures.

**Structure-Based Graph Condensation.** To synthesize graph structure, these methods utilize a separate neutral network to generate links between nodes based on the synthetic node features.

**GCond** [12], the first GC method, matches the gradients of the original graph  $\mathcal{T}$  and condensed graphs  $\mathcal{S}$  by:  $\min_{\mathcal{S}} \mathbb{E}_{\theta_0 \sim P_{\theta_0}} \left[ \sum_{t=0}^{T-1} D\left( \nabla_{\theta} \mathcal{L}_{\mathcal{T}}, \nabla_{\theta} \mathcal{L}_{\mathcal{S}} \right) \right]$ , where  $D(\cdot, \cdot)$  denotes a distance function. Then, GCond applies MLP on learned features to generate the graph structure. Inside this optimization, GCond also updates  $\theta$  by training the GNN several epochs on the condensed graph  $\mathcal{S}$ , which is called **inner loop**. However, the nested loop of this method significantly hinders its efficiency and scalability. To address this, **DosCond** [26] proposes a one-step gradient match scheme followed by learning a Bernoulli distribution to sample a graph structure. To avoid generating dense graphs while producing diverse structures, **MSGC** [28] utilizes multiple sparse graphs to enhance the capture of neighborhood information. To explicitly incorporate the information of original structure, **SGDD** [29] broadcasts the original structure into the synthetic graph by optimal transport.

**Structure-Free Graph Condensation.** Some other methods do not generate graph structure during the condensation. An important hypothesis for designing a structure-free method is that the structure information can be incorporated into the synthetic node features. As a variant of GCond, GCondX [12] only learns the condensed node features via gradient matching without an inner loop as suggested by the original paper. SFGC [30] learns node features by matching the GNN training trajectories with the guidance of the offline expert parameter distribution:  $\min_{\mathcal{S}} \mathcal{L} = \parallel \hat{\theta}_{t+N} - \theta_{t+M}^* \parallel_2^2$ , where  $\hat{\theta}$  is the student parameters optimized on condensed graph and  $\theta^*$  is the expert parameters. **GEOM** [27] utilizes an expanding window technique that adjusts the matching range for nodes of varying difficulty during the process of matching training trajectories. To address the issue of higher computational consumption in the inner loop, **GCSNTK** [31] replaces it with Graph Neural Tangent Kernel (GNTK) [32] in the Kernel Ridge Regression (KRR) paradigm, which can efficiently synthesize a smaller graph:  $\mathcal{L}_{\text{KRR}} = \frac{1}{2} \parallel \mathbf{y}_{\mathcal{T}} - \mathbf{K}_{\mathcal{TS}} (\mathbf{K}_{\mathcal{SS}} + \epsilon \mathbf{I})^{-1} \mathbf{y}_{\mathcal{S}} \parallel^2$ , where **K** is the kernel matrix and **y** is concatenated graph labels <sup>2</sup>.

### 2.2 Coreset Selection and Graph Coarsening

**Coreset Selection.** Coreset selection [33] is a widely used strategy to select the most representative samples based on specific criteria. In graph domain, it typically selects nodes or edges and then utilizes selected nodes or edges to induce a small graph. To avoid label leakage, the following selection methods are all selecting nodes from training set. We choose the following coreset selection methods as our baselines: **Random**, which randomly selects nodes. **KCenter** [33, 34] selects nodes in a way that minimizes the maximum distance of any node's embedding to the nearest chosen center, thereby effectively covering the feature space. **Herding** [35] selects nodes by iteratively minimizing the difference between the mean embedding and the sum of the embeddings of the selected nodes. More selection methods are explored in Appendix A.3.

**Graph Coarsening.** To avoid missing important nodes, graph coarsening methods group nodes and aggregate them to supernodes. The following graph coarsening methods are chosen as baselines — **Virtual Node Graph (VNG)** [36] minimizes the forward propagation error by applying weighted k-means to obtain a mapping matrix, which maps each node to a supernode. VNG obtains the adjacency matrix by solving an optimization problem. **Averaging**, a data initialization strategy in MSGC [28], creates supernodes by averaging the features of training set nodes within each class.

**Remark.** We emphasize the necessity of exploring a broader spectrum of graph reduction methods beyond GC. **First**, recent years have seen the development of many coreset selection [37] and coarsening methods [38], which show high potential in preserving GNN performance. Thus, these methods are indispensable baselines for comparison with GC methods. **Second**, these methods can all serve as data initialization strategies for GC as we will explore in Section 4.5. Therefore, it can be limited to study GC in isolation without considering other graph reduction methods.

### **3** Benchmark Design

### 3.1 Evaluation Protocol

A Unified Evaluation Approach. Existing GC methods employ a variety of evaluation strategies to identify optimal condensed graphs throughout the condensation process. First, some approaches utilize the GNTK as the validation model, while others employ conventional GNNs. Second, some select graphs based on the best test results rather than validation results. Third, some assess the

<sup>&</sup>lt;sup>2</sup>GCSNTK only synthesizes structure for Flickr and Reddit, and thus we treat it as a structure-free method.

condensed graph at every condensation epoch, whereas others opt for periodic evaluations to conserve computational resources. Consequently, a unified evaluation approach is crucial for ensuring a fair comparison. Moreover, many methods neglect essential dimensions of evaluation such as scalability, transferability, and NAS performance. Thus, we establish this benchmark to facilitate a comprehensive comparison of various GC methods across the key aspects:

(a) Performance and Scalability. We first attempt to reproduce and measure the basic results of all graph reduction methods within our scope. In addition to evaluating the performance of GCN in node classification, we assess their efficiency and highlight the trade-off between performance and efficiency to assist users in selecting the appropriate method based on their hardware resources. Our efficiency reports include preprocessing time, running time per epoch, total running time, peak memory usage, and GPU memory usage. By examining the resource consumption across various dataset sizes and reduction rates, we can also illustrate the scalability of different methods. Additionally, we also examine the condensation performance across broader reduction rates. Metrics summary: We expect a graph condensation method to achieve good performance while also ensuring high efficiency.

(b) Transferability. The most critical aspect of evaluating GC methods is determining whether the condensed data can be effectively used to train diverse GNNs, adhering to a data-centric perspective. Usually, condensed graphs are closely tied to the backbone GNN used during the condensation process such as GCN and SGC, potentially embedding the inductive biases of that particular GNN, which might impair their performance on other GNNs. To address this concern, we aim for condensed graphs to exhibit consistent performance across different GNNs. Some previous studies [26, 28] don't include experiments evaluating transferability across GNNs. Additionally, evaluations of various methods are often performed on different datasets or reduction rates, hindering fair comparison. Thus, we assess the performance of condensed graphs on multiple widely-used GNN models with a unified evaluation setting. Metrics summary: A high-quality condensed graph, like a graph in the real world, should be versatile enough to train different models.

(c) Neural Architecture Search (NAS). NAS [39, 40] is one of the most promising applications of graph condensation. NAS focuses on identifying the most effective architecture from a vast pool of potential models. This technique is characterized by its intensive computational demands, necessitating the training of numerous architectures on the full dataset and choosing the top performer based on validation results. Since the condensed graph is much smaller than the whole graph, graph condensation methods are utilized to accelerate NAS [22]. In practical situations, preserving the rank of validation results between models trained on the condensed graph and the whole graph is important because we select the best architectures based on top validation results. We argue that all the graph condensation methods should be evaluated on the NAS task because it can effectively evaluate the practical value of a condensation method. *Metrics summary: We expect a reliable correlation in validation performance between training on the condensed graph and the whole graph to be observed*.

### 3.2 Impact of Intermediate Choices

Current GC methods share similar procedures, offering multiple choices at each intermediate stage. However, the impact of these choices remains underexplored.

**Data Initialization.** As a crucial stage in the standard procedure of GC, data initialization helps accelerate convergence and enhances final results [16]. Besides, the initialization of the condensed graph can naturally integrated with coreset selection and graph coarsening methods. Previous work primarily relies on random selection for data initialization, with only a few studies employing alternative methods such as KCenter and Averaging [27, 28]. Therefore, we aim to conduct a comprehensive study on whether different data initialization can impact the performance of GC.

**Structure-Free vs. Structure-Based Methods.** Another important choice is whether to condense the structure. To assist future research in making this decision, we discuss the advantages and disadvantages of structure-free and structure-based methods in Section 4.2 and 4.7.

### **3.3** Deeper Probe on Graph Condensation

**Graph Property Preservation.** Graphs naturally contain features, structures, and labels. Numerous metrics are developed to characterize these aspects. Leveraging these developments, we aim to explore what kind of graph properties are preserved by condensed graphs and understand the reasons behind the success of current GC methods. We study the preservation of graph properties by the following metrics: **Density, Max Eigenvalue** of Laplacian matrix, Davies-Bouldin Index (**DBI**) [41] and **Homophily** [42]. To further incorporate structural information into DBI, we developed a new

metric named **DBI-AGG**, which calculates DBI based on node embeddings after two rounds of GCN-like aggregation. The aspect that each metric covers is listed in Table 3.

**Robustness.** Since GC preserves the essential information of the original graph, it can potentially reduce noise present in the original graph, even though it is not specifically designed for this purpose. We hypothesize that this capability may provide GC with robustness against various types of noise. To study the robustness of GC, we inject three types of corruptions to the original graph before inputting it into the GC algorithms: (1) **Feature noise**, which randomly changes features for all nodes, (2) **Structural noise**, which randomly modifies edges, and (3) **Adversarial structural attack**, which learns corrupt graph structure to degrade the performance of the GNN model. Furthermore, to examine the robustness of GC in two settings, transductive and inductive, we apply poisoning plus evasion corruption (i.e., corrupting both the training and test graphs) on transductive datasets, and poisoning corruption (i.e., only corrupting the training graph) on inductive datasets.

### 4 Empirical Studies

### 4.1 Experimental Setup

In an attempt to address unfairness in this area, we unify some of the settings in GC papers while leaving other hyperparameters as reported in their papers or source code. First, we restrict one set of hyperparameters for each dataset, ensuring that they do not vary across different reduction rates. For methods that do not follow this setting, we use the set of hyperparameters from the highest reduction rate. This setting is more practical because tuning for every reduction rate can be very expensive. **Second**, we set the evaluation interval to the number of epochs divided by 10 to balance the frequency of intermediate evaluations and total epochs for each method. Third, we adopt GCN in all evaluation parts, training a 2-layer GCN with 256 hidden units on the reduced graph. We then evaluate it on the validation and test sets of the original graph, using 300 epochs without early stopping. We select condensed graphs with best validation accuracy for final evaluation. To mitigate the effect of randomness, we run each evaluation 10 times and report the average performance. The above GNN training settings are applied across intermediate, final evaluations, and all other experiments. Additionally, sparsification is only applied to the final evaluation, with the threshold adhering to the reported results in the original paper. Specifically, for structure-free methods, an identity matrix is used as the adjacency matrix during training stage. Then, in inference stage, the original graph is input into the trained model. To benchmark methods under both transductive and inductive settings, we use the former for Citeseer, Cora [7], and Arxiv [43], and the latter for Flickr and Reddit [44]. All data preprocessing and training/validation/test set splits follow the GCond paper [12]. More details about datasets and implementation are in Appendix A.1 and A.2.

### 4.2 Performance and Scalability

We report the performance of graph reduction methods in Table 1 and the trade-off between performance and efficiency in Figure 1. From Table 1, we observe that GC methods significantly outperform coreset selection and coarsening methods, especially at low reduction rates. Among all, GEOM and SFGC lead across most datasets and reduction rates. They are only outperformed by structure-based methods at low reduction rates on small graphs. Similarly, when solely comparing GCondX and GCond, the absence of structure seems to impede performance.

We report the efficiency and resource consumption in Figure 2 and find that: (1) Though achieving state-of-the-art performance in Table 1, both GEOM and SFGC require additional preprocess time and large disk space to produce and store the trajectory of experts. (2) Structure-based methods require more memory and GPU resources compared to structure-free ones, especially for large graphs. This can be concluded from the comparison between GCond and GCondX. (3) Structure-free methods show better scalability across reduction rates, as the computational resources do not increase significantly with the increase of reduction rates. The reason is that these methods are free from the inner loop and do not synthesize the structure.

Furthermore, we adjust the reduction rate from values corresponding to only one node per class to values that cause OOM on large datasets and present the results in Figure 3. While Figure 3 generally shows a positive correlation between performance and the reduction rate, we have three unique findings that are not observed in vision dataset condensation [16]: (1) GC methods can still perform well when the Instance Per Class (IPC) is as low as 1; (2) Unlike in the CV domain, GC

Table 1: Performance of graph reduction methods under three reduction rates. The best and the second-best results, excluding the whole graph training, are marked in **bold** and underlined.

_	Reduction	Co	reset Selec	tion	Coarsen					Conden	sation				
Dataset	Rate (%)		eset seree	lion	course			Structure-free			Structure-based				Whole
		Random	Herding	KCenter	Averaging	VNG	GCondX	GEOM	SFGC	GCSNTK	DosCond	GCond	MSGC	SGDD	
	0.36	35.37	43.73	41.43	69.75	66.14	67.79	67.61	66.27	63.51	69.41	70.05	60.24	71.87	
Citeseer	0.90	50.71	59.24	51.15	69.59	66.07	69.69	70.70	70.27	62.91	70.83	69.15	72.08	70.52	72.6
	1.80	62.62	66.66	59.04	69.50	65.34	68.38	73.03	72.36	63.90	72.18	69.35	72.21	69.65	
	0.50	35.14	51.68	44.64	75.94	70.40	79.74	78.14	75.11	71.58	80.65	80.17	80.54	80.15	
Cora	1.30	63.63	68.99	63.28	75.87	74.48	78.67	82.29	79.55	71.22	80.85	80.81	80.98	80.29	81.5
	2.60	72.24	73.77	70.55	75.76	76.03	78.60	82.82	80.54	73.34	<u>81.15</u>	80.54	80.94	81.04	
	0.05	50.39	51.49	50.52	59.62	54.89	59.40	64.91	64.91	58.21	55.70	60.49	57.66	58.50	
Arxiv	0.25	58.92	58.00	55.28	59.96	59.66	62.46	<b>68.78</b>	66.58	59.98	57.39	63.88	64.85	59.18	71.4
	0.50	60.19	57.70	58.66	59.94	60.93	59.93	69.59	67.03	54.73	61.06	64.23	65.73	63.76	
	0.10	42.94	42.80	43.01	37.93	44.33	46.66	47.15	46.38	41.85	45.87	46.75	46.21	46.69	
Flickr	0.50	44.54	43.86	43.46	37.76	43.30	46.69	46.71	46.38	33.39	45.89	47.01	46.77	46.39	47.4
	1.00	44.68	45.12	43.53	37.66	43.84	46.58	46.13	<u>46.61</u>	31.12	45.81	46.99	46.12	46.24	
	0.05	40.13	46.88	40.24	88.23	69.96	86.56	90.63	90.18	OOM	86.56	85.39	87.62	87.37	
Reddit	0.10	55.73	59.34	48.28	88.32	76.95	88.25	91.33	89.84	OOM	88.32	89.82	88.15	88.73	94.4
	0.20	58.39	73.46	56.81	88.33	81.52	88.73	91.03	90.71	OOM	88.84	90.42	87.03	90.65	





Figure 2: Comparison of GPU memory, disk memory, preprocess time, and total time on Arxiv (r = 0.5%).



Figure 1: Test accuracy vs. total time for



methods cannot scale to larger IPC values due to OOM issues; (3) Structure-based GC methods are more susceptible to OOM than structure-free methods. We foresee the need for more scalable GC techniques, particularly those structure-based ones. In addition, our results indicate some instability of structure-free GC, as shown by r=0.5% on Reddit for GEOM and r=1.25% on Arxiv for GCondX.

Key Takeaway 1: Compared to structure-based methods, structure-free methods are more efficient while still performing well.

**Key Takeaway 2:** GC can achieve higher performance at the same reduction rate compared to vision dataset condensation, but they struggle to scale to larger reduction rates where vision datasets can.

### 4.3 Transferability

blue and red, respectively.

We conduct extensive experiments assessing the performance of condensed graphs on six widely-used GNN models: GCN [7], SGC [45], APPNP [46], Cheby [47], GraphSage [11] and GAT [8]. All evaluation models adopt 2 convolutional layers, with the search space for hyperparameters listed in Appendix A.4. To simplify, we fix the reduction ratios at 2.6%, 0.5%, and 0.1% for Cora, Arxiv and Reddit, respectively. From Figure 9 we can observe that: **First**, there is no significant performance loss for most methods when condensed graphs are transferred to various GNNs. This highlights the success of GC methods, which typically use GCN or SGC for condensation. Second, GEOM and SFGC achieve significantly better performance than GCondX. Similarly, GCond outperforms



Figure 4: Condensed graph performance evaluated by different GNNs. The **relative accuracy** refers to the accuracy preserved compared to training on the whole dataset.

Table 2: NAS evaluation. The best result is in **bold**. The runner-up is <u>underlined</u>. The worst is colored red.

	Random	K-Center	GCondX	SFGC	GEOM	GCond	DosCond	MSGC	Whole
Top 1 (%)	81.88	81.74	81.49	82.42	82.19	81.82	81.91	82.40	82.51
Acc. Corr.	0.56	0.47	0.40	0.72	0.65	0.70	0.14	0.71	-
Rank Corr.	0.64	0.60	0.57	0.71	0.74	0.66	0.20	0.78	-

DosCond. These two phenomena indicate that trajectory matching or the inner loop is key to improving transferability. We conjecture these two designs introduce additional inductive biases related to the backbone models used in the condensation process, which could benefit all message-passing based GNNs. **Third**, for some methods such as DosCond and SGDD, GAT performs much worse than other GNNs because it is more structure-sensitive and can only leverage the connection information instead of the edge weights. **Overall**, GC methods can generally be easily transferred to different GNNs, since most GNNs follow the message-passing paradigm. We also investigate the transferability to Graph Transformer [48] in Appendix A.4. We find that the performance of Graph Transformer drops a lot, which suggests future research should explore the transferability to non-GNN graph learning architectures. **In addition**, we observe that Averaging achieves comparable transferability to GC methods on Reddit, revealing the potential of simple graph reduction methods.

**Key Takeaway 1:** GC methods can generally be easily transferred to different GNNs. **Key Takeaway 2:** Trajectory matching or the inner loop facilitates transferability.

### 4.4 Neural Architecture Search

As one of the most promising applications of GC, we evaluate the performance of NAS using three commonly-used metrics: Top 1 test accuracy, correlation between validation set accuracies, and correlation between ranks of validation set accuracies of the condensed graph and the whole graph. We use the Pearson coefficient [49] to quantify the correlation. We conduct NAS with APPNP, a flexible GNN model whose structure can vary by using a different number of propagation layers, residual coefficients, etc. More details are provided in the Appendix A.5. The results listed in Table 2 demonstrate that: (1) GC methods show a higher potential to figure out the best architectures, sometimes even surpassing the original dataset; (2) Both the structure-free methods, which use trajectory matching, and the structure-based method, which synthesizes multiple adjacency matrices, work well in NAS; (3) The methods without an inner loop, i.e., DosCond and GCondX, exhibits poor NAS results with Pearson coefficient lower than 0.6. We speculate that the inner loop, which accesses the training trajectory, is crucial for achieving effective NAS.

Key Takeaway 1: Trajectory matching or inner loop is necessary to obtain reliable NAS effectiveness.

### 4.5 Data Initialization

To study the impact of different data initialization strategies, we equip 5 GC methods with 4 initializations across all datasets. Figure 5 illustrates that there is no single best data initialization method for every GC method or dataset, due to the high heterogeneity of these methods and graph datasets. However, there are some notable exceptions. **First**, KCenter is the average best initialization method for most datasets. It is also the best choice for structure-free methods, especially GEOM. **Second**,



Figure 5: Test accuracy for different methods with different initialization.

Table 3: Graph properties of condensed graphs on Cora and correlation between original and condensed graphs across all datasets. Potential preserved properties are in **bold**.

Graph Property		VNG	GCond	MSGC	SGDD	Avg.	Whole
Density%	<i>Cora</i>	52.17	82.28	22.00	100.00	64.11	0.14
(Structure)	Corr.	-0.81	0.07	0.55	0.13	-0.02	
Max Eigenvalue	<i>Cora</i>	3.73	34.90	1.69	14.09	13.60	169.01
(Spectra)	Corr.	0.85	0.25	0.95	0.28	0.58	
DBI	<i>Cora</i>	3.69	1.84	0.70	4.34	2.64	9.28
(Label & Feature)	Corr.	0.81	0.93	0.94	0.97	<b>0.91</b>	
DBI-AGG	<i>Cora</i>	3.59	0.38	0.57	0.18	1.18	4.67
(Label & Feat. & Stru.)	Corr.	0.99	0.93	0.95	0.89	<b>0.94</b>	
Homophily	<i>Cora</i>	0.14	0.16	0.19	0.13	0.16	0.81
(Label & Structure)	Corr.	-0.83	-0.68	-0.46	-0.80	-0.69	

Averaging is a very unstable strategy, especially for large datasets, and it only works in rare cases. From the analysis above, we can conclude that GC methods do not need to be consistently good with different initialization strategies. Therefore, we recommend treating initialization strategies as hyperparameters in future studies. Additionally, when we compare it with coreset selection columns in Table 1, we find that the best selection method, Herding, is not necessarily the best data initialization method for GC. This finding cautions that future research should carefully combine different graph reduction methods, as various GC methods may not complement each other effectively.

**Key Takeaway 1:** Current initialization strategies do not have a consistent impact across all datasets or GC methods. We suggest treating it as hyperparameters.

Key Takeaway 2: Better coreset selection methods do not guarantee better GC initialization.

### 4.6 Graph Property Preservation

We explore the relationship between graph property preservation and structure-based GC methods. We calculate the metrics related to different graph properties for the condensed graph. For MSGC which produces multiple graphs, we calculate the average results. Despite examining various graph-size-agnostic graph properties, our results in Table 3 show that none of the absolute values tend to be preserved. Consequently, we resort to the Pearson correlation between metrics in the original and condensed graphs. For full results on all datasets and structure-free methods, we refer readers to Appendix A.6. From the results, we can conclude that only **DBI** and **DBI-AGG** are relatively preserved, as they have average correlation coefficients of 0.91 and 0.94. Therefore, we suggest that researchers explicitly preserve these two properties to potentially bolster performance. In contrast, **Density** appears to be the least important property to preserve among these GC methods. Additionally, we observe that a homophilous graph is often condensed into a heterophilous graph while still achieving high performance and homophily [50, 51] in future studies.

**Key Takeaway 1:** None of the absolute values of properties is preserved in the condensed graph. **Key Takeaway 2:** Only the properties related to node features and aggregated features, i.e., **DBI** and **DBI-AGG**, are relatively preserved in condensed graphs.

_		Featur	e Noise	Structu	ral Noise	Adversarial S	Structural Attack
Dataset	Method	Test Acc. ↑	Perf. Drop $\downarrow$	Test Acc. ↑	Perf. Drop $\downarrow$	Test Acc. ↑	Perf. Drop↓
	Whole	64.07	11.75%	57.63	20.62%	53.90	25.76%
Citasaar 1.80%	GCond	64.06	7.63%	65.64	5.35%	66.19	4.55%
Cheseer 1.0%	GCondX	61.27	10.40%	60.42	11.65%	60.75	11.15%
	GEOM	58.77	19.53%	51.41	29.60%	57.94	20.67%
	Whole	74.77	8.26%	72.13	11.49%	66.63	18.24%
Cora 260	GCond	67.62	16.04%	63.14	21.61%	68.90	14.45%
Cora 2.0%	GCondX	67.72	13.85%	63.95	18.63%	69.24	11.91%
	GEOM	49.68	40.01%	53.59	35.29%	66.32	19.93%
	Whole	46.68	1.51%	42.60	10.13%	44.44	6.24%
Eliabre 10%	GCond	46.29	1.49%	46.97	0.04%	43.90	6.58%
<i>Γιι</i> ΟΚΓ 1%	GCondX	45.60	2.11%	46.19	0.83%	42.00	9.83%
	GEOM	45.38	1.63%	45.52	1.32%	<u>44.72</u>	3.06%

Table 4: Robustness evaluation. "Perf. Drop" shows the relative loss of accuracy compared to the original results before corruption. The best results are in **bold** and results that outperform whole dataset training are underlined. Structure-free and structure-based methods are colored blue and red.

### 4.7 Robustness

To explore the robustness benefits of GC methods, specifically their resilience to noise in the graph condensation process, we implement three types of representative corruptions as outlined in Section 3.3. These include: (1) **Feature Noise**: We simulate feature noise by masking node features to zero. (2) **Structural Noise**: This is introduced by randomly adding edges to the graph. (3) **Adversarial Structural Attack**: We employ PR-BCD [52], a scalable adversarial attack using Projected Gradient Descent (PGD). In transductive settings, where the full graph is under consideration, we apply both poisoning and evasion corruptions. This affects both the training and test phases of the graph. The perturbation rates are set to 50% for feature and structural noise and 25% for adversarial structural attack, respectively. Each corruption is repeated three times, producing three distinct corrupted graphs. We then evaluate and report the average performance across these graphs.

As illustrated in Table 4, GC methods outperform GCN trained on the whole corrupted graph in the last two structural corruptions, but GC does not show robustness against feature noise. Additionally, the state-of-the-art methods GEOM and the structure-free version of GCond, GCondX show lower performance compared to GCond after being corrupted, indicating that structure-free methods lose some robustness if they do not synthesize the structure.

**Key Takeaway 1:** GC methods naturally contain a certain level of robustness against structural noise and attack. Structure-based methods are more robust than structure-free ones.

### 5 Conclusion and Outlook

This paper establishes the first benchmark for GC methods with multi-dimension evaluation, providing insights on intermediate choices, graph property preservation and robustness of current GC methods. The findings from our experimental results inspire the following future directions:

- (1) Scalability. Future work can scale GC methods to larger datasets and larger reduction rates.
- (2) **Robustness.** Future work can further explore the robustness of graph condensation methods under diverse corruptions, such as feature attacks and out-of-distribution (OOD) and develop techniques to enhance their robustness against these corruptions. Furthermore, it would also be of interest to incorporate GNN defense methods to enhance the robustness of GC methods.
- (3) Leveraging coreset selection or coarsening. Future work can combine powerful coreset selection and graph coarsening methods, making GC competitive in both efficiency and performance.

**Limitations.** We anticipate that our benchmark and insights will contribute to progress in the field and encourage the development of more practical GC methods going forward. However, GC-Bench is not without limitations and some areas of benchmarking can be further explored. These include measuring NAS effectiveness in larger architecture spaces such as Graph Design Space [53], examining the transferability of condensed knowledge to various domains and downstream tasks, and identifying and preserving certain graph properties to improve performance.

### References

- [1] Patrick Reiser, Marlen Neubert, André Eberhard, Luca Torresi, Chen Zhou, Chen Shao, Houssam Metni, Clint van Hoesel, Henrik Schopmans, Timo Sommer, et al. Graph neural networks for materials science and chemistry. *Communications Materials*, 3(1):93, 2022.
- [2] Zhichun Guo, Bozhao Nan, Yijun Tian, Olaf Wiest, Chuxu Zhang, and Nitesh V Chawla. Graph-based molecular representation learning. *International Joint Conference on Artificial Intelligence*, 2023.
- [3] Hao Wang, Jiaxin Yang, and Jianrong Wang. Leverage large-scale biological networks to decipher the genetic basis of human diseases using machine learning. *Artificial Neural Networks*, pages 229–248, 2021.
- [4] Zewen Liu, Guancheng Wan, B Aditya Prakash, Max SY Lau, and Wei Jin. A review of graph neural networks in epidemic modeling. *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2024.
- [5] Yu Wang, Yuying Zhao, Yi Zhang, and Tyler Derr. Collaboration-aware graph convolutional network for recommender systems. In *Proceedings of the ACM Web Conference 2023*, 2023.
- [6] Kaize Ding, Albert Jiongqian Liang, Bryan Perozzi, Ting Chen, Ruoxi Wang, Lichan Hong, Ed H Chi, Huan Liu, and Derek Zhiyuan Cheng. Hyperformer: Learning expressive sparse feature representations via hypergraph transformer. In *Proceedings of the 46th International* ACM SIGIR Conference on Research and Development in Information Retrieval, pages 2062– 2066, 2023.
- [7] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.
- [8] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018.
- [9] Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S Yu. A comprehensive survey on graph neural networks. *arXiv preprint arXiv:1901.00596*, 2019.
- [10] Jiajun Zhou, Zhi Chen, Min Du, Lihong Chen, Shanqing Yu, Guanrong Chen, and Qi Xuan. Robustecd: Enhancement of network structure for robust community detection. *IEEE Transactions* on Knowledge and Data Engineering, 35(1):842–856, 2021.
- [11] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017.
- [12] Wei Jin, Lingxiao Zhao, Shichang Zhang, Yozen Liu, Jiliang Tang, and Neil Shah. Graph condensation for graph neural networks. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=WLEx3Jo4QaB.
- [13] Shichang Zhang, Atefeh Sohrabizadeh, Cheng Wan, Zijie Huang, Ziniu Hu, Yewen Wang, Jason Cong, Yizhou Sun, et al. A survey on graph neural network acceleration: Algorithms, systems, and customized hardware. arXiv preprint arXiv:2306.14052, 2023.
- [14] Tongzhou Wang, Jun-Yan Zhu, Antonio Torralba, and Alexei A Efros. Dataset distillation. *arXiv preprint arXiv:1811.10959*, 2018.
- [15] Ruonan Yu, Songhua Liu, and Xinchao Wang. Dataset distillation: A comprehensive review. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.
- [16] Justin Cui, Ruochen Wang, Si Si, and Cho-Jui Hsieh. Dc-bench: Dataset condensation benchmark. *Advances in Neural Information Processing Systems*, 35:810–822, 2022.
- [17] Mohammad Hashemi, Shengbo Gong, Juntong Ni, Wenqi Fan, B Aditya Prakash, and Wei Jin. A comprehensive survey on graph reduction: Sparsification, coarsening, and condensation. *International Joint Conference on Artificial Intelligence (IJCAI)*, 2024.
- [18] Xinyi Gao, Junliang Yu, Wei Jiang, Tong Chen, Wentao Zhang, and Hongzhi Yin. Graph condensation: A survey. *arXiv preprint arXiv:2401.11720*, 2024.
- [19] Hongjia Xu, Liangliang Zhang, Yao Ma, Sheng Zhou, Zhuonan Zheng, and Bu Jiajun. A survey on graph condensation. *arXiv preprint arXiv:2402.02000*, 2024.

- [20] Tianlong Chen, Yongduo Sui, Xuxi Chen, Aston Zhang, and Zhangyang Wang. A unified lottery ticket hypothesis for graph neural networks. In *International conference on machine learning*, pages 1695–1706. PMLR, 2021.
- [21] Guibin Zhang, Kun Wang, Wei Huang, Yanwei Yue, Yang Wang, Roger Zimmermann, Aojun Zhou, Dawei Cheng, Jin Zeng, and Yuxuan Liang. Graph lottery ticket automated. In *The Twelfth International Conference on Learning Representations*, 2023.
- [22] Mucong Ding, Xiaoyu Liu, Tahseen Rabbani, Teresa Ranadive, Tai-Ching Tuan, and Furong Huang. Faster hyperparameter search for gnns via calibrated dataset condensation. 2022.
- [23] Qiying Pan, Ruofan Wu, LIU Tengfei, Tianyi Zhang, Yifei Zhu, and Weiqiang Wang. Fedgkd: Unleashing the power of collaboration in federated graph neural networks. In *NeurIPS 2023 Workshop: New Frontiers in Graph Learning*, 2023.
- [24] Yilun Liu, Ruihong Qiu, and Zi Huang. Cat: Balanced continual graph learning with graph condensation. In 2023 IEEE International Conference on Data Mining (ICDM), pages 1157– 1162. IEEE, 2023.
- [25] Yilun Liu, Ruihong Qiu, and Zi Huang. Gcondenser: Benchmarking graph condensation. 2024.
- [26] Wei Jin, Xianfeng Tang, Haoming Jiang, Zheng Li, Danqing Zhang, Jiliang Tang, and Bing Yin. Condensing graphs via one-step gradient matching. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 720–730, 2022.
- [27] Yuchen Zhang, Tianle Zhang, Kai Wang, Ziyao Guo, Yuxuan Liang, Xavier Bresson, Wei Jin, and Yang You. Navigating complexity: Toward lossless graph condensation via expanding window matching. *arXiv preprint arXiv:2402.05011*, 2024.
- [28] Jian Gao and Jianshe Wu. Multiple sparse graphs condensation. *Knowledge-Based Systems*, 278:110904, 2023.
- [29] Beining Yang, Kai Wang, Qingyun Sun, Cheng Ji, Xingcheng Fu, Hao Tang, Yang You, and Jianxin Li. Does graph distillation see like vision dataset counterpart? *Advances in Neural Information Processing Systems*, 36, 2024.
- [30] Xin Zheng, Miao Zhang, Chunyang Chen, Quoc Viet Hung Nguyen, Xingquan Zhu, and Shirui Pan. Structure-free graph condensation: From large-scale graphs to condensed graph-free data. *Advances in Neural Information Processing Systems*, 36, 2024.
- [31] Lin Wang, Wenqi Fan, Jiatong Li, Yao Ma, and Qing Li. Fast graph condensation with structure-based neural tangent kernel. *arXiv preprint arXiv:2310.11046*, 2023.
- [32] Simon S Du, Kangcheng Hou, Russ R Salakhutdinov, Barnabas Poczos, Ruosong Wang, and Keyulu Xu. Graph neural tangent kernel: Fusing graph neural networks with graph kernels. *Advances in neural information processing systems*, 32, 2019.
- [33] Sariel Har-Peled and Akash Kushal. Smaller coresets for k-median and k-means clustering. In Proceedings of the twenty-first annual symposium on Computational geometry, pages 126–134, 2005.
- [34] Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. *arXiv preprint arXiv:1708.00489*, 2017.
- [35] Max Welling. Herding dynamical weights to learn. In *Proceedings of the 26th annual international conference on machine learning*, pages 1121–1128, 2009.
- [36] Si Si, Felix Yu, Ankit Singh Rawat, Cho-Jui Hsieh, and Sanjiv Kumar. Serving graph compression for graph neural networks. In *The Eleventh International Conference on Learning Representations*, 2022.
- [37] Mucong Ding, Yinhan He, Jundong Li, and Furong Huang. Spectral greedy coresets for graph neural networks. *arXiv preprint arXiv:2405.17404*, 2024.
- [38] Linfeng Cao, Haoran Deng, Chunping Wang, Lei Chen, and Yang Yang. Graph-skeleton: 1% nodes are sufficient to represent billion-scale graph. *arXiv preprint arXiv:2402.09565*, 2024.
- [39] Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *Journal of Machine Learning Research*, 20(55):1–21, 2019.
- [40] Pengzhen Ren, Yun Xiao, Xiaojun Chang, Po-Yao Huang, Zhihui Li, Xiaojiang Chen, and Xin Wang. A comprehensive survey of neural architecture search: Challenges and solutions. ACM Computing Surveys (CSUR), 54(4):1–34, 2021.

- [41] David L Davies and Donald W Bouldin. A cluster separation measure. *IEEE transactions on pattern analysis and machine intelligence*, (2):224–227, 1979.
- [42] Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. Advances in neural information processing systems, 33:7793–7804, 2020.
- [43] Weihua Hu, Matthias Fey, Hongyu Ren, Maho Nakata, Yuxiao Dong, and Jure Leskovec. Ogblsc: A large-scale challenge for machine learning on graphs. arXiv preprint arXiv:2103.09430, 2021.
- [44] Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor Prasanna. Graphsaint: Graph sampling based inductive learning method. arXiv preprint arXiv:1907.04931, 2019.
- [45] Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International conference on machine learning*, pages 6861–6871. PMLR, 2019.
- [46] Johannes Gasteiger, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. In *International Conference on Learning Representations*, 2018.
- [47] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. *Advances in neural information processing* systems, 29, 2016.
- [48] Qitian Wu, Wentao Zhao, Chenxiao Yang, Hengrui Zhang, Fan Nie, Haitian Jiang, Yatao Bian, and Junchi Yan. Sgformer: Simplifying and empowering transformers for large-graph representations. In *Advances in Neural Information Processing Systems*, 2023.
- [49] Israel Cohen, Yiteng Huang, Jingdong Chen, Jacob Benesty, Jacob Benesty, Jingdong Chen, Yiteng Huang, and Israel Cohen. Pearson correlation coefficient. *Noise reduction in speech processing*, pages 1–4, 2009.
- [50] Xin Zheng, Yi Wang, Yixin Liu, Ming Li, Miao Zhang, Di Jin, Philip S Yu, and Shirui Pan. Graph neural networks for graphs with heterophily: A survey. arXiv preprint arXiv:2202.07082, 2022.
- [51] Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *Advances in neural information processing systems*, 33:7793–7804, 2020.
- [52] Simon Geisler, Tobias Schmidt, Hakan Şirin, Daniel Zügner, Aleksandar Bojchevski, and Stephan Günnemann. Robustness of graph neural networks at scale. *Advances in Neural Information Processing Systems*, 34:7637–7649, 2021.
- [53] Jiaxuan You, Zhitao Ying, and Jure Leskovec. Design space for graph neural networks. *Advances in Neural Information Processing Systems*, 33:17009–17021, 2020.
- [54] Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.
- [55] Amy N Langville and Carl D Meyer. Deeper inside pagerank. *Internet Mathematics*, 1(3): 335–380, 2004.
- [56] Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. The pagerank citation ranking: Bring order to the web. In Proc. of the 7th International World Wide Web Conf, 1998.
- [57] Sitao Luan, Chenqing Hua, Qincheng Lu, Jiaqi Zhu, Mingde Zhao, Shuyuan Zhang, Xiao-Wen Chang, and Doina Precup. Is heterophily a real nightmare for graph neural networks to do node classification? *arXiv preprint arXiv:2109.05641*, 2021.

## **A** Appendix

### A.1 Datasets

We evaluate all the methods on three transductive datasets: Cora, Citeseer and Arxiv, and two inductive datasets: Flickr and Reddit. The **reduction rate** is calculated by (number of nodes in condensed graph) / (number of nodes in training graph). Specifically, the training graph is defined as the whole graph in transductive datasets, and only the training set for inductive datasets. Dataset statistics are shown in Table 5.

Dataset	#Nodes	#Edges	#Classes	#Features	Training/Validation/Test
Citagoar	2 2 2 7 7	1 722	6	2 702	120/500/1000
Cheseel	5,527	4,752	0	5,705	120/300/1000
Cora	2,708	5,429	7	1,433	140/500/1000
Arxiv	169,343	1,166,243	40	128	90,941/29,799/48,603
Flickr	89,250	899,756	7	500	44,625/22,312/22,313
Reddit	232,965	57,307,946	210	602	15,3932/23,699/55,334

Table 5: Datasets Statistics

For the choices of reduction rate r, we divide the discussion into two parts: for transductive datasets (i.e. Citeseer, Cora and Arxiv), their training graph is the whole graph. For Citeseer and Cora, since their labeling rates of training graphs are very small (3.6% and 5.2%, respectively), we choose r to be {10%, 25%, 50%} of the labeling rate. For Arxiv, the labeling rate is 53% and we choose r to be {1%, 5%, 10%} of the labeling rate; for inductive datasets (i.e. Flickr and Reddit), the nodes of their training graphs are all labeled (labeling rate is 100%). Thus, the fraction of labeling rate is equal to the final reduction rate r. The labeling rate, fraction of labeling rate and final reduction rate r of each dataset are shown in Table 6.

### A.2 Implementation Details

Since the node selection of Random, KCenter, and Herding varies too much in each random seed, we run these three methods three times, and all the results in Table 1 represent the average performance. We conduct all the experiments on a cluster mixed with NVIDIA A100, V100 and K80 GPUs. We use Pytorch (modified BSD license) and PyG [54] (MIT license) to reproduce all those methods in a unified way. Specifically, the condensed graph of SFGC are obtained by their source code<sup>3</sup> due to disk space limit but all other methods are implemented in our package<sup>4</sup>.

### A.3 Performance and Scalability

Table 7 and 8 provide the complete average accuracy with the standard deviation of 10 runs results. We also append two coreset selection baselines first introduced by Cao et al. [38]: **Cent-D** selects nodes based on their degree, prioritizing those with the highest connectivity. **Cent-P** [55] selects nodes with high PageRank [56] values, prioritizing those that are more central and influential in the graph structure.

Figure 6, Figure 7 and Figure 8 illustrate the scalability of structure-free and structure-based GC methods across three datasets. The number of epochs is a hyperparameter for each method. To ensure a fair comparison, we also record the epoch time for each method. **First**, structure-free GC methods are more efficient than structure-based ones, as they generally require less epoch time. **Second**, different hyperparameter settings result in varying time costs across datasets. For instance, GEOM employs soft labels to train GNNs on Cora, which significantly increases the time cost. **Third**, as the reduction rate increases, the performance and time costs do not necessarily rise.

<sup>&</sup>lt;sup>3</sup>https://github.com/Amanda-Zheng/SFGC

<sup>&</sup>lt;sup>4</sup>https://github.com/Emory-Melody/GraphSlim/tree/main/benchmark

Dataset	Labeling Rate	Reduction Rate of Labeled Nodes	Reduction Rate r
Citeseer	3.6%	10% 25% 50%	$0.36\% \\ 0.9\% \\ 1.8\%$
Cora	5.2%	10% 25% 50%	0.5% 1.3% 2.6%
Arxiv	53%	1% 5% 10%	$0.05\% \\ 0.25\% \\ 0.5\%$
Flickr	100%	$0.1\% \\ 0.5\% \\ 1\%$	$0.1\% \\ 0.5\% \\ 1\%$
Reddit	100%	$0.05\% \\ 0.1\% \\ 0.2\%$	$0.05\% \\ 0.1\% \\ 0.2\%$

Table 6: Explanation of Reduction Rate under transductive (first three rows) and inductive (last two rows) settings. Reduction Rate = *Labeling Rate \* Reduction Rate of Labeled Nodes*.

Table 7: Test accuracy and standard error of each graph reduction method across different datasets and three representative reduction rates for each dataset. The best and second-best results, excluding the whole graph training results, are marked in **bold** and underlined, respectively.

Dataset	Reduction			Sparsification	Coarsen				
	<i>Tuic</i> ( <i>10</i> )	Cent-D	Cent-P	Random	Herding	K-Center	Averaging	VN	VNG
Citeseer	0.36	42.86 +/- 2.69	37.78 +/- 1.29	35.37 +/- 2.77	43.73 +/- 1.61	41.43 +/- 1.38	69.75 +/- 0.55	34.32 +/- 5.94	66.14 +/- 0.30
	0.90	58.77 +/- 0.52	52.83 +/- 0.37	50.71 +/- 0.76	59.24 +/- 0.43	51.15 +/- 1.06	69.59 +/- 0.49	40.14 +/- 5.25	66.07 +/- 0.37
	1.80	62.89 +/- 0.41	63.37 +/- 0.35	62.62 +/- 0.63	66.66 +/- 0.54	59.04 +/- 0.90	69.50 +/- 0.59	41.98 +/- 7.01	65.34 +/- 0.55
Cora	0.50	57.79 +/- 1.74	58.44 +/- 1.71	35.14 +/- 2.45	51.68 +/- 2.05	44.64 +/- 4.38	75.94 +/- 0.67	24.62 +/- 5.66	70.40 +/- 0.58
	1.30	66.45 +/- 2.19	66.38 +/- 1.65	63.63 +/- 1.33	68.99 +/- 0.72	63.28 +/- 1.39	75.87 +/- 0.64	51.07 +/- 5.80	74.48 +/- 0.46
	2.60	75.79 +/- 0.65	75.64 +/- 1.64	72.24 +/- 0.59	73.77 +/- 0.93	70.55 +/- 1.35	75.76 +/- 1.08	56.75 +/- 5.43	76.03 +/- 0.37
Arxiv	0.05	32.88 +/- 2.67	36.48 +/- 1.99	50.39 +/- 1.35	51.49 +/- 0.68	50.52 +/- 0.51	59.62 +/- 0.42	OOM	54.89 +/- 0.30
	0.25	48.85 +/- 1.08	47.90 +/- 0.89	58.92 +/- 0.79	58.00 +/- 0.49	55.28 +/- 0.64	59.96 +/- 0.33	OOM	59.66 +/- 0.18
	0.50	52.01 +/- 0.48	55.65 +/- 0.50	60.19 +/- 0.52	57.70 +/- 0.24	58.66 +/- 0.36	59.94 +/- 0.30	OOM	60.93 +/- 0.23
Flickr	0.10	40.70 +/- 0.38	40.97 +/- 0.93	42.94 +/- 0.26	42.80 +/- 0.07	43.01 +/- 0.54	37.93 +/- 0.31	32.77 +/- 5.70	44.33 +/- 0.26
	0.50	42.90 +/- 0.29	44.06 +/- 0.31	44.54 +/- 0.48	43.86 +/- 0.49	43.46 +/- 0.83	37.76 +/- 0.35	33.79 +/- 5.23	43.30 +/- 0.60
	1.00	42.62 +/- 0.24	44.51 +/- 0.26	44.68 +/- 0.55	45.12 +/- 0.39	43.53 +/- 0.59	37.66 +/- 0.34	34.39 +/- 5.99	43.84 +/- 0.83
Reddit	0.05	40.00 +/- 1.10	45.83 +/- 1.65	40.13 +/- 0.85	46.88 +/- 0.41	40.24 +/- 0.78	88.23 +/- 0.08	OOM	69.96 +/- 0.48
	0.10	50.47 +/- 1.41	51.22 +/- 1.41	55.73 +/- 0.50	59.34 +/- 0.70	48.28 +/- 0.73	88.32 +/- 0.09	OOM	76.95 +/- 0.23
	0.20	55.31 +/- 1.76	61.56 +/- 0.21	58.39 +/- 2.26	73.46 +/- 0.51	56.81 +/- 1.69	88.33 +/- 0.09	OOM	81.52 +/- 0.58



Figure 6: Performance vs. Total Time and Epoch Time on **Cora**.

# 

Figure 7: Performance vs. Total Time and Epoch Time on **Arxiv**.

### A.4 Transferability

### A.4.1 Hyperparameters Searching

For fair evaluation between different architectures, we conduct hyperparameter searching while training each architecture on the condensed graph. We select the best hyperparameter combinations based on validation results and report corresponding testing results. The search space of hyperparameters for each GNN is as follows: Number of hidden units is selected from  $\{64, 256\}$ , learning rate is chosen from  $\{0.01, 0.001\}$ , weight decay is 0 or 5e-4, dropout rate is 0 or 0.5. For GAT, since we fix the number of attention heads to 8, to avoid OOM, the number of hidden units is selected from  $\{16, 64\}$  and the search space of dropout rate is in  $\{0.0, 0.5, 0.7\}$ . Additionally, for SGC and APPNP, we

	Reduction				Conde	nsation				
Dataset	rate (%)		Structi	ire-free			Structu	re-based		Whole
		GCondX	GEOM	SFGC	GCSNTK	DosCond	GCond	MSGC	SGDD	
	0.36	67.79 +/- 0.68	67.61 +/- 0.68	66.27 +/- 0.79	63.51 +/- 1.91	69.41 +/- 0.83	70.05 +/- 2.12	60.24 +/- 6.02	71.87 +/- 0.55	
Citeseer	0.90	69.69 +/- 0.45	70.70 +/- 0.51	70.27 +/- 0.70	62.91 +/- 0.82	70.83 +/- 0.44	69.15 +/- 1.19	72.08 +/- 0.71	70.52 +/- 0.61	72.6
	1.80	68.38 +/- 0.45	73.03 +/- 0.31	72.36 +/- 0.53	63.90 +/- 3.44	72.18 +/- 0.61	69.35 +/- 0.82	72.21 +/- 0.38	69.65 +/- 1.68	
	0.50	79.74 +/- 0.49	78.14 +/- 0.45	75.11 +/- 2.18	71.58 +/- 0.89	80.65 +/- 0.56	80.17 +/- 0.78	80.54 +/- 0.28	80.15 +/- 0.54	
Cora	1.30	78.67 +/- 0.37	82.29 +/- 0.59	79.55 +/- 0.32	71.22 +/- 2.60	80.85 +/- 0.37	80.81 +/- 0.51	80.98 +/- 0.51	80.29 +/- 0.83	81.5
	2.60	78.60 +/- 0.31	82.82 +/- 0.17	80.54 +/- 0.45	73.34 +/- 0.60	81.15 +/- 0.50	80.54 +/- 0.67	80.94 +/- 0.39	81.04 +/- 0.54	
	0.05	59.40 +/- 0.45	64.91 +/- 0.39	64.91 +/- 0.51	58.21 +/- 1.71	55.70 +/- 0.33	60.49 +/- 0.39	57.66 +/- 0.37	58.50 +/- 0.24	
Arxiv	0.25	62.46 +/- 0.34	68.78 +/- 0.12	66.58 +/- 0.30	59.98 +/- 1.70	57.39 +/- 0.19	63.88 +/- 0.21	64.85 +/- 0.26	59.18 +/- 0.24	71.4
	0.50	59.93 +/- 0.54	69.59 +/- 0.24	67.03 +/- 0.48	54.73 +/- 4.98	61.06 +/- 0.59	64.23 +/- 0.16	65.73 +/- 0.17	63.76 +/- 0.22	
-	0.10	46.66 +/- 0.08	47.15 +/- 0.10	46.38 +/- 0.20	41.85 +/- 3.08	45.87 +/- 0.26	46.75 +/- 0.09	46.21 +/- 0.13	46.69 +/- 0.13	
Flickr	0.50	46.69 +/- 0.12	46.71 +/- 0.15	46.38 +/- 0.20	33.39 +/- 6.01	45.89 +/- 0.30	47.01 +/- 0.16	46.77 +/- 0.14	46.39 +/- 0.15	47.4
	1.00	46.58 +/- 0.14	46.13 +/- 0.22	46.61 +/- 0.13	31.12 +/- 4.24	45.81 +/- 0.12	46.99 +/- 0.12	46.12 +/- 0.22	46.24 +/- 0.28	
	0.05	86.56 +/- 0.15	90.63 +/- 0.18	90.18 +/- 0.17	OOM	86.56 +/- 0.43	85.39 +/- 0.19	87.62 +/- 0.10	87.37 +/- 0.18	
Reddit	0.10	88.25 +/- 0.30	91.33 +/- 0.13	89.84 +/- 0.31	OOM	88.32 +/- 0.19	89.82 +/- 0.10	88.15 +/- 0.13	88.73 +/- 0.31	94.4
	0.20	88.73 +/- 0.20	91.03 +/- 0.28	90.71 +/- 0.12	OOM	88.84 +/- 0.16	90.42 +/- 0.09	87.03 +/- 0.13	90.65 +/- 0.11	

Table 8: Performance of graph condensation methods, continued from Table 7



Figure 8: Performance vs. Total Time and Epoch Time on **Reddit**.



Figure 9: Performance of condensed graphs evaluated by different GNNs.

also explore the number of linear layers in  $\{1, 2\}$ . For APPNP, we further search for alpha in  $\{0.1, 0.2\}$ .

### A.4.2 Relative and Absolute Accuracy

The relative accuracy is calculated by dividing the results of the model trained on the condensed graph by the results of the same model trained on the whole graph. For example, the accuracy of GCN on the GCond condensed graph is divided by the accuracy of results on the whole graph. As a complement to Figure 4 in the main content, which shows the relative accuracy, we present the absolute results of each GNN in Figure 9.



Figure 10: Condensed graph performance evaluated using different models including **SGFormer** on Cora.

Architecture	Search Space
Number of propagation $K$	$\{2, 4, 6, 8, 10\}$
Residual coefficient $\alpha$	{0.1, 0.2}
Hidden dimension	{16, 32, 64, 128, 256, 512}
Activation function	{Sigmoid, Tanh, ReLU, Linear, Softplus, LeakyReLU, ReLU6, ELU}

### Table 9: Architecture search space for APPNP.

### A.4.3 Evaluate Condensed Graph by Graph Transformer

The architectures discussed in the main content primarily utilize message-passing styles, which facilitate their transfer to each other. However, they may encounter challenges when applied to an entirely different architecture. Therefore, to conduct a more comprehensive evaluation of transferability, we assess the performance of various condensation methods using a graph transformer-based architecture **SGFormer** [48], which is totally different from those message-passing architectures. Figure 10 shows that SGFormer achieves comparable performance with other architectures on three non-GNN methods (Random, KCenter, Averaging). However, its performance significantly drops when trained on graphs condensed by GNN-involved methods. This suggests that future research should explore the transferability of other graph learning architectures.

### A.5 Neural Architecture Search

We utilize APPNP [46] for NAS experiments because its architecture modules are flexible and can be easily modified. The detailed architecture search space is shown in Table 9. Following the settings in GC ond [12], we search full combinations of these choices, i.e. 480 in total for each dataset.

### A.6 Graph property preservation

The full results on graph property preservation are listed in Table 10. As we mention in the main content, different GC methods show totally different behavior w.r.t. property preservation. **First**, VNG and SGDD tend to produce almost complete graphs linking each node pair. That also leads to a lower homophily, as they create more proportion of inter-class connections. **Second**, VNG performs best in property preservation, however, it shows suboptimal accuracy in Table 7. This suggests that the selected graph properties are unnecessary to maintain or to preserve as much as possible. **Third**, as the only method that creates sparse graphs, MSGC is unique among these methods except in the Homophily. From this point of view, we hold that homophily is very important for future research

Graph property	Dataset	VNG	GCond	MSGC	SGDD	Avg.	Whole
Density%	Citeseer 1.8%	36.95	84.58	22.50	100.00	61.01	0.08
(Structure)	Cora 2.6%	52.17	82.28	22.00	100.00	64.11	0.14
	Arxiv 0.5%	100.00	75.40	8.17	99.91	70.87	0.01
	Flickr 1%	100.00	100.00	3.44	99.96	75.85	0.01
	Reddit 0.1%	100.00	2.67	32.07	74.85	52.39	0.05
	Corr.	-0.81	0.07	0.55	0.13	-0.01	-
Max Eigenvalue	Citeseer 1.8%	2.98	22.53	1.67	10.29	9.37	100.04
(Spectra)	Cora 2.6%	3.73	34.90	1.69	14.09	13.60	169.01
	Arxiv 0.5%	2,092.99	163.95	2.33	79.95	584.81	13,161.87
	Flickr 1%	1,133.94	281.04	1.76	123.86	385.15	930.01
	Reddit 0.1%	1,120.64	152.00	2.00	99.84	343.62	2,503.07
	Corr.	0.85	0.25	0.95	0.28	0.58	-
DBI	Citeseer 1.8%	4.14	1.40	1.98	3.47	2.75	12.07
(Label & Feature)	Cora 2.6%	3.69	1.84	0.70	4.34	2.64	9.28
	Arxiv 0.5%	2.27	2.62	2.49	2.80	2.55	7.12
	Flickr 1%	5.60	7.14	7.33	13.57	8.41	31.02
	Reddit 0.1%	1.51	2.16	1.49	1.53	1.67	9.59
	Corr.	0.81	0.93	0.94	0.97	0.91	-
DBI-AGG	Citeseer 1.8%	4.11	0.76	1.75	0.00	1.66	8.49
(Label & Feature & Structure)	Cora 2.6%	3.59	0.38	0.57	0.18	1.18	4.67
	Arxiv 0.5%	2.38	2.86	2.61	1.77	2.41	4.40
	Flickr 1%	20.26	11.60	7.90	6.51	11.57	25.61
	Reddit 0.1%	1.56	1.90	1.49	1.37	1.58	2.48
	Corr.	0.99	0.93	0.95	0.89	0.94	-
Homophily	Citeseer 1.8%	0.18	0.18	0.23	0.15	0.18	0.74
(Label & Structure)	Cora 2.6%	0.14	0.16	0.19	0.13	0.16	0.81
	Arxiv 0.5%	0.08	0.07	0.04	0.07	0.07	0.65
	Flickr 1%	0.34	0.27	0.27	0.27	0.29	0.33
	Reddit 0.1%	0.04	0.04	0.04	0.07	0.05	0.78
	Corr.	-0.83	-0.68	-0.46	-0.80	-0.69	-

Table 10: Graph properties in condensed graphs from different structure-based GC methods. The "**Corr.**" row shows the correlation of certain properties between the condensed graph and the whole graph across five datasets. Potential preserved properties are in **bold**.

on structure-based GC since all structure-based methods behave consistently even though they do not follow the homophily of whole dataset. Current research mostly holds the view that the loss of homophily is harmful [57], but our benchmark may provide a contradictory perspective on this.

Since only the metric DBI does not rely on structure, we also exhibit the correlation of DBI of structure-free methods across all five datasets in Table 11. From the comparison between structure-free and structure-based methods, we find that GCondX and GEOM also preserve this correlation of DBI to some extent, similar to structure-based methods.

Table 11: DBI in condensed graphs from both structure-based and structure-free GC methods, continued from Table 10.

Datasets	VNG	GCond	MSGC	SGDD	GCondX	GEOM	Avg.	Whole
Citeseer 1.8%	4.14	1.40	1.98	3.47	2.90	2.55	2.74	12.07
Cora 2.6%	3.69	1.84	0.70	4.34	2.18	3.16	2.65	9.28
Arxiv 0.5%	2.27	2.62	2.49	2.80	5.52	4.37	3.35	7.12
Flickr 1%	5.60	7.14	7.33	13.57	22.93	6.04	10.43	31.02
Reddit 0.1%	1.51	2.16	1.49	1.53	0.57	2.96	1.70	9.59
Corr.	0.81	0.93	0.94	0.97	0.95	0.78	0.90	-

### A.7 Robustness

The full results on robustness are in Table 10. Apart from GC methods, we also add coreset selection methods as baselines. Results show that the simple baseline, Random, contains a certain level of

Table 12: Robustness of selected methods. "Perf. Drop" shows the relative loss of accuracy compared to the original results of each method before being corrupted. The best results are in **bold** and results that outperform whole dataset training are <u>underlined</u>. Structure-free and structure-based methods are colored as blue and red.

		Featur	e Noise	Structur	ral Noise	Adversarial S	tructural Attack
Dataset	Method	Test Acc. ↑	Perf. Drop $\downarrow$	Test Acc. ↑	Perf. Drop $\downarrow$	Test Acc. ↑	Perf. Drop $\downarrow$
	Whole	64.07	11.75%	57.63	20.62%	53.90	25.76%
	Random	56.91	9.11%	61.56	1.69%	59.42	5.12%
Citeseer 1.8%	KCenter	52.80	10.57%	55.41	6.15%	55.07	6.73%
(Poisoning & Evasion)	GCond	64.06	7.63%	65.64	5.35%	66.19	4.55%
-	GCondX	61.27	10.40%	60.42	11.65%	60.75	11.15%
	GEOM	58.77	19.53%	51.41	29.60%	57.94	20.67%
	Whole	74.77	8.26%	72.13	11.49%	66.63	18.24%
	Random	59.89	17.10%	62.64	13.28%	65.33	9.57%
Cora 2.6%	KCenter	59.88	15.13%	62.94	10.79%	65.51	7.14%
(Poisoning & Evasion)	GCond	67.62	16.04%	63.14	21.61%	68.90	14.45%
	GCondX	67.72	13.85%	63.95	18.63%	69.24	11.91%
	GEOM	49.68	40.01%	53.59	35.29%	66.32	19.93%
	Whole	46.68	1.51%	42.60	10.13%	44.44	6.24%
	Random	44.33	0.78%	43.28	3.13%	43.93	1.69%
Flickr 1%	KCenter	43.15	0.88%	42.36	2.68%	42.21	3.03%
(Poisoning)	GCond	46.29	1.49%	46.97	0.04%	43.90	6.58%
	GCondX	45.60	2.11%	46.19	0.83%	42.00	9.83%
	GEOM	45.38	1.63%	45.52	1.32%	44.72	3.06%

robustness in terms of performance drop in Citeseer and Flickr. Meanwhile, KCenter exhibits the lowest performance drop in Cora corrupted by structural noise and adversarial structural attack. However, these phenomena do not necessarily mean they can defend the attack as the performance of these two methods before being corrupted is worse than GC methods. In contrast, the GC methods naturally outperform whole graph training in most scenarios, even though they are not specifically designed for defense.