An Energy Stable Nonlinear Incompressible Multi-Phase Flow Formulation

Jan Nordström^{a,b}, Arnaud.G. Malan^c

^aDepartment of Mathematics, Applied Mathematics, Linköping University, SE-581 83 Linköping, Sweden ^bDepartment of Mathematics & Applied Mathematics, University of Johannesburg, Auckland Park 2006, South Africa ^cInCFD Research Group, Department of Mechanical Engineering, University of Cape Town, Cape Town 7700, South Africa

Abstract

We show that a reformulation of the governing equations for incompressible multi-phase flow in the volume of fluid setting leads to a well defined energy rate. Weak nonlinear inflow-outflow and solid wall boundary conditions complement the development and lead to an energy estimate in terms of external data. The new formulation combined with summation-by-parts operators lead to provably nonlinear energy stability.

Keywords: multi-phase flow, volume of fluid formulation, weak boundary conditions, energy stability, summation-by-parts

1. Introduction

Initial boundary value problems (IBVPs) for nonlinear flow problems including boundary conditions are notoriously difficult to bound. We have previously [1, 2, 3, 4], reformulated the shallow water equations and the incompressible and compressible Euler and Navier-Stokes equations such that energy estimates were obtained. We also discretized the new formulations and arrived at provably stable nonlinear schemes [5].

We consider IBVPs for incompressible multi-phase liquid-gas flows in the volume of fluid (VOF) setting [6]. The VOF formulation is applicable to complex interface motions, it is mass conservative and tracks the interface (possibly sharpened [7]) by advecting the volume fraction of the target phase. Combined with a single liquid-gas velocity, a "one-fluid" formulation [8, 9] results. Previous work considering energy stability include [10, 11, 12, 13]. In these papers, the original equations are similar, but the dependent variables are different from ours and boundary conditions are essentially ignored. Here we consider a one-fluid VOF formulation as a starting point and derive a new formulation which elegantly yields provable energy stability.

2. The reformulation

We consider an incompressible viscous liquid (l) and gas (g) mixture in two dimensions (2D) (with trivial extension to 3D). Using Einstein's summation convention, the classical one-fluid VOF formulation [6] reads

$$\partial_t \alpha + u_j \partial_j \alpha = 0$$

$$\partial_t u_i + u_j \partial_j u_i = \partial_j \tau_{ij} / \rho, \quad i = 1, 2$$

$$\partial_i u_i = 0.$$
(2.1)

The derivatives involved are denoted $\partial_t \psi = \psi_{,t} = \partial \psi / \partial t$ and $\partial_j \psi = \psi_{,j} = \partial \psi / \partial x_j$, α is the volume fraction of the liquid, u_j is velocity in direction x_j , $\tau_{ij} = \tau_{ij}^* - \delta_{ij}p$ is the stress tensor, $\tau_{ij}^* = [\mu (u_{i,j} + u_{j,i})]$ is the viscous stress tensor and p is pressure. Furthermore, $\rho = \alpha \rho_l + (1 - \alpha)\rho_g$ and $\mu = \alpha \mu_l + (1 - \alpha)\mu_g$ are the volume averaged density and viscosity respectively. We neglected the external gravity forces which have no impact on stability. To get at an energy bound, the formulation (2.1)) will be modified in two steps.

Email address: jan.nordstrom@liu.se (Jan Nordström)

Preprint submitted to Elsevier

In the first step we replace the volume fraction by the density as dependent variable and move the divergence relation to the righthand side leading to $(S_{ij} = \tau_{ij} \text{ and } S_{3j} = -u_j)$ the equivalent formulation

$$\partial_t \rho + u_j \partial_j \rho = 0$$

$$\partial_t u_i + u_j \partial_j u_i = \partial_j S_{ij} / \rho, \quad i = 1, 2$$

$$0 = \partial_j S_{3j}.$$
(2.2)

In the second step we aim for a scaling of the viscous terms and introduce the new variables $[\phi_0, \phi_j, \phi_3]^T = [\sqrt{\rho}, \sqrt{\rho}u_j, p]$ (see [1, 2, 3, 4], for similar but not identical choices) into (2.2) to yield the new equation set

$$\partial_t \phi_0 + u_j \partial_j \phi_0 = 0$$

$$\partial_t \phi_i + u_j \partial_j \phi_i = \partial_j S_{ij} / \phi_0, \quad i = 1, 2$$

$$0 = \partial_i S_{3i}.$$
(2.3)

Introducing $\Phi = [\phi_0, \phi_1, \phi_2, \phi_3]^T$, $\tilde{I} = diag[1, 1, 1, 0]$, $\tilde{A}_j = diag[u_j, u_j, u_j, 0]$, $\tilde{B} = diag[0, 1/\phi_0, 1/\phi_0, 1]$, $S_j = (0, S_{1j}, S_{2j}, S_{3j})^T$ and noting that $\tilde{A}_{j,j}$ vanish, we cast (2.3) in the final matrix-vector form

$$\tilde{I}\partial_t \Phi + \frac{1}{2} \Big[\partial_j (\tilde{A}_j \Phi) + \tilde{A}_j \partial_j \Phi \Big] = \tilde{B}\partial_j S_j.$$
(2.4)

Remark 2.1. The first step leading to (2.2) produces the skew-symmetric lefthand side of (2.4) suitable for Green's theorem. The second step leading to (2.3) produces a scaling of the righthand side in (2.4) again opening up for Green's theorem. Reformulating (2.1) into (2.4) is required for the upcoming energy analysis.

3. Energy analysis

Focusing first on the skew-symmetric lefthand side of (2.4), we multiply with Φ^T and integrate to get

$$\int_{\Omega} \Phi^{T} \tilde{I} \partial_{t} \Phi d\Omega + \frac{1}{2} \int_{\Omega} \left[\Phi^{T} \partial_{j} (\tilde{A}_{j} \Phi) + \Phi^{T} \tilde{A}_{j} \partial_{j} \Phi \right] d\Omega = \int_{\Omega} \Phi^{T} \tilde{B} \partial_{j} S_{j} d\Omega.$$
(3.1)

Letting $\int_{\Omega} \Phi^T \tilde{I} \Phi d\Omega = ||\Phi||_{\tilde{I}}^2$ and $\Phi^T \partial_j (\tilde{A}_j \Phi) = \partial_j (\Phi^T \tilde{A}_j \Phi) - (\partial_j \Phi)^T \tilde{A}_j \Phi$ followed by Green's theorem yields

$$\frac{d}{dt}||\Phi||_{\tilde{I}}^{2} + \oint_{\partial\Omega} \Phi^{T}\left(n_{j}\tilde{A}_{j}\right)\Phi ds = 2\int_{\Omega} \Phi^{T}\tilde{B}\partial_{j}S_{j}d\Omega.$$
(3.2)

In (3.2), $\partial\Omega$, ds and n_j are respectively the boundary, its surface element and outward pointing unit normal. Focusing secondly on the rescaled righthand-side of (2.4), we see that the righthand side of (3.2) implies

$$\int_{\Omega} \Phi^T \tilde{B} \partial_j S_j d\Omega = \int_{\Omega} \left[\phi_i \partial_j S_{ij} / \phi_0 + \phi_3 \partial_j S_{3j} \right] d\Omega = \int_{\Omega} \left[u_i \tau_{ij,j} - p u_{i,i} \right] d\Omega = \int_{\Omega} \left[(u_i \tau_{ij})_{,j} - u_{i,j} \tau_{ij} - p u_{i,i} \right] d\Omega$$
$$= \int_{\Omega} \left[(u_i \tau_{ij})_{,j} - u_{i,j} \tau_{ij} - p u_{i,i} \right] d\Omega$$

$$= \int_{\Omega} \left[(u_i \tau_{ij})_{,j} - u_{i,j} \left(\tau_{ij}^* - \delta_{i,j} p \right) - p u_{i,i} \right] d\Omega = \oint_{\partial \Omega} u_i \tau_{ij} n_j ds - \int_{\Omega} u_{i,j} \tau_{ij}^* d\Omega$$
(3.3)

where we again used Green's theorem. Inserting (3.3) into (3.2) and rearranging leads to the energy rate

$$\frac{d}{dt}||\Phi||_{\tilde{I}}^{2} + 2\int_{\Omega} u_{i,j}\tau_{ij}^{*}d\Omega + \oint_{\partial\Omega} \mathbb{B}\mathbb{T}ds = 0$$
(3.4)

where the 2^{nd} term $(u_{i,j}\tau_{ij}^* = 2u_{i,i}^2 + (u_{1,2} + u_{2,1})^2 \ge 0)$ provides dissipation and the boundary term \mathbb{BT} is

$$\mathbb{BT} = \Phi_1^T A \Phi_1 - 2 \left[u_n (\tau_n - p) + u_t \tau_t \right].$$
(3.5)

In (3.5), $A = diag[u_n, u_n, u_n]$ and $\Phi_1^T = [\phi_0, \phi_n, \phi_t] = [\phi_0, \phi_0 u_n, \phi_0 u_t]$. The subscripts n, t denote components normal and tangential to $\partial\Omega$. For the stress term in (3.5) we use $\tau^T = [\tau_1, \tau_2] = [\tau_{1j}^* n_j, \tau_{2j}^* n_j]$ and the rotation matrix N (given in (3.20 below) to obtain $\mathbf{u}^T \tau = \mathbf{u}^T (N^T N) \tau = (N \mathbf{u})^T (N \tau) = [u_n, u_t] \cdot [\tau_n, \tau_t]^T$.

3.1. The boundary term

The unrestrained boundary term in (3.5) can be written in vector-matrix-vector form as

$$\mathbb{BT} = \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix}^T \begin{pmatrix} A & B \\ B^T & 0 \end{pmatrix} \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix} \quad \text{where} \quad \Phi_2 = \begin{pmatrix} p \\ \tau_n \\ \tau_t \end{pmatrix} \quad \text{and} \quad B = \frac{1}{\phi_0} \begin{pmatrix} 0 & 0 & 0 \\ 1 & -1 & 0 \\ 0 & 0 & -1 \end{pmatrix}$$
(3.6)

while Φ_1 and A are given above. Next, we introduce the non-singular block rotation matrix \mathbb{R} as

$$\mathbb{RR}^{-1} = \begin{pmatrix} I & R \\ 0 & I \end{pmatrix} \begin{pmatrix} I & -R \\ 0 & I \end{pmatrix} = \begin{pmatrix} I & 0 \\ 0 & I \end{pmatrix},$$
(3.7)

where the blocks are 3×3 matrices. The rotation matrix (3.7) introduced into (3.6) yields

$$\mathbb{BT} = \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix}^T \mathbb{RR}^{-1} \begin{pmatrix} A & B \\ B^T & 0 \end{pmatrix} \mathbb{RR}^{-1} \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix}$$
$$= \begin{pmatrix} \mathbb{R}^{-1} \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix} \end{pmatrix}^T \begin{pmatrix} A & AR + B \\ R^T A + B^T & R^T (AR + B) + B^T R \end{pmatrix} \begin{pmatrix} \mathbb{R}^{-1} \begin{pmatrix} \Phi_1 \\ \Phi_2 \end{pmatrix} \end{pmatrix}.$$
(3.8)

With matrix A being non-singular, we cancel the off-diagonal matrices in (3.8) with $R = -A^{-1}B$ to get

$$\mathbb{BT} = \begin{pmatrix} A^{-1}[A\Phi_1 + B\Phi_2] \\ \Phi_2 \end{pmatrix}^T \begin{pmatrix} A & 0 \\ 0 & -B^T A^{-1}B \end{pmatrix} \begin{pmatrix} A^{-1}[A\Phi_1 + B\Phi_2] \\ \Phi_2 \end{pmatrix}$$
$$= \begin{pmatrix} A\Phi_1 + B\Phi_2 \\ B\Phi_2 \end{pmatrix}^T \begin{pmatrix} I/u_n & 0 \\ 0 & -I/u_n \end{pmatrix} \begin{pmatrix} A\Phi_1 + B\Phi_2 \\ B\Phi_2 \end{pmatrix} = \begin{pmatrix} W_1 \\ W_2 \end{pmatrix}^T \begin{pmatrix} \Lambda_1 & 0 \\ 0 & \Lambda_2 \end{pmatrix} \begin{pmatrix} W_1 \\ W_2 \end{pmatrix}.$$
(3.9)

The details in (3.9) seen in (3.10) reveal that 5 independent variables are involved in the boundary conditions.

$$\Lambda_1 = \frac{1}{u_n} I, \Lambda_2 = -\Lambda_1, W_1 = A\Phi_1 + B\Phi_2 = \frac{1}{\phi_0} \begin{pmatrix} \phi_n \phi_0 \\ \phi_n^2 - (\tau_n - \phi_3) \\ \phi_n \phi_t - \tau_t \end{pmatrix}, W_2 = B\Phi_2 = \frac{1}{\phi_0} \begin{pmatrix} 0 \\ -(\tau_n - \phi_3) \\ -\tau_t \end{pmatrix}.$$
 (3.10)

3.2. Boundary Conditions

The different types of boundary conditions are determined by the normal velocity u_n which determine the sign of the diagonal entries Λ_1 and Λ_2 that in turn determine whether W_1 or W_2 must be bounded.

3.2.1. Boundary conditions of inflow-outflow type

We start by determining the number of boundary conditions [14] required at inflow-outflow boundaries.

- At inflow $u_n < 0$, $W_1^T \Lambda_1 W_1 < 0$ and we need three conditions since W_1 has three components.
- At outflow $u_n > 0$, $W_2^T \Lambda_2 W_2 < 0$ and we need two conditions since W_2 has two non-zero components.

Following [5], the boundary conditions are applied weakly by inserting (3.9) and a lifting operator into (3.4):

$$\frac{d}{dt}||\Phi||_{\tilde{I}}^{2}+2\int_{\Omega}u_{i,j}\tau_{ij}^{*}d\Omega + \oint_{\partial\Omega} \begin{pmatrix} W_{1}\\ W_{2} \end{pmatrix}^{T} \begin{pmatrix} \Lambda_{1} & 0\\ 0 & \Lambda_{2} \end{pmatrix} \begin{pmatrix} W_{1}\\ W_{2} \end{pmatrix} ds + 2\int_{\Omega} \Phi^{T}L(\Sigma\mathbb{B}\mathbb{C})d\Omega = 0.$$
(3.11)

Here \mathbb{BC} denotes the boundary conditions, Σ is a penalty matrix and L is a lifting operator implementing boundary conditions weakly. It is defined by $\int_{\Omega} \psi^T L(\phi) d\Omega = \oint_{\partial \Omega} \psi^T \phi ds$ where ψ, ϕ are smooth vector fields.

We will apply boundary conditions such that the boundary terms in (3.11) are bounded by external data only. Following [3], we consider the nonlinear characteristic-like boundary condition on weak form

$$\mathbb{BC} = \sqrt{|\Lambda^{-}|}W^{-} - \mathbf{G} = 0, \qquad (3.12)$$

where Λ^- and W^- are functions of the solution and ${f G}$ is external data.

To implement inflow boundary conditions weakly where $u_n < 0$, we need an operator T_1 such that

$$W^{-} = W_{1} = A\Phi_{1} + B\Phi_{2} = \frac{1}{\phi_{0}} \begin{pmatrix} \phi_{n}\phi_{0} \\ \phi_{n}^{2} - (\tau_{n} - \phi_{3}) \\ \phi_{n}\phi_{t} - \tau_{t} \end{pmatrix} = T_{1}\Phi = (\Phi^{T}T_{1}^{T})^{T}.$$
(3.13)

At an outflow boundary where $u_n > 0$ we require an operator T_2 such that

$$W^{-} = W_{2} = B\Phi_{2} = \frac{1}{\phi_{0}} \begin{pmatrix} 0 \\ -(\tau_{n} - \phi_{3}) \\ -\tau_{t} \end{pmatrix} = T_{2}\Phi = (\Phi^{T}T_{2}^{T})^{T}.$$
(3.14)

Implementing the boundary condition (3.12) weakly into (3.11) yields the augmented boundary term:

$$\mathbb{BT} = W^{+^{T}} \Lambda^{+} W^{-} - W^{-^{T}} |\Lambda^{-}| W^{-} + 2\Phi^{T} \Sigma \left(\sqrt{|\Lambda^{-}|} W^{-} - \mathbf{G} \right).$$
(3.15)

Next we choose $\Sigma = T^T \sigma_0 \sqrt{|\Lambda^-|}$, where $T = T_1$ or T_2 depending on the signs of $\Lambda_{1,2}$, which gives

$$\mathbb{BT} = W^{+^{T}} \Lambda^{+} W^{-} - (1 - 2\sigma_{0}) W^{-^{T}} |\Lambda^{-}| W^{-} - 2\sigma_{0} W^{-^{T}} \sqrt{|\Lambda^{-}|} \mathbf{G}.$$
(3.16)

Choosing $\sigma_0 = 1$ as well as adding and subtracting \mathbf{G}^T leads to an estimate in terms of data only since

$$\mathbb{BT} = W^{+^{T}}\Lambda^{+}W^{-} + \left(W^{-}\sqrt{|\Lambda^{-}|} - \mathbf{G}\right)^{T}\left(W^{-}\sqrt{|\Lambda^{-}|} - \mathbf{G}\right) - \mathbf{G}^{T}\mathbf{G} \ge -\mathbf{G}^{T}\mathbf{G}.$$
(3.17)

3.2.2. Boundary conditions of solid wall type

At solid wall boundaries where $u_n = 0$ we work directly on the \mathbb{BT} in (3.6) which we group as follows

$$\mathbb{BT} = \left[\Phi_1^T A \Phi_1 + 2\Phi^T \Sigma_1 \mathbb{BC}_1\right] + \left[2\Phi_1^T B \Phi_2 + 2\Phi^T \Sigma_2 \mathbb{BC}_2\right].$$
(3.18)

We will remove the terms within brackets on the righthand-side of (3.18) by appropriately selecting the penalty terms $\Sigma_1 \mathbb{BC}_1$ and $\Sigma_2 \mathbb{BC}_2$. Only the two boundary conditions $u_n = u_t = 0$ are available at a solid wall. For accuracy reasons they must cancel both bracketed terms in (3.18) when imposed weakly.

For the first term in brackets in (3.18), we set $\Sigma_1 = R_1^T \Sigma_1'$ with $R_1 \Phi = \Phi_1$ to obtain

$$\Phi_1^T A \Phi_1 + 2\Phi^T \Sigma_1 \mathbb{B} \mathbb{C}_1 = \Phi_1^T A \Phi_1 + 2\Phi_1^T \Sigma_1' \mathbb{B} \mathbb{C}_1$$
(3.19)

where

$$R_1 = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & n_1 & n_2 & 0 \\ 0 & -n_2 & n_1 & 0 \end{pmatrix} \quad \text{and} \quad \begin{pmatrix} n_1 & n_2 \\ -n_2 & n_1 \end{pmatrix} = N$$
(3.20)

is the rotation matrix used in (3.5) above. Next, we insert $\Sigma'_1 = \sigma_1$ and $\mathbb{BC}_1 = A\Phi_1$ into (3.19) to give

$$\Phi_1^T A \Phi_1 + 2\Phi_1^T \Sigma_1' \mathbb{BC}_1 = \Phi_1^T A \Phi_1 + 2\Phi_1^T (\sigma_1 A \Phi_1) = \Phi_1^T A \Phi_1 [1 + 2\sigma_1].$$
(3.21)

Equating $\sigma_1 = -1/2$ yields stability. Accuracy is proven by noting that u_n is forced to zero by $\Sigma_1 \mathbb{BC}_1$ since

$$\Sigma_1 \mathbb{B} \mathbb{C}_1 = \sigma_1 R_1^T A \Phi_1 = \sigma_1 R_1^T \Phi_1 u_n$$

For the second term in brackets in (3.18) we set $\Sigma_2 = R_2^T \Sigma_2'$ with $R_2 \Phi = \Phi_2$ to obtain

$$2\Phi_1^T B\Phi_2 + 2\Phi^T \Sigma_2 \mathbb{BC}_2 = 2 \left(B\Phi_2\right)^T \Phi_1 + 2\Phi_2^T \Sigma_2' \mathbb{BC}_2$$
(3.22)

where $R_2 = P_e T_r S_c$, $S_c = diag[1, 1/\phi_0, 1/\phi_0, 1]$ and

$$P_e = \begin{pmatrix} 0 & 0 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}, \ T_r = \begin{pmatrix} 0 & T_{r_{11}} & T_{r_{11}} & 0 \\ 0 & T_{r_{21}} & T_{r_{22}} & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}, \ T_r = \mu N \left[\begin{pmatrix} 2n_1 & n_2 \\ 0 & n_1 \end{pmatrix} \frac{\partial}{\partial x} + \begin{pmatrix} n_2 & 0 \\ n_1 & 2n_2 \end{pmatrix} \frac{\partial}{\partial y} \right].$$
(3.23)

Setting $\Sigma'_2 = \sigma_2$ and $\mathbb{BC}_2 = B^T \Phi_1$ into (3.22):

$$2(B\Phi_2)^T \Phi_1 + 2\Phi_2^T \Sigma_2' \mathbb{BC}_2 = 2(B\Phi_2)^T \Phi_1 + 2\sigma_2 (B\Phi_2)^T \Phi_1 = 2(1+\sigma_2) (B\Phi_2)^T \Phi_1.$$
(3.24)

Equating $\sigma_2 = -1$ yields stability. Accuracy is proven by noting that $\Sigma_2 \mathbb{BC}_2$ forces u_n and u_t to zero since

$$\Sigma_2 \mathbb{B} \mathbb{C}_2 = R_2^T \Sigma_2' \mathbb{B} \mathbb{C}_2 = \sigma_2 R_2^T B^T \Phi_1 = \sigma_2 R_2^T B^T \begin{pmatrix} \phi_0 \\ \phi_n \\ \phi_t \end{pmatrix} = \sigma_2 R_2^T \begin{pmatrix} u_n \\ -u_n \\ -u_t \end{pmatrix}.$$

4. A stable straightforward nonlinear numerical approximation

The focus in this short article is on the continuous analysis, but we conclude by sketching how a stable nonlinear scheme can be constructed based on the new formulation (2.4). The semi-discrete version of (2.4) (ignoring boundary conditions) using summation-by-parts (SBP) operators $\mathbf{D}_{\mathbf{x}_i}$ [5, 15, 16] can be written

$$\tilde{\mathbf{I}}\frac{d\bar{\boldsymbol{\Phi}}}{dt} + \frac{1}{2} \Big[\mathbf{D}_{\mathbf{x}_{j}}(\mathbf{A}_{j}\bar{\boldsymbol{\Phi}}) + \mathbf{A}_{j}\mathbf{D}_{\mathbf{x}_{j}}\bar{\boldsymbol{\Phi}} \Big] = \mathbf{B}\mathbf{D}_{\mathbf{x}_{j}}\mathbf{S}_{j}, \tag{4.1}$$

where $\tilde{\mathbf{I}} = \tilde{I} \otimes \mathbb{I}, \mathbb{I} = I_x \otimes I_y$ and $\vec{\Phi} = (\vec{\phi}_0^T, \vec{\phi}_1^T, \vec{\phi}_2^T, \vec{\phi}_3^T)^T$ include approximations of $\Phi = (\phi_0, \phi_1, \phi_2, \phi_3)^T$ in each of the $N \times M$ nodes. The matrix elements of $\mathbf{A_j}, \mathbf{B}$ are matrices with node values of the matrix elements in \tilde{A}_j, \tilde{B} given in Section 2 injected on the diagonal as exemplified for the $n \times n$ matrix C below

$$C = \begin{pmatrix} c_{11} & \dots & c_{1n} \\ \vdots & \ddots & \vdots \\ c_{n1} & \dots & c_{nn} \end{pmatrix}, \quad \mathbf{C} = \begin{pmatrix} \mathbf{c_{11}} & \dots & \mathbf{c_{1n}} \\ \vdots & \ddots & \vdots \\ \mathbf{c_{n1}} & \dots & \mathbf{c_{nn}} \end{pmatrix}, \quad \mathbf{c_{ij}} = diag(c_{ij}(x_1, y_1), \dots, c_{ij}(x_N, y_M)).$$
(4.2)

Moreover $\mathbf{D}_{\mathbf{x}_j} = I_4 \otimes \mathbb{D}_{x_j}$, $\mathbb{D}_{x_1} = D_x \otimes I_y$ and $\mathbb{D}_{x_2} = I_x \otimes D_y$ where $D_{x,y} = P_{x,y}^{-1}Q_{x,y}$ are 1D SBP difference operators, $P_{x,y}$ are positive definite diagonal quadrature matrices, $Q_{x,y}$ satisfies the SBP constraint $Q_{x,y} + Q_{x,y}^T = B_{x,y} = diag[-1, 0, ..., 0, 1]$, \otimes denotes the Kronecker product and I with subscripts denote identity matrices. All matrices have appropriate sizes such that the matrix-matrix and matrix-vector operations are defined. Based on the 1D SBP operators, the 2D SBP relations mimicking integration-by-parts are

$$\vec{U}^T \mathbf{P} \mathbf{D}_{\mathbf{x}_j} \vec{V} = -(\mathbf{D}_{\mathbf{x}_j} \vec{U})^T \mathbf{P} \vec{V} + \vec{U}^T \mathbf{B}_{\mathbf{x}_j} \vec{V}, \quad \vec{u}^T \mathbb{P} \mathbb{D}_{x_j} \vec{v} = -(\mathbb{D}_{x_j} \vec{u})^T \mathbb{P} \vec{v} + \vec{u}^T \mathbb{B}_{x_j} \vec{v}, \tag{4.3}$$

where $\vec{U}^T \mathbf{B}_{\mathbf{x}_j} \vec{V}$ and $\vec{u}^T \mathbb{B}_{x_j} \vec{v}$ contain numerical integration along rectangular domain boundaries. In (4.3) we have also used $\mathbf{P} = I_4 \otimes \mathbb{P}, \mathbb{P} = P_x \otimes P_y, \mathbf{B}_{\mathbf{x}_j} = I_4 \otimes \mathbb{B}_{x_j}, \mathbb{B}_{x_1} = B_x \otimes P_y$ and $\mathbb{B}_{x_2} = P_x \otimes B_y$.

The discrete energy method (multiply (4.1) from the left with $2\vec{\Phi}^T \mathbf{P}$) yields

$$2\vec{\Phi}^T \mathbf{P} \tilde{\mathbf{I}} \frac{d\vec{\Phi}}{dt} + \vec{\Phi}^T (\mathbf{P} \mathbf{D}_{\mathbf{x}_j} \mathbf{A}_j + \mathbf{A}_j \mathbf{P} \mathbf{D}_{\mathbf{x}_j}) \vec{\Phi} = 2\vec{\Phi}^T \mathbf{B} \mathbf{P} \mathbf{D}_{\mathbf{x}_j} \mathbf{S}_j,$$
(4.4)

since $\mathbf{A}_{\mathbf{j}}$ and \mathbf{B} commute with \mathbf{P} . Using the notation $\|\vec{\Phi}\|_{\tilde{\mathbf{P}}}^2 = \vec{\Phi}^T \tilde{\mathbf{P}} \vec{\Phi} = \vec{\Phi}^T \mathbf{P} \tilde{\mathbf{I}} \vec{\Phi}$, the symmetric part of $\mathbf{PD}_{\mathbf{x}_j} \mathbf{A}_j + \mathbf{A}_j \mathbf{PD}_{\mathbf{x}_j}$ and after applying the SBP relations (4.3) we obtain the final semi-discrete energy rate

$$\frac{d}{dt} \|\vec{\Phi}\|_{\vec{\mathbf{P}}}^2 + 2(\mathbb{D}_{x_j}\vec{u}_i)^T \mathbb{P}\tau^{\vec{*}_{ij}} + \vec{\Phi}^T (\mathbf{B}_{\mathbf{x}_j}\mathbf{A}_j)\vec{\Phi} - 2\vec{u}_i^T \mathbb{B}_{x_j}\tau_{ij} = 0.$$

$$(4.5)$$

The semi-discrete energy rate (4.5) mimicks the continuous energy rate (3.4) perfectly on a rectangular domain. The second term from the left in (4.5) is the dissipation numerically integrated over the domain and the two terms that follow contain the boundary terms numerically integrated along the boundary. In an upcoming article we will provide a more detailed derivation including the numerical construction and numerical implementation of the weak dissipative boundary conditions derived in Section 3.

5. Summary and outlook

We have shown that a new formulation of the incompressible multi-phase liguid-gas flow equations leads to a well defined energy rate. We also derived weak boundary conditions of inflow-outflow and solid wall types that lead to an energy estimate. The paper was concluded with a short illustration of how to construct a semi-discrete energy stable scheme by combining the new formulation with summation-by-parts operators. In future work we will develop nonlinear energy stable schemes including weak boundary conditions and perform numerical simulations based on this new provably energy bounded continuous formulation.

Acknowledgments

J. N. was supported by Vetenskapsrådet, Sweden [award 2021-05484 VR] and University of Johannesburg. A. G. M. was supported by the National Research Foundation (NRF) of South Africa [grant 89916].

References

- J. Nordström, Nonlinear and linearised primal and dual initial boundary value problems: When are they bounded? how are they connected?, Journal of Computational Physics 455 111001 (2022).
- J. Nordström, A skew-symmetric energy and entropy stable formulation of the compressible Euler equations, Journal of Computational Physics 470 111573 (2022).
- J. Nordström, Nonlinear boundary conditions for initial boundary value problems with applications in computational fluid dynamics, Journal of Computational Physics 498 112685 (2024).
- [4] J. Nordström, A skew-symmetric energy stable almost dissipation free formulation of the compressible Navier-Stokes equations, Journal of Computational Physics 512 113145 (2024).
- [5] J. Nordström, A roadmap to well posed and stable problems in computational physics, J. Sci. Comput. 71 (1) (2017) 365–385.
- [6] C. Hirt, B. Nichols, Volume of fluid (VOF) method for the dynamics of free boundaries, Journal of Computational Physics 39 (1981).
- [7] S. Mirjalili, C. V. Ivey, A. Mani, A conservative phase field method for two-phase flows with provable boundedness properties, Journal of Computational Physics 401 109006 (2020).
- [8] O. Oxtoby, A. Malan, J. Heyns, A computationally efficient 3D finite-volume scheme for violent liquid-gas sloshing, International Journal for Numerical Methods in Fluids 79 (2015).
- [9] L. Malan, A. Malan, P. Rousseau, S. Zaleski, A geometric vof method for interface resolved phase change and conservative thermal energy advection, Journal of Computational Physics 426 (2021).
- [10] C. Liu, N. J. Walkington, Convergence of numerical approximations of the incompressible Navier–Stokes equations with variable density and viscosity, SIAM Journal on Numerical Analysis 45 (3) (2007) 1287–1304.
- [11] J. Shen, X. Yang, Decoupled, energy stable schemes for phase-field models of two-phase incompressible flows, SIAM Journal on Numerical Analysis 53 (1) (2015) 279 – 296.
- [12] Z. Yang, S. Dong, An unconditionally energy-stable scheme based on an implicit auxiliary energy variable for incompressible two-phase flows with different densities involving only precomputable coefficient matrices, Journal of Computational Physics 393 (2019) 229–257.
- [13] M. Pan, C. Fu, W. Zhu, F. Jiao, D. He, Linear, second-order, unconditionally energy stable scheme for an electrohydrodynamic model with variable density and conductivity, Communications in Nonlinear Science and Numerical Simulation 125 (2023) 107329.
- [14] J. Nordström, T. M. Hagstrom, The number of boundary conditions for initial boundary value problems, SIAM Journal on Numerical Analysis 58 (5) (2020) 2818–2828.
- [15] M. Svärd, J. Nordström, Review of summation-by-parts schemes for initial-boundary-value problems, Journal of Computational Physics 268 (2014) 17–38.
- [16] D. C. D. R. Fernández, J. E. Hicken, D. W. Zingg, Review of summation-by-parts operators with simultaneous approximation terms for the numerical solution of partial differential equations, Computers & Fluids 95 (2014) 171–196.