Neural Probabilistic Logic Learning for Knowledge Graph Reasoning

Fengsong Sun¹, Jinyu Wang¹, Zhiqing Wei¹, Xianchao Zhang²

1.Key Laboratory of Universal Wireless Communications, Ministry of Education Beijing University of Posts and Telecommunications Beijing, China 100876 {sfs_2021_9, wangjinyubu, weizhiqing}@bupt.edu.cn
2.Provincial Key Laboratory of Multimodal Perceiving and Intelligent Systems Jiaxing University Jiaxing, China 314001 zhangxianchao@zjxu.edu.cn

Abstract

Knowledge graph (KG) reasoning is a task that aims to predict unknown facts based on known factual samples. Reasoning methods can be divided into two categories: rule-based methods and KG-embedding based methods. The former possesses precise reasoning capabilities but finds it challenging to reason efficiently over large-scale knowledge graphs. While gaining the ability to reason over large-scale knowledge graphs, the latter sacrifices reasoning accuracy. This paper aims to design a reasoning framework called Neural Probabilistic Logic Learning(NPLL) that achieves accurate reasoning on knowledge graphs. Our approach introduces a scoring module that effectively enhances the expressive power of embedding networks, striking a balance between model simplicity and reasoning capabilities. We improve the interpretability of the model by incorporating a Markov Logic Network based on variational inference. We empirically evaluate our approach on several benchmark datasets, and the experimental results validate that our method substantially enhances the accuracy and quality of the reasoning results.

1 Introduction

Knowledge representation has long been a fundamental challenge in artificial intelligence. Knowledge graphs, a form of structured knowledge representation, have gained significant traction in recent years due to their ability to capture rich semantics and facilitate reasoning over large-scale data. Compared to conventional approaches such as semantic networks and production rules, knowledge graphs offer a more expressive and scalable representation of entities and their relationships in a graph-based formalism. This structured representation not only assists human comprehension and reasoning but also enables seamless integration with machine learning techniques, facilitating a wide range of downstream applications.

One prominent line of research in knowledge graph reasoning revolves around embedding-based methods. These techniques aim to map the elements of a knowledge graph into a low-dimensional vector space, capturing the underlying associations between entities and relations through numerical representations. While this approach has demonstrated promising results, it suffers from inherent limitations, including low interpretability, suboptimal performance on long-tail relations, and challenges in capturing complex semantic information and logical relationships.

Alternatively, rule-based knowledge reasoning methods operate by extracting logical rules from the knowledge graph, typically in the form of first-order predicate logic, and performing inference based on these rules. However, these methods often face challenges stemming from the vast search space and limited coverage of the extracted rules. Markov Logic Networks (MLNs) [1] have been proposed as a principled framework for combining probabilistic graphical models with first-order logic, enabling the effective integration of rules and embedding methods for more accurate reasoning.

In this paper, we seek to develop a method that can better leverage the outputs of embedding networks to support knowledge graph reasoning. To this end, we propose a novel reasoning framework called Neural Probabilistic Logic Learning (NPLL). NPLL introduces a scoring module that efficiently utilizes knowledge graph embedding data, enhancing the training process of the entire framework. Our method, illustrated in Figure 1, makes the following key contributions:

Efficient Reasoning and Learning: NPLL can be viewed as an inference network for MLNs, extending MLN inference to larger-scale knowledge graph problems.

Tight Integration of Logical Rules and Data Supervision: NPLL can leverage prior knowledge from logical rules and supervision from structured graph data.

Balance between Model Size and Reasoning Capability: Despite its compact architecture and relatively fewer parameters, NPLL demonstrates remarkable reasoning capabilities, sufficient to capture the intricate relationships and semantics within knowledge graphs. Even in data-scarce scenarios where the available dataset size is relatively small, NPLL can achieve a high level of reasoning performance, making it well-suited for practical applications with limited labeled data.

Zero-shot Learning Ability: Our proposed NPLL framework exhibits strong zero-shot learning capabilities, enabling it to handle reasoning tasks involving target predicates with very few or no labeled instances. This flexibility and generalization power are particularly valuable in real-world settings where exhaustive labeling of all possible relationships is often impractical.



Figure 1: Visualization of Neural Probabilistic Logic Learning (NPLL)

2 Related Work

One prominent category of methods for knowledge graph reasoning is rule-based approaches. These methods leverage logical rules, generally defined as $B \rightarrow A$, where A is the target fact, and B can be considered a set of condition facts. Facts are composed of predicates and variables. To better utilize these symbolic features, methods like AMIE[2], RuleN[3], and RLvLR[4] employ rule mining tools to extract logical rules from knowledge graphs for reasoning. Approaches like KALE[5], RUGE[6], and IterE[7] started combining logical rules with embedding learning to construct joint knowledge graph reasoning models. Additionally, NeuralLP[8] proposed an end-to-end differentiable method to effectively learn the parameters and structures of logical rules in knowledge graphs. NeuralLP-num-lp[9] combined summation operations and dynamic programming with NeuralLP, which can be used to learn numerical regulations better. Simultaneously, DRUM[10] introduced a rule-based end-to-end differentiable model. Then, pLogicNet designed a probabilistic logic neural network [11], demonstrating exemplary reasoning performance. Building on this, ExpressGNN[12] achieved more efficient reasoning by fine-tuning the GNN model. DiffLgic[13] designed a differential framework to improve reasoning efficiency and accuracy for large knowledge graphs. NCRL[14] proposed an end-to-end neural method that recursively leverages the compositionality of logical rules

to enhance systematic generalization. In contrast to these approaches, our proposed NPLL framework is significantly more effective for knowledge graph reasoning.

Another category of approaches for knowledge graph reasoning is embedding-based methods. These techniques primarily represent entities and relations using vector embeddings. Knowledge graph reasoning is achieved by defining various scoring functions to model different reasoning processes. For instance, methods like TransE[15], TransH[16], TransR[17], TransD[18], TranSparse[19], TransRHS[20], RotatE[21] project entities and relations into vector spaces, transforming computations between facts into vector operations. The essential scoring function is the difference between the head entity-relation vector and the tail entity vector. Rescal[22], DistMult[23], ComplEx[24], HolE[25], analog[26], SimplE[27], QuatE[28], DualE[29], HopfE[30], LowFER[31], QuatRE[32] represent each fact in the knowledge graph as a three-dimensional tensor, decomposed into a combination of low-dimensional entity and relation vectors. They use vector matrices to represent the latent semantics of each entity and relation. The primary scoring function is the product of the head entity, relation, and tail entity. Methods like SME[33], NTN[34], and NAM[35] employ neural networks to encode entities and relations into high-dimensional spaces. ConvE[36] first introduced 2D convolutional layers for reasoning. RGCN[37], NBF-net[38], and RED-GNN[39] use graph neural networks to aggregate neighbor node information and decoders as scoring functions. However, these embedding-based methods often sacrifice interpretability and prediction quality. In contrast, our proposed NPLL framework significantly improves the quality of reasoning results while more properly handling reasoning problems through the principled integration of logical rules.

3 Preliminary

A knowledge graph is a graph-structured model composed of triplets, where the entities in the triplets are nodes and the relations are edges. Given a known knowledge graph K = (E, L, F), where $E = \{e_1, e_2, \ldots, e_M\}$ represents a set of M entities, with entities typically referring to person names, objects, locations and proper nouns; $L = \{l_1, l_2, \ldots, l_N\}$ represents a set of N relations; $F = \{f_1, f_2, \ldots, f_S\}$ represents a set of known facts involving entities from E and relations from L, where fi can be described as $f_i = \{e_h, l, e_t\}, e_h, e_t \in E, l \in L$, indicating e_h has a relation l with e_t , or can be written as $l(e_h, e_t)$, where l is treated as a predicate and e_h and e_t as constants.

We now introduce the predicate logic representation, where each relation in the relation set is represented as a function l(x, y), with x and y having the domain E, and l(x, y) being directed, so l(x, y) and l(y, x) are different. For example, l(x, y) := S(Tom, basketball) (S denotes proficient sport), indicates that Tom's proficient sport is basketball, which clearly cannot be expressed as S(basketball, Tom).

Using the predicate logic representation, new facts can be inferred through logical deduction, e.g., $S(Tom, basketball) \land F(Tom, John) \Rightarrow S(John, basketball)(F$ denotes being friends). If variables replace the constant entities in the above formula, it is called a rule, generally represented as: $Pred_1(x, y_1) \land Pred_2(y_1, y_2) \land \ldots Pred_n(y_{n-1}, z) \Rightarrow Pred(x, z) \ n \ge 1$, where x, y_i', z are all variables. Pred(A, B) is called an atom, with A and B being the subject and object or the head and tail entities in the triplet. Pred(x, z) is the head atom; the rest are body atoms. After substituting variables with constants, e.g. let C_1, C_2, C_3 be constants, $Pred_1(C_1, C_2) \land Pred_2(C_2, C_3) \Rightarrow Pred_3(C_1, C_3)$, which is called ground rule, and each atom with variables replaced by constants is called a ground predicate, whose value is a binary truth value. For example, $Pred_1(C_1, C_2) = \{0, 1\}$. If $Pred_1(C_1, C_2) \in F$, then $Pred_1(C_1, C_2) = 1$. Therefore, the goal of knowledge reasoning is to infer unknown facts $U = \{U_j\}$ from the known facts $F = \{f_i = 1\}_{i=1,2,...}$

Inferring unknown facts from known facts is a generative problem, which requires building a joint probability distribution model and maximizing the generation probability to obtain the unknown facts. Hence, we must construct a suitable joint probability distribution model for the reasoning task. Considering the above conditions, the knowledge graph can be modeled as a MLN, which combines first-order predicate logic and probabilistic graphical models. Traditional methods employ first-order predicate logic for deductive reasoning in a black-and-white manner. However, as the example $S(Tom, basketball) \land F(Tom, John) \Rightarrow S(John, basketball)$ shows, it is not necessarily always true. MLN assign a weight ω to each rule, representing the probability of the event occurring, thus transforming the hard conditions of predicate logic into probabilistic conditions. The rule

representation form in first-order predicate logic is converted to Conjunctive Normal Form (CNF) for computational convenience.

$$S(A,B) \wedge F(A,C) \Rightarrow S(C,B) \Leftrightarrow \neg S(A,B) \ \lor \ \neg F(A,C) \ \lor \ S(C,B)$$

Therefore, to construct a MLN from a knowledge graph, each ontology rule needs to be defined as a network in the MLN, each having a weight ω . The probability calculation formula for MLN is:

$$P(F, U|\omega) = \frac{1}{Z(\omega)} \prod_{r \in R} \exp\left(\omega_r N(F, U)\right), \tag{1}$$

where F is the set of known facts, U is the set of unknown facts, $R = \{r\}$ is the set of rules, ω_r is the weight of rule r, and N(F, U) is the number of ground rules satisfying rule r. $Z(\omega)$ is the partition function, which is the sum of all possible ground rule cases for normalization:

$$Z(\omega) = \sum_{F,U} \prod_{r \in R} exp(\omega_r N(F, U)).$$
⁽²⁾

All ground rules of each rule form a clique in MLN, $\exp(\omega_r N(F, U))$ is the potential function of rule r, and each potential function expresses the situation of a clique. Generally, all ground rules of one rule form a clique, where each primary node, i.e., fact, is treated as a basic atom. Each state of MLN assigns different occurrence possibilities to all facts, representing a possible open world. Each set of possible worlds combines $\{F, U, R\}$ relations, jointly determining the truth values of all basic atoms. After establishing the joint probability distribution, we infer the unknown facts U from the known facts F by solving the posterior distribution $P(U|F, \omega)$, which can be viewed as an approximate inference problem.

Unlike rule-based reasoning methods that evaluate rules holistically, knowledge embedding methods mainly score facts, assigning higher scores to correct facts and lower scores to incorrect ones, obtaining embedding vectors for different entities, and enabling inference of unknown facts.

4 Model

This section introduces a knowledge reasoning method that combines MLNs with embedding learning. By utilizing MLN, which is trained with EM algorithm[40], to establish a joint probability distribution model of known facts and unknown facts, we decompose $P(F|\omega)$ to obtain the following equation:

$$logP(F|\omega) = log[\frac{P(F,U|\omega)}{Q(U)}] - log[\frac{P(U|F,\omega)}{Q(U)}],$$
(3)

in equation 3, $P(F, U|\omega)$ is the joint probability distribution of known facts and unknown facts. In contrast, $P(U|F, \omega)$ is the posterior distribution, and Q(U) is the approximate posterior distribution. Taking the expectation of both sides of 3 with respect to Q(U), we can define $logP(F|\omega)$ as the sum of the evidence lower bound(ELBO) and the Kullback-Leibler(KL) divergence:

$$logP(F|\omega) = ELBO + KL(q||p), \tag{4}$$

where
$$ELBO = \sum_{U} Q(U) \log\left(\frac{P(F,U|\omega)}{Q(U)}\right)$$
, $KL(q||p) = -\sum_{U} Q(U) \log\left(\frac{P(U||F,\omega)}{Q(U)}\right)$.

When the approximate posterior distribution Q(U) is the same as the true posterior distribution, we obtain the optimal result, at which point KL(q||p) is 0 and ELBO is maximized. Therefore, our optimization objective becomes maximizing the ELBO value:

$$d_{ELBO}(Q,P) = \sum_{U} Q(U) log P(F,U|\omega) - \sum_{U} Q(U) log Q(U),$$
(5)

the approximate posterior distribution Q(U) is the probability distribution of unknown facts based on known facts.

Specifically, in the t-th iteration, the first step is to fix the rule weight ω as ω_t , which is a constant. We then update the probability set of each factor in all ground rules through the reasoning method proposed in this paper and obtain the current approximate posterior probability distribution Q(U). The second step substitutes the approximate posterior distribution into ELBO and updates ω by maximizing ELBO:

$$\omega = argmax_{\omega} \sum (Q(U)logP(F, U|\omega) - Q(U)logP(U, F|\omega^{t})),$$
(6)

in equation 6, the second term is independent of ω and can be treated as a constant. Therefore, to reduce computation, we simplify the first step to fixing ω and computing the expectation of $logP(F, U|\omega)$ concerning Q(U). The second step fixes the posterior distribution and updates ω , obtaining $\omega^{t+1} = argmax_{\omega} \sum_{U} Q(U)logP(F, U|\omega)$.

4.1 Scoring Module

The most crucial part of the entire reasoning architecture is generating the approximate posterior probability. We design a scoring module to generate evaluation scores for facts. The generated evaluation scores can be the approximate posterior probability to compute the KL divergence from the actual posterior distribution. Additionally, they must satisfy the constraint that the loss for correct facts is minimized while the loss for incorrect facts is maximized. Therefore, we use vectors e_h and e_t to represent the head and tail entity features in a fact while representing the relation using three weight matrices.

Our scoring module consists of three parts. First, an embedding network initializes the vector features for each entity. Then, a scoring function $g(l, e_h, e_t)$ computes the evaluation score for each fact. Finally, the evaluation scores are processed to form the approximate posterior probability. For the scoring function, the model computes the following function to represent the possibility of the head and tail entities forming a valid fact under a given relation:

$$g(l, e_h, e_t) = u_R^T f(e_h^T W_R e_t + V_R [e_h e_t] + b_R),$$
(7)

where f is a non-linear activation function. W_R is a d * d * k dimensional tensor, and $e_h^T W_R e_t$ results from a bilinear tensor product, yielding a k-dimensional vector. V_R is a k * 2d dimensional tensor, and $V_R [e_h e_t]$ is the result of a linear tensor product, also a k-dimensional vector. u_R and b_R are also k-dimensional, so the final result is a scalar. We design the each parts as follows:

We set up initial vectors for entities in the knowledge graph separately. We then build a neural network to update the vector features for all entities. The output of this part is the updated head and tail entity vectors $\{e_h, e_t\}$ with dimension d.

We initialize a bilinear neural network layer W_R and two linear neural network layers V_R , u_R . Taking the head and tail entity vector features as input, we pass them through the scoring function $g(l, e_h, e_t)$ to output the result and compute the evaluation scores for all known facts, unknown facts, and negative sample facts.

We define the obtained evaluation scores as the approximate posterior probability for known and unknown facts. Specifically, we process the evaluation scores using the sigmoid function to bound them between 0 and 1, i.e., $p = sigmod(g(l, e_h, e_t))$, where $sigmod(.) = \frac{1}{1 + \exp(.)}$.

4.2 E-step

In the expectation step, to solve for the unknown facts in the knowledge graph based on the known facts, we need to obtain the posterior distribution $P(U|F, \omega)$ of the unknown facts. This can be achieved by minimizing the KL divergence between the approximate and true posterior distributions. However, directly solving the joint probability distribution model established by MLN is highly complex. Therefore, this paper randomly samples batches of ground rules to form datasets, wherein the ground rules are approximately independent of each batch. By applying the mean-field theorem[40], we define the approximate posterior distribution as the product of the probability distributions of the individual ground rules. The truth value of a ground rule is 1 when it holds and 0 when it does not, and the truth value of each ground rule is jointly determined by the truth values of its constituent facts. Therefore, we set the probability distribution of a ground rule as the product of the probability distributions of its constituent facts. For example, for the ground rule $R_1 = \neg S(Tom, basketball) \bigvee \neg F(Tom, John) \bigvee S(John, basketball)$.

The truth value of the ground rule R1 is determined by its three constituent facts. Thus, we define:

$$Q(U) = \prod_{u_g \in U} q(u_g) = \prod_{u_g \in U} \prod_{u_k \in u_g} f_k(u_k),$$
(8)

in equation 8, u_k represents fact u_k , u_g represents all facts in a ground rule g, and U is the set of unknown facts. Each fact probability distribution $f_k(u_k)$ follows a Bernoulli distribution, where the truth value is 1 when the fact occurs and 0 when it does not, i.e., $f_k(u_k) = p_k^{u_k} (1 - p_k)^{(1-u_k)}$. The probability p_k of the fact occurring is obtained from the scoring module.

The truth value of each ground rule is jointly determined by the truth values of its constituent facts. Therefore, the number of ground rules is represented as:

$$N(F,U) = \sum_{u_g \in u_r} \prod_{u_k \in u_g} u_k,$$
(9)

where u_r represents the set of facts belonging to rule r. Thus, equation 1 can be defined as:

$$P(\omega|F,U) = \frac{1}{Z(\omega)} \prod_{r \in R} \exp\left(\omega_r \sum_{u_g \in u_r} \prod_{u_k \in u_g} u_k\right).$$
(10)

Substituting equations (8) and (10) into the optimization function (5), the term $Z(\omega)$ can be treated as a constant, leading to:

$$\sum_{r \in R} \omega_r \sum_{u_g \in u_r} \prod_{u_k \in u_g} p_k - \sum_{r \in R} \sum_{u_g \in u_r} \sum_{u_k \in u_g} \left((1 - p_k) \log (1 - p_k) + p_k log p_k \right).$$
(11)

This paper constructs the score d_{fact} of the known fact set F to add constraints. We want the score d_{fact} of the positive sample to be as small as possible. The final objective function is defined as:

$$\sum_{r \in R} \left(\omega_r \sum_{u_g \in u_r} \prod_{u_k \in u_g} p_k - \sum_{u_g \in u_r} \sum_{u_k \in u_g} \left((1 - p_k) \log \left(1 - p_k \right) + p_k log p_k \right) + d_{fact} \right).$$
(12)

4.3 M-step

In the M-step, we fix Q(U) and then update the weights ω_r of the rule set R. At this point, the partition function in equation 2 from the E-step is no longer a constant. Therefore, in the M-step, we optimize the rule weights by minimizing the negative of the ELBO. However, when dealing with large-scale knowledge graphs, the number of facts also becomes enormous, making it difficult to optimize the ELBO directly. Consequently, we adopt the widely used pseudo-log-likelihood [39] as an alternative optimization objective, defined as:

$$P(F, U|\omega) := \sum Q(U) \left(\sum_{u_k \in U} log P(u_k|\omega, MB_k) \right).$$
(13)

 MB_k represents the Markov Blanket of an individual fact k in a ground rule. Therefore, following existing studies [11][12], for each grounding formula k connecting the base predicate with its Markov Blanket, we optimize the weights using the gradient descent formula:

$$\nabla_{\omega_k} \sum f\left(u_k\right) \left(\log P\left(u_k|\omega, MB_k\right)\right). \tag{14}$$

5 Experiment

5.1 Experiment Settings

We evaluate the NPLL method on four benchmark datasets through the knowledge base completion task and compare it with other state-of-the-art knowledge base completion methods. We will release the code after the publication of the paper.

Datasets. We evaluate our proposed model on four widely used benchmark datasets. Specifically, we use the UMLS dataset[41], Kinship dataset[42], FB15k-237 dataset[43], and WN18RR dataset[36]. FB15k-237 and WN18RR are more challenging versions of the FB15K and WN18 datasets. The dataset statistics are summarized in Appendix A.

Evaluation metrics. Following existing studies[15], we use the filtered setting during evaluation. Mean Reciprocal Rank (MRR), Hit@10, Hit@3, and Hit@1 are treated as the evaluation metrics.

Competitor methods: We compare knowledge graph embedding methods, rule-based methods, and methods combining the two. For knowledge graph embedding methods, we select some of the most classic distance translation and semantic matching algorithms, including TransE[15], DistMult[23], ComplEx [24], ConvE[36], RotatE[21]. For rule-based reasoning algorithms that integrate rules, we compare with NeuralLP[8], DRUM[10], pLogicNet[11], ExpressGNN[12], DiffLogic[13], NCRL[14]. The comparative experiments are conducted under the same experimental conditions, selecting the best training hyperparameters provided by the open-source codes of each algorithm. For our method, we consider two variants: NPLL-GNN, which utilizes a tunable graph neural network[12] in the scoring module for training, and NPLL-basic, which employs only a single-layer embedding network in the scoring module for training.

Experimental setting: To generate logical rules, we use the NeuralLP method on the training set to generate candidate rules and select the candidate rules with the highest confidence scores. On different datasets, we create candidate rules with different parameters. See the Appendix B for details on specific rule selection.For NPLL, we use 0.0005 as the initial learning rate, and decay it by half for every 10 epochs without improvement. For the four datasets FB15k-237, WN18RR, Kinship, UMLS, the embedding size of NPLL-basic are 256, 256, 512, 128.

General setting: All experiments are conducted on the same server with two GPUs (Nvidia RTX 2080Ti, 11G), using Cuda version 10.2, Ubuntu 16.04.6 system, and Intel(R) Xeon(R) CPU E5-2620 v3 @ 2.40GHz CPU.



5.2 Results

Figure 2: Performance of KG completion vs sparsity ratio

KG completion performance analysis. The experimental results are shown in Table 1. The NPLLbasic and NPLL-GNN methods achieve good performance across all four datasets. On the FB15k-237 and UMLS datasets, the NPLL-basic method significantly outperforms other methods, achieving the best results on all four metrics. On the WN18RR and Kinship dataset, NPLL-basic and NPLL-GNN

Table 1: Results of KG completion. We select the metrics provided in the papers for the DiffLogic and NCRL algorithms from the rule-learning methods, as we could not find suitable open-source codes for them. (The red numbers indicate the best performance achieved on a particular metric.) Hit@K is in %.

Methods	Models	FB15k-237				WN18RR			
Wiethous	Wouchs	MRR	Hit@10	Hit@3	Hit@1	MRR	Hit@10	Hit@3	Hit@1
	TransE	0.33	52.71	29.28	18.93	0.2231	52.12	40.10	1.31
	DistMult	0.2878	45.67	31.43	20.31	0.4275	50.71	44.01	38.21
KGE	ComplEx	0.3016	48.08	33.10	21.28	0.4412	51.03	46.11	41.01
	ConvE	0.3251	50.11	35.68	23.80	0.4295	52.13	44.34	39.87
	RotatE	0.3213	53.10	34.52	22.81	0.4714	55.71	47.29	42.87
	Neural LP	0.1983	29.84	21.73	14.48	0.3800	40.79	38.81	36.80
	DRUM	0.2430	36.39	21.91	17.43	0.3861	41.02	38.93	36.91
Dula Laurning	pLogicNet	0.3300	52.79	36.87	23.12	0.2300	53.09	41.48	1.5
Kule-Learning	ExpressGNN	0.4894	60.80	48.10	38.91	-	-	-	-
	NCRL	0.3000	47.30	-	20.90	0.6700	85.00	-	56.30
	DiffLogic	-	-	-	-	0.5001	58.70	-	-
	NPLL-basic	0.6223	68.57	64.52	58.63	0.7668	78.14	77.38	75.83
us	NPLL-GNN	0.5442	61.93	57.06	50.25	0.5282	61.52	55.50	48.17
Methods	Models		Kins	hip		UMLS			
1010010015	inouclo	MRR	Hit@10	Hit@3	Hit@1	MRR	Hit@10	Hit@3	Hit@1
	TransE	0.3509	80.36	50.14	1.10	0.7806	99.13	96.05	59.56
VCE	DistMult	0.3925	77.86	42.68	23.73	0.4770	78.83	53.87	33.57
NUE	ComplEx	0.7201	95.91	80.86	59.73	0.8950	98.34	95.58	82.70
	RotatE	0.4890	86.95	56.32	32.41	0.5884	83.41	68.33	44.23
	Neural LP	0.5637	88.00	63.94	41.49	0.7312	91.29	84.70	59.37
Rule-Learning	DRUM	0.3312	70.15	48.23	25.67	0.5634	85.64	65.58	35.79
	NCRL	0.6400	92.90	-	49.00	0.7800	95.10	-	65.90
	NPLL-basic	0.8663	92.68	87.91	83.55	0.9763	99.21	98.26	96.76
us	NPLL-GNN	0.7705	87.55	79.09	71.77	0.9754	99.05	98.66	96.45

Table 2: A comparison of the model parameter counts for NPLL-basic, NPLL-GNN, and ExpressGNN methods on the FB15k-237 dataset

	Models	FB15k-237
Total params count(k)	ExpressGNN NPLL-basic NPLL-GNN	251,337k 64,967k <mark>64,953k</mark>

comprehensively outperform the data-driven embedding methods, while NPLL-basic achieve the best results on the MRR, Hit@3, and Hit@1 metrics. This indicates that the reasoning effectiveness and expressiveness of NPLL have been enhanced.

Performance analysis of NPLL-basic and NPLL-GNN. Compared to NPLL-GNN, NPLL-basic performs better on the FB15k-237, WN18RR, and Kinship datasets. On the UMLS dataset, their performances are similar.

Parameter counts. The terms of model parameter counts, we compare NPLL with the ExpressGNN method, which has relatively high overall performance among the baseline methods on the FB15k-237 dataset. As shown in Table 2, the parameter count of our method is approximately one-fourth of ExpressGNN.

Analysis of data efficiency. We investigate the data efficiency of NPLL-basic and NPLL-GNN, and compare them with baseline methods. We divide the FB15k-237 knowledge base into fact/train/valid/test files[8], and vary the size of the train set from 0% to 20%, while providing the complete fact set to the models. The results can be seen in Table 3. In Figures 2, the NPLL methods are shown as solid lines, while other methods are dashed lines. We can clearly see that

Models		FB-0				FB-0.05			
	MRR	Hit@10	Hit@3	Hit@1	MRR	Hit@10	Hit@3	Hit@1	
TransE	0.2412	42.71	26.39	16.10	0.2523	43.09	26.87	16.43	
Neural LP	0.0128	1.75	0.73	0.41	0.1531	24.51	16.72	10.43	
DistMult	0.2297	38.87	25.02	15.10	0.2317	39.28	25.13	15.25	
CompIEx	0.2363	40.29	25.72	15.47	0.2395	40.70	25.98	15.75	
ExpressGNN	0.4276	53.88	45.74	36.65	0.4187	54.24	44.89	35.50	
NPLL-basic	0.5356	62.55	56.87	51.03	0.5384	63.09	57.84	51.38	
NPLL-GNN	0.4989	58.78	52.95	44.88	0.4911	58.15	52.23	44.07	
Models		FB-	0.1			FB-	0.2		
Models	MRR	FB- MRR	0.1 MRR	MRR	 MRR	FB- Hit@10	0.2 Hit@3	Hit@1	
Models TransE	MRR 0.2531	FB- MRR 43.41	0.1 MRR 26.92	MRR 16.68	 MRR 0.2533	FB- Hit@10 43.92	0.2 Hit@3 27.13	Hit@1 16.81	
Models TransE Neural LP	MRR 0.2531 0.1624	FB- MRR 43.41 25.88	0.1 MRR 26.92 17.81	MRR 16.68 11.16	MRR 0.2533 0.1699	FB- Hit@10 43.92 26.79	0.2 Hit@3 27.13 18.53	Hit@1 16.81 11.86	
Models TransE Neural LP DistMult	MRR 0.2531 0.1624 0.2333	FB- MRR 43.41 25.88 39.47	0.1 MRR 26.92 17.81 25.36	MRR 16.68 11.16 15.37	MRR 0.2533 0.2533 0.1699 0.2371	FB- Hit@10 43.92 26.79 40.07	0.2 Hit@3 27.13 18.53 25.80	Hit@1 16.81 11.86 15.64	
Models TransE Neural LP DistMult CompIEx	MRR 0.2531 0.1624 0.2333 0.2409	FB- MRR 43.41 25.88 39.47 40.74	0.1 MRR 26.92 17.81 25.36 26.24	MRR 16.68 11.16 15.37 15.89	MRR 0.2533 0.1699 0.2371 0.2451	FB- Hit@10 43.92 26.79 40.07 41.63	0.2 Hit@3 27.13 18.53 25.80 26.71	Hit@1 16.81 11.86 15.64 16.16	
Models TransE Neural LP DistMult CompIEx ExpressGNN	MRR 0.2531 0.1624 0.2333 0.2409 0.4226	FB- MRR 43.41 25.88 39.47 40.74 55.30	0.1 MRR 26.92 17.81 25.36 26.24 45.49	MRR 16.68 11.16 15.37 15.89 35.91	MRR 0.2533 0.1699 0.2371 0.2451 0.4273	FB- Hit@10 43.92 26.79 40.07 41.63 55.59	0.2 Hit@3 27.13 18.53 25.80 26.71 45.81	Hit@1 16.81 11.86 15.64 16.16 36.34	
Models TransE Neural LP DistMult CompIEx ExpressGNN NPLL-basic	MRR 0.2531 0.1624 0.2333 0.2409 0.4226 0.5466	FB- MRR 43.41 25.88 39.47 40.74 55.30 63.40	0.1 MRR 26.92 17.81 25.36 26.24 45.49 57.20	MRR 16.68 11.16 15.37 15.89 35.91 51.93	MRR 0.2533 0.1699 0.2371 0.2451 0.4273 0.5594	FB- Hit@10 43.92 26.79 40.07 41.63 55.59 63.62	0.2 Hit@3 27.13 18.53 25.80 26.71 45.81 57.57	Hit@1 16.81 11.86 15.64 16.16 36.34 52.11	

Table 3: Results on the FB15k-237 dataset with various data sizes. Hit@K is in %

Table 4: Results on the zero-shot dataset constructed from the FB15k-237 dataset. Hit@K is in %.

Methods	Models	FB-zero-shot					
		MRR	Hit@10	Hit@3	Hit@1		
KGE	TransE DistMult ComplEx RotatE	0.0031 0.0011 0.0042 0.0061	0.5 0.18 6.76 1.98	0.1 0.01 0.36 0.13	0.01 0.01 0.24 0.01		
Rule-Learning	Neural LP ExpressGNN	0.0172 0.1851	3.47 29.59	1.88 21.47	0.15 12.93		
us	NPLL-basic NPLL-GNN	0.4425 0.2151	50.30 32.02	46.44 23.50	<mark>40.81</mark> 17.66		

NPLL performs significantly better than the baselines with smaller training data. Even with more training data for supervision, NPLL still exhibits excellent performance across all metrics. This clearly demonstrates that NPLL can more accurately predict the correct answers and has outstanding data utilization ability.

Zero-shot learning. In real-world scenarios, most relations in knowledge bases are long-tail relations, meaning most relations may have only a few facts. Therefore, it is very important to study the model's performance on relations with insufficient training data. We use the zero-shot dataset constructed from FB15k-237[12], which enforces disjoint relation sets between training and test data. Table 4 shows the results. As expected, the performance of all supervised relation learning methods based on embeddings almost drops to zero. This indicates the limitation of these methods in handling sparse long-tail relations. Compared to the rule-exploiting methods like NeuralLP and ExpressGNN, NPLL also shows significant improvement in dealing with long-tail data.

6 Conclution

In this paper, we study knowledge graph reasoning and propose a method called Neural Probabilistic Logic Learning (NPLL), which effectively integrates logical rules with data embeddings. NPLL

utilizes neural networks to extract node features from the knowledge graph and then supports the reasoning of Markov Logic Networks through a scoring module, effectively enhancing the model's expressiveness and reasoning capabilities. NPLL is a general framework that allows tuning the encoding network to boost model performance.

References

- Matthew Richardson and Pedro Domingos. Markov logic networks. *Machine learning*, 62:107– 136, 2006.
- [2] Luis Antonio Galárraga, Christina Teflioudi, Katja Hose, and Fabian Suchanek. Amie: association rule mining under incomplete evidence in ontological knowledge bases. In *Proceedings of* the 22nd international conference on World Wide Web, pages 413–422, 2013.
- [3] Christian Meilicke, Manuel Fink, Yanjie Wang, Daniel Ruffinelli, Rainer Gemulla, and Heiner Stuckenschmidt. Fine-grained evaluation of rule-and embedding-based systems for knowledge graph completion. In *The Semantic Web–ISWC 2018: 17th International Semantic Web Conference, Monterey, CA, USA, October 8–12, 2018, Proceedings, Part I 17*, pages 3–20. Springer, 2018.
- [4] Pouya Ghiasnezhad Omran, Kewen Wang, and Zhe Wang. An embedding-based approach to rule learning in knowledge graphs. *IEEE Transactions on Knowledge and Data Engineering*, 33(4):1348–1359, 2019.
- [5] Shu Guo, Quan Wang, Lihong Wang, Bin Wang, and Li Guo. Jointly embedding knowledge graphs and logical rules. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pages 192–202, 2016.
- [6] Shu Guo, Quan Wang, Lihong Wang, Bin Wang, and Li Guo. Knowledge graph embedding with iterative guidance from soft rules. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.
- [7] Wen Zhang, Bibek Paudel, Liang Wang, Jiaoyan Chen, Hai Zhu, Wei Zhang, Abraham Bernstein, and Huajun Chen. Iteratively learning embeddings and rules for knowledge graph reasoning. In *The world wide web conference*, pages 2366–2377, 2019.
- [8] Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. *Advances in neural information processing systems*, 30, 2017.
- [9] Po-Wei Wang, Daria Stepanova, Csaba Domokos, and J Zico Kolter. Differentiable learning of numerical rules in knowledge graphs. In *International Conference on Learning Representations*, 2019.
- [10] Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. Drum: End-to-end differentiable rule mining on knowledge graphs. Advances in Neural Information Processing Systems, 32, 2019.
- [11] Meng Qu and Jian Tang. Probabilistic logic neural networks for reasoning. *Advances in neural information processing systems*, 32, 2019.
- [12] Yuyu Zhang, Xinshi Chen, Yuan Yang, Arun Ramamurthy, Bo Li, Yuan Qi, and Le Song. Efficient probabilistic logic reasoning with graph neural networks. arXiv preprint arXiv:2001.11850, 2020.
- [13] Chen Shengyuan, Yunfeng Cai, Huang Fang, Xiao Huang, and Mingming Sun. Differentiable neuro-symbolic reasoning on large-scale knowledge graphs. *Advances in Neural Information Processing Systems*, 36, 2024.
- [14] Kewei Cheng, Nesreen K Ahmed, and Yizhou Sun. Neural compositional rule learning for knowledge graph reasoning. *arXiv preprint arXiv:2303.03581*, 2023.
- [15] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. Advances in neural information processing systems, 26, 2013.
- [16] Zhen Wang, Jianwen Zhang, Jianlin Feng, and Zheng Chen. Knowledge graph embedding by translating on hyperplanes. In *Proceedings of the AAAI conference on artificial intelligence*, volume 28, 2014.

- [17] Yankai Lin, Zhiyuan Liu, Maosong Sun, Yang Liu, and Xuan Zhu. Learning entity and relation embeddings for knowledge graph completion. In *Proceedings of the AAAI conference on artificial intelligence*, volume 29, 2015.
- [18] Guoliang Ji, Kang Liu, Shizhu He, and Jun Zhao. Knowledge graph completion with adaptive sparse transfer matrix. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.
- [19] Guoliang Ji, Shizhu He, Liheng Xu, Kang Liu, and Jun Zhao. Knowledge graph embedding via dynamic mapping matrix. In Proceedings of the 53rd annual meeting of the association for computational linguistics and the 7th international joint conference on natural language processing (volume 1: Long papers), pages 687–696, 2015.
- [20] Fuxiang Zhang, Xin Wang, Zhao Li, and Jianxin Li. Transrhs: a representation learning method for knowledge graphs with relation hierarchical structure. 2020.
- [21] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. arXiv preprint arXiv:1902.10197, 2019.
- [22] Maximilian Nickel, Volker Tresp, Hans-Peter Kriegel, et al. A three-way model for collective learning on multi-relational data. In *Icml*, volume 11, pages 3104482–3104584, 2011.
- [23] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. arXiv preprint arXiv:1412.6575, 2014.
- [24] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International conference on machine learning*, pages 2071–2080. PMLR, 2016.
- [25] Maximilian Nickel, Lorenzo Rosasco, and Tomaso Poggio. Holographic embeddings of knowledge graphs. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.
- [26] Hanxiao Liu, Yuexin Wu, and Yiming Yang. Analogical inference for multi-relational embeddings. In *International conference on machine learning*, pages 2168–2178. PMLR, 2017.
- [27] Seyed Mehran Kazemi and David Poole. Simple embedding for link prediction in knowledge graphs. *Advances in neural information processing systems*, 31, 2018.
- [28] Shuai Zhang, Yi Tay, Lina Yao, and Qi Liu. Quaternion knowledge graph embeddings. *Advances in neural information processing systems*, 32, 2019.
- [29] Zongsheng Cao, Qianqian Xu, Zhiyong Yang, Xiaochun Cao, and Qingming Huang. Dual quaternion knowledge graph embeddings. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 6894–6902, 2021.
- [30] Anson Bastos, Kuldeep Singh, Abhishek Nadgeri, Saeedeh Shekarpour, Isaiah Onando Mulang, and Johannes Hoffart. Hopfe: Knowledge graph representation learning using inverse hopf fibrations. In Proceedings of the 30th ACM International Conference on Information & Knowledge Management, pages 89–99, 2021.
- [31] Saadullah Amin, Stalin Varanasi, Katherine Ann Dunfield, and Günter Neumann. Lowfer: Lowrank bilinear pooling for link prediction. In *International Conference on Machine Learning*, pages 257–268. PMLR, 2020.
- [32] Dai Quoc Nguyen, Thanh Vu, Tu Dinh Nguyen, and Dinh Phung. Quatre: Relation-aware quaternions for knowledge graph embeddings. In *Companion Proceedings of the Web Conference* 2022, pages 189–192, 2022.
- [33] Antoine Bordes, Xavier Glorot, Jason Weston, and Yoshua Bengio. A semantic matching energy function for learning with multi-relational data: Application to word-sense disambiguation. *Machine learning*, 94:233–259, 2014.
- [34] Richard Socher, Danqi Chen, Christopher D Manning, and Andrew Ng. Reasoning with neural tensor networks for knowledge base completion. *Advances in neural information processing* systems, 26, 2013.
- [35] Quan Liu, Hui Jiang, Andrew Evdokimov, Zhen-Hua Ling, Xiaodan Zhu, Si Wei, and Yu Hu. Probabilistic reasoning via deep learning: Neural association models. *arXiv preprint arXiv:1603.07704*, 2016.

- [36] Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.
- [37] Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *The semantic* web: 15th international conference, ESWC 2018, Heraklion, Crete, Greece, June 3–7, 2018, proceedings 15, pages 593–607. Springer, 2018.
- [38] Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal Xhonneux, and Jian Tang. Neural bellman-ford networks: A general graph neural network framework for link prediction. Advances in Neural Information Processing Systems, 34:29476–29490, 2021.
- [39] Yongqi Zhang and Quanming Yao. Knowledge graph reasoning with relational digraph. In *Proceedings of the ACM web conference 2022*, pages 912–924, 2022.
- [40] Radford M Neal and Geoffrey E Hinton. A view of the em algorithm that justifies incremental, sparse, and other variants. In *Learning in graphical models*, pages 355–368. Springer, 1998.
- [41] Olivier Bodenreider. The unified medical language system (umls): integrating biomedical terminology. *Nucleic acids research*, 32(suppl_1):D267–D270, 2004.
- [42] Geoff Hinton. Kinship. 1990. DOI: https://doi.org/10.24432/C5WS4D.
- [43] Kristina Toutanova and Danqi Chen. Observed versus latent features for knowledge base and text inference. In Proceedings of the 3rd workshop on continuous vector space models and their compositionality, pages 57–66, 2015.

Appendix

A Dataset Details

To comprehensively evaluate the performance of our proposed method, we conducted extensive comparative experiments across four widely-adopted benchmark datasets: UMLS, Kinships, FB15k-237, and WN18RR. Additionally, to investigate the impact of dataset size on reasoning performance, we performed a splitting operation on the FB15k-237 dataset, creating four subsets: FB-0, FB-0.05, FB-0.1, and FB-0.2, where the Train file was divided into varying proportions. Furthermore, we constructed a zero-shot learning scenario, FB-zero-shot, derived from FB15k-237, where the relation sets of the training and test data are disjoint. The specific details and statistics of these datasets are provided in Table 5.

This diverse set of benchmark datasets allows for a comprehensive evaluation of our method's reasoning capabilities across varying dataset sizes, knowledge graph complexities, and zero-shot learning settings. The UMLS and Kinships datasets represent domain-specific knowledge graphs, while FB15k-237 and WN18RR are more general-purpose knowledge bases. By including both small-scale and large-scale datasets, as well as the zero-shot learning scenario, we can thoroughly assess the robustness, scalability, and generalization abilities of our proposed approach under a wide range of conditions encountered in real-world knowledge graph reasoning tasks.

Dataset	#Fact	#Train	#Test	#Valid	#Relation	#Entity	#Rules
UMLS	4006	1321	633	569	46	135	1055
Kinship	6375	2112	1100	1099	25	104	71
Fb15k-237	204087	68028	20466	17536	237	14541	516
Fb-0	204087	1	20466	17536	237	14541	516
Fb-0.05	204087	3401	20466	17536	237	14541	516
Fb-0.1	204087	6802	20466	17536	237	14541	516
Fb-0.2	204087	13605	20466	17536	237	14541	516
Fb-zero-shot	173486	57462	3178	14874	237	14541	516
WN18RR	65127	21708	3134	3034	11	40943	33

Table 5: Knowledge base completion datasets statistics

B Logic Rules

For the selection of logical rules across the four benchmark datasets, we first generated candidate rules using the Neural LP[8] method, a state-of-the-art rule mining approach. We then preprocessed the candidate rules by removing self-reflective logical rules and eliminating duplicates. Next, we applied a confidence score threshold, selecting all rules with a confidence score greater than a predefined parameter α for the same target predicate. Finally, we determined the most suitable logical rule set for each dataset through extensive experiments. Table 6 presents the performance metrics of the NPLL-basic method on the four benchmark datasets with different rule sets.

Based on the experimental results, we identified the optimal rule sets for each dataset: for the UMLS dataset, we selected rules with a confidence score greater than 0; for the Kinships dataset, rules with a confidence score greater than 0.99; for the FB15k-237 dataset, rules with a confidence score greater than 0.87; and for the WN18RR dataset, rules with a confidence score greater than 0.99. This systematic process of rule selection and empirical evaluation allowed us to identify the most suitable logical rules for each knowledge graph, ensuring that our proposed method leverages high-quality symbolic knowledge to enhance its reasoning capabilities.

C limitations

In our experimental evaluation, the proposed NPLL algorithm was benchmarked on four widely-used datasets: FB15k-237, UMLS, WN18RR, and Kinships. On the FB15k-237 and UMLS datasets, NPLL achieved state-of-the-art performance, outperforming existing methods. However, on the

UMLS (α)	MRR	Hit@10	Hit@3	Hit@1
0.99	0.8029	82.15	80.24	78.32
0.9	0.8109	83.81	81.28	79.15
0.8	0.8885	91.15	89.34	87.36
0.7	0.8839	91.63	89.57	86.02
0.6	0.8985	92.65	90.6	87.99
0.5	0.926	96.76	94.23	90.13
0.4	0.9376	97.24	95.42	91.63
0	0.9729	99.21	97.95	96.29
Kinship (α)	MRR	Hit@10	Hit@3	Hit@1
0.99	0.7884	89.18	81.09	73.68
0.97	0.7759	88.09	80.14	72.45
0.95	0.7744	87.64	79.36	72.64
0.93	0.7683	86.27	78.68	72.27
0.92	0.7474	85.14	76.50	69.04
0.91	0.7471	86.50	78.45	72.65
0.9	0.769	86.23	77.86	72.91
0.89	0.7671	84.91	77.68	71.86
0.85	0.7484	82.64	75.68	71.09
0.8	0.7302	80.27	74.59	69.05
0	0.1731	22.27	16.68	13.95
fb15k-237 (α)	MRR	Hit@10	Hit@3	Hit@1
fb15k-237 (α) 0.99	MRR 0.5741	Hit@10 63.88	Hit@3 59.61	Hit@1 53.68
fb15k-237 (α) 0.99 0.95	MRR 0.5741 0.5295	Hit@10 63.88 61.16	Hit@3 59.61 55.83	Hit@1 53.68 48.29
fb15k-237 (α) 0.99 0.95 0.9	MRR 0.5741 0.5295 0.5417	Hit@10 63.88 61.16 62.92	Hit@3 59.61 55.83 56.6	Hit@1 53.68 48.29 49.45
fb15k-237 (α) 0.99 0.95 0.9 0.89	MRR 0.5741 0.5295 0.5417 0.5951	Hit@10 63.88 61.16 62.92 66.77	Hit@3 59.61 55.83 56.6 62.04	Hit@1 53.68 48.29 49.45 55.53
fb15k-237 (α) 0.99 0.95 0.9 0.89 0.873	MRR 0.5741 0.5295 0.5417 0.5951 0.6044	Hit@10 63.88 61.16 62.92 66.77 67.3	Hit@3 59.61 55.83 56.6 62.04 62.82	Hit@1 53.68 48.29 49.45 55.53 56.55
fb15k-237 (α) 0.99 0.95 0.9 0.89 0.873 0.87	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11
fb15k-237 (α) 0.99 0.95 0.9 0.89 0.873 0.87 0.87 0.867	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31
fb15k-237 (α) 0.99 0.95 0.9 0.89 0.873 0.87 0.867 0.867	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5
fb15k-237 (α) 0.99 0.95 0.9 0.89 0.873 0.87 0.867 0.867 0.86 0.84	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77
	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47
fb15k-237($α$) 0.99 0.95 0.9 0.87 0.87 0.867 0.86 0.84 0.83	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1
fb15k-237(α) 0.99 0.95 0.9 0.873 0.877 0.867 0.863 WN18RR(α) 0.99	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15
fb15k-237(α) 0.99 0.95 0.9 0.873 0.867 0.867 0.863 WN18RR(α) 0.99 0.95	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01
fb15k-237(α)0.990.950.90.8730.8730.8670.863WN18RR(α)0.990.950.9	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65
fb15k-237(α)0.990.950.90.8730.8770.8670.863WN18RR(α)0.990.950.90.85	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483 0.5348	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65 62.01	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47 53.38	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65 50.40
fb15k-237(α)0.990.950.90.8730.8770.8670.863WN18RR(α)0.990.950.90.850.83	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483 0.5348 0.5941	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65 62.01 66.64	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47 53.38 61.97	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65 50.40 55.31
fb15k-237($α$)0.990.950.90.8730.8770.8670.863WN18RR($α$)0.990.950.90.850.81	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483 0.5348 0.5941 0.5698	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65 62.01 66.64 64.06	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47 53.38 61.97 59.78	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65 50.40 55.31 52.70
fb15k-237(α)0.990.950.90.8730.8770.8670.863WN18RR(α)0.990.950.90.850.830.810.7	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483 0.5348 0.5941 0.5698 0.4702	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65 62.01 66.64 64.06 52.74	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47 53.38 61.97 59.78 48.72	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65 50.40 55.31 52.70 43.60
fb15k-237(α) 0.99 0.95 0.9 0.873 0.873 0.867 0.863 WN18RR(α) 0.99 0.95 0.9 0.83 WN18RR(α) 0.99 0.95 0.9 0.85 0.83 0.81 0.7 0.5	MRR 0.5741 0.5295 0.5417 0.5951 0.6044 0.6113 0.6038 0.5606 0.5624 0.5945 MRR 0.6012 0.5157 0.4483 0.5348 0.5941 0.5698 0.4702 0.3848	Hit@10 63.88 61.16 62.92 66.77 67.3 68.03 67.34 64.25 64.69 66.87 Hit@10 68.63 62.28 58.65 62.01 66.64 64.06 52.74 42.50	Hit@3 59.61 55.83 56.6 62.04 62.82 63.88 62.98 58.65 58.59 61.71 Hit@3 63.27 53.99 48.47 53.38 61.97 59.78 48.72 39.68	Hit@1 53.68 48.29 49.45 55.53 56.55 57.11 56.31 51.5 51.77 55.47 Hit@1 56.15 46.01 37.65 50.40 55.31 52.70 43.60 36.08

Table 6: The performance indicators of NPLL-basic under different confidence rules in four benchmark datasets. The embedding size is 128

WN18RR and Kinships datasets, while NPLL surpassed data-driven embedding methods, its Hit@10 performance did not exceed that of the rule-based NCRL method. It is noteworthy that in the experiments with the NPLL algorithm, a base set of candidate rules is required as part of the input data. Furthermore, extensive experiments are necessary to identify the optimal rule set for each dataset, as the selection of rules can significantly impact the reasoning performance.